Ensemble of deep learning language models to support the creation of living systematic reviews for the COVID-19 literature

Julien Knafou[1] {julien.knafou@hesge.ch}

Quentin Haas[2] {quentin.haas@risklick.ch}

Nikolay Borissov[2,6] {nikolay.borissov@risklick.ch}

Michel Counotte[3,4] {michel.counotte@wur.nl}

Nicola Low[3] {nicola.low@unibe.ch}

Hira Imeri[3] {hira.imeri@jacobscenter.uzh.ch}

Aziz Mert Ipekci[3] {mert.ipekci@unibe.ch}

Diana Buitrago-Garcia[3] {diana.buitragogarcia@unibe.ch}

Leonie Heron[3] {leonie.heron@unibe.ch}

Poorya Amini[2,6] {poorya.amini@risklick.ch}

Douglas Teodoro[5,1] {douglas.teodoro@unige.ch}

[1] University of Applied Sciences and Arts of Western Switzerland (HES-SO), Rue de la Tambourine 17, 1227, Geneva, Switzerland

[2] Risklick AG, Bern, Switzerland

[3] Institute of Social and Preventive Medicine, University of Bern, Bern, Switzerland

[4] Wageningen Bioveterinary Research, Wageningen University & Research, Wageningen, The Netherlands

[5] Department of Radiology and Medical Informatics, University of Geneva, Geneva, Switzerland

[6] CTU Bern, University of Bern, Bern

Abstract

Background:

The COVID-19 pandemic has led to an unprecedented amount of scientific publications,

growing at a pace never seen before. Multiple living systematic reviews have been developed

to assist professionals with up-to-date and trustworthy health information, but it is

increasingly challenging for systematic reviewers to keep up with the evidence in electronic

databases. We aimed to investigate deep learning-based machine learning algorithms to

classify COVID-19 related publications to help scale-up the epidemiological curation

process.

Methods:

In this retrospective study, five different pre-trained deep learning-based language models

were fine-tuned on a dataset of 6,365 publications manually classified into two classes, three

subclasses and 22 sub-subclasses relevant for epidemiological triage purposes. In a k-fold

cross-validation setting, each standalone model was assessed on a classification task and

compared against an ensemble, which takes the standalone model predictions as input and

uses different strategies to infer the optimal article class. A ranking task was also considered,

in which the model outputs a ranked list of sub-subclasses associated with the article.

Results:

The ensemble model significantly outperformed the standalone classifiers, achieving a F1-

score of 89.2 at the class level of the classification task. The difference between the

standalone and ensemble models increases at the sub-subclass level, where the ensemble

reaches a micro F1-score of 70% against 67% for the best performing standalone model. For

the ranking task, the ensemble obtained the highest recall@3, with a performance of 89%.

Using an unanimity voting rule, the ensemble can provide predictions with higher confidence

on a subset of the data, achieving detection of original papers with a F1-score up to 97% on a

subset of 80% of the collection instead of 93% on the whole dataset.

Conclusion:

This study shows the potential of using deep learning language models to perform triage of

COVID-19 references efficiently and support epidemiological curation and review. The

ensemble consistently and significantly outperforms any standalone model. Fine-tuning the

voting strategy thresholds is an interesting alternative to annotate a subset with higher

predictive confidence.

Keywords

COVID-19, Living systematic review, Literature screening, Text classification, Language

model, Deep learning, Transfer learning

Background

The pandemic coronavirus disease 2019 (COVID-19), caused by severe acute respiratory

syndrome coronavirus 2 (SARS-CoV-2), has led to a historic wave of scientific publications

in the biomedical literature (1,2). As of the beginning of the pandemic, scientific publications

related to SARS-CoV-2 and COVID-19 came from the most diverse domains and became

available in a myriad of digital repositories (preprint servers, technical reports, peer-reviewed

scientific journals, etc.) (3). This outbreak of publications grew at an unprecedented rate. In

this context, it became challenging for medical experts and epidemiologists to follow the

latest scientific developments, and for curators to manually review and annotate all the

available COVID-19 literature to consolidate the fast-moving existing body of knowledge

(1).

Several methods for producing living systematic reviews have been proposed to provide up to

date support for professionals dealing with the pace, amount and complexity of the COVID-

19-related literature (4–7). A living systematic review describes a review methodology that

allows updating information as soon as new evidence becomes available, rather than the

methods applied to classic, time-restricted systematic reviews (8,9). Moreover, living

evidence can narrow the gap between knowledge and practice, as fresh publication findings

are swiftly integrated in scientifically informed guidelines (5,6,9). However, the maintenance

of living evidence systems still require continuous manual curation from highly qualified

human resources (10,11). One of the most time-consuming tasks is to screen the titles and/or

abstracts resulting from a literature search and to exclude articles that are clearly ineligible,

which may comprise a third or more of all records (2).

To address this paradigm, (semi-)automatic curation systems based on text mining and

natural language processing (NLP) technologies have been developed to support review and

annotation of large literature corpora (12–22). These systems support the identification and

ranking of relevant articles, the categorization of the selected documents in classes and

subclasses for reviewing procedures, and enable information extraction from text passages

(e.g., identification of disease passages). For example, Textpresso Central (16) provides a

platform that allows users to create a customized annotated corpus by uploading and

processing documents of their choosing. Once documents are loaded, personalized curation

searches and pipelines can be applied. PubTator Central (19) is a service for viewing and

retrieving bioconcept annotations in full text biomedical articles. It comprises state-of-the-art

text mining models for annotation of several biomedical entities, such as genes and proteins,

diseases, chemicals, and species. SIBiLS (20) provide an optimized search engine in the

biological literature by augmenting its contents with keywords and standardized entities.

Variomes (22) is a system that can perform triage of publication to support evidence-based

decision. Finally, PubTerm (13) enables the organization of abstracts by terms, using the co-

occurrence of terms or by specific phrases, among others, to facilitate the biomedical curation

process.

Automatic text classification appears as an essential methodology to ensure high quality of

living evidence updates. Text classification consists of assigning categorical labels to a given

text passage (e.g., an abstract) based on its similarity to the existing labeled examples (23–

25). Classical text classifiers use statistical document representations, in which the relevance

of a word to a document is proportional to its frequency in the document and inversely

proportional to its frequency in the collection (the so-called term frequency-inverse document

frequency (tf-idf) framework), to create a vectorial representations of the documents (26).

These representations are then used in machine learning models, such as logistic regression

and k-nearest neighbors, to learn a mapping function between the input text and the output

classes (27,28). The trained models can then predict the predefined labels for new input

representations. These models are however limited as they essentially fail to capture the

sequential nature of text and the context in which words are embedded.

To overcome the limitations of the tf-idf framework, state-of-the-art text classifiers use deep

learning-based language models to create word and document contextual representations,

with improved syntactic and semantic features (29). Language models are a particular type of

probabilistic model that, given a sequence of words, compute the probability distribution of

the next word. Recent deep learning-based language models, such as the Bidirectional

Encoder Representations of Transformers (BERT) (30), learn word representations

considering both the forward- and backward-direction contexts of a word using a masked

word approach, in which random words are masked from a context and the algorithm tries to

predict the most likely hidden word. The models are then trained on large corpora, resulting

in better word and document representations. These representations are further used as input

to other NLP tasks, including text classification and question-answering, in a process called

transfer learning, which has resulted in significant improvements of the state-of-the-art

performance in the past years (31).

In this article, we investigated the use of automatic text classifiers supported by deep

learning-based language models to enhance literature triage and annotation in COVID-19

living systematic review systems. Our analysis assessed the effectiveness of different

individual deep learning-based language classifiers against two ensemble strategies, in which

individual models are combined using either the probability sum of the predictions or a

voting strategy where each classifier has a voting right and the classification decision is given

to the class obtaining a majority of votes (32–34).

Methodology

Study design

An overview of the study design is presented in Figure 1. In this retrospective machine

learning-based study, we evaluated the performance of different deep learning text classifiers

to categorize COVID-19 literature according to their publication type in the COVID-19 Open

Access Project (COAP) Living Evidence database aggregator, which includes publications

about SARS-CoV-2 and COVID-19 from Pubmed, EMBASE, medRxiv and bioRxiv (4).

Five individual classifiers were trained with the publication title, abstract and source

associated with annotation categories of a living systematic review knowledge base.

Publication title, abstract and source were imputed to the original dataset whenever missing.

Remaining publications without title or abstract were excluded from the training and

evaluation sets. Then, at inference time, the classifiers were applied to individual records to

predict the publication category as output. Two ensemble strategies were created using these

predictions (32,34). The first strategy uses a voting system that takes each classifier output as

a vote for a class, while the second considers the sum of the class probabilities attributed by

the individual classifiers. For the voting strategy, different cut-offs for the minimal number of

votes were applied to compute the final class associated with the publication.

Figure 1

Caption: Overview of the study design. All articles were manually annotated, then the title,

abstract and source retrieved. In a k-fold cross-validation setting (k is set to 5 in our

experiments), 5 models were fine-tuned and each standalone model was compared against

each other as well as against two types of ensemble.

Model training and evaluation were performed on a dataset of articles, which were annotated

manually by a crowdsourced team of people with training in epidemiology and systematic

reviews (2). Each article was manually classified across 22 sub-subclasses describing the type

of COVID-19 publications according to their study design or article type (case report,

ecological study, modeling study, editorial, etc.). The sub-subclasses are nested into three

subclasses, namely epidemiologic study designs (EPI), basic biological or other laboratory-

based research studies (BASIC) and other types of articles (OTHER). The subclasses are

nested into two classes of original research (ORIGINAL) and articles that were

commentaries, editorials or narrative literature reviews (NON-ORIGINAL). The source

dataset is publicly available at https://zika.ispm.unibe.ch/assets/data/pub/search_beta/. To

improve the robustness of the results, we trained and evaluated our models using a k-fold

cross-validation methodology (k is set to 5 in our experiments). For each fold, 70% of the

articles (~4.6k publications) were used to train the model parameters, 10% unseen documents

(dev set) were used to optimize the model hyperparameters and the remaining 20% unseen

documents (test set) were used to evaluate the performance of the classifier. The final

performance was obtained by averaging the results obtained on the k unseen test sets. We

used standard classification metrics - precision, recall, F1-score and area under the receiver

operating characteristics curve (AUC-ROC) - to assess performance of the individual models

in comparison to the ensemble, and the performance of the latter at different vote majority

levels (i.e., simple and absolute). The experiments were performed using the Python package

HuggingFace on a Linux machine with a TPU (V3-8).

Dataset description and pre-processing

The COAP data snapshot version used in our experiments contains 6,365 publications

annotated between 7th January and 10th December 2020.Table 1A shows the distribution of

publications across classes, subclasses and sub-subclasses in the COAP snapshot dataset. The

categories are imbalanced for the three categorization levels, as is typically the case for real-

world data. Illustratively, the *BASIC: Within-host modelling* sub-subclass composes only

0.5% of the collection (31 documents) while the *OTHER: Comment, editorial, ..., non-*

original sub-subclass is responsible for 27.6% (1,758 documents). There are 799 documents

for the *BASIC* subclass and 3,665 documents for the *EPI* subclass, which accounts for 57.6%

of the dataset. At the class level, the *ORIGINAL* class is responsible for 70.1% of the dataset,

with the remaining documents (29.9%) being categorized according to the *NON-ORIGINAL*

class.

In the pre-processing phase, the title, abstract and source fields were concatenated before

being fed to a classifier, and each classification model used its own tokenizer in order to

separate the free text passages into tokens (words or sub-words) (35–38). All model tokenizer

specificities are given in their respective papers (see Table 1B).

A

Class	Subclass	Sub-subclass	Count	%
ORIGINAL	EPI	Case report	241	3.8
ORIGINAL	EPI	Case series	350	5.5
ORIGINAL	EPI	Case-control study	74	1.2
ORIGINAL	EPI	Cohort study	246	3.9
ORIGINAL	EPI	Cross-sectional study	284	4.5
ORIGINAL	EPI	Diagnostic study	181	2.8
ORIGINAL	EPI	Ecological study	92	1.4
ORIGINAL	EPI	Guidelines	326	5.1
ORIGINAL	EPI	Modeling study	808	12.7
ORIGINAL	EPI	Other	130	2.0

ORIGINAL	EPI	Outbreak or surveillance report	133	2.1
ORIGINAL	EPI	Qualitative study	35	0.5
ORIGINAL	EPI	Review	725	11.4
ORIGINAL	EPI	Trial	40	0.6
ORIGINAL	BASIC	Animal experiment	43	0.7
ORIGINAL	BASIC	Basic research review	135	2.1
ORIGINAL	BASIC	Biochemical/protein structure studies	264	4.1
ORIGINAL	BASIC	In vitro experiment	85	1.3
ORIGINAL	BASIC	Sequencing and phylogenetics	241	3.8
ORIGINAL	BASIC	Within-host modeling	31	0.5
NON-ORIGINAL	OTHER	Other	143	2.2
NON-ORIGINAL	OTHER	Comment, editorial, ..., non-original	1758	27.6
		ALL	6365	100.0

194   B

Pre-trained models	Corpus type	# Parameters (M)

RoBERTa$_{base}$ (39)	General	110
RoBERTa$_{large}$ (39)	General	340
COVID-Twitter-BERT (40)	Bio (COVID-19)	110
BioBERT (41)	Bio	110
PubMedBERT (42)	Bio	110

196   Table 1

197   *Caption:*

198   *A: Dataset document count and proportion by class, subclass and sub-subclass.*

199   *B: pre-trained models used in the experiments, the corpus type used in their training, and the*

200   *number of parameters per model.*

Classification models

In our experiments, we used the pre-trained models shown in Table 1B, which were

originally pre-trained using the masked language model task. In a masked language model

task, large corpora, such as Medline or Wikipedia, are used to create low-dimensional word

(or sub-words) representations in a context. In each training step, a sentence taken from the

corpus is provided to the model with (sub-)words masked. The model is then trained to

predict the masked (sub-)words for that context. The resulting model encodes contextualized

(sub-)words in a low-dimensional space and optimal tensorial representations can then be

used in downstream tasks, such as text classification, a process called transfer learning. Two

out of the five models (RoBERTa-base and RoBERTa-large) were pre-trained on a general

corpus, created using Book Corpus and Wikipedia, while three other models (COVID-

Twitter-BERT, BioBERT and PubMedBERT) were pre-trained on biomedical corpora.

Among the models trained on biomedical corpora, one was pre-trained on a COVID-19

related corpus and one can be considered as large, gathering 340M parameters. All

specificities of the models can be found in their related literature (see Table 1B).

Individual deep learning-based classifier for biomedical literature classification

Transformer models (43) with a fully connected perceptron layer on top of the output

attention layer were used to discriminate sub-subclasses of given documents. Using the pre-

trained language model classifiers, knowledge acquired by the model in the pre-training

phase can be transferred to the specific task, during the so called fine-tuning phase, in which

task specific examples are given the original model so its parameters can be updated to the

task at hand (30). In our case, the specific classification task consists of fine-tuning the

models on a subset [training set] of the manually annotated dataset, followed by the

classification of documents from another unseen subset [test set] among the 22 sub-

subclasses of the knowledge base. At the inference phase, the model extracts features from

the document metadata (i.e., title, abstract and source) and outputs a probability for each of

the 22 sub-subclasses. As sub-subclasses are mutually exclusive, for a given document, the

sum of all the probabilities across sub-subclasses is equal to 1. Additionally, predictions with

respect to the subclass and class levels were computed. To do so, the probabilities for sub-

subclasses belonging to a subclass (or classes) are summed. In other words, the probability of

a document to be classified in a given class is the sum of the probabilities for that document

to be classified in all the sub-subclasses mapped to that class; mapping as per Table 1A. The

predicted category, i.e., class, subclass or sub-subclass, is then defined as the highest

probability across all the predicted probabilities.

Figure 2 shows the publication classification workflow. The model starts with a publication

containing a title, an abstract and a source. The text contained in those three fields is

concatenated and a tokenizer splits it into tokens (e.g., words or sub-words). Each token is

then linked to a token id which allows the language model to look up for a vectorial

representation of the said token. In our example, the word "Study" is split into the "Stu" and

"#dy" sub-words. "Stu" is the token id number 51 and finds its vectorial representation in the

51th model matrix row. Once retrieved, the language model will receive its vector

representation v_{51} as an input along with all the other token representations. The language

model then gives the publication representation to a classifier, which outputs a probability for

each sub-subclass.

Figure 2

Caption: Publication classifier workflow. The model starts with the title, abstract and source

fields and concatenates their text contents before tokenizing it. Each model computes their

predictions and an ensemble strategy, voting or probability sum, combines them to get a final

prediction.

Ensemble: voting and probability sum strategies

Assembling models can be performed by making individual models vote for a category. In the default version, the final category is defined by the higher number of votes. A threshold of votes which would trigger a voting ensemble prediction can also be used. In this setting, an *unknown* prediction, that is, the model is unsure about the category, is possible when there is a tie or when the number of votes is below the threshold (i.e., there is no unanimity). With this ensemble strategy, only the class level (binary) is ensured to always get predictions with a threshold equal to 3 in our setting (5 models). Alternatively, a probability sum strategy can be used to create the ensemble. The idea is to sum the probabilities of the classifiers for all the categories and then take the most probable category as the ensemble classification. If not stated otherwise, the probability sum strategy would be the default ensemble as this method always gives a unique prediction in every situation. In Figure 2, as an example, 3 out of 5 models predicted the *EPI* subclass, so the voting ensemble ended up predicting the *EPI* subclass. For the probability sum strategy, the sum of all subclass predictions among all the 5 models gives a score of 3.1 for the *EPI* subclass, which makes it the highest score among all the other subclasses. Even if in this case predictions are the same for both strategies, it is worth noting that it is not systematically the case.

Model interpretation

To get an insight of the model word impact, the integrated gradient (44) was performed using captum (45) implementation on the PubMedBERT model on the subclass level. According to this method, the higher a token scores, the more important it is to the prediction, and the score polarity implies the positive/negative classification impact. This experiment is two-fold. First, about 600 never-seen documents were classified and the 20 highest positive impact words for each subclass prediction were reported. To deal with tokenized sub-words, a word score was

computed using the mean of all its sub-words compositions. Then, to reflect a more general

impact of a given word for a subclass, each word was lemmatized and the word score is

computed as the mean of the respective lemmatized word scores. This way, a word and its

plural would merge, for example, "simulation" and "simulations" would gather their scores

and attribute their scores to the lemmatized word "simulation". To avoid non-generalized

high-impact-words, only words with at least 5 occurrences were considered. In the second

part of this experiment, a few publication scores were analyzed. To do so, the set of analyzed

documents sampling was driven by the top-20 positive words statistics.

Statistical analysis

To evaluate our models, standard multiclass classification metrics were used, such as

precision, recall, F1-score and AUC-ROC (26). Precision describes the proportion of

correctly classified documents over all the documents being classified by the model to the

same class:

289
$$precision = \frac{tp}{tp+fp},$$

291 where tp is the number of true positives and fp is the number of false positives. Recall

292 describes the proportion of correctly classified documents among all the positive documents

293 for given class:

$$recall = \frac{tp}{tp + fn},$$

where *fn* is the number of false negatives. Finally, F1-score can be formulated as the

harmonic mean of the model precision and recall:

$$F1 = \frac{2 \times precision \times recall}{precision + recall}.$$

For these three metrics, the closer the result is to 1, the better is the model performance.

Lastly, AUC-ROC, computes the area under ROC, where the ROC plots the curve given a

classification threshold of the *tp* rate (or recall or sensitivity) against the *fp* rate (or 1 –

specificity):

$$fp\ rate = \frac{fp}{fp + tn}.$$

To get a confidence interval (CI) of the AUC-ROC, a bootstrapping with a sample of n=2000

was computed. The 2.5% and 97.5% values of the distribution were reported to get a 95% CI.

The McNemar test is used for statistical significance testing (46).

In the ranking experiments, the model predicts a ranked list of sub-subclasses according to

their probabilities for a given input document. Thus, we use standard information retrieval

metrics to report our results. The precision at ranking k (@k) is the precision across all the

first k sub-subclasses returned by our classifiers. As it is a multi-class problem, each

document belongs only to one true class; thus, the theoretical maximum precision is equal to

1/k. By analogy, recall@k is set across the first k sub-subclasses. Conversely to precision, the

more k increases, the more the recall@k should be close to 1. As there are 22 sub-subclasses,

by definition recall@22 is equal to 1. Finally, the mean average precision (MAP) @k is the

mean of all the average precisions (AP) @k, which is defined as follows:

320
$$AP_k = \frac{\sum_{i=1}^{k} P(i) \times rel(i)}{N_{Relevant}},$$

where $P(i)$ is the precision at i position, $rel(i)$ is a function equal to 1 if the i^{th} returned

document is relevant and equal to zero otherwise, and $N_{Relevant}$ is the number of documents

relevant for a given query. As our classification problem is mutually exclusive, $N_{Relevant}$ is

equal to 1 and $P@1 = R@1 = MAP@1$. Compared to traditional classification metrics, which

only consider the top model prediction, the ranking metrics help us to understand how good

are the top-k classification predictions.

Results

Classification performance

Table 2A-C shows the performance of the different models using the F1-score metric at the

class, subclass and sub-subclass levels, respectively. The ensemble outperformed the best

standalone model significantly with a micro F1-score of 89% (Table 2A). PubMedBERT

obtained the best F1-score across the standalone models for all the classes. When comparing

models to each other, there is no significant improvement. Although the improvement of the

ensemble with respect to the PubMedBERT model is statistically significant, it accounts for

less than a point for both the micro and macro F1-scores. At the subclass level (Table 2B),

similarly to the class level the ensemble outperformed all single models significantly, but in

this case for more than a percentage point for both micro and macro F1-scores (86% *vs.* 85%

micro F1-score and 84% *vs.* 83% macro F1-score), and it is also consistently the best

performing model across all the subclasses. PubMedBERT was again the overall best

standalone model at the subclass level, with a micro and macro F1-scores of 85% and 83%,

respectively. At sub-subclass level (Table 2C), the ensemble significantly achieved the best

micro and macro average F1-score (70% and 55%), having the highest F1-score for 10 sub-

subclasses, for which 3 of the improvements were statistically significant. For the standalone

models, PubMedBERT had the best micro F1-score (67%), while RoBERTa-*large* presented

the best macro F1-score (53%). The relevant gap between aggregated scores (micro and

macro F1-scores) from Tables 2B and 2C suggests that there were more intra-level than inter-

level misclassifications. In other words, misclassified sub-subclasses were often confused

with sub-subclasses belonging to the same subclass. Finally, Table 2D shows the AUC-ROC

performance and their respective 95% CI for each level. Here, the ensemble reports

systematically a higher performance than any standalone model. When compared to

BioBERT, the best standalone model in this metric, for each level there is no CI overlap,

confirming the statistically significant improvement by the ensemble model.

The worst performing sub-subclasses (F1-score < 30.00), namely *EPI: Other*, *BASIC: Basic*

research review, *BASIC: Within-host modelling* and *OTHER: Other*, are all underrepresented

in the dataset, accounting for only 2.0%, 2.1%, 0.5% and 2.2%, respectively. The poor

performance for these classes had a negative impact on the macro average F1-score, which is

below the micro average for all the models. In opposition, in the best performing sub-

subclasses (F1-score > 70.00), namely *EPI: Case report*, *EPI: Modelling study*, *EPI: Review*,

BASIC: Animal experiment, *BASIC: Sequencing and Phylogenetics* and *OTHER: Comment,*

editorial, ..., non-original, all accounted for 3.8%, 12.7%, 11.4%, 0.7%, 3.8% and 27.6% of

the dataset, respectively. Those 6 sub-subclasses (30% of the sub-subclasses) account for

about 60% of the collection, yet with a high variance in their distribution. These results

suggest that the number of training examples alone are not enough to explain the model

performance and that textual features in the title+abstract+source fields and/or category

definition make some classes easier to be learned.

A

Label	F1-score (%)					
	RoBERTa base	RoBERTa large	BioBERT	PubMedBERT	COVID-Twitter	Ensemble
ORIGINAL	91.06	91.33	91.44	91.94	90.61	92.35
NON-ORIGINAL	78.46	79.19	79.64	80.52	76.72	81.66*
micro avg	87.30	87.70	87.92	88.53	86.46	89.16*
macro avg	84.76	85.26	85.54	86.23	83.66	87.00*

367   B

Label	F1-score (%)					
	RoBERTa base	RoBERTa large	BioBERT	PubMedBERT	COVID-Twitter	Ensemble
EPI	88.17	88.05	88.38	88.70	87.26	89.47
BASIC	78.15	78.85	79.20	78.13	78.36	80.47
OTHER	78.44	79.22	79.86	80.72	76.71	81.97*
micro avg	84.01	84.26	84.68	84.99	82.99	86.10*

macro avg	81.59	82.04	82.48	82.51	80.77	83.97*

368   C

Label	F1-score (%)					
	RoBERTa base	RoBERTa large	BioBERT	PubMed BERT	COVID-Twitter	Ensemble
EPI: Case report	83.91	84.70	86.55	84.65	81.97	86.85
EPI: Case series	62.76	62.30	65.12	63.42	58.60	65.37
EPI: Case-control study	31.79	40.98	35.51	36.80	32.65	39.02
EPI: Cohort study	51.26	53.18	52.85	56.33	48.68	54.10
EPI: Cross-sectional study	59.89	65.46	66.19	64.10	62.01	65.46
EPI: Diagnostic study	67.01	66.32	65.81	63.83	64.77	69.61
EPI: Ecological study	41.27	41.51	46.53	46.81	42.33	46.46
EPI: Guidelines	57.28	60.32	59.01	60.65	56.26	62.52
EPI: Modelling study	87.61	86.51	87.78	87.05	88.15	88.43*
EPI: Other	21.34	19.33	17.82	17.54	17.61	21.33
EPI: Outbreak or surveillance report	32.81	30.71	30.30	32.28	33.99	38.30
EPI: Qualitative study	20.41	31.75	35.29	40.00	33.33	36.73

EPI: Review	66.44	65.94	67.59	66.22	63.77	70.78*
EPI: Trial	56.76	60.76	73.68	68.35	55.70	71.60
BASIC: Animal experiment	65.12	71.91	57.53	57.89	57.78	72.29
BASIC: Basic research review	19.92	24.60	16.67	13.10	18.64	23.15
BASIC: Biochemical/protein structure studies	60.72	63.48	62.39	64.03	58.13	65.67
BASIC: In vitro experiment	36.36	48.75	41.61	44.05	42.77	46.36
BASIC: Sequencing and phylogenetics	68.68	66.94	72.06	69.64	67.33	70.08
BASIC: Within-host modelling	0.00	11.76	0.00	10.53	13.64	11.11
OTHER: Other	17.39	16.95	20.56	20.11	15.25	19.32
OTHER: Comment, editorial, ..., non-original	78.28	79.22	79.54	80.79	76.83	82.03*
micro avg	65.85	66.89	67.38	67.40	64.69	69.50*
macro avg	49.41	52.43	51.84	52.19	49.55	54.84*

369   D

	AUC-ROC	
Level	BioBERT	Ensemble
Class	91.77 (CI: 90.95, 92.50)	94.33 (CI: 93.70, 94.88)*
Subclass	91.35 (CI: 90.66, 92.01)	94.25 (CI: 93.72, 94.76)*
Sub-subclass	92.06 (CI: 91.56, 92.54)	94.77 (CI: 94.38, 95.12)*

371   Table 2

372   *Caption :*

373   *A,B,C: F1-score performance for the different models across categories and classification*

374   *levels. D: AUC-ROC performance and a 95% CI for the different classification levels for the*

375   *best standalone and the ensemble models. * Statistically significant improvement.*

Analyses of the ensemble model

In Figure 3, we analyzed major aspects of the ensemble outcomes. In Figure 3A, the

ensemble precision/recall curve is plotted against the curves for the *RoBERTa* base and large

models for the *ORIGINAL* class. As we can notice, the ensemble curve is consistently above

both *RoBERTa* models, which shows the robustness of using a probability sum strategy for

assembling models. The precision/recall curve obtained by the ensemble model for the 22

sub-subclasses are presented in Figure 3B. The same under-performing sub-subclasses as

previously spotted in the strict classification results can be distinguished, in particular, *EPI:*

Other, *BASIC: Basic research review*, *BASIC: Within-host modelling* and *OTHER: Other* (as

in Table 2A). This demonstrates that the low performance obtained for these categories is not

a result of the classification threshold tuning. Despite their poor performance, they are well

above a random classifier baseline, which would have a theoretical constant precision of

about 0.05 (1/22 sub-subclasses).

Figure 3

Caption:

A: Precision/recall curves of the ORIGINAL class for the RoBERTa base/large and the

ensemble. B: Precision/recall curves obtained by the ensemble model for the sub-subclasses.

Well represented sub-subclasses usually perform better than underrepresented ones.

Figure 4 shows the confusion matrix for the different classification levels obtained by the

ensemble model. As we can see from Figure 4A and 4B, the ensemble tends to predict *EPI*

subclass when misclassifying a document. When switching from Figure 4A to 4B, the *EPI*

confusion is split from the *BASIC* class into both *BASIC* and *OTHER*. For the sub-subclass

level (Figure 4C), the *EPI: Review* class (13) was consistently confused with the *BASIC:*

Basic research review (20). This confusion is expected considering that both sub-subclasses

refer to review documents. Moreover, the ensemble tends to get confused for some of the

EPI: ... study sub-subclasses, predicting often *Cohort* (4) instead of *Case-control* (3), *Cross-*

sectional (5) instead of *Qualitative* (12), *Modelling* (9) instead of *Ecological* (7), and others.

There is also a clear confusion cluster when the ensemble predicts *Biochemical/protein*

structure studies (17) and *Sequencing and phylogenetics* (18), as these documents are often

confused with some of the *BASIC* sub-subclasses (in particular from 15 to 19). These

observations reinforce our previous hypothesis that sub-subclasses were often misclassified

inside the same subclass. It becomes more evident if we focus on the sub-subclass confusion

matrix by square segments as highlighted in Figure 4C (horizontal and vertical gray lines):

from index 1 to 14 → *EPI*, from index 15 to 20 → *BASIC* and for index 21 and 22 → *OTHER*.

All shady squares inside this perimeter (the majority) are intra-subclass misclassifications,

while the ones outside are inter-subclass misclassifications. Lastly, a vertical line of

confusion can also be observed for the *OTHER: Comment, editorial, ..., non-original* sub-

subclass predictions, which the ensemble tends to predict for a wide variety of documents

(more precisely 8, 10-13, 20-21). The broad definition of this category is likely the reason for

its confusion with so many other sub-subclasses.

417

Figure 4

Caption: Confusion matrix for class (A), subclass (B) and sub-subclass (C). The ensemble

has a higher probability of confusing sub-subclasses inside their nested subclasses and

classes which is why performances tend to be higher at those higher levels.

Ranking analysis

Table 3 shows the ranking performance for the standalone models and the ensemble.

BioBERT performed better than all the other standalone models for the ranking metrics,

whereas it tended to be *PubMedBERT* in the strict classification perspective. However, in

both perspectives, the ensemble achieves the highest performance across all models. In fact,

the ensemble returns the right sub-subclass in the top-1 position in 71% of cases, with

precision@3 of 30% (theoretical maximum of 33%) and a recall@3 of 89%. This means that

in almost 9 out 10 document classifications, the ensemble returned the correct sub-subclass in

the top 3. Moreover, the ensemble got MAP@3 of 79%, representing more than 2.5 points

improvement with respect to the best standalone model (*BioBERT*).

Model	{P,R,MAP}@1 (%)	P@3 (%)	R@3 (%)	MAP@3 (%)
RoBERTa$_{base}$	65.99	27.10	81.29	72.69
RoBERTa$_{large}$	67.29	28.12	84.37	74.86
BioBERT	68.55	28.63	85.89	76.16
PubMedBERT	68.33	28.47	85.42	75.92
COVID-Twitter-BERT	64.98	27.88	83.64	73.14
Ensemble	70.57	29.69	89.07	78.92

Table 3

Caption: Metrics per label using the top-k retrieved categories. P=precision, R=recall,

MAP=mean average precision. As this is a single-label task, the max value for P@3 is 1/3

(33%).

k-vote analysis

In Figures 5, we show the strict classification performance for the *ORIGINAL* class using the

ensemble for different voting thresholds. The threshold for the number of votes (t)

corresponds to the minimal number of votes for a category required for the ensemble to

trigger a classification decision. Differently, the probability threshold per vote (t_v) refers to

the probability threshold a single model needs to reach to vote for a given category. When

such a probability threshold is not met, the model would not be allowed to vote. Such voting

strategies make *unknown* predictions possible, reducing the size of the classification set. In

addition to static voting thresholds (3, 4, 5), a dynamic threshold, for majority and unanimity,

is introduced where the total of votes can change depending on *unknown* predictions for a

given classifier. This means that if 2 classifiers (out of 5) were to predict *unknown* for a

publication, the dynamic majority and unanimity thresholds would be set at 2 and 3,

respectively.

The behavior of the *ORIGINAL* class prediction in terms of F1-score is presented in Figure

5A. As it is a binary problem, setting a dynamic majority and a static one ($t = 3$) while $t_v =$

0.5 produced the same results, a full size dot placed around 92%. This phenomenon is

possible because there will always be a predicted class that has more than $t_v = 0.5$; hence, all

the models end up voting. Overall, there is an average of about 93% F1-score on most of the

dataset across all the t_v when using majority voting rules and 97% F1-score on a subset of

about 80% of the dataset when using the static unanimity voting rule. In other words, for the

ORIGINAL class, confident results can be obtained (about 4 points F1-score growth) on a

subset of the collection (representing about 80% of the collection) when switching from a

majority to static unanimity voting rule. The respective performance in terms of precision and

recall metrics are shown in Figures 5B and 5C. We can notice that recall is consistently

higher than precision, which means that this ensemble strategy is better at retrieving

ORIGINAL articles than refining the selection. The observed trend is similar to the F1-score

performance, where we trade a 100% dataset classification and a precision of about 91.5%,

for a precision of about 96% on about 80% of the dataset with a fixed $t_v = 0.5$ when

switching from a majority to a static unanimity voting rule. A recall of about 99% and a F1-

score of about 98.5% are achieved on 50% of the subset when setting $t_v = 0.99$ and $t = 5$,

enabling the classification of half of the publications with almost no mistakes.

468 Figure 5

469 *Caption: F1-score (A)/Precision (B)/Recall (C) for the ORIGINAL class with respect to a*

470 *probability threshold per vote when using the voting strategy across the predictions on the*

471 *class level. Using different thresholds improves considerably performance while reducing the*

472 *number of predicted publications.*

 Model interpretation

Figure 6

Caption:

A-B-C: Top 20 positive impact words for either EPI (A), BASIC (B) or OTHER (C)

subclasses when taking the integrated gradient on a never-seen set of about 600 documents.

D-E-F: Classification examples with a focus on passages with impact words scores.

Figures 6A to 6C show the top 20 positive impact words for *EPI*, *BASIC* and *OTHER*

subclasses. When taking a close look at some lexical fields, in the *EPI* subclass for instance,

documents containing "modeling", "mathematical", "modelling", "simulation", "simulated"

and "equation" are all related to the *EPI: Modelling study* sub-subclass. Indeed, in the 38

documents subset containing at least one of those words, 37 were classified by the model as

EPI: Modelling study. In *BASIC*, the same applies for "seq" and "sequence" lexicons, where

27 publications out of 28 were classified by the model as either *BASIC: Sequencing and*

phylogenetics or *BASIC: Biochemical/protein structure studies*. In other words, the model

clearly seems to retain high importance words at the sub-subclass level, which makes sense

as it is the level the model was fine-tuned on. As for *OTHER*, it seems the classifier attributes

a lot of credit to the word "viewpoint" for any *OTHER: Comment, editorial, ..., non-original*

publications, with 7 out of 7 publications containing the word classified as so.

Figures 6D to 6F depict three publications highlighted using their integrated gradient scores.

Publication in Figure 6D[1] was chosen because it illustrates the usage of the top *BASIC* impact

words whereas publications in Figures 6E[2] and 6F[3] were selected because they emphasize the

---

[1] *https://www.biorxiv.org/content/10.1101/2020.04.07.029488v1.full*

[2] https://pubmed.ncbi.nlm.nih.gov/32237161/

[3] https://www.medrxiv.org/content/10.1101/2020.04.03.20051813v2

highest *EPI* impact words while giving an example of a negative impact word. In Figure 6D, the model predicts the *BASIC* label with 98% probability and the impact words seem to focus on the "sequence analysis" part, with "sequence" being the top impact word in average for that subclass. A look at the sub-subclass prediction level gives a probability of about 95% for the *BASIC: Sequencing and phylogenetics* sub-subclass. In Figure 6E, there is an example of a "sectional" occurrence, the reported most important word for the subclass *EPI*. In our set, the word appears in 7 documents, each time along with the words "cross" and "study". This publication is classified in *EPI: Cross-sectional study* sub-subclass with a probability of 96%. Interestingly, all 7 documents were classified as *EPI: Cross-sectional study* except for the publication of Figure 6F which was classified as *EPI: Cohort study* with 74% probability and, for which, the classifier seems to give more importance to the word "retrospective" in the methods section than to "sectional" in the design section. As both sub-subclasses are nested into the same subclass, the publication is still classified in the *EPI* subclass with a high probability of 98%.

Discussion

In this article, we introduce an efficient methodology to assist epidemiologists and biomedical curators to screen articles for inclusion in living systematic reviews by providing a COVID-19 literature triage solution based on deep learning methods. Supported by an existing manually classified collection, we proposed a classification method that automatically assigns categories from a living evidence knowledge base to scientific documents using BERT-like language models, based on which we proposed two methods to combine individual model predictions (probability sum and voting). The results demonstrate that the ensemble performs consistently better than any standalone model, statistically improving upon the best standalone baseline on both strict classification and ranking tasks.

Error analyses for the living evidence dataset used in our experiments showed that

classification confusion often happens at the intra category level. It helped to explain the

difference of performance observed when zooming from sub-subclass to class level, for

which micro F1-score goes from almost 70% to almost 90%, respectively. We believe that in

this case there are important patterns within categories that the machine learning models can

identify and exploit to provide the correct predictions at the class and subclass levels. On the

other hand, at the sub-subclass level, we expect that the documents could be often related to

more than one category, that is, they are mostly within one category, but may also contain

information associated to another category, which could lead to the confusion of the classifier

when assigning the sub-subclass, a phenomenon which also occurs during the human

annotation. Hence, we believe that a multi-label assignment strategy at the sub-subclass level

could be an interesting alternative in the original annotation protocol.

Given the strong performance of the proposed classifier, it could be used to support

annotation of scientific articles and help to speed up, augment and scale up epidemiological

reviews and biomedical curation. When looking at the problem from a ranking perspective, in

which the system suggests a list of sub-subclasses for a given article, the ensemble returned

the right category in its top 3 suggestions for almost 90% of the cases. Such a robust

performance could help augment the annotation process, for example, by enabling human

annotators to double the number of screened articles, replacing an annotator by a machine

annotation in the standard double annotation process. In this setting, if the category proposed

by the human annotator matched one of the top 3 categories proposed by the automatic

classifier, this category would be deemed validated. Otherwise, it would be sent to a senior

annotator for a final decision on the remaining 10% of the cases. Considering that a typical

inter-annotator agreement in the health and life sciences field is around 80% (47), this setup

could reduce the number of human resources required by at least 50% while maintaining the

high quality of the annotations. Alternatively, when using a voting strategy with a confidence

threshold, we showed that our method was capable of robust and superior performances in a

subset of the collection on the class level (about 98.5% F1-score on 50% of the dataset). This

approach could be used for example in the triage process, when a large batch of articles needs

to be classified, thus scaling up the classification process.

The interpretability analysis showed that the model is not a complete black box as it is often

the case in deep learning applications. Using the integrated gradient method helped to

understand why the model classified a publication according to a sub-subclass instead of

another. These results could be additionally used by annotation experts as a tool to highlight

documents during the curation process. It would also be interesting to investigate the results

of this analysis at the subclass level, which we believe could lead to a lexicon defining each

subclass. Such approaches could then be combined to get multiple views by category level,

which could be further assembled to get better publication insights and perhaps better

screening results. We leave this investigation for future works.

A main limitation of the study is that it uses a dataset of only one living evidence knowledge

base to train and evaluate the models. Thus, it is unclear how the proposed methodology will

generalize to corpora and categories used in other reviews and living evidence knowledge

bases. That said, given the strong performance obtained in other corpus types by a similar

methodology (34), we believe that it shall generalize well. Second, in our experiments, we

fail to explore the full contents of the articles. This is due to the unavailability of the full text

for a large portion of the collection due to either paywall or restriction by publishers to

process full text by NLP pipelines. Additionally, as the time complexity of the models used

are quadratic with the number of words, the computation time becomes prohibitive as we

move from abstract to full text content. Nevertheless, we believe that valuable information

supporting the classification can sometimes only be found in the full text of the manuscripts.

An extended version of the approach could investigate such corpora.

Conclusions

In this work we described an effective methodology to perform automatic classification of

COVID-19-related literature to support creation of systematic living reviews and living

evidence knowledge bases. The proposed ensemble model provided strong (semi-)automatic

classification performance, significantly outperforming standalone methods, and enabled the

categorization of a subset of the collection with improved accuracy. Hence, this approach

could serve as an alternative assistant to professionals dealing with the COVID-19 pandemic

literature outbreak. Ultimately, our method provides a performant and generic procedure,

enabling efficient annotation of important volumes of scientific literature, which could be

leveraged to assist experts in different literature classification tasks and extended to different

types of review methodologies.

List of abbreviations

BERT: Bidirectional Encoder Representations of Transformers; NLP: Natural Language

Processing; COAP: COVID-19 Open Access Project; AUC-ROC: Area Under the Curve of

the Receiver Operating Characteristics; CI: Confidence Interval; MAP: Mean Average

Precision

Declarations

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and materials

The datasets used and analyzed during the current study are available in the COAP living

Evidence database: https://zika.ispm.unibe.ch/assets/data/pub/ncov/. The training, testing and

ensemble source codes are available under https://github.com/ds4dh/CovidReview.

Competing interests

The authors declare that they have no competing interests.

Funding

This project has been supported by CINECA (UE H2020 GRANTT #825775 and Canadian

Institute of Health Research (CIHR) GRANTT #404896), Innosuisse project funding number

41013.1 IP-ICT, Swiss National Science Foundation (project number 176233), and European

Union Horizon 2020 research and innovation programme - project EpiPose (grant agreement

number 101003688).

Authors' contributions

JK designed and implemented the models, ran the experiments and analyses. JK, DT and QH

wrote the manuscript draft. NB created the benchmark dataset. DT, PA and NL conceived the

experiments. MC, HI and LH programmed and maintained the COVID-19 Open Access

Project living evidence database. DBG and AMI organized the annotation of study design in

the study records. All authors reviewed and approved the manuscript.

Acknowledgements

Lucia Araujo-Chaveron, Ingrid Arevalo-Rodriguez, Muge Cevik, Agustín Ciapponi,

Muhammad Irfanul Alam, Kaspar Meili, Eric A. Meyerowitz, Nirmala Prajapati, Xueting

Qiu, Aaron Richterman, William Gildardo Robles-Rodríguez, Shabnam Thapa, Ivan

Zhelyazkov annotated records in the COVID-19 Open Access Project living evidence

database.

References

1.   Chen Q, Allot A, Lu Z. LitCovid: an open database of COVID-19 literature. Nucleic

Acids Res. 2021 Jan 8;49(D1):D1534–40.

2.   Ipekci AM, Buitrago-Garcia D, Meili KW, Krauer F, Prajapati N, Thapa S, et al.

Outbreaks of publications about emerging infectious diseases: the case of SARS-CoV-2 and

Zika virus. BMC Med Res Methodol. 2021;50–50.

3.   Lu Wang L, Lo K, Chandrasekhar Y, Reas R, Yang J, Eide D, et al. CORD-19: The

Covid-19 Open Research Dataset. 2020 [cited 2022 Jun 29]; Available from:

https://search.bvsalud.org/global-literature-on-novel-coronavirus-2019-

ncov/resource/en/ppcovidwho-2130

4.   Counotte M, Imeri H, Leonie H, Ipekci M, Low N. Living Evidence on COVID-19

[Internet]. 2020 [cited 2022 Jun 29]. Available from: https://ispmbern.github.io/covid-

19/living-review/

5.   The COVID-NMA initiative [Internet]. [cited 2022 Jun 29]. Available from:

https://covid-nma.com/

6.   National COVID-19 Clinical Evidence Taskforce [Internet]. [cited 2022 Jun 29].

Available from: https://covid19evidence.net.au/

7.   COVID-19: Living systematic map of the evidence [Internet]. [cited 2022 Jun 29].

Available from:

http://eppi.ioe.ac.uk/cms/Projects/DepartmentofHealthandSocialCare/Publishedreviews/COV

ID-19Livingsystematicmapoftheevidence/tabid/3765/Default.aspx

8.   Elliott JH, Turner T, Clavisi O, Thomas J, Higgins JPT, Mavergames C, et al. Living

Systematic Reviews: An Emerging Opportunity to Narrow the Evidence-Practice Gap. PLOS

Med. 2014 Feb 18;11(2):e1001603.

9.   Tendal B, Vogel JP, McDonald S, Norris S, Cumpston M, White H, et al. Weekly

updates of national living evidence-based guidelines: methods for the Australian living

guidelines for care of people with COVID-19. J Clin Epidemiol. 2021 Mar 1;131:11–21.

10.   Baumgartner WA, Cohen KB, Fox LM, Acquaah-Mensah G, Hunter L. Manual

curation is not sufficient for annotation of genomic databases. Bioinforma Oxf Engl. 2007 Jul

1;23(13):i41–8.

11.   Bourne PE, Lorsch JR, Green ED. Perspective: Sustaining the big-data ecosystem.

Nature. 2015 Nov 5;527(7576):S16-17.

12.   Chai KEK, Lines RLJ, Gucciardi DF, Ng L. Research Screener: a machine learning

tool to semi-automate abstract screening for systematic reviews. Syst Rev. 2021 Apr

1;10(1):93.

13.   Garcia-Pelaez J, Rodriguez D, Medina-Molina R, Garcia-Rivas G, Jerjes-Sánchez C,

Trevino V. PubTerm: a web tool for organizing, annotating and curating genes, diseases,

molecules and other concepts from PubMed records. Database J Biol Databases Curation.

2019 Jan 8;2019.

14.   Hirschman L, Burns GAPC, Krallinger M, Arighi C, Cohen KB, Valencia A, et al.

Text mining for the biocuration workflow. Database. 2012 Jan 1;2012:bas020.

15.   Lee K, Famiglietti ML, McMahon A, Wei CH, MacArthur JAL, Poux S, et al. Scaling

up data curation using deep learning: An application to literature triage in genomic variation

resources. PLOS Comput Biol. 2018 Aug 13;14(8):e1006390.

16.   Müller HM, Van Auken KM, Li Y, Sternberg PW. Textpresso Central: a customizable

platform for searching, text mining, viewing, and curating biomedical literature. BMC

Bioinformatics. 2018 Mar 9;19(1):94.

17.   O'Mara-Eves A, Thomas J, McNaught J, Miwa M, Ananiadou S. Using text mining

for study identification in systematic reviews: a systematic review of current approaches. Syst

Rev. 2015 Jan 14;4(1):5.

18.   Van Auken K, Fey P, Berardini TZ, Dodson R, Cooper L, Li D, et al. Text mining in

the biocuration workflow: applications for literature curation at WormBase, dictyBase and

TAIR. Database J Biol Databases Curation. 2012 Nov 15;2012:bas040.

19.   Wei CH, Allot A, Leaman R, Lu Z. PubTator central: automated concept annotation

for biomedical full text articles. Nucleic Acids Res. 2019 Jul 2;47(W1):W587–93.

20.   Gobeill J, Caucheteur D, Michel PA, Mottin L, Pasche E, Ruch P. SIB Literature

Services: RESTful customizable search engines in biomedical literature, enriched with

automatically mapped biomedical concepts. Nucleic Acids Res. 2020 Jul 2;48(W1):W12–6.

21.   Pasche E, Mottaz A, Caucheteur D, Gobeill J, Michel PA, Ruch P. Variomes: a high

recall search engine to support the curation of genomic variants. Bioinformatics. 2022 Apr

28;38(9):2595–601.

22.   Mottaz A, Pasche E, Michel PAA, Mottin L, Teodoro D, Ruch P. Designing an

Optimal Expansion Method to Improve the Recall of a Genomic Variant Curation-Support

Service. Stud Health Technol Inform. 2022;294:839–43.

23.   Dhar A, Mukherjee H, Dash NS, Roy K. Text categorization: past and present. Artif

Intell Rev. 2021 Apr 1;54(4):3007–54.

24.   Sebastiani F. Machine learning in automated text categorization. ACM Comput Surv.

2002 Mar 1;34(1):1–47.

25.   Teodoro D, Knafou J, Naderi N, Pasche E, Gobeill J, Arighi CN, et al. UPCLASS: a

deep learning-based classifier for UniProtKB entry publications. Database. 2020 Jan

1;2020:baaa026.

26.   Manning C, Schütze H. Foundations of Statistical Natural Language Processing.

Cambridge, MA, USA: MIT Press; 1999. 718 p.

27.   Teodoro, Gobeill J, Pasche E, Ruch P, Vishnyakova D, Lovis C. Automatic IPC

encoding and novelty tracking for effective patent mining. Tokyo, Japan; 2010. p. 309–17.

28.   Hastie T, Tibshirani R, Friedman J. The elements of statistical learning [Internet]. 2nd

ed. Springer; 2009. Available from: https://web.stanford.edu/~hastie/Papers/ESLII.pdf

29.   Peters ME, Ammar W, Bhagavatula C, Power R. Semi-supervised sequence tagging

with bidirectional language models. In: Proceedings of the 55th Annual Meeting of the

Association for Computational Linguistics (Volume 1: Long Papers) [Internet]. Vancouver,

Canada: Association for Computational Linguistics; 2017 [cited 2022 Jun 29]. p. 1756–65.

Available from: https://aclanthology.org/P17-1161

30.   Devlin J, Chang MW, Lee K, Toutanova K. BERT: Pre-training of Deep Bidirectional

Transformers for Language Understanding. ArXiv181004805 Cs [Internet]. 2019 May 24

[cited 2020 May 1]; Available from: http://arxiv.org/abs/1810.04805

31.   Aum S, Choe S. srBERT: automatic article classification model for systematic review

using BERT. Syst Rev. 2021 Dec;10(1):285.

32.   Knafou J, Naderi N, Copara J, Teodoro D, Ruch P. BiTeM at WNUT 2020 Shared

Task-1: Named Entity Recognition over Wet Lab Protocols using an Ensemble of Contextual

Language Models. In: Proceedings of the Sixth Workshop on Noisy User-generated Text (W-

NUT 2020) [Internet]. Online: Association for Computational Linguistics; 2020 [cited 2022

Jun 29]. p. 305–13. Available from: https://aclanthology.org/2020.wnut-1.40

33.   Copara J, Naderi N, Knafou J, Ruch P, Teodoro D. Named entity recognition in

chemical patents using ensemble of contextual language models [Internet]. arXiv; 2020 [cited

2022 Jun 29]. Available from: http://arxiv.org/abs/2007.12569

34.   Naderi N, Knafou J, Copara J, Ruch P, Teodoro D. Ensemble of Deep Masked

Language Models for Effective Named Entity Recognition in Health and Life Science

Corpora. Front Res Metr Anal [Internet]. 2021 [cited 2022 Jun 29];6. Available from:

https://www.frontiersin.org/article/10.3389/frma.2021.689803

35.   Gage P. A New Algorithm for Data Compression. :14.

36.   Schuster M, Nakajima K. Japanese and Korean Voice Search. In: International

Conference on Acoustics, Speech and Signal Processing. 2012. p. 5149–52.

37.   Sennrich R, Haddow B, Birch A. Neural Machine Translation of Rare Words with

Subword Units [Internet]. arXiv; 2016 [cited 2022 Jun 29]. Available from:

http://arxiv.org/abs/1508.07909

38.   Wu Y, Schuster M, Chen Z, Le QV, Norouzi M, Macherey W, et al. Google's Neural

Machine Translation System: Bridging the Gap between Human and Machine Translation

[Internet]. arXiv; 2016 [cited 2022 Jun 29]. Available from: http://arxiv.org/abs/1609.08144

39.   Liu Y, Ott M, Goyal N, Du J, Joshi M, Chen D, et al. RoBERTa: A Robustly

Optimized BERT Pretraining Approach. ArXiv190711692 Cs [Internet]. 2019 Jul 26 [cited

2020 Apr 30]; Available from: http://arxiv.org/abs/1907.11692

40.   Müller M, Salathé M, Kummervold PE. COVID-Twitter-BERT: A Natural Language

Processing Model to Analyse COVID-19 Content on Twitter [Internet]. arXiv; 2020 [cited

2022 Jun 29]. Available from: http://arxiv.org/abs/2005.07503

41.   Lee J, Yoon W, Kim S, Kim D, Kim S, So CH, et al. BioBERT: a pre-trained

biomedical language representation model for biomedical text mining. Bioinformatics. 2020

Feb 15;36(4):1234–40.

42.   Gu Y, Tinn R, Cheng H, Lucas M, Usuyama N, Liu X, et al. Domain-Specific

Language Model Pretraining for Biomedical Natural Language Processing. ACM Trans

Comput Healthc. 2022 Jan 31;3(1):1–23.

43.   Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al. Attention Is

All You Need. ArXiv170603762 Cs [Internet]. 2017 Dec 5 [cited 2020 Feb 8]; Available

from: http://arxiv.org/abs/1706.03762

44.   Sundararajan M, Taly A, Yan Q. Axiomatic Attribution for Deep Networks. In:

Proceedings of the 34th International Conference on Machine Learning [Internet]. PMLR;

2017 [cited 2022 Jun 29]. p. 3319–28. Available from:

https://proceedings.mlr.press/v70/sundararajan17a.html

45.   Captum · Model Interpretability for PyTorch [Internet]. [cited 2022 Jun 29]. Available

from: https://captum.ai/

46.   McNemar Q. Note on the sampling error of the difference between correlated

proportions or percentages. Psychometrika. 1947 Jun 1;12(2):153–7.

47.   Wilbur WJ, Rzhetsky A, Shatkay H. New directions in biomedical text annotation:

definitions, guidelines and corpus construction. BMC Bioinformatics. 2006;7:356.

A. EPI

sectional
modeling
simulation
modelling
mathematical
cohort
simulated
review
questionnaire
meta
model
survey
prediction
consensus
equation
assumed
advice
estimation
literature
pubmed

Words

B. BASIC

sequencing
seq
computational
characterization
dynamic
structural
dataset
here
resolution
work
transcriptome
docking
sequence
analyzed
structure
genomic
identification
phylogenetic
analysis
simulation

C. OTHER

viewpoint
psychiatry
moral
pediatrics
perspective
something
lesson
education
commentary
news
colleague
lancet
caregiver
recommend
discus
oral
scientist
doctor
ethical
figure

Scores

D

Legend: ☐ Negative ☐ Neutral ☐ Positive

Predicted Label   **Word Importance**

BASIC (0.98)

Journal: bioRxiv

Title: Vulnerabilities of the SARS-CoV-2 virus to proteotoxicity - opportunity for repurposed chemotherapy of COVID-19 infection

Abstract: [start of abstract] ... Sequence analysis of functional domains in the SARS-CoV-2 proteome showed 0.8-fold depletion of cysteine residues and 4.9-fold enrichment of arginine residues, suggesting methylglyoxal modification may inactivate the virus. We discovered ... [end of abstract]

E

Legend: ☐ Negative ☐ Neutral ☐ Positive

Predicted Label   **Word Importance**

EPI (0.99)

Journal: Journal of Medical Virology

Title: Is Pakistan prepared for the COVID-19 epidemic? A questionnaire-based survey

Abstract: COVID-19 is a pandemic that began in china in december 2019. World health organization (WHO) has expressed fears that Pakistan might emerge as the next epicenter of this pandemic. We hypothesize that at present the Pakistani masses are not prepared to face any threat of a looming epidemic. The main aim of this study was to evaluate the basic knowledge of educational and health care workers (hcw's) regarding COVID-19, its control, and prevention. Knowledge about origin, symptoms, and spread of viral infection was assessed. In this cross-sectional survey, a self - designed questionnaire was distributed among ... [end of abstract]

F

Legend: ☐ Negative ☐ Neutral ☐ Positive

Predicted Label   **Word Importance**

EPI (0.98)

Journal: medRxiv

Title: Separate Fever Clinics Prevent the Spread of COVID-19 and Offload Emergency Resources: Analysis from a large tertiary hospital in China

Abstract:

[start of abstract] ...

Design : A population-based cross-sectional study.

Participants : A total of 6,365 patients were screened in the FC.

Methods : The FC of Peking Union Medical College Hospital (PUMCH) was upgraded on January 20, 2020. We performed a retrospective study of patients presenting to the FC between December 12, 2019 to february 29, 2020, covering a period of 40 days before and after upgrading the FC. ... [end of abstract]