20230127

Analysis of convolutional neural networks reveals the computational properties essential for subcortical processing of facial expression

Chanseok Lim[1,2], Mikio Inagaki[1,3], Takashi Shinozaki[3,4], Ichiro Fujita[1,3,5, *]

[1]Laboratory for Cognitive Neuroscience, and [2]Perceptual and Cognitive Neuroscience Laboratory, Graduate School of Frontier Biosciences, Osaka University, 1-4 Yamadaoka, Suita, Osaka 565-0871, Japan; [3]Center for Information and Neural Networks, National Institute of Information and Communications Technology, 1-4 Yamadaoka, Suita, Osaka 565-0871, Japan; [4]Computational Neuroscience Laboratory, Faculty of Informatics, Kindai University, 3-4-1 Kowakae, Higashiosaka, Osaka 577-8502, Japan; [5]Research Organization of Science and Technology, Ritsumeikan University, 1-1-1 Noji-higashi, Kusatsu, Shiga 525-8577, Japan

ORCID numbers:
	Chanseok Lim	0000-0002-4611-2740
	Mikio Inagaki	0000-0002-5294-501X
	Takashi Shinozaki	0000-0002-0641-6782
	Ichiro Fujita	0000-0003-3293-8610

*Corresponding author: Ichiro Fujita, PhD
Laboratory for Cognitive Neuroscience, Graduate School of Frontier Biosciences, Osaka University, 1-4 Yamadaoka, Suita, Osaka 565-0871, Japan
Phone: +81-6-6879-4439
Fax: +81-6-6879-4439
E-mail: fujita@fbs.osaka-u.ac.jp

Number of pages: 36 pages
Number of figures: 8 figures
Number of tables: 1 table
Number of words in abstract: 200 words

37 **Abstract**
38

Perception of facial expression is crucial in the social life of primates. This visual information
is processed along the ventral cortical pathway and the subcortical pathway. Processing of face
information in the subcortical pathway is inaccurate, but the architectural and physiological
properties that are responsible remain unclear. We analyzed the performance of convolutional
neural networks incorporating three prominent properties of this pathway: a shallow layer
architecture, concentric receptive fields at the first processing stage, and a greater degree of
spatial pooling. The neural networks designed in this way could be trained to classify seven
facial expressions with a correct rate of 51% (chance level, 14%). This modest performance was
gradually improved by replacing the three properties, one-by-one, two at a time, or all three
simultaneously, with the corresponding features in the cortical pathway. Some processing units
in the final layer were sensitive to spatial frequencies (SFs) in the retina-based coordinate,
whereas others were sensitive to object-based SFs, similar to neurons in the amygdala.
Replacement of any one of these properties affected the SF coordinate of units. All three
properties constrain the accuracy of facial expression information in the subcortical pathway,
and are essential for determining the coordinate of SF representation.

54
55
56 **Keywords**

Introduction

Perceiving the facial expressions of other individuals plays a critical role in the social life of primates, including humans. Two neural pathways, the ventral cortical pathway and the subcortical pathway, contribute to this perceptual ability (Fig. 1A; Pessoa and Adolphs, 2010; Tamietto and de Gelder, 2010; Petray and Bickford, 2019). The ventral cortical pathway consists of a network of areas in the occipito-temporal region of the cerebral cortex, and processes a variety of visual features of objects, people, and environments, including shape, color, texture, material properties, and binocular disparity (Ungerleider and Mishkin, 1982; Connor et al., 2007; Conway et al., 2010; Roe et al., 2012; Kravitz et al., 2013; Vaziri et al., 2014; Verhoef et al., 2016; Komatsu and Goda, 2018). Neurons that preferentially respond to images of faces or facial features are found in several clusters along this pathway (Desimone et al., 1984; Perrett et al., 1987; Fujita et al., 1992; Haxby et al., 2000; Tsao and Livingstone, 2008; Duchaine and Yovel, 2015; Freiwald et al., 2016). They constitute the neural system that analyzes facial details such as expression, identity, and direction of attention. The subcortical pathway consists of a few processing stages in phylogenetically ancient regions: the superior colliculus in the midbrain, the pulvinar nucleus in the posterior thalamus, and the amygdala in the medial limbic system. The subcortical pathway is suggested to mediate rapid behavioral and physiological (autonomic) responses to sensory signals related to possible dangers such as fearful faces (Tamietto and de Gelder, 2010; Nakano et al., 2013; for a critical review, see Pessoa and Adolphs, 2010). The ventral cortical pathway and the subcortical pathway intersect at the amygdala.

Psychological and brain imaging studies suggest that the subcortical pathway subserves the ability of some patients with lesions in the primary visual cortex (V1) to discriminate facial expressions despite lacking visual awareness ("affective blindsight"; deGelder et al., 1999; Pegna et al., 2005; Striemer et al., 2019). These patients also reflexively exhibit specific facial expressions and pupillary reactions when exposed to fearful or happy faces (Tamietto et al., 2009). Studies have also shown that the subcortical pathway supports unconscious face perception in neurologically healthy subjects (Morris et al., 1999, 2001). Furthermore, orientation bias toward faces or face-like patterns by newborn babies is suggested to be mediated by the subcortical pathway (Cassia et al., 2001; Johnson, 2005; but see Buiatti et al., 2019). Importantly, these perceptual abilities are not perfectly accurate, instead resulting in modest performance at above-chance levels. These findings suggest that information on faces conveyed by the subcortical pathway is less accurate than that carried by the ventral cortical pathway.

Electrophysiological studies have demonstrated that processing of facial expression in the subcortical pathway is indeed fast and not very accurate. Méndez-Bértolo and colleagues (2016) showed that intracranial local field potentials in the human amygdala respond differentially to fearful faces versus other faces within 74 ms after stimulus onset. A recent single-neuron recording study in the monkey revealed that a population of amygdala neurons responded to threatening faces even within 50 ms (Inagaki et al., 2022a). This early response, when combined across an ensemble of neurons, carries information that allows linear classifiers to discriminate threatening faces from neutral and affiliative faces. The rate of correctly discriminating the three expressions is around 50%; this is well above chance (33%), but significantly worse than perfect.

105   Some neurons in the superior colliculus and pulvinar of the monkey also respond to faces and
106   face-like patterns with an even shorter latency of 30–50 ms (Nguyen et al., 2013, 2014).
107
What architectural and physiological properties of the subcortical pathway are responsible for
its fast, crude processing? The fast processing most likely arises from the small number, or
"shallowness," of processing stages in the subcortical pathway, given that the ventral cortical
pathway and its upstream area (the lateral geniculate nucleus) consist of a larger number of
regions (at least six before reaching the amygdala) than the subcortical pathway (only two), and
that every transition from one cortical region to the next takes at least 10 ms (Schmolesky et al.,
1998). It is unclear whether the shallow processing similarly explains the low accuracy of the
information transmitted by the subcortical pathway to the amygdala. This uncertainty arises
from the fact that in addition to the difference in the number of processing stages, visual
response properties differ markedly between the two pathways. Neurons in the superior
colliculus at the first stage of the subcortical pathway show circular receptive fields with center-
surround organization, which can be modeled using the difference-of-Gaussian (DoG) function
(Cynader and Berman 1972; Updyke 1974; Marino et al. 2008; Churan et al., 2012). By contrast,
simple cells of V1 at the first stage of the cortical pathway have elongated receptive fields with
side-by-side ON and OFF subregions, which can be modeled by two-dimensional Gabor
functions (Jones and Palmer, 1987). Furthermore, the receptive field is typically larger in the
superior colliculus (for the foveal field, 1.5–10° in superficial layers, 10–20° in deep layers;
Goldberg and Wurtz, 1972; Wallace et al., 1997) than in V1 (1.18° in simple cells, 1.3° in
complex cells; Van den Bergh et al., 2010) and the extrastriate areas V2 and V4 (Freeman and
Simoncelli, 2011). Thus, spatial pooling across ascending stages occurs over a wider visual field
area in the subcortical pathway than in the ventral cortical pathway.
129
In the present study, we addressed how these properties of the subcortical pathway, i.e., the
shallowness of processing stages, DoG-type receptive fields at the initial stage, and spatial
pooling over a wider visual field, influence facial expression processing. To this aim, we
constructed convolutional neural networks (CNNs) and analyzed their performance in facial
expression discrimination. CNNs are one type of multilayer perceptron, and can be optimized
("learn") to classify inputs by varying connection weights between processing units through
supervised learning algorithms (LeCun et al., 2015). Typical CNNs have several to tens of layers
(deep neural networks, DNNs). DNNs developed for classifying visual objects share
architectural and representational features similar to those of the ventral cortical pathway
(Yamins et al., 2014; Güçlü and van Gerven, 2015; Yamins and DiCarlo, 2016; Hassabis et al.,
2017). We designed our CNNs to imitate the subcortical pathway by reducing the number of
processing stages and by implementing DoG-type receptive fields and a wider extent of pooling.
These CNNs, hereafter referred to as shallow neural networks (SNNs), learned to discriminate
facial expressions with modest correct rates. Replacing the three properties, one-by-one, two at
a time, or all three simultaneously, with the corresponding properties in the ventral cortical
pathway gradually improved discrimination performance, suggesting that all three features are
responsible for limiting the performance of the SNNs. We further showed that like some neurons
in the amygdala, a major group of units in the final processing layer of the SNNs were sensitive
to spatial frequency (SF) in the retina-based reference frame as initially detected in the first

processing layer, and that the three subcortical properties contribute to preserving the retina-
based SF sensitivity.
151
152
153 **Materials and Methods**
154
Architecture of SNNs.
We constructed SNNs incorporating the distinct properties of the primate subcortical pathway
(Fig. 1B–D; Table 1). Unlike typical DNNs, the SNNs consisted of only two sets of convolution
and pooling layers followed by two fully connected layers (FC1, FC2), approximating the small
number of processing stages of the subcortical pathway. The first convolution layer incorporated
32 DoG-type filters (Fig. 1C, top) with a spatial resolution of 11×11 pixels, whereas weights
in the second convolution layer were initially random, i.e., the filters had no structure, and
gradually changed through training. A rectified linear unit (ReLU) was used as the activation
function of a unit in the convolution layers and FC1; the ReLU forwards the processing results
directly to the next stage if they are positive, otherwise it outputs zero. A max pooling operation
was performed over 5×5 sliding regions with a stride of 4 for the outputs of convolution layers
(Fig. 1D, top). Max pooling selected the largest value among the responses of units within a
sliding window over the preceding convolution layer, and forwarded the value to the next layer.
A local response normalization process was added after the pooling layers to aid generalization
(Krizhevsky et al., 2012; we used slightly different parameters from theirs; k = 1, n = 5, $\alpha = 2 \times$
10^{-5}, $\beta = 0.75$). Every unit in FC1 and FC2 received inputs from all units in the immediately
preceding layer, i.e., each was fully connected. FC1 is the final processing layer, and FC2
outputs the results of entire processing by the SNNs. These features were implemented to
capture the architectural and computational properties of the subcortical pathway, i.e., fewer
processing stages compared to the ventral cortical pathway (Fig. 1A), DoG-type receptive fields
in the superficial layer of the superior colliculus (Churan et al., 2012), and large receptive fields
of deeper superior colliculus neurons (Wallace et al., 1997). The first three processing layers
were intended to represent the superior colliculus, pulvinar, and amygdala, respectively. The
processing types of these layers, i.e., convolution and pooling in the first two layers and full
connection in FC1, were chosen to match the retinotopic organization of the three brain regions.
The convolution and pooling processes in the first two layers exploit retinotopy, as the superior
colliculus and pulvinar contain retinotopic maps (Bender, 1981; Chen et al., 2019). The FC1
layer loses retinotopic information because of the fully convergent connection from the earlier
stage, as the amygdala does not have a retinotopic map (Morawetz et al., 2010).
184
185 The SNNs were trained to discriminate images of facial expressions representing seven basic
186 emotions: angry, disgusted, fearful, happy, sad, surprised, and neutral (Fig. 1E; see below for
187 details). For each input image, the seven units in FC2 yielded scores ranging from 0 to 1 for the
188 seven expression categories, representing the probabilities of classified expressions. The
189 expression with the highest score was taken as the output of the model.
190

191
192
Figure 1. Shallow neural networks (SNNs) and modifications. (A) Cortical and subcortical
visual pathways for processing facial expressions in the primate brain. AMYG: amygdala; AIT,
PIT: anterior and posterior parts of inferior temporal cortex; LGN: lateral geniculate nucleus;
PU: pulvinar nucleus; SC: superior colliculus; V1, V2, V4: visual areas 1, 2, 4. (B) A schematic
illustration of the SNNs and full-replacement models. In the full-replacement models,
processing layers were added, the filters in the initial layer were changed with Gabor filters, and
the range of pooling was narrowed. (C) DoG filters for the SNNs and DoG models (upper) and
Gabor filters for the Gabor models (lower). (D) The pooling range for the SNNs (5×5) and the
narrow-pooling models (3×3). (E) Examples of presented face images with seven expressions
(angry, disgusted, fearful, happy, sad, surprised, neutral) of two individuals (upper: female,
AF06; lower: male, AM27). The original images were obtained from the Karolinska Directed
Emotional Faces database (Lundqvist et al., 1998).
205

206   *Table 1.* Architecture of the Shallow Neural Network (SNN). Each row describes a layer *i* with
207   calculation operator Fi, output resolution $H_i \times W_i$, and the number of output channels C_i. Conv
208   denotes convolution layer, and Pool denotes max pooling layer.
209

Input & Layer i	Operator F_i	Resolution $H_i \times W_i$	#Channels C_i
Input		227×227	3
Layer 1	11×11 Conv (stride 4) & 5×5 Pool (stride 4)	55×55	32
Layer 2	5×5 Conv (stride 1) & 5×5 Pool (stride 4)	4×4	64
Layer 3	Fully connected	1×1	32
Layer 4	Fully connected	1×1	7

210
211
212
213   The DoG-type filters of the first convolution layer were built using the following formula:
214
215    $$DoG(r) = \pm A_1 exp\left(-\frac{r^2}{2\sigma_1{}^2}\right) \mp A_2 exp\left(-\frac{r^2}{2\sigma_2{}^2}\right), \qquad (1)$$
216
where *r* is the polar radius from the filter center, A_1 and A_2 are the amplitudes of exponentials of
two Gaussian functions, and σ_1 and σ_2 are the standard deviations. Values of A_1, A_2, σ_1, and σ_2
were chosen empirically so that DoG curves took the shapes of Mexican hats. A_1 values were
0.4, 0.67, 0.8, and 1.0. A_2 values were determined based on $A_1 - A_2 = 0.4$. When A_1 was 0.4 (i.e.,
A_2 is 0, and σ_2 cannot be defined), we set the σ_1 value at $1/2\sqrt{2}, 1/4\sqrt{2}, 1/8\sqrt{2}$, or $1/16\sqrt{2}$.
Otherwise, the σ_1 value was $1/2\sqrt{2}$ or $1/4\sqrt{2}$. The σ_2 value was based on $\sigma_1/\sigma_2 = 0.5$ or 0.25.
The same number of filters was generated for each A_1 value.
224
We also constructed modified models in which the three properties of the SNNs were replaced
one-by-one, two at a time, or all three simultaneously with the corresponding properties in the
ventral cortical pathway. First, we added additional convolution layers with filters of 3×3 pixels
after each of the first two convolution layers to increase the number of processing stages (add-
layer model). In adding the convolution layers, the stride of sliding filters was reduced to 1 to
keep the output resolutions unchanged before and after adding the new layers. Also, to keep the
number of the output channels unchanged, the new layers contained the same number of filters
as the preceding layers.
233
234   Second, we replaced the DoG-type filters with Gabor-type filters (Gabor model). Gabor-type
235   filtering occurs in simple cells of V1, and emerges in the first layer of DNNs after they are
236   trained to classify object images (Krizhevsky et al., 2012; Rai and Rivas, 2022). We constructed
237   the Gabor-type filters with the following formula:
238
239    $$g(x,y; f,\theta) = Aexp(-\frac{x^2+y^2}{2\sigma^2})exp(2\pi if(xcos\theta + ysin\theta)), \qquad (2)$$
240

where *A* is the amplitude of the Gaussian envelope, *i* is $\sqrt{-1}$, *f* is the carrier frequency of a Gabor filter, and *θ* is the orientation (Movellan, 2002). *A* was fixed at 0.4 to match the amplitude of the DoG filters. *σ* was fixed at 0.125 so that the half-amplitude width was half of the filter width. *f* values were 2 or 4 cycles/image. Orientation *θ* was 0, 22.5, 45, 67.5, 90, 112.5, 135, or 157.5. We built even- and odd-symmetric filters for every combination of variables. In total, we obtained 32 Gabor-type filters (Fig. 1C, bottom).

Finally, we made the pooling window (convergence field) in the max pooling layers smaller (3 × 3; Fig. 1D, bottom) than that of the SNNs (5 × 5; Fig. 1D, top), enabling better spatial resolution of processing (narrow-pooling model) to mimic the smaller receptive fields in the visual cortices compared to the superior colliculus and pulvinar (Wallace et al., 1997; Vand den Bergh et al., 2010; Freeman and Simoncelli, 2011). The pooling range of 3 × 3 is often used in DNNs (e.g., AlexNet of Krizhevsky et al., 2012; ResNet of He et al., 2016).

Face images and training of the SNNs.
Face images were obtained from Karolinska Directed Emotional Faces (KDEF; Lundqvist et al., 1998) and Radboud Faces Database (RaFD; Langer et al., 2010). Images of the seven expressions of 40 individuals (half females, half males) were chosen from each database (the total number of images was 560 = 7 × 40 × 2). We converted the images from color into grayscale, and extracted the face region by removing hair, neck, and ears with the face-detection function of a computer vision library, OpenCV (Open Source Computer Vision Library; Bradski, 2000). The isolated faces were pasted on a gray background (198 × 198 pixels; RGB values = 128; Fig. 1E). We augmented the number of face images by changing size and position, and by flipping horizontally; seven sizes (28 × 28, 56 × 56, 85 × 85, 113 × 113, 141 × 141, 170 × 170, and 198 × 198 pixels), five positions (center, left-top, right-top, left-bottom, and right-bottom; directional displacements = 10 pixels), and two horizontally flipped images. The augmentation increased the number of images by 70 times to 39,200. At each training session, we randomly split this augmented set of face images into a training set (29,400 images), a validation set (2,450 images), and a test set (7,350 images). The number of images per facial expression was identical within each of these stimulus sets. To avoid the inadvertently biased assignment of face images of a particular size, position, or horizontal flip state into a given set, all images from the same individual were assigned into the same set.

The training was performed through supervised learning, and was conducted individually 20 times with randomized initial weights except for the built-in weights of the fist convolution layer, i.e., 20 SNNs with different initial states were built. In training, the weights other than the first convolution layer were optimized for classification of face images into the seven categories. Stochastic gradient descent was used for weight optimization. For each iteration, 32 samples were randomly selected from the training set as a mini-batch. The averaged cross-entropy (Goodfellow et al., 2016) across the 32 images in a mini-batch was calculated as an estimate of loss value, which is a measure of the difference between a model output and a supervised signal, and is used for quantifying the training effect. The number of iterations (i.e., weight-updating processes with single mini-batches) was set at 240,000. Initial weight parameters followed a normal distribution with a mean of 0 and a standard deviation of $\sqrt{(2/N)}$ (*N* is the total number of weights; He et al., 2015). Weights were updated at each iteration with a constant learning rate

of 0.001. This learning rate was determined empirically; a preliminary analysis based on 10
constructed SNNs (different from the 20 SNNs in the main analysis) revealed no decrease in
loss values (i.e., no learning) with a learning rate of 0.01, which has frequently been used for
DNNs in the literature (e.g., Simonyan and Zisserman, 2014). A dropout process was added
before FC2 to facilitate learning across all units. The proportion of units dropped out of each
weight update was set to 0.5. The training was conducted in a Python environment (Chainer
3.0.0; Tokui et al., 2015) on a graphics processing unit (GPU) machine (Intel$^®$ Core™ i7-5820K
Processor. Intel, Santa Clara, CA, USA; The GeForce$^®$ GTX 1080 Ti, NVIDIA, Santa Clara,
CA, USA). While the SNNs were being trained with the training set, the correct rate and loss
value for the validation set were periodically checked to monitor signs of overfitting. After
training was completed, the performance of the models was evaluated using the test dataset that
had not been used for training. This was done to ensure that the models acquired a genuine
ability to classify the facial expressions, as opposed to simply sorting the training images into
the seven facial expression categories according to the instruction signals.

Test for reference frames of SF tuning of model units.
A difference in visual responses between the two pathways is the reference frame of neuronal
tuning to SFs (Inagaki and Fujita, 2011). Neurons in the inferior temporal cortex, the final stage
of the ventral cortical pathway, are tuned to object-based SFs (cycles/object) and represent face
patterns in a size-invariant, hence distance-invariant, manner (Fig. 2A, right). Thus, the ventral
cortical pathway converts the representation of SFs in the retina-based coordinate
(cycles/degree) to that of object-based SFs. By contrast, many amygdala neurons preserve
sensitivity to retina-based SFs. When the stimulus size is changed, these neurons change their
preferred object-based SFs; for large stimuli, they respond to higher object-based SFs, which
correspond to the same retina-based SFs (Fig. 2A, left). We analyzed the reference frame of
FC1 SF tuning to evaluate how well our models captured this characteristic of subcortical
processing.

Bandpass-filtered face images were used to examine the SF tunings of FC1 units (Fig. 2B).
These images were created by multiplying Gaussian functions with the original face images on
the polar Fourier domain. Gaussian functions had 61 different center frequencies between 1
cycle/object and 64 cycles/object. The center frequencies had discrete values at steps of 0.1
cycles/object on a log scale. Gaussian functions shared the same variance at 2.4 octaves,
regardless of their center frequencies. The filtered images had amplitude spectra that were
determined solely by the Gaussian function because their spectra were set to be flat before the
multiplication. To balance the total luminance contrast among the filtered face images, the peak
amplitude of the Gaussian function was set inversely proportional to the center image-based SF
(Inagaki and Fujita, 2011). These bandpass-filtered images were created for the seven facial
expressions at two different sizes (99×99 and 198×198 pixels).

326
327
Figure 2. Test determining whether units are tuned for object- or retina-based spatial
frequencies (SFs). (A) Hypothetical tuning curves for object-based SFs of units ideally tuned to
retina-based SFs (left: peak shift = 1) or object-based SFs (right: peak shift = 0). (B) The models
were fed face images with two different sizes (198 × 198 and 99 × 99 pixels) and 64 different
bandpass filtering. These images were created by applying two-dimensional bandpass filters
that shared the same center object-based SF across different sizes. For each unit in FC1, we
obtained responses to images of different center SFs to create tuning curves for object-based
SFs.
336

To characterize the reference frame of SF tuning of each unit, the peak SFs for the two stimulus
sizes were estimated, defined by the SFs at which filtered face stimuli activated a unit most
strongly. For a given unit, 14 peak SFs were determined (two sizes × seven expressions). The
degree to which unit responses to SFs depended on the stimulus size was quantified by
calculating differences in peak SFs on a log scale between the two face sizes. A peak shift of 0
indicates that a unit respond to the same cycles/object regardless of the image size, and is
perfectly tuned to object-based SFs (Fig. 2A, right). A peak shift of 1 means that an SF tuning
curve shifts by the amount corresponding to the change in the stimulus size, indicating that a
unit is perfectly tuned to retina-based SFs (Fig. 2A, left). This analysis excluded cases in which
units did not respond to face images or were not sensitive to SFs, and cases in which peak SFs
were at either end of the tested range of SFs and the peak positions could not be determined.
348
Analysis of the effects of the max pooling operation on SF selectivity.
The max pooling operation collapses positional information of edges, which is detected by
convolution filters and is critical for encoding the SFs of facial images. We therefore examined
the effects of the max pooling on the SF selectivity of units. We were particularly interested in
the role of the max pooling in converting sensitivity to retina-based SFs to sensitivity to object-
based SFs. Bandpass-filtered images of the two stimulus sizes (198 × 198 and 99 × 99 pixels)
were fed to the models, and it was determined how different stimulus sizes affected the
responses of units to SFs in the first convolution layer (before pooling) and the first max pooling
layer (after pooling). Changes in response patterns across the units associated with different
stimulus sizes were quantified by calculating the dissimilarity index. The dissimilarity index D
(x, y) for responses x to the large stimuli and responses y to the small stimuli was defined by the
Euclidean distance between x and y as follows:
361
362　　$D(x, y) = \|x - y\|/(NM)$ 　　　　　　　　　　　　　　　　　　　　　　　　　(3)
363
where $\|\cdot\|$ is the Euclidean distance, and N is the number of elements of x and y. M is the
maximum value among the 6,405 Euclidean distances calculated for 61 center SFs and the seven
facial expressions of 15 individuals. To probe the roles of the max pooling, the ratio of the
dissimilarity index before pooling in the first convolution layer and after pooling in the first max
pooling layer was then calculated. This analysis was applied to the case of wide pooling (5 × 5)
and narrow pooling (3 × 3), as well as to the case of the SNNs and the Gabor models. By dividing
$\|x - y\|$ by M, the dissimilarity index was normalized across the layers (convolution vs. max
pooling) and the models (SNNs vs. Gabor models), taking values from 0 to 1.
372
373
374　**Results**
375
Performance of SNNs in facial expression classification.
The SNNs were trained to classify each face image in the training set into one of the seven facial
expressions. The training improved the classification performance rapidly over the initial
iterations and then slowly thereafter. The correct rate across the seven facial expressions rose
from the chance level (0.14), surpassed 0.6 around 50,000 iterations, further improved to around
0.8 over 150,000 iterations, and reached an asymptote (Fig. 3A for an example SNN; 3B for the

average of the 20 constructed SNNs; orange lines). The correct rate for the validation set
saturated at around 0.5, which was substantially lower than for the training set, indicating
insufficient generalization to "unseen" images. However, the validation correct rate reached a
plateau in a similar way to the training correct rate. This indicates that the low correct rate was
not the result of inadequate training, but represents the limited learning ability of the SNNs. It
also indicates that no overfitting occurred. The loss value also quickly decreased over the initial
50,000 iterations, and became gradually stable (Fig. 3A, B; cyan lines). The results indicate that
within the range of adopted iterations (240,000), the SNNs were trained to classify facial
expressions without overfitting.
391
The correct rates for the test set were higher than the chance level ($1 / 7 = 0.14$) for all facial
expressions, but were modest; the average correct rate across the seven expressions was 0.51
for the example SNN shown in Fig. 3A. The average correct rate across the 20 constructed SNNs
was 0.51 ($\pm$ 0.03, s.d.). This was not different from the average correct rate across 20 additional
SNNs that were trained with 3,000,000 iterations (0.50 ± 0.03; $p = 0.289$, t-test). The training
performance thus did not improve even when the SNNs underwent overly excessive training,
assuring that the modest correct rate was not due to insufficient training but instead reflected the
limited ability of the SNNs. Confusion matrices showed that the correct rates varied among the
facial expressions (Fig. 3A, B, right panels). Based on the averaged performance, the
classification performance of the SNNs was best for happy (0.74) and surprised faces (0.72),
followed by angry (0.50), disgusted (0.47), and fearful (0.44) faces, and was worst for sad (0.37)
and neutral (0.34) faces. Sad faces were often confused with neutral, angry, and fearful faces.
Neutral faces were often confused with sad and angry faces. This expression-dependent
performance was consistent across the 20 constructed SNNs (Fig. 3C; $p < 0.001$ for expressions,
$p = 0.562$ for models, two-way ANOVA).
407

Figure 3. Learning curves and confusion matrices of an example SNN (A) and the average of 20 SNNs with different initial weights (B). Left panels show changes in correct rates that occurred during training in the training set (orange) and the validation set (red), and loss values (cyan). Confusion matrices on the right indicate the rate of classification of each facial expression (true label) as one of the seven expressions (prediction label). (C) The correct rates for the seven expressions. Black line indicates the mean of the 20 SNNs, and lines with other colors indicate the individual performance of the 20 SNNs. The order of facial expression is based on the mean correct rate.

Effects of modification of SNNs on classification performance.
Replacement of one or more of the three subcortical properties, namely the shallowness of
processing stages, the DoG-type receptive fields at the initial stage, and spatial pooling over a
wider visual field, with the corresponding cortical properties improved the classification
accuracy (Fig. 4A; $p < 0.001$, ANOVA). The correct rates averaged across the seven expressions
and the 20 constructed models of each modification were increased from 0.51 in the SNNs to
0.55 in the narrow-pooling models, 0.64 in the Gabor models, and 0.69 in the add-layer models
($p < 0.01 / 28 = {}_8C_2$; t-test with Bonferroni correction). Among these models with one replaced
property, the add-layer models exhibited the best performance. The results indicate that all three
properties had effects on classification performance, and the layer structure was the most
influential.
430
When two properties were replaced together, the narrow-pooling + Gabor models and the
narrow-pooling + add-layer models performed better than the narrow-pooling models and the
Gabor models ($p < 0.01 / 28 = {}_8C_2$; t-test with Bonferroni correction), but comparably to the add-
layer models (correct rate, 0.69, $p = 0.778$ for the narrow-pooling + Gabor models; 0.69, $p =$
0.564 for the narrow-pooling + add-layer models). The Gabor + add-layer models performed
better than all one-property-replacement models (correct rate, 0.75; $p < 0.01 / 28 = {}_8C_2$). When
all three properties were replaced together (full-replacement models), the correct rate was 0.77,
which was better than all other models ($p < 0.01 / 28 = {}_8C_2$) except for the Gabor + add-layer
models ($p = 0.00846 > 0.01 / 28 = {}_8C_2$). The performance was improved for all facial expressions
(Fig. 4B; mean correct rates: happy = 0.92; surprised = 0.85; disgusted = 0.81; neutral = 0.78;
angry = 0.75; fearful = 0.66; sad = 0.65). As in the SNNs, it was highest for happy and surprised
faces, and lowest for fearful and sad faces. The performance was improved most for neutral
faces (SNNs, 0.37; full-replacement models, 0.78). The variance of the correct rates was affected
both by facial expressions and models (Fig. 4C; $p < 0.001$ for facial expressions, $p = 0.00285$
for models, two-way ANOVA). The improved performance of the two-property–replacement
and full-replacement models indicate that the effects of the three features on classification
performance were partially additive, suggesting that the three features exerted their effects
partially independently.
449

450
451
Figure 4. Effects on model performance of replacing subcortical properties with corresponding
cortical properties. (A) Discrimination performances of the SNNs and the modified models. The
discrimination performance differed across the models (ANOVA, $p < 0.001$). The pairs of
models with statistically significant differences in the performances are linked with horizontal
lines in the upper part (*t*-test, Bonferroni correction, $p < 0.01/ 28={_8}C_2$). (B) Confusion matrix
for the full-replacement models (average of the 20 constructed models). (C) The correct rate for
the seven expressions across the 20 full-replacement models. The black line indicates the mean,
and lines with other colors indicate the data for individual full-replacement models.
460

Spatial frequency representation in the FC1 layer.
As shown above, the SNNs exhibited modest performance in facial expression classification,
and this performance was improved by changing SNN subcortical properties to corresponding
cortical properties. These findings suggest that the SNNs captured aspects of processing in the
subcortical pathway to the extent that they explained the suboptimal perceptual performance of
V1-lesioned patients. We next looked into individual computational units to gain insights about
the processing in the models. We examined SF sensitivities of FC1 units using two different
sizes of input images (198×198 and 99×99 pixels). This procedure allowed us to determine
whether units were sensitive to retina- or object-based SFs (Fig. 2; see Materials and Methods).
470
FC1 units of the SNNs exhibited a variety of dependencies of SF tunings on stimulus size (Fig.
5A). Some units responded to the same range of object-based SFs for both large and small
stimuli, and the peak positions of the SF tuning curves remained unchanged (Fig. 5Aa, Ab).
Other units exhibited different preferred SFs for large and small stimuli, and in these cases the
peak position shifted horizontally along the abscissa (Fig. 5Ac–f). We quantified these shifts by
measuring the difference between preferred SFs on a log scale for the two stimulus sizes. A peak
shift of 0 means that the unit encoded SFs in the object-based coordinate, whereas a peak shift
of 1 means that the unit encoded SFs in the retina-based coordinate. The peak shifts of the
example units shown in Fig. 5A were 0.0 (a), 0.1 (b), 0.1 (c), 0.9 (d), 1.0 (e), and 1.3 (f).
480
We plotted the peak positions of 2,401 FC1 units of the 20 SNNs in a two-dimensional space
defined by the peak SF for the large stimuli on the abscissa, and the peak SF for the small stimuli
on the ordinate (Fig. 5B, left). Note that 46% of FC units were excluded from this analysis,
either because they were not sensitive to SFs (23%) or because the largest responses were found
at the end of the examined range of SFs and the peak SFs could not be determined (23%). The
diagonal solid line in Fig. 5B represents the responses of a peak shift of 0, and the dashed line
next to it represents the responses of a peak shift of 1. FC1 units of the SNNs were clustered in
multiple groups in this scatter plot. One conspicuous group was selective to low SFs and was
centered on the diagonal, i.e., peak shift values around 0. Another group was selective to higher
SFs, and was clustered on the dashed line indicative of peak shift values around 1. The
multimodality of the distribution can also be seen in the histogram (Fig. 5C, left). We applied
an excess mass test for multimodality (Ameijeiras-Alonso et al., 2019, 2021) to this distribution.
This test statistically determines the number of peaks in the distribution, with the null hypothesis
that the true number of peaks is N ($N = 1, 2, 3, ...$). The true number of peaks is estimated as the
smallest N under which the null hypothesis is not rejected. The excess mass test also estimates
the locations and heights of peaks from Gaussian kernel density estimation. The test revealed
that there were three peaks in the distribution of the SNNs (first p-value < 0.001, second p-value
< 0.001, third p-value $= 0.096$). Based on the probability density function derived from the
histogram (Ameijeiras-Alonso et al., 2021), the peaks were estimated to be located at -4.85,
0.144, and 0.909 (open and solid arrowheads in Fig. 5C, left). Units sensitive to low SFs below
2 cycles/object were most frequent around a peak shift of 1 (gray columns). Comparing this
result and the density map, the peak around 0 was mostly from the low spatial frequency group
and the peak around 1 was from the high spatial frequency group. Although the third peak at the
far periphery (at -4.85, open arrowhead) was statistically detected, it was much smaller in height
than the other two peaks (1.1% of the peaks near 0 and 1). The results indicate that FC1
contained two major groups of units, those sensitive to low SFs, encoding SFs in the object-
based coordinate, and those sensitive to high SFs, encoding SFs in the retina-based coordinate.

509
510

Figure 5. SF tuning reference frames of FC1 units of the SNNs and full-replacement models. Responses of FC1 units to SF-filtered face images were examined at two different sizes (198 × 198, 99 × 99 pixels). (A) Six example FC1 units of SNNs with a different peak shift (PS). (B) Two-dimensional histograms of peak SFs at large images versus small images for the SNNs (left) and the full-replacement models (right). Solid lines indicate peak shifts of 0, and dashed lines indicate peak shifts of 1. (C) Distribution of peak shifts of units in the 20 SNNs (left) and the 20 full-replacement models (right). Arrowheads indicate the estimated locations of multiple peaks in the distribution (solid: major peaks, open: statistically detected but less obvious peaks). Gray columns indicate units with a response peak at SFs below 2 cycles/object for large and/or small stimuli.

The distribution of peak shift values was drastically altered in the full-replacement models. In the two-dimensional plot shown in Fig. 5B (right), most data points were diffusely distributed in an elongated area between the diagonal and dashed lines, indicating that the SF reference frame of most units was intermediate between retina-based and object-based. An excess mass test again detected three peaks located at −4.84, 0.436, and 4.98 (Fig. 5C right, solid and open arrowheads; first p-value < 0.001, second p-value < 0.001, third p-value = 0.096). The second and third peaks at −4.84 and 4.98 (open arrowheads) were smaller than the primary peak at 0.436 (3.1% and 2.6% of the primary peak, respectively), making the distribution nearly unimodal.

Given the change of the peak shift distribution in the full-replacement models, we next analyzed one- and two-property replacement models to determine which subcortical properties were essential for the multimodal distribution of the SNNs. All these modified models exhibited unimodal distributions of the major peak (solid arrowheads) at different peak positions (Fig. 6). An excess mass test for multimodality detected two other less obvious peaks (open arrowheads) in each model as in the cases of the SNNs and the full-replacement models (Fig. 5C). The heights of these smaller peaks were 2.6–26 % of those of the major peaks, and were located at the periphery of the distribution.

Each of the three one-property–replacement models showed a characteristic distribution of the peak shift values. The narrow pooling models contained units with peak shift values between 0 and 1 in addition to units with peak shift values around either 0 or 1. The distribution became unimodal and broad, and was estimated to be centered at 0.85. In the Gabor models, units with peak shift values intermediate between 0 and 1 were the most abundant with a smaller number of units of peak shift values around 0 and 1. The distribution peak was estimated at 0.51. In the add-layer models, units with peak shift values around 0 were predominant, and exhibited a sharp distribution peak at 0.32. As to the two-property–replacement models, the narrow-pooling + Gabor models and the Gabor + add-layer models showed a broad distribution straddling the peak values from 0 to 1 (peak for the former, 0.56; peak for the latter, 0.52), whereas the narrow-pooling + add-layer models showed a sharp distribution peak at 0.20. As in the SNNs and the full-replacement models, units sensitive to low SFs (below 2 cycles/object) were most frequently found around the peak shift of 0 in all of the one- and two-property replacement models (gray columns). The results indicate that all of the three computational properties were responsible for the multimodal distribution of peak shift values observed in the SNNs. In particular, the smaller number of units with peak shift values around 1 in the Gabor models and the add-layer models suggests that the shallowness and the DoG-type filters were critical for preserving the unit sensitivities to retina-based SFs. The broad distribution observed for the narrow-pooling models and the narrow-pooling + Gabor models suggests that the wide pooling employed in the SNNs contributed to the two peaks at 0 and 1, by reducing units with peak shift values intermediate between 0 and 1.

562
563
Figure 6. Distributions of peak shifts of FC1 units of the SNNs and one-property or two-
property–replacement models. (A) Data from narrow-pooling model, add-layer model, and
Gabor model. (B) Data from models with two modifications: narrow-pooling + Gabor, Gabor +
add-layer, narrow-pooling + add-layer. Gray columns indicate units with a response peak at SFs
below two cycles/object for large or small stimuli. Arrowheads indicate the estimated locations
of multiple peaks in the distribution (solid: major peaks, open: statistically detected but small
peaks). Gray columns indicate units with a response peak at SFs below 2 cycles/object for large
and/or small stimuli.
572

Effects of max pooling on SF tuning.
We showed above that FC1 units of the SNNs were roughly grouped into two populations in
terms of the reference frame of SF encoding. Because the max pooling yields the same output
from a population of convolution layer units in response to slightly different spatial arrangement
of local features, the max pooling operation is likely to affect the encoding of global
configuration of face components. This information of global configuration will be reflected in
a low range of SFs. Therefore, we next compared the effect of max pooling on the representation
of SFs across different SF ranges.
581
We first analyzed the responses of the 96,800 units (32 filters × 55 × 55 resolution) in the first
convolution layer. We obtained the response patterns across these units by feeding bandpass-
filtered faces of two sizes (198 × 198 and 99 × 99 pixels; Fig. 2B) to the models, and quantified
the difference between the SF tunings obtained for the two stimulus sizes by calculating the
dissimilarity index (see Materials and Methods). In the SNNs with DoG filters, the dissimilarity
index was high (around 0.6) for a low SF range up to approximately four cycles/object, but
gradually decreased over a higher range of SFs (Fig. 7A, black curve). In the pooling layer, the
dissimilarity index of the 6,272 units (32 filters × 14 × 14 resolution) became lower for a low
SF range of less than four cycles/object than that of the convolution layer. For a high SF range
of greater than four cycles/object, by contrast, it became higher than that of the convolution
layer (Fig. 7A, compare the orange and cyan curves with the black curve). Thus, max pooling
resulted in the SF tuning becoming similar between the two stimulus sizes for a low SF range,
consistent with the results of peak shift analysis (Fig. 5C). Although these changes were
observed both for wide pooling (5 × 5) and narrow pooling (3 × 3), the effects were larger for
the former than for the latter (Fig. 7A, compare the orange curve with the cyan curve). This was
more evident when we plotted the ratio of dissimilarity indices between before and after pooling
(Fig. 7B). Furthermore, the ratio curve for wide pooling had smaller standard deviations than
that for narrow pooling (shown as shades in Fig. 7B), indicating that wide pooling exerted its
effects more consistently across the 15 individual faces and the seven facial expressions than
narrow pooling.
602
By contrast, the convolution-layer units of the Gabor models exhibited a constantly high
dissimilarity index over most of the SF range (Fig. 7C, black). However, when we applied max
pooling with windows of either 5 × 5 or 3 × 3 in size, the dissimilarity index became small over
almost the entire SF range, with the largest decrease for 1–16 cycles/object (Fig. 7C; compare
the orange and blue curves with the black curve). As in the case of the SNNs, the effect was
stronger for wide pooling than for narrow pooling (Fig. 7D). These results demonstrated that
max pooling rendered the SF tuning more invariant to stimulus size for units sensitive to low
SFs, enabling them to represent SFs in the object-based coordinate. Regardless of the filter type
in the first convolution layer (i.e., DoG vs. Gabor), wide pooling was more effective than narrow
pooling in creating this response property.
613

Figure 7. Effects of max pooling on the size-invariant responses to SFs. (A) Dissimilarity index curves of responses of units in the first convolution layer of the SNNs before max pooling operation (black), after wide pooling (blue), and after narrow pooling (orange). Dissimilarity indices, defined by the Euclidean distances of unit responses between different stimulus sizes (see Method and Methods), are plotted against the center SFs of input images. Solid lines indicate the means of dissimilarity indices across the seven facial expressions. Shades indicate standard deviations. Each dissimilarity index was normalized by the number of units and the maximum values. (B) Dissimilarity ratios of inputs and outputs of the max pooling operation (upper, after wide pooling; lower, after narrow pooling). (C, D) Data from units in the first convolution layer of the Gabor models. The conventions are the same as in A and B.

Effects of alternation of sliding strides on SF tuning.
Finally, we examined the effect of another free parameter of our models, the stride size, on the
SF sensitivity of FC1 units. We changed the stride of the two max pooling layers of the SNNs
from 4 to 2. The stride size of 2 was also employed in the narrow-pooling model. This modified
model with a smaller stride of 2 achieved a mean correct rate of 0.54, which was better than the
SNNs (0.51) but similar to the narrow pooling models (0.55) (vs. SNN, $p = 0.0020$; vs. the
narrow pooling, $p = 0.23$; t-test with Bonferroni correction).
634
An analysis of FC1 responses to two stimulus sizes (198×198 and 99×99 pixels) revealed that
the distribution of the peak shift had three peaks, at −4.17, −0.0107, and 0.976 (first p-value <
0.001, second p-value < 0.001, third p-value = 0.098; excess mass test for multimodality; solid
and open arrowheads in Fig. 8). Two of them were conspicuous and located near 0 or 1 (solid
arrowheads), and the third one at the periphery of −4.17 (open arrowhead) was small (3.2% and
3.3% of the two major peaks). Comparisons with Fig. 5B, C show that the small-stride model
exhibited a similar SF representation as in the SNNs, in that there were two main groups of units,
one sensitive to low SFs, representing SFs in the object-based coordinate (peak shift around 0),
and the other sensitive to high SFs, representing SFs in the retina-based coordinate (peak shift
around 1). The change of the stride from 4 to 2 had little effects on the reference frame of SF
sensitivity of FC1 units.
646
647

Figure 8. Effects of alternation of sliding strides of pooling windows on SF tuning reference frames of FC1 units of the SNNs. Responses of FC1 units were obtained in the same way as in Fig. 5. (A) A two-dimensional histogram of peak SFs obtained with large (198 × 198) versus small (99 × 99) stimulus images. (B) Distribution of peak shifts of units. Arrowheads indicate the estimated locations of multiple peaks in the distribution.

Discussion

We analyzed the ability of the SNNs and modified models to classify facial expressions, with the goal of determining what architectural or physiological properties underlie the modest performance of facial expression discrimination supported by the primate subcortical pathway. The SNNs were implemented with the three prominent subcortical properties, i.e., shallow processing, DoG-type filters at the first processing stage, and spatial pooling over wide areas (Fig. 1). The SNNs classified the seven basic facial expressions with modest performance (Fig. 3). Replacement of any one of these properties with the corresponding cortical properties resulted in higher performances (Fig. 4). Replacement of a combination of two or three properties further improved classification performances in a partially additive manner (Fig. 4). These results suggest that all three subcortical properties of the SNNs underlie the modest performance. A major group of units in the final processing layer (FC1) of the SNNs was sensitive to SFs defined in the retina-based coordinate, whereas another group responding to low SFs encoded SFs in the object-based coordinate (Fig. 5). The number of retina-based units was reduced in most of the modified models, suggesting that the three features are also important for preserving retina-based SF information (Figs. 5, 6). Max pooling over the wide window employed in the SNNs contributed to object-based SF representation of units sensitive to low SFs (Fig. 7). These findings advance our understanding of the computational processes utilized by the subcortical pathway in facial expression recognition.

Modest performance of the SNNs and neural computations of the subcortical pathway.

Based on psychological assessment and brain imaging in V1-lesioned patients, it has been proposed that affective blindsight is mediated by components of the subcortical pathway spared by the lesions, including the superior colliculus, pulvinar, and amygdala (de Gelder et al.,1999; Pegna et al., 2005; Striemer et al., 2019). One view assumes that the shortest route directly connecting the three subcortical structures conveys facial expression information from the superior colliculus via the pulvinar to the amygdala (Tamietto and de Gelder, 2010). A different view proposes that information from the pulvinar reaches the amygdala through the facial processing system in the temporal cortex, under an assumption that "the direct connections of the pulvinar with the amygdala are likely insufficient in themselves for recognizing emotional expressions" (Gerbella et al., 2019). The present study demonstrates that the SNNs with only three processing stages and the subcortical physiological properties can successfully acquire an ability to discriminate facial expressions.

The average correct rate of classifying the seven facial expressions in the present study was 0.51. This rate was well above chance ($1/7 = 0.14$), but was far from perfect. The modest correct rate is in line with the performance of patients with affective blindsight. Pegna et al. (2005) reported that a patient with bilateral lesions in V1 discriminated happy faces from either angry, sad, or horrified faces at correct rates of 0.58–0.62, marginally above the chance level of 0.5. Another patient with bilateral lesions in V1 exhibited correct rates of 0.64–0.67 for happy vs. fearful or angry faces (chance level = 0.5; Striemer et al. 2019). The residual ability of facial expression classification in these patients was only moderate compared to the nearly perfect performance

in healthy people. This raises the question of why subcortical processing supports vision more
poorly than visual functions mediated by the cortical pathway.

A traditional explanation is that neurons in the subcortical pathway respond to low SFs and are
less sensitive to high SFs than the cortical pathway (e.g., Vuilleumier et al., 2003; Méndez-
Bértolo et al., 2016; Burra et al., 2019). This will limit the ability of the subcortical pathway to
analyze the fine details of visual images, and can itself result in the inaccurate processing of face
images. However, the dependence of the subcortical response on low SFs has been disputed by
other researchers (De Cesarei and Codispoti, 2013; McFadyen et al., 2017). Our results suggest
that low SF sensitivity, if important, was not the only cause, because the DoG filter models
combined with narrow-pooling or add-layer modifications exhibited improved performances,
despite the fact that our DoG filters were tuned to low SFs, and had full width at half maximum
of 0.067–1.0 cycles/degree. Note that we estimated this value on an assumption of the image
size of 30.5° based on our DoG parameters, the filter resolution, and the RF size of superior
colliculus neurons representing the foveal region. The range of DoG-filter width corresponds to
that applied in models of the superior colliculus in a recent simulation study (Méndez et al.,
2022).

Another explanation is that the small number of processing stages in the cortical pathway
hampers detailed analysis of visual inputs. However, a previous study (Dailey et al., 2002)
showed that CNNs that had only two processing layers, with Gabor filters at the first stage,
performed highly accurate discrimination of facial expressions (the mean correct rate for
classifying six facial expressions was 0.90). The performance of our SNNs incorporating the
three subcortical properties was not this high. This was not due to inadequate training, because
the performance reached a plateau and stayed stable over a large number of iterations in the
training sessions (Fig. 3). This was further verified by showing that the correct performance for
the test set remained unchanged even after overly excessive training with 3,000,000 iterations.
Furthermore, replacing not only the small number of processing layers but also the filter type at
the first processing layer and the width of the pooling window with the corresponding cortical
properties improved the performance of the SNNs (Fig. 4). The three properties at least partially
underlie the less accurate processing of facial images in the subcortical pathway, and hence,
may be responsible for the low performance in affective blindsight.

Confusions of facial expressions in the SNNs, DNNs and patients.

The classification accuracy of the SNNs varied across facial expressions (Fig. 3A, B). The
classification performance of the SNNs was best for happy and surprised faces and worst for
sad and neutral faces. The rank order of performance on the seven facial expressions was largely
consistent across the 20 SNNs trained independently from random states (Fig. 3C). It also
corresponds to the classification performance by previously developed AlexNet-based DNNs
(Inagaki et al., 2022b). These DNNs were trained to discriminate between the seven expressions
derived either from the KDEF database or the Kokoro Research Center (KRC) facial expression
database (Ueda et al., 2019). Like the SNNs, the DNNs exhibited the best performance for happy
and surprised faces (KDEF: 0.93 for happy, 0.84 for surprised; KRC: 0.91 for happy, 0.84 for
surprised; chance level, 0.14). This coincidence may simply suggest that within each database,

facial features are consistent across faces with happy or surprised expressions, but are more
diverse across faces with sad or neutral expressions. However, the variations across examples
of facial expressions within a database are not the sole reason for the difference in the
performance across facial expressions, because neutral faces were classified poorly by the SNNs
(Fig. 3B; correct rate = 0.34), but the DNNs of Inagaki et al. (2022b) classified them with high
correct rates (0.85 for KDEF, 0.82 for KRC). An alternative, yet-to-be-tested explanation is that
the ease (or difficulty) of classification may vary across the facial expressions owing to
differences in the conspicuousness of component facial actions underlying various expressions.
Similarities between neural networks regarding expression-specific performance may vary
according to these differences.
757
The relatively poor ability to distinguish between sad and neutral faces was also observed in
another CNN with the first layer of DoG filtering and average pooling (Méndez et al., 2022).
This CNN was constructed to simulate facial processing in the superior colliculus, and was
trained to discriminate three facial expressions: happy, sad, and neutral. The CNN showed the
best performance for happy faces and moderate performance for sad faces, but classified neutral
faces into neutral faces with a classification rate of 0.49 and into sad faces with a rate of 0.39.
The fact that this CNN and the SNNs in the present study demonstrated this confusion, whereas
AlexNet-based DNNs and our add-layer models (0.52 for sad, 0.67 for neutral) did not, suggests
that the convolution processes after the initial DoG filtering (in the case of add-layer models) or
the convolution by the Gabor filters (in the case of AlexNet-based DNNs) may be critical for
classification of sad and neutral faces.
769
770 Finally, we point out that the expression-dependent performance of the SNNs also had both
771 similarities and dissimilarities to that observed in a V1-lesioned patient. The patient reported by
772 de Gelder et al. (1999) classified happy and sad faces with a higher correct rate than angry and
773 fearful faces; our SNNs and this patient classified happy faces well, whereas the performance
774 for sad faces was poor in the SNNs but good in the patient.
775
776 ***Reference frame of coding SF information and invariance of visual responses.***
777
FC1 units of the SNNs consisted of two major groups, each with different properties regarding
SF processing (Fig. 5). One group of units responded best to the same object-based SFs
(cycles/object) regardless of the stimulus size (peak shift around 0). This size-invariant response
indicates that these units represent SFs in the object-based coordinate. Most of these units were
tuned to a low SF range (around one to two cycles/object). In the other group of units, the
optimal object-based SFs shifted when testing was performed with different stimulus sizes. The
direction of the shift was consistent with the interpretation that the units were tuned to retina-
based SFs (cycles/degree) (peak shift around 1). That is, for larger stimuli, the units responded
to higher object-based SFs that corresponded to the same retina-based SFs. The DoG filters at
the initial stage and the shallow architecture appear to be critical for preserving the SF
representation based on the retina-based coordinate, because FC1 units with retina-based SF
sensitivity were reduced in number when the first convolution layer were changed to Gabor
filters or when the number of processing layers was increased (Fig. 6A, middle, bottom).
791

A major group of the object-based SF units in the SNNs were tuned to low SFs (Fig. 5B). This
curious bias of the object-based units towards low SF sensitivity likely resulted from the wide
max pooling process. Lowpass-filtered facial images contain only coarse structure such as solid
blobs at eye or mouth positions. Positional information of these blobs is initially detected by
DoG filters, and is encoded as response patterns across units in the convolution layer. These
blobs appear in different positions and scales for images of different sizes, and thus the response
patterns vary between different sizes. After the max pooling operation, however, response
patterns would become more similar between different sizes, because this operation renders
units in the pooling layer insensitive to slight changes in spatial arrangement of local features.
Indeed, the dissimilarity index for lowpass-filtered images decreased after max pooling in our
data (Fig. 7). This effect might result in object-based SF tuning (i.e., preferential responses
invariant of image size to a particular range of object-based SFs) for lowpass-filtered images.
Wider pooling window would enhance this effect at the expense of losing fine details of inputs.
When the pooling window is narrower, this effect would be incomplete, and units with
intermediate peak shift values would increase, as we found in the narrow-pooling models (Fig.
6A, top).
808
One may wonder why FC1 units of the SNNs maintained sensitivity to retina-based SFs, i.e.,
size-dependent representation of SFs, despite the demand that we imposed on the SNNs to
classify facial expressions regardless of the seven different face image sizes. One possibility is
that the architecture of our SNNs cannot achieve sufficient object-based representation, and
remains suboptimal for the required task even after the excessive training sessions. This may be
a reason for the modest classification performance of the SNNs. Indeed, replacement of the
subcortical processing properties with the cortical properties resulted in the representation
becoming more object-based (Fig. 5B, C, Fig. 6) and improved the classification performance
(Fig. 4). However, if object-based SF encoding was the only requirement for optimal
performance under our training conditions, the models that showed object-based SF encoding
should have had the highest correct rate, but this was not the case. The add-layer models and the
narrow-pooling + add-layer models exhibited the best object-based encoding of SFs (Fig. 6A
bottom, 6B bottom), while they performed worse than the full-replacement model (Fig. 4A).
The representation acquired for the classification depended not only on the task demand of size-
invariant classification of facial expressions, but also on other, yet unspecified, constraints
deriving probably from the architecture of the models.
825
In the primate amygdala, the responses of many neurons are affected by retina-based SFs, and
only a minority of neurons have perfect object-based SF sensitivity (Inagaki and Fujita, 2011).
By contrast, many FC1 units tuned to low SFs of the SNNs exhibited object-based SF sensitivity.
The paucity of evidence for units with object-based SF sensitivity in the amygdala may be
related to the fact that the previous electrophysiological study (Inagaki and Fujita, 2011) did not
present face images with very low SFs, and may have overlooked the neurons with object-based
SF sensitivity in this range of SFs.
833
Some inferior temporal cortex neurons exhibit invariant responses to changes in shape sizes
(Rolls and Baylis, 1986; Ito et al., 1995). The max pooling operation may help achieve these
invariant responses. To some degree, max pooling ignores positional changes of inputs in each
region of interest. Because size changes involve alternations in edge positions without

modifications in topologies, if the changes are small enough to be covered by each region of
interest, stimuli before and after the changes would yield similar responses. The effects of wide
pooling shown in Figure 7 suggest that some aspects of the invariant responses of inferior
temporal cortex neurons can simply be achieved by bypassing early cortical areas with high
spatial resolutions such as V1. Such shortcut routes indeed exist, including the projection from
the pulvinar to V2 and then to the posterior inferior temporal cortex and the projection from the
pulvinar to V4 and then to the anterior inferior temporal cortex (Pessoa and Adolphs, 2010).
845
The size invariance in low SFs is important in newborns. They have blurred visions that relies
on low SFs (Atkinson et al., 1974; Dobson & Teller, 1978), but respond to faces or face-like
patterns irrespective of the stimulus size or the viewing distance (Cassia et al., 2001; De Heering
et al., 2008). These findings indicate that the ability of size-invariant face recognition based on
low SFs is innately implemented in our visual system. Convergence of inputs from the
superficial layer of the superior colliculus to the deep layer, which is already present in newborns
(Wallace et al., 1997), may be part of the neural substrate supporting this aspect of size-invariant
face recognition.
854
855 ***Concluding remarks***
856
The present study provides the first computational model for facial expression processing along
the subcortical pathway (see Méndez et al., 2022 for a model of face processing in the superior
colliculus). Despite the celebrated success of DNNs in modeling visual processing in the ventral
cortical pathway, it has remained unclear whether and how the CNN architecture can be adapted
to processing in the subcortical pathway. We demonstrated that the SNNs implemented with the
three computational properties of the subcortical pathway, i.e., a shallow layer architecture,
concentric receptive fields at the first processing stage, and a greater degree of spatial pooling,
were successfully trained to discriminate facial expressions with a modest correct rate. The three
properties were all essential for reproducing the modest performance seen in V1-lesioned
patients, as well as the representation of SFs in the retina-based coordinate observed in a
population of amygdala neurons. Research interest in the role of subcortical structures in
cognitive functions has recently surged, but physiological data are still much sparser for
subcortical structures than for the cerebral cortex (Janacsek et al., 2022). Computational
approaches such as the one we present here are expected to partially compensate for this data
scarcity and to guide future research.

References

Ameijeiras-Alonso, J., Crujeiras, R.M. and Rodríguez-Casal, A. Mode testing, critical bandwidth and excess mass. *TEST*, **28**, .900-919 (2019). doi: 10.1007/s11749-018-0611-5

Ameijeiras-Alonso, J., Crujeiras, R.M. and Rodríguez-Casal, A. Multimode: An R package for mode assessment. *J. Stat. Softw.* **97**, Issue 9 (2021). doi: 10.18637/jss.v097.i09

Atkinson, J., Braddick, O. & Braddick, F. Acuity and contrast sensitivity of infant vision. *Nature* **247**, 403-404 (1974). doi: 10.1038/247403a0

Bender, D.B. Retinotopic organization of macaque pulvinar. *J. Neurophysiol.* **46**, 672-693 (1981). doi: 10.1152/jn.1981.46.3.672

Bradski, G. The OpenCV Library. *Dr. Dobb's Journal of Software Tools* (2000). https://opencv.org/ (version, 2.4.8; this version is no longer available)

Buiatti, M., Di Giorgio, E., Piazza, M., Polloni, C., Menna, G., Taddei, F,, Baldo, E. & Vallortigara, G. Cortical route for facelike pattern processing in human newborns. *Proc. Natl. Acad. Sci. U.S.A.* **116**, 4625–4630 (2019). doi: 0.1073/pnas.181241911

Burra, N., Hervais-Adelman, A., Celeghin, A., De Gelder, B. & Pegna, A.J. Affective blindsight relies on low spatial frequencies. *Neuropsychol.* **128**, 44-49 (2019). doi: 10.1016/j.neuropsychologia.2017.10.009

Cassia, V.M, Simion, F. & Umiltaà, C. Face preference at birth: the role of an orienting mechanism. *Develop. Sci.* **4**, 101-108 (2001). doi: 10.1111/1467-7687.00154

Chen, C-Y., Hoffmann, K.-P., Distler, C., & Hafed, Z. M. The foveal visual representation of the primate superior colliculus. *Curr. Biol.* **29**, 2109-2119 (2019). doi: 10.1016/j.cub.2019.05.040

Chen, C-Y., Sonnenberg, L., Weller, S., Witschel, T. & Hafed, Z.M. Spatial frequency sensitivity in macaque midbrain. *Nat. Comm.*, **9**, pp.1-13 (2018). doi: 10.1038/s41467-018-05302-5

Churan, J., Guitton, D. & Pack, C.C. Spatiotemporal structure of visual receptive fields in macaque superior colliculus. *J. Neurophysiol.* **108**, 2653-2667 (2012). doi: 10.1152/jn.00389.2012

Connor, C.E., Brincat, S.L. & Pasupathy, A. Transformation of shape information in the ventral pathway. *Curr. Opin. Neurobiol.* **17**, 140-147 (2007). doi: 10.1016/j.conb.2007.03.002

Conway, B.R., Chatterjee, S., Field, G.D., Horwitz, G.D., Johnson, E.N., Koida, K. & Manscuso,
K. Advances in color science: from retina to behavior. *J. Neurosci.* **30**, 14955-14963 (2010).
doi: 10.1523/JNEUROSCI.4348-10.2010

Cynader, M. & Berman, N. Receptive-field organization of monkey superior colliculus. *J.*
Neurophysiol. **35**, 187-201 (1972). doi: 10.1152/jn.1972.35.2.187

Dailey, N.M., Cottrell, W.G., Padgett, C. & Adolphs, R. EMPATH: A neural network that
categorizes facial expressions. *J. Cogni. Neurosci.* **14**, 1158-1173 (2002).
doi: 10.1162/089892902760807177

De Cesarei, A. & Codispoti, M. Spatial frequencies and emotional perception. Rev. Neurosci.
24, 89-104 (2013). doi: 10.1515/revneuro-2012-0053

de Gelder, B., Vroomen, J., Pourtois, G. & Weiskrantz, L. Non-conscious recognition of affect
in the absence of striate cortex. *NeuroRep.* **10**, 3759-3763 (1999).
doi: 10.1097/00001756-199912160-00007
917
918 De Heering, A., Turati, C., Rossion, B., Bulf, H., Goffaux, V. & Simion, F. Newborns' face
919   recognition is based on spatial frequencies below 0.5 cycles per degree. Cognition, 106(1),
920   pp.444-454 (2008). doi: 10.1016/j.cognition.2006.12.012
921
922 Desimone, R., Albright, T.D., Gross, C.G. & Bruce, C. Stimulus-selective properties of inferior
923   temporal neurons in the macaque. *J. Neurosci.* **4**, 2051-2062 (1984).
924   doi: 10.1523/JNEUROSCI.04-08-02051.1984
925
Dobson, V. & Teller, D.Y. Visual acuity in human infants: a review and comparison of
behavioral and electrophysiological studies. *Vis. Res.* **18**, 1469-1483 (1978).
doi: 10.1016/0042-6989(78)90001-9

Duchaine, B. & Yovel, G. A revised neural framework for face processing. *Annu. Rev. Vis. Sci.*
1, 393-416 (2015). doi: 10.1146/annurev-vision-082114-035518

Freeman, J. & Simoncelli, E.P. Metamers of the ventral stream. *Nat. Neurosci.* **14**, 1195-1201
(2011). doi: 10.1038/nn.2889

Freiwald, W., Duchaine, B. & Yovel, G. Face processing systems: from neurons to real-world
social perception. *Annu. Rev. Neurosci.* **39**, 325-346 (2016).
doi: 10.1146/annurev-neuro-070815-013934
936
Fujita, I., Tanaka, K., Ito, M. & Cheng, K. Columns for visual features of objects in monkey
inferotemporal cortex. Nature 360, 343-346 (1992).
doi: 10.1038/360343a0

Gerbella, M., Caruana, F. & Rizzolatti, G. Pathways for smiling, disgust and fear recognition in
blindsight patients. *Neuropsychol.* **128**, 6-13 (2019).
doi: 10.1016/j.neuropsychologia.2017.08.028

Goldberg, M. E. & Wurtz, R. H. Activity of superior colliculus in behaving monkey. I. Visual
receptive fields of single neurons. *J. Neurophysiol.* **35**, 542–559 (1972).
doi: 10.1152/jn.1972.35.4.542

Goodfellow, I., Bengio, Y. & Courville, A. *Deep Learning.* Cambridge: MIT Press, pp. 71–73
(2016). http://www.deeplearningbook.org (doi is not available)

Güçlü, U. & van Gerven, M.A.J. Deep neural networks reveal a gradient in the complexity of
neural representations across the ventral stream. *J. Neurosci.* **35**, 10005-10014 (2015).
doi.org/10.1523/JNEUROSCI.5023-14.2015

Hassabis, D., Kumaran, D., Summerfield, C. & Botvinick, M. Neuroscience-inspired artificial
intelligence. *Neuron.* **95**, 245-258 (2017). doi: 10.1016/j.neuron.2017.06.011

Haxby, J.V, Hoffman, E.A. & Gobbini, M.I. The distributed human neural system for face
perception. *Trends Neurosci.* **4**, 223-233 (2000). doi: 10.1016/s1364-6613(00)01482-0

He, K., Zhang, X., Ren, S. and Sun, J. Delving deep into rectifiers: Surpassing human-level
performance on ImageNet classification. *Proc. IEEE Int. Conf. Comput. Vis. pp.* 1026-1034
(2015). doi: 10.1109/ICCV.2015.123

He, K., Zhang, X., Ren, S. & Sun, J. Deep residual learning for image recognition. *Proc. IEEE
Comput. Soc. Conf. Comput. Vis. Pattern Recognit.* 770-778 (2016).
doi: 10.1109/CVPR.2016.90

Inagaki, M. & Fujita, I. Reference frames for spatial frequency in face representation differ in
the temporal visual cortex and amygdala. *J. Neurosci.* **31**, 10371-1039 (2011).
doi: 10.1523/JNEUROSCI.1114-11.2011

Inagaki, M., Inoue, K.-I., Tanabe, S., Kimura, K., Takada, M. & Fujita, I. Rapid processing of
threatening faces in the amygdala of nonhuman primates: subcortical inputs and dual roles.
Cereb. Cortex. 10.1093/cercor/bhac109 (2022a). doi: 10.1093/cercor/bhac109

Inagaki, M., Ito, T., Shinozaki, T. & Fujita, I. Convolutional neural networks reveal differences
in action units of facial expressions between face image databases developed in different
countries. *Front. Psychol.* doi: 10.3389/fpsyg.2022.988302 (2022b).

Ito, M., Tamura, H., Fujita, I. & Tanaka, K. Size and position invariance of neuronal responses
in monkey inferotemporal cortex. *J. Neurophysiol.* **73**, 218-226 (1995).
doi: 10.1152/jn.1995.73.1.218

Janacsek, K., Evans, T.M., Kiss, M. Shah, L., Blumenfeld, H. & Ullman, M.T. Subcortical
cognition: the fruit below the rind. *Annu. Rev. Neurosci.* **45**, 361-386 (2022).
doi: 10.1146/annurev-neuro-110920-013544

Johnson, M.H. Subcortical face processing. *Nat. Rev. Neurosci.* **6**, 766-774 (2005).
doi: 10.1038/nrn1766

Jones, J.P. & Palmer, L.A. An evaluation of the two-dimensional Gabor filter model of simple
receptive fields in cat striate cortex. *J. Neurophysiol.* 58, 1233–1258 (1987).
doi: 10.1152/jn.1987.58.6.1233

Komatsu, H. & Goda, N. Neural mechanisms of material perception: Quest on Shitsukan.
Neurosci. **392**, 329-347 (2018). doi: 10.1016/j.neuroscience.2018.09.001

Kravitz, D.J., Saleem, K.S., Baker, C.I., Ungerleider, L.G. & Mishkin, M. The ventral visual
pathway: an expanded neural framework for the processing of object quality. *Trends Cogn.*
Sci. **17**, 26-49 (2013). doi: 10.1016/j.tics.2012.10.011

Krizhevsky, A., Sutskever, I. & Hinton, G.E. ImageNet classification with deep convolutional
neural networks. *Adv. Neural Inf. Proces. Syst (NeurIPS).* **25**, 1097-1105 (2012).
https://proceedings.neurips.cc/paper/2012/file/c399862d3b9d6b76c8436e924a68c45b-
Paper.pdf (doi is not available)

Langner, O., Dotsch, R., Bijlstra, G., Wigboldus, D.H., Hawk, S.T. & Van Knippenberg, A.D.
Presentation and validation of the Radboud Faces Database. *Cogni. Emot.* **24**, 1377-1388
(2010). doi: 10.1080/02699930903485076

LeCun, Y., Bengio, Y. & Hinton, G. Deep learning. *Nature.* **521**, 436-444 (2015).
doi: 10.1038/nature14539

Lundqvist, D., Flykt, A. & Öhman, A. The Karolinska Directed Emotional Faces - KDEF.
Stockholm: Department of Clinical Neuroscience, Psychology section, Karolinska Institute.
CD-ROM (1998).

Marino, R.A., Rodgers, C.K., Levy, R. & Munoz, D.P. Spatial relationships of visuomotor
transformations in the superior colliculus map. *J. Neurophysiol.* **100**, 2564-2576 (2008).
doi: 10.1152/jn.90688.2008

Méndez, C.A., Celeghin, A., Diano, M., Orsenigo, D., Ocak, B. & Tamietto, M. A deep neural
network model of the primate superior colliculus for emotion recognition. *Phil. Trans. R.*
Soc. B **377**, 20210512 (2022). doi: 10.1098/rstb.2021.0512

Méndez-Bértolo, C., Moratti, S., Toledano, R., Lopez-Sosa, F., Martinez-Alvarez, R., Mah,
Y.H., Vuilleumier, P., Gil-Nagel, A. & Strange, B.A. A fast pathway for fear in human
amygdala. *Nat. Neurosci.,* **19**, 1041-1049 (2016). doi: 10.1038/nn.4324

Morawetz, C., Baudewig, J., Treue, S. & Dechent, P. Diverting attention suppresses human
amygdala responses to faces. *Front. Human Neurosci.* **4**, 226 (2010).
doi: 10.3389/fnhum.2010.00226

Morris, J.S., DeGelder, B., Weiskrantz, L. & Dolan, R.J. Differential extrageniculostriate and
amygdala responses to presentation of emotional faces in a cortically blind field. *Brain.*
126, 1241-1252 (2001). doi: 10.1093/brain/124.6.1241

Morris, J.S., Öhman, A. & Dolan, R.J. A subcortical pathway to the right amygdala mediating
"unseen" fear. *Proc. Natl. Acad. Sci. U.S.A.* **96**, 1680-1685 (1999).
doi: 10.1073/pnas.96.4.1680

Movellan, J.R. Tutorial on Gabor filters. *Open Source Document.* **40**, 1–23 (2002).
https://inc.ucsd.edu/mplab/75/media//gabor.pdf (access, 2022/12/31; doi is not available)

Nakano, T., Higashida, N. & Kitazawa, S. Facilitation of face recognition through the retino-
tectal pathway. *Neuropsychol.* **51**, 2043-2049 (2013).
doi: 10.1016/j.neuropsychologia.2013.06.018

Nguyen, M.N., Hori, E., Matsumoto, J., Tran, H.T., Ono, T. & Nishijo, H. Neuronal responses
to face-like stimuli in the monkey pulvinar. *Eur J Neurosci.* **37**, 35-51, (2013).
doi: 10.1111/ejn.12020

Nguyen, M.N., Matsumoto, J., Hori, E., Maior, R.S., Tomaz, C., Tran, A.H., Ono, T., & Nishijo,
H. Neuronal responses to face-like and facial stimuli in the monkey superior colliculus.
Front. Behav. Neurosci. **8**, 85 (2014). doi: 10.3389/fnbeh.2014.00085

Pegna, A.J., Khateb, A., Lazeyras, F., & Seghier, M.L. Discriminating emotional faces without
primary visual cortices involves the right amygdala. *Nat. Neurosci.* **8**, 24-25 (2005).
doi: 10.1038/nn1364

Perret. D.I., MIstlin, A.J., & Chitty, A.J. Visual neurones responsive to faces. *Trends Neurosci.*
10, 358-364 (1987). doi: 10.1016/0166-2236(87)90071-3

Pessoa, L. & Adolphs, R. Emotion processing and the amygdala: from a "low road" to "many
roads" of evaluating biological significance. *Nat. Rev. Neurosci.* **11**, 773-782 (2010).
doi: 10.1038/nrn2920

Petry, H.H. & Bickford, M.E. The second visual system of the tree shrew. *J. Comp. Neurol.* **527**,
679-693 (2019). doi: 10.1002/cne.24413

Rai, M. & Rivas, P. A review of convolutional neural networks and Gabor filters in object
recognition. *2020 Int. Conf. Comput. Sci. Comput. Intelligence (CSCI)* 1560-1567 (2020).
doi: 10.1109/CSCI51800.2020.00289

Roe, A.W., Chelazzi, L., Connor, C.E., Conway, B.R., Fujita, I., Gallant, J.L., Lu, H., &
Vanduffel, W. Toward a unified theory of visual area V4. *Neuron* **74**, 12-29 (2012).
doi: 10.1016/j.neuron.2012.03.011

Rolls, E.T. & Baylis, G.C. Size and contrast have only small effects on the responses to faces
of neurons in the cortex of the superior temporal sulcus of the monkey. Exp. Brain Res.
65, 38-48 (1986). doi: 10.1007/BF00243828

Schmolesky, M.T., Wang, Y, Hanes, D.P., Thompson, K.G., Leutgeb, S., Schall, J.D. &
Leventhal, A.G. Signal timing across the macaque visual system. *J. Neurophysiol.* **79**,
3272-3278 (1998). doi: 10.1152/jn.1998.79.6.3272

Simonyan, K. & Zisserman, A. Very deep convolutional networks for large-scale image
recognition. *arXiv* 1409.1556 (2014). doi: 10.48550/arXiv.1409.1556

Striemer, C.L., Whitwell, R.L. & Goodale, M.A. Affective blindness in the absence of input
from face processing regions in occipital-temporal cortex. *Neuropsychol.* **128**, 50-57
(2019). doi: 10.1016/j.neuropsychologia.2017.11.014

Tamietto, H., Castelli, L., Vighetti, S., Perozzo, P., Geminiani, G., Weiskrantz, L. & de Gelder,
B. Unseen facial and bodily expressions trigger fast emotional reactions. *Proc. Natl. Acad.*
Sci. U.S.A. **106**, 17661-17666 (2009). doi: 10.1073/pnas.0908994106

Tamietto, H. & de Gelder, B. Neural bases of the non-conscious perception of emotional signals.
Nat. Rev. Neurosci. **11**, 697-709 (2010). doi: 10.1038/nrn2889

Tokui, S., Oono, K., Hido, S. & Clayton, J. Chainer: a next-generation open source framework
for deep learning. *Proc. Workshop on machine learning systems (LearningSys) in 29th*
annual conference on neural information processing systems. **5**, 1-6 (2015).
http://learningsys.org/papers/LearningSys_2015_paper_33.pdf.
https://github.com/chainer/chainer/releases/tag/v3.0.0 (version, 3.0.0; release, Oct 17,
2017) (doi is not available)

Tsao, D.Y. & Livingstone, M.S. Mechanisms of face perception. *Annu. Rev. Neurosci.* **31**, 411-
437 (2008). doi: 10.1146/annurev.neuro.30.051606.094238

Ueda, Y., Nunoi, M., & Yoshikawa, S. Development and validation of the Kokoro Research
Center (KRC) facial expression database. *Psychologia* **61**, 221-240 (2019).
doi: 10.2117/psysoc.2019-A009

Ungerleider, L.G. & Mishkin, M. Two cortical visual systems. In Ingle, DJ, Goodale, MA &
Mansfield, RJW, editors. *Analysis of Visual Behavior.* Cambridge: MIT Press, pp. 549–
586 (1982). https://www.cns.nyu.edu/~tony/vns/readings/ungerleider-mishkin-1982.pdf
(doi is not available)

Updiyke, B.V. Characteristics of unit responses in superior colliculus of the Cebus monkey. *J.*
Neurophysiol. **37**, 896-909 (1974). doi: 10.1152/jn.1974.37.5.896

Van den Bergh, G., Zhang, B., Arckens, L. & Chino, Y.M. Receptive-field properties of V1 and
V2 neurons in mice and macaque monkeys. *J. Comp. Neurol.* 518, 2051-2070 (2010). doi:
10.1002/cne.22321

Verhoef, B-E., Vogels, R. & Janssen, P. Binocular depth processing in the ventral visual
pathway. *Phil. Trans. R. Soc. B* **371**, 20150259 (2016). doi: 10.1098/rstb.2015.0259

Vuilleumier, P., Armony, J.L., Driver, J. & Dolan, R.J. Distinct spatial frequency sensitivities
for processing faces and emotional expressions. *Nat. Neurosci.* **6**, 624–631 (2003).
doi: 10.1038/nn1057

Wallace, M. T., McHaffie, J. G. & Stein, B. E. Visual response properties and visuotopic
representation in the newborn monkey superior colliculus. *J. Neurophysiol.* **78**, 2732–2741
(1997). doi: 10.1152/jn.1997.78.5.2732

Yamins, D.L.K. & DiCarlo, J.J. Using goal-driven learning models to understand sensory cortex.
Nat. Neurosci. **19**, 356-365 (2016). doi: 10.1038/nn.4244

Yamins, D.L.K., Hong, H., Cadieu, C.F., Solomon, E.A., Seibert, D. & DiCarlo, J.J.
Performance-optimized hierarchical models predict neural responses in higher visual
cortex. *Proc. Natl. Acad. Sci. U.S.A.* **111**, 8619-8624 (2014).
doi: 10.1073/pnas.1403112111

20230127

Acknowledgments

This work was supported by grants from the Ministry of Education, Culture, Sports, Science and Technology of Japan (JP17H01381 and JP21H02596 to IF; JP18H04197, JP20H04578, and 20K12023 to MI); the Center for Information and Neural Networks; the Ministry of Internal Affairs and Communications of Japan. CL was supported by the Research Fellowship for Young Scientists from the Japan Society for the Promotion of Science.

Author contributions

CL, MI, TS, and IF designed the research; CL, MI, and TS performed the research; CL, MI, TS, and IF wrote the paper. All authors approved the submitted version.

Competing interests

The authors declare no conflicts of interest.

Data availability

All data and analysis codes are available from the corresponding author upon request.

Ethics statement

Written informed consent was obtained for the publication of any identifiable images included in this article.