The impact of similarity metrics on cell type clustering in highly multiplexed in situ imaging cytometry data

Elijah Willie[1,2], Pengyi Yang[1,2,3,5], and Ellis Patrick[1,2,3,4]

[1]Sydney Precision Data Science Centre, The University of Sydney, NSW, Australia.

[2]School of Mathematics and Statistics, The University of Sydney, NSW, Australia.

[3]Laboratory of Data Discovery for Health Limited (D24H), Science Park, Hong Kong SAR, China.

[4]Centre for Cancer Research, The Westmead Institute for Medical Research, The University of Sydney, NSW 2006, Australia.

[5]Computational Systems Biology Group, Children's Medical Research Institute, The University of Sydney, Westmead, NSW 2145, Australia.

[*]To whom correspondence should be addressed. Email: Ellis Patrick, ellis.patrick@sydney.edu.au.

Abstract

Highly multiplexed *in situ* imaging cytometry assays have enabled researchers to scrutinize cellular systems at an unprecedented level. With the capability of these assays to simultaneously profile the spatial distribution and molecular features of many cells, unsupervised machine learning, and in particular clustering algorithms, have become indispensable for identifying cell types and subsets based on these molecular features. However, the most widely used clustering approaches applied to these novel technologies were developed for cell suspension technologies and may not be optimal for *in situ* imaging assays. In this work, we systematically evaluated the performance of various similarity metrics used to quantify the similarity between cells when clustering. Our results demonstrate that performance in cell clustering varies significantly when different similarity metrics were used. Lastly, we propose FuseSOM, an ensemble clustering algorithm employing hierarchical multi-view learning of similarity metrics and self-organizing maps (SOM). Using a stratified subsam-

pling analysis framework, FuseSOM exhibits superior clustering performance compared to the current best-practice clustering approaches for *in situ* imaging cytometry data analysis.

Key words: Clustering, Image analysis, Bioinformatics, Machine learning, Biostatistics

1   Introduction

Technological advancements over the past decade have provided researchers the capability to simultaneously measure multiple molecular features in tissue at subcellular resolution [1]. Key technologies that are pioneering a new era for spatially-resolved proteomics include Imaging Mass Cytometry (IMC) [2], Multiplexed Ion Beam Imaging by Time Of Flight (MIBI-TOF) [3], Co-Detection by indEXing (CODEX) [4] and its successor Phenocycler. These technologies can measure approximately 50-100 features with high throughput, enabling researchers to address complex questions about the spatial distribution and interaction of various types of cells *in situ* [5]. Before interrogating the spatial relationships between cells however, a ubiquitous analytical step when analyzing highly multiplexed imaging data is defining functionally distinct cell types.

Unsupervised clustering algorithms are valuable tools for discovering both known and novel cell types in highly multiplexed data, even in cases where prior knowledge of the cell types present in an experiment is lacking [6]. In our review of the literature, over 70 percent of manuscripts employing highly multiplexed imaging data for analysis utilized one of three clustering algorithms. IMC and MIBI-TOF data was predominately clustered using either Phenograph [7], a graph-based Louvain community detection method, or FlowSOM [8], a self-organising map approach, while CODEX data was predominately clustered using X-shift, a KNN algorithm accessible through the Vortex GUI[9]. In the remaining manuscripts, other Louvain and Leiden graph-based community detection algorithms, hierarchical clustering and K-means clustering were used.

Despite their popularity in imaging modalities, Phenograph, FlowSOM and X-shift were developed in 2015 and 2016 for suspension cytometry technologies which do not share all of the same technical limitations and noise profiles with tissue based imaging technologies. Additionally, in practice these methods are often employed to generate a large set of candidate clusters which using expert domain knowledge are then manually clustered, refined and annotated based on biological features such as key marker expression, cell localization. Following this, there exist multiple avenues for further exploration of how clustering algorithms could be tailored for multiplexed imaging data.

Choosing an appropriate similarity metric is crucial for clustering algorithms as it de-

termines how points in a dataset, in our case cells, are partitioned into clusters. Different similarity metrics, often referred to as distance metrics, can yield different clusters. While the Euclidean distance is commonly used in many clustering algorithms, recent studies have shown that correlation-based metrics such as Pearson or Spearman correlation perform better when clustering in other multiplexed technologies [10, 11]. Evaluating the performance of different similarity metrics for defining cell types in multiplexed imaging data may guide the improvement or development of new clustering algorithms which are optimal for these exciting technologies.

In this study, we systematically assess the performance of various distance- and correlation-based metrics across 15 imaging datasets, using multiple performance metrics. We also compare the performance of best-practice clustering methods that currently employ different similarity metrics. Based on our assessment, which highlights the benefits of combining information from multiple similarity metrics, we introduce a new clustering algorithm called FuseSOM. FuseSOM utilizes self-organizing maps (SOM) and combines multiple similarity metrics through multi-view ensemble learning and hierarchical clustering. This algorithm aims to accurately and robustly identify cell types in multiplexed in situ imaging cytometry assays. Overall, our work demonstrates the impact of similarity metrics on clustering cells in multiplexed imaging cytometry data and proposes FuseSOM as a promising method for the analysis of such data.

Results

Evaluating the impact of similarity metrics

To assess the impact of similarity metrics on clustering performance, we performed hierarchical clustering on a MIBI-TOF dataset using either correlation-based metrics (Pearson, Spearman, and Cosine) or distance-based metrics (Euclidean, Manhattan, and Maximum) [12]. To assess performance, we compared the clusters from the hierarchical clustering to the manually curated cell type labels identified in the manuscript (**Figure 1**). On average, correlation-based metrics outperform distance-based metrics by 8.0% for ARI, 10.7% for NMI, 1.70% for FM-index, and 8.0% for F-Measure. Furthermore, there is evidence that clustering performance is improved when using correlation-based metrics compared to distance-based metrics, as seen across three evaluation metrics.

To provide a comprehensive assessment of the performance of the similarity metrics, we quantified the clustering performance of the metrics on 15 multiplexed in situ imag-

ing cytometry datasets (**Table 1**). These datasets were chosen as each had some manual intervention when cell type labels were defined. Each dataset was randomly subsampled to 20K cells five times, and each subset was clustered using hierarchical clustering with all the similarity metrics. Finally, the average was taken across the five subsets. Across all 15 datasets, correlation-based metrics consistently outperformed distance-based metrics (**Figure 2**), more accurately recapitulating the manually curated cell-type labels from their original publications. These results show the efficacy of correlation-based metrics in hierarchical clustering.

Next, we assessed if the performance differences between correlation and Euclidean distance are consistent across multiple clustering methods. We reconfigured PhenoGraph, FlowSOM, and K-means clustering to use correlation instead of euclidean [7, 8]. As previously, the 15 datasets were randomly subsetted to 20K cells five times, and after clustering, the average score was taken across all evaluation metrics. While there does not appear to be a significant benefit in clustering performance for PhenoGraph, the overall PhenoGraph performance for both distance measures is worse when compared to the correlation-based distances (**Figure 3**) and (**Supplementary Figure S1**). For K-means, hierarchical clustering, and FlowSOM, we observe Pearson correlation performing better than Euclidean distance across all evaluation metrics. See (**Figure 3**) and (**Supplementary Figure S1**).

Combining similarity metrics is beneficial

Given the performance differences between the similarity metrics, we next wondered if combining multiple metrics using strategies such as multi-view ensemble learning would further improve performance [13]. To evaluate the efficacy of combining multiple distance metrics for clustering, we performed a comparison study combining various combinations of Pearson, Spearman, Cosine, and the Euclidean distance. First, all possible combinations of metrics were used to cluster the prototypes generated by the SOM algorithm. Of all the combinations, combining Pearson, Spearman, Cosine, and Euclidean consistently provided the best score across all four evaluation metrics (**Figure 4**). The combination of Pearson, Spearman, and Cosine also provided strong results, which imply that the addition of Euclidean does not markedly improve overall clustering performance.

FuseSOM combines self-organizing maps with multi-view ensemble learning of similarity metrics

Here, we introduce FuseSOM for the clustering of highly multiplexed imaging data. FuseSOM leverages all the ideas already discussed by combining similarity metrics with a Self Organizing Map and multiview hierarchical clustering to define cell types robustly (**Figure 5**). In comparison to FlowSOM which uses Euclidean distance by default, FuseSOM has superior performance in our stratified subsampling analysis framework which demonstrates that multiview ensemble of similarity metrics does provide a more robust clustering (**Figure 6**). The performance gain is particularly evident when looking at ARI and NMI, with average differences in scores being 32% for ARI, 27% for NMI, 10% for FM-Index, and 9.0% for FMeasure.

Several methods for estimating the number of clusters have been implemented in the FuseSOM R package. The relative error (RE) between the predicted number of clusters and the number of clusters used in the corresponding manuscripts was used to assess the accuracy of the cluster estimation methods. The Jump and Discriminant method tends to overestimate the actual number of clusters while the others tend to underestimate the actual number of clusters (**Figure** 7). Next, FuseSOM was used to cluster the cells in the datasets using the number of clusters estimated by each method. For both ARI and NMI, the Jump and Discriminant methods appear to have the highest average score across all datasets (**Figure 7**). This demonstrates that the Discriminant and Jump methods have the greatest average accuracy in predicting the number of clusters chosen in the original manuscripts. This is further reflected in the clustering performance based on the predicted number of clusters.

To investigate the running time and memory usage of FuseSOM, we applied FuseSOM to the Hoch dataset [14]. This dataset contains 800K cells across 41 markers. Next, clustering was performed in increments of 100K cells (8 clustering solutions in total) to gauge how memory and running are affected by an increasing number of cells. Clustering was performed on an 11th Gen Intel® Core™ i7-1165G7 @ 2.80GHz with four cores and 32 GB of memory. Memory usage scales linearly with the size of the data (**Supplmentary Figure S2a**). Doubling the size of the data requires twice as much memory. FuseSOM can process a dataset with 800K cells using only 8GB of memory, implying that FuseSOM can scale to datasets with more than a million cells with moderate memory usage. FuseSOM is also efficient, being able to process 800K cells in under 5 minutes (**Supplementary Figure S2b**). The computational time scales sub-linearly as the size of the dataset increases. For example, the running time is not doubled by doubling the data size.

Discussion

In this work, we performed a comparative analysis of the performance of various similarity metrics for clustering highly multiplexed *in situ* imaging cytometry assays. Using multiple clustering methods across multiple similarity metrics, we demonstrated that the choice of similarity metric does affect the clustering performance of highly multiplexed cytometry *in situ* imaging data with correlation-based metrics on average out-performing distance-based metrics. We then leveraged these findings to develop a novel multi-view clustering algorithm called FuseSOM and demonstrated its ability to recover semi-supervised cell-type annotations across various datasets from differing imaging technologies with reasonable accuracy. Our results comprehensively demonstrate the impact of similarity metric choice on cell type clustering in highly multiplexed imaging cytometry data, and highlight the need to develop new best-practice clustering algorithms for these technologies.

While we have demonstrated that correlation metrics are often superior to distance metrics for multiplexed imaging data, we have not demonstrated why. We do however demonstrate that this phenomena is consistent across the imaging platforms. Our hypothesis is that distance-based metrics such as Euclidean and Manhattan are sensitive to the scaling of the data and therefore are susceptible to changes in the expression of markers across images or even different regions of the tissue imaged. However, correlation-based metrics such as Pearson and Spearman are scale-invariant and, therefore, could be less susceptible to changes in the expression of markers driven by technical artifacts. As correlation-based metrics only consider the relative expression between markers, we suspect this makes them more robust and therefore are more accurate in capturing cell type specific expression trends in highly multiplexed in situ imaging cytometry data.

For many clustering algorithms, the number of clusters is a parameter that must be chosen before executing the algorithm. Some algorithms, including graph and density based, can estimate the number of clusters as part of the algorithm, however, even for these methods other parameters indirectly affect the number of clusters. For example, the size of the neighborhood in density-based methods can affect the number of clusters. Selecting a suitable number of clusters should always be viewed in the context of the application and while it can be guided by quantitative approaches, like those we have implemented in FuseSOM, should ultimately be assess qualitatively. For example, to identify rare cell types in biological data, one might need to deeply cluster the data to find smaller populations of cells. Or, after over-clustering data to identify smaller cell subsets, expert domain knowledge may be used to reduce the number of clusters so that the resulting clusters were biologically sensi-

ble or interpretable. We expect that clustering will always benefit from manual intervention and scrutiny to decide the number of appropriate clusters for a dataset and we advocate for leveraging prior domain knowledge when annotating cell types.

Methods

Imaging datasets collection and processing

To benchmark the performance of FuseSOM on imaging datasets from various technologies, we selected a set of 15 datasets generated using different imaging technologies. In addition, we selected datasets with human intervention in manually gating cell populations or merging biologically similar clusters. Datasets were sourced from major databases, including Zenodo, Figshare, and Mendeley. When available, we used the version data that had been processed as described in the original manuscript. We also used the same markers for clustering as described in the manuscript. The imaging technologies used included Co-detection by indexing(CODEX) (four datasets), Imaging Mass Cytometry(IMC) (six datasets), Multiplexed ion beam imaging by the time of flight (MIBI-TOF) (four datasets), and sequential Fluorescence In Situ Hybridization (seqFISH) (one dataset) [3, 4, 15, 16]. Next, we employed a substratification framework for each dataset to evaluate clustering methods. This framework takes an imaging dataset as input, and five stratified samples are returned. Substratification is done to account for possible variability in clustering results. This framework takes as input and returns five stratified datasets. Stratification is done by selecting 80% of cells from each annotated class [10].

Similarity metrics

Six types of metrics across two classes that are predominantly used across machine learning clustering literature were used in this study. The two classes include correlation-based and distance-based. The distance-based metrics were Euclidean, Manhattan, and Maximum distance, while the correlation-based metrics included Pearson correlation, Spearman correlation, and Cosine similarity. More formally, let x_{im} and x_{jm} denote the expression of a marker $m = 1, ..., M$ in cell $i = 1, ..., N$ and cell $j = 1, ..., N$, where G and N are the total number of markers and cells, respectively. Led $D = d_{ij}$ be a distance matrix where d_{ij} represents the distance between $cell_i$ and $cell_j$. We can then define the distance-based metrics as follows:

Euclidean distance,

$$d_{ij} = \sqrt{\sum_{m=1}^{M}(x_{im} - x_{jm})^2} \tag{1}$$

Manhattan distance,

$$d_{ij} = \sum_{m=1}^{M}|x_{im} - x_{jm}| \tag{2}$$

Maximum distance,

$$d_{ij} = \max_{m}|x_{im} - x_{jm}| \tag{3}$$

Similarly, the correlation-based metrics can be defined as follows:

Pearson distance,

$$d_{ij} = \sqrt{2\left(1 - \frac{\sum_{m=1}^{M}(x_{im} - \bar{x}_i)(x_{jm} - \bar{x}_j)}{\sqrt{\sum_{m=1}^{M}(x_{im} - \bar{x}_i)^2}\sqrt{\sum_{m=1}^{M}(x_{jm} - \bar{x}_j)^2}}\right)} \tag{4}$$

Spearman distance,

$$d_{ij} = \sqrt{2\left(1 - \frac{\sum_{m=1}^{M}(r_{im} - \bar{r}_i)(r_{jm} - \bar{r}_j)}{\sqrt{\sum_{m=1}^{M}(r_{im} - \bar{r}_i)^2}\sqrt{\sum_{m=1}^{M}(r_{jm} - \bar{r}_j)^2}}\right)} \tag{5}$$

Cosine distance

$$d_{ij} = \sqrt{2\left(1 - \frac{\sum_{m=1}^{M}x_{im}x_{jm}}{\sqrt{\sum_{m=1}^{M}x_{im}^2}\sqrt{\sum_{m=1}^{M}x_{jm}^2}}\right)} \tag{6}$$

where r_{ij} is the rank of marker m in $cell_i$, $\bar{x}_i$ is the mean expression of $cell_i$, $\bar{x}_j$ is the mean expression of $cell_j$, $\bar{r}_i$ is the mean expression rank of $cell_i$, and $\bar{r}_j$ is the mean expression rank of $cell_j$,

The hierarchical clustering and self-organizing map algorithms

We used the agglomerative hierarchical clustering algorithm with varying similarity metrics to investigate the effect of similarity metrics on clustering algorithms. Agglomerative clustering is a type of clustering where each data point starts as its cluster. At every step, two clusters are merged using a linkage function. This step repeats until a single cluster comprises the entire dataset. There are many options for a linkage function. We opted to use the average linkage function, which merges two clusters based on the average distance between pairs of points between two clusters [17]. This algorithm outputs a tree-like structure called a dendrogram which can be cut at any level to generate k clusters. We also used the FlowSOM algorithm proposed by [8]. This algorithm uses a Self Organizing Map (SOM) architecture to generate prototypes which are then clustered using hierarchical consensus clustering using

euclidean distances to generate meta-clusters. These meta-clusters are then projected back on the original dataset to obtain clusters.

FuseSOM

Here the FuseSOM algorithm is described. The algorithm starts by generating a Self Organizing Map. A Self Organizing Map is a type of dimensionality reduction algorithm that maps points in a high dimensional space ($d > 2$) to a lower dimensional space ($d = 2$). The SOM architecture preserves the topological relationships between points when reduced to a lower dimension. The SOM also provides a set of points called prototypes which are representations of points in the higher dimensional space. Like cluster centers in the k-means algorithm, many points can be mapped to a single prototype. For a more thorough treatment of SOMs, see [18]. The *YASOMI* package was obtained and modified to implement the self-organizing map used in FuseSOM [19].

In this work, we generate a SOM, and the prototypes are used for clustering. After clustering, the clusters are projected back to the original data to classify the original data points. The SOM algorithm requires a 2-d grid(x,y) size, which determines the number of prototypes. Grid sizes of varying shapes are allowed. However, square grids are typically used. To estimate the size of the grid for a dataset, we use the method described in [20]. This method computes the number of eigenvalues of a covariance matrix significantly different from the Tracy-Widom distribution [21].

Next, multiview integration combines the Pearson correlation distance, Cosine distance, Spearman correlation, and Euclidean distance between the prototypes to generate a final distance matrix for clustering. We adopted a multiview integration method to combine the four transformed matrices [22]. The *analogue* package is used to perform the multiview integration [23]. The *psych* package transforms the similarity matrices into distance matrices [24]. Finally, to generate final cluster labels using the integrated distance matrices, hierarchical clustering using the average linkage function is used. The *FCPS* package was used for hierarchical clustering [25].

Estimating the number of clusters

For most clustering algorithms, the number of clusters k is an important hyperparameter that must be set. To this end, many methods have been developed to help practitioners choose an appropriate number for their dataset. We have included well-known methods for estimating the number of clusters as part of the FuseSOM package. These methods include the Gap

statistic, the Slope statistic, the Jump statistic, the Silhouette statistic, and the within-cluster distance (WCD) [26–29]. We also developed a method for estimating the number of clusters based on maximum clusterability discriminant projection pursuit. To accomplish this, we couple hierarchical clustering with discriminant analysis and multimodality testing to estimate the number of clusters [30–35]. First, we generate a dendrogram using hierarchical clustering with average linkage. Next, for each node in the resulting tree, we project the two classes onto a line such that both classes are well separated. See (**Supplementary Figure S3**). The Dip test for multimodality testing is then applied to the distribution of the points along this line [34]. See (**Figure 7**). The family-wise error rate (FWER) is controlled using the method described in [36]. Finally, the number of nodes with significant p-values is returned as the number of clusters.

Evaluation metrics

To evaluate clustering performance for clustering solutions generated across methods, we used a set of methods; the Adjusted Rand Index (ARI), Normalized Mutual Information (NMI), Fowlkes-Mallows index (FM-Index), and the F-Measure [37–40]. All these metrics take values between 0 and 1, with 0 being no similarity and 1 being perfect similarity.

Data availability

Publicly available data were used for all evaluations. All data were downloaded as described in the originating manuscripts.

Code availability

The *FuseSOM* R package is available on Bioconductor and is available under the GPL-3 license. All code for analysis done can be found at Github

Acknowledgments

The authors thank all their colleagues, particularly at The University of Sydney, Sydney Precision Data Science Centre and Charles Perkins Centre for their support and intellectual engagement.

The following sources of funding for each author are gratefully acknowledged: the AIR@innoHK programme of the Innovation and Technology Commission of Hong Kong to EP and PY. Australian Research Council Discovery Early Career Researcher Award (DE200100944) funded by the Australian Government to EP; National Health and Medical Research Council (NHMRC) Investigator Grant (1173469) to P.Y.; and the University of Sydney Postgraduate Excellence Award for E.W.; The funding sources had no impact on the study design; in the collection, analysis, and interpretation of data, the writing of the manuscript, and in the decision to submit the manuscript for publication.

Author contributions

EP and EW conceived and designed the study. EP and EW led the method development and guided the evaluation data analysis with input from PY. EW curated the imaging data, implemented all data analytics, and developed the corresponding R code. All authors wrote, read, reviewed the manuscript, and approved the final version.

Conflict of interest

The authors declare that they have no conflict of interest.

References

1. Lewis, S. M. *et al.* Spatial omics and multiplexed imaging to explore cancer biology. *Nature Methods* **18,** 997–1012 (2021).

2. Giesen, C. *et al. Highly multiplexed imaging of tumor tissues with subcellular resolution by mass cytometry* Mar. 2014.

3. Keren, L. *et al.* MIBI-TOF: A multiplexed imaging platform relates cellular phenotypes and tissue structure. en. *Science Advances* **5,** eaax5851. ISSN: 2375-2548 (Oct. 2019).

4. Black, S. *et al.* CODEX multiplexed tissue imaging with DNA-conjugated antibodies. en. *Nature Protocols* **16,** 3802–3835. ISSN: 1754-2189, 1750-2799 (Aug. 2021).

5. Baharlou, H., Canete, N. P., Cunningham, A. L., Harman, A. N. & Patrick, E. Mass Cytometry Imaging for the Study of Human Diseases—Applications and Data Analysis Strategies. *Frontiers in Immunology* **10,** 2657. ISSN: 1664-3224 (Nov. 2019).

6. Karim, M. R. *et al.* Deep learning-based clustering approaches for bioinformatics. *Briefings in Bioinformatics* **22,** 393–415 (2020).

7. Levine, J. H. *et al.* Data-Driven Phenotypic Dissection of AML Reveals Progenitor-like Cells that Correlate with Prognosis. *Cell* **162,** 184–197 (July 2015).

8. Van Gassen, S. *et al.* FlowSOM: Using self-organizing maps for visualization and interpretation of cytometry data: FlowSOM. en. *Cytometry Part A* **87,** 636–645. ISSN: 15524922 (July 2015).

9. Samusik, N., Good, Z., Spitzer, M. H., Davis, K. L. & Nolan, G. P. Automated mapping of phenotype space with single-cell data. en. *Nature Methods* **13,** 493–496. ISSN: 1548-7091, 1548-7105 (June 2016).

10. Kim, T. *et al.* Impact of similarity metrics on single-cell RNA-seq data clustering. en. *Briefings in Bioinformatics* **20,** 2316–2326. ISSN: 1467-5463, 1477-4054 (Nov. 2019).

11. Watson, E. R., Mora, A., Taherian Fard, A. & Mar, J. C. How does the structure of data impact cell–cell similarity? Evaluating how structural properties influence the performance of proximity metrics in single cell RNA-seq data. en. *Briefings in Bioinformatics* **23,** bbac387. ISSN: 1467-5463, 1477-4054 (Nov. 2022).

12. McCaffrey, E. F. *et al.* The immunoregulatory landscape of human tuberculosis granulomas. en. *Nature Immunology* **23,** 318–329. ISSN: 1529-2908, 1529-2916 (Feb. 2022).

13. Cao, Y., Geddes, T. A., Yang, J. Y. H. & Yang, P. Ensemble deep learning in bioinformatics. *Nature Machine Intelligence* **2,** 500–508 (2020).

14. Hoch, T. *et al.* Multiplexed imaging mass cytometry of the chemokine milieus in melanoma characterizes features of the response to immunotherapy. en. *Science Immunology* **7,** eabk1692. ISSN: 2470-9468 (Apr. 2022).

15. Giesen, C. *et al.* Highly multiplexed imaging of tumor tissues with subcellular resolution by mass cytometry. en. *Nature Methods* **11,** 417–422. ISSN: 1548-7091, 1548-7105 (Apr. 2014).

16. Eng, C.-H. L. *et al.* Transcriptome-scale super-resolved imaging in tissues by RNA seqFISH+. en. *Nature* **568,** 235–239. ISSN: 0028-0836, 1476-4687 (Apr. 2019).

17. Nielsen, F. in *Introduction to HPC with MPI for Data Science* 195–211 (Springer International Publishing, Cham, 2016). ISBN: 9783319219028 9783319219035.

18. Miljkovic, D. *Brief review of self-organizing maps* in *2017 40th International Convention on Information and Communication Technology, Electronics and Microelectronics (MIPRO)* (IEEE, Opatija, Croatia, May 2017), 1061–1066. ISBN: 9789532330908.

19. Rossi, F. *yasomi: Yet Another Self Organising Map Implementation* R package version 0.3/r39 (2012).

20. Patterson, N., Price, A. L. & Reich, D. Population Structure and Eigenanalysis. *PLOS Genetics* **2,** 1–20 (Dec. 2006).

21. Tracy, C. A. & Widom, H. Level-spacing distributions and the Airy kernel. en. *Communications in Mathematical Physics* **159,** 151–174. ISSN: 0010-3616, 1432-0916 (Jan. 1994).

22. Melssen, W., Wehrens, R. & Buydens, L. Supervised Kohonen networks for classification problems. en. *Chemometrics and Intelligent Laboratory Systems* **83,** 99–113. ISSN: 01697439 (Sept. 2006).

23. Simpson, G. L. & Oksanen, J. *analogue: Analogue and weighted averaging methods for palaeoecology* R package version 0.17-6 (2021).

24. Revelle, W. *psych: Procedures for Psychological, Psychometric, and Personality Research* R package version 2.2.9. Northwestern University (Evanston, Illinois, 2022).

25. Thrun, M. C. & Stier, Q. Fundamental clustering algorithms suite. en. *SoftwareX* **13,** 100642. ISSN: 23527110 (Jan. 2021).

26. Tibshirani, R., Walther, G. & Hastie, T. Estimating the number of clusters in a data set via the gap statistic. en. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)* **63,** 411–423. ISSN: 13697412 (2001).

27. Fujita, A., Takahashi, D. Y. & Patriota, A. G. A non-parametric method to estimate the number of clusters. en. *Computational Statistics & Data Analysis* **73,** 27–39. ISSN: 01679473 (May 2014).

28. Sugar, C. A. & James, G. M. Finding the Number of Clusters in a Dataset: An Information-Theoretic Approach. en. *Journal of the American Statistical Association* **98,** 750–763. ISSN: 0162-1459, 1537-274X (Sept. 2003).

29. Rousseeuw, P. J. Silhouettes: A graphical aid to the interpretation and validation of cluster analysis. en. *Journal of Computational and Applied Mathematics* **20,** 53–65. ISSN: 03770427 (Nov. 1987).

30. Etemad, K. & Chellappa, R. Discriminant analysis for recognition of human face images. en. *Journal of the Optical Society of America A* **14,** 1724. ISSN: 1084-7529, 1520-8532 (Aug. 1997).

31. Mokari, M., Mohammadzade, H. & Ghojogh, B. Recognizing Involuntary Actions from 3D Skeleton Data Using Body States. en. *Scientia Iranica* **0,** 0–0. ISSN: 2345-3605 (May 2018).

32. Samadani, A.-A., Kubica, E., Gorbet, R. & Kulić, D. Perception and Generation of Affective Hand Movements. en. *International Journal of Social Robotics* **5,** 35–51. ISSN: 1875-4791, 1875-4805 (Jan. 2013).

33. Ameijeiras-Alonso, J., Crujeiras, R. M. & Rodríguez-Casal, A. Mode testing, critical bandwidth and excess mass. en. *TEST* **28,** 900–919. ISSN: 1133-0686, 1863-8260 (Sept. 2019).

34. Hartigan, J. A. & Hartigan, P. M. The Dip Test of Unimodality. *The Annals of Statistics* **13.** ISSN: 0090-5364 (Mar. 1985).

35. Silverman, B. W. Using Kernel Density Estimates to Investigate Multimodality. en. *Journal of the Royal Statistical Society: Series B (Methodological)* **43,** 97–99. ISSN: 00359246 (Sept. 1981).

36. Meinshausen, N. Hierarchical testing of variable importance. *Biometrika* **95,** 265–278. ISSN: 0006-3444. eprint: `https://academic.oup.com/biomet/article-pdf/95/2/265/623449/asn007.pdf` (June 2008).

37. Steinley, D. Properties of the Hubert-Arable Adjusted Rand Index. en. *Psychological Methods* **9,** 386–396. ISSN: 1939-1463, 1082-989X (2004).

38. Kvålseth, T. On Normalized Mutual Information: Measure Derivations and Properties. en. *Entropy* **19,** 631. ISSN: 1099-4300 (Nov. 2017).

39. Fowlkes, E. B. & Mallows, C. L. A Method for Comparing Two Hierarchical Clusterings. en. *Journal of the American Statistical Association* **78,** 553–569. ISSN: 0162-1459, 1537-274X (Sept. 1983).

40. Hripcsak, G. Agreement, the F-Measure, and Reliability in Information Retrieval. en. *Journal of the American Medical Informatics Association* **12,** 296–298. ISSN: 1067-5027, 1527-974X (Jan. 2005).

41. Schürch, C. M. *et al.* Coordinated Cellular Neighborhoods Orchestrate Antitumoral Immunity at the Colorectal Cancer Invasive Front. en. *Cell* **182,** 1341–1359.e19. ISSN: 00928674 (Sept. 2020).

42. Phillips, D. *et al.* Immune cell topography predicts response to PD-1 blockade in cutaneous T cell lymphoma. en. *Nature Communications* **12,** 6726. ISSN: 2041-1723 (Dec. 2021).

43. Brbić, M. *et al. Annotation of Spatially Resolved Single-cell Data with STEL-LAR* en. preprint (Bioinformatics, Nov. 2021).

44. Moldoveanu, D. *et al.* Spatially mapping the immune landscape of melanoma using imaging mass cytometry. en. *Science Immunology* **7,** eabi5072. ISSN: 2470-9468 (Apr. 2022).

45. Van Maldegem, F. *et al.* Characterisation of tumour microenvironment remodelling following oncogene inhibition in preclinical studies with imaging mass cytometry. en. *Nature Communications* **12,** 5906. ISSN: 2041-1723 (Dec. 2021).

46. Rendeiro, A. F. *et al.* The spatial landscape of lung pathology during COVID-19 progression. en. *Nature* **593,** 564–569. ISSN: 0028-0836, 1476-4687 (May 2021).

47. Damond, N. *et al.* A Map of Human Type 1 Diabetes Progression by Imaging Mass Cytometry. en. *Cell Metabolism* **29,** 755–768.e5. ISSN: 15504131 (Mar. 2019).

48. Bortolomeazzi, M. *et al.* Immunogenomics of Colorectal Cancer Response to Checkpoint Blockade: Analysis of the KEYNOTE 177 Trial and Validation Cohorts. en. *Gastroenterology* **161,** 1179–1193. ISSN: 00165085 (Oct. 2021).

49. Risom, T. *et al.* Transition to invasive breast cancer is associated with progressive changes in the structure and composition of tumor stroma. en. *Cell* **185,** 299–310.e18. ISSN: 00928674 (Jan. 2022).

50. Liu, C. C. *et al.* Reproducible, high-dimensional imaging in archival human tissue by multiplexed ion beam imaging by time-of-flight (MIBI-TOF). en. *Laboratory Investigation* **102,** 762–770. ISSN: 0023-6837, 1530-0307 (July 2022).

51. Lohoff, T. *et al.* Integration of spatial and single-cell transcriptomic data elucidates mouse organogenesis. en. *Nature Biotechnology* **40,** 74–85. ISSN: 1087-0156, 1546-1696 (Jan. 2022).

Figure legends

Figure 1: UMAP visualization of cells from a sample imaging dataset. (A) Cells colored by annotations from original study [12]. (B) Hierarchical clustering using Pearson's Correlation and concordance quantified by ARI, NMI, FM-Index, and FMeasure. (C) Hierarchical clustering using Cosine's Distance (D) Hierarchical clustering using Spearman's Correlation. (E) Hierarchical clustering using Euclidean distance. (F) Hierarchical clustering using Manhattan distance. (G) Hierarchical clustering using Maximum distance.

Figure 2: Benchmarking similarity metrics on agglomerative clustering of 15 multiplexed imaging datasets. Each dataset was subsetted to 20K cells five times, and the average clustering score was recorded. Results were ranked in descending order across all similarity metrics and datasets by each evaluation metric. A larger circle size indicates better performance. Correlation-based metrics are consistently ranked higher than distance-based metrics across most datasets.

Figure 3: Boxplots of clustering performance of four clustering methods using Pearson correlation and euclidean across four evaluation metrics (ARI, NMI, FM-Index, and FMeasure). For three of the four methods, Pearson on average performs better than euclidean for clustering. This is not evident for PhenoGraph.

Figure 4: Scatter plots of average clustering performance of all combinations of Pearson, Cosine, Spearman, and Euclidean. Across all performance metrics, there is evidence that combining all distances provides a better signal for clustering.

Figure 5: Overview of FuseSOM: This new scalable algorithm uses (i) A Self Organizing Map to reduce the dimension of the data while preserving its topological structure; (ii) A multiview integration of various similarity metrics to capture all relevant signals; and (iii) Hierarchical clustering to generate a clustering solution for further downstream analysis.

Figure 6: (A) Bar plots of average clustering performance for FuseSOM and FlowSOM showed for all 15 datasets across four performance metrics (ARI, NMI, FM-Index, and FMeasure). For a majority of the datasets, FuseSOM outperforms FlowSOM. (B) Boxplots for the average clustering performance across all datasets. For all four evaluation metrics, FuseSOM shows an overall higher average score.

Figure 7: (A) Bar plots of cluster estimation performance for methods included in FuseSOM across all 15 datasets. The relative error metric was used to gauge performance. The Jump and Discriminant methods are the top performers. The dashed line represents a relative error of zero. In contrast, values above this line indicate an underestimation of the true number of clusters, and values below indicate an overestimation of the true number of clusters. (B) Boxplots of clustering performance based on the estimated number of clusters for methods included in FuseSOM. The Jump and Discriminant methods are top performers across all evaluation metrics.

Tables

Table 1: Imaging Datasets Used

Dataset	Technology	Num Markers	Num Cells	Num Celltypes	Disease	Tissue
Shcurch et al [41]	CODEX	49	258,385	29	Colorectal Cancer	Colon
Phillips et al [42]	CODEX	52	117,170	21	Lymphoma	Skin
Brbic et al [43]	CODEX	48	248,285	21	None	Small intestine/colon
Brbic et al [43]	CODEX	44	219,926	13	Normal/Bartett's esophagus	Tonsil
Moldoveanu et al [44]	IMC	12	227,592	10	Melanoma	Skin
Van Maldegem et al [45]	IMC	17	282, 837	16	Lung Cancer	Lung
Hoch et al [14]	IMC	41	864,263	10	Melanoma	Skin
Rendeiro et al [46]	IMC	38	515,791	17	Covid-19	Lung
Damond et al [47]	IMC	36	252,059	16	Type 1 Diabetes	Pancreas
Bortolomeazzi et al [48]	IMC	30	218,615	9	Colorectal Cancer	Colon
Risom et al [49]	MIBI-TOF	22	69,672	23	Breast Cancer	Breast
Keren et al [3]	MIBI-TOF	16	201,656	6	TN Breast Cancer	Various
McCafferry et al [12]	MIBI-TOF	37	30,943	16	Tuberculosis	Various
Liu et al [50]	MIBI-TOF	12	345,490	8	Various Cancers	Various
Lohoff et al [51]	seqFISH	50	57,536	24	None	Mouse embryos

Supplementary Figures

Supplementary Figure S1: (A) Bar plots of K-means clustering of a subset of 20K cells for 15 datasets using Pearson correlation and Euclidean distance. K-means with Pearson correlation, on average, performs better than Euclidean for most of the datasets across all evaluation metrics. (B) Bar plots of Hierarchical clustering of a subset of 20K cells for 15 datasets using Pearson correlation and Euclidean distance. On average, hierarchical clustering with Pearson correlation performs better than Euclidean for most datasets across all evaluation metrics. C) Bar plots of FlowSOM clustering of a subset of 20K cells for 15 datasets using Pearson correlation and Euclidean distance. FlowSOM clustering with Pearson correlation, on average, performs better than Euclidean for most datasets across all evaluation metrics. D) Bar plots of PhenoGraph clustering of a subset of 20K cells for 15 datasets using Pearson correlation and Euclidean distance. There is no evidence of performance differences between Pearson and Euclidean.

Supplementary Figure S2: (A) Scatter plot of total memory usage for FuseSOM across an increasing number of cells. (B) Scatter plot of total running time for FuseSOM across an increasing number of cells.

Supplementary Figure S3: An example of discriminant coordinates cluster number estimation. (A) and (C) Shows two classes separated by a discriminant line in black. (B) and (D) Shows the Dip test applied to the projection of the two classes onto this discriminant line. Note that for (B), a significant p-value is obtained, reflecting the class separation. For (D), the opposite is observed. P-values $< 2e^{-16}$ were rounded to 0.