VRPG: an interactive web viewer for reference-projected pangenome graph

Zepu Miao[1], Jia-Xing Yue[1,*]

[1]State Key Laboratory of Oncology in South China, Collaborative Innovation Center for Cancer Medicine, Guangdong Key Laboratory of Nasopharyngeal Carcinoma Diagnosis and Therapy, Sun Yat-sen University Cancer Center, Guangzhou, China.

*Corresponding author

E-mail: yuejiaxing@gmail.com (J.-X. Y.)

E-mail and ORCID for all authors:

Zepu Miao > zpmiao@sysucc.org.cn, 0000-0002-9734-682X

Jia-Xing Yue > yuejiaxing@gmail.com, 0000-0002-2122-9221

Abstract

With the increasing availability of high-quality genome assemblies, pangenome graph is emerging as a new paradigm in the genomics field for identifying, encoding, and interpreting genomic variation landscape at both population and species levels. To facilitate a better examination of pangenome graph towards novel biological insights, here we present VRPG, a web-based interactive viewer of pangenome graph. VRPG provides dynamic and efficient support for exploring and annotating pangenome graphs built upon hundreds of whole genome assemblies along a reference-based coordinate system. Moreover, VRPG shines with its unique features in highlighting the directed path of any graph-constitutive assembly as well as in denoting copy number variation of genomic segments represented by graph-constitutive nodes, which are highly valuable in genome comparison and variant analysis. To further demonstrate its features and scalability, we applied VRPG to the cutting-edge yeast and human reference pangenome graphs derived from hundreds of high-quality genome assemblies via a dedicated website (https://www.evomicslab.org/app/vrpg/).

Contact: yuejiaxing@gmail.com

Introduction

Long-read-based DNA sequencing has become the go-to-choice for most genome sequencing projects nowadays, empowering the production of chromosome-level telomere-to-telomere (T2T) genome assemblies for diverse organisms (including human) [1–3]. With such T2T reference assembly panel continuously expanding at both population and species levels, researchers began to use pangenome graphs to better represent the population- and species-wide genomic variation landscapes in a sequence-resolved manner [4]. Compared with the conventional linear reference genome, pangenome graph offers enhanced power and accuracy in read mapping and variant discovery, especially in the presence of sequence polymorphisms and structural variants (SVs) [5]. Therefore, a representative pangenome graph is expected to shed novel insights into the interpretation of the genotype-to-phenotype association and the discovery of missing heritability.

While a number of tools have been developed to build pangenome graph based on genome alignments, Minigraph [6], Minigraph-Cactus[7], and PGGB [8] are among the most popular ones. Minigraph is designed for efficiently constructing a reference-based pangenome graph with large variants (e.g., SVs) compactly encoded in its accompanied reference Graphical Fragment Assembly (rGFA) format, which records the origin of each graph constitutive segment from the input linear genomes and therefore allows for traversing the pangenome graph along a stable coordinate system. This unique feature makes the pangenome graph built by Minigraph a natural and intuitive extension to the conventional linear reference genomes, although certain level of bias might be introduced during the graph building process regarding selected reference and input genome order [9]. Minigraph preferentially considers large variants (e.g., SVs) while being less discriminative for small variants such as single-nucleotide-variants (SNVs) and small insertion/deletions (INDELs) during graph construction, therefore pangenome graphs created by Minigraph is not a strictly lossless representation of the full genetic variation possessed by the input genomes at the per base level. As an improvement, Minigraph-Cactus was proposed as a new pangenome graph building pipeline that combines the compactness and efficiency of Minigraph as well as the base-level sensitivity and accuracy of Cactus. Therefore, the pangenome graph built by Minigraph-Cactus can effectively represents the full genetic variation across both base-level and structural-level scales while still preserving the coordinate of the

linear reference genome. Finally, PGGB adopted a reference-free approach for pangenome graph construction based on all-against-all genome alignments, which is theoretically unbiased but computationally more expensive. Also, PGGB will clip and collapse the highly similar genomic segments of the input genomes and therefore disrupt the linearity of genome coordinates, making it less straightforward in tracing the original genome coordinates of each graph constitutive segment.

An intuitive visualization of pangenome graph can greatly assist researchers to explore and understand the global and local genomic variation in their graph representation. To date, several tools have been developed for visualizing pangenome graph, among which Bandage [10] and GFAviz [11] focus more on large-scale topology, while SeauenceTubeMap [12] and MoMI-G [13] are more suitable for visualizing fine-scale sequence level details. The recently developed ODGI [14] showed improved performance on large-scale pangenome graphs with extended visualization
function for binned and linearized 1-dimentional local graph structure rendering. However, none of these tools work well for dynamically visualizing full-scaled pangenome graphs on the fly due to limitations in scalability. Moreover, most of these tools only provide simple visualization function for the graph itself with limited features in exploiting the connection between pangenome graph and the input linear genome assemblies where it derives from.

In this study, we present VRPG, a web-based interactive viewer for reference-projected pangenome graph with scalability. VRPG natively supports the rGFA-formatted pangenome graph built by Minigraph and provides pre-shipped auxiliary command line module (gfa2view) for projecting pangenome graphs built by Minigraph-Cactus and PGGB (both in GFA format) to a reference-based stable coordinate system. Such design helps VRPG to render a linear reference-based intuitive pangenome graph visualization while providing biological informative features such as genome path highlighting and copy number variation presenting, which are highly valuable in both large-scale genome comparison and fine-scale variant analysis. Moreover, VRPG is algorithmically optimized to be highly scalable, capable of reading, processing, and dynamically rendering large-scale pangenome graphs built upon hundreds of input genome assemblies. As a live demonstration, we applied VRPG to the cutting-edge yeast

and human pangenome graphs via a dedicated website (https://www.evomicslab.org/app/vrpg/), which showcases the feature and power of VRPG in exploring the power of pangenome graph.

Results

Software design

VRPG is an interactive web viewer for pangenome graphs encoded in rGFA or GFAv1 formats. VRPG is easy to deploy and highly efficient in visualizing complex pangenome graphs derived from hundreds of genome assemblies on the fly. VRPG renders pangenome graph by implementing a reference-based projection, which make it highly intuitive and informative to relate the pangenome graph topology to biological annotations compiled for the traditional linear reference genome. Moreover, a graph simplification function is further implemented to enable users to dynamically remove nodes corresponding to small variants (e.g., SNVs and INDELs), which is very useful when visualizing pangenome graphs built by Minigraph-Cactus and PGGB, in which base-level small variants are encoded as individual nodes and therefore making the graph topology become too complex to display as the query region extends.

VRPG mainly operates via a web browser, in which users can easily query and browse the input pangenome graph (Figure 1). Once users specify the query region based on its genomic coordinates in the reference genome, VRPG can extract and render the corresponding subgraph in three different layouts: squeezed (default), expanded, and cola. Three levels of graph simplification strategies are provided: non-ref nodes (default), all nodes, and none. Users can select the preferred strategy based on the graph complexity of the query genomic region. In the rendered graph, further information regarding node origin, node copy number status, and assembly-to-graph path can be easily extracted and displayed by simple clicks, which comes handy for users to relate the graph topology to the input linear genome assemblies.

Figure 1. The interactive user interface of VRPG when opened in a web browser. After selecting the input pangenome graph dataset, users can interactively visualize, navigate, and query the pangenome graph based on reference-based genomic coordinate system.

Basic view and highlighting

In the graph rendered by VRPG, graph nodes correspond to the pre-defined reference genome are shown along the center line, while non-reference nodes are shown in the peripheral space. When clicking on a graph node, the node block will become thicker and the information about the corresponding genomic segment will be reported on the right panel (Figure 2A). When clicking on a graph edge, the edge will be colored in red (Figure 2B) and its color will revert to black on a second click. In addition, VRPG provides a "Highlight" feature for highlighting the path of any constitutive genome assembly in the pangenome graph (Figure 2C). When selecting a specific genome assembly in the "Highlight" field, the assembly-to-graph path of the selected assembly will be highlighted in red. All matched nodes will be marked by red dotted lines and all matched

edges will be marked by red solid lines. The arrows on the matched edges reflect the relative orientation of the input genome assembly along the pangenome graph.

Figure 2. The reference pangenome graph visualization with VRPG. (A) VRPG visualization with the node s32871 selected by clicking on this graph node. (B) VRPG visualization with the two edges surround the node s32871 selected by clicking on these two graph edges. (C) VRPG visualization with the assembly-to-graph mapping path of the assembly ADE#HP0 highlighted by selecting ADE#HPD in the "Highlight" selection field.

Node information inquiry

In VRPG, users can easily obtain the source genome assembly information of any node together with its copy number status across all input assemblies by a simple click. Here the source genome assembly information specifies the genome assembly origin and coordinates (1-based) of the genomic segment that defines the corresponding node when building the pangenome graph. When preprocessing the input pangenome graph, VRPG will summarize the node-specific mapping depth by aligning each input genome assembly to the pangenome graph and calculate the assembly-to-graph mapping depth for all nodes encompassed in the graph. During

visualization, the mapping depth of the query node will be reported for all input assemblies, where the mapping depth value reflect the actual copy number of the corresponding genomic segment that defines this node.

Genomic variant representation in VRPG

One major motivation of developing a pangenome graph visualization tool is to provide an intuitive way to associate specific genomic variants to their graph representation. With VRPG and its reference-based projection and assembly path highlighting feature, this is very straightforward. In Figure 3, we exemplified how different types of genomic variants from a query genome relative to the reference genome will be depicted by VRPG in the context of pangenome graph (Figure 3). As VRPG sequentially depicts nodes representing the reference genome according to their actual genomic coordinates along the center line, any highlighted query genome path that deviates this center line implies the occurrence of one or more genomic variants. The direction of the path reflects the connecting order from one node to another, which is especially useful when identifying directional variants such as inversions. The path will also be thickened if the highlighted genome traverses the path more than once, which implies the occurrence of duplications.

| Variant type | Linear representation | Graph representation in VRPG |

Figure 3. VRPG visualization for different types of genomic variants. For different types of genomic variants such as (A) Polymorphism, (B) Insertion, (C) Deletion, (D) Inversion, (E) Duplication, and (F) Duplication with Polymorphism, their graph representations in VRPG are depicted with path highlighting for the reference and query genome respectively.

Application demonstration 1: visualizing pangenome graph derived from 163 yeast genome assemblies.

To demonstrate the application of VRPG in real world examples, we set up a dedicated webserver (https://www.evomicslab.org/app/vrpg/) to visualize reference pangenome graphs derived from 163 budding yeast genome assemblies. Here we employed Minigraph to construct a pangenome graph using the *Saccharomyces cerevisiae* reference assembly panel (ScRAP) that we recently assembled [15]. This yeast pangenome graph consists of 37,062 nodes and 52,756 edges, with a total length of 2,7190,479 bp.

Based on this yeast pangenome graph, we used VRPG to visualize a famous flip/flop inversion region on the chromosome XIV (chrXIV) of the *S. cerevisiae* genome. This flip/flop inversion region is flanked by two 4.2-kb inverted repeat (IR) regions and remains polymorphic in *S. cerevisiae* and its sister species in the genus *Saccharomyces* [16]. For example, within *S. cerevisiae*, our previous study revealed that the Sake strain Y12 shared conserved synteny with the *S. cerevisiae* reference strain S288C within this region whereas the North American strain YPS128 shows an inverted form relative to S288C within this region instead [1] (Figure 4A). In accordance with this prior knowledge, by enabling the genome path highlight feature, we can recapture such polymorphic inversion with VRPG in the pangenome graph. As illustrated by VRPG, both S288C and Y12 reveal a simple linear assembly-to-graph path through the nodes along the central line, suggesting their reference-like sequence structure in this region (Figure 4B and 4C). In contrast, YPS128 show an S-shape assembly-to-graph path in the flip/flop region, which implies the existence of an inverted sequence structure (Figure 4D).

Figure 4. VRPG visualization for the chromosome XIV (chrXIV) flip/flop region in the yeast pangenome graph. (A) The genome sequence and synteny comparison among S288C, Y12, and YPS128 for the chrXIV flip/flop region, with the red and blue shades representing different degrees of sequence similarity. (B-D) VRPG visualization for the yeast pangenome

graph correspond to the query reference coordinate of chrXIV:569857-602365 with the genome path of S288C (B), Y12 (C), and YPS128 (D) highlighted respectively.

Application demonstration 2: visualizing pangenome graphs derived from 90 human genome assemblies.

As a further proof for VRPG's versatility and scalability, we retrieve the human pangenome graphs generated by the Human Pangenome Reference Consortium (HPRC) based on 90 human genome assemblies [17] and visualized them via our VRPG demonstration webserver (https://www.evomicslab.org/app/vrpg/). Starting with the same input genome set, HPRC built three human pangenome graphs with Minigraph, Minigraph-Cactus, and PGGB respectively. The HPRC human pangenome graphs built by Minigraph consists of 391,950 nodes and 566,204 edges, with a total length of 3,198,196,033 bp. In comparison, the total node and edge numbers of graphs built by Minigraph-Cactus (81,415,956 nodes and 112,955,105 edges) and PGGB (110,884,673 nodes and 154,756,169 edges) are substantially larger as small variants such as SNV and INDELs are fully considered by Minigraph-Cactus and PGGB during their graph construction whereas Minigraph predominantly consider larger variants such as SVs.

For the demonstration, we used VRPG to visualize an inversion locate in the intron 32 of the *DSCAM* gene[18] (Figure 5). This inversion is mediated by two inverted 6.0-kb L1 elements, forming a structure much like the yeast chrXIV flip/flop inversion described above (Figure 5A). *DSCAM* gene belongs to the immunoglobulin superfamily of cell adhesion molecules (Ig-CAMs) and functions in central and peripheral nervous system development. *DSCAM* gene is a clinically relevant gene with significant association with Down syndrome (DS) and congenital heart disease (DSCHD) [19,20]. This *DSCAM* inversion is segregate between the current human reference genome GRCh38 and the telomere-to-telomere (T2T) assembly CHM13 (Figure 5B). When highlighting the path of the CHM13 genome assembly, this inversion is clearly visible in the pangenome graph built by Minigraph (Figure 5C). For the pangenome graph built by Minigraph-Cactus and PGGB, the graph layouts are much more complex due to the incorporation of small variants (i.e., variants < 50bp) by Minigraph-Cactus and PGGB. This is where the layout simplification function of VRPG can help, which serves to generate a much

simpler graph layout by hiding small variant related nodes. We found the *DSCAM* inversion in CHM13 popped up clearly with a characteristic S-shape path in the simplified Minigraph-Cactus pangenome graph (Figure 5D). In the PGGB graph, the pattern is more complex even with layout simplification, showing loop-like structure in the inversion region instead, which highlights a methodological difference between PGGB and the other two graph builders (i.e., Minigraph and Minigraph-Cactus) in graph construction when haplotype collapsing is invoked.

A human *DSCAM* gene exon 31-33 (chr21: 40,010,001-40,045,000)

C HPRC 90 human genome graph built by Minigraph

genome path highlight: CHM13

without layout simplification

with layout simplification for non-ref nodes

D HPRC 90 human genome graph built by Minigraph-Cactus

genome path highlight: CHM13

without layout simplification

with layout simplification for non-ref nodes

E HPRC 90 human genome graph built by PGGB

genome path highlight: CHM13

without layout simplification

with layout simplification for non-ref nodes

Figure 5. VRPG application demonstration with the human pangenome graphs for the *DSCAM* inversion. (A) The UCSC genome browser view for the *DSCAM* exon 31-33 region at chr21:40010001-40045000 with annotation tracks for chromosome ideogram, gene structure, repetitive sequence features. (B) The genome sequence and synteny comparison between the human reference genome GRCh38 and the telomere-to-telomere (T2T) genome CHM13 for the *DSCAM* exon 31-33 region, with the red and blue shades representing different degrees of sequence similarity. (C-E) VRPG visualization for the *DSCAM* inversion in the human pangenome graphs derived from Minigraph (C), Minigraph-Cactus (D), and PGGB (E), with the genome path of CHM13 highlighted respectively.

Discussion

As genome sequencing technologies keep progressing towards longer read length and higher per-base accuracy, generating reference-quality genomes at a population scale is becoming increasingly affordable [21]. Along with this tread, researchers began to develop new computational frameworks to accommodate and analyze such growing collection of high-quality genomes with better efficiency. Pangenome graph serve as a compact yet extendable data structure that describes population-level genetic diversity at both base and structure level via a graph representation [4]. This is a highly active research field with new tools and applications rolling out very quickly. One can envision that many genomics analyses that currently relies on conventional linear reference genome will eventual be performed based on pangenome graphs in near future. A better understanding of how different layouts and topologies of pangenome graphs correspond to the actual genomic variation in the population is of critical for correctly interrogating and interpretating pangenome-graph-based analysis results. In this study, we developed VRPG, a web-based interactive pangenome graph viewer with full scalability, capable of rendering complex pangenome graphs derived from hundreds of genome assemblies. In addition to intuitive graphical visualization, VRPG also provides biologically relevant features that directly reflects the sequence and copy number variation of the genome assemblies that comprise the graph. As demonstrated with real world examples based on yeast and human pangenome graphs, we expect VRPG to become a highly useful visualization tool to help researchers to explore the full power of pangenome graph.

Conclusions

Here we present VRPG, a web-based pangenome graph viewer. In addition to enabling interactive visualizing and analyzing pangenome graph on the fly, VRPG also shines in providing an intuitive interface that connects linear genome assemblies and their embedded genomic variants to the pangenome graph.

Availability

VRPG is free for use under the MIT license, with the source code available at https://github.com/codeatcg/VRPG. The real-case demonstration of VRPG on yeast and human pangenome graph is hosted at https://www.evomicslab.org/app/vrpg/ .

Materials and Methods

Naming scheme of input assemblies

The naming scheme of input assemblies in VRPG follows a relaxed version of the PanSN prefix naming specification (https://github.com/pangenome/PanSN-spec). The input genome assembly identifier consists of three parts: sample tag, delimiter, and haplotype tag. The sample tag and haplotype tag can be any strings consist of letters and/or numbers, while the delimiter can be any character (e.g., "#" or ":").

Input pangenome graph specification

In a pangenome graph, a node represents a directed genomic segment while an edge represents the relative order and direction of the two inter-connected nodes. VRPG natively works with pangenome graph files in the rGFA format, which can be straightforwardly constructed using Minigraph[6]. Compared with pangenome graph encoded in other formats, the rGFA-formatted pangenome graph inherently tracks the origin of each node in terms of its location and direction from the input assembly, which comes handy when analyzing and interpretating the corresponding pangenome graph. In addition, VRPG offers further support for genome graphs encoded in the GFAv1 format with a pre-shipped sub-module named gfa2view, which can transform the GFAv1 format into an rGFA-like format that encodes segment coordinate information as well.

GFAv1 to rGFA-like transformation

GFAv1 is a widely used pangenome graph format. Unlike the rGFA-formatted pangenome graph, there is no pre-defined reference genome for establishing the coordinate system when constructing the pangenome graph in the GFAv1 format. Therefore, to accommodate GFAv1-formated graph with VRPG, a user defined reference genome is required. When there are multiple copies of highly similar segments (e.g., in the case of segmental or tandem duplication) in a given genome assembly, some pangenome graph builders such as PGGB tends to collapse them into a single node, which is more efficient in compressing genomic information but also breaks the linearity of the reference genome coordinate system. To walkaround this challenge, the gfa2view module of VRPG will traverse the reference path to find the collapsed nodes, which are nodes been traversed for two or more times and insert the corresponding "shadow nodes" and their associated edges into the graph to restore the original reference coordinates for the given node. In this way, the reference genome rendered by VRPG by sequentially chaining through reference nodes still keeps linearity and the genomic regions collapsed by the original pangenome graph builder (e.g., PGGB) can still be traced with VRPG's path highlighting function. The resulting graph with these added shadow nodes is recorded in a rGFA-like format, which can be used for VRPG as the input file for visualization.

Node and edge rendering

Representative genomic segments are denoted by graph nodes and further illustrated as colored blocks in the view window. For nodes representing the reference genome (pre-defined when building the reference pangenome graph), their block sizes are generally proportional to the actual size of the corresponding genomic segments. For nodes representing non-reference assemblies, their corresponding blocks can only roughly reflect the actual segment sizes. If the segment size (denoted as "S" herein) is smaller than 2 kb, the node will be illustrated as a rectangular block. If the segment size is greater than 2 kb, the node will be represented by a curved block where the corner count of the curved block is proportional to the multiples of 2-kb determined by S. The connections between different genomic segments are represented by graph edges and further illustrated as directed lines. For the cleanness and efficacy of rendering, additional graph simplification algorithms are further applied to trim off those peripheral nodes that are far away from the reference nodes (e.g., when traversing depths >= 10) as well as

optionally to hide small nodes (e.g., those representing genomic segments that are < 50 bp) in the graph. These features are especially helpful when visualizing genome graphs built by Minigraph-Cactus and PGGB where all base-level variants such as SNV and INDEL are coded as nodes.

Efficient access to the graph

VRPG implemented a block index system to enable quick access to the subgraph corresponding to any given region along the pre-defined reference genome. The reference genome was first subdivided into blocks with each block containing 2000 reference nodes. For each block, a breadth-first search algorithm was implemented to find all edges and non-reference nodes associated with the reference nodes within the corresponding block and a block index corresponding to these edges and nodes was created. To reduce the search space and accelerate the indexing process, VRPG only uses edges that have no joins with all other chromosomes/scaffolds/contigs during indexing. Based on the indexed nodes and edges, an ordered block index array for each assembly path was created. Based on such block index system, VRPG can efficiently locate the subgraph associated with the query region for rendering.

Yeast reference pangenome graph construction

The yeast reference pangenome graph was constructed by this study. This graph was built upon 163 yeast genome assemblies from 142 strains, with some heterozygous/polyploid strains having both phased and collapsed assemblies. Briefly, we took the *Saccharomyces cerevisiae* reference genome (version: R64-1-1; denoted as SGDref) retrieved from *Saccharomyces* genome database (SGD; https://www.yeastgenome.org/) as well as 162 assemblies from our recently released *Saccharomyces cerevisiae* Reference Assembly Panel (ScRAP) [15] to construct reference pangenome graph. Minigraph [6] was used for this graph construction with the command 'minigraph -cxggs -l 5000'. With the SGDref as the reference genome, we incrementally added those 162 ScRAP assemblies into the graph according to their phylogenetic distances to SGDref. The phylogenetic distances employed here were extracted from the phylogenetic tree of these 163 input genomes built upon their concatenated 1-to-1 orthologous gene matrix (See [15] for details). Regarding the haplotype tag, for the yeast reference pangenome graph, we used "HP0" to denote haplotypes of haploid or homozygous diploid strains, while using "collapsed", "HP1", and "HP2" to denote collapsed, or the two phased haplotypes of heterozygous diploid strains.

Human reference pangenome graph construction

Human Pangenome Reference Consortium (HPRC) constructed three human pangenome graphs using Minigraph, Minigraph-Cactus, and PGGB respectively based on 90 genome assemblies from 46 samples [17]. Aside from the classic (GRCh38) and T2T (CHM13) human reference genome assemblies, the other 44 samples all have two fully phased genome assemblies. We retrieved the human Minigraph-Cactus and PGGB pangenome graph from the HRPC's Github page (https://github.com/human-pangenomics/hpp_pangenome_resources) and downloaded a slightly updated version of the Minigraph pangenome graph provided by Heng Li (https://zenodo.org/record/6983934#.Y767A3ZByUk)[22]. For these human reference pangenome graphs, "0" was used to denote haplotypes of haploid or collapsed samples while "mat" and "pat" were used to denote the maternal and paternal haplotypes of the phased diploid samples.

Software implementation and web deployment

The backend of VRPG is implemented in C++ and Python3 based on the Django framework, while both D3.js (https://github.com/d3/d3) and WebCola (https://github.com/tgdwyer/WebCola) were employed at the frontend for data visualization. Bootstrap and jQuery were further used for interactive query and rendering. The demonstration webserver is deployed via an Alibaba Simple Application Server with 2 CPU, 4 Gb RAM, and 80 Gb ESSD data storage.

Acknowledgements

We are grateful to Dr. Jing Li for valuable feedback on the manuscript.

Funding

This work is supported by National Natural Science Foundation of China (32070592 to J.-X. Y.), Guangdong Basic and Applied Basic Research Foundation (2022A1515010717 to J.-X. Y.), and Guangdong Pearl River Talents Program (2019QN01Y183 to J.-X. Y.).

Conflict of Interest: none declared.

References

1. Yue J-X, Li J, Aigrain L, Hallin J, Persson K, Oliver K, et al. Contrasting evolutionary genome dynamics between domesticated and wild yeasts. Nature Genetics. 2017;49: 913–924. doi:10.1038/ng.3847

2. Jiao W-B, Schneeberger K. Chromosome-level assemblies of multiple Arabidopsis genomes reveal hotspots of rearrangements with altered evolutionary dynamics. Nat Commun. 2020;11: 989. doi:10.1038/s41467-020-14779-y

3. Nurk S, Koren S, Rhie A, Rautiainen M, Bzikadze AV, Mikheenko A, et al. The complete sequence of a human genome. Science. 2022;376: 44–53. doi:10.1126/science.abj6987

4. Eizenga JM, Novak AM, Sibbesen JA, Heumos S, Ghaffaari A, Hickey G, et al. Pangenome Graphs. Annual Review of Genomics and Human Genetics. 2020;21: 139–162. doi:10.1146/annurev-genom-120219-080406

5. Paten B, Novak AM, Eizenga JM, Garrison E. Genome graphs and the evolution of genome inference. Genome Res. 2017;27: 665–676. doi:10.1101/gr.214155.116

6. Li H, Feng X, Chu C. The design and construction of reference pangenome graphs with minigraph. Genome Biology. 2020;21: 265. doi:10.1186/s13059-020-02168-z

7. Hickey G, Monlong J, Ebler J, Novak A, Eizenga JM, Gao Y, et al. Pangenome Graph Construction from Genome Alignment with Minigraph-Cactus. bioRxiv; 2023. p. 2022.10.06.511217. doi:10.1101/2022.10.06.511217

8. Garrison E, Guarracino A, Heumos S, Villani F, Bao Z, Tattini L, et al. Building pangenome graphs. bioRxiv; 2023. p. 2023.04.05.535718. doi:10.1101/2023.04.05.535718

9. Garrison E, Guarracino A. Unbiased pangenome graphs. Bioinformatics. 2022; btac743. doi:10.1093/bioinformatics/btac743

10. Wick RR, Schultz MB, Zobel J, Holt KE. Bandage: interactive visualization of de novo genome assemblies. Bioinformatics. 2015;31: 3350–3352. doi:10.1093/bioinformatics/btv383

11. Gonnella G, Niehus N, Kurtz S. GfaViz: flexible and interactive visualization of GFA sequence graphs. Bioinformatics. 2019;35: 2853–2855. doi:10.1093/bioinformatics/bty1046

12. Beyer W, Novak AM, Hickey G, Chan J, Tan V, Paten B, et al. Sequence tube maps: making graph genomes intuitive to commuters. Bioinformatics. 2019;35: 5318–5320. doi:10.1093/bioinformatics/btz597

13. Yokoyama TT, Sakamoto Y, Seki M, Suzuki Y, Kasahara M. MoMI-G: modular multi-scale integrated genome graph browser. BMC Bioinformatics. 2019;20: 548. doi:10.1186/s12859-019-3145-2

14. Guarracino A, Heumos S, Nahnsen S, Prins P, Garrison E. ODGI: understanding pangenome graphs. Bioinformatics. 2022;38: 3319–3326. doi:10.1093/bioinformatics/btac308

15. O'Donnell S, Yue J-X, Saada OA, Agier N, Caradec C, Cokelaer T, et al. 142 telomere-to-telomere assemblies reveal the genome structural landscape in Saccharomyces cerevisiae. bioRxiv; 2022. p. 2022.10.04.510633. doi:10.1101/2022.10.04.510633

16. Salzberg LI, Martos AAR, Lombardi L, Jermiin LS, Blanco A, Byrne KP, et al. A widespread inversion polymorphism conserved among Saccharomyces species is caused by recurrent homogenization of a sporulation gene family. PLOS Genetics. 2022;18: e1010525. doi:10.1371/journal.pgen.1010525

17. Liao W-W, Asri M, Ebler J, Doerr D, Haukness M, Hickey G, et al. A draft human pangenome reference. Nature. 2023;617: 312–324. doi:10.1038/s41586-023-05896-x

18. Audano PA, Sulovari A, Graves-Lindsay TA, Cantsilieris S, Sorensen M, Welch AE, et al. Characterizing the Major Structural Variant Alleles of the Human Genome. Cell. 2019;176: 663-675.e19. doi:10.1016/j.cell.2018.12.019

19. Grossman TR, Gamliel A, Wessells RJ, Taghli-Lamallem O, Jepsen K, Ocorr K, et al. Over-Expression of DSCAM and COL6A2 Cooperatively Generates Congenital Heart Defects. PLOS Genetics. 2011;7: e1002344. doi:10.1371/journal.pgen.1002344

20. Liu H, Caballero-Florán RN, Hergenreder T, Yang T, Hull JM, Pan G, et al. DSCAM gene triplication causes excessive GABAergic synapses in the neocortex in Down syndrome mouse models. PLOS Biology. 2023;21: e3002078. doi:10.1371/journal.pbio.3002078

21. De Coster W, Weissensteiner MH, Sedlazeck FJ. Towards population-scale long-read sequencing. Nat Rev Genet. 2021;22: 572–587. doi:10.1038/s41576-021-00367-3

22. Li H. Minigraph pangenome graphs for HPRC year-1 samples. 2022 [cited 20 Jan 2023]. doi:10.5281/zenodo.6983934

A

VRPG rendered graph with graph node selection

B

VRPG rendered graph with graph edge selection

C

VRPG rendered graph with genome path highlighting

Segment Name:

32871

Segment Source:

Assembly: CPS#collapsed

Chr: chrl

Start: 9476

End: 15405

Segment mapping depth:

Assembly	Depth
AAB#HP0	0
AAC#HP1	0
AAC#HP2	0
AAR#HP0	0
ABA#HP0	1
ABH#HP0	0

Highlight ADE#HP0

Variant type	Linear representation	Graph representation in VRPG

A human *DSCAM* gene exon 31-33 (chr21: 40,010,001-40,045,000)

UCSC browser

B

exon 33

GRCh38

4.3 kb

exon 32   exon 31

CHM13

1 Kb   100%   98.0%

C HPRC 90 human genome graph built by Minigraph

genome path highlight: CHM13

without layout simplification   with layout simplification for non-ref nodes

D HPRC 90 human genome graph built by Minigraph-Cactus

genome path highlight: CHM13

without layout simplification   with layout simplification for non-ref nodes

E HPRC 90 human genome graph built by PGGB

genome path highlight: CHM13

without layout simplification   with layout simplification for non-ref nodes