In silico Antibody-Peptide Epitope prediction for Personalized cancer therapy

Ivan Jacobs [1]*, **Lim Chwee Ming** [2], **Jamie Mong** [3],**Maragkoudakis Emmanoil** [4],
Nishant Malik [5]

[1] *Research and Development, AI4U S.A., Luxembourg, Luxembourg*
[2] *Department of Otolaryngology-Head and Neck Surgery,National University Hospital, Singapore, Singapore*
[3] *Biodevices and Diagnostics, Institute of Bioengineering and Nanotechnology, Singapore 138669, Singapore*
[4] *Department of Informatics, Ionian University, 49100 Corfu, Greece*
[5] *School of Mathematical Sciences, Rochester Institute of Technology, Rochester, NY, USA.*

Correspondence*:
Corresponding Author
ivan.jacobs@ai4u.ai

ABSTRACT

The human leukocyte antigen (HLA) system is a complex of genes on chromosome 6 in humans that encodes cell-surface proteins responsible for regulating the immune system. Viral peptides presented to cancer cell surfaces by the HLA trigger the immune system to kill the cells, creating Antibody-peptide epitopes (APE). This study proposes an in-silico approach to identify patient-specific APEs by applying complex networks diagnostics on a novel multiplex data structure as input for a deep learning model. The proposed analytical model identifies patient and tumor-specific APEs with as few as 20 labeled data points. Additionally, the proposed data structure employs complex network theory, and other statistical approaches that can better explain and reduce the black box effect of deep learning. The proposed approach achieves an F1-score above 80% on patient and above 90% on tumor specific tasks and minimizes training time and the number of parameters.

Keywords: complex networks, machine learning, deep learning, personalized medicine, cancer, tumor, antibody-peptide,epitope

1 INTRODUCTION

The human leukocyte antigen (HLA) system or complex is a complex of genes on chromosome 6 in humans which encode cell-surface proteins responsible for the regulation of the immune system. The HLA system is also known as the human version of the major histocompatibility complex (MHC) is found in many animals.

HLA genes are highly polymorphic, which means that there are thousands of different forms of these genes called alleles, allowing them to fine-tune the adaptive immune system. The proteins encoded by certain genes are also known as antigens, because of their historic discovery as factors in organ transplants.

As shown in Figure 1 HLA's proteins present viral peptides from inside the cell to the surface of the cell.
For example, if the cell is infected by a virus or is cancerous, the HLA system brings abnormal fragments,
called peptides, to the surface of the cell so that the cell can be destroyed by the immune system.

Predicting the specific HLA peptide combination that will present the peptide to the surface of the
cell, permits the creation of a treatment that will trigger the human immune system to destroy the cell.
Specifically, in cancer this ability is extremely important, given that cancer is highly mutagenic with tumor
and patient specific mutations. This means that patients with same tumor type will have different mutations
that results in different reactions to the same treatment.

Advances in Deoxyribonucleic acid (DNA) sequencing, Messenger Ribonucleic acid (mRNA) vaccines
and high computational power gives us the ability to work towards patient specific therapy. This approach,
called personalized mRNA-based antitumor vaccine, visualized in Figure 2, is bound to play a major role
in the future.

The approach is meant to trigger an antitumor immune response in patients by challenging them with
mRNAs encoding tumor-specific antigens (1). These mRNAs can be directly injected as naked RNA or
loaded into patient-derived dendritic cells.

In this work we propose to extend the approach with additional laboratory and analytical optimization
steps. Concretely DNA sequenced from the patient is used to select candidate peptides that will result
from gene expression. As the space of possible combinations is huge a subset of potential peptides is
synthesized and their reaction to the patient's specific HLA alleles is tested by applying enzyme-linked
immunospot (ELISpot) assay. An enzyme-linked immunospot (ELISpot) assay (2), shown in Figure 3, is a
highly versatile and sensitive technique that is used for qualitative and quantitative measurement of the
cytokine-secreting cells at the single-cell level. (3)

In this assay, involving culturing cells on a surface on which a reagent (e.g., a specific capture antibody)
is immobilized. Secreted proteins by the cells, such as cytokines, will be captured by the specific antibodies
on the surface. Post appropriate incubation time, cells are washed, and the secreted molecule is identified
by applying a detection antibody. The addition of a substrate produces colored, fluorescent, or luminescent
reaction (e.g., visible spots on the surface). Each spot corresponds to an individual cytokine-secreting cell
and is indicative of the concentration of the reactants. The generated data permits to fine tune an analytical
approach to a specific patient's and tumor's mutations and reevaluate the peptides sequences with the
purpose of selecting the optimal HLA allele-peptide combination. Once a subset of peptides is identified a
mRNA vaccine is created that will force the body to trigger an immune response and destroy cancerous
cells. The mRNA vaccine creation and evaluation are outside the scope of this work. The purpose of this
work is to identify an analytical approach that can predict HLA-peptide interaction. With this effort we
hope to provide a framework that gives the ability to select and optimize personalized analytical methods
from a wide range of possibilities as graph theory, machine learning, deep learning, meta-learning and
machine learning on graphs and leverage on high performance computing with graphic processing unit
(GPU) acceleration.

2 RELATED WORK

59 Epitope prediction is an important approach in tumor immunology and immunotherapy. The main classes
60 of importance in the HLA molecules are the are Class I and II molecules, that present epitopes to CD8[+]
61 T cells and CD4[+] T cells respectively. Methods for assessing immunogenicity are MS-based MHC-I
62 peptide binding prediction and immunogenicity verification by specific response assays (4, 5, 6). A

plethora of analytical approaches have been applied for such purposes distinguishing two main type of approaches, allele-specific and pan-specific. Where the former trains one model for every MHC-I allele (7, 8, 9, 10, 11, 12) and the latter considers them to be as one and trains a global model together on both (13, 14, 15, 16). Methods with the highest achieved accuracy use data from The Immune Epitope Database (17). In the recent years, the high rate of deep learning research resulted in a variety of deep learning based methods proposed by researchers (12, 13, 18, 19, 20). A number of approaches combine graph theory principles with deep learning or deep learning on graphs (21, 22, 23, 24) in order to detect interactive propensities embedded in HLA-peptide pairs.

Even though high affinity in an MHC-peptide complex tends to be associated with immune responsiveness, it is not sufficient to define immunogenicity. The existing analytical models are lacking in several aspects that are influential to immunogenicity such as the rate of expression, failure to represent sophisticated dynamics in molecular systems and abundance of proteins. A number of top-ranking analytical approaches regularly falsely predict neoantigens (25, 26, 27). Hence, the need to better comprehend immune responsiveness based on MHC-peptide complex and dynamic structures and interaction in the context of a complex dynamical system environment is key for peptide-based personalized vaccines.

3 APPROACH

To compare and predict systems interactions and behavior we will look at measures and metrics that these networks express. Calculating and assigning these metrics for every individual system permits us to create a data set that can be used in statistical, machine and deep learning analysis approaches. Our approach takes the network measures as input and makes a binary decision whether a system composed of multiple patient specific peptides and HLAs will result in presentation of viral epitopes (in known EBV driven cancer such as nasopharyngeal cancer) on the surface of the cancer cells. As shown in Figure 4 ,the work can be divided into the following phases: (1) Data Collection, (2) ELISpot assay, (3) Structures and Measurements generation, (4) Analytical approach evaluation.

3.1 Data

The data, originally published in a study on patient-derived nasopharyngeal cancer (NPC) Organoids for Disease Modeling (28), consists of eighteen NPC tissue samples obtained from patients who underwent biopsy or surgical resection at the National University Hospital Singapore between March 2015 and April 2019. The datasets presented in (28) can be found in online repositories. The names of the repository/repositories and accession number(s) can be found at: NCBI Gene Expression Omnibus.

Specimen collection and experimental use for the study has been approved by the Institutional Review Board of National Healthcare Group (DSRB Reference: 2015/00098-SRF0004). One part of the tissue collected from patients were immediately transferred to RPMI-1460 media with HEPES and L-Glutamine and 5X antibiotic/antimycotic and 5 µg/ml Metronidazole at 4°C. Other part was fixed in 10% neutral buffered formalin (10% NBF) for routine Hematoxylin and Eosin (HI&E) staining and remaining tissues were snap frozen in liquid nitrogen for DNA and RNA extraction. As a proof of our methodology, we used mRNA and DNA sequences of 2 patients where one where sequences areas of mutation have been selected and potential peptide candidates have been identified. With patient one diagnosed with lung cancer and patient two with nasopharyngeal cancer.

Additionally, enzyme-linked immunospot (ELISpot) assays have been performed with the corresponding
patient specific HLA alleles and peptides producing the quantitative measurements of the immune response
(i.e., values we wish to predict).

In order to show the ability of the model to perform well on tumor specific tasks, we apply the analytical
approach on the Cancer Epitope Database and Analysis Resource (CEDAR) (29) containing 1,345,569
Peptidic Epitopes, 116,026 T Cell Assays, 855,280 B Cell Assays, 4,030,973 MHC Ligand Assays,1,588
Epitope Source Organisms, 652 Restricting MHC Alleles and 4,452 References, originating from cancer
related studies.

3.1.1 Data overview

110 The produced data's attributes as listed in table 1 will give us the ability to create the data structures that
111 represent the relationships between HLA alleles and peptides. This data structure will give us better insights
112 and permit to apply analytical approaches to predict HLA-peptide interactions expressed as discretized
113 class representing ranges of the numbers of matched blood mononuclear cells (PBMC's).

3.1.2 Generated Molecular Structures

A peptide, as illustrated in figure 5, is a short chain of amino acids (typically 2 to 50) linked by chemical
bonds (called peptide bonds). The HLA cell-surface protein, as illustrated in figure 6, is a chain of amino
acids that is responsible to regulate the immune system. To understand HLA-peptide interactions we need
to understand how the peptide is binding, as illustrated in Figure 7, to the HLA.

The HLA-peptide interaction is dependent of the amino acid's atoms chemical reactions that will fall
close enough in 3-dimensional space. During phase 2 of our work, as shown in Figure 8, we generate an
in-silico representation of the molecular structures composing a system i.e., the patient specific peptides
and HLAs in a system.

3.2 Generated Network Structures

In order to study the diverse types of relations and interactions that exist between the components we
chose a network representation with a notion of layers. This type of networks is called multiplex networks
where a node corresponds to a "physical object," while node-layer pairs are different instances of the same
object.

For instance a node could represent an online user, while node-layer pairs would represent different
accounts of the same user in different online social networks; or a node could represent a social actor,
while node-layer pairs would represent different social roles (friend, worker, family member) of the same
social actor; or a node could stand for a location in a transportation network, while node-layer pairs would
represent stations of different transportation modes (e.g., streets, highways, and subways).

The connection between nodes and node-layer pairs is given by the notion of supra-nodes: i.e., cliques in
the supra-graph formed by node-layer pairs that are instances of the same object. To correctly represent a
physical object in the different layers of the multiplex we break down the peptides to amino acids and the
amino acids to their smallest component atoms and their connections bonds. The layers coordinate, atom,
monomer, polymer, complex and system are introduced. The Coordinate layer represents the 3-dimensional
coordinates of every atom present in the system. The Atom layer, as shown in Figure 9, is the layer that
represents the atoms and their bonds that construct objects in the monomer layer e.g., amino acid.

The Monomer layer, as shown in Figure 10, represents the objects of type monomer that are a molecule
of any of a class of compounds, mostly organic, that can react with other molecules to form very large
molecules, or polymers.

The Polymer layer, as shown in Figure 11, represents the objects of type polymer. Polymer is any object
of a class of natural or synthetic substances composed of very large molecules, called macromolecules,
which are multiples of monomers.

The Complex layer, as shown in Figure 12, represents polymers that form a complex by binding to each
other e.g., peptide binds to an HLA to form a complex as shown in Figure 5.

The System layer represents the totality of complexes that exist in an ELISpot assay and is representative
of multiple HLA-peptide complexes. One system could be represented as shown in Figure 13 where we are
omitting the coordinates layer.

3.3 Networks Measures and Metrics

152 After generating the graph structures, we calculate network measures on each system. The goal is to
153 select measures such that the analytical model would be able to identify patterns in their values to allow
154 them to distinguish between the two classes of systems i.e., systems that will produce an antibody-peptide
155 epitope and systems that will not produce an antibody-peptide epitope. The used network measures are
156 discussed in detail Appendix Network Measures

4 MODEL TRAINING

4.1 Model

We define the prediction of an antibody-peptide epitope as a binary classification problem. Our proposed
model takes as input a set of complex networks measures and uses them as features to learn patterns and
distinguish between systems that are more likely or less likely to produce an antibody-peptide epitope.
Since we seek to discover latent features in the complex networks that represent systems, we choose to rely
on deep learning, discussed in Appendix Deep Learning.

Our U-Net with self-attention (UNET-ATT) takes the U-net with attention deep learning approach
proposed in (29) consisting of blocks of convolutions and deconvolutions, where a convolution block
consists of 1 Dimensional Convolutional layer followed by a Max Pooling layer and deconvolution blocks
consisting of 1 Dimensional Deconvolutional layer. The visualization of this architecture can be found in
Figure 14.

The input of the UNET-ATT is a vector with 22 complex networks measures values that undergo
batch normalization through introducing additional layers, to stabilize their distribution and control their
mean and variance. The batch normalized inputs flow into a convolution that reduces the input space.
Convolutional layers extract higher dimensional representations by processing local features layer wise.
Resulting in separation of complex network measurements in a high dimensional space based on their
semantics. The layer output is produced by sequential application of a linear transformation followed by
non-linear activation function. We apply the Rectified Linear Unit (ReLU) as non-linear activation function
for the convolution layers. To refine the weighting of the latent features, we apply a max-pooling layer. The
max pool layer considers the most prominent feature values by eliminating non-prominent features and
essentially reducing the feature space.

The input to a deconvolution block is the output of the previous deconvolution gated through an attention
gate together with the output of a corresponding convolution block. The deconvolution layer performs the
opposite transformation to a convolution layer, by applying transformation with the layer parameters to
augment the feature space. By minimizing the training objective, e.g., cross entropy loss, the weights of the
layer are adjusted as such that it learns to boost important features and makes them more prominent in the
network.

Attention gates are highlighting salient features that are flown through the skip connection see Figure
14. Information extracted from previous layers is transformed through gating to disambiguate irrelevant
activations in skip-connections. This is applied before the concatenation in order to merge exclusively
important features.

The applied randomizing training procedures risk to introduce bias into the model by overpredicting
classes that are repeatedly fed into the model during training. To avoid this potential overfitting, we
introduce a dropout layer that hides a random subset of nodes at each training iteration.

We extend (30) by using the output of the last deconvolution block, a dense representation of non-
observable feature maps of the inputted complex networks measures values, as input to the fully connected
dense layer in which each node of the layer applies transformation to output from all nodes from the
previous layer. The fully connected layer produces the classification values by producing a probabilistic
decision whether the system will produce an antibody-peptide epitope given the initial inputs i.e., the
complex networks measures of the system. The parameters of the UNET-ATT are learnt by minimizing the
error, e.g., cross-entropy loss using stochastic gradient descent (SGD).

4.2   Datset

To prepare the dataset, we discretize PBMC values and label the ELISpot assays with "1" if the value
is above a threshold and is likely to produce an antibody-peptide epitope and "0" if the value is beneath
it. Our feature vector consists of the 22 network measure values, calculated for the positive and negative
examples.

For the tumor specific task, we group the CEDAR data on the tissue type of the Antigen presenting cells
and take epitopes into account with a length between 8 and 25 amino acids, originating from homo sapiens
and being part of MHC class I.

5   EVALUATION AND DISCUSSION

This section describes our empirical study aimed to evaluate the proposed approach, as well as its main
results. We formulated the following research questions:

RQ1: To what extent is the UNET-ATT model able to correctly predict that a system composed of
multiple patient and tumor specific peptides and HLAs or T cell receptors (TCRs) will result in presentation
of viral epitopes on the surface of the cancer cells in comparison with other models.

RQ2: To what extent are the models personalized to the patient.

5.1 RQ1 Correctness

5.1.1 Approach

To address RQ1, we explore the ability of the proposed models to correctly predict if a system composed of multiple patient specific peptides and HLAs will result in presentation of viral epitopes on the surface of the cancer cells. Hence, we train individual models for both patients and compare the performance of Decision tree classifier (DTC), Multi-layer Perceptron classifier (MLPC), Random Forest classifier (RFC), Support Vector Machine (SVM), Naive Bayes classifier (NBC), Logistic Regression classifier (LRC), K-Neighbors Classifier (KNC), U-net with self-attention (UNET-ATT), deep learning on graphs classifier (DLGCL). To evaluate the performance of the algorithms, we use out-of-sample bootstrap validation since this validation technique yields the best balance between the bias and variance in comparison to single-repetition holdout validation (30).

5.1.2 Results

To measure the effectiveness of our various models, 4 metrics were used: recall, precision, F-measure, described in detail in Appendix Evaluation metrics. Precision is the ideal metric to determine the validity of our models and their adequacy in identifying potential systems that will trigger an immune system response. Precision tells the level in which the model was able to correctly identify the systems with high PBMC value to all instances with high PBMC value.

Recall was used, as it allowed us to see the potentially skipped opportunities that the model missed. Utilizing the F-measure statistic, we combined recall and precision into a metric that was able to test the accuracy of the various models. The final metric used to compare the model types was the ROC curve area score, which computes a score from the variability generated by the ROC curve. This metric is useful to show an overall level of model effectiveness, although it summarizes the variability that is shown in the ROC curve. We trained personalized models for patients one and two with their respective data and evaluated them on the unseen data. As shown in Table 2, for the personalized models of patient one, Decision tree classifier, Random Forest classifier, and UNET-ATT performed the best. However, as shown in Table 3, Decision tree classifier and Random Forest classifier did not perform consistently in contrast with UNET-ATT with data from patient two.

We conjecture that a proper conveyance of the topological attributes, measures, and relationships in complex networks require sophisticated feature engineering using neural networks classification strategy rather than traditional machine learning classification models. Since the UNET-ATT, consistently outperforms the other models we opt to choose it as our best candidate.

In order to statistically compare the performance of the models, we apply the McNemar test (31) and the Odds Ratio (OR) effect size, where OR larger than 1 indicates that the first technique outperformed the second.

We ran the statistical tests 10 times and compared the results, as shown in Table 4 and Table 5. To accommodate the fact that we performed multiple comparisons, we adjusted the p-values by applying the Bonferonni correction (32).

In this context we formulate our null hypothesis for each test as: there is no statistically significant difference between the performance of the two algorithms and the alternative hypothesis as: there is a statistically significant difference between the performance of the two algorithms. We adjusted the alpha value to 0.005 to perform the hypothesis test as a 5% significance level.

As we can observe in Table 4 and Table 5, the McNemar test results show that the null hypothesis is
rejected as there are statistically significant differences ($p < 0.5/10$) in the performance of the UNET-ATT
model compared to all the other models. The OR values show that the UNET-ATT model has more chances
to correctly predict that a system will result in presentation of viral epitopes on the surface of the cancer
cells from the other methods.

We further apply the analytical approach on the CEDAR dataset, that contains 1,345,569 tumor related
peptidic epitopes, where we create tumor specific UNET-ATT models by grouping the data based on the
cell tissue type of the antigen presenting cells.

In Table 6, we present the performance metrics of the tumor specific UNET-ATT models trained on
antigen presenting cell tissue type specific data. The UNET-ATT model can generalize with acceptable
F-measure performance on all tissue types, when trained on specific tissue type it archives remarkable
F-measures for Breast and Lung and acceptable for Lymphoid.

5.2   RQ2 Personalized model

5.2.1   Approach

To address RQ2, we apply statistical analysis techniques as Multivariate analysis of variance (MANOVA)
on the network measures to evaluate if they are statistically significantly different per patient. Additionally,
we look at how different network measures correlate with PMBC values per patient. We apply a structure
learning algorithm to the data to learn the structure of the directed acyclic graph (DAG) to analyze the
causality of data features i.e., network measures and the matched PBMC values. Finally, we compare
the performance of personalized models on unseen data from a different patient in order to understand
if models are able to generalize over unseen data from different patients. The applied statistical analysis
techniques are discussed in detail in Appendix Statistical Analysis.

5.2.2   Results

From the performed data exploration on the network measures, we can conclude that data attributes have
a patient specific distribution and correlation. This finding agrees with the general understanding that tumor
mutations and reaction of immune system are patient and tumor specific and that a personalized approach
is required. Additionally, the data exploration shows that network attributes of the molecular structures are
patient and tumor specific and that some of them show correlations with statistical significance with the
produced PMBC values. That indicates that a machine learning approach that relies on these attributes as
input can be applied to produce patient personalized predictions. Finally, we compared the performance of
personalized models on unseen data from a different patient and observed that they do not generalize well
to data from different patients and perform better on unseen data from the same patient.

6   THREATS TO VALIDITY

6.1   Internal and Construct Validity

Our analysis is mostly threatened by the generation of the molecular structures in a system, as wrong
placement of molecular structures in a complex may result in different network measures values. However,
not all network measures will be impacted, and the "skewing" of these network measures values will be
consistent over all the data systems. As for the selection of threshold for the PBMC values such that they
are split into positive and negative systems i.e., systems that produce an antibody-peptide epitope and
systems that don't, this threshold can be modified by domain experts without resulting in a drastic change

of model performance given that the data is well balanced and sampled. The same reasoning can be applied
to choosing to predict more than two classes i.e., splitting the PBMC values in buckets and predicting a
range of PMBC values within which a system would fall.

6.2 External Validity

296   Our analysis was performed on data from 2 patients with the same tumor. However, we cannot claim the
297 generality of our observations to other tumors or all patients with the concrete tumor of our data. Further
298 investigation is needed on data from multiple tumors and more patients to mitigate this threat.

7 CONCLUSION

Predicting the specific antibody-peptide that will be presented to the surface of a tumor cell, is of paramount
importance and permits the creation of personalized treatments that will trigger the human immune
system to destroy the tumor cell. In this study we proposed a novel data structure leveraging on multiplex
networks and derive network measures as attributes leveraging on complex networks theory together with a
deep learning approach for optimal feature engineering and personalized antibody-peptide epitope binary
classification. Our results reveal that machine learning and deep learning models are able to binary classify
antibody-peptide epitopes based on the derived attributes from the proposed data structure.

In particular, the proposed UNET-ATT demonstrates an F-measure of 0.8 and 0.93 for personalized
models for patients one and two respectively. Additionally, the UNET-ATT model consistently outperforms
the other models on both patients in contrast with other models that show different results for different
patients. The proposed UNETT-ATT model can generalize with acceptable F-measures on all tissue types
and can specialize on tumor specific tasks with demonstrated F-measures of 0.92 and 1.0 for Lung and
Breast antigen presenting tissue types respectively.

Additionally, we analyzed the validity of building personalized models and found that data attributes have
a patient specific distribution and correlation. The data exploration shows that network attributes of the
molecular structures are patient and tumor specific and that some of them show correlation with statistical
significance with PMBC values.

Finally, we compared the performance of personalized models on unseen data from a different patient
and observed that they do not generalize well to data from different patients and perform better on unseen
data from the same patient.

These findings agree with the general understanding that tumor mutations and reactions of the immune
system are patient and tumor specific and that a personalized approach is required for optimal result.
However, we need to caution that these findings cannot be generalized to other tumors or even to other
patients with the concrete tumor from our data, given that the sample size is too small. Further investigation
is needed on data from multiple tumors and more patients to mitigate this threat.

8 APPENDIX

8.1 Network Measures

8.1.1 Attribute Assortativity Coefficient Source

Assortativity measures the similarity of connections in the graph with respect to the attribute source.
In the generated multiplex structure, the attribute "source" refers to the unique id of the node the edge
originates from.

8.1.2 Degree Pearson Correlation Coefficient

Measures the degree assortativity of a network i.e., the similarity of connections in the graph with respect
to the node degree. It varies between $-1 \leq r \leq 1$: for $r < 0$ the network is assortative, for $r = 0$
the network is neutral and for $r > 0$ the network is disassortative.

8.1.3 Closeness Centrality

Closeness centrality of a node u is the reciprocal of the average shortest path distance to u
over all $n-1$ reachable nodes.

$$C(u) = \frac{n-1}{\sum_{v=1}^{n-1} d(v,u)} \tag{1}$$

336 where $d(v, u)$ is the shortest-path distance between v and u, and n is the number of nodes that can reach
337 u. Concretely we average the betweenness centrality.

$$\langle c \rangle = \frac{1}{n} \sum_{u=1}^{n} c(u) \tag{2}$$

338 8.1.4 Betweenness Centrality

339 Betweenness Centrality measures the importance of a node based on the number of paths between two
340 other nodes that pass through it. Betweenness Centrality is a guide to the influence nodes have over the
341 flow of information, energy between others. Betweenness Centrality x_i is given by

$$x_i = \sum_{st} n_{st}^i \tag{3}$$

342 where n_{st}^i is the node i that lies on the shortest path from vertice s to t. Concretely we average the
343 betweenness centrality

$$\langle x \rangle = \frac{1}{n} \sum_{i=1}^{n} x_i \tag{4}$$

344 8.1.5 Density

345 Density of a graph is the ratio between the edges present in a graph and the maximum number of edges
346 that the graph can contain. Conceptually, it provides an idea of how dense a graph is in terms of edge

347 connectivity.

$$d = \frac{m}{n\,(n-1)} \tag{5}$$

348 where n is the number of nodes and m is the number of edges in a graph G.

8.1.6 Average Core Hubs

350 Average core hubs is a measure of the average of the degrees of the top-100 hubs in a system:

$$\frac{1}{n} \sum_{i=1}^{100} k_i \tag{6}$$

351 where k is the degree of vertice i.

8.1.7 Average Degree

353 The average degree of a network:

$$\langle k \rangle = 2 \frac{\text{number of edges}}{\text{number of nodes}} \tag{7}$$

354 is related to the density of the network, where in a dense network the average degree grows linearly with
355 the number of nodes, while in a sparse network it grows sub linearly.

8.1.8 Transitivity

357 The fundamental type of relation between nodes in a network is "connected by an edge." If the "connected
358 by an edge" relation were transitive it would mean that if node u is connected to node v, and v is connected
359 to w, then u is also connected to w.

$$T = 3 \frac{\#triangles}{\#triads} \tag{8}$$

360 where "triads" are two edges with a shared vertex and triangles are loops of length three.

8.1.9 Global Clustering Coefficient

362 Clustering coefficient is a measure of the degree to which vertices in a network tend to create tightly knit
363 groups, closed triads:

$$C = \frac{(\text{number of closed paths of length two})}{(\text{number of paths of length two})} \tag{9}$$

364 $C = 1$ implies perfect transitivity, a network whose components are all closed triads. $C = 0$ implies no
365 closed triads. Concretely we apply the Watts and Strogatz defined a clustering coefficient that quantifies
366 the likelihood that two nodes that are connected to the same node are also connected to each other. degree
367 to which vertices in a network tend to create tightly knit groups, closed triads:

$$C = \frac{(\text{number of triangles}) * 3}{(\text{number of connected triples})} \tag{10}$$

368 Concretely we apply the following equation

$$C = \frac{1}{n} \sum_{u=1}^{n} c_u \tag{11}$$

369   where n is the number of nodes and c_u is:

$$c_u = \frac{2T(u)}{deg(u)(deg(u)-1)} \tag{12}$$

370   where $T(u)$ is the number of triangles through node u and $deg(u)$ is the degree of u.

8.1.10   Size largest Component

372   In undirected networks typically exists large components that fill most of the network, while the rest
373   of the network is divided into a lot of small, disconnected components. The size of the largest connected
374   component can be expressed by:

$$S = 1 - e^{-cS} \tag{13}$$

375   introduced by Erdos and Renyi in 1958 where c denotes mean degree or the average of in- and out-going
376   edges. We compute the size of the largest component S of each system and and look at its distribution and
377   correlation with the particular patient and the measured matched PBMC's i.e., ELISpot values.

8.1.11   Average Spectral clustering

A fast approach to separate a network in communities is by applying spectral modularity maximization
by assigning a node to one of two groups communities. If we consider s as a vector in n-dimensional space,
that implies that the vector must point to one of the corners of the n-dimensional hypercube. By creating
a relaxed method where s is aloud to take any value of $|s| = \sqrt{n}$ the form we arrive at a matrix notation
$Bs = \beta s$. Hense the optimal s is on of the eigenvectors of the modularity matrix and β is the corresponding
eigenvalue. We can find which eigenvector by applying

$$Q = \frac{n}{4m}\beta \tag{14}$$

385   Since $s^T s = n$ we can maximize the inner product $s^T u = \sum_i s_i u_i$. The maximum is achieved when $s_i u_i$
386   is positive for all i, which occurs when s_i has the same sign as u_i for all i:

$$s_i = \begin{cases} +1, & \text{if } u_i > 0 \\ -1, & \text{if } u_i < 0 \end{cases} \tag{15}$$

387   This leads to a simple approach; we calculate the eigenvector of ton the modularity matrix corresponding
388   to the highest eigenvalue and assign nodes to communities according to the signs of the elements in this
389   vector. We slightly modify it by assigning zero to the nodes that correspond to negative eigenvalues instead
390   of -1:

$$s_i = \begin{cases} +1, & \text{if } u_i > 0 \\ 0, & \text{if } u_i < 0 \end{cases} \tag{16}$$

391   Then we calculate the average $\frac{1}{n}\sum_{s=1}^{n} s_i$ of the assigned values that produces a value between zero and
392   one and is indicative of how balanced the distribution of the nodes between two communities is.

8.1.12   Small World

One of the network phenomena is the small-world effect, the observation that in most networks the
typical distances between any pairs of nodes are surprisingly short. Example is the Kevin Bacon degree of
separation game.

If we consider an undirected network with d_{ij} as length of the shortest path through the network between
nodes i and j or otherwise called distance between i and j. Then the mean distance l_i between nodes i and
j is:

$$l_i = \frac{1}{n} \sum_j d_{ij} \tag{17}$$

400 Then the mean distance l between nodes for the whole network is the average of this quantity over all nodes

$$l = \frac{1}{n} \sum_i l_i = \frac{1}{n^2} \sum_j d_{ij} \tag{18}$$

8.1.13 Degree Distribution

Degree distribution is defined as the fraction of the nodes that have a particular degree k. Following the
frequency probability approach, we can say that the probability of k or $p_k = \frac{k}{n_k}$; n_k is the number of nodes
with degree k. We can us p_k for example to find the number of nodes with such degree with np_k. It turns
out that almost all real-world networks have degree distributions with a tail of high-degree hubs like this.
In the language of statistics, we say that the degree distribution is right-skewed. In mathematical terms that
means that the logarithm of p_k is a linear function to the logarithm of k thus:

$$\ln p_k = -\alpha \times ln\ k + c \tag{19}$$

408 where $\alpha,\ c$ are constants. We can rewrite the relation between p_k and k in the form

$$p_k = Ck^{-\alpha} \tag{20}$$

409 where $C = e^c$ is another constant. Distribution of this form is called a power law distribution.

8.1.14 Cumulative Distribution of Degree

411 A way of properly visualizing a power-low distribution is to construct the cumulative distribution function,
412 which is defined as

$$P_k = \sum_{k'=k}^{\infty} P_{k'} \tag{21}$$

413 Or P_k is the fraction of nodes that have degree k or greater or alternatively as probability P_k that a
414 randomly chosen node has a degree k or greater.

8.1.15 Walks, loops, and paths

416 A walk is any sequence of nodes such that every consecutive pair of nodes in the sequence is connected
417 by an edge. In general, a walk can intersect itself, revisiting nodes it has visited before. Walks that do
418 not intersect themselves are called paths or self-avoiding walks. The length r of a walk in a network is
419 the number of edges (not nodes) traversed along the walk. The number of walks of a given length r in a
420 network can be generalized to: Laplacian clustering

$$N_{ij}^{(r)} = [A^r]_{ij} \tag{22}$$

where $[\ldots]_{ij}$ denotes the ij^{th} element of the matrix and A is the adjacency matrix.

Loops is a special type of walk that start and end at the same node i. The total number of loops of length r is the sum of this quantity over all possible starting points i:

$$L_r = \sum_{i=1}^{n}[A^r]_{ii} = TrA^r \qquad (23)$$

where Tr stands for trace $TrA = \sum_{i=1}^{n} a_{ii} = a_{11} + a_{22} + a_{33} + \ldots + a_{nn}$

8.1.16 Paths lengths

The so-called small world-effect, the observation that typically the lengths of paths between nodes in networks tend to be short. By using the graph's diameter, we can examine how the small-world effect arises as the graph grows. A graph diameter is the longest shortest path in a graph. The diameter of the graph varies with the n number of nodes as ln n. (natural log of n). The basic idea of the calculation of the diameter is that if we grow a set of nodes in a graph by iteratively adding neighbors to the set, the number of neighbors grows up by a factor of c , the average degree $c = \frac{2m}{n}$; where m is the number of edges in the graph and n is the number of nodes, on average per iteration s.

So, the average number of nodes one step away is c and by growing by a factor of c every iteration then the average number of nodes s iterations away is c^s. Given the exponential growth it does not take long until the number of nodes reached is equal to the total number of nodes in the graph $c^s \simeq n$ or equivalently $s \simeq \frac{\ln n}{\ln c}$ implying that the diameter is approximately $\frac{ln \; n}{ln c}$

8.1.17 Degree centrality

A large volume of work is dedicated to centrality. The question which are the most important vertices in or central nodes in a network. There are many possible definitions of importance and consequently many centrality measures. Degree, the number of incoming and outgoing edges a node has, is sometimes called degree centrality to emphasize its use as a centrality measure. Useful though it is quite a crude measure as it awards a node one centrality point for every neighbor it has. But not all neighbors are necessarily equivalent.

8.1.18 Eigenvector centrality

In many circumstances a node's importance in a network is increased by having connections with other nodes that are themselves important. Eigenvector centrality is an extension of degree centrality that takes this factor into account. Eigenvector centrality awards to a node several points proportional to the centrality scores of its neighbors. The eigenvector centrality x_i of node i is defined to be proportional to the sum of the centralities of i's neighbors

$$x_i = k^{-1}\sum_{ji} x_j \qquad (24)$$

An alternative way of writing using the adjacency matrix is:

$$x_i = k^{-1} \sum_{j=1}^{n} A_{ij} x_j \tag{25}$$

451   In matrix notation

$$x = k^{-1} A x$$
$$A x = k x$$

452   where x is the vector with elements equal to the centrality scores x_i and k is a constant. In other words, x
453   is an eigenvector of the adjacency matrix.

8.1.19   Katz centrality

455   One solution is to grant every node with a small amount of centrality, regardless of its position:

$$x_i = \alpha \sum_{j=1}^{n} A_{ij} x_j + \beta \tag{26}$$

456   where α, β are positive constants.

8.1.20   Page Rank Centrality

If a node with high Katz centrality has edges pointing to many others, then all of those others also get
high centrality. A high-centrality node pointing to one million others gives all one million of them high
centrality. One could argue that this is not always appropriate. In many cases it means less if a node is only
one among many that are pointed to. The centrality gained by virtue of receiving an edge from a prestigious
node is diluted by being shared with so many others. We can derive the following variant of Katz centrality
in which the centrality we derive from our network neighbors is proportional to their centrality divided by
their out-degree.

$$x_i = \alpha \sum_{j} A_{ij} \frac{x_j}{k_j^{out}} + \beta \tag{27}$$

8.1.21   Hubs and authorities

The concept of hubs and authorities in networks was first put forward by Kleinberg and developed by
him into a centrality algorithm called hyperlink-induced topic search or HITS. The HITS algorithm gives
each node i in a directed network two different centrality scores, the authority centrality x_i and the hub
centrality y_i , which quantify nodes' prominence in the two roles.

The defining characteristic of a node with high authority centrality is that it is pointed to by many nodes
with high hub centrality. Conversely, the defining characteristic of a node with high hub centrality is that it
points to many nodes with high authority centrality. In Kleinberg's approach the authority centrality of a

node is defined to be proportional to the sum of the hub centralities of the nodes that point to it:

$$x_i = \alpha \sum_j A_{ij} y_j \tag{28}$$

where α is a constant. Similarly, the hub centrality of a node is proportional to the sum of the authority centralities of the nodes it points to:

$$y_i = \beta \sum_j A_{ji} x_j \tag{29}$$

Thus, the authority and hub centralities are respectively given by eigenvectors of AA^T and $A^T A$ with the same eigenvalue.

8.1.22 Multiplex Participation Coefficient

As we are operating in the context of Multiplex data structure, it is necessary to introduce measurements that can capture and quantify the heterogeneity and the richness of the connectivity patterns between layers. A suitable measure to compute is the distribution of degree of a node among the various layers. This value will be equal to zero if all the node's links are in the same layer, on the other hand it will take its maximum value if the edges are uniformly distributed over the layers.

The multiplex participation coefficient follows the same principle to quantify the participation of a node to different layers of the network. By measuring values in $[0, 1]$ it quantifies whether the edges to a vertex are uniformly distributed amongst all the layers.

Concretely, the coefficient P_i is equal to zero when all the edges of i are in the same layer, while $P_i = 1$ when vertex i has the same number of edges on each of the M layers. The participation coefficient of the multiplex is defined as the average of the participation coefficients of all the vertices, i.e.,

$$P = 1/N \sum_i P_i \tag{30}$$

8.1.23 Multiplex interdependence

To capture the multiplex contribution to the reachability of each layer of the network, the node interdependence is introduced as:

$$\lambda_i = \sum_{j \neq i} \frac{\varphi_{ij}}{\sigma_{ij}} \tag{31}$$

where σ_{ij} is the total number of shortest paths between node i and node j on the multiplex network. φ_{ij} is the number of shortest paths between node i and node j that use links in two or more layers. Hence, the node independence is 1 when the shortest paths make us of edges in at least two layers, and 0 when each of the shortest paths uses only of the layers in the system. Averaging λ_i over all nodes, produces the multiplex interdependence, i.e.,

$$\lambda = (1/N) \sum_i \lambda_i \tag{32}$$

8.1.24   Supracentrality

Introduced in (33) supracentrality is a generalization of eigenvector based centralities, centrality measures
that includes PageRank, hub and authority scores and eigenvector centrality. Coupling centrality measures
across layers with weighed interlayer edges creates a supracentrality matrix $C(w)$, where w controls the
extent to which centrality changes over the layers.

8.2   Machine Learning Algorithms

8.2.1   Cluster Analysis K-means

Cluster analysis divides data into groups (clusters) that are meaningful, useful, or both. If meaningful
groups are the goal, then the clusters should capture the natural structure of the data. In clustering analysis
there are multiple types of techniques to identify and group objects together. The Prototype-based clustering
techniques create a one-level partitioning of the data objects where a cluster is a set of objects in which
each object is closer (more similar) to the prototype that defines the cluster than to the prototype of any
other cluster. For data with continuous attributes, the prototype of a cluster is often a centroid, i.e., the
average (mean) of all the points in the cluster. The K-means clustering technique is simple, and we begin
with a description of the basic algorithm. We first choose K initial centroids, where K is a user specified
parameter, namely, the number of clusters desired. Each point is then assigned to the closest centroid, and
each collection of points assigned to a centroid is a cluster. The centroid of each cluster is then updated
based on the points assigned to the cluster. We repeat the assignment and update steps until no point
changes clusters, or equivalently, until the centroids remain the same.

8.2.2   Cluster Analysis K-means

For the purpose of classification, we are interested in computing the probability of observing a class label
y for a data instance given its set of attribute values x. This can be represented as $P(y|x)$, which is known
as the posterior probability of the target class. The Naïve Bayes classifier assumes that the class-conditional
probability of all attributes x can be factored as a product of class-conditional probabilities of every attribute
x_i, as described in the following equation:

$$P(y|x) = \frac{P(y) \prod_{i=1}^{d} P(x_i|y)}{P(x)} \tag{33}$$

523   Since $P(x)$ is fixed for every y and only acts as a normalizing constant to ensure that $P(y|x)$ in $[0, 1]$, we
524   can write

$$P(y|x) \propto P(y) \prod_{i=1}^{d} P(x_i|y) \tag{34}$$

525   Hence, we are looking for a class $c \in [Y, N]$ that maximizes $P(y) \prod_{i=1}^{d} P(x_i|y)$ where x is an instance
526   from the dataset with d attributes. To use the classification approach, we utilize the discrete classes as
527   described in Table 1 as ground truth.

528 8.2.3   Decision tree classifier

To solve a classification problem, we can ask a series of carefully crafted questions about the attributes of
the instance. Each time we receive an answer, we could ask a follow-up question until we can conclusively
decide on its class label. The series of questions and their possible answers can be organized into a
hierarchical structure called a decision tree. The tree has three types of nodes: A root node, with no
incoming links and zero or more outgoing links. Internal nodes, each of which has exactly one incoming
link and two or more outgoing links. Leaf or terminal nodes, each of which has exactly one incoming link
and no outgoing links. Every leaf node in the decision tree is associated with a class label. The non-terminal
nodes, which include the root and internal nodes, contain attribute test conditions that are typically defined
using a single attribute. Each possible outcome of the attribute test condition is associated with exactly one
child of this node.

539 8.2.4   Deep Learning

A multi-layer neural network generalizes the basic concept of a perceptron to more complex architectures
of nodes that are capable of learning nonlinear decision boundaries. A generic architecture of a multi-layer
neural network where the nodes are arranged in groups called layers. These layers are commonly organized
in the form of a chain such that every layer operates on the outputs of its preceding layer. In this way, the
layers represent different levels of abstraction that are applied on the input features in a sequential manner.
The composition of these abstractions generates the final output at the last layer, which is used for making
predictions.

During the training process of deep learning models, we iterate over mini batches and minimize the
loss for the mini batch. We can empirically verify that the loss is going down while the accuracy is going
up per iteration step. Several challenges arise during the training and selection of a model. The biggest
being the bias-variance trade of. We refer to bias as the error we introduce when we try to approximate
a real-life task with a mathematical function i.e., a machine learning or deep learning model. When the
model can successfully approximate a task, it becomes more flexible and fits well the data as such bias
reduces. Variance refers to the amount the error changes when the model is presented with new data.
Ideally, we wish that the difference in performance on different data sets is minimal and that the model
generalizes well on the task. Usually, as the models become more flexible, the variance will increase, and
the bias will decrease. In other words, the models will be able to approximate the task better but will
not generalize on unseen data. As we train the models, the bias tends to initially decrease faster than the
variance increases. Consequently, the expected test error declines. However, at some point increasing
flexibility has negligible impact on the bias but starts to significantly increase the variance. When this
happens the test error increases. We say that the model is overfitting on the training data, it has learned it
by heart, and will not generalize well.

Especially large deep learning models can suffer from this phenomenon as the substantial number of
parameters provides for the ability to become more flexible to the training data set. For example, in the
field of Computer Vision it is common that a model starts to wrongly associate a specific background with
a class of an object and will misclassify objects based on their background.

8.3 Statistical Analysis

8.3.1 ELISpot value Distribution

In Figure 15, we analyze the distribution of the ELISpot values for both patients. The medians from both patients are different as well as the distribution of the values. The values of patient one is restricted to a smaller range and show an outlier in the upper quartile. In contrast patient two shows values distributed over a wider range, again with a wider distribution in the upper quartile. We can conclude that the patients show different distributions of observed PBMC values, i.e., the PBMC values are patient specific.

8.3.2 Peptides number versus ELISpot Value

In Figure 16, we graph a violin plot to analyze how the number of peptides in a system correlate with the PBMC values and specific patient. We see that patient two has systems with exclusively one peptide in contrast to patient one that has systems with one, two and three peptides. Patient one has a high concentration of systems with only one peptide. The correlation between number of peptides and ELISPot values is not clear. Systems with one peptide seem to produce higher PBMC values in contrast to systems with multiple peptides. This conclusion should be taken with caution since only patient one has systems with more than one peptide.

8.3.3 Number of Amino acids versus ELISpot values

In Figure 17, we analyze the distribution of ELISpot values in relation to the total number of Amino Acids originating from the peptides in a system. We look at these correlations for both patients individually and together. Here the difference between the patients is not so clear, we observe a pattern in both patients where the lower and the upper range of the number of patients correlate with a high ELISPot value. It is notisible that systems with 30 amino acids consistently produce PBMC values above 500 for patient two. We can conclude that systems with higher total number of amino acids in the peptides tend to produce higher ELISpot values.

8.3.4 Linear Model coefficient analysis

In order to better understand the potential influence of particular data attributes we apply a linear regression model. Analyzing the coefficients, we can understand the predictors influence on the produced PBMC values. From the results shown in Table 7, we can see that the total number of amino acids in a system have positive linear relationship with the produced PBMC's for patient one and negative for patient two. The performance of the model differs between the two patients and the same coefficients have different linear relationship on the produced PBMC for the two patients. Hence the relationship between these coefficients and the matched PBMC value is patient specific. This observation indicates that tumor mutations and immune system response are not only tumor but also patient specific.

8.3.5 Multivariate analysis of variance

Multivariate analysis of variance (MANOVA) is a statistical procedure for comparison of multivariate sample means. It is often used when there are two or more dependent variables, and we wish to perform regression analysis and analysis of variance for them by one or more factor variables or covariates. In our case we wish to determine which networks measures are highly significantly different among patients. From the results shown in Tables 7 to 24, we see that Matched PBMC, Average Core hubs, Average Betweenness Centrality have a high statistical significance with p-value¡0.001. Closeness Centrality, Degree Pearson

605 Correlation Coefficient, Page Rank Centrality, Attribute Assortativity Coefficient Source with p-value¡0.01
606 Size largest Component, Response Degree Centrality, Density statistical significance with p-value¡0.05

8.3.6   Size largest Component

As visualized in Figure 18, even though the medians of both patients are close, the values of patient
one is better distributed with a large portion in the lower quartile. Patient two shows a high concentration
around the median and the upper quartile and an outlier in the upper whisker.

When considering the S values over all the systems, we observe a positive correlation with the matched
PBMC's with statistical significance shown by a p-value¡0.10. This could mean that systems that create
larger connected components, have a higher chance of producing a higher PBMC value. This is confirmed
by the distribution of the PBMC values of patient two, showing overall significantly higher values than
patient one, and a distribution of the size of the largest components that is concentrated around the median
of 30 and the upper quartile. When looking at the individual patients, we observe that patient two shows
inverse correlation, even though not significant, with the matched PBMC's. Patient one shows a positive
correlation with matched PBMC's.

8.3.7   Average Spectral clustering

As visualized in Figure 19, we calculate the average spectral clustering for each system and look at its
distribution and correlation with the patient and the measured matched PBMC's i.e., ELISpot values. We
see that the distributions for both patients are quite similar. Patient two produces values that are skewed
towards the lower quartile while patient one values are better distributed around the median. Even though
combined data of both patients show a inverse Pearson correlation coefficient with the matched PBMC's,
patient one shows a positive correlation with statistical significance indicated by a p-value¡0.05. This might
indicate that there is a difference in the produced PMBC's between patients with similar avg. spectral
clustering values. In other words, the systems of individual patients react differently to a similar internal
node distribution between two communities.

8.3.8   Global Clustering Coefficient

As visualized in Figure 20,we calculate global clustering coefficient for each system and look at its
distribution and correlation with the particular patient and the measured matched PBMC's i.e., ELISpot
values. We see that the distributions for both patients are quite similar. Patient two produces values that
are skewed towards the upper quartile while patient one values are better distributed around the median.
Combined data of both patients shows a positive Pearson correlation coefficient, with statistical significance
indicated by a p-value¡0.05, with the matched PBMC's. Patients one and two show a similar positive
correlation. This observation can imply that systems with high clustering coefficient, i.e., systems where
monomers, polymers and atoms that are connected to the same monomer, polymer or atom have a high
likelihood to be connected to each other, will produce a higher number of matched PBMC's.

8.3.9   Transitivity

As visualized in Figure 21,we calculate the transitivity for each system and look at its distribution and
correlation with the patient and the measured matched PBMC's i.e., ELISpot values. We see that the
distributions for both patients are quite similar. Patient one produces values that are skewed towards the
lower quartile while patient two values are better distributed around the median. Combined data of both
patients show a positive Pearson correlation coefficient, with no statistical significance, with the matched

PBMC's. Patients one and two show a similar positive correlation.This confirms the observed correlation
with the global clustering coefficient.

8.3.10   Average Degree

As visualized in Figure 22,we calculate $\langle k \rangle$ for each system and look at its distribution and correlation
with the patient and the measured matched PBMC's i.e., ELISpot values. We see that the distributions for
both patients are somewhat similar. Patient one produces values that are skewed towards the lower quartile
while patient two values are better distributed around the median. The median of patient one is significantly
higher. Combined data of both patients show an inverse Pearson correlation coefficient, with no statistical
significance, with the matched PBMC's. Patient two shows a similar positive correlation in contrast to
patient one that shows a positive correlation. From these observations we could imply that impact of the
density of the network on the matched PBMC's is patient specific.

8.3.11   Degree Centrality

As visualized in Figure 23,we calculate the degree centrality for each system and look at its distribution
and correlation with the patient and the measured matched PBMC's i.e., ELISpot values. We see that the
distributions for both patients are different. Patient one produces values that are mostly skewed towards
the lower quartile while patient two are skewed towards the upper quartile. The median of patient one is
significantly higher. Combined data of both patients show a positive Pearson correlation coefficient with a
statistical significance indicated by a p-value¡0.05, with the matched PBMC's. Patient two shows a similar
positive correlation in contrast to patient one that shows a correlation near to zero. From these observations
we could imply that impact of high number of incoming and outgoing edges from the vertices in the system
have a positive impact on the matched PBMC's. There is however a patient specific aspect in the magnitude
of the positive impact.

8.3.12   Average Core Hubs

As visualized in Figure 24,we calculate the average core hubs for each system and look at its distribution
and correlation with the patient and the measured matched PBMC's i.e., ELISpot values. We see that the
distributions for both patients are different. Patient one produces values that are mostly skewed towards
the lower quartile while patient two skewed towards the upper quartile. The median of patient one is
significantly higher. Combined data of both patients show a positive Pearson correlation coefficient with
statistical significance indicated by a p-value¡0.01, with the matched PBMC's. Patient two shows a similar
positive correlation in contrast to patient one that shows a correlation near to zero. From these observations
we could imply that impact of high number of incoming and outgoing edges from the vertices in the
system have a positive impact on the matched PBMC's. There is however a patient specific aspect in the
magnitude of the positive impact. This observation agrees with the observations of Degree Centrality and
its correlation with the matched PBMC values.

8.3.13   Density

As visualized in Figure 25,we calculate the density for each system and look at its distribution and
correlation with the particular patient and the measured matched PBMC's i.e., ELISpot values. We see that
the distributions for both patients are different. Patient one produces values that are mostly skewed towards
the lower quartile while patient's two are skewed towards the upper quartile. The median of patient one is
significantly higher. Combined data of both patients show a positive Pearson correlation coefficient with
statistical significance indicated by a p-value¡0.01, with the matched PBMC's. Patient two shows a similar

positive correlation in contrast to patient one that shows a correlation near to zero. From these observations
we could imply that a high number of incoming and outgoing edges from the vertices in the system have a
positive impact on the matched PBMC's. There is however a patient specific aspect in the magnitude of
the positive impact. This observation agrees with the observations of Degree Centrality and Average Core
Hubs. As the measures, Density, Degree Centrality and Average Core Hubs, overlap it make sense to select
the one with the highest correlation and statistical significance i.e., Average Core Hubs.

8.3.14 Betweenness Centrality

As visualized in Figure 26,we calculate the Betweenness Centrality for each system and look at its
distribution and correlation with the particular patient and the measured matched PBMC's i.e., ELISpot
values. We see that the distributions for both patients are different. Patient one produces values that are
mostly skewed towards the lower quartile while patient's two are skewed towards the upper quartile. The
median of patient one is significantly higher. Combined data of both patients show a positive Pearson
correlation coefficient with statistical significance indicated by a p-value¡0.01, with the matched PBMC's.
Patient two shows a similar positive correlation in contrast to patient one that shows a correlation near to
zero. From these observations we could imply that impact of high number nodes in a system that are on
the path between other nodes has a positive impact on the matched PBMC's. There is however a patient
specific aspect in the magnitude of the positive impact.

8.3.15 Closeness Centrality

As visualized in Figure 27,we calculate the Closeness Centrality for each system and look at its distribution
and correlation with the particular patient and the measured matched PBMC's i.e., ELISpot values. We see
that the distributions for both patients are different. Patient one produces values that are mostly skewed
towards the lower quartile while patient two are evenly distributed. The median of patient one is significantly
higher. Combined data of both patients show a positive Pearson correlation coefficient with statistical
significance indicated by a p-value¡0.05, with the matched PBMC's. Patient one and two shows a similar
positive correlation. From these observations we could imply that, the impact of high number nodes in a
system with a high number of shortest distances to all other nodes, has a positive impact on the matched
PBMC's.

8.3.16 Degree Pearson Correlation Coefficient

As visualized in Figure 28,we calculate the Degree Pearson correlation Coefficient for each system and
look at its distribution and correlation with the particular patient and the measured matched PBMC's i.e.,
ELISpot values. We see that the distributions for both patients are different. Patient one and two produce
values that are mostly skewed towards the upper quartile but there is a significant difference in their medians.
Combined data of both patients show a positive Pearson correlation coefficient with statistical significance
indicated by a p-value¡0.05, with the matched PBMC's. Patients one and two show a similar positive
correlation. From these observations we could imply that, a high number of similar connections between
nodes in a system e.g., monomers, polymers, atoms have a positive impact on the matched PBMC's.

8.3.17 Eigen Vector Centrality

As visualized in Figure 29,we calculate the average Eigen Vector Centrality for each system and look at
its distribution and correlation with the particular patient and the measured matched PBMC's i.e., ELISpot
values. We see that the distributions for both patients are very similar. Patient one and two produce values
that are mostly skewed towards the upper quartile with patient two having a longer tail. Combined data

of both patients show a positive Pearson correlation coefficient with no statistical significance, with the
matched PBMC's. However, patient two shows an inverse correlation in contrast to positive correlation of
patient one. From these observations we could imply that importance of this measure towards the impact
on the matched PBMC's is not significant and it is patient specific.

8.3.18 Page Rank Centrality

As visualized in Figure 30,we calculate the average Page Rank Centrality for each system and look at its
distribution and correlation with the particular patient and the measured matched PBMC's i.e., ELISpot
values. We see that the distributions for both patients are very different. Patient one and two produce
similar medians but patient one distribution is skewed toward the lower quartile and patient two toward
the higher quartile. Combined data of both patients show a positive Pearson correlation coefficient with
statistical significance shown by a p-value < 0.05, with the matched PBMC's. Patient two has similar
correlation. From these observations we could imply that systems with a high number of nodes that have
a high centrality based on connections from nodes that on their turn have high centrality has a positive
influence on the produced PMBC's. However, this influence seems to be patient specific.

8.3.19 Attribute Assortativity Coefficient Source

As visualized in Figure 31,we calculate the average Attribute Assortativity Coefficient for attribute Source
for each system and look at its distribution and correlation with the particular patient and the measured
matched PBMC's i.e., ELISpot values. We see that the distributions for both patients are very different.
Patient one and two produce similar medians but patient one distribution is skewed toward the upper
quartile and patient two toward the lower quartile. Combined data of both patients show an inverse Pearson
correlation coefficient with statistical significance shown by a p-value<0.05, with the matched PBMC's.
Patients one and two have similar correlation. From these observations we could imply that systems with a
more diverse unique node distribution have a higher likelihood to produce more PMBC's.

8.3.20 Causality

A Bayesian network is probabilistic model that represents the variables and their conditional dependencies
as directed acyclic graph (DAG). In a DAG, variables are represented as vertices and conditional
dependencies as edges. Vertices that are not connected represent conditionally independent variables. Each
node is associated with a probability function that takes in, a particular set of values for the node's parent
variables, and gives the probability, or probability distribution, of the variable represented by the node. As
shown in Figure 32, we apply a structure learning algorithm to the data to learn the structure of the directed
acyclic graph (DAG) from the data. Concretely we apply Incremental Association (IAMB) algorithm, based
on the Markov blanket detection algorithm of the same name, which is based on a two-phase selection
scheme (a forward selection followed by an attempt to remove false positives). Analyzing the DAG, we
see that the matched PBMC, vectors, Average core hubs, Attribute Assortativity Coefficient Source, Size
largest component, Eigen vector Centrality and closeness centrality are conditionally dependent on the
patient. This observation confirms observations made the correlation analysis. This indicates that system
structures have patient specific attributes and their matched PBMC's are as well patient specific.

8.3.21 Personal Models cross evaluation

765 We evaluate the performance of personal model, trained on data from patient one, on data from patient
766 two and vice versa. As shown in Table 2, the metrics Precision, Recall and F-measure drop significantly

in contrast to their respective values in Table 2 and Table 3. We can conclude that the models do not necessarily generalize to unseen data from other patients and that personalized models perform better.

8.4 Evaluation metrics

8.5 Accuracy

Accuracy is the most intuitive performance measure and it is simply a ratio of correctly predicted observation to the total observations.

$$Accuracy = TP+TN/TP+FP+FN+TN$$

8.6 Precision

Precision is the ratio of correctly predicted positive observations to the total predicted positive observations.

$$Precision\ = TP/TP+FP$$

8.7 Recall

Recall (Sensitivity) is the ratio of correctly predicted positive observations to the all observations in actual class - yes

$$Recall\ = TP/TP+FN$$

8.8 F-measure

F-measure is the weighted average of Precision and Recall. Therefore, this score takes both false positives and false negatives into account. Intuitively it is not as easy to understand as accuracy, but F1 is usually more useful than accuracy, especially if you have an uneven class distribution. Accuracy works best if false positives and false negatives have similar cost. If the cost of false positives and false negatives are quite different, it's better to look at both Precision and Recall.

$$F1\ Score\ = 2*(Recall * Precision) / (Recall + Precision)$$

8.8.1 Permission to Reuse and Copyright

Figures, tables, and images will be published under a Creative Commons CC-BY licence and permission must be obtained for use of copyrighted material from other sources (including re-published/adapted/modified/partial figures and images from the internet). It is the responsibility of the authors to acquire the licenses, to follow any citation instructions requested by third-party rights holders, and cover any supplementary charges.

CONFLICT OF INTEREST STATEMENT

The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

AUTHOR CONTRIBUTIONS

797 "IJ contributed to conception and design of the study and performed the statistical analysis and wrote
798 the first draft of the manuscript. LM contributed to the medical aspect and JM of the study. All authors
799 contributed to manuscript revision, read, and approved the submitted version."

DATA AVAILABILITY STATEMENT

800 The datasets for this study can be found in the In silico Antibody-Peptide Epitope prediction for Personalized
801 cancer therapy.

TRAINED MODELS AVAILABILITY STATEMENT

802 The trained models from this study will be made available for usage on Linked Chain website under the
803 section A.I. tools.

REFERENCES

1 .Pastor F, Berraondo P, Etxeberria I, Frederick J, Sahin U, Gilboa E, et al. An RNA toolbox for
cancer immunotherapy **17** (????) 751–767. doi:10.1038/nrd.2018.132. Number: 10 Publisher: Nature
Publishing Group.
2 .Engvall E, Perlmann P. Enzyme-linked immunosorbent assay (ELISA). quantitative assay of
immunoglobulin g **8** (????) 871–874. doi:10.1016/0019-2791(71)90454-x.
3 .Paulie S, Perlmann P, Perlmann H. Chapter 64 - enzyme-linked immunosorbent assay. Celis JE, editor,
Cell Biology (Third Edition) (Academic Press) (????), 533–538. doi:10.1016/B978-012164730-8/
50065-4.
4 .Tan X, Li D, Huang P, Jian X, Wan H, Wang G, et al. dbPepNeo: a manually curated database for
human tumor neoantigen peptides **2020** (????) baaa004. doi:10.1093/database/baaa004.
5 .Pearson H, Daouda T, Granados DP, Durette C, Bonneil E, Courcelles M, et al. MHC class i-associated
peptides derive from selective regions of the human genome **126** (????) 4690–4701. doi:10.1172/
JCI88590.
6 .Barabas S, Spindler T, Kiener R, Tonar C, Lugner T, Batzilla J, et al. An optimized IFN-y ELISpot assay
for the sensitive and standardized monitoring of CMV protein-reactive effector cells of cell-mediated
immunity **18** (????) 14. doi:10.1186/s12865-017-0195-y.
7 .Andreatta M, Nielsen M. Gapped sequence alignment using artificial neural networks: application to
the MHC class i system **32** (????) 511–517. doi:10.1093/bioinformatics/btv639.
8 .Lundegaard C, Lamberth K, Harndahl M, Buus S, Lund O, Nielsen M. NetMHC-3.0: accurate web
accessible predictions of human, mouse and monkey MHC class i affinities for peptides of length 8-11
36 (????) W509–512. doi:10.1093/nar/gkn202.
9 .Peters B, Sette A. Generating quantitative models describing the sequence specificity of biological
processes with the stabilized matrix method **6** (????) 132. doi:10.1186/1471-2105-6-132.
10 .Nielsen M, Andreatta M. NetMHCpan-3.0; improved prediction of binding to MHC class i molecules
integrating information from multiple receptor and peptide length datasets **8** (????) 33. doi:10.1186/
s13073-016-0288-x.
11 .Karosiene E, Lundegaard C, Lund O, Nielsen M. NetMHCcons: a consensus method for the major
histocompatibility complex class i predictions **64** (????) 177–186. doi:10.1007/s00251-011-0579-8.

12 .Vang YS, Xie X. HLA class i binding prediction via convolutional neural networks **33** (????) 2658–2665.
doi:10.1093/bioinformatics/btx264.

13 .Han Y, Kim D. Deep convolutional neural networks for pan-specific peptide-MHC class i binding
prediction **18** (????) 585. doi:10.1186/s12859-017-1997-x.

14 .Liu Z, Cui Y, Xiong Z, Nasiri A, Zhang A, Hu J. DeepSeqPan, a novel deep convolutional neural
network model for pan-specific class i HLA-peptide binding affinity prediction **9** (????) 794. doi:10.
1038/s41598-018-37214-1.

15 .Hu Y, Wang Z, Hu H, Wan F, Chen L, Xiong Y, et al. ACME: pan-specific peptide-MHC class i
binding prediction through attention-based deep neural networks **35** (????) 4946–4954. doi:10.1093/
bioinformatics/btz427.

16 .Jiang L, Yu H, Li J, Tang J, Guo Y, Guo F. Predicting MHC class i binder: existing approaches and a
novel recurrent neural network solution **22** (????) bbab216. doi:10.1093/bib/bbab216.

17 .[Dataset] IEDB.org: Free epitope database and prediction resource (????).

18 .Han Y, Kim D. Deep convolutional neural networks for pan-specific peptide-MHC class i binding
prediction **18** (????) 585. doi:10.1186/s12859-017-1997-x.

19 .Jurtz V, Paul S, Andreatta M, Marcatili P, Peters B, Nielsen M. NetMHCpan-4.0: Improved peptide-
MHC class i interaction predictions integrating eluted ligand and peptide binding affinity data **199**
(????) 3360–3368. doi:10.4049/jimmunol.1700893.

20 .Shao XM, Bhattacharya R, Huang J, Sivakumar IA, Tokheim C, Zheng L, et al. High-throughput
prediction of MHC class i and II neoantigens with MHCnuggets **8** (????) 396–408. doi:10.1158/
2326-6066.CIR-19-0464.

21 .Yang X, Zhao L, Wei F, Li J. DeepNetBim: deep learning model for predicting HLA-epitope interactions
based on network analysis by harnessing binding and immunogenicity information **22** (????) 231.
doi:10.1186/s12859-021-04155-y.

22 .Zhao L, Wong L, Lu L, Hoi SC, Li J. B-cell epitope prediction through a graph model **13** (????) S20.
doi:10.1186/1471-2105-13-S17-S20.

23 .[Dataset] Lu S, Li Y, Ma Q, Nan X, Zhang S. A structure-based b-cell epitope prediction model through
combing local and global features (????). doi:10.1101/2021.07.13.452188. Pages: 2021.07.13.452188
Section: New Results.

24 .Wang Y, Tang H, Gao C, Ge M, Li Z, Dong Z, et al. Flexibility-aware graph model for accurate epitope
identification **149** (????) 106064. doi:10.1016/j.compbiomed.2022.106064.

25 .Lee CH, Yelensky R, Jooss K, Chan TA. Update on tumor neoantigens and their utility: Why it is good
to be different **39** (????) 536–548. doi:10.1016/j.it.2018.04.005.

26 .Gfeller D, Bassani-Sternberg M, Schmidt J, Luescher IF. Current tools for predicting cancer-specific t
cell immunity **5** (????) e1177691. doi:10.1080/2162402X.2016.1177691.

27 .Liu XS, Mardis ER. Applications of immunogenomics to cancer **168** (????) 600–612. doi:10.1016/j.
cell.2017.01.014.

28 .Lucky SS, Law M, Lui MH, Mong J, Shi J, Yu S, et al. Patient-derived nasopharyngeal cancer organoids
for disease modeling and radiation dose optimization **11** (????) 622244. doi:10.3389/fonc.2021.622244.

29 .[Dataset] CEDAR - cancer epitope database and analysis resource (????).

30 .[Dataset] Oktay O, Schlemper J, Folgoc LL, Lee M, Heinrich M, Misawa K, et al. Attention u-net:
Learning where to look for the pancreas (????). doi:10.48550/arXiv.1804.03999.

31 .Dieterich n. Approximate statistical tests for comparing supervised classification learning algorithms
10 (????) 1895–1923. doi:10.1162/089976698300017197.

32 .Analysis of variance and the kruskal-wallis test. Dalgaard P, editor, *Introductory Statistics with R*
(Springer), Statistics and Computing (????), 111–127. doi:10.1007/0-387-22632-X_6.

FIGURES AND TABLES

Attribute	Description
Peptide Sequence	Represents the structure of amino acids of peptide and is of type string. Every letter represents an amino acid.
HLA alleles	The patients HLA alleles. Represents the HLA protein structure as a sequence of amino acids represented as letters.
Matched PBMC's	The number of matched blood mononuclear cells (PBMC's)
Discretized PBMC's	PBMC values are discretized into 2 classes: 'no reaction','reaction'

Table 1. Data dictionary of the used data set.

Classifier	Precision	Recall	F-measure	PR-AUC
Decision tree classifier	**1.0**	**1.0**	**1.0**	**1.0**
Multi-layer Perceptron classifier	0.05	0.21	0.08	0.89
Random Forest classifier	**1.0**	**1.0**	**1.0**	**1.0**
Support Vector Machine	0.05	0.21	0.08	0.89
Naive Bayes classifier	0.88	0.86	0.83	0.92
Logistic Regression classifier	0.84	0.43	0.43	0.92
K-Neighbors Classifier	0.88	0.86	0.83	0.92
UNET-ATT	**0.95**	**0.93**	**0.93**	**0.99**

Table 2. Patient's one models: Performance of the classifiers for with the highest value in bold.

Classifier	Precision	Recall	F-measure	PR-AUC
Decision tree classifier	0.43	0.4	0.4	0.52
Multi-layer Perceptron classifier	0.05	0.21	0.08	**0.89**
Random Forest classifier	0.8	0.6	0.57	0.75
Support Vector Machine	0.16	0.4	0.23	0.7
Naive Bayes classifier	0.6	0.6	0.6	0.6
Logistic Regression classifier	0.43	0.4	0.4	0.52
K-Neighbors Classifier	0.16	0.4	0.23	0.7
UNET-ATT	**0.87**	**0.8**	**0.8**	**0.83**

Table 3. Patient's two models: Performance of the classifiers with the highest value in bold.

Comparison	p-value	OR
UNET-ATT vs MLPC	<0.005	1.46*
UNET-ATT vs RFC	**<0.005**	1.20*
UNET-ATT vs SVM	<0.005	1.46*
UNET-ATT vs NBC	<0.005	1.39*
UNET-ATT vs LRC	<0.005	1.39*
UNET-ATT vs KNC	<0.005	1.39*

Table 4. Patient One: Statistical comparison between different classification algorithms (McNemar's test and Odds Ratio). '*' captures the smallest OR among 10 times statistical tests.

Comparison	p-value	OR
UNET-ATT vs MLPC	<0.005	1.37*
UNET-ATT vs RFC	<0.005	1.37*
UNET-ATT vs SVM	<0.005	0.92*
UNET-ATT vs NBC	<0.005	1.36*
UNET-ATT vs LRC	<0.005	0.91*
UNET-ATT vs KNC	<0.005	0.91*

Table 5. Patient Two: Statistical comparison between different classification algorithms (McNemar's test and Odds Ratio). '*' captures the smallest OR among 10 times statistical tests.

Tumor specific classifier	Accuracy	Precision	Recall	F-measure	PR-AUC
All tissue types	0.69	0.66	0.76	0.70	0.69
Blood	0.56	0.60	0.47	0.52	0.56
Breast	1	1	1	1	1
Lung	0.90	1	0.86	0.92	0.92
Lymphoid	0.71	0.67	0.76	0.71	0.72

Table 6. Tumor specific classifiers: Performance of the classifier on tumor specific tasks.

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.007	0.006	0.003	0.012
Mean Sq	2	0.002	0.002	0.0002	0.003
F value	1	14.286		14.286	14.286
Pr(>F)	1	0.0004		0.0004	0.0004

Table 7. Response Size largest Component

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.00002	0.00003	0.00000	0.00004
Mean Sq	2	0.00000	0.00000	0.00000	0.00000
F value	1	1.128		1.128	1.128
Pr(>F)	1	0.293		0.293	0.293

Table 8. Response Laplacian clustering

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.009	0.013	0.0002	0.018
Mean Sq	2	0.0003	0.0001	0.0002	0.0003
F value	1	0.641		0.641	0.641
Pr(>F)	1	0.427		0.427	0.427

Table 9. Response Global Clustering Coeffiecient

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.075	0.082	0.017	0.133
Mean Sq	2	0.010	0.011	0.002	0.017
F value	1	7.502		7.502	7.502
Pr(>F)	1	0.008		0.008	0.008

Table 10. Response Transitivity

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.027	0.039	0.0001	0.055
Mean Sq	2	0.0005	0.001	0.0001	0.001
F value	1	0.056		0.056	0.056
Pr(>F)	1	0.814		0.814	0.814

Table 11. Response Average degree

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.0001	0.0001	0.00001	0.0001
Mean Sq	2	0.00000	0.00000	0.00000	0.00001
F value	1	3.257		3.257	3.257
Pr(>F)	1	0.076		0.076	0.076

Table 12. Response Average Clustering

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.002	0.003	0.00001	0.004
Mean Sq	2	0.00004	0.00004	0.00001	0.0001
F value	1	0.131		0.131	0.131
Pr(>F)	1	0.719		0.719	0.719

Table 13. Response Degree Centrality

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.009	0.013	0.0002	0.019
Mean Sq	2	0.0003	0.0001	0.0002	0.0003
F value	1	0.671		0.671	0.671
Pr(>F)	1	0.416		0.416	0.416

Table 14. Response Average Core hubs

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.0001	0.0001	0.00001	0.0001
Mean Sq	2	0.00000	0.00000	0.00000	0.00001
F value	1	3.257		3.257	3.257
Pr(>F)	1	0.076		0.076	0.076

Table 15. Response Density

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.00000	0.00000	0.00000	0.00000
Mean Sq	2	0.00000	0.00000	0.00000	0.00000
F value	1	10.164		10.164	10.164
Pr(>F)	1	0.002		0.002	0.002

Table 16. Response Vectors

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.224	0.205	0.079	0.369
Mean Sq	2	0.043	0.051	0.006	0.079
F value	1	12.395		12.395	12.395
Pr(>F)	1	0.001		0.001	0.001

Table 17. Response Average Betweenness Centrality

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.00000	0.00000	0.00000	0.00000
Mean Sq	2	0.00000	0.00000	0.00000	0.00000
F value	1	10.164		10.164	10.164
Pr(>F)	1	0.002		0.002	0.002

Table 18. Response Closeness Centrality

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	173,139.200	235,923.700	6,315.891	339,962.500
Mean Sq	2	6,088.656	321.358	5,861.422	6,315.891
F value	1	1.078		1.078	1.078
Pr(>F)	1	0.304		0.304	0.304

Table 19. Response Degree Pearson Correlation Coefficient

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.00000	0.00000	0.00000	0.00000
Mean Sq	2	0.000	0.000	0.000	0.00000
F value	1	13.680		13.680	13.680
Pr(>F)	1	0.0005		0.0005	0.0005

Table 20. Response Eigenvector Centrality

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.003	0.003	0.001	0.005
Mean Sq	2	0.001	0.001	0.0001	0.001
F value	1	11.914		11.914	11.914
Pr(>F)	1	0.001		0.001	0.001

Table 21. Response Page Rank Centrality

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.002	0.002	0.001	0.004
Mean Sq	2	0.0003	0.0003	0.0001	0.001
F value	1	7.848		7.848	7.848
Pr(>F)	1	0.007		0.007	0.007

Table 22. Response Attribute Assortativity Coefficient Type

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.0001	0.0001	0.00000	0.0001
Mean Sq	2	0.00000	0.00000	0.00000	0.00000
F value	1	0.046		0.046	0.046
Pr(>F)	1	0.830		0.830	0.830

Table 23. Response Attribute Assortativity Coefficient Source

Statistic	N	Mean	St. Dev.	Min	Max
Df	2	29.500	40.305	1	58
Sum Sq	2	0.00000	0.00000	0.00000	0.00000
Mean Sq	2	0.000	0.00000	0.000	0.00000
F value	1	10.011		10.011	10.011
Pr(>F)	1	0.002		0.002	0.002

Table 24. Response Matched PBMC

Figure 1. HLA proteins (green) display peptides (red) from inside the cell to help immune cells find cancerous or infected cells

Exome sequencing
RNA sequencing

Mutation identification

Tumor tissue bioply

Normal tissue

Sample

MHC-binding identification

Peptide

Peptide binding groove

HLA

Plasma membrane

Vaccine formulation

mRNA

Figure 2. The exome of tumor cells isolated from a biopsy sample and the exome of normal cells are compared to identify tumor-specific mutations. Point non-synonymous mutations, gene deletions, or rearrangements can give rise to neoantigens. Several bioinformatics tools are used to predict major histocompatibility complex (MHC) class I and class II binding (necessary for recognition by T cells) and RNA expression presence of the mutated antigen among tumor cells (clonality). RNA sequencing enables verification that the gene encoding the neoantigen is actually expressed by tumor cells. A tandem gene encoding several neoantigen peptides is cloned into a plasmid and transcribed to mRNA. Finally, these mRNAs are injected as naked RNA, formulated into liposomes or loaded into dendritic cells.

Secreted Protein

Capture antibody

Steptavidin Conjugate

Biotinylated Antibody

Figure 3. Visualisation of an enzyme-linked immunospot (ELISpot) Assay

Figure 4. Approach is divided into the following phases: (1) Data Collection, (2) ELISpot assay, (3) Structures and Measurements generation, (4) Analytical approach evaluation

Figure 5. Peptide, short chain of amino acids, represented in 3 dimensional space.

Figure 6. HLA cell-surface protein,chain of amino acids, represented in 3 dimensional space.

Figure 7. HLA-peptide complex formed by the binding of a peptide to a HLA cell-surface protein, represented in 3 dimensional space.

Figure 8. In-silico molecular complexes present in a system, represented in 3 dimensional space.

Figure 9. Atom layer,representing the atoms and their bonds that construct objects in the monomer layer e.g., amino acid, represented in 3 dimensional space.

Figure 10. Monomer layer,representing objects of type monomer that are a molecule of any of a class of compounds, mostly organic, that can react with other molecules to form very large molecules,represented in 3 dimensional space.

Figure 11. Polymer layer,representing objects of type polymer that are objects of a class of natural or synthetic substances composed of very large molecules, called macromolecules, which are multiples of monomers,represented in 3 dimensional space.

Figure 12. Complex layer,represents polymers that form a complex by binding to each other e.g., peptide binds to an HLA to form a complex ,represented in 3 dimensional space.

Figure 13. System layer,represents the totality of complexes that exist in an ELISpot assay and is representative of multiple HLA-peptide complexes, represented in 3 dimensional space.

Figure 14. Block diagram of the proposed U-NET with self-attention model architecture. Input feature vector is progressively down sampled and filtered at each step. Attention gates (AG) filter the latent feature vectors that flow through the skip connections.

Figure 15. ELISpot histogram plot, depicting ELISpot values for both patients. The medians from both patients are different as well as the distribution of the values.

Figure 16. ELISpot violin plot, depicting ELISpot values for both patients. In order to analyze how the number of peptides in a system correlate with the PBMC values and specific patient.

Figure 17a. Patient One

Figure 17b. Patient two

Figure 17c. All patiens

Figure 17. Distribution of ELISpot values in relation to the total number of Amino Acids originating from the peptides in a system. **(A)** Distribution of Patient one ELISpot values in relation to the total number of Amino Acids. **(B)** Distribution of Patient two ELISpot values in relation to the total number of Amino Acids.**(C)** Distribution of both patients ELISpot values in relation to the total number of Amino Acids.

Figure 18. Patient Matched PBMC's vs. Size largest Component.

Figure 19. Patient Matched PBMC's vs. Avg. Spectral clustering

Figure 20. Patient Matched PBMC's vs. Global Clustering Coefficient

Figure 21. Patient Matched PBMC's vs. Transitivity

Figure 22. Patient Matched PBMC's vs. Average Degree

Figure 23. Patient Matched PBMC's vs. Degree Centrality

Figure 24. Patient Matched PBMC's vs. Average Core Hubs

Figure 25. Patient Matched PBMC's vs. Density

Figure 26. Patient Matched PBMC's vs. Average Betweenness Centrality

Figure 27. Patient Matched PBMC's vs. Closeness Centrality

Figure 28. Patient Matched PBMC's vs. Degree Pearson Correlation Coefficient

Figure 29. Patient Matched PBMC's vs. Eigen Vector Centrality

Figure 30. Patient Matched PBMC's vs. Page Rank Centrality

Figure 31. Patient Matched PBMC's vs. Attribute Assortativity Coefficient Source

Figure 32. Structure learning casual network.