Neural tuning instantiates prior expectations in the human visual system

William J Harrison[1,2], Paul M Bays[3], & Reuben Rideaux[2,4]*

[1]School of Psychology, The University of Queensland, St Lucia, Australia

[2]Queensland Brain Institute, The University of Queensland, St Lucia, Australia

[3]Department of Psychology, The University of Cambridge, Cambridge, UK

[4]School of Psychology, The University of Sydney, Camperdown, Australia

*corresponding author: reuben.rideaux@gmail.com

Conflict of interest statement: The authors declare no competing interests.

Acknowledgements: We thank Valentin Wyart and Jean-Remi King for sharing their data. This work was supported by an Australian Research Council Discovery Early Career Researcher Award to RR (DE210100790).

Keywords: efficient encoding, oblique effect, EEG, inverted encoding, natural image statistics

ABSTRACT

Perception is often modelled as a process of active inference, whereby prior expectations

are combined with noisy sensory measurements to estimate the structure of the world. This

mathematical framework has proven critical to understanding perception, cognition, motor

control, and social interaction. While theoretical work has shown how priors can be

computed from environmental statistics, their neural instantiation could be realised through

multiple competing encoding schemes. Using a data-driven approach, here we extract the

brain's representation of visual orientation and compare this with simulations from different

sensory coding schemes. We found that the tuning of the human visual system is highly

conditional on stimulus-specific variations in a way that is not predicted by previous

proposals. We further show that the adopted encoding scheme effectively embeds an

environmental prior for natural image statistics within the sensory measurement, providing

the functional architecture necessary for optimal inference in the earliest stages of cortical

processing.

INTRODUCTION

The human visual system is tasked with inferring environmental attributes from image data that can be corrupted by noise from both internal and external sources. To combat the influence of such noise, a statistically optimal, or ideal, observer would compute the distribution of possible environmental states, and combine this prior information with incoming sensory signals to infer the true state of a scene[1]. While this general framework for understanding sensory encoding is relatively uncontroversial, the biological instantiation of the prior for environmental statistics is largely mysterious.

Sensory representations are thought to be tuned to behaviourally relevant statistics of natural environments over evolutionary and developmental timescales[1–4]. As shown in **Figure 1a**, edges and contours in natural images are primarily oriented along the cardinal axes[5–8]. There is a corresponding anisotropy in the orientation selectivity of visual neurons in several mammalian species that prioritises the encoding of cardinally oriented information (**Fig. 1b**; Fang et al., 2022; Roth et al., 2012; Wang et al., 2003). Analogously, humans are superior on a range of visual tasks for stimuli that are oriented around cardinal orientations relative to oblique orientations [12]. Such biases in encoding and behaviour are even present in artificial intelligence systems trained on naturalistic movies[13,14]. Several computational accounts have attempted to unify the influence of environmental statistics on the properties of sensory neurons as well as perception[5,15,16], but have been unable to address empirically how such encoding is implemented at the neural level.

Figure 1. Neural tuning anisotropies mirror natural image statistics. a) Example image of natural scene (left) and its composite orientations (right). Orientations are coloured according to inset colour wheel; summary of relative orientation distribution indicated by inset histogram. b) Distribution of orientation selectivity in primary visual cortex of mouse[10], cat[11], and macaque[9].

One way in which environmental regularities could be represented by biological systems is via sensory encoding schemes that allocate neural resources in relation to the natural frequency of various features. However, such models are consistent with multiple competing encoding schemes. In the domain of visual orientation, for example, biases in perception can be explained by corresponding biases in either the width *or* spacing of

sensory tuning curves[5,15–18]. Therefore, while it is generally accepted that perceptual biases

can be linked to anisotropies in environmental statistics, there is far less clarity about how

these anisotropies are represented in the human visual system (as discussed in [19]).

Moreover, leading models that account for cardinal biases in perception equate the prior

probability of horizontal and vertical features[5,15,16], whereas earlier work suggests that

horizontal features are over-represented relative to vertical[6,20]. These discrepancies may

obfuscate a clear understanding of neural encoding schemes; we are not aware of any prior

work that has attempted to link such biased environmental statistics with population-level

responses of the human visual system. The way in which environmental priors are

represented in biological systems is a critical gap in our understanding of how the brain

achieves optimal inference.

In the present study, we investigated the instantiation of environmental priors in the

human visual system using electroencephalography (EEG) and inverted encoding

models[21,22]. We developed novel neural decoding and generative modelling procedures with

which to infer anisotropic coding in the human visual system, and compared these

anisotropies with responses generated from encoding schemes with known neural response

functions. Our approach therefore provides a generalisable means to test arbitrarily

specified sensory encoding schemes. We show, however, that no previously proposed

encoding scheme can explain the empirical neural data. Instead, we show that anisotropic

neural responses can be explained almost entirely by a redistribution of sensory tuning

curves that prioritises the most dominant environmental structure. We further show that the

recovered neural code embeds a prior for natural image statistics within the sensory

measurement, thereby simplifying the biological instantiation of optimal inference. Our

results thus support the biological plausibility of perception as Bayesian inference by

explaining how prior expectations are encoded by the tuning properties of sensory neurons.

RESULTS

Decoded neural responses over-represent horizontal. We recorded human

observers' brain activity with EEG while they viewed rapidly presented oriented gratings

(randomly sampled from a uniform distribution between 0-180º) and monitored for

occasional changes in spatial frequency (**Fig. 2a**). Prior to the main analyses of the neural

activity evoked by the gratings, we established that orientation information was primarily

represented in parietal and occipital EEG sensors (**Fig. S1**; *Method - Neural Decoding*);

thus, we only included the signal from these 20 sensors in all subsequent analyses (inset of

Fig. 2b, cyan dots). We first characterized orientation-related univariate activity. We sorted
the gratings into six orientation bins (±15º around 0º, 30º, 60º, 90º, 120º, and 150º, where
0º is horizontal) and calculated the difference between the average evoked response for
each bin from the grand average of all gratings. As shown in **Figure 2b**, there were
significant differences in the response to orientations between approximately 50 to 400 ms
following stimulus onset. The largest deviation from the mean response to all gratings was
for horizontal orientations, which occurred in the initial stages of stimulus processing (50-
100 ms following stimulus onset). We then collapsed the responses across time and
calculated the average absolute response for each grating orientation and found that
response amplitude peaked around horizontal gratings (**Fig. 2c**).

Figure 2. Anisotropic univariate neural responses evoked by oriented gratings. a)
Schematic showing the experimental design; observers viewed rapidly presented
oriented gratings (neural probe) while monitoring for target gratings with lower
spatial frequency. Following the neural probe, participants indicated the number of
target gratings detected using the mouse. b) Difference in event related potentials for
gratings within orientation bins ([0°, 30°, 60°, 90°, 120°, 150°] ±15°) from the average
of all orientations. Signals averaged across parietal and occipital EEG sensors (blue
dots on topographic map) and participants (n=36). Orientation bin indicated in colour;
event-locked and subsequent gratings indicated by solid and dashed black
rectangles, respectively, and cluster-corrected periods of significant difference
between orientations indicated by horizontal black bars. c) Time-averaged absolute
signal amplitude for each grating orientation, binned to the nearest whole degree. The
black line indicates the moving averages of data points.

We next quantified temporal dynamics in orientation tuning using inverted encoding
analyses[21]. Using cross-fold validation, we trained and tested an inverted model using the
EEG signals to decode the orientation of each grating from the neural activity at each time
point. From the trial-by-trial decoded signals, we derived summary parameter estimates of
orientation tuned responses (the strength of the response at the presented stimulus
orientation), *precision* (the variability of decoded orientations within each bin), and *bias* (the
average decoded angle relative to the presented orientation; see *Method – Neural*
Decoding).

The results from the neural decoding are shown in cyan in **Figure 3**. Orientation tuned

responses rose sharply from ~50 ms following stimulus onset and gradually reduced over

the following 400 ms (**Fig. 3a**, cyan data), revealing that decodable information is relatively

stable across time, consistent with recent work[23,24]. We found a similar pattern of results for

the *precision* of decoded responses (**Fig. 3b**, cyan data), with precision increasing sharply

from ~50 ms and gradually reducing. Precision was significantly above chance prior to

stimulus presentation, likely because the decoder produced an over-representation of some

orientations, which is consistent with the anisotropic representation of orientations shown in

Figure 2c. As expected, we found no significant deviations in bias when averaged across

orientations (**Fig. 3c**, blue data). The orange data in **Figure 3** are the results of a re-analysis

of a previous study[23], which we will describe further in the following section.

Figure 3. Anisotropies in the neural representation of orientation revealed by inverted encoding. Average a) orientation response, b) precision (normalized decoding variability of decoded orientations, from 0 [uniform distribution] to 1 [no variability]), and c) bias of orientations decoded from neural responses. Cyan and orange lines indicate data from our experiment and from a previously published study[23], respectively. Shaded error bars in (a-b) and (c) indicate SEM and CI_{95}, respectively; coloured horizontal bars indicate cluster corrected periods that showed a significant difference from chance; horizontal dashed lines indicate chance-level. Note that this difference was significant for the entire period displayed in (b). d-f) The time-averaged (d) orientation response, (e) precision, and (f) bias of the inverted model responses, at all orientations, calculated from data collected in our experiment. Cyan lines in (d-f) indicate moving averages of data points (semi-transparent cyan dots). g-i) Same as (d-f), but calculated from previously published data [23].

Neural coding is highly anisotropic. To quantify stimulus-specific variations in neural representations, we measured orientation tuned responses, precision, and bias as a function of grating orientation. To do so, we developed a novel inverted model analysis which returns these parameter estimates for each of 180 unique grating stimuli (one for each orientation rounded to the nearest degree; *Methods – Neural Decoding*). To maximize the signal-to-noise ratio for each bin, we averaged results over the period in which there was above-chance orientation response (50-450 ms), but the pattern of results is stable across different periods (**Fig. S2**).

Neural responses were strongly anisotropic, but not in a way predicted from any leading model of neural coding[15,16]. For orientation tuned responses, we found a trimodal

pattern of results such that there was one large peak centered on horizontal and two smaller peaks positioned around vertical (**Fig. 3d**). By contrast, we found a unimodal pattern of results for precision, such that horizontal gratings were decoded most precisely (**Fig. 3e**). We found a sinusoidal pattern of biases, comprising two attractive curves centered on the cardinal gratings (**Fig. 3f**). Although we found better orientation tuning and precision for horizontal orientations, the magnitude of the attractive biases was larger around the vertical than the horizontal gratings. A split-half analysis of the neural signals in the epoch used to decode orientation parameters confirmed this pattern of results was stable over the course of the epoch (**Fig. S2**).

To test the reproducibility of these results, we performed these analyses on a separate, previously published, dataset[23]. This prior study differed from our own in many aspects, such as the stimulus parameters, the observers' task, and the temporal design, which resulted in differences in the temporal dynamics of the decoded signal (as shown in **Figure 3a-c**, orange data). Despite these considerable differences across experiments, however, we found strikingly similar stimulus-specific variations in neural representations (**Fig. 3g-i**). Note that the observers' task in the previous study was to report whether grating stimuli were more cardinally or obliquely oriented on a given trial, resulting in increased precision around those orientations (**Fig. 3h**). This re-analysis therefore demonstrates that our neural decoding method is sensitive to task-related goals, with replicable estimates of orientation anisotropies in tuned responses and bias.

Generative modelling of neural population responses. Previous theoretical work provides two primary variations in efficient encoding schemes to explain how anisotropies in orientation coding could be implemented at the neural level[5,15,16]. The proposed neural populations are instantiated such that either neurons tuned to cardinal orientations have narrower tuning (**Fig. 4a**, uneven tuning width) or that there are more neurons tuned to cardinal orientations (**Fig. 4a**, uneven tuning preference); however, these competing explanations cannot be resolved using behavioural measurements as they predict the same patterns of estimation error. To adjudicate between these population codes, therefore, we developed a novel generative modelling procedure to simulate EEG activity from neural tuning functions that had either isotropic tuning, or anisotropic tuning as specified by uneven tuning widths or uneven tuning preferences (*Methods – Generative Modelling*). We then applied the same inverted encoding analyses used on the empirical data to estimate orientation tuned responses, precision, and bias, as a function of orientation (**Fig. 4b**). While concerns have recently been raised about the extent to which inverted encoding analyses

can be used to infer population representations[25–27], our novel generative modelling

approach overcomes such issues by directly mapping the transformation of the output of a

range of generative models to neural responses. A similar implementation has recently

shown that such an approach is sensitive to changes in underlying population

representations[28]. If either of the hypothesised models of anisotropic orientation coding

explains the true underlying neural implementation, then the empirical data should match

the decoded responses of the simulated data from only a single generative population code.

Figure 4. Generative modelling of anisotropic neural tuning properties. a) Neural
response functions for a population of orientation tuned neurons. Neurons may have
even tuning properties across all orientations (even tuning), but theoretical work
suggests that the anisotropies in orientation perception are either explained by
denser clustering (uneven tuning preference) or narrower tuning (uneven tuning
width) of neurons around cardinal orientations. Horizontally distributed black dots
indicate tuning preferences. b) Illustration of the generative modelling procedure
used to simulate neural data to test hypotheses of cardinal biases. A bank of
orientation tuned neurons are connected to EEG sensors via random weights. We
simulate EEG activity in response to multiple oriented gratings and then decode the
orientation using inverted encoding. From the decoded orientations we calculate
orientation response, precision, and bias parameters.

We first generated neural responses from an unbiased isotropic bank of tuning

functions (**Fig. 4a**, even tuning). As expected, this simulation did not replicate the pattern of

results observed for the empirical data, as it produced a uniform pattern of orientation tuned

responses, precision, and biases across all orientations (**Fig. 5a**). We then generated neural

responses from an anisotropic bank of tuning functions specified by narrower tuning around

the cardinals (**Fig. 5b**). Although this population code produced a non-uniform distribution

of parameter estimates, the pattern of results did not match the empirical data: orientation

tuned responses and precision peaked around the obliques, not cardinals, and there was

no clear pattern of biases. Finally, we generated neural responses from tuning functions with

orientation tuning preferences clustered around the cardinals (**Fig. 5c**). The pattern of

orientation tuned responses, precision, and biases produced by this simulation captured the

empirical results best out of the three models tested: orientation tuned responses and

precision peaked around cardinals, with modest attractive biases. In contrast to the empirical

results of the two datasets, however, the peak responses and biases around horizontal and

vertical orientations were equivalent, revealing that the modelled response functions did not

fully reflect the neural architecture underlying orientation anisotropies in human visual

cortex.

Figure 5. Standard encoding schemes produce anisotropic neural representations of orientation, but do not explain the empirical data. a-c) Results of simulations using neural response functions with (a) even or uneven (b) width, (c) or preference. The left column shows the neural response functions from which data were derived. The columns to the right are the parameter estimate results. Dark grey lines in indicate moving averages of data points (semi-transparent dots). Blue insets show the corresponding moving averages from the empirical data; horizontally distributed black dots in the left panels indicate tuning preferences.

Neither of the proposed tuning schemes reproduced the empirical results. We therefore exhaustively searched the space of cardinal and oblique tuning biases to test which population code best explained the empirical data. We chose to manipulate tuning preferences because the uneven tuning preference scheme provided the most promising match to the empirical data (**Fig. 5c**). The modelled data and empirical data were compared using their *discriminability*[29], a metric that considers the precision and bias – but not the orientation tuned response – of the decoded signal. We computed the similarity between the discriminability of the empirical results and from data generated from population codes comprising all possible combinations of horizontal and vertical biases (**Fig. 6a**), i.e., by independently varying the clustering around horizontal and vertical orientations. We found that the model that best described the empirical data was a population code with anisotropic cardinal biases, where horizontals are 'more preferred' than verticals by a ratio of approximately 2:1. These results are consistent with our univariate analyses (**Fig. 2**), and confirm that there is an asymmetry between cardinal orientations, such that horizontals are

more preferred than verticals. Further, the ratio of horizontal to vertical asymmetry is
consistent with previous estimates of the orientation content in natural visual scenes, but
not human-made scenes[5].

A population code with uneven tuning preferences and an asymmetric cardinal
anisotropy captured the empirical results well (**Fig. 6b**): this model reproduced the increased
precision at horizontal orientations, and the sinusoidal pattern of biases with a larger
attractive bias around vertical gratings. It also reproduced the trimodal distribution of
orientation tuned responses, despite this metric not being used in the discriminability metric
used in the fitting procedure. It is unclear, however, to what extent the redistribution of tuning
curves around horizontal and vertical each influence the decoded pattern of anisotropic
orientation representation; that is, which changes in orientation tuned responses, precision,
and biases are related to the horizontal preference, and which are related to the vertical
preference? To address this question, we generated EEG data from neural tuning functions
with tuning preferences for horizontal orientations only (**Fig. 6c**). This simulation captured
many of the phenomena observed in the empirical results: it recapitulated the increased
orientation tuned response and precision for horizontal gratings, and the asymmetric
attractive biases around cardinal gratings. We did not expect a horizontal preference to
capture the empirical patterns of results more closely than the classic symmetric cardinal
preference models shown in **Figure 5b-c**.

Figure 6. Horizontal preferences explain orientation anisotropies in human visual cortex. a) Difference (error) in discriminability (see *Methods – Generative Modelling* for detailed description) between empirical and simulated data as a function of horizontal and vertical clustering in the generative population code; less error indicates greater similarity between empirical and simulated data. The black outline indicates the region with the lowest 5% of error, and the white dashed circles indicate the position of the example population codes shown on the right. The red dotted circle indicates the position of the best fitting model (4). Results of simulations using neural response functions with **(b)** asymmetric cardinal tuning preferences and **(c)** unimodal horizontal tuning preference. The left column shows the neural response functions from which data were derived. The columns to the right are the parameter estimate results. Dark grey lines indicate moving averages of data points (semi-transparent dots). Blue insets show the corresponding moving averages from the empirical data; horizontally distributed black dots in the left panels indicate tuning preferences.

A key diagnostic characteristic of the two empirical datasets is the reduction in orientation responses for vertical orientations (**Fig. 3d, 3g**). This feature is only captured by a population code with asymmetric cardinal preferences (**Fig. 6b**). To understand why asymmetric cardinal preferences are critical to reproduce the neural responses around vertical orientations, we varied the noise level in the generative model. In the models presented above, we matched each population code to the signal-to-noise of the empirical data by titrating the noise injected into the simulated data (see *Method – Generative*

Modelling). By reducing the noise level in the generative models, we can uncover the

explanation for the reduction in neural responses around vertical: the reduced orientation

tuned response around vertical is due to a small repulsive bias (**Fig. S3**). This repulsive bias

around vertical and the attractive bias around horizontal are additive, resulting in the

appearance of a plateau in overall bias around vertical that can be seen in both empirical

datasets (**Fig. 3f, 3i**) as well as the generated data (**Fig. 6b**), all of which include the

influence of noise.

Joint coding of the prior and sensory measurement. A general solution to

performing Bayesian inference involves embedding the prior *within* the sensory

measurement[30–32]. In brief, if tuning curves are distributed such that their sum approximates

the log of the prior, then the posterior is a linear readout of the population response,

simplifying the biological instantiation of optimal inference (full mathematical detail is given

in *Method – Joint coding of the prior and sensory measurement*). We therefore compared

how well the properties of the best-fitting population code, derived from our data-driven

approach described above, capture environmental priors for natural and constructed scenes

(**Fig. 7**). This analysis revealed that the sensory tuning curves do indeed embed the prior

for natural image statistics (left panels, **Fig. 7**). The activity of the population code that best

captures the responses of the human visual system therefore provides a stimulus

representation from which a full (log) posterior can be computed through simple linear

summation of activity, resulting in optimal inference in natural scenes. By comparison, the

properties of the population code provide a poorer description of the prior for constructed

scenes (right panels, **Fig. 7**).

Figure 7. The redistribution of tuning curves effectively embeds a prior for natural image statistics in the sensory measurement. a) Horizontal-biased population code that best explained the neural responses, as described in Results. **b-c)** The left and right plots show the match of the properties of this population code with the distribution of orientation statistics for natural scenes (b) and constructed scenes (c) as measured by Girshick et al. (2011). In each plot, the coloured trace shows the probability of each orientation in a set of images, while the black trace shows the exponentiated sum of the best fitting tuning functions recovered from our generative model. Extending theory developed by Simoncelli (2009), the exponentiated sum of the tuning curves is proportional to the prior for natural scenes: $\exp(\sum_n f_n(\theta)) \propto P(\theta)$. Assuming Poisson neural variability, this allows the log posterior to be obtained as a weighted sum of the neural responses: $\log P(\theta|\mathbf{r}) = \sum_n r_n \log f_n(\theta) + const.$, providing an efficient means by which to perform optimal inference in the human visual system.

DISCUSSION

We investigated whether the human visual system represents environmental attributes that are critical for optimal inference. Using our novel decoding analyses, we quantified surprising anisotropic neural responses that deviated from the expectations of leading models of visual prediction. By developing novel generative modelling tools, we were able to recover the underlying tuning properties of the population code driving the anisotropic neural responses. In addition to the cardinal anisotropy of orientation coding suggested by prior computational and behavioural investigations[5,15,16], we reveal that an asymmetry in cardinal representations is an inherent property of visual coding. Most importantly, our data provide the first clear evidence for a recent hypothesis about how priors are instantiated in biological systems[30]: the prior is embedded in the sensory measurement (**Figure 7**). By adjusting tuning curves to prioritise horizontal orientations and, to a lesser extent, vertical orientations, the early visual system implicitly combines the prior for natural images with incoming sensory signals. This coding scheme negates the need for the prior to be represented by a separate population of neurons, thereby improving neural efficiency.

The prioritisation of neural resources to horizontal orientations can be understood in the context of efficient coding[33]. A neural code is efficient if resources are allocated proportionally to the variation in the input signal along some feature dimension. While most prominent computational work models the anisotropic distribution of orientations as being

symmetrical across cardinals, differences in horizontal and vertical contrast energy have been reported in measurements of natural image statistics[6,7] and a matching asymmetry has been observed in the tuning preferences of orientation-selective neurons[9–11]. For example, in a recent analysis of over 26,000 high quality digital photos of natural images, Harrison[7] reported that horizontal orientations were 10% more prevalent relative to vertical orientations. In an earlier analysis of 60 images, Hansen and Essock[20] found a similar over-representation of horizontal information across multiple spatial scales, suggesting the dominance of horizontal information is a scale invariant property of natural scenes. In their Bayesian account of visual orientation perception, Girshick et al.[5] derived estimates of observers' priors for orientation and found a close correspondence to cardinally-biased, but symmetric, environmental statistics. Close inspection of their results, however, shows that both the average of observers' recovered prior and the distribution of image statistics indicated greater representation of horizontal over vertical information, particularly in images of natural scenes (their data are re-plotted as the coloured traces in **Fig. 7**). A sensory population code that prioritises horizontal information over vertical, and cardinals over obliques, can thus be interpreted as representing the true distribution of environmental statistics derived from natural scenes. It is interesting to note that the sum of the tuning curves provides a relatively poor approximation of the statistics of constructed scenes, raising the possibility that the default tuning of sensory systems depends more on statistics accumulated over evolutionary time scales than developmental time scales.

Linking anisotropies in orientation perception to neural tuning schemes is challenging because behavioural measurements are confounded by response biases, which can be in direct conflict with perceptual biases[34]. Here we avoided this confound by measuring biases in the neural representation of passively viewed oriented gratings, and we then replicated these effects using an independent dataset in which observers were actively engaging in a visual discrimination task. A further advantage of our method is that it allowed us to directly test, through generative modelling, the population level neural tuning properties that give rise to anisotropies in the representation of orientation. The impact of this method is highlighted by the inability of previous work to adjudicate between population codes designed with uneven tuning preferences versus uneven tuning widths. Our results may appear to contradict earlier neuro-imaging studies that found horizontal and vertical orientations are equally over-represented in cortex relative to obliques[35]. However, close inspection of these earlier data also reveals a clear horizontal/vertical asymmetry. It is therefore likely that the assumption of equal cardinal responsiveness has led the

asymmetries we reveal to have been overlooked in more recent neuro-imaging investigations[36,37].

Beyond providing a diagnostic marker for the underlying neural implementation of orientation tuning in the human visual cortex, the reduced orientation tuned responses and small repulsive bias around vertical gratings (**Fig. S3**) may explain previous inconsistencies in the behavioural literature of perceptual cardinal biases. In particular, both attractive and repulsive perceptual biases have been reported around the cardinal orientations, when measured using different experimental paradigms[5,34,38]. This discrepancy has been explained within a Bayesian framework as the result of either manipulating external (stimulus) or internal (neural) noise[16]. Under this framework, humans are assumed to have a prior distribution that gives preference to cardinal orientations. Increasing external noise results in a greater reliance on this prior (attraction towards cardinals), whereas increasing internal noise produces a bias away from this prior (repulsion away from cardinals). Our findings show that there is small repulsive bias around vertical, which is surrounded by a - considerably larger - attractive bias. It is feasible that the smaller repulsive bias could be obscured by the larger attractive bias under conditions of low signal-to-noise. Thus, this provides an alternative explanation for how manipulating noise could lead to observing either attractive or repulsive biases (at least around vertical orientations), which can be tested in future psychophysical investigations.

In summary, here we apply novel neural decoding and generative modelling approaches that reveal, replicate, and explain hitherto unknown aspects of sensory anisotropies. For the first time, we adjudicate between competing models of uneven neural tuning, demonstrating that uneven tuning preferences, but not tuning width, explain cardinal biases. We further show that anisotropies in the representation of orientation are almost entirely explained by a preference for horizontal orientations, while the smaller preference for vertical orientations produces a small repulsive bias that may account for previous discrepancies in attractive and repulsive cardinal bias. More broadly, we demonstrate both a new neural decoding algorithm and a corresponding generative modelling procedure that can be used in a principled manner to describe neural representations in high fidelity and explain their underlying architecture.

METHODS

Participants. Thirty-seven neurotypical human adults (mean±standard deviation age, 23.8±4.6 years; 23 females) participated in the experiment. Observers were recruited from The University of Queensland, had normal or corrected-to-normal vision (assessed using a standard Snellen eye chart), and were required to pass an initial screening session to qualify for the experiment (see *Stimuli, task, and procedure* Section for details). Data from one participant were omitted from analyses due to hardware failure. All participants were naïve to the aims of the experiment and gave informed written consent. The experiment was approved by The University of Queensland Human Research Ethics Committee.

Apparatus. The experiment was conducted in a dark, acoustically and electromagnetically shielded room. The stimuli were presented on a 24-inch ViewPixx monitor (VPixx technologies, Inc., Montreal) with 1920 x 1080 resolution and a refresh rate of 144 Hz. Viewing distance was maintained at 45 cm using a chinrest, meaning the screen subtended 61.18º x 36.87º (each pixel 2.4' x 2.4'). Stimuli were generated in MATLAB (The MathWorks, Inc., Matick, MA) using Psychophysics Toolbox[39,40] (see http://psychtoolbox.org/). EEG signals were recorded using 64 Ag-AgCl electrodes (BioSemi, Amsterdam, Netherlands).

Stimuli, task, and procedure. The stimuli comprised sinewave gratings (1 cycle/º, 0.5 contrast, random phase) presented centrally within a circular aperture (radius 4.2º), which was smoothed at the edges, on a mid-grey background. A centrally positioned green fixation dot (radius 0.25º) was presented to reduce eye movements. To maintain attention, participants were instructed to count the number of 'target' stimuli, in which the spatial frequency of the grating was reduced (0.66 cycle/º). Between 0-3 targets appeared during each trial, selected at random.

Trials consisted of grating stimuli (orientations randomly selected between 0-180º) presented for .05 s each, separated by a blank 0.15 s inter-stimulus-interval (ISI) for 10 s (neural probe). The numbers 0-3 were then displayed on the screen and participants were given 2 s to indicate the number of targets presented, using the mouse (detection task). This was repeated 12 times per block. Participants performed 6 blocks of trials (~20 min), receiving feedback on their detection accuracy at the end of each block.

Prior to the main experiment, participants were required to pass an initial screening session in which they completed the same task but without EEG. To pass the screening, participants were required to perform above chance (25%) on the detection task. Further, they were required to show a significant repulsive bias on a separate orientation

reproduction task (assessed using a one-tailed *t*-test), which was related to data collected

for a different study. This resulted in approximately half of the participants being screened

out. Screening and experiment sessions were separated by a minimum of 24 h.

EEG. The EEG signals were digitised at 1024 Hz sampling rate with a 24-bit A/D

conversion. The 64 active scalp Ag/AgCl electrodes were arranged according to the

international standard 10–20 system for electrode placement[41] using a nylon head cap. As

per BioSemi system design, the common mode sense and driven right leg electrodes served

as the ground, and all scalp electrodes were referenced to the common mode sense during

recording. Offline EEG pre-processing was performed using EEGLAB in accordance with

best practice procedures[42,43]. The data were initially down-sampled to 512 Hz and subjected

to a 0.5 Hz high-pass filter to remove slow baseline drifts. Using EEGLAB[44], electrical line

noise was removed using *pop_cleanline.m*, and *clean_artifacts.m*[44] was used to remove bad

channels (identified using Artifact Subspace Reconstruction), which were then interpolated

from the neighbouring electrodes. Data were then re-referenced to the common average

before being epoched into segments around each neural probe stimulus (-0.25 s to 0.5 s

from the stimulus onset). Systematic artefacts from eye blinks, movements and muscle

activity were identified using semi-automated procedures in the SASICA toolbox [45] and

regressed out of the signal.

Neural Decoding. To characterise sensory representations of the stimuli, we used

an inverted modelling approach to reconstruct the orientation of the gratings from the EEG

signal[22]. We make several advances in the application of our models that negate the recent

concerns[25,26] about the validity of the properties of the recovered population code (see

Generative Modelling section below*)*. A theoretical (forward) model was nominated that

described the measured activity in the EEG sensors given the orientation of the presented

grating. The forward model was then used to obtain the inverse model that described the

transformation from EEG sensor activity to stimulus orientation. The forward and inverse

models were obtained using a ten-fold cross-validation approach in which 90% of the neural

probe data were used to obtain the inverse model on which the remaining 10% were

decoded. In our modelling, we assume that EEG sensor noise is isotropic across

orientations and additive with the signal; while this assumption would be violated if there

were a systematic relationship between orientation preference and anatomical location

across participants, abundant evidence rules out such a relationship in human and non-

human brains[9,46–48].

Similar to previous work[21], the forward model comprised six hypothetical channels,

with evenly distributed idealized orientation preferences between 0° and 180°. Each channel

consisted of a half-wave rectified sinusoid raised to the fifth power. The channels were

arranged such that a tuning curve of any orientation preference could be expressed as a

weighted sum of the six channels. The observed EEG activity for each presentation could

be described by the following linear model:

$$\mathbf{B} = \mathbf{WC} + \mathbf{E} \tag{1}$$

where $\mathbf{B}$ indicates the (m sensors $\times$ n presentations) EEG data, $\mathbf{W}$ is a weight matrix (m

sensors $\times$ 6 channels) that describes the transformation from EEG activity to stimulus

orientation, $\mathbf{C}$ denotes the hypothesized channel activities (6 channels $\times$ n trials), and $\mathbf{E}$

indicates the residual errors.

To compute the inverse model, we estimated the weights that, when applied to the

data, would reconstruct the underlying channel activities with the least error. Similar to

previous MEG work[24,49], when computing the inverse model, we deviated from the forward

model proposed by [21] by taking the noise covariance into account to optimize it for EEG

data, given the high correlations between neighbouring sensors. We then estimated the

weights that, when applied to the data, would reconstruct the underlying channel activities

with the least error.

In the orientation focused analyses (**Fig. 3d-e**), we adapted a method recently

introduced by [27], which uses sparsely distributed channels to produce a dense

representation of channel responses. The standard inverted modelling approach typically

involves training and testing a model using a relatively small number of channels (e.g., 6) to

represent the entire spectrum of identities across a given feature (e.g., orientation). The

'enhanced inverted encoding model' (eIEM) method involves repeatedly computing the

inverse model while rotating the forward model channel orientation preferences until each

orientation is represented by a channel response (e.g., 180 channels, one for each

orientation). The eIEM method was established using data with feature identities sampled

from discrete bins, which determines: *a*) the number of channels used in each model, and

b) the number of feature identities from which predictions could be derived from the dense

output. By contrast, we presented observers with orientations sampled from a continuous

uniform distribution of all orientations. Thus, while we sorted presentations into five

orientation bins to maintain sufficient data to estimate the weights for each channel, after

rotating channels to produce 180 channel responses for each trial, we then binned the

responses according to the orientation nearest to that presented in each trial. This allowed us to produce high-resolution model predictions for each orientation. We performed this analysis at each time point within the epoch, but to improve the signal of the estimates we averaged predictions across time points when there was reliable decoding accuracy (50-450 ms following stimulus onset).

For each presentation, we decoded orientation by converting the channel responses to polar form:

$$z = \mathbf{c} \cdot e^{2i\varphi} \tag{2}$$

and calculating the estimated angle:

$$\hat{\theta} = \frac{\arg(z)}{2} \tag{3}$$

where $\mathbf{c}$ is a vector of channel responses and φ is the vector of angles at which the channels peak (multiplied by two to project 180° orientation space onto the full 360° space). From the decoded orientations, we computed three estimates: *orientation tuned response*, *precision*, and *bias*. Orientation tuned responses represented the strength of the response at the presented orientation[24], and were expressed by projecting the mean resultant of the difference between decoded and grating orientations onto a vector with 0°:

$$\hat{r}_\theta = \mathrm{Re}[\bar{R}], \quad \bar{R} = \frac{1}{n}\sum_{j=1}^{n} \exp\left(i(\hat{\theta}_j - \theta)\right) \tag{4}$$

Precision was estimated by calculating the angular deviation [50] of the decoded orientations within each orientation bin:

$$\hat{\sigma}_\theta = \sqrt{2(1 - |\bar{R}|)} \tag{5}$$

and normalized, such that values ranged from 0 to 1, where 0 indicates a uniform distribution of decoded orientations across all orientations (i.e., chance-level decoding) and 1 represents perfect consensus among decoded orientations:

$$\hat{p}_\theta = 1 - \frac{2\hat{\sigma}_\theta}{\sqrt{2}} \tag{6}$$

Bias was estimated by computing the circular mean of angular difference between the decoded and presented orientation:

$$\hat{b}_\theta = \arg(\bar{R}) \tag{7}$$

Prior to the main neural decoding analyses, we established the sensors that contained the most orientation information by treating time as the decoding dimension and obtaining inverse models for each sensor, using ten-fold cross-validation. This analysis revealed that orientation was primarily represented in posterior sensors (**Fig. S3**); thus, for

all subsequent analyses we only included signals from the parietal, parietal-occipital,
occipital, and inion sensors to compute the inverse model.

Generative Modelling. To characterise changes in neural tuning which might have
given rise to the empirical results observed, we used inverted modelling to decode
orientation from simulated EEG data produced by neural populations with either isotropic
tuning or anisotropic tuning specified by differences in tuning preferences or tuning widths.
Although the empirical EEG data comprises a time series of neural activity, we only
simulated temporally static data as we were comparing this with the time averaged
empirical data. Simulated data were produced by assuming variable weights between a
bank of response curves, each of which represented the aggregate responses of neural
populations with similar tuning, with different orientation preference (n=16) and EEG sensors
(m=32). As with the forward model, the neural functions were arranged such that a tuning
curve of any orientation preference could be expressed as a weighted sum of the 16
functions. Thus, for each simulated presentation, the EEG activity was computed as:

$$s_i = \mathbf{c_\theta}\mathbf{w}_i + u \tag{8}$$

where s_i denotes the activity of sensor i, $\mathbf{c}_\theta$ indicates the tuning curve of orientation θ, $\mathbf{w}_i$
denotes the weights between the sensor i and the response functions, and u indicates
Gaussian noise (s.d.=6). The noise level was selected to approximate the level of noise
observed in the empirical results. Neural tuning consisted of von Mises functions (κ=2),
normalized such that they ranged from 0 to 1. Neuron-to-sensor weights were randomly
assigned from a uniform distribution between 0 and 1. Uneven *tuning preferences* were
modelled by shifting the neural tuning functions according to the sum of two von Mises
derivative functions (κ=0.5) centered on 0° (amplitude=15) and 90° (amplitude=10), such
that the maximum shift applied was 15°. Uneven *tuning widths* were modelled by narrowing
the neural tuning functions according to the sum of two von Mises functions (κ=2) centered
on 0° (amplitude=15) and 90° (amplitude=10), such that the maximum increase to κ was 15.

In line with the empirical experiment, the orientation of each simulated presentation
was drawn from a uniform distribution between 1-180°. We simulated 3600 presentations
from the even and uneven neural response functions. We then applied the same analyses
as used on the empirical data to estimate orientation tuned response, precision, and bias as
a function of orientation. The final presented results are the average of parameters
estimated from 36 simulated datasets.

To find the orientation anisotropy that best captured the empirical neural data, we
computed the difference (error) between the empirical data and data that was simulated
using all possible combinations of cardinal and oblique neural tuning preferences. The error
was calculated as the difference between the *discriminability* of the decoded orientations
from empirical and simulated data. Discriminability combines measures of precision and bias
to provide an index of how discriminable signals are at each orientation [29]:

$$d_\theta = \frac{\hat{\sigma}_\theta}{1 + \hat{b}'_\theta} \tag{9}$$

555 where $\hat{b}'_\theta$ is the change in bias at orientation θ, which we estimated as:

$$\hat{b}'_\theta \approx \frac{\hat{b}\left(\theta + \frac{\delta}{2}\right) - \hat{b}\left(\theta - \frac{\delta}{2}\right)}{\delta} \tag{10}$$

where δ indicates the size to the window of estimation (16°). The generative data was
stochastic, due to the injected noise, so we calculated the error ten times for each model
and used the average. Neural tuning preference anisotropies were produced in the same
manner as described above, and the amplitude of the shift was independently varied around
both horizontal (0°) and vertical (90°) orientations, from -45 to 45, in increments of 1,
resulting in a total of 91×91=8281 models.

Joint coding of the prior and sensory measurement. Although there is general
agreement that the brain combines prior information with sensory signals, the physiological
implementation of such Bayesian inference is less clear[51–54]. In a population of *N* neurons
with independent Poisson variability and tuning curves $f(\theta)$, the joint likelihood of the
response of the population given a stimulus of orientation θ is:

$$P(\mathbf{r}|\theta) = \prod_n^N \frac{f_n(\theta)^{r_n}}{r_n!} e^{-f_n(\theta)} \tag{11}$$

567 where $\mathbf{r}$ is a vector containing each unit's spike count and r_n is the number of spikes for unit
568 n. It is convenient for biological sensory systems to signal log probabilities so that joint (log)
569 probabilities can be computed linearly, for example by summing spikes:

$$\log P(\mathbf{r}|\theta) = \sum_n^N r_n \log f_n(\theta) - \sum_n^N f_n(\theta) - \sum_n^N \log r_n! \tag{12}$$

570   Bayes' rule tells us that the posterior is computed by multiplying the likelihood, for
571 example as computed above, with a prior, $P(\theta)$, and dividing by the marginal likelihood,
572 $P(\mathbf{r})$. Using log probabilities, the formulation for computing the log-posterior can then be
573 written as:

$$\log P(\theta|\mathbf{r}) = \sum_n^N r_n \log f_n(\theta) - \sum_n^N f_n(\theta) + \log P(\theta) + C_1 \qquad (13)$$

where C_1 is a normalizing constant that does not depend on θ and can be ignored for purposes of comparing posterior probabilities or obtaining a *maximum a posteriori* (MAP) estimate. Estimating the posterior in this way would require at least three populations of neurons (or if, for example, the computations are performed via the weights of lateral connections, three sets of weights): one set to encode the stimulus, one to represent the prior, and another to decode the signal. As noted by Simoncelli[30], a more general solution to performing Bayesian inference involves embedding the prior into the sensory measurement by distributing the sensory tuning curves such that their sum is equal (up to an additive constant) to the log of the prior:

$$\sum_n^N f_n(\theta) = \log P(\theta) + C_2. \qquad (14)$$

In this case, the second and third terms of equation 13 cancel out, such that the full log-posterior distribution can be computed (up to an additive constant) as a simple linear function of the sensory measurement:

$$\log P(\theta|\mathbf{r}) = \sum_n^N r_n \log f_n(\theta) + C_3. \qquad (15)$$

This solution is more efficient than encoding the prior in a separate population, requiring only two populations: one to encode the stimulus and another to obtain the linear readout over the population.

The equations above specify optimal inference for a population of spiking neurons, whereas we measured meso-scale activity across the scalp. On the assumption that the best fitting population code we recovered from the neural data is a linear transformation of the underlying neural activity, then if the prior is embedded in the sensory measurement Eq 14 should hold. Or equivalently,

$$e^{\sum_n^N f_n(\theta)} \propto P(\theta). \qquad (16)$$

To test this, we fit the exponentiated sum of the best-fitting tuning curves in our study to the distribution of image statistics as measured by Girshick et al.[5] for natural scenes versus constructed scenes using two separate linear models. While the sum of the tuning curves predicted both sets of image statistics ($ps < .001$), they almost perfectly recovered the statistics of natural scenes, accounting for 92% of the variation in natural scene statistics, while providing a poor fit to constructed scenes, accounting for only 46% of the variation in constructed scene statistics. The requirement that the exponentiated sum of the tuning

curves is proportional to the prior, as specified by equation 16, is therefore met for natural

image statistics. The recovered coding scheme of the human visual system thus embeds

the prior in the sensory measurement, providing a concise means by which to perform

optimal inference.

Re-analysis of published data. To test the reproducibility of our empirical results,

we re-analyzed a dataset from a comparable, previously published, study from another

laboratory [23]. This dataset comprised 32 channel EEG activity in response to viewing of

uniformly sampled oriented gratings. In King and Wyart's[23] experiment, observers were

presented eight rapidly presented (5 Hz) oriented gratings per trial and tasked with reporting

whether the gratings were, on average, aligned more to the cardinal or oblique axes. In total,

there were approximately 4800 presentations per participant, with 15 participants included;

for a more detailed description of the experiment and data, see [23]. We received the

preprocessed data from the authors, on which we performed the same inverted encoding

analyses as used on the data from our experiment.

Statistical analyses. Statistical analyses were performed in MATLAB. For analyses

of differences in univariate responses and parameter estimates between orientations as a

function of time, a cluster correction was applied to remove spurious significant differences.

First, at each time point, the effect size of orientation was calculated. A repeated measures

analysis of variance was applied to calculate the F statistic associated with orientation. Next,

we calculated the summed value of these statistics (separately for positive and negative

values) within contiguous temporal clusters of significant values. We then simulated the null

distribution of the maximum summed cluster values using permutation (n=1000) of the

orientation labels, from which we derived the 95% percentile threshold value. Clusters

identified in the data with a summed effect-size value less than the threshold were

considered spurious and removed.

Data Availability. EEG recordings have been deposited in OSF

(https://osf.io/5ba9y/).

Code Availability. Code has been deposited in GitHub (URL TBA upon publication).

REFERENCES

1. Geisler, W. S. Visual Perception and the Statistical Properties of Natural Scenes. *Annual review of psychology* **59**, 167–192 (2008).

2. Barlow, H. B. Single Units and Sensation: A Neuron Doctrine for Perceptual Psychology? *Perception* **1**, 371–394 (1972).

3. Burgess, A. E., Wagner, R. F., Jennings, R. J. & Barlow, H. B. Efficiency of human visual signal discrimination. *Science* **214**, 93–94 (1981).

4. Srinivasan, M. V., Laughlin, S. B. & Dubs, A. Predictive Coding: A Fresh View of Inhibition in the Retina. *Proceedings of the Royal Society B: Biological Sciences* **216**, 427–459 (1982).

5. Girshick, A. R., Landy, M. S. & Simoncelli, E. P. Cardinal rules: visual orientation perception reflects knowledge of environmental statistics. *Nat Neurosci* **14**, 926–932 (2011).

6. Hansen, B. C. & Essock, E. A. A horizontal bias in human visual processing of orientation and its correspondence to the structural components of natural scenes. *Journal of Vision* **4**, 5 (2004).

7. Harrison, W. J. Luminance and Contrast of Images in the THINGS Database: *Perception* **51**, 244–262 (2022).

8. Oliva, A. & Torralba, A. Modeling the Shape of the Scene: A Holistic Representation of the Spatial Envelope. *International Journal of Computer Vision* **42**, 145–175 (2001).

9. Fang, C., Cai, X. & Lu, H. D. Orientation anisotropies in macaque visual areas. *Proceedings of the National Academy of Sciences* **119**, e2113407119 (2022).

10. Roth, M. M., Helmchen, F. & Kampa, B. M. Distinct Functional Properties of Primary and Posteromedial Visual Area of Mouse Neocortex. *Journal of Neuroscience* **32**, 9716–9726 (2012).

11. Wang, G., Ding, S. & Yunokuchi, K. Difference in the representation of cardinal and oblique contours in cat visual cortex. *Neuroscience Letters* **338**, 77–81 (2003).

12. Appelle, S. Perception and discrimination as a function of stimulus orientation: The 'oblique effect' in man and animals. *Psychological Bulletin* **78**, 266–278 (1972).

13. Rideaux, R. & Welchman, A. E. But still it moves: Static image statistics underlie how we see motion. *J. Neurosci.* **40**, 2538–2552 (2020).

14. Rideaux, R. & Welchman, A. E. Exploring and explaining properties of motion processing in biological brains using a neural network. *Journal of Vision* **21**, 11 (2021).

15. Taylor, R. & Bays, P. M. Efficient Coding in Visual Working Memory Accounts for Stimulus-Specific Variations in Recall. *J. Neurosci.* **38**, 7132–7142 (2018).

16. Wei, X.-X. & Stocker, A. A. A Bayesian observer model constrained by efficient coding can explain 'anti-Bayesian' percepts. *Nat Neurosci* **18**, 1509–1517 (2015).

17. Fischer, B. J. Bayesian estimates from heterogeneous population codes. in *The 2010 International Joint Conference on Neural Networks (IJCNN)* 1–7 (2010). doi:10.1109/IJCNN.2010.5596687.

18. Ganguli, D. & Simoncelli, E. Implicit encoding of prior probabilities in optimal neural populations. in *Advances in Neural Information Processing Systems* vol. 23 (Curran Associates, Inc., 2010).

19. Maloney, R. T. & Clifford, C. W. G. Orientation anisotropies in human primary visual cortex depend on contrast. *NeuroImage* **119**, 129–145 (2015).

20. Hansen, B. C., Essock, E. A., Zheng, Y. & Deford, J. K. Perceptual anisotropies in visual processing and their relation to natural image statistics. *Network: Computation in Neural Systems* **14**, 501–526 (2003).

21. Brouwer, G. J. & Heeger, D. J. Decoding and reconstructing color from responses in human visual cortex. *Journal of Neuroscience* **29**, 13992–14003 (2009).

22. Brouwer, G. J. & Heeger, D. J. Cross-orientation suppression in human visual cortex. *Journal of Neurophysiology* **106**, 2108–2119 (2011).

23. King, J.-R. & Wyart, V. The Human Brain Encodes a Chronicle of Visual Events at Each Instant of Time Through the Multiplexing of Traveling Waves. *J. Neurosci.* **41**, 7224–7233 (2021).

24. Kok, P., Mostert, P. & de Lange, F. P. Prior expectations induce prestimulus sensory templates. *Proceedings of the National Academy of Sciences* **114**, 10473–10478 (2017).

25. Liu, T., Cable, D. & Gardner, J. L. Inverted Encoding Models of Human Population Response Conflate Noise and Neural Tuning Width. *J. Neurosci.* **38**, 398–408 (2018).

26. Gardner, J. L. & Liu, T. Inverted Encoding Models Reconstruct an Arbitrary Model Response, Not the Stimulus. *eNeuro* **6**, (2019).

27. Scotti, P. S., Chen, J. & Golomb, J. D. *An enhanced inverted encoding model for neural reconstructions*. 2021.05.22.445245 https://www.biorxiv.org/content/10.1101/2021.05.22.445245v2 (2021) doi:10.1101/2021.05.22.445245.

28. Rideaux, R., West, R. K., Rangelov, D. & Mattingley, J. B. Distinct early and late neural mechanisms regulate feature-specific sensory adaptation in the human visual system. *Proceedings of the National Academy of Sciences* **120**, e2216192120 (2023).

29. Wei, X.-X. & Stocker, A. A. Lawful relation between perceptual bias and discriminability. *Proceedings of*
the National Academy of Sciences **114**, 10244–10249 (2017).

30. Simoncelli, E. P. Optimal Estimation in Sensory Systems. (2009) doi:10.7551/mitpress/8029.003.0046.

31. Ganguli, D. & Simoncelli, E. P. Efficient sensory encoding and Bayesian inference with heterogeneous
neural populations. *Neural Computation* **26**, 2103–2134 (2014).

32. Rich, D., Cazettes, F., Wang, Y., Peña, J. L. & Fischer, B. J. Neural representation of probabilities for
Bayesian inference. *J Comput Neurosci* **38**, 315–323 (2015).

33. Simoncelli, E. P. & Olshausen, B. A. Natural Image Statistics and Neural Representation. *Annu. Rev.*
Neurosci. **24**, 1193–1216 (2001).

34. Tomassini, A., Morgan, M. J. & Solomon, J. A. Orientation uncertainty reduces perceived obliquity. *Vision*
Research **50**, 541–547 (2010).

35. Furmanski, C. S. & Engel, S. A. An oblique effect in human primary visual cortex. *Nat Neurosci* **3**, 535–
536 (2000).

36. van Bergen, R. S., Ji Ma, W., Pratte, M. S. & Jehee, J. F. M. Sensory uncertainty decoded from visual
cortex predicts behavior. *Nat Neurosci* **18**, 1728–1730 (2015).

37. Roth, Z. N., Kay, K. & Merriam, E. P. Natural scene sampling reveals reliable coarse-scale orientation
tuning in human V1. *Nat Commun* **13**, 6469 (2022).

38. de Gardelle, V., Kouider, S. & Sackur, J. An oblique illusion modulated by visibility: Non-monotonic sensory
integration in orientation processing. *Journal of Vision* **10**, 6 (2010).

39. Brainard, D. H. The Psychophysics Toolbox. *Spatial Vision* **10**, 433–436 (1997).

40. Pelli, D. G. The VideoToolbox software for visual psychophysics: Transforming numbers into movies.
Spatial Vision vol. 10 437–442 Preprint at https://doi.org/10.1163/156856897X00366 (1997).

41. Oostenveld, R. & Praamstra, P. The five percent electrode system for high-resolution EEG and ERP
measurements. *Clinical Neurophysiology* 7 (2001).

42. Bigdely-Shamlo, N., Mullen, T., Kothe, C., Su, K.-M. & Robbins, K. A. The PREP pipeline: standardized
preprocessing for large-scale EEG analysis. *Frontiers in Neuroinformatics* **9**, (2015).

43. Keil, A. *et al.* Committee report: Publication guidelines and recommendations for studies using
electroencephalography and magnetoencephalography. *Psychophysiology* **51**, 1–21 (2014).

44. Delorme, A. & Makeig, S. EEGLAB: an open source toolbox for analysis of single-trial EEG dynamics
including independent component analysis. *Journal of Neuroscience Methods* **134**, 9–21 (2004).

45. Chaumon, M., Bishop, D. V. M. & Busch, N. A. A practical guide to the selection of independent

components of the electroencephalogram for artifact correction. *Journal of Neuroscience Methods* **250**,

47–63 (2015).

46. Roth, Z. N., Heeger, D. J. & Merriam, E. P. Stimulus vignetting and orientation selectivity in human visual

cortex. *eLife* **7**, e37241 (2018).

47. Larsson, J. & Heeger, D. J. Two Retinotopic Visual Areas in Human Lateral Occipital Cortex. *J. Neurosci.*

26, 13128–13142 (2006).

48. De Valois, R. L., William Yund, E. & Hepler, N. The orientation and direction selectivity of cells in macaque

visual cortex. *Vision Research* **22**, 531–544 (1982).

49. Mostert, P., Kok, P. & de Lange, F. P. Dissociating sensory from decision processes in human perceptual

decision making. *Sci Rep* **5**, 18253 (2015).

50. Zar, J. H. *Biostatistical analysis.* (Pearson Education India, 1999).

51. Georgopoulos, A. P., Schwartz, A. B. & Kettner, R. E. Neuronal Population Coding of Movement Direction.

Science **233**, 1416–1419 (1986).

52. Jazayeri, M. & Movshon, J. A. Optimal representation of sensory information by neural populations. *Nat*

Neurosci **9**, 690–696 (2006).

53. Ma, W. J., Beck, J. M., Latham, P. E. & Pouget, A. Bayesian inference with probabilistic population codes.

Nat Neurosci **9**, 1432–1438 (2006).

54. Pouget, A., Dayan, P. & Zemel, R. S. Inference and Computation with Population Codes. *Annual Review*

of Neuroscience **26**, 381–410 (2003).

SUPPLEMENTARY MATERIAL

Figure S1. Topographic multivariate responses to orientations. a) Topographic orientation responses, averaged across orientation for either the entire epoch (-50 to 500 ms), early in the epoch (50 to 250 ms) or late in the epoch (250 to 450 ms).

Figure S2. Temporal stability of anisotropies in the neural representation of orientation. a-c) The time-averaged (a) orientation response, (b) precision, and (c) bias of the inverted model responses, at all orientations, calculated from neural responses between 50 – 250 ms following stimulus onset. Cyan lines in indicate moving averages of data points (semi-transparent cyan dots). **d-f)** Same as (a-c), but calculated from neural responses between 250 – 450 ms following stimulus onset.

Figure S3. The influence of asymmetric cardinal tuning preferences when neural responses have high signal-to-noise. In our main simulations, we titrated the noise in the data to achieve similar signal-to-noise in the parameter estimates as in the empirical data. To reveal phenomena that may have been obscured by noise, here we reran the simulations with less noise. Results of simulations using neural response functions with (a) a symmetric cardinal anisotropy, (b) an asymmetric cardinal anisotropy, or (c) a horizontal anisotropy. The columns to the right are the parameter estimate results. Dark grey lines in indicate moving averages of data points (semi-transparent dots). Blue insets show the corresponding moving averages from the empirical data; horizontally distributed black dots indicate tuning preferences.