2   movedesign: Shiny R app to evaluate sampling

3   design for animal tracking movement studies

Inês Silva[1*], Christen H. Fleming[2,3], Michael J. Noonan[4], William F. Fagan[2], Justin M.

Calabrese[1,2,5]

[1] *Center for Advanced Systems Understanding (CASUS), Helmholtz-Zentrum Dresden-*
Rossendorf (HZDR), Görlitz, Germany

[2] *Department of Biology, University of Maryland, College Park, Maryland, USA*

[3] *Smithsonian National Zoo and Conservation Biology Institute, Virginia, USA*

[4] *Department of Biology, University of British Columbia Okanagan, British Columbia, Canada*

[5] *Helmholtz Centre for Environmental Research—UFZ, Leipzig, Germany*

* Corresponding author: i.simoes-silva@hzdr.de, imss.silva@gmail.com

13   Abstract

1.   Projects focused on movement behavior and home range are commonplace, but beyond

a focus on choosing appropriate research questions, there are no clear guidelines for

such studies. The estimation of space-use and movement properties is often necessary

to answer basic movement ecology questions, but designing an animal tracking study to

produce reliable estimates is often done in an *ad hoc* manner.

2.   We developed 'movedesign', a user-friendly Shiny application, which can be utilized to

investigate the precision of three estimates regularly reported in movement and spatial

ecology studies: home range area, speed, and distance traveled. Conceptually similar

to statistical power analysis, this application enables users to assess the degree of

estimate precision that may be achieved with a given sampling design.

3.   Leveraging the 'ctmm' R package, we utilize two methods proven to handle many

common biases in animal movement datasets: autocorrelated Kernel Density Estimators

(AKDE) and continuous-time speed and distance (CTSD) estimators. Longer sampling

durations are required to reliably estimate home range areas via the detection of a

sufficient number of home range crossings. In contrast, speed and distance estimation

requires a sampling interval short enough to ensure that a statistically significant

signature of the animal's velocity remains in the data.

4. This application addresses key challenges faced by researchers when designing

tracking studies, including the trade-off between long battery life and high resolution of

GPS devices, which may result in a compromise between reliably estimating home

range or speed and distance. 'movedesign' has broad applications for researchers and

decision-makers, supporting them to focus efforts and resources in achieving the optimal

sampling design strategy for their research questions, prioritizing the correct deployment

decisions for insightful and reliable outputs, while understanding the trade-off associated

with these choices.

Keywords: experimental design, biologgers, GPS sampling, GPS tracking, trajectory,

home range, space use

42 1. Background

Modern tracking technologies are advancing the fields of biology and ecology, with data-

rich studies revealing how movement shapes ecological processes, biological

interactions, and behavioral responses to natural or human-induced environmental

changes (Kays et al., 2015; Nathan et al., 2022). Biologging and telemetry devices, such

as global positioning system (GPS) and very-high frequency (VHF) transmitters, are

common sampling methods in this field, and have been used to answer a multitude of

research questions —the majority of which rely on estimates of large-scale processes,

such as home ranges (Fleming & Calabrese, 2017; Horne et al., 2019), or fine-scale

processes, such as speed or distance traveled (Gurarie et al., 2016; Noonan, Fleming,

et al., 2019).

The technology is improving, with cheaper, less invasive tags available (Foley & Sillero-

Zubiri, 2020; Gottwald et al., 2019), allowing researchers access to high-volume high-

resolution movement data for an increasingly number of species (Kays et al., 2015): the

animal tracking data platform Movebank (www.Movebank.org) already hosts 2.4 billion

locations for over 1,000 species. And although these data are critical for conservation,

tracking devices can still be costly and/or logistically difficult to deploy (Hays et al., 2016).

Researchers often track as many animals as possible, for as long as possible, recording

new locations at regular intervals and at short sampling intervals —particularly if the goal

is to identify finer movement behaviors (Nathan et al., 2022). However, although GPS

loggers can record animal locations at higher rates than VHF transmitters, achieving both

long battery life and high resolution is challenging. Excluding other factors that may

further reduce the longevity of tracking devices in the wild (*e.g.*, additional sensors, signal

acquisition time, algorithm efficiency, data recovery method), GPS battery life shortens

with shorter sampling intervals (Forrest et al., 2022; Moriarty & Epps, 2015). Successfully

designing an animal tracking study therefore requires a compromise between *sampling*

duration (how long an animal should be tracked for) and *sampling interval* (time between

which new locations are recorded; reciprocal of sampling frequency). Moreover, target

analyses and sampling design are tightly linked, so we must keep specific goals in mind:

there are circumstances where we may be able to address either large-scale or fine-

scale questions, but not both concurrently.

Our objective is to provide a more rigorous *a priori* approach, analogous to statistical

power analysis (Steidl et al., 1997), for determining the ideal sampling duration and

sampling interval of an animal tracking project. We consider three common estimates—

home range area, speed, and distance traveled—through the lens of continuous-time

movement models and the 'ctmm' R package (Calabrese et al., 2016). The 'ctmm' methods are insensitive to the sampling schedule and deal with many of the biases present in modern movement datasets, providing robust comparisons across individuals, species, and ecosystems (Fleming et al., 2015, 2018, 2019; Fleming & Calabrese, 2017; Silva et al., 2022). We chose to implement this in the Shiny R application, 'movedesign' (version 0.1.0) to facilitate adoption and accessibility to the broadest possible audience, and hope that we can contribute to the increase of comparable and reliable movement ecology studies. This application was built using the 'golem' framework (Fay et al., 2021), and is available as an installable R package at https://github.com/CASUS/movedesign.

2. Conceptualization

2.1. Parameters

Explicitly modelling all the complex interactions between internal states, biophysical constraints, environmental cues and social dynamics that determine animal movement is generally considered impossible (Codling et al., 2008). However, by interpreting movement as a continuous-time stochastic process (Calabrese et al., 2016; Fleming et al., 2014a; Gurarie & Ovaskainen, 2011), we can efficiently summarize behavior using characteristic timescales, including the position autocorrelation (τ_p) and velocity autocorrelation (τ_v) timescale parameters, and describe long-term dispersal behavior and short-term movement behavior across levels of data resolution and duration. These timescales impose constraints on the sampling design that must be met in order to evaluate both small-scale (speed and distance) and large-scale phenomena (home range).

The position autocorrelation parameter (τ_p) can be interpreted as the home range crossing time, or the time is takes on average for an animal to cross the linear extent of its range (Silva et al., 2022). As τ_p increases, we can expect an animal to take longer to

travel this linear extent. Range-resident animals tend to travel away from their point of

origin at a rate controlled by the variance parameter (σ_p) while simultaneously reverting

back to it at a rate driven by τ_p (Péron et al., 2017). As $\tau_p \to \infty$, movement becomes

endlessly diffusive ($\sigma_p \to \infty$), with no range residency behavior; for range-resident

species, σ is asymptotically constant and proportional to home range area (Calabrese et

al., 2016; Fleming et al., 2014a).

The velocity autocorrelation parameter (τ_v) describes how velocity persists through time

(directional persistence; Fleming *et al.* 2014). Animals with strong directional persistence

(linear movement bursts) will tend to have a large τ_v parameter, while animals with more

tortuous movement (less linear) tend towards a much smaller τ_v. Both speed and

distance traveled are properties of an animal's movement velocity over time, which is

proportional to σ_p/τ (Noonan, Fleming, et al., 2019), *e.g.*, mean square speed is given

by $\sigma_v = \sigma_p/(\tau_v \times \tau_v)$. For any value of σ_v, as $\tau_v \to \infty$, the movement process

approximates ballistic motion.

2.2. Sampling design

Study design optimization requires clearly defined research questions and objectives

(Fieberg & Börger, 2012), and an understanding of existing constraints, both those

related to the study species (τ_p, τ_v, σ_p, and σ_v) and the sampling parameters (duration,

and interval).

Our choice of sampling parameters largely determines our ability to detect the

characteristic timescales of the movement process: it is the sampling duration and

interval relative to characteristic timescales that determine whether there will be any

signature of the animal's range crossing time (τ_p), or its directional persistence (τ_v).

Typically, sampling duration (T) should be at least as long as τ_p (and ideally many times

longer) for home range estimation (Fleming et al., 2019; Fleming & Calabrese, 2017;

Silva et al., 2022). For estimating speed and distance, the sampling interval (Δt) needs

to be at most as short as the velocity autocorrelation timescale for distance and speed

estimation (Noonan, Fleming, et al., 2019). If $\Delta t > 3\tau_v$ then no statistically significant

signature of the animal's velocity will remain (Noonan, Fleming, et al., 2019).

We can evaluate how much information is present in an animal tracking dataset by

considering the *effective sample size* (N). The concept of effective sample size, while

well-discussed in statistical literature, is frequently ignored in movement ecology studies.

Effective sample sizes are the number of independent locations that provide the same

information as the non-independent data under consideration (Fieberg & Börger, 2012;

Fleming et al., 2019; Silva et al., 2022). Considering that collected locations are rarely

independent in modern tracking datasets (as most tracking devices collect new locations

at shorter sampling intervals than in the past; Calabrese *et al.* 2016; Patterson *et al.*

2017), a satisfactory effective sample size is a fundamental component of a reliable

movement metric or space-use estimate.

The choice between tracking devices further complicates sampling design. With

GPS/satellite loggers, sampling is automated and conducted by satellite systems, with

GPS battery life inherently linked to both sampling duration and frequency. With Very-

High-Frequency (VHF) transmitters, the interval between new locations is subject only

to the data collection employed manually in the field. As such, battery life is decoupled

from any specific sampling interval, and depends only on the sampling duration specified

by the manufacturer.

In contrast with conventional radio-telemetry, GPS loggers have a higher potential to

resolve fine-scale movements; however, the trade-off between battery life and resolution

is more conspicuous, and with a greater impact on potential outputs. To facilitate

sampling design within 'movedesign', we visualize this trade-off (sampling duration *versus*

sampling interval) by simulating GPS battery life as a three-parameter log-logistic

function (Appendix S1), based on the battery life-resolution trade-off of several GPS

models of animal tracking devices.

2.3. Analytic scope

Our evaluation of sampling design focuses on the precision of three estimates at two

different scales —large-scale (*home range area*) and fine-scale (*speed* and *distance*

traveled). As analytical choices can further obscure estimate interpretation and

comparison (Fieberg & Börger, 2012; Fleming et al., 2015), we leverage the 'ctmm'

package to develop a reliable inferential framework for sampling design evaluation,

generating comparable estimates with confidence intervals (Calabrese et al., 2016;

Fleming et al., 2018, 2019; Fleming & Calabrese, 2017).

Home range area is one of the core outputs of movement or spatial ecology studies and

provides information on the long term space-use requirements, which are invaluable for

conservation policies and protected area delimitation (Bartoń et al., 2019; Lambertucci

et al., 2014). Here, we follow the definition of home range as the area repeatedly used

throughout an animal's lifetime for all its normal behaviors and activities, excluding the

occasional exploratory excursions (Burt, 1943; Calabrese et al., 2016; Silva et al., 2022),

and estimate it using the Autocorrelated Kernel Density Estimator (AKDE; Calabrese *et*

al. 2016), which accounts for the autocorrelation present in tracking data.

Both speed and distance traveled provide quantifiable links between behavior and

energetics, as demographic outcomes and population dynamics are affected by how far

and how fast animals must travel to meet their nutritional and reproductive needs

(Morales et al., 2010; Noonan, Fleming, et al., 2019)*. Distance* traveled is usually

equated with the sum of the straight-line displacement (SLD) between all subsequent

locations, while *speed* is the sum of SLD divided by time. Here, we use the continuous-

time speed and distance (CTSD) estimator instead, as it overcomes important limitations

of SLD estimation (Noonan, Fleming, et al., 2019).

There are two objective metrics that quantify the performance of these estimators: the

effective sample size for home range estimation (N_{area}), or how many independent

location fixes would be required to calculate the same quality home range estimate, and

the effective sample size for speed estimation (N_{speed}), or how many independent

velocity fixes would be required to calculate the same quality mean speed estimate.

In addition, the precision of estimates calculated from any sampling design is judged by

the relative error of both point estimates and their confidence intervals compared to the

exact expectation values from simulations. For home range areas, we derive the exact

expectation value of the true 95% area based on the model from which data are

simulated (see Fleming et al., 2014b; Noonan, Tucker, et al., 2019; Silva et al., 2022).

For speed and distance traveled, the expected values are extracted from a fine-scale

error-free trajectory simulated for 10 days at a sampling interval of $\tau_v/10$ (Noonan,

Fleming, et al., 2019), functioning as a Riemann sum approximation of the path length

that achieves a relative error of $\mathcal{O}(10^{-3})$ while reducing computation time.

193 3. Workflow

The main goal of '`movedesign`' is to determine if a particular sampling design is sufficient

to answer an *a priori* defined research question, following the workflow presented in

Figure 1. First, we extract relevant measures —characteristic timescales (τ)*,* variance

(σ_p), and velocity (σ_v)— from animal tracking datasets through automated model fitting

and selection (Fleming et al., 2019). Second, we input sampling design parameters —

duration (T) and interval (Δt) — to generate simulated datasets conditional on the

previously fitted models. Third, we run estimators for home range and/or speed/distance

traveled on the simulated data, while calculating the expected values in the background,

from the model and parameters used in the simulation. Finally, we compare the

estimates with the expected values ("truth") and with simulation results from previous

studies (Noonan, Fleming, et al., 2019; Silva et al., 2022), providing an overview of the reliability of that sampling design for estimating home range areas or speed and distance traveled.

Figure 1. Conceptual workflow of the key elements of the 'movedesign' application, providing a R/Shiny-powered user interface to test different sampling designs for specified tracking projects. The application is divided into four main sections: "Data" (where data are uploaded, selected or simulated to extract relevant parameters and measures), "Device" (where users select sampling duration and sampling interval, visualize potential trade-offs, and evaluate effective sample sizes), "Analyses" (where users can estimate home range areas, using Autocorrelated Kernel Density Estimator, AKDE, and speed and distance traveled, using continuous-time speed and distance, CTSD, from the 'ctmm' R package), and "Report" (a summary page of all inputs, outputs, and final recommendations).

The application consists of four main sections, organized as eight easy-to-navigate tabs (Figure 1). Once the user has set their data source and research question(s), the sidebar will automatically subset to only the required steps. We advise users to follow along the guided tutorial available in the "Home" tab, until they feel confident with the application's workflow. Each run-through of the entire workflow may take a few minutes up to several hours to run; computation bottlenecks arise from the `ctmm::ctmm.select()` and `ctmm::speed()` functions, particularly if the absolute sample size exceeds 10^3 locations, or with very short sampling intervals.

3.1. Importing movement data

There are three data source options available in 'movedesign': (1) Import data, (2) Select data, and (3) Simulate data. For the first option, and prior to using 'movedesign', users should find an animal tracking dataset for their intended study species (*e.g.*, from Movebank, published studies, requesting directly from data owners), preferably in a similar environment to the focal study site (*e.g.*, natural *versus* human-dominated environment); if this is not available, search for species with a similar physiological and behavioral phenotype (*e.g.*, the same genus or family, occupying the same ecological niche, similar body size). As the outputs from 'movedesign' depend heavily on the extracted species parameters from pre-existing datasets, this step is crucial to ensure the interpretability and reliance of all subsequent steps. Correctly importing data into the 'movedesign' application requires that datasets conform to Movebank naming conventions (http://www.Movebank.org/). We recommend that users first upload their datasets (privately if needed) to Movebank, as this will facilitate data preparation. For the second option, the user can select one of the seven example species available within the 'ctmm' package and extract their parameters, which serve as worked examples, but may also help inform animal tracking studies of species with similar movement behaviors to those listed. For the third option, the user can simulate an animal tracking dataset from

scratch by inputting model parameters (τ_p, τ_v) and associated measures (σ_p, σ_v) directly;

if chosen, this option requires previous knowledge of the study species' movement

behavior, and an educated guess regarding their species parameters. For range-resident

species, τ_p is generally on the order of days to weeks, while τ_v is generally on the order

of minutes to hours (Noonan, Tucker, et al., 2019); however, these parameters are likely

to differ between species, populations, or individuals.

For options one and two ("Import data" and "Select data"), the application checks if

datasets are valid: specifically, if there is still a signature of the animal's position or

velocity autocorrelation parameter. For example, if the user is interested in speed

estimation but provides only a coarsely-sampled tracking dataset ($\Delta t \gg \tau_v$) then the

property of continuous velocities is not supported by the data and the resulting movement

model is fractal (*i.e.*, we cannot proceed with speed estimation). Data visualization boxes

are also available to assist in additional validation steps that cannot be done

automatically, such as variograms to confirm range residency if the goal is home range

estimation (Fleming et al., 2014a), or plots to identify outliers (which should be removed

and the data re-uploaded before proceeding).

For option three ("Simulate data"), the application will simulate autocorrelated tracking

data using an isotropic Ornstein-Uhlenbeck with foraging (OUF) Gaussian process,

which incorporates both correlated velocities and constrained space use. This OUF

model is also the most frequently selected across modern GPS tracking datasets

(Noonan, Tucker, et al., 2019).

3.2. Choosing sampling design

This section allows for the simulation of a new dataset, conditioned upon previously

extracted parameters, and based on the sampling design of the user's choice. First,

users are prompted to input their desired device type (GPS/Satellite loggers or VHF

transmitter) as appropriate sampling design is dependent on the device's battery life: for

GPS/Satellite loggers, battery life depends on both duration and frequency, while for

VHF transmitters, battery life depends only on duration. For the GPS option, if users do

not intend to visualize the trade-off curve and already have a specific sampling design in

mind, they can uncheck the 'Select from plot' to 'Set regime manually' located in the

footer of the Device settings box (this is tantamount to setting VHF transmitter as the

device of choice).

The application will once again validate all current inputs, and inform the user of the

expected run time of the simulation step. For home range estimation, we recommend

that the user check the range residency assumption through the variogram in the data

visualization boxes. The user can also check the effective sample sizes extracted from

the new model fit, which will assist in decision making (to continue with the current

sampling design, or to make further adjustments before proceeding).

3.3. Running estimators and building the report

In this section, there will be one or two tabs available to the user, based on the chosen

outputs: (1) Home range, and/or (2) Speed & distance. Each tab will run an estimator on

the simulated dataset, created during the previous section. For each output, there will be

two sets of values in the main output box: "Estimate", which is the point estimate followed

by the 95% confidence intervals (CIs), and "Expected error", which is the relative error

(in %) of the point estimate (and of the 95% CIs) in relation to the expected values. The

user can utilize these outputs (as well as effective sample sizes) to plan an appropriate

sampling duration and interval so the confidence intervals are sufficiently narrow and

relative errors acceptably low: typically, a more reliable home range estimate requires a

longer sampling duration than the one specified, while a more reliable speed and

distance estimation requires shorter sampling intervals. However, we advise caution in

two scenarios for speed and distance estimation: (1) producing a CTSD estimate at $\Delta t >$

$3\tau_v$ does not guarantee a meaningful output, and (2) $\Delta t \ll \tau_v$ may only yield a marginal

benefit over $\Delta t < \tau_v$ while markedly increasing computation time (see Noonan, Fleming,

et al., 2019 for more details). Users can then navigate to the last section, the "Report"

tab, to see a summary of all previous inputs and outputs, and the final recommendations

regarding home range and/or speed and distance estimation.

4. Case study

Figure 2. Initial steps in the `movedesign` Shiny application workflow ("Home" and "Species" tabs). For the current case study, we recommend setting a fixed seed to reproduce all outputs, the correct data source and both research questions, and then the appropriate species and individual from the list (before validation and extraction).

To present the application's key features, we used the African Buffalo (*Syncerus caffer*)

data available within the `ctmm` R package as a case study. These individuals were

tracked in Kruger National Park, South Africa (Cross et al., 2009). Our objectives were

to reliably estimate home range area and speed/distance traveled (Figure 2) using GPS

loggers for a hypothetical tracking project with the same species in a similar study site.

From our research into different tracking devices, we choose a GPS model with a

maximum lifespan of two years if four new locations were collected every day ($\Delta t = 1$ fix

every 6 hours).

Figure 3. Example outputs shown in the "Device" tab, including the simulated trade-off between sampling
duration and sampling interval (shown in logarithmic scale) for the specified device settings, with the chosen
interval selected from the plot (1 fix every hour), and the absolute and effective sample sizes extracted from
the new model fit.

We selected the individual "Cilla" for parameter extraction; once validated, we extracted

parameters from the fitted OUF anisotropic model for a τ_p of approximately 7.5 days (CI:

4.4 – 12.7), and a τ_v of 42 minutes (39.6 – 44.7). We plotted our sampling design options

based on the chosen tracking device parameters (Figure 3), which revealed that a rough

estimate of N_{area} for any sampling interval was substantially smaller the N_{speed} (as

expected, since $\tau_p \gg \tau_v$). As our focus was both home range and speed/distance

estimation, we wanted to maximize N_{area} and N_{speed}, so we selected a sampling interval

of one hour (which sets our sampling duration to 5.9 months, due to the battery/resolution

trade-off discussed earlier). Once we successfully validated and ran our new simulation,

our sample sizes were $n = 4{,}232$, $N_{area} = 19.5$ and $N_{speed} = 4{,}130$.

Figure 4. Example outputs shown in the "Analyses" tabs, including the point estimates (and corresponding
confidence intervals) and/or expected errors associated with both home range and speed/distance. We can
also visualize the home range estimate (with the true 95% area for comparison), and the instantaneous
speed estimates at different time scales.

With an appropriate movement model available, the next step was to estimate home

range area, mean speed and total distance traveled (Figure 4). Once the final report was

built, the AKDE estimates showed high uncertainty, while the CTSD estimates did not.

Based on these results and the effective sample sizes, we determined that our sampling

design was adequate for speed/distance estimation, but could be insufficient for home

range estimation (Figure 5). After exploring further sampling designs for our choice of

GPS model, we decided upon one fix every 2 hours for a sampling duration of 11 months,

reducing the uncertainty associated with home range area —although at the cost of

increased uncertainty in speed/distance estimation (follow along the guided tutorial in the

"Home" tab for this particular workflow).

342
343   Figure 5. Final report for a workflow that requested both home range and speed/distance as the research
344   questions, for a hypothetical tracking study of the African buffalo (*Syncerus caffer*) species with a sampling
345   duration of 5.9 months and a sampling interval of one hour, based on a GPS model with a maximum battery
346   life of 2 years if the sampling interval was set to 6 hours.

Final considerations

Data collection and sampling design optimization allows researchers to better address key ecological questions, as conclusions drawn from lower-resolution data may not be appropriate to detect fine-scale movement properties, while higher-resolution datasets may still be unsuitable to detect patterns at larger spatial or temporal scales (*e.g*., space-use), if the sampling duration is too short (Nathan et al., 2022). Our workflow allows users to evaluate a wide range of potential sampling designs, which can then serve as a solid foundation for future tracking projects, or even the evaluation of on-going and published studies. We are continuously working to improve the application's code, and have plans to explore new use cases and address more challenging sampling design questions.

Data Availability statement

The empirical dataset used in the manuscript is openly accessible: the African buffalo tracking data are archived in the MoveBank Data Repository (Cross et al., 2016) and partially included in the `ctmm` package (Fleming & Calabrese, 2022). Source code of the 'movedesign' application is available on GitHub (https://github.com/CASUS/movedesign), and release version 0.1.0 has been archived on Zenodo (Silva, 2023).

Acknowledgements

This work was partially funded by the Center of Advanced Systems Understanding (CASUS), which is financed by Germany's Federal Ministry of Education and Research (BMBF) and by the Saxon Ministry for Science, Culture and Tourism (SMWK) with tax funds on the basis of the budget approved by the Saxon State Parliament. C.H.F. and J.M.C. were supported by NSF IIBR 1915347.

Conflict of interests

The authors declare no conflicts of interest.

Authors' contributions

I.S., C.H.F., M.J.N., and J.M.C. conceived the ideas; I.S. designed and developed the application; J.M.C. and I.S. led the drafting the manuscript; I.S., C.H.F., M.J.N., W.F.F., and J.M.C. edited the draft. All authors reviewed the application, contributed critically to the manuscript and gave final approval for publication.

References

Bartoń, K. A., Zwijacz-Kozica, T., Zięba, F., Sergiel, A., & Selva, N. (2019). Bears without borders: Long-distance movement in human-dominated landscapes. *Global Ecology and Conservation*, *17*, e00541.

Burt, W. H. (1943). Territoriality and home range concepts as applied to mammals. *Journal of Mammalogy*, *24*(3), 346–352.

Calabrese, J. M., Fleming, C. H., & Gurarie, E. (2016). ctmm: An r package for analyzing animal relocation data as a continuous-time stochastic process. *Methods in Ecology and Evolution*, *7*(9), 1124–1132.

Codling, E. A., Plank, M. J., & Benhamou, S. (2008). Random walk models in biology. *Journal of The Royal Society Interface*. https://doi.org/10.1098/rsif.2008.0014

Cross, P. C., Bowers, J. A., Hay, C. T., Wolhuter, J., Buss, P., Hofmeyr, M., Toit, J. T., & Getz, W. M. (2016). *Data from: Nonparameteric kernel methods for constructing home ranges and utilization distributions.* Movebank data repository. https://doi.org/10.5441/001/1.j900f88t/1

Cross, P. C., Heisey, D. M., Bowers, J. A., Hay, C. T., Wolhuter, J., Buss, P., Hofmeyr, M., Michel, A. L., Bengis, R. G., & Bird, T. L. F. (2009). Disease, predation and demography: Assessing the impacts of bovine tuberculosis on African buffalo by monitoring at individual and population levels. *Journal of Applied Ecology*, *46*(2), 467–475.

Fay, C., Guyader, V., Rochette, S., & Girard, C. (2021). Golem: A framework for robust shiny applications. *R Package Version 0.3*, *1*.

Fieberg, J., & Börger, L. (2012). Could you please phrase "home range" as a question? *Journal of Mammalogy*, *93*(4), 890–902.

Fleming, C. H., & Calabrese, J. M. (2017). A new kernel density estimator for accurate home-range and species-range area estimation. *Methods in Ecology and Evolution*, *8*(5), 571–579.

Fleming, C. H., & Calabrese, J. M. (2022). *Ctmm: Continuous-Time Movement Modeling. R package version 1.1.0.* (R package version 1.1.0). https://CRAN.R-project.org/package=ctmm

Fleming, C. H., Calabrese, J. M., Mueller, T., Olson, K. A., Leimgruber, P., & Fagan, W. F. (2014a). From fine-scale foraging to home ranges: A semivariance approach to identifying movement modes across spatiotemporal scales. *The American Naturalist*, *183*(5), E154–E167.

Fleming, C. H., Calabrese, J. M., Mueller, T., Olson, K. A., Leimgruber, P., & Fagan, W. F. (2014b). Non-
Markovian maximum likelihood estimation of autocorrelated movement processes. *Methods in*
Ecology and Evolution, *5*(5), 462–472. https://doi.org/10.1111/2041-210X.12176

Fleming, C. H., Fagan, W. F., Mueller, T., Olson, K. A., Leimgruber, P., & Calabrese, J. M. (2015). Rigorous
home range estimation with movement data: A new autocorrelated kernel density estimator.
Ecology, *96*(5), 1182–1188.

Fleming, C. H., Noonan, M. J., Medici, E. P., & Calabrese, J. M. (2019). Overcoming the challenge of small
effective sample sizes in home-range estimation. *Methods in Ecology and Evolution*, *10*(10), 1679–
1689.

Fleming, C. H., Sheldon, D., Fagan, W. F., Leimgruber, P., Mueller, T., Nandintsetseg, D., Noonan, M. J.,
Olson, K. A., Setyawan, E., & Sianipar, A. (2018). Correcting for missing and irregular data in home-
range estimation. *Ecological Applications*, *28*(4), 1003–1010.

Foley, C. J., & Sillero-Zubiri, C. (2020). Open-source, low-cost modular GPS collars for monitoring and
tracking wildlife. *Methods in Ecology and Evolution*, *11*(4), 553–558.

Forrest, S. W., Recio, M. R., & Seddon, P. J. (2022). Moving wildlife tracking forward under forested
conditions with the SWIFT GPS algorithm. *Animal Biotelemetry*, *10*(1), 19.
https://doi.org/10.1186/s40317-022-00289-9

Gottwald, J., Zeidler, R., Friess, N., Ludwig, M., Reudenbach, C., & Nauss, T. (2019). Introduction of an
automatic and open-source radio-tracking system for small animals. *Methods in Ecology and*
Evolution, *10*(12), 2163–2172. https://doi.org/10.1111/2041-210X.13294

Gurarie, E., Bracis, C., Delgado, M., Meckley, T. D., Kojola, I., & Wagner, C. M. (2016). What is the animal
doing? Tools for exploring behavioural structure in animal movements. *Journal of Animal Ecology*,
85(1), 69–84.

Gurarie, E., & Ovaskainen, O. (2011). Characteristic spatial and temporal scales unify models of animal
movement. *The American Naturalist*, *178*(1), 113–123.

Hays, G. C., Ferreira, L. C., Sequeira, A. M. M., Meekan, M. G., Duarte, C. M., Bailey, H., Bailleul, F., Bowen,
W. D., Caley, M. J., Costa, D. P., Eguíluz, V. M., Fossette, S., Friedlaender, A. S., Gales, N., Gleiss,
A. C., Gunn, J., Harcourt, R., Hazen, E. L., Heithaus, M. R., … Thums, M. (2016). Key Questions
in Marine Megafauna Movement Ecology. *Trends in Ecology & Evolution*, *31*(6), 463–475.
https://doi.org/10.1016/j.tree.2016.02.015

Horne, J., Fieberg, J., Börger, L., Rachlow, J. L., Calabrese, J. M., & Fleming, C. H. (2019). Animal Home
Ranges. *Population Ecology in Practice*.

Kays, R., Crofoot, M. C., Jetz, W., & Wikelski, M. (2015). Terrestrial animal tracking as an eye on life and
planet. *Science*, *348*(6240).

Lambertucci, S. A., Alarcón, P. A., Hiraldo, F., Sanchez-Zapata, J. A., Blanco, G., & Donázar, J. A. (2014).
Apex scavenger movements call for transboundary conservation policies. *Biological Conservation*,
170, 145–150.

Morales, J. M., Moorcroft, P. R., Matthiopoulos, J., Frair, J. L., Kie, J. G., Powell, R. A., Merrill, E. H., &
Haydon, D. T. (2010). Building the bridge between animal movement and population dynamics.
Philosophical Transactions of the Royal Society B: Biological Sciences, *365*(1550), 2289–2301.

Moriarty, K. M., & Epps, C. W. (2015). Retained satellite information influences performance of GPS devices
in a forested ecosystem. *Wildlife Society Bulletin*, *39*(2), 349–357. https://doi.org/10.1002/wsb.524

Nathan, R., Monk, C. T., Arlinghaus, R., Adam, T., Alós, J., Assaf, M., Baktoft, H., Beardsworth, C. E.,
Bertram, M. G., & Bijleveld, A. I. (2022). Big-data approaches lead to an increased understanding
of the ecology of animal movement. *Science*, *375*(6582), eabg1780.

Noonan, M. J., Fleming, C. H., Akre, T. S., Drescher-Lehman, J., Gurarie, E., Harrison, A.-L., Kays, R., &
Calabrese, J. M. (2019). Scale-insensitive estimation of speed and distance traveled from animal
tracking data. *Movement Ecology*, *7*(1), 1–15.

Noonan, M. J., Tucker, M. A., Fleming, C. H., Akre, T. S., Alberts, S. C., Ali, A. H., Altmann, J., Antunes, P.
C., Belant, J. L., & Beyer, D. (2019). A comprehensive analysis of autocorrelation and bias in home
range estimation. *Ecological Monographs*, *89*(2), e01344.

Patterson, T. A., Parton, A., Langrock, R., Blackwell, P. G., Thomas, L., & King, R. (2017). Statistical
modelling of individual animal movement: An overview of key methods and a discussion of practical
challenges. *AStA Advances in Statistical Analysis*, *101*(4), 399–438.

Péron, G., Fleming, C. H., de Paula, R. C., Mitchell, N., Strohbach, M., Leimgruber, P., & Calabrese, J. M.
(2017). Periodic continuous-time movement models uncover behavioral changes of wild canids
along anthropization gradients. *Ecological Monographs*, *87*(3), 442–456.

Silva, I. (2023). *ecoisilva/movedesign: Movedesign v0.1.0*. Zenodo. https://doi.org/10.5281/zenodo.7576244

Silva, I., Fleming, C. H., Noonan, M. J., Alston, J., Folta, C., Fagan, W. F., & Calabrese, J. M. (2022).

Autocorrelation-informed home range estimation: A review and practical guide. *Methods in Ecology*

and Evolution, *13*(3), 534–544.

Steidl, R. J., Hayes, J. P., & Schauber, E. (1997). Statistical power analysis in wildlife research. *The Journal*

of Wildlife Management, 270–279.