Encoding of continuous perceptual choices
in human early visual cortex

Riccardo Barbieri[1*], Felix M. Töpfer[1*], Joram Soch[1,2], Carsten Bogler[1],
Henning Sprekeler[4], John-Dylan Haynes[1,3]

[1] Bernstein Center for Computational Neuroscience & Berlin Center for Advanced Neuroimaging & Department of Neurology, Charité – Universitätsmedizin Berlin, corporate member of Freie Universität Berlin, Humboldt-Universität zu Berlin and Berlin Institute of Health (BIH), Berlin, Germany.

[2] German Center for Neurodegenerative Diseases, Göttingen, Germany.

[3] Berlin School of Mind and Brain & Institute of Psychology, Humboldt-Universität zu Berlin, Berlin, Germany.

[4] Department for Electrical Engineering and Computer Science, Technische Universität Berlin, Berlin, Germany.

Keywords: Continuous decision making, encoding model, Gaussian process regression, early visual cortex

[*] These authors contributed equally

Correspondence:
Please address correspondence to Riccardo Barbieri (riccardo.barbieri@bccn-berlin.de) and Felix M. Töpfer (felix.toepfer@bccn-berlin.de).

Conflict of interest:
The authors declare no competing financial interests

ABSTRACT

Research on the neural mechanisms of perceptual decision-making has typically focused on

simple categorical choices, say between two alternative motion directions. Studies on such

discrete alternatives have often suggested that choices are encoded either in a motor-based or

in an abstract, categorical format in regions beyond sensory cortex. However, many sensory

features are graded rather than discrete, raising the question how choices are encoded when

they span the full sensory continuum. Here we assessed this using motion stimuli that could

vary anywhere between $0°$ and $360°$. We employed a combination of neuroimaging and

encoding models based on Gaussian Process Regression to assess how either stimuli or choices

were encoded in brain responses. We found that single-voxel tuning patterns could be used to

reconstruct the trial-by-trial physical direction of motion as well as the participants' continuous

choices. Importantly, these continuous choice signals were primarily observed in early visual

areas. The tuning properties in this region generalized between choice encoding and stimulus

encoding, even for reports that reflected pure guessing. We found only little information related

to the decision outcome in regions beyond visual cortex, such as parietal cortex, possibly

because our task did not involve differential motor preparation. This could suggest that

decisions for continuous stimuli take can place already in sensory brain regions, potentially

using similar mechanisms to the sensory recruitment in visual working memory.

INTRODUCTION

The brain mechanisms of perceptual decisions involve several sequential steps (Gold &

Shadlen, 2007): First, information about an external stimulus is encoded in sensory brain

regions (e.g. whether an object is moving leftward, or rightward). Then, the sensory evidence

supporting the different potential states of the world is gathered in a decision variable, which

typically also integrates information over time (Gold & Shadlen, 2007; but see Uchida et al.,

2006). Finally, once enough evidence is collected in favor of a certain hypothesis, a decision

is made and the observer takes an action to indicate their choice.

Several stages of this processes have been characterized in detail, both in humans and in

monkeys (Gold & Shadlen, 2007; Heekeren et al., 2008; Mulder et al., 2014; Forstmann et al.,

2016; Hanks & Summerfield, 2017). In monkeys, sensory neurons encode stimulus-related

information, such as the physical direction of movement of dots in the visual field (Shadlen et

al., 1996). Regions of parietal and frontal cortex encode the gradual accumulation of choice-

related, categorical evidence in monkeys (Gold & Shadlen, 2007) and in humans (Siegel et al.,

2011; Mulder et al., 2014; Wilming et al., 2020). Neuroimaging signals also reflect levels of

evidence (Heekeren et al., 2004; Forstmann et al., 2016) and strategic adjustments in decisions

(Mulder et al., 2014). As for the outcome of the decision, many human neuroimaging studies

have identified choice-related brain signals in several areas including parietal cortex (Tosoni

et al., 2008, 2014; Liu & Pleskac, 2011; Hebart et al., 2012, 2016; Levine & Schwarzbach,

2017), insular cortex (Liu & Pleskac, 2011; Ho et al., 2009) and prefrontal cortex (Heekeren et

al., 2004, 2006; Filimon et al., 2013; Hebart et al., 2016). Interestingly, studies have shown that

activity already in sensory areas is influenced by the behavioral choice, especially in

ambiguous stimulus conditions (Ress & Heeger, 2003; Serences & Boynton, 2007; Sousa et

al., 2021).

Due to this variety of decision signals, the representational space in which decision outcomes

are encoded has remained somewhat unclear, with some suggesting a motor-based

"intentional" frame of reference (Shadlen et al., 2008; Tosoni et al., 2014) whereas others have

shown that decision signals can be dissociated from motor plans in both monkeys and humans

(Bennur & Gold, 2011; Hebart et al., 2012; Filimon et al., 2013; Park et al., 2014; Brincat et

al., 2018, but see discussion below).

Importantly, there is an issue that has only received little attention: Studies of perceptual

decision making have typically employed few discrete alternative stimulus features, whereas

perception of most sensory features is inherently continuous (Levinson & Sekuler, 1976;

Nichols & Newsome, 2002; Prinzmetal et al., 1998; van Bergen et al., 2015). For example,

most studies that use perceptual judgements of coherent motion focus on few alternative motion

directions in each trial and require categorical responses (Gold & Shadlen, 2007; Huk &

Meister, 2012; Hanks & Summerfield, 2017). In these tasks a small set of possible motion

directions (e.g. motion left or motion right) has to be mapped onto a small set of predetermined

motor responses (e.g. pressing the left or the right button or making a saccade to a left or right

target). In such cases, participants might encode their choices in a motor frame of reference or

in a lower-dimensional categorical form ("left" vs "right"). In contrast, choices could also be

encoded in some kind of continuous perceptual space (Beck et al. 2008; van Bergen et al.,

2015; Smith, 2016; Ratcliff, 2018). Note that even if a paradigm allows to dissociate choices

from motor plans by the use of trial-wise varying stimulus-response mappings (Bennur & Gold,

2011; Hebart et al. 2012), the encoding of choices still occurs in the form of such stimulus-

response-mappings and thus uses discrete, lower-dimensional representations. Alternatively,

however, choices could be encoded on a full 360° continuum.

RESULTS

Here we assessed the encoding of continuous perceptual choices using a combination of fMRI

and voxel-wise fMRI encoding models (Nevado et al., 2004; Thirion et al., 2006; Kay et al.,

2008; Dumoulin et al., 2008; Brouwer & Heeger, 2009; Naselaris et al., 2011; Haynes, 2015;

see Materials and Methods for full details). As stimuli we used random dot kinematograms

(RDKs) as in many studies of perceptual decision making (Newsome & Parè, 1988). These

stimuli consist of an array of dots moving in various directions like a detuned TV-set. By

modifying the proportion of dots that coherently move in a single target direction (signal)

among others moving in random directions (noise), it is possible to assess perceptual decisions

under varying levels of sensory information.

For our feature-continuous motion stimuli the directions were drawn from a uniform

distribution between 0° and 360°. Participants reported their judgements by pressing a button

when a rotating sensory comparison stimulus matched their choice (Figure 1). In previous work

we found that reports like this that used a sensory reference stimulus, instead of e.g. the

movement of a track ball, had the highest accuracy for continuous judgements (Töpfer et al.,

2022). It also allows to decouple choice-related signals from specific motor preparation. We

measured trial-by-trial brain activity under three different coherence levels: 0%, intermediate

and 100% coherence. Note that at 0% coherence there is no physical evidence regarding the

stimulus direction and participants are purely guessing. This condition is of particular

importance because it allows to study choices independent of physical stimulus information,

and it will be the primary focus of our preregistered analyses. In contrast, at 100% coherence

stimulus direction and choices are highly correlated (see below).

Figure 1: A single trial stimulus sequence. Participants were instructed to fixate the center of a bullseye for the entire duration of the experiment. 0.5 s after trial onset, they were presented with 2 s of random dot motion stimulus (RDK) displayed with a different direction of motion and coherence level for every trial. The direction of motion was continuously distributed and spanned between 0° and 360°. For the training task participants were presented with five different coherence levels (0%, 12.5%, 25%, 50% and 100%). For the fMRI task, instead, only three coherence levels were presented (0%, an intermediate coherence level individually estimated during the training phase, and 100%). Based on previous experiments (Töpfer et al., 2022) we used a report method that involved a rotating perceptual comparison stimulus and thus was given in a perceptual (as opposed to a motor) frame of reference. This has the advantage of increasing accuracy and minimizing bias (Töpfer et al., 2022). Specifically, participants were instructed to report the net motion direction by pressing the response button when a self-moving rotating bar on the screen matched the direction of motion they perceived. After the report was given the bar continued its cycle so that the presentation duration was always 7.5 s. Inter-trial-intervals (ITIs) for the training task were 1 or 2s, for the fMRI task they were between 3s, 5s, 7s and 9s, exponentially distributed so that shorter ITIs happened more frequently than longer ones.

Participants were able to correctly perform the continuous task with increasing accuracy the

higher the coherence of the stimuli (Figure 2). When sensory information was absent (0%

coherence) there was no relationship between direction and report, thus as expected participants

responded largely randomly (Figure 2 A,B left panels). With increasing sensory evidence the

distributions of responses became narrower and centered around the veridical direction (Figure

2 A,B mid and right panels). This was also reflected in increasing levels of accuracy with

increasing coherence (Figure 2C). As expected from previous work (Töpfer et al., 2022) our

chosen report method (see Methods) minimized the reporting biases across the motion

directions.

Figure 2: Behavioral results. The three plots show the behavioral performance pooled from all subjects (N=23) for each coherence level. **(A)** Scatterplots and marginal distributions of the stimulus and reported directions for each level of coherence (each point corresponds to one trial). **(B)** Distribution of participants' response deviations (where 0° corresponds to perfect performance). Note the flat distribution when direction information is absent (0% coherence) and the narrowing of the response distributions with increasing coherence. **(C)** Performance accuracy (measured as deviations as in **B** but replotted as FCA, which is scaled such that 100 is perfect performance and 50 is chance performance; see Methods). In each box, the central red line indicates the median accuracy, the asterisk indicates the mean accuracy. The bottom and top edges of the box indicate the 25th and 75th percentiles, respectively. The whiskers extend to the most extreme data points not considered outliers, and the outliers are plotted individually using a red cross. The dashed black line indicates chance performance. There was a main effect of coherence on accuracy (repeated measures ANOVA; F(1.26, 27.818) = 1357.545; p < 0.001; Greenhouse-Geisser corrected for non-sphericity).

The brain signals associated with these behavioral judgements were then entered into two

different preregistered encoding model analyses: One that assessed encoding of the *physical*

stimulus direction, and the other that modelled the encoding of the participants' trial-by-trial

reports. Our model extends the framework of so-called choice probabilities that were primarily

developed for binary choices (Britten et al., 1996; Chicharro et al., 2021) to continuous

encoding. In comparison to other studies, our encoding models were based on a cyclic version

of Gaussian Process Regression (GPR; Rasmussen & Williams, 2005; Caywood et al., 2017;

Dimitrova et al., 2020). This has the advantage of providing not only an estimate of the mean

response in each voxel for a given direction, but also of the distribution across trials, separately

for each direction, allowing to obtain tuning response profiles (see Methods for details). Also,

this approach does not require any a priori assumptions regarding the smoothness of the tuning

functions (compared to e.g. Brouwer & Heeger, 2009). Figure 3 shows examples of these voxel

tuning functions for sixteen visually responsive voxels of one participant. There is considerable

variability with some voxels showing various forms of smoothly varying tuning functions,

while others are non-informative and flat. Note that these tuning functions cannot be directly

interpreted in terms of single-neuron tuning, but reflect a complex integration of a population

of tuned neurons within a voxel (Kriegeskorte et al., 2010; Ramirez et al., 2014; Sprague et al.,

2018; Gardner & Liu, 2019, Sprague et al., 2019).

Figure 3: Trial-wise activity and estimated sensory voxel tuning response profiles based on GPR (see Methods)
for encoding of physical stimulus direction. The plot shows the trial-wise fMRI response (black dots) as a function
of motion direction, along with the estimated GPR-based tuning functions of 16 voxels (mean = black lines;
standard deviation = gray bands; example participant; 100% coherence condition). The voxels were randomly
chosen from the subject's most informative searchlight of the ROI described in the exploratory analyses (see
Additional exploratory analyses in the Materials and Methods section). Trial-wise activity (y-axis) is here plotted
as parameter estimates of a trial-wise 1st level GLM versus corresponding stimulus motion directions (x-axis).
The estimated response profiles (thick lines, grey regions) were obtained by averaging the voxel-wise GPR
predictions across 10 cross-validation folds. The data were mean-centered and are shown at the same scale to
facilitate comparison.

Figure 4: *Voxel-wise GPR estimation to obtain tuning response profiles*. This schematic example is based on simulated data and illustrates the steps involved in the voxel-wise GPR estimation. For a given direction of motion in a given trial we obtain a (trial-wise) parameter estimate for the response amplitude in each voxel. The middle shows a set of trial-wise measurements for two example voxels. The x-axis corresponds to the direction of motion in a trial and the y-axis to the trial-wise activity in that voxel. Each vertical section is equivalent to a likelihood function of a brain response amplitude in a voxel given a certain stimulus direction. We use Gaussian Process Regression (GPR) to estimate the family of these likelihood functions across different movement directions (right column, "GPR estimation"). The analysis can be performed either with the veridical stimulus motion direction θ_s or the reported direction θ_r.

In the next step, we used ensembles of voxel-wise tuning functions from different pre-defined ROIs to reconstruct (a) the veridical motion direction and (b) the reported direction in each given trial (see Figures 4 and 5 for details on methods). These five bilateral ROIs were early visual cortex (EVC), MT+, superior parietal cortex (SPC), intraparietal sulcus (IPS), and inferior parietal cortex (IPC). These areas have been reported in previous work to be involved in encoding of motion and decision signals (Kamitani & Tong, 2006; Serences & Boynton, 2007; Hebart et al, 2012; Bode et al., 2013; Levine & Schwarzbach, 2017).

Figure 5: *Searchlight-based GPR reconstruction from a multivoxel ensemble of tuning response profiles*. This shows the steps involved in the searchlight-based reconstruction of one trial focusing on just two voxels. The red arrow on the left shows an unknown true direction on a single trial T_1. The aim is to estimate this true direction with maximum precision from an ensemble of trial-wise brain responses using the tuning response profiles. The red parameters on the y-axis in the middle column ($\beta_{1, T1}$ and $\beta_{2, T1}$) show the measured brain responses in that trial in the two voxels. The horizontal red section illustrates the likelihood values for each direction. If one were only using a single voxel one would estimate the direction as that where the likelihood is maximal (assuming a flat prior as in our study). In our case we combine the likelihood estimates across an ensemble of voxels (in a searchlight) and identify the maximal value, which corresponds to our decoded direction of motion in that trial.

Figure 6 shows the stimulus-related and report-related accuracies for each of these ROIs and each coherence level. For each ROI, we tested whether coherence or label (stimulus versus report) influenced accuracy. Based on previous research on motion direction decoding with fMRI we expected that fMRI-signals would carry highest information in early visual cortex (Kamitani & Tong, 2006; Serences & Boynton, 2007; Hebart et al, 2012), whereas it was unclear whether this region is expected to encode choice (Ress & Heeger 2003; Serences & Boynton, 2007; Brouwer & van Ee 2007; Krishna et al., 2021). As expected, we found a main effect of coherence on reconstruction performance for the visual ROI (coherence on EVC: $F_{(2, 44)} = 11.909$, $p < 0.001$) but there was no difference between accuracies for stimuli and reports

and no interaction (F(1,22) = 2.42, p = 0.134; label*coherence F(2,44) = 0.69, p = 0.507). A

post-hoc t-test performed on EVC revealed no difference between the stimulus and the report

reconstruction at 0% coherence (t = -1.793; p = 1, Bonferroni corrected for a family of 15

multiple comparisons).

As in some (but not all) previous studies we also expected the motion sensitive complex MT+

to be informative of veridical motion direction (Kamitani & Tong, 2006) and of perceptual

judgements (Serences & Boynton, 2007). We also expected a main effect of coherence on

stimulus and report reconstruction (Britten et al., 1996). In contrast to this prediction, the results

of a repeated measures ANOVA revealed no effect of coherence in MT+ (F(2, 44) = 0.664, p

= 0.52), no effect of which label was being reconstructed (label on MT+: F(1,22) = 2.72, p =

0.113) and no interaction (label * coherence on MT+: F(2,44) = 0.628, p = 0.538). Additional

post-hoc t-tests revealed that the mean stimulus reconstruction performance at 100% coherence

was not different from that of 0% coherence, in which the stimulus has no net direction of

motion (t = 1.069; p = 1, Bonferroni corrected for a family of 15 multiple comparisons). Please

note that these differences to previous work might reflect the fact that we employed continuous

stimuli and also that we used a very different response format that did not involve differential

or even dispositional motor preparation.

We also found a main effect of coherence on reconstruction performance for one region of

parietal cortex (SPC; coherence SPC: F(2,44) = 4.219, p = 0.021), but no effect of which label

was reconstructed (label SPC: F(1,22) = 0.712, p = 0.408) and no interactions were found

(label*coherence SPC: F(2,44) = 0.502, p = 0.609). We did not find any effect on

reconstruction performance for the other parietal ROIs (IPS and IPC).

284
Figure 6: Reconstruction from regions of interest in visual and parietal cortex. The top row shows reconstruction
accuracy (expressed as balanced feature continuous accuracy, BFCA, which is corrected for biases due to unequal
distribution of responses across the sensory continuum, see Methods) for regions of interest in early visual cortex
(comprising V1, V2 and V3) and MT+ separately for each coherence level. The bottom row shows the same for
three regions of parietal cortex. Filled versus open symbols indicate reconstruction of stimulus and report
respectively. Error bars are standard errors. Dashed lines indicate chance level (N = 23).
291

We then conducted an exploratory analysis aimed to identify informative regions beyond our

pre-defined regional hypotheses. For this, we used whole-brain searchlight reconstruction maps

(see Methods). In line with our ROI-based findings this only revealed a cluster in early visual

cortex (left occipital pole; Appendix 1 – Figure 2). Interestingly, we found no region where

coherence affected reconstruction of choices (see Appendix 1 - *Statistical analyses:*

searchlight-based reconstructions and effect of coherence).

Taken together, the early visual cortex is the only area where we were able to reconstruct

information about continuous motion stimuli and their corresponding choices. At 0%

coherence we found no evidence for either stimulus encoding (as expected) or response

encoding in our early visual ROI. In constrast, other studies have revealed choice signals

already in early visual areas (Ress & Heeger, 2003; Serences & Boynton 2007; Sousa et al.

2021). We thus assessed whether our a priori defined early visual ROI might be defined too

widely to reveal potential differences between stimulus and report reconstruction. For this, we

conducted a single test with a more focused analysis of the voxels that encoded both stimulus

and report across all of the coherence levels (0%, Intermediate and 100%). Such voxels were

located in the occipital cortex bilaterally. We found a label*coherence interaction effect on the

reconstruction performance in these areas ($F(1.327, 29.191) = 4.426$, $p = 0.034$; Greenhouse-

Geisser correction for non-sphericity; see Figure 7). Moreover, post-hoc t-tests revealed a

significant difference between stimulus and report reconstruction at 0% coherence for this more

focused voxel set (Table 1 - $t = 3.560$; $p = 0.011$, Bonferroni corrected for a family of 15

multiple comparisons). Please note that the voxel selection for this analysis was collapsed

across both stimulus and report reconstruction and was thus not biased a priori to yield such a

difference.

316
317   **Figure 7:** Interaction between coherence level and reconstructed label within a subsection of the early visual
318   region (the conjunction of voxels that code for both stimulus and report). The plot displays the averaged above-
319   chance accuracy (expressed as BFCA, see Methods) across voxels for each coherence level and each reconstructed
320   label, error bars are standard errors, the black dashed line represent chance level (N = 23). Please note that this
321   voxel selection does not affect the difference between encoding of stimulus versus reports.

Post Hoc Comparisons – Coherence * Reconstructed Label

		Mean Difference	SE	t	P_bonf
Coherence 0%, Report	Coherence Intermediate, Report	-0.854	0.508	-1.682	1.000
	Coherence 100%, Report	-1.338	0.508	-2.635	0.155
	Coherence 0%, Stimulus	1.397	0.392	3.560	0.011 *
	Coherence Intermediate, Stimulus	-0.379	0.530	-0.715	1.000
	Coherence 100%, Stimulus	-1.453	0.530	-2.744	0.114
Coherence Intermediate, Report	Coherence 100%, Report	-0.484	0.508	-0.953	1.000
	Coherence 0%, Stimulus	2.251	0.530	4.250	< .001 ***
	Coherence Intermediate, Stimulus	0.475	0.392	1.211	1.000
	Coherence 100%, Stimulus	-0.599	0.530	-1.131	1.000
Coherence 100%, Report	Coherence 0%, Stimulus	2.735	0.530	5.164	< .001 ***
	Coherence Intermediate, Stimulus	0.959	0.530	1.810	1.000
	Coherence 100%, Stimulus	-0.115	0.392	-0.294	1.000
Coherence 0%, Stimulus	Coherence Intermediate, Stimulus	-1.776	0.508	-3.498	0.012 *
	Coherence 100%, Stimulus	-2.850	0.508	-5.613	< .001 ***
Coherence Intermediate, Stimulus	Coherence 100%, Stimulus	-1.074	0.508	-2.116	0.568

Note. P-value adjusted for comparing a family of 15
* p < .05, ** p < .01, *** p < .001

323
324 **Table 1:** Post-hoc t-tests performed on the stimulus and report reconstruction performance. Please, note that in
325 the 0% coherence condition, the stimulus labels are unrelated with the motion direction (motion signal is absent,
326 and labels are randomly assigned), hence the chance-level reconstruction performance is to be expected.
327

Model generalization

In order to further test these choice-related signals, we performed a specifically targeted cross-

prediction analysis. We took the report-related reconstruction model estimated at the 0%

coherence condition and used it to cross-predict the stimuli in the 100% coherence condition.

This model generalization constitutes an independent test of the choice signals. Importantly,

by training the reconstruction model on the 0% condition we avoid that our model is influenced

by residual sensory information. This tests whether the choices at 0% coherence, i.e. when

participants are guessing, use a similar representational format as the encoding of stimuli.

Indeed, the 0% coherence report model generalized to the 100% stimulus condition (and vice-

versa) (right tailed one sample t-test; $t(22) = 2.969$; $p = 0.004$). For exploratory purposes we

also repeated this procedure with stimulus motion directions in the intermediate and 0%

coherence condition. The generalization tests between the different reporting conditions

constitute a test of model consistency across evidence levels and were all above chance. As

predicted the cross-prediction was significant between 0% coherence report and the two above-

chance stimulus encoding conditions, but not the 0% coherence condition where there is no

sensory information. The summary of this cross-prediction analysis is displayed in Figure 8.

Thus, we conclude that choice-related signals are present at guessing levels in early visual

cortex and that these signals are encoded in a similar form as the physical stimulus features.

347
Figure 8: Cross-prediction performances. The figure summarizes the cross-prediction analyses performed to test
the model generalization and model consistency. Each bar displays the above-chance generalization accuracy
(expressed as BFCA, see Methods) of the 0% report report-related GPR model to every other condition. The bars
on the right hand of the plot (in red) indicate how well the 0% report model allows to reconstruct the stimulus
identity in each coherence condition (model generalization). We were primarily interested in observing the
generalization performance of the 0% coherence report model to the 100% stimulus (first bar on the right). Also
note that since the 0% coherence stimulus model is based on random directions (unrelated with the report or the
stimulus), it represents here a form of control condition in which chance-level generalization performance is to be
expected (the first red bar in the right group). The group of bars on the left hand of the plot (in blue) illustrates
how well the 0% report model allow to reconstruct behavioral reports in each coherence condition (model
consistency)(N=23; errorbars: SEM).
359
360

In order to control for involuntary eye movements that might have confounded our

reconstruction analyses, we had first decided to exclude trials where subjects exceed a

threshold of 2 dva for more than 200 ms during the stimulation period. However, recent

evidence indicates that involuntary eye movements below our adopted threshold might still

affect brain activity, thus constituting a potential confound (Merriam et al., 2013; Thielen et

al., 2019). For this reason, we complemented our preregistered results with an additional

analysis that exploited the same GPR-based estimation and reconstruction techniques adopted

for the analysis of brain signals, to the eye movements recorded with eye-tracker (see Appendix

1 - *Control analysis: stimulus and report reconstruction from eye-tracking data*). Our results

revealed that the pattern of eye movement was unrelated to the stimulus or the report in the

100% and the intermediate coherence condition, but it was predictive of participants' reports

in the 0% coherence condition (Appendix 1 – Figure 3). Thus, it could have been possible that

the choice signals in the guessing condition were partly affected by eye movements. However,

this would not explain why our report model generalized from the guessing to the other

conditions, where eye movements did not play a role.

DISCUSSION

Previous studies on neural mechanisms of perceptual decision making have often focused on

simple decisions involving discrete alternatives. These have found discrete decisions to be

encoded either in intention-related formats (Shadlen et al., 2008), or in high-level but effector-

independent formats (Heekeren et al., 2008; Bennur & Gold, 2011; Hebart et al., 2012; Park et

al., 2014; Brincat et al., 2018). However, it has remained unclear how the brain encodes

perceptual choices regarding an entire continuum of features, which is what our study aimed

to address (see also Nichols & Newsome, 2002; van Bergen et al., 2015; Ratcliff, 2018 for

other examples of continuous stimuli). Our study also disentangled stimulus and choice-related

activity from motor responses by using a visual comparison stimulus (a rotating bar). Our

modelling of single-voxel responses as continuously varying distributions using Gaussian

Process Regression (GPR; Rasmussen & Williams, 2005) allowed us to estimate tuning

functions in considerable detail and without making a priori assumptions regarding their

smoothness.

Our design revealed that the activity of visual voxels was modulated by both the stimulus

directions across trials (Figure 3) and by participants' perceptual choices regarding the motion

direction. We were able to reconstruct the stimulus motion direction from clusters of voxels in

early visual cortex (Figure 6), and to identify a region of occipital cortex in which the change

in coherence level had a different effect on stimulus and report reconstruction (Figure 7). These

findings extend previous research on decoding of visual motion direction and perceptual

choices from brain signals (Kamitani & Tong, 2006, Serences & Boynton, 2007; Hebart et al,

2012) to the feature-continuous case. Moreover, they indicate that perceptual decisions can be

represented by neural populations encoding the stimulus distribution over a continuous feature

space in early visual areas (Beck et al., 2008; Smith, 2016; Ratcliff, 2018). By effectively using

such distributions for quantifying the degree to which trial-by-trial variations in brain signals

are predictive of the corresponding judgements, we adapted the framework of so-called choice

probabilities (Britten et al., 1996; Chicharro et al., 2021) to a feature-continuous task.

Our encoding models also allowed us to go beyond studying encoding itself and to explicitly

assess the similarity between the stimulus-encoding and the report-encoding. For this we tested

whether the information encoded by the report model when guessing could be used to infer the

stimulus motion direction in a set of cross-prediction analyses (Figure 8). This procedure relies

on the assumption that if the model estimated during one condition allows to predict data from

another, then the brain activity patterns elicited by the two conditions are similar (Cichy et al.,

2012; Kaplan et al., 2015; Levine & Schwarzbach, 2017). Note that for 100% and intermediate

coherence levels there is a strong correspondence between the stimulus and corresponding

reports (see e.g. Figure 2-B). This would make any correlation between stimulus and response

encoding trivial. Thus, we limited our generalization analysis to the "guessing" condition, i.e.

the reports for 0% coherence, which were not contaminated by stimulus-related signals. By

using information encoded from this report model, we were able to predict the stimulus

direction at intermediate and full coherence. We refer to this effect as model generalization. In

contrast, we refer to model consistency as the ability of the report to predict reports in other

coherence levels, but this is not a key focus here (see Figure 8). Our generalization analysis

was successful, thus indicating that the sensory information and the choices are encoded in a

similar representational feature space. This would suggest that the neural mechanisms recruited

by visual areas to support perceptual decisions are, to some extent, the same used to encode

visual stimuli. Whether this generalizes to discrete choice options or to other forms of report

remains an open question.

Using our stimuli and task we did not find any significant motion direction or choice-related

signal in area MT+. Previous studies have yielded somewhat inconsistent results on what to

expect. There are numerous studies indicating the key role of MT+ in motion perception

(Newsome & Parè, 1988; Rees et al., 2000; Braddick et al., 2001; Kamitani & Tong, 2006;

Serences & Boynton, 2007; Sousa et al. 2021). However, other researchers employing

multivariate pattern analysis and fMRI also did not find direction of motion information in

MT+ (possibly due to short viewing times of stimuli, see e.g. Hebart et al., 2012, but see also

Wang et al., 2014). Others have also found considerably lower levels of direction-related

information in neuroimaging signals recorded from MT+ compared to V1 (Kamitani & Tong,

2006; Serences & Boynton, 2007). Please note that the relationship between single cell tuning

and single voxel BOLD response profiles requires additional assumptions on how the voxel

samples population of tuned sensory neurons (Nevado et al., 2004; Haynes, 2015; Sprague et

al., 2018; Gardner & Liu, 2019, Sprague et al., 2019). For example, our negative finding could

reflect the fact that the spatial distribution of cells encoding stimulus directions or choices in

MT+ might not have been sufficiently anisotropic to differentially influence the fMRI signals.

Alternatively, it could also reflect the continuous or graded nature of the task.

There are two other factors besides the continuous decisions that might help explain why

choice-related information is only observed in early visual areas with our design. First, in our

task specific motor preparation is impossible due to the employment of a visual comparison

stimulus that rotated independently. While some studies have decorrelated choices and specific

motor commands (e.g. Bennur & Gold, 2011; Bode et al., 2013) this is typically done by post-

cueing a variable stimulus-response mapping and thus, the preparation of the response can be

at least conditionally prepared (i.e. the motor command can be prepared in form of a differential

response to a mapping cue).

A second difference is that the nature of our task involves a brief delay between the perceptual

decision and the report in the absence of any possibility for motor preparation. Solving such a

task might be achieved by briefly memorizing the target stimulus. In human neuroimaging

studies of visual working memory sensory regions have been shown to encode stimulus

features across short delays (Serences et al., 2009; Riggal & Postle, 2012; Pratte & Tong, 2014;

Christophel et al., 2017), which is consistent with neuroimaging evidence from feature-

continuous perceptual tasks involving a working memory component (van Bergen et al., 2015).

To summarize, our combination of a continuous feature task and fMRI encoding models

suggested that early visual areas, but not MT+, allowed to reconstruct both continuous physical

motion stimuli as well as continuous choices. Taken together, our results indicate that

perceptual decisions regarding continuous sensory features might be encoded in early visual

areas, potentially akin to visual working memory signals in sensory areas.

MATERIALS AND METHODS

Preregistration

The hypotheses, methods and analyses employed in this study were preregistered at https://osf.io/e2bvn before analyzing the data. Any additional exploratory analyses that go beyond what is specified in the preregistration are explicitly marked as such below.

Data and Code availability

The data needed to reproduce the main analyses described in the paper are openly available on OSF at https://osf.io/vcmdg/ (DOI 10.17605/OSF.IO/VCMDG), whereas the code is available on Github https://github.com/RiccardoBarb/GPR_fMRI.

Participants, payment and exclusion criteria

We recruited participants from several sources. Some were contacted using an internal mailing list consisting of people who previously participated in fMRI experiments in our lab. Others were recruited from Facebook groups for English-speaking jobs in Berlin and Berlin university students. All of the participants gave written informed consent, were paid 7€/h for the behavioral training session and 10€/h for the fMRI sessions. Those who completed all of the experimental sessions (1 training + 2 fMRI) received an additional bonus of 50€. The research protocol was conducted in accordance with the Declaration of Helsinki and approved by the local psychological ethics committee.

We selected healthy right-handed subjects with no history of neurological or psychiatric

diseases. Furthermore, following our previous studies (Töpfer et al., 2022), we decided to

exclude participants *prior to scanning* on the basis of their performance in a behavioral training

session.

1) A participant was excluded if they were not sufficiently precise in the indication of

motion direction, which was defined as the the 95% percentile of the Δx distribution

(see below, eq.1) in the full coherence condition exceeding a cutoff of 36.5°.

2) We also excluded participants that were not able to correctly perceive the stimulus in

another, more systematic way. We had previously observed that some subjects

frequently mistake a motion direction with its 180-degree opposite, a phenomenon that

would be mistaken for a guess in most conventional categorical motion judgement

tasks. For this reason, we employed a von Mises mixture model (vMMM) to quantify

the frequency of reports of opposite direction (ROOD; Töpfer et al., 2022). ROOD rates

exceeding 5% at full coherence led to the exclusion of a participant.

We initially collected behavioral training data from 41 subjects. Of these, 13 were excluded

after the training phase prior to scanning following the abovementioned exclusion criteria.

Three participants didn't complete the MRI sessions for technical reasons and were excluded

from the subsequent analyses; thus, 25 participants completed the fMRI sessions. One

participant with low behavioral performance in the training session was accidentally included

in scanning and was subsequently removed leading to a total of 24 participants who

successfully concluded the experiment according to our pre-defined criteria (9 females; age

range: 18-34; mean age: 25.6; SD: 4.6). We used the data of one participant to develop and

check our Gaussian Process Regression (GPR) pipeline. In order to avoid any circularity or

overfitting this participant was not included in the final analyses, which led to a total sample

size of 23 subjects considered for all the statistical analyses.

Stimuli: general features

The random dot kinematograms (RDKs – Figure 1) consisted of white dots moving inside a

circular aperture on a black background. The aperture was centered on the screen and had an

inner diameter of 2.5 dva and an outer diameter of 15 dva. Alpha blending was applied at the

borders to avoid sharp contrast boundaries. For this, the luminance of the dots was

progressively reduced before they wrapped around the other side of the annulus. The dot size

was 0.1 dva (Braddick, 1973). The motion speed of the dots was 6º/s (van de Grind et al., 1983;

Geisler, 1999) and the dot density was 1.6 dots/dva^2 (Downing & Movshon, 1989), leading to

a total of 275 dots. A white bullseye fixation target (Thaler et al., 2013) was placed in the

central aperture spanning 0.25 dva. The mean luminance measured on the white center of the

bullseye was 17.5 cd/m^2. The mean luminance measured on the black background was 0.206

cd/m^2.

Stimuli: directions of motion

To pseudo-randomize the directions across trials, while maintaining the continuous nature of

the task, we separated the stimuli into 8 hidden randomization bins. Each bin divided the

stimulus space into equal portions of 45º. The bin edges were set at 337.5º, 22.5º, 67.5º, 112.5º,

157.5º, 202.5º, 247.5º, 292.5º (0° pointing up, 90° pointing right). Within a bin, the direction

of motion was uniformly randomly distributed. In this way we made sure that the motion

direction varied continuously across trials, while respecting some experimental constraints. We

used an equal amount of trials for each subject in each directional bin, the same bin did not

occur more than twice in a row and the same coherence level was not presented more than three

times in a row.

Training session: experimental setup

In order to train participants on the task lying-down in supine position (as during MR-

scanning), we used a custom-built mock scanner. The training phase of the experiment took

place in a dimly illuminated room (mean background luminance as measured on a white wall:

0.0998 cd/m^2), where participants were lying in this mock scanner. They placed their head on

a pillow and viewed a DELL LCD monitor 35 cm wide through a reflecting mirror. The monitor

was set with 60 Hz refresh rate and a resolution of 1024x768 pixels. The stimuli were generated

and presented using MATLAB R2016a (The MathWorks Inc.) and Psychtoolbox 3 (Brainard,

1997; Kleiner et al., 2007). For behavioral training, participants had their right hands on a

standard computer keyboard placed on their hips.

Training task

For the training session, each trial started with the presentation of a fixation bullseye which

remained present throughout the whole duration of the trial (see Figure 1). Participants were

instructed to fixate the center of the bullseye for the entire duration of the trial. After 0.5s,

participants were presented for 2s with a random dot motion stimulus (RDK) that had a

different direction of motion and coherence level for every trial. The direction of motion was

continuously distributed between 0° and 360° and its order of presentation was subject to

constraints (see above). There were five different coherence levels in the training phase: 0%,

12.5%, 25%, 50%, 100%. After termination of the stimulus, participants gave a judgement of

motion direction using a report that employs a perceptual frame of reference with a visual

comparsion stimulus (see Figure 1). In a previous study (Töpfer et al., 2022) we observed that

this method of responding avoided systematic biases that are observed when using continuous

reports involving trackballs that employ a motor frame of reference. Specifically, after offset

of the motion stimulus a self-moving rotating bar was presented inside the aperture.

Participants were asked to indicate the net motion direction of the dots by pressing the response

button as soon as they believed the bar on the screen to match the direction of motion they

perceived. The bar pointed from the center of the aperture to the outer border of the stimulus

(like the arm of a clock), starting from a random position in every trial. The bar was 7.5 dva in

length. It was randomly chosen to rotate clockwise or counterclockwise around the central

fixation at a speed of 0.2 cycles/second, and it kept rotating after the response was given so

that the total rotation time was always 7.5s. Participants were instructed to always respond as

precisely as they could, even if they were unsure. On some trials (catch trials), a portion of the

rotating bar changed contrast after the response indication. Participants were instructed to press

the response button as fast as possible when they detected the contrast change. The purpose of

such trials was to make sure that participants were paying attention to the bar rotation

throughout the entire duration of the response period (even after they indicated their response),

while maintaining fixation. In the training task, participants' responses were followed by a

uniform inter-trial interval (ITI) of 1 or 2s, after which a new trial started. Subjects performed

9 blocks of 40 trials during the training phase. An additional block was used to estimate the

exact level of coherence that yielded intermediate performance using the QUEST staircase

method (Watson & Pelli, 1983).

fMRI experimental task

Participants who completed the training and matched our performance requirements (see

section *Participants and exclusion criteria*) were scheduled for 2 different MRI sessions on 2

different days. Participants performed a total of 10 experimental runs (5 runs in each session).

The structure of the training and the experimental tasks were essentially the same, except for

the inter-trial interval (ITI), which was chosen between 3s, 5s, 7s and 9s, where ITI frequency

was exponentially distributed (shorter ITIs were more likely than longer ones). Moreover, in

the scanning sessions, the RDK was presented with three coherence levels instead of five: 0%,

an intermediate coherence level estimated for each subject from the training phase data (mean

coherence level: 19.47%; SD: 5.3%), and 100%. Each coherence level was presented 16 times

in each run which resulted in 48 trials per run for a total of 10 runs. Participants were required

to maintain fixation for the entire duration of the trial. Their eye position was monitored with

an MRI compatible EyeLink1000+ eyetracking system.

fMRI localizer task

After the experimental runs, participants performed 2 runs of an MT-localizer task on each day,

for a total of 4 runs on both days. In the localizer, their task was to passively view the presented

stimulus while maintaining fixation. After 0.5 s of bullseye, they viewed an 8s RDK at 100%

coherence with random directions changing at a frequency of 2Hz, followed by 8 s RDK at 0%

coherence. The ITI was implemented in the same way as in the main fMRI task. Participants

were instructed to fixate the center of a bullseye for the entire block. The total number of blocks

for each run was 32 (16 coherent, and 16 incoherent). This particular design has been proven

effective in eliciting a strong BOLD signal in motion-sensitive visual areas (Braddick et al.,

2001).

MRI data acquisition

Functional MRI data were acquired on a 3T Siemens Prisma scanner (Siemens, Erlangen,

Germany) equipped with a 64-channel head-coil, using a T2-weighted multi-band accelerated

EPI sequence (from the Human Connectome Project - HCP) with a multiband factor of 8. The

fMRI runs (TR = 800 ms, TE = 37 ms, flip angle = 52°, voxel size = 2 mm x 2 mm isotropic,

72 slices, 1.9 mm inter-slice gap) were preceded by a high-resolution T1-weighted MPRAGE

structural scan (208 sagittal slices, TR = 2400 ms, TE = 2.22 ms, flip angle = 8°, voxel size =

0.8 mm^2 isotropic, FOV = 256 mm). The MRI sessions took place over the course of two days.

Each day comprised 5 experimental runs (805 whole-brain volumes per run) and 2 functional

localizer runs (480 whole-brain volumes per run). The first 4 TRs were discarded to allow for

magnetic saturation effects.

Eye-Tracking data acquisition

Horizontal and vertical gaze position as well as the area of the pupil, were recorded from each

subject's dominant eye in the MRI scanner using an EyeLink 1000 + (SR-Research, sampling

rate 1000 Hz) with long distance mount. Calibration took place before the experiment once at

the beginning of every session.

Data analysis

Behavior: Measures of performance accuracy

The absolute trial-by-trial circular response deviation from the target direction was used as a

primary measure of performance accuracy. This is obtained by calculating

645
$$|\Delta x| = |\theta_s - \theta_r|$$
(1)

647 where θ_s is the stimulus direction and θ_r is the reported direction. Furthermore, as in previous

648 studies we rescaled the absolute deviation in the range 0% - 100% (feature-continuous

649 accuracy, FCA – see also Pilly & Seitz, 2009) following the formula:

651
$$FCA = \frac{180° - |\Delta x|}{180°} \times 100$$
(2)

Here chance performance, i.e. randomly guessing the continuous direction, corresponds to an

average FCA of 50% (or $|\Delta x| = 90°$) and perfect performance, i.e. identically matching the

presented direction, corresponds to an FCA of 100% (or $|\Delta x| = 0°$). This approach has the

advantage of providing a trial-by-trial measure of performance, which is interpretable at all

coherence levels (including 0% coherence) and facilitates the comparison with more

conventional 2-choice accuracies. An alternative to this approach would consist in fitting a

mixture model to obtain an estimate of detection and guessing (Zhang & Luck, 2008; Bae &

Luck; 2019; Töpfer et al., 2022). However, at 0% coherence, when there is no motion direction

information available and subjects are purely guessing, the model fit would provide

uninterpretable estimates for the detection parameter (Töpfer et al., 2022).

Localizer: Definition of ROIs

The fMRI data from the localizer runs were first spatially realigned, coregistered to individual anatomical images (Glasser et al., 2013) and spatially smoothed using a Gaussian kernel with an FWHM of 6mm. For each subject, we then modelled the activity during the localizer in each voxel using a general linear model implemented in SPM12. For each of the 4 runs, we included 1 regressor for coherent motion and 1 for incoherent motion, as well as 6 regressors of no interest to account for participants' head movement. We then performed two univariate analyses: The first assessed in which voxels the BOLD signal was stronger during coherent compared to incoherent motion (for definition of MT+, see below). The second assessed where both coherent and incoherent motion activated voxels above baseline (for early visual and parietal brain regions, see below). The statistical maps obtained with this contrast were corrected for multiple comparison and thresholded at $p < 0.05$ (FWE). ROIs can be seen on the left part of Figure 6.

Early visual cortex (EVC): Early visual cortex was defined based on a combination of a spatially normalized functional mask of motion-related activity and an anatomical mask defined by the union of V1, V2 and V3. Unlike MT+ masks, the functional EVC mask was defined at the group level because we didn't expect significant inter-individual differences in the activation maps elicited by our contrast. Specifically, the functional activation elicited by both localizer stimuli (coherent and incoherent against baseline) constituted a large cluster ($p < 0.05$, FWE) at the occipital pole. Please note that this voxel selection is independent of motion coding information. For the anatomical mask we employed the SPM Anatomy Toolbox (Eichkoff et al., 2005) to define an anatomical mask spanning the occipical areas hOC1, hOC2 (Amunts et al., 2000), hOC3d (Rottschy et al., 2007) and hOC3v (Kujovic et al., 2013). Our

early visual ROI is defined as the intersection between the functionally and the anatomically

defined masks.

Area MT+: The motion complex MT+ was identified as the set of voxels activated more to the

coherent than the incoherent localizer stimuli within a sphere (r = 10mm) located in the center

of the significant clusters lateral to the parietal-occipital sulcus bilaterally (see Figure 6 for the

MT+ ROI of an example subject).

Parietal areas: We used the SPM Anatomy Toolbox (Eichoff et al., 2005) to further select

voxels from three different subregions of parietal cortex that have previously been reported as

informative about behavioral choices in similar perceptual decision-making experiments (Bode

et al., 2013; Hebart et al., 2012, 2016): Superior Parietal Cortex (SPC - areas 5L, 5M, 5Ci, 7A,

7PC, 7M, 7P; Scheperjans et al., 2008), Inferior Parietal Cortex (IPC - areas PFop, PFt, PF,

PFm, PFFcm, PGa, PGp; Caspers et al., 2006) and Intraparietal Sulcus (IPS - areas hIP 1-3;

Choi et al., 2006; Scheperjans et al., 2008).

Main experiment: Selection of trials based on eye-tracking

In order to avoid potential eye-movement confounds in our main fMRI analysis we checked

that participants maintained fixation using the eye-tracker data. For this, in a first step we used

a preprocessing pipeline adapted from Urai and colleagues (2017). Missing data and blinks

were not interpolated for fixation control. The standard deviation of the gaze position was

estimated for every run and every subject. We obtained the probability density function of the

distribution of all standard deviations of eye positions, collapsed across all subjects and runs,

using a kernel density estimation. A noise threshold was defined by estimating the inverse of

the cumulative density at the probability of 0.9. This is equivalent to excluding the 10% of the

noisiest runs based on the fixation analysis. Furthermore, trials where subjects exceed a

deviation threshold of 2 dva for more than 200 ms during the stimulation period were rejected

from the analysis of the neuroimaging data. The eye fixation control resulted in the exclusion

of 295 trials, or an average of 2.3% of trials for each participant (mean number of trials: 11.13;

SD: 14.51). Together with trials in which participants didn't report their perceived direction,

we excluded an average of 2.5% trials per subject (mean number of trials: 12.17; SD: 14.42).

A repeated-measures ANOVA revealed no significant difference in the amount of excluded

trials across coherence levels ($F_{(2,44)} = 1.296$, $p = 0.284$).

Main experiment: Statistical analyses of behavioral performance

In order to evaluate the effect of coherence on behavioral performance, we performed a

repeated-measure ANOVA on performance accuracy (FCA – see eq. 2), with coherence level

as within-subject factor. The test was performed with JASP.

Main experiment: FMRI data analysis

The fMRI data analysis of the main experimental task was performed in MATLAB using SPM

12, the GPML toolbox (Rasmussen & Nickish, 2010) and custom functions. Before the

analysis, data were motion corrected and coregistered to anatomical images. After this

preprocessing, the analysis proceeded in four steps: (1) trial-wise and voxel-wise GLM; (2)

voxel-wise Gaussian Process Regression (GPR) estimation; (3) searchlight-based stimulus and

report reconstruction; (4) group level analyses.

Trial-wise GLM: For each participant, we modeled the fMRI signal acquired in each voxel

during the 2s of the stimulus period with a trial-wise GLM (Rissman et al., 2004). Our model

consisted of one regressor per trial and 6 head-motion regressors of no interest for each run.

Voxel-wise GPR estimation: In a next step we computed what we refer to as Full Distribution

Tuning Functions (FDTF) for each voxel to assess how the estimated trial-wise responses in

that voxel were modulated either by the stimulus direction θ_s or by the reported direction θ_r.

The key idea of the FDTF over and above conventional voxel encoding models is to not only

estimate the mean response in a given voxel as a function of direction, but to estimate the entire

ensemble of direction-conditional likelihood functions (for details see below). For this we used

Gaussian Process Regression (Rasmussen & Williams, 2005). The trial-wise parameter

estimates were entered into two separate cyclic GPR, models, one for the corresponding

stimulus motion direction θ_s and one for the reported direction θ_r. This yielded a feature-

continuous model of the entire distribution of fMRI responses for each direction, akin to a

voxel-tuning function that includes not only the mean but also the distribution at each direction.

The GPR has the advantage that it does not pre-suppose a fixed number of sensory channels

per voxel (Brouwer & Heeger, 2009; van Bergen et al., 2015). This procedure was repeated for

each coherence level, leading to the estimation of two separate sets of FDTFs for each voxel,

three coherence levels and physical vs reported directions (six estimated models in total).

To be more specific, consider the t = 160 total trials for one coherence level across runs. Then,

let $\hat{\beta}_j$ be the $t \times 1$ vector of trial-wise parameter estimates in a single voxel j and let θ be the

corresponding vector of stimulus or reported motion directions:

$$762 \qquad \hat{\beta}_j = \begin{bmatrix} \hat{\beta}_{j1} \\ \vdots \\ \hat{\beta}_{jt} \end{bmatrix} \text{ and } \theta = \begin{bmatrix} \theta_1 \\ \vdots \\ \theta_t \end{bmatrix}.$$

We assumed that the response amplitude of each voxel j during each trial i was a function of

this trial's direction of motion $\theta_i \in \Theta = (0, 2\pi]$ and the voxel-specific kernel parameters L_j,

plus the normally distributed noise term ε_{ji} :

$$\hat{\beta}_{ji} = f(\theta_i, L_j) + \varepsilon_{ji} \text{ where } f: \Theta \to \mathbb{R}. \qquad\qquad (3)$$

The function f is intentionally specified unconstrained, because it was estimated using voxel-

wise GPR of responses $\hat{\beta}_j$ against directions θ, such that each voxel j obtained a unique

response profile f_j. The estimation of such voxel-wise response profiles was performed

separately for each coherence level. For this we only used trials in which participants

maintained fixation, as evaluated by the analysis of the eye-tracking data (see *Main*

Experiment: Selection of trials based on eye-tracking). In order to avoid overfitting in the

subsequent phases of the analysis (i.e. the searchlight reconstruction), we estimated the

response profiles f_j by including the trials from all runs except one, and repeated the procedure

until the trials from all runs were used for the model estimation (leave-one-run-out cross-

validation scheme). Each iteration was based on a maximum of $9/10 \times 160 = 144$ datapoints

(which could be maximally achieved when no data were excluded after fixation control).

Searchlight-based stimulus and report reconstruction: Next, we used the estimated tuning

functions to reconstruct the direction for a set of independent test trials. We then combined

the estimated $\hat{\beta}_j$ parameters from a group of voxels within a searchlight (r = 4 voxels) into the

matrix $\widehat{\mathrm{B}}$, to predict the stimulus direction θ_s or the reported direction θ_r using a run-wise

cross-validation procedure. The estimated voxel-wise response profiles $f_j = f(\theta_i, L_j)$ can be

used to predict the $1 \times v$ vector of response amplitudes across voxels j in one trial i, i.e. one

row of $\widehat{\mathrm{B}}$:

789
$$\hat{\beta}_{j\bullet} = g(\theta_i, \widehat{L}) + \varepsilon_{j\bullet} \text{ where } g: \Theta \rightarrow \mathbb{R}^{1 \times v} \tag{4}$$

791 as well as the whole $t \times v$ matrix of trial-wise parameter estimates $\widehat{\mathrm{B}}$:

793
$$\widehat{\mathrm{B}} = h(\theta, \widehat{L}) + E \text{ where } h: \Theta^{t \times 1} \rightarrow \mathbb{R}^{t \times v} \tag{5}$$

795 with $\widehat{L} = \{L_1, \dots, L_v\}$, where g and h can be written in terms of f as:

797
$$g(\theta_i, L) = [f(\theta_i, L_1), \dots, f(\theta_i, L_v)] \text{ and } h(\theta, L) = \begin{bmatrix} g(\theta_1, L) \\ \vdots \\ g(\theta_t, L) \end{bmatrix} \tag{6}$$

799 Let's partition the trial-wise parameter matrix $\widehat{\mathrm{B}}$ into training data $\widehat{\mathrm{B}}_{\mathrm{train}}$ and test data $\widehat{\mathrm{B}}_{\mathrm{test}}$

800 and let $\widehat{L} = \{L_1, \dots, L_v\}$, be the set of estimated kernel parameters obtained from $\widehat{\mathrm{B}}_{\mathrm{train}}$. Then,

801 the residuals of the GPR model in the voxel-wise GPR equation are:

803
$$\widehat{R} = \widehat{\mathrm{B}}_{\mathrm{train}} - h(\theta_{train}, \widehat{L}) \tag{7}$$

804 and estimated covariance is:

806
$$\widehat{\Sigma} = \frac{1}{t} \widehat{R}^{\mathrm{T}} \widehat{R} \tag{8}$$

808 In the case that the number of voxels in a searchlight v is larger than the number of trials across

809 runs t, the matrix is not invertible, such that it has to be regularized. Here, we chose a shrinkage

810 estimator by mixing in a diagonal matrix of sample variances

812
$$\hat{\Sigma} = (1 - r) \cdot \frac{1}{t} \hat{R}^T \hat{R} + r \cdot \text{diag}([\hat{\sigma}_1^2, \dots, \hat{\sigma}_v^2]) .$$
(9)

814 Where the mixing coefficient r was a function of the voxel-to-trial ratio:

816
$$r \, (v/t) = \frac{1}{\pi} \left[\arctan \left(\ln \frac{v}{t} \right) \right] \quad \text{(arctan regularization)}$$
(10)

818 or

819
$$r \, (v/t) = \frac{1}{\left[1 + \exp \left[-\ln \frac{v}{t} \right] \right]} \quad \text{(logistic regularization)}$$
(11)

821 such that $r = \frac{1}{2}$ when $\frac{v}{t} = 1$ and $\lim_{x \to 0} r(x) = 0$ as well as $\lim_{x \to \infty} r(x) = 1$.

823 Let's consider the responses of all voxels in just one trial. According to the GPR model, those

824 single-trial across-voxel responses are distributed as

826
$$\hat{\beta}_{\bullet i} = g(\theta_i, L) + \varepsilon_{\bullet i}, \; \varepsilon_{\bullet i} \sim \mathcal{N}(0, \Sigma)$$
(12)

827
828 Which implies a multivariate normal log-likelihood function

830
$$\text{LL}(\theta_i) = \log p \left(\hat{\beta}_{\bullet i} | \theta_i \right) = \log \mathcal{N} \left(\hat{y}_{\bullet i}; g(\theta_i, L), \Sigma \right)$$
(13)

832 where $\mathcal{N}(x; \mu, \Sigma)$ is the probability density function of the multivariate normal distribution

833 and Σ is the unknown $v \times v$ spatial covariance matrix.

834 The stimulus or the reported motion direction in a particular trial of the test set can be

835 reconstructed by maximum-likelihood estimation (MLE), i.e. by simply maximizing the out-

836 of-sample likelihood function, given the in-sample parameter estimates $\hat{L}$ and $\hat{\Sigma}$:

838
$$\hat{\theta}_i = \underset{\theta \epsilon \Theta}{\text{argmax}} \, \text{LL}(\theta) = \underset{\theta \epsilon \Theta}{\text{argmax}} \, \log \mathcal{N}\left(\widehat{\mathrm{B}}_{\text{test}}^{(i)}; g(\theta, \hat{L}), \hat{\Sigma}\right) \qquad (14)$$

where $\widehat{\mathrm{B}}_{\text{test}}^{(i)}$ is the i-th row of $\widehat{\mathrm{B}}_{test}$, containing parameter estimates from the i-th test trial. To

efficiently determine $\hat{\theta}_i$, we perform a grid-based search, ranging θ from 1° to 360° in steps of

1° and evaluating $\text{LL}(\theta)$ at the corresponding values. This approach is similar to inverting a set

of forward encoding models (Thirion et al., 2006; Brouwer & Heeger, 2009; Naselaris et al.,

2011; Haynes, 2015; Sprague et al., 2018; Kriegeskorte & Diedrichsen, 2019).

Reconstruction performance evaluation: The outcome of the reconstruction is the matrix of

predicted directions $\hat{\theta}$

849
$$\hat{\theta} = \begin{bmatrix} \hat{\theta}_{11} & \cdots & \hat{\theta}_{s1} \\ \vdots & \ddots & \vdots \\ \hat{\theta}_{1t} & \cdots & \hat{\theta}_{st} \end{bmatrix}$$

where t is the number of trials and s is the number of searchlights.

Following our preregistration protocol, we evaluated the reconstruction performance in terms

of feature-continuous accuracy (FCA, eq. 2). For each searchlight and trial, we compared the

true (stimulus or report) direction θ_t and the predicted direction $\hat{\theta}_t$ in terms of absolute angular

deviation, rescaled into the range 0-100%, according to equations (1) and (2). We then

computed the averaged FCA across trials. This measure works well with balanced independent

variable distributions, such as that of the stimulus motion directions. However, in order to avoid

spurious above-chance reconstruction performance in case of an unbalanced distribution of the

dependent variable (i.e. during the reconstruction of participants' reports which are not equally

distribution across the directions, especially at lower coherence levels), we computed a

balanced version of FCA (BFCA):

862                    $$\text{BFCA} = \frac{1}{2\pi} \int_0^{2\pi} \text{FCA}(\theta, \hat{\theta}) \, d\theta \qquad (15)$$

where the integral is calculated using trapezoidal numerical integration across the sorted

directions of motion θ and reconstructions $\hat{\theta}$. Note that, in case of balanced labels, the use of

FCA or BFCA produce virtually identical results (See Appendix 2 for details).

Statistical analyses: ROIs

In order to evaluate how the stimulus and the report reconstruction performance were affected

by coherence in early visual cortex, MT+ and parietal areas, we evaluated the effect of

coherence level on the reconstruction performance for five bilateral ROIs (see *Localizer:*

Definition of ROIs). Parietal areas encode a variety of task-related variables (Bennur & Gold,

2011; Rigotti et al., 2013; Park et al., 2014; Brincat et al., 2018), including perceptual choices

in previous studies where decisions only had few alternative options (Liu & Pleskac, 2011;

Hebart et al., 2012, 2016). We expected an effect of coherence on report reconstruction in

visual areas and MT+ reflecting the increased correlation between stimulus and response for

higher coherence levels. To test these hypotheses, we first computed the average reconstruction

performance for each label (stimulus and report) in each ROI for each subject. We then

submitted the data to five independent repeated-measures ANOVAs (one for each ROI) with

coherence level and reconstructed label as repeated measure factors. The statistical tests for the

ROI analyses were performed with JASP (JASP Team, 2020).

Additional exploratory analyses: fMRI data

In order to deepen our understanding of the relationship between coherence level and

reconstruction performance, and to explore the similarity between the stimulus and report GPR

models, we further performed two exploratory analyses. The analyses were performed on an

ROI defined by the intersection of voxels with an average above-chance reconstruction

performance for both the stimulus and the report (thresholded at $p < 0.001$, uncorrected).

• *Interaction between coherence level and reconstructed labels.* We wanted to clarify

whether the coherence level affected the stimulus and the report reconstruction in

the voxels that code for both. For this, we computed the mean reconstruction

performance of the ROI for each coherence level and each reconstructed label.

Finally, we performed a repeated-measures ANOVA to test for an interaction effect

between coherence level and reconstructed label.

• *Model generalization.* To further explore the similarity between the encoding of

stimulus and report information in the brain, we performed a series of cross-

prediction analyses. The principle of this analyses is the same as in other examples

of cross-classification (Cichy et al., 2012; Kaplan et al., 2015; Levine &

Schwarzbach, 2017). It involves the use of the GPR estimated in one condition (e.g.

the report model estimated with the data acquired in the 0% coherence condition)

to predict the data of a different one (e.g. the stimulus directions at 100% coherence

condition). If the model generalizes, then there is evidence that the pattern of brain

activity is similar across the two conditions. For each subject we tested how well

the report model estimated in the 0% coherence condition (which is independent of

the physical stimulus) would allow to predict the stimulus identity in each

coherence level and vice versa (averaged). The procedure was similar to the one

described in *Main experiment: fMRI data analysis - Voxel-wise GPR estimation* and

Searchlight based stimulus and report reconstruction. However, we ran the analysis

on a limited number of voxels (see above). Since we were primarily interested in

the generalization of the report model estimated at 0% coherence to the stimulus

model estimated at 100% coherence (see Discussion), we tested whether the

generalization performance of this pair of conditions were above chance by

computing a one tailed t-test.

APPENDIX 1

Statistical analyses: searchlight-based reconstructions and effect of coherence

We also performed additional whole-brain searchlight decoding to identify regions potentially

outside our pre-defined ROIs that might encode stimulus-related or choice-related information.

For this, the single-subject BFCA maps resulting from the searchlight reconstructions were

smoothed using a Gaussian kernel with a FWHM of 6 mm and spatially normalized with

SPM12. In order to identify searchlights in which the reconstruction performance was

significantly above chance (i.e. BFCA > 50%), we used two one-way factorial designs (one for

stimulus and one for report) with coherence level as a within-subject factor. For each model,

we specified three t-contrasts. In this way we could identify clusters with significant above-

chance information for each coherence level. We expected the reconstruction performance of

searchlights located in visual areas, to decrease as a function of decreasing coherence. We also

expected to identify clusters of voxels carrying information about perceptual judgements in

visual (Britten et al., 1996; Serences & Boynton, 2007; Hebart et al., 2012; Sousa et al., 2021)

and parietal areas (Gold & Shadlen, 2007; Brincat et al., 2018; Hebart et al., 2012, 2016; Levine

& Schwarzbach, 2017). We further predicted the coherence level to have an effect on report

reconstruction performance as well. We evaluated the effect of coherence on the reconstruction

performance by inclusively masking the voxels that showed an average effect of reconstruction

across coherence levels ($p < 0.001$, uncorrected). This procedure was done separately for

stimulus reconstruction and report reconstruction. Please note that this analysis is not circular

because the test for an effect of coherence is orthogonal to the test for average reconstruction

performance.

The whole-brain searchlight reconstruction at 100% coherence revealed stimulus information

from voxel clusters located in the left (FWE$_c$, $p < 0.05$, $K = 1677$; cluster-defining threshold p

< 0.001) and in the right occipital cortex (FWE$_c$, $p < 0.05$, $K = 1024$; cluster-defining threshold

p<0.001). For the intermediate coherence condition and for the 0% coherence condition, we

found no searchlights that were significantly predictive of the stimulus motion direction. Note

that in the 0% coherence condition, the stimulus has no global motion direction, thus a chance-

level reconstruction performance is to be expected. In the left and right occipital cortex, we

also found clusters of voxels informative about participants' reports for the 100% coherence

condition (left: FWE$_c$, $p < 0.05$, $K = 1049$; cluster-defining threshold $p < 0.001$; right: FWE$_c$, p

< 0.05, $K = 864$; cluster-defining threshold $p < 0.001$) as well as for the intermediate coherence

condition (left: FWE$_c$, $p < 0.05$, $K = 201$; cluster-defining threshold p<0.001; right: FWE$_c$, $p <$

0.05, $K = 487$; cluster-defining threshold p<0.001). For the 0% coherence condition, we were

not able to identify clusters informative about participants' reports.

Appendix 1-Figure 1: Searchlight-based accuracy maps (plotted here for BFCA, see Methods). The images show
results of the searchlight-based stimulus and report reconstructions for three coherence levels (left: 0%; middle:
intermediate; right: 100%). The searchlights are mapped with different colors: red indicates significantly above-
chance reconstruction performance for stimulus, blue indicate above-chance reconstruction performance for
report, and purple indicate the overlap between the two. Please note that the maps are shown for display purposes
(for visualization thresholded at $p < 0.001$ and not corrected for multiple comparisons).

Since neurons in early and extrastriate visual areas are tuned to motion directions (Albright et

al. 1984; Movshon & Newsome, 1996; Nichols & Newsome, 2002), we reasoned that if

population-level measurements of neural activity obtained from single voxels reflects this

property (Nevado et al., 2004; Haynes, 2015; Sprague et al., 2018), the stimulus reconstruction

performance should be maximum in the 100% coherence condition, and progressively decrease

at intermediate coherence. At 0% coherence instead, the stimulus has no net motion direction

and the reconstruction performance should be at chance level. We therefore expected to

identify a main effect of coherence on the stimulus reconstruction performance in visual areas.

Appendix 1 – Figure 2: Effect of coherence on searchlight-based stimulus reconstruction performance. The
picture on top shows clusters of voxels where coherence has a significant effect on stimulus reconstruction
performance. The map is thresholded at $p < 0.001$, uncorrected for multiple comparisons. The plot on the bottom
displays the averaged above-chance accuracy (BFCA minus baseline of 50%) extracted from the searchlights in
which coherence had a significant effect on stimulus reconstruction performance, error bars are standard errors
(N=23).

We identified a cluster of voxels located in the left occipital pole, where coherence level had

an effect on the performance in stimulus reconstruction (FWE$_c$, $p < 0.05$, K = 262; cluster-

defining threshold p<0.001). Similarly, we predicted that a possible effect of coherence on the

report reconstruction might be present, and driven by the expected correlation between the

stimulus identity and participants' report, when the stimulus is clearly visible. However, we

did not find clusters that showed such effect for the report reconstruction performance.

Control analysis: stimulus and report reconstruction from eye-tracking data.

The use of motion stimuli such as our RDK might trigger involuntary eye movement (Cohen

et al., 1977) that can be informative about the direction of perceived motion (Wilbertz et al.,

2018). Eye movements also have an effect on brain activity measured with fMRI and can thus

constitute a potential confound (Merriam et al., 2013), even when participants are specifically

instructed to maintain fixation (Thielen et al., 2019). For this reason, we tested whether the

recorded gaze position (x and y ordinates), was informative about the physical stimulus

direction or participants' perceived direction. For this analysis we used the gaze position of 21

out of 23 subjects who participated in the main fMRI experiment (we couldn't record the traces

of two participants for technical reasons). We reasoned that if the gaze position is

systematically correlated with the presented motion direction or with participants' reports, the

x and y ordinates should exhibit a specific position profiles, that can in turn be used to perform

stimulus and report reconstruction. In order to check whether the pattern of participants' eye

movements was related with the stimulus or the reported motion directions, we estimated such

profiles with a cyclic version of the GPR (see *Main experiment: fMRI data analysis - Voxel-*

wise GPR estimation in the Materials and Methods section) and performed stimulus and report

reconstruction at each time point with a procedure similar to the one adopted for the main fMRI

analysis (see Materials and Methods: *Searchlight-based stimulus and report reconstruction*).

The preprocessing pipeline employed for this analysis was different from the one performed for fixation control (see *Main experiment: Selection of trials based on eye-tracking* in the Materials and Methods section). Blinks, detected by the provided software from Eye Link, were linearly interpolated using the approach described in Urai et al. (2017). The resulting traces were filtered for electronic noise using a Butterworth filter (low cut off 5Hz, high cut off 100Hz) following Thielen et al. (2018). The complete trace of each session was linearly detrended to account for drifts that appear due to the long continuous recordings during each session (each approximately 1.5h). An additional linear detrending was performed separately on each run, to counterbalance slow drifts in head position in the scanner. Periods of interest (500 ms before stimulus onset together with 2000 ms stimulus period) were combined across the two recording sessions. Data from the period of interest were baseline corrected using the pre-stimulus interval (500 ms up to stimulus onset).

After preprocessing, the x and y gaze positions of each subject were grouped by coherence levels (0%, medium, 100% coherence) resulting in a maximum of 160 trials per condition. To reduce computational time, we only considered time points during the stimulus period (2000 ms) and resampled the signal at 50Hz. For each time point we estimated two position-related profiles (one for each ordinate) by entering the trial-wise position value together with the corresponding stimulus motion direction θ_s or the reported direction θ_r into a cyclic version of the GPR. Please note that this procedure is very similar to the one previously described for the estimation of voxel-wise response profiles (see eq. 3 in the Materials and Methods section - where the parameter $\hat{\beta}_j$ represents now the trial-wise recorded position of each ordinate in a single time point). The estimation of the position profiles was performed with a leave-one-run-out cross-validation scheme, by only using trials in which participants were maintaining fixation (see *Main experiment: Selection of trials based on eye-tracking* in the Materials and Methods section).

The stimulus and report reconstructions were estimated using the same procedure described in

the section *Main experiment: fMRI data analysis - Searchlight based stimulus and report*

reconstruction in the Materials and Methods section. However, the estimated gaze position

profiles instead of voxel response profiles, were used to predict the stimulus direction θ_s or the

reported direction θ_r in a run-wise cross-validation procedure. Please note, that in this case it

is not necessary to adopt regularization for estimation of the covariance matrix because the

number of position profiles (one for x and one for y ordinates) does not exceed the number of

trials across runs (see eq. 9 in the Materials and Methods section). The results were evaluated

by testing if the averaged BFCA (see *Main experiment: fMRI data analysis - Reconstruction*

performance evaluation in the Materials and Methods section*)* across subjects was above

chance for each timepoint. Statistical analyses were corrected for multiple comparison by

performing a cluster-based permutation test (Maris & Oostenveld, 2017).

The group-level average reconstruction performance for the stimulus and the report labels are

depicted in Appendix 1- Figure3. We were not able to identify stimulus-related information in

any of the three coherence levels. Instead, the evaluation of the report model indicates that the

pattern of eye movements was informative about participants' report in the 0% coherence

condition. More precisely we were able to identify clusters of above-chance reconstruction

performance, peaking after 1000 ms. Eye movement were not predictive of participant's

choices for the intermediate or 100% coherence levels.

1049
Appendix 1 - Figure 3: Group average (N=21) accuracy (expressed as BFCA, see Methods) at each time point
relative to stimulus onset. The upper picture displays the stimulus reconstruction performance, the lower picture
shows the report reconstruction performance for three coherence levels (blue: 0%; red: intermediate; orange:
100%). Shading around the individual curves indicates ±1 SEM. The light blue lines on top of the curves depict
clusters of time points for which the reconstruction performance was greater than chance after correction for
multiple comparisons. Please note that GPR estimated from eye-movements are predictive of the reports for the
0% coherence condition but not of those given at intermediate and 100% coherence. Such result together with
those of our model consistency and model generalization analyses (Figure 8), suggest that eye movements were
unrelated with the brain signals used to reconstruct participants' choices in the 0% coherence condition (Figure
6).

1060

1061

1062 **APPENDIX 2**

1063

1064 *The need for BFCA*

1065

In order to evaluate the performance of our GPR-based reconstructions, we implemented a

balanced version of FCA (BFCA – see eq. 15 in the Materials and Methods section). Our goal

was to obtain a measure of performance that could be intuitively compared to a standard

accuracy measure with values distributed between 0% and 100%. FCA is derived by rescaling

the continuous values of the absolute angular deviation (see eq. 1 and 2 in the Materials and

Methods section); see also Pilly & Seitz, 2009), to evaluate the reconstruction performance.

The need for a *balanced* version of FCA was due to participants' responses in the 0% coherence

condition being unbalanced (Appendix 2 – Figure 1) as is often the case for reports, even

despite the use of our sensory matching approach that minimizes such biases (Töpfer et al.

2022). In case of a standard classification analysis, training and testing a classifier with

unbalanced labels make accuracy an unreliable measure of performance (Japkowicz &

Stephen, 2002). More specifically, when the performance of a classifier is tested on an

imbalanced dataset, it might lead to the misleading finding of significant above-chance

performance of the classifier (Brodersen et al., 2010), simply because the classifier tends to

reproduce the distribution of the training dataset.

1081

1082

Appendix 2 – Figure 1: The scatterplots display the trial-wise reported direction of 3 example participants against
the trial-wise motion direction, with the corresponding marginal distributions. A) Each plot on the top row shows
the data distribution obtained from 160 trials in the 100% coherence condition. B) The bottom row shows the data
distribution for the 0% coherence condition. Note that in this case the motion direction labels were generated
following the randomization scheme described in the manuscript (section *Stimuli: directions of motion* in the
Materials and Methods section), as no real motion direction was present in the stimulus.
1089

Comparing FCA and BFCA: simulation

In order to illustrate how BFCA and FCA are related with each other, as well as with the

underlying independent variable distribution, we here show a simulation performed on

synthetic data. In order to match the features of our experimental design, we simulated a $t \times 1$

vector of trial-wise parameter estimates $\hat{\beta}_j$ for a total of 1000 voxels where $t = 160$ total trials

were generated across 10 runs. We also generated a vector θ corresponding to the independent

variable (the stimulus or the report direction):

$$\hat{\beta}_j = \begin{bmatrix} \hat{\beta}_{j1} \\ \vdots \\ \hat{\beta}_{jt} \end{bmatrix} \quad \text{and} \quad \theta = \begin{bmatrix} \theta_1 \\ \vdots \\ \theta_t \end{bmatrix}.$$

For the current simulation we distinguished four alternative scenarios:

1)   **θ modulates $\widehat{\beta}_j$ and the distribution of θ is balanced**. This situation corresponds to the

hypothesized behavior of voxels sensitive to motion directions (as the stimulus directions

are balanced across runs in our experimental design);

2) **θ modulates $\widehat{\beta}_j$ and the distribution of θ is unbalanced**. This scenario corresponds to

the hypothesized behavior of voxels sensitive to participants' reports in our experimental

design (as participants' reports are unbalanced, especially at 0% coherence level);

3) **θ does not modulate $\widehat{\beta}_j$ and the distribution of θ is balanced**. This should be the case

for voxels insensitive to the stimulus direction. Such voxels should not produce spurious

above-chance FCA when combined for searchlight-based reconstruction;

4) **θ does not modulate $\widehat{\beta}_j$ and the distribution of θ is unbalanced**. We assume that this

scenario could possibly produce spurious above-chance FCA when the voxels are

combined for searchlight-based reconstruction.

We applied the same analyses described in the manuscript (see *Main experiment: fMRI data*

analysis in the Materials and Methods section) to estimate voxel-wise response profiles using

GPR and to perform the searchlight-based reconstruction using MLE. The simulated

searchlights consisted of 241 voxels. We finally evaluated the reconstruction performance by

using averaged FCA and BFCA.

1116

The results of the simulation are summarized in Appendix 2 – Figure 2. We obtained an above-

chance reconstruction performance for cases 1 (mean FCA: 92.31%, SD: 1.57; mean BFCA:

91.73%, SD: 1.9) and 2 (mean FCA: 92.72%, SD: 1.09; mean BFCA: 90.99%, SD: 1.91).

Interestingly, for case 3 the mean reconstruction performance is around chance for both

measures (mean FCA: 50.36% , SD: 2.61; mean BFCA: 49.21%, SD: 2.56) whereas for case 4

the distribution of FCA is skewed toward right (mean FCA: 56.23%, SD: 4.25) whereas BFCA

values are not (mean BFCA: 46.98%, SD: 6.06), as confirmed by two one-sample right tailed

 t-tests evaluating whether the mean values were greater than 50% (FCA > 50% : t = 46.278; p

 < 0.001; BFCA > 50%: t = -15.747; p = 1).

1126

1127

1128 **Appendix 2 - Figure 2:** Comparison of reconstruction performances obtained with simulated data. The picture
1129 illustrates the distribution of FCA (red) and BFCA (green) in the four scenarios examined in the simulation. 1.
1130 The relationship between FCA and BFCA for the condition in which θ modulates $\hat{\beta}_j$ and the distribution of θ is
1131 balanced. 2. Condition in which θ modulates $\hat{\beta}_j$ and the distribution of θ is unbalanced. 3. θ does not modulate
1132 $\hat{\beta}_j$ and the distribution of θ is balanced. 4. θ does not modulate $\hat{\beta}_j$ and the distribution of θ is unbalanced.
1133

1134

1135 *Comparing FCA and BFCA: real data*

1136

We computed the result the whole-brain searchlight analysis for all of the 23 subjects both with

FCA and BFCA as measures of reconstruction performance. The maps were obtained following

the procedure described in *Main experiment: FMRI data analysis* in the Materials and Methods

section. For the purpose of this analysis we only considered three main conditions:

1) **Stimulus labels at 100% coherence**. In this condition, the stimulus motion directions are

balanced, therefore the reconstruction performance should be above chance only for the

searchlights with voxels sensitive to motion directions. Because the distribution of the

stimulus directions is balanced, we expect no difference between the reconstruction

performance computed with FCA and BFCA.

2) **Stimulus labels at 0% coherence**. In this condition, the stimulus had no real motion

direction, but each trial was assigned a motion direction, generated according to our

randomization scheme (see section *Stimuli: directions of motion* in the Materials and

Methods section) This results in a balanced label distribution. Because of this, no

searchlight should result in above-chance reconstruction performance. Following the

outcome of the simulation described above, we expect no difference between the

reconstruction performance computed with FCA and BFCA.

3) **Report labels at 0% coherence**. Here, the labels assigned to each trial correspond to the

motion directions reported by participants. Therefore, the distribution of the reports across

trials reflects the idiosyncratic biases of each subject (see Appendix 2 – Figure 1 for an

example). In this condition, because some participants' choices lead to an unbalanced

distribution of reported motion directions, we suspect that FCA leads to spurious above-

chance reconstruction performance. Based on the outcome of the simulation, we

hypothesize a difference in the reconstruction performance computed with FCA and BFCA.

1162

Appendix 2 – Figure 3: The plots illustrate the difference between reconstruction performances obtained with two accuracy measures, FCA and BFCA. 1-3 show the relationship between FCA and BFCA for the 100% coherence stimulus reconstruction, for the 0% coherence stimulus reconstruction, and for the 0% coherence report reconstruction respectively. Results are plotted for each searchlight, averaged across subjects (N=23). The brain map on the bottom right is obtained from a 2nd level t-test evaluating searchlights where FCA was higher than BFCA in the 0% coherence report reconstruction (N=23). The map is thresholded at p<0.001, uncorrected for multiple comparisons.

We then used SPM12 to compare the FCA and the BFCA maps of the 23 participants. We

performed three second-level paired t-tests to evaluate our hypotheses.

The two measures (FCA and BFCA) were not significantly different when using the stimulus

labels at 100% coherence and 0% coherence (Appendix 2 - Figure 3). However, the FCA was

significantly different from BFCA when using the labels of the 0% reports in a large cluster

covering various portions of the brain (FWE$_c$, p < 0.05, K = 667990; cluster-defining voxel

threshold p < 0.001). The results remained consistent even when we lowered the cluster-

defining threshold to p < 0.0001 or p < 0.00001, with many significant clusters of smaller size

1181   scattered throughout the brain reaching significance level (FWE$_c$, $p < 0.05$, smallest K = 70;

1182   cluster-defining voxel threshold $p < 0.0001$; FWE$_c$, $p < 0.05$, smallest K = 20; cluster defining

1183   voxel threshold $p < 0.00001$).

1184

1185   **Acknowledgments**

1186

1187   Funded by the Excellence Initiative of the German Federal Ministry of Education (Excellence

1188   Cluster Science of Intelligence), the BMBF (through the Max Planck School of Cognition), the

1189   DFG (GRK 2386 "Extrospection"), and a joint grant by the John Templeton Foundation and

1190   the Fetzer Institute. We would like to thank Philipp Sterzer and Tobias Donner for their

1191   valuable input.

1192

REFERENCES

Albright, T. D. (1984). Direction and orientation selectivity of neurons in visual area MT of the macaque. *Journal of Neurophysiology*, *52*(6), 1106–1130. https://doi.org/10.1152/jn.1984.52.6.1106

Amunts, K., Malikovic, A., Mohlberg, H., Schormann, T., Zilles, K. (2000). Brodmann's Areas 17 and 18 Brought into Stereotaxic Space—Where and How Variable? *NeuroImage*, *11*(1), 66–84. https://doi.org/10.1006/nimg.1999.0516

Bae, G., & Luck, S. J. (2019). Decoding motion direction using the topography of sustained ERPs and alpha oscillations. *NeuroImage, 184*, 242–255. https://doi.org/10.1016/j.neuroimage.2018.09.029

Beck, J.M., Ma, W.J., Kiani, R., Hanks, T., Churchland, A.K., Roitman, J., Shadlen, M.N., Latham, P.E., Pouget, A. (2008). Probabilistic population codes for Bayesian decision making. *Neuron 60*(6). 1142-52. https://doi.org/10.1016/j.neuron.2008.09.021.

Bennur, S., & Gold, J. I. (2011). Distinct representations of a perceptual decision and the associated oculomotor plan in the monkey lateral intraparietal area. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *31*(3), 913–921. https://doi.org/10.1523/JNEUROSCI.4417-10.2011

Bode, S., Bogler, C., Haynes, J.-D. (2013). Similar neural mechanisms for perceptual guesses and free decisions. *NeuroImage*, *65*, 456–465. https://doi.org/10.1016/j.neuroimage.2012.09.064

Braddick, O.J. (1973). The masking of apparent motion in random-dot patterns. *Vision Research*, *13*(2), 355–369. https://doi.org/10.1016/0042-6989(73)90113-2

Braddick, O. J., O'Brien, J. M. D., Wattam-Bell, J., Atkinson, J., Hartley, T., & Turner, R. (2001). Brain Areas Sensitive to Coherent Visual Motion. *Perception*, *30*(1), 61–72. https://doi.org/10.1068/p3048

Brainard, D. H., (1997). The Psychophysics Toolbox. *Spatial Vision, 10*(4), 433–436. https://doi.org/10.1163/156856897X00357

Brincat, S. L., Siegel, M., von Nicolai, C., Miller, E. K. (2018). Gradual progression from sensory to task-related processing in cerebral cortex. *Proceedings of the National Academy of Sciences, 115*(30), E7202-E7211. https://doi.org/10.1073/pnas.1717075115

Britten, K. H., Newsome, W. T., Shadlen, M. N., Celebrini, S., Movshon, J. A. (1996). A relationship between behavioral choice and the visual responses of neurons in macaque MT. *Visual Neuroscience*, *13*(1), 87–100. https://doi.org/10.1017/S095252380000715X

Brodersen, K. H., Ong, C. S., Stephan, K. E., & Buhmann, J. M. (2010). The Balanced Accuracy and Its Posterior Distribution. *2010 20th International Conference on Pattern Recognition*, 3121–3124. https://doi.org/10.1109/ICPR.2010.764

1241

1242 Brouwer, G. J., & Heeger, D. J. (2009). Decoding and reconstructing color from responses in
1243 human visual cortex. *The Journal of Neuroscience, 29*(44), 13992–14003.
1244 https://doi.org/10.1523/JNEUROSCI.3577-09.2009

1245

1246 Brouwer, G. J., & van Ee, R. (2007). Visual cortex allows prediction of perceptual states during
1247 ambiguous structure-from-motion. *Journal of Neuroscience, 27*(5), 1015-1023.
1248 https://doi.org/10.1523/JNEUROSCI.4593-06.2007

1249

1250 Caspers, S., Geyer, S., Schleicher, A., Mohlberg, H., Amunts, K., Zilles, K. (2006). The human
1251 inferior parietal cortex: Cytoarchitectonic parcellation and interindividual variability.
1252 *NeuroImage*, *33*(2), 430–448. https://doi.org/10.1016/j.neuroimage.2006.06.054

1253

1254 Caywood, M.S., Roberts, D.M., Colombe, J.B., Greenwald, H.S. and Weiland, M.Z. (2017)
1255 Gaussian Process Regression for Predictive But Interpretable Machine Learning Models: An
1256 Example of Predicting Mental Workload across Tasks. *Frontiers in Human Neuroscience, 10,*
1257 647. https://doi.org/10.3389/fnhum.2016.00647

1258

1259 Cichy, R.M., Heinzle, J., Haynes, J.D. (2012). Imagery and Perception Share Cortical
1260 Representations of Content and Location, *Cerebral Cortex*, *22*(2), 372–
1261 380. https://doi.org/10.1093/cercor/bhr106

1262

1263 Chicharro, D., Panzeri, S., Haefner, R. M. (2021). Stimulus-dependent relationships between
1264 behavioral choice and sensory neural responses. *eLife, 10*, e54858.
1265 https://doi.org/10.7554/eLife.54858

1266

1267 Choi, H.-J., Zilles, K., Mohlberg, H., Schleicher, A., Fink, G. R., Armstrong, E., Amunts, K.
1268 (2006). Cytoarchitectonic identification and probabilistic mapping of two distinct areas within
1269 the anterior ventral bank of the human intraparietal sulcus. *The Journal of Comparative
1270 Neurology*, *495*(1), 53–69. https://doi.org/10.1002/cne.20849

1271

1272 Churchland, A. K., Kiani, R., Shadlen, M. N. (2008). Decision-making with multiple
1273 alternatives. *Nature Neuroscience*, *11*(6), 693-702. https://doi.org/10.1038/nn.2123

1274

1275 Cohen, B., Matsuo, V., Raphan, T.(1977). Quantitative analysis of the velocity characteristics
1276 of optokinetic nystagmus and optokinetic after-nystagmus. *The Journal of Physiology*, 270.
1277 https://doi.org/10.1113/jphysiol.1977.sp011955.

1278

1279 Christophel, T. B., Klink, P. C., Spitzer, B., Roelfsema, P. R., & Haynes, J. D. (2017). The
1280 Distributed Nature of Working Memory. *Trends in cognitive sciences*, *21*(2), 111–124.
1281 https://doi.org/10.1016/j.tics.2016.12.007

1282

Dimitrova, R., Pietsch, M., Christiaens, D., Ciarrusta, J., Wolfers, T., Batalle, D., Hughes, E.,
Hutter, J., Cordero-Grande, L., Price, A. N., Chew, A., Falconer, S., Vecchiato, K., Steinweg,
J. K., Carney, O., Rutherford, M. A., Tournier, J. D., Counsell, S. J., Marquand, A. F., Rueckert,
D., … O'Muircheartaigh, J. (2020). Heterogeneity in Brain Microstructural Development
Following Preterm Birth. *Cerebral cortex*, 30(9), 4800–4810.
https://doi.org/10.1093/cercor/bhaa069

1289

Downing, C. J., & Movshon, J. A. (1989). Spatial and temporal summation in the detection of motion in stochastic random dot displays. *Investigative Ophthalmology and Visual Science, 30*, 72.

Dumoulin, S. O., & Wandell, B. A. (2008). Population receptive field estimates in human visual cortex. *NeuroImage*, *39*(2), 647–660. 10.1016/j.neuroimage.2007.09.034

Eickhoff, S. B., Stephan, K. E., Mohlberg, H., Grefkes, C., Fink, G. R., Amunts, K., Zilles, K. (2005). A new SPM toolbox for combining probabilistic cytoarchitectonic maps and functional imaging data. *NeuroImage*, *25*(4), 1325–1335. https://doi.org/10.1016/j.neuroimage.2004.12.034

Filimon, F., Philiastides, M. G., Nelson, J. D., Kloosterman, N. A., Heekeren, H. R. (2013). How Embodied Is Perceptual Decision Making? Evidence for Separate Processing of Perceptual and Motor Decisions. *Journal of Neuroscience*, *33*(5), 2121–2136. https://doi.org/10.1523/JNEUROSCI.2334-12.2013

Forstmann, B. U., Ratcliff, R., Wagenmakers, E.J. (2016). Sequential Sampling Models in Cognitive Neuroscience: Advantages, Applications, and Extensions. *Annual Review of Psychology*, *67*, 641–666. https://doi.org/10.1146/annurev-psych-122414-033645

Freedman, D. J., & Assad, J. A. (2011). A proposed common neural mechanism for categorization and perceptual decisions. *Nature Neuroscience*, *14*(2), 143–146. https://doi.org/10.1038/nn.2740

Fusi, S., Miller, E. K., Rigotti, M. (2016). Why neurons mix: High dimensionality for higher cognition. *Current Opinion in Neurobiology*, *37*, 66–74. https://doi.org/10.1016/j.conb.2016.01.010

Gardner, J. L., & Liu, T. (2019). Inverted Encoding Models Reconstruct an Arbitrary Model Response, Not the Stimulus. *eNeuro*, *6*(2), ENEURO.0363-18.2019. https://doi.org/10.1523/ENEURO.0363-18.2019

Geisler, W. S. (1999). Motion streaks provide a spatial code for motion direction. *Nature*, *400*(6739), 65–69. https://doi.org/10.1038/21886

Glasser, M. F., Sotiropoulos, S. N., Wilson, J. A., Coalson, T. S., Fischl, B., Andersson, J. L., Xu, J., Jbabdi, S., Webster, M., Polimeni, J. R., Van Essen, D. C., Jenkinson, M., WU-Minn HCP Consortium. (2013). The minimal preprocessing pipelines for the Human Connectome Project. *NeuroImage*, *80*, 105–124. https://doi.org/10.1016/j.neuroimage.2013.04.127

Gold, J. I., & Shadlen, M. N. (2007). The Neural Basis of Decision Making. *Annual Review of Neuroscience*, *30*(1), 535–574. https://doi.org/10.1146/annurev.neuro.29.051605.113038

Grind, W. A. van de, Doorn, A. J. van, Koenderink, J. J. (1983). Detection of coherent movement in peripherally viewed random-dot patterns. *Journal of the Optical Society of America*, *73*(12), 1674–1683. https://doi.org/10.1364/JOSA.73.001674

Hanks, T. D., & Summerfield, C. (2017). Perceptual Decision Making in Rodents, Monkeys, and Humans. *Neuron*, *93*(1), 15–31. https://doi.org/10.1016/j.neuron.2016.12.003

Haynes, J.D. (2015). A Primer on Pattern-Based Approaches to fMRI: Principles, Pitfalls, and Perspectives. *Neuron*, *87*(2), 257–270. https://doi.org/10.1016/j.neuron.2015.05.025

Hebart, M. N., Donner, T. H., Haynes, J.D. (2012). Human visual and parietal cortex encode visual choices independent of motor plans. *NeuroImage*, *63*(3), 1393–1403. https://doi.org/10.1016/j.neuroimage.2012.08.027

Hebart, M. N., Schriever, Y., Donner, T. H., Haynes, J.D. (2016). The Relationship between Perceptual Decision Variables and Confidence in the Human Brain. *Cerebral Cortex*, *26*(1), 118–130. https://doi.org/10.1093/cercor/bhu181

Heekeren, H. R., Marrett, S., Bandettini, P. A., Ungerleider, L. G. (2004). A general mechanism for perceptual decision-making in the human brain. *Nature*, *431*(7010), 859–862. https://doi.org/10.1038/nature02966

Heekeren, H. R., Marrett, S., Ruff, D. A., Bandettini, P. A., Ungerleider, L. G. (2006). Involvement of human left dorsolateral prefrontal cortex in perceptual decision making is independent of response modality. *Proceedings of the National Academy of Sciences*, *103*(26), 10023–10028. https://doi.org/10.1073/pnas.0603949103

Heekeren, H. R., Marrett, S., Ungerleider, L.G. (2008). The neural systems that mediate human perceptual decision making. *Nature Reviews Neuroscience,* 9, 467–479. https://doi.org/10.1038/nrn2374

Ho, T. C., Brown, S., Serences, J. T. (2009). Domain General Mechanisms of Perceptual Decision Making in Human Cortex. *The Journal of Neuroscience*, *29*(27), 8675–8687. https://doi.org/10.1523/JNEUROSCI.5984-08.2009

Huk, A. C., & Meister, M. L. (2012). Neural correlates and neural computations in posterior parietal cortex during perceptual decision-making. *Frontiers in integrative neuroscience*, *6*, 86. https://doi.org/10.3389/fnint.2012.00086

Hummel, N., Cuturi, L. F., MacNeilage, P. R., Flanagin, V. L. (2016a). The effect of supine body position on human heading perception. *Journal of Vision*, *16*(3), 19. https://doi.org/10.1167/16.3.19

Japkowicz, N., & Stephen, S. (2002). The class imbalance problem: A systematic study. *Intelligent Data Analysis*, *6*(5), 429–449. http://dx.doi.org/10.3233/IDA-2002-6504

Kamitani, Y., & Tong, F. (2006). Decoding seen and attended motion directions from activity in the human visual cortex. *Current biology,* *16*(11), 1096-1102. https://doi.org/10.1016/j.cub.2006.04.003

Kaplan, J. T., Man, K., Greening, S. G. (2015). Multivariate cross-classification: applying machine learning techniques to characterize abstraction in neural representations. *Frontiers in Human Neuroscience. 9*, 151. https://doi.org/10.3389/fnhum.2015.00151

Kay, K. N., Naselaris, T., Prenger, R. J., Gallant, J. L. (2008). Identifying natural images from human brain activity. *Nature*, *452*(7185), 352–355. https://doi.org/10.1038/nature06713

Kleiner, M., Brainard, D., Pelli, D. (2007). What's new in Psychtoolbox-3?. Perception 36 ECVP Abstract Supplement.

Kriegeskorte, N., Cusack, R., & Bandettini, P. (2010). How does an fMRI voxel sample the neuronal activity pattern: compact-kernel or complex spatiotemporal filter?. *NeuroImage*, *49*(3), 1965–1976. https://doi.org/10.1016/j.neuroimage.2009.09.059

Kriegeskorte, N., & Diedrichsen, J. (2019). Peeling the Onion of Brain Representations. *Annual Review of Neuroscience*, *42*(1), 407–432. https://doi.org/10.1146/annurev-neuro-080317-061906

Kriegeskorte, N., Goebel, R., Bandettini, P. (2006). Information-based functional brain mapping. *Proceedings of the National Academy of Sciences*, *103*(10), 3863–3868. https://doi.org/10.1073/pnas.0600244103

Krishna, A., Tanabe, S., Kohn, A. (2021). Decision signals in the local field potentials of early and mid-level macaque visual cortex. *Cerebral Cortex, 31*(1), 169-183. https://doi.org/10.1093/cercor/bhaa218

Kujovic, M., Zilles, K., Malikovic, A., Schleicher, A., Mohlberg, H., Rottschy, C., Eickhoff, S. B., Amunts, K. (2013). Cytoarchitectonic mapping of the human dorsal extrastriate cortex. *Brain Structure and Function*, *218*(1), 157–172. https://doi.org/10.1007/s00429-012-0390-9

Levine, S. M., & Schwarzbach, J. (2017). Decoding of auditory and tactile perceptual decisions in parietal cortex. *NeuroImage*, *162*, 297–305. https://doi.org/10.1016/j.neuroimage.2017.08.060

Levinson, E., & Sekuler, R. (1976). Adaptation alters perceived direction of motion. *Vision Research, 16*(7), 779-IN7. https://doi.org/10.1016/0042-6989(76)90189-9

Liu, T., & Pleskac, T. J. (2011). Neural correlates of evidence accumulation in a perceptual decision task. *Journal of Neurophysiology*, *106*(5), 2383–2398. https://doi.org/10.1152/jn.00413.2011

Maris, E., Oostenveld, R. (2007). Nonparametric statistical testing of EEG and MEG-data. *Journal of Neuroscience Methods*, *164*(1), 177–190. https://doi.org/10.1016/j.jneumeth.2007.03.024

Merriam, E.P. , Gardner, J.L., Movshon, J.A., Heeger, D.J. (2013). Modulation of visual responses by gaze direction in human visual cortex. *The Journal of Neuroscience*, 33(24), 9879–9889. https://doi.org/10.1523/JNEUROSCI.0500-12.2013

Movshon, J. A., & Newsome, W. T. (1996). Visual response properties of striate cortical neurons projecting to area MT in macaque monkeys. *Journal of Neuroscience*, *16*(23), 7733-7741. https://doi.org/10.1523/JNEUROSCI.16-23-07733.1996

Mulder M.J., van Maanen L., Forstmann B.U. (2014). Perceptual decision neurosciences—a model-based review. *Neuroscience*. 2014; 277:872–84. https://doi.org/10.1016/j.neuroscience.2014.07.031

1440

1441 Naselaris T., Kay K.N., Nishimoto S., Gallant J.L. (2011). Encoding and decoding in fMRI.
1442 *NeuroImage*, *56*, 400-410. https://doi.org/10.1016/j.neuroimage.2010.07.073

1443

1444 Nevado, A., Young, M. P., Panzeri, S. (2004). Functional imaging and neural information
1445 coding. *NeuroImage, 21*(3), 1083-1095. https://doi.org/10.1016/j.neuroimage.2003.10.043

1446

1447 Newsome, W. T., & Paré, E. B. (1988). A selective impairment of motion perception following
1448 lesions of the middle temporal visual area (MT). *The Journal of Neuroscience*, *8*(6), 2201–
1449 2211. https://doi.org/10.1523/jneurosci.08-06-02201.1988

1450

1451 Nichols, M. J., & Newsome, W. T. (2002). Middle temporal visual area microstimulation
1452 influences veridical judgments of motion direction. *The Journal of Neuroscience*, *22*(21),
1453 9530–9540. https://doi.org/10.1523/JNEUROSCI.22-21-09530.2002

1454

1455 Park, I., Meister, M., Huk, A., Pillow, J.W. (2014). Encoding and decoding in parietal cortex
1456 during sensorimotor decision-making. *Nature Neuroscience 17*, 1395–1403.
1457 https://doi.org/10.1038/nn.3800

1458

1459 Pilly, P. K., & Seitz, A. R. (2009). What a difference a parameter makes: A psychophysical
1460 comparison of random dot motion algorithms. *Vision Research*, *49*(13), 1599–1612.
1461 https://doi.org/10.1016/j.visres.2009.03.019

1462

1463 Pratte, M.S., and Tong, F. (2014). Spatial specificity of working memory representations in the
1464 early visual cortex. *Journal of Vision*. *14*, 22. http://dx.doi.org/10.1167/14.3.22

1465

1466 Prinzmetal, W., Amiri, H., Allen, K., Edwards, T. (1998). Phenomenology of attention: I.
1467 Color, location, orientation, and spatial frequency. *Journal of Experimental Psychology:*
1468 *Human Perception and Performance, 24*(1), 261. https://doi.org/10.1037/0096-1523.24.1.261

1469

1470 Ramírez, F. M., Cichy, R. M., Allefeld, C., & Haynes, J. D. (2014). The neural code for face
1471 orientation in the human fusiform face area. *The Journal of Neuroscience*, *34*(36), 12155–
1472 12167. https://doi.org/10.1523/JNEUROSCI.3156-13.2014

1473

1474 Rasmussen, C. E., & Nickisch, H. (2010). Gaussian processes for machine learning (GPML)
1475 toolbox. *The Journal of Machine Learning Research*, *11*, 3011-3015.

1476

1477 Rasmussen, C. E., & Williams, C. K. I. (2005). *Gaussian processes for machine learning*. MIT
1478 Press. https://doi.org/10.7551/mitpress/3206.001.0001

1479

1480 Ratcliff R. (2018). Decision making on spatially continuous scales. *Psychological*
1481 *review*, *125*(6), 888–935. https://doi.org/10.1037/rev0000117

1482

1483 Rees, G., Friston, K., Koch, C. (2000). A direct quantitative realtionship between the functional
1484 properties of human and macaque V5. *Nature Neuroscience*, *3*, 716-723.
1485 https://doi.org/10.1038/76673

1486

1487 Ress, D., Heeger, D.J. (2003). Neuronal correlates of perception in early visual cortex. *Nature*
1488 *Neuroscience, 6*(4), 414-20. https://doi.org/10.1038/nn1024

1489

Riggall, A. C., & Postle, B. R. (2012). The relationship between working memory storage and elevated activity as measured with functional magnetic resonance imaging. *The Journal of Neuroscience, 32*(38), 12990–12998. https://doi.org/10.1523/JNEUROSCI.1892-12.2012

Rigotti, M., Barak, O., Warden, M. R., Wang, X.-J., Daw, N. D., Miller, E. K., Fusi, S. (2013). The importance of mixed selectivity in complex cognitive tasks. *Nature*, *497*(7451), 585–590. https://doi.org/10.1038/nature12160

Rissman, J., Gazzaley, A., D'Esposito, M. (2004). Measuring functional connectivity during distinct stages of a cognitive task. *Neuroimage*, *23*(2), 752-763. https://doi.org/10.1016/j.neuroimage.2004.06.035

Rottschy, C., Eickhoff, S. B., Schleicher, A., Mohlberg, H., Kujovic, M., Zilles, K., Amunts, K. (2007). Ventral visual cortex in humans: Cytoarchitectonic mapping of two extrastriate areas. *Human Brain Mapping*, *28*(10), 1045–1059. https://doi.org/10.1002/hbm.20348

Scheperjans, F., Eickhoff, S. B., Hömke, L., Mohlberg, H., Hermann, K., Amunts, K., Zilles, K. (2008). Probabilistic Maps, Morphometry, and Variability of Cytoarchitectonic Areas in the Human Superior Parietal Cortex. *Cerebral Cortex*, *18*(9), 2141–2157. https://doi.org/10.1093/cercor/bhm241

Serences, J. T., & Boynton, G. M. (2007). The Representation of Behavioral Choice for Motion in Human Visual Cortex. *Journal of Neuroscience*, *27*(47), 12893–12899. https://doi.org/10.1523/JNEUROSCI.4021-07.2007

Serences, J. T., Ester, E. F., Vogel, E. K., & Awh, E. (2009). Stimulus-specific delay activity in human primary visual cortex. *Psychological science*, *20*(2), 207–214. https://doi.org/10.1111/j.1467-9280.2009.02276.x

Shadlen M.N., Britten K.H., Newsome W.T., Movshon J.A. (1996). A computational analysis of the relationship between neuronal and behavioral responses to visual motion. *Journal of Neuroscience, 16*, 1486–510. https://doi.org/10.1523/JNEUROSCI.16-04-01486.1996

Shadlen, M. N., Kiani, R., Hanks, T. D., Churchland, A. K. (2008). Neurobiology of decision making: An intentional framework. In C. Engel & W. Singer (Eds.), Better than conscious? Decision making, the human mind, and implications for institutions (pp. 71–101). MIT Press. https://doi.org/10.7551/mitpress/9780262195805.003.0004

Siegel, M., Engel, A. K., Donner, T. H. (2011). Cortical network dynamics of perceptual decision-making in the human brain. *Frontiers in Human Neuroscience, 5*, 21. https://doi.org/10.3389/fnhum.2011.00021

Smith, P. L. (2016). Diffusion theory of decision making in continuous report. *Psychological Review, 123*(4), 425–451. https://doi.org/10.1037/rev0000023

Sousa, T., Duarte, J.V., Costa, G.N., Kemper, V.G., Martins, R., Goebel, R., Castelo-Branco, M. (2021). The dual nature of the BOLD signal: Responses in visual area hMT+ reflect both input properties and perceptual decision. *Human Brain Mapping*. *42*, 1920– 1929. https://doi.org/10.1002/hbm.25339

Sprague, T. C., Adam, K., Foster, J. J., Rahmati, M., Sutterer, D. W., & Vo, V. A. (2018). Inverted Encoding Models Assay Population-Level Stimulus Representations, Not Single-Unit Neural Tuning. *eNeuro*, *5*(3), ENEURO.0098-18.2018. https://doi.org/10.1523/ENEURO.0098-18.2018

Sprague, T. C., Boynton, G. M., & Serences, J. T. (2019). The Importance of Considering Model Choices When Interpreting Results in Computational Neuroimaging. *eNeuro*, *6*(6), ENEURO.0196-19.2019. https://doi.org/10.1523/ENEURO.0196-19.2019

Thaler, L., Schütz, A. C., Goodale, M. A., Gegenfurtner, K. R. (2013). What is the best fixation target? The effect of target shape on stability of fixational eye movements. *Vision Research*, *76*, 31–42. https://doi.org/10.1016/j.visres.2012.10.012

Thielen, J., Bosch, S.E., van Leeuwen, T.M., van Gerven, M.A.J., van Lier, R. (2019). Evidence for confounding eye movements under attempted fixation and active viewing in cognitive neuroscience. *Scientific Reports, 9*, 17456. https://doi.org/10.1038/s41598-019-54018-z

Thielen, J., van Lier, R., & van Gerven, M. (2018). No evidence for confounding orientation-dependent fixational eye movements under baseline conditions. *Scientific Reports*, *8*(1), 1-10. https://doi.org/10.1038/s41598-018-30221-2

Thirion, B., Duchesnay, E., Hubbard, E., Dubois, J., Poline, J.-B., Lebihan, D., Dehaene, S. (2006). Inverse retinotopy: inferring the visual content of images from brain activation patterns. *NeuroImage*, *33*(4), 1104–1116. https://doi.org/10.1016/j.neuroimage.2006.06.062

Töpfer, F. M., Barbieri, R., Sexton, C. M., Wang, X., Soch, J., Bogler, C., & Haynes, J. D. (2022). Psychophysics and computational modeling of feature-continuous motion perception. *Journal of Vision*, *22*(11), 16. https://doi.org/10.1167/jov.22.11.16

Tosoni, A., Corbetta, M., Calluso, C., Committeri, G., Pezzulo, G., Romani, G. L., Galati, G. (2014). Decision and action planning signals in human posterior parietal cortex during delayed perceptual choices. *European Journal of Neuroscience*, *39*(8), 1370–1383. https://doi.org/10.1111/ejn.12511

Tosoni, A., Galati, G., Romani, G. L., Corbetta, M. (2008). Sensory-motor mechanisms in human parietal cortex underlie arbitrary visual decisions. *Nature Neuroscience*, *11*(12), 1446–1453. https://doi.org/10.1038/nn.2221

Uchida, N., Kepecs, A., Mainen, Z. (2006). Seeing at a glance, smelling in a whiff: rapid forms of perceptual decision making. *Nature Reviews Neuroscience, 7*, 485–491. https://doi.org/10.1038/nrn1933

Urai, A., Braun, A., Donner, T. (2017). Pupil-linked arousal is driven by decision uncertainty and alters serial choice bias. *Nature Communications 8*, 14637. https://doi.org/10.1038/ncomms14637

van Bergen, R. S., Ma, W. J., Pratte, M. S., Jehee, J. F. (2015). Sensory uncertainty decoded from visual cortex predicts behavior. *Nature Neuroscience, 18*(12), 1728-1730. https://doi.org/10.1038/nn.4150

1590
1591 Wang, H. X., Merriam, E. P., Freeman, J., & Heeger, D. J. (2014). Motion direction biases and
1592 decoding in human visual cortex. *The Journal of Neuroscience*, *34*(37), 12601–12615.
1593 https://doi.org/10.1523/JNEUROSCI.1034-14.2014
1594
1595 Watson, A. B., & Pelli, D. G. (1983). QUEST: A Bayesian adaptive psychometric method.
1596 Perception & psychophysics, 33(2), 113-120. https://doi.org/10.3758/BF03202828
1597
1598 Wilbertz, G., Ketkar, M., Guggenmos, M., Sterzer, P. (2018). Combined fMRI-and eye
1599 movement-based decoding of bistable plaid motion perception. *Neuroimage*, *171*, 190–198.
1600 https://doi.org/10.1016/j.neuroimage.2017.12.094
1601
1602 Wilming, N., Murphy, P.R., Meyniel, F., Donner, T.H. (2020). Large-scale dynamics of
1603 perceptual decision information across human cortex. *Nature Communications* 11, 5109.
1604 https://doi.org/10.1038/s41467-020-18826-6
1605
1606 Zhang, W., & Luck, S. J. (2008). Discrete fixed-resolution representations in visual working
1607 memory. *Nature, 453*(7192), 233–235. https://doi.org/10.1038/nature06860
1608