1   Conflicts are parametrically encoded: initial evidence for a cognitive space view to
2   reconcile the debate of domain-general and domain-specific cognitive control
3

4   Guochun Yang,[1,2,3,4] Haiyan Wu,[5] Qi Li,[6] Xun Liu,[1,2*] Zhongzheng Fu,[7,8] Jiefeng
5   Jiang[3,4]
[1] CAS Key Laboratory of Behavioral Science, Institute of Psychology, Beijing
100101, China.
[2] Department of Psychology, University of Chinese Academy of Sciences, Beijing
100101, China.
[3] Department of Psychological and Brain Sciences, University of Iowa, Iowa City, IA
52242, USA.
[4] Cognitive Control Collaborative, University of Iowa, Iowa City, IA 52242, USA.
[5] Centre for Cognitive and Brain Sciences and Department of Psychology, University
of Macau, Taipa, Macau 999078, China.
[6] Beijing Key Laboratory of Learning and Cognition, School of Psychology, Capital
Normal University, Beijing 100048, China.
[7] Department of Neurosurgery, Cedars-Sinai Medical Center, Los Angeles, CA
90048, USA.
[8] Division of Humanities and Social Sciences, California Institute of Technology,
Pasadena, CA 91125, USA.
*Correspondence: liux@psych.ac.cn

Abstract
Cognitive control resolves conflicts between task-relevant and -irrelevant information
to enable goal-directed behavior. As conflicts can arise from different sources (e.g.,
sensory input, internal representations), how a limited set of cognitive control
processes can effectively address diverse conflicts remains a major challenge. Based
on the cognitive space theory, different conflicts can be parameterized and
represented as distinct points in a (low-dimensional) cognitive space, which can then
be resolved by a limited set of cognitive control processes working along the
dimensions. It leads to a hypothesis that conflicts similar in their sources are also
represented similarly in the cognitive space. We designed a task with five types of
conflicts that could be conceptually parameterized. Both human performance and
fMRI activity patterns in the right dorsolateral prefrontal (dlPFC) support that
different types of conflicts are organized based on their similarity, thus suggesting
cognitive space as a principle for representing conflicts.
36
37 Keywords: cognitive control, cognitive space, domain-general, domain-specific,
38 conflict
39

Introduction

Cognitive control enables humans to behave purposefully by modulating neural
processing to resolve conflicts between task-relevant and task-irrelevant information.
For example, when naming the color of the word "BLUE" printed in red ink, we are
likely to be distracted by the word meaning, because reading a word is highly
automatic in daily life. To keep our attention on the color, we need to mobilize the
cognitive control processes to resolve the conflict between the color and word by
boosting/suppressing the processing of color/word meaning. As task-relevant and
task-irrelevant information can come from different sources, the sources of conflicts
and how they should be resolved can vary greatly (Kornblum et al., 1990). For
example, the conflict may occur between items of sensory information, such as
between a red light and a police officer signaling cars to pass. Alternatively, conflict
may occur between sensory and motor information, such as when a voice on the left
asks you to turn right. A key unsolved question in cognitive control is how our brain
efficiently resolves these different types of conflicts.
A first step to addressing this question is to examine the commonalities and/or
dissociations across different types of conflicts that can be categorized into different
domains. Examples of the domains of conflicts include experimental paradigm
(Freitas et al., 2007; Magen & Cohen, 2007), sensory modality (Hazeltine et al., 2011;
Yang et al., 2017), or conflict type regarding the dimensional overlap of conflict
processes (Jiang & Egner, 2014; Liu et al., 2004).
Two solutions to resolving different conflict types are proposed. They differ
based on whether the same cognitive control mechanisms are applied across domains.
On the one hand, the *domain-general* cognitive control theories posit that the

frontoparietal cortex adaptively encodes task information and can thus flexibly
implement control strategies for different types of conflicts. This is supported by the
generalizable control adjustment (i.e., encountering a conflict trial from one type can
facilitate conflict resolution of another type) (Freitas et al., 2007; Kan et al., 2013) and
similar neural patterns (Peterson et al., 2002; Wu et al., 2020) across distinct conflict
tasks. A broader domain-general view holds that the frontoparietal brain
regions/networks are widely involved in multiple control demands well beyond the
conflict domain (Assem et al., 2020; Cole et al., 2013), which explains the remarkable
flexibility in human behaviors. However, since domain-general processes are by
definition likely shared by different tasks, when we need to handle multiple task
demands at the same time, the efficiency of both tasks would be impaired due to
resource competition or interference (Musslick & Cohen, 2021). Therefore, the
domain-general processes is evolutionarily less advantageous for humans to deal with
the diverse situations requiring high efficiency (Cosmides & Tooby, 1994). On the
other hand, the *domain-specific* theories argue that different types of conflicts are
handled by distinct cognitive control processes (e.g., where and how information
processing should be modulated)(Egner, 2008; Kim et al., 2012). However, according
to the domain-specific view, the diverse conflict situations require a multitude of
preexisting control processes, which is biologically implausible (Abrahamse et al.,
2016).
To reconcile the two theories, researchers recently proposed that cognitive control
might be a mixture of domain-general and domain-specific processes. For instance,
Freitas and Clark (2015) found that trial-by-trial adjustment of control can generalize
across two conflict domains to different degrees, leading to domain-general (strong
generalization) or domain-specific (weak or no generalization) conclusions depending
on the task settings of the consecutive conflicts. Similarly, different brain networks
may show domain-generality (i.e., representing multiple conflicts) or domain-
specificity (i.e., representing individual conflicts separately)(Jiang & Egner, 2014; Li
et al., 2017). Even within the same brain area (e.g., medial frontal cortex), Fu et
al.(2022) found that the neural population activity can be factorized into orthogonal
dimensions encoding both domain-general and domain-specific conflict information,
which can be selectively read out by downstream brain regions. While the mixture
view provides an explanation for the contradictory findings (Braem et al., 2014), it
suffers the same criticism as domain-specific cognitive control theories, as it still
requires many cognitive control processes to fully cover all possible conflicts.
A key to reconciling domain-general and domain-specific cognitive control is to
organize the large number of conflict types using a system with limited, dissociable
dimensions. A construct with a similar function is the *cognitive space* (Bellmund et
al., 2018), which extends the idea of cognitive map (Behrens et al., 2018) to the
representation of abstract information. Critically, the cognitive space view holds that
the representations of different abstract information are organized continuously and
the representational geometry in the cognitive space is determined by the similarity
among the represented information (Bellmund et al., 2018).

In the human brain, it has been shown that abstract (Behrens et al., 2018; Schuck
et al., 2016) and social (Park et al., 2020) information can be represented in a
cognitive space. For example, social hierarchies with two independent scores (e.g.,
popularity and competence) can be represented in a 2D cognitive space (one
dimension for each score), such that each social item can be located by its score in the
two dimensions (Park et al., 2020). In the field of cognitive control, recent studies
have begun to conceptualize different control states within a cognitive space (Badre et
al., 2021). For example, Fu et al.(2022) mapped different conflict conditions to
locations in a low/high dimensional cognitive space to demonstrate the domain-
general/domain-specific problems; Grahek et al. (2023) used a cognitive space model
of cognitive control settings to explain behavioral changes in the speed-accuracy
tradeoff. However, the cognitive spaces proposed in these studies were only
applicable to a limited number of control states involved in their designs. Therefore, it
remains unclear whether there is a cognitive space that can explain the large number
of control states, similar to that of the spatial location (Bellmund et al., 2018) and
non-spatial knowledge (Behrens et al., 2018). A challenge to answering this question
lies in how to construct control states with continuous levels of similarity. Our recent
work (Yang et al., 2021) showed that it is possible to manipulate continuous conflict
similarity by using a mixture of two independent conflict types with varying ratios,
which can be used to further examine the behavioral and neural evidence for the
cognitive space view. It is also unclear how the cognitive space of cognitive control is
encoded in the brain, although that of spatial locations and non-spatial abstract
knowledge has been relatively well investigated in the medial temporal lobe, medial
prefrontal and orbitofrontal system (Behrens et al., 2018; Bellmund et al., 2018).
Recent research has suggested that the abstract task structure could be encoded and
implemented by the frontoparietal network (Vaidya & Badre, 2022; Vaidya et al.,
2021), but whether a similar neural system encodes the cognitive space of cognitive
control remains untested.
The present study aimed to test the geometry of cognitive space in conflict
representation. Specifically, we hypothesize that different types of conflicts are
represented as points in a cognitive space. Importantly, the distance between the
points, which reflects the geometry of the cognitive space, scales with the difference
in the sources of the conflicts being represented by the points. The dimensions in the
cognitive space of conflicts can be the aforementioned *domains*, in which domain-
specific cognitive control processes are defined. For a specific type of conflict, its
location in the cognitive space can be parameterized using a limited number of
coordinates, which reflect how much control is needed for each of the domain-
specific cognitive control processes. The cognitive space can also represent different
types of conflicts with low dimensionality (Badre et al., 2021; MacDowell et al.,
2022). Different domains can be represented conjunctively in a single cognitive space
to achieve domain-general cognitive control, as conflicts from different sources can
be resolved using the same set of cognitive control processes. We further hypothesize
that the cognitive space representing different types of conflicts may be located in the

frontoparietal network due to its essential roles in conflict resolution (Freund, Bugg,
et al., 2021; Fu et al., 2022) and abstract task representation (Vaidya & Badre, 2022).

Fig. 1. Experimental design. (A) The left panel shows the orthogonal stimulus-response mappings of
the two participant groups. In each group the stimuli were only displayed at two quadrants of the
circular locations. One group were asked to respond with the left button to the upward arrow and with
the right button to the downward arrow presented in the top-left and bottom-right quadrants, and the
other group vice versa. The right panel shows the time course of one example trial. The stimuli were
displayed for 600 ms, preceded and followed by fixation crosses that lasted for 1400 ms in total. (B)
Examples of the five types of conflicts, each containing congruent and incongruent conditions. The
arrows were presented at locations along five orientations with isometric polar angles, in which the
vertical location introduces the spatial Stroop conflict, and the horizontal location introduces the Simon
conflict. Dashed lines are shown only to indicate the location of arrows and were not shown in the
experiments. (C) The definition of the angular difference between two conflict types and the conflict
similarity. The angle θ is determined by the acute angle between two lines that cross the stimuli and the
central fixation. Therefore, stimuli of the same conflict type form the smallest angle of 0, and stimuli
between Stroop and Simon form the largest angle of 90°, and others are in between. Conflict similarity
is defined by the cosine value of θ. H = high; L = low; M = medium.

In this study, we adjusted the paradigm from our previous study (Yang et al.,
2021) by including transitions of trials from five different conflict types, which
enabled us to test if these conflict types are organized in a cognitive space (Fig. 1A).
Specifically, on each trial, an arrow, pointing either upwards or downwards, was

presented on one of the 10 possible locations on the screen. Participants were required
to respond to the pointing direction of the arrow (up or down) by pressing either the
left or right key. Importantly, conflicts from two sources can occur in this task. On
one hand, the vertical location of the arrow can be incongruent with the direction
(e.g., an up-pointing arrow on the lower half of the screen), resulting spatial Stroop
conflict (Liu et al., 2004; Lu & Proctor, 1995). On the other hand, the horizontal
location of the arrow can be incongruent with the response key (e.g., an arrow
requiring left response presented on the right side of the screen), thus causing Simon
conflict (Lu & Proctor, 1995; Simon & Small, 1969). As the arrow location rotates
from the horizontal axis to the vertical axis, spatial Stroop conflict increases, and
Simon conflict decreases. Therefore, the 10 possible locations of the arrow give rise
to five conflict types with unique blend of spatial Stroop and Simon conflicts (Yang et
al., 2021). As the increase in spatial Stroop conflict is highly correlated with the
decrease in Simon conflict, we can use a 1D cognitive space to represent all five
conflict types.
One way to parameterize (i.e., defining a coordinate system) the cognitive space
is to encode each conflict type by the angle of the axis connecting its two possible
stimulus locations (Fig. 1B). Within this cognitive space, the similarity between two
conflict types can be quantified as the cosine value of their angular difference (Fig.
1C). The rationale behind defining conflict similarity based on combinations of
different conflict sources, such as spatial-Stroop and Simon, stems from the evidence
that these sources undergo independent processing (Egner, 2008; Li et al., 2014; Liu
et al., 2010; Wang et al., 2014). Identifying these distinct sources is critical in
efficiently resolving diverse conflicts. If the conflict types are organized as a
cognitive space in the brain, the similarity between conflict types in the cognitive
space should be reflected in both the behavior and similarity in the neural
representations of conflict types. Our data from two experiments using this
experimental design support both predictions: using behavioral data, we found that the
influence of congruency (i.e., whether the task-relevant and task-irrelevant
information indicate the same response) from the previous trial to the next trial
increases with the conflict similarity between the two trials. Using fMRI data, we
found that more similar conflicts showed higher multivariate pattern similarity in the
right dorsolateral prefrontal cortex (dlPFC).

Results

Conflict type similarity modulates behavioral congruency sequence effect (CSE)

Experiment 1.
We conducted a behavioral experiment (n = 33, 18 females) to examine how CSEs
across different conflict types are influenced by their similarity. First, we validated the
experimental design by testing the congruency effects. All five conflict types showed
robust congruency effects such that the incongruent trials were slower and less
accurate than the congruent trials (Note S1; Fig. S1 A/B). To test the influence of
similarity between conflict types on behavior, we examined the CSE in consecutive

trials. Specifically, the CSE was quantified as the interaction between previous and
current trial congruency and can reflect how (in)congruency on the previous trial
influences cognitive control on the current trial (Egner, 2007; Schmidt & Weissman,
2014). It has been shown that the CSE diminishes if the two consecutive trials have
different conflict types (Akcay & Hazeltine, 2011; Egner et al., 2007; Torres-Quesada
et al., 2013). Similarly, we tested whether the size of CSE increases as a function of
conflict similarity between consecutive trials. To this end, we organized trials based
on a 5 (previous trial conflict type) × 5 (current trial conflict type) × 2 (previous trial
congruency) × 2 (current trial congruency) factorial design, with the first two and the
last two factors capturing between-trial conflict similarity and the CSE, respectively.
The cells in the 5 × 5 matrix were mapped to different similarity levels according to
the angular difference between the two conflict types (Fig. 1C). As shown in Fig. 2,
the CSE, measured in both reaction time (RT) and error rate (ER), scaled with conflict
similarity.
To test the modulation of conflict similarity on the CSE, we constructed a linear
mixed effect model to predict RT/ER in each cell of the factorial design using a
predictor encoding the interaction between the CSE and conflict similarity (see
Methods). The results showed a significant effect of conflict similarity (RT: $\beta = 0.10$
± 0.01, $t(1719.7) = 15.82$, $p < .001$, $\eta_p^2 = .120$; ER: $\beta = 0.15 \pm 0.02$, $t(204.5) = 7.84$, p
$< .001$, $\eta_p^2 = .085$, Fig. S2B/E). In other words, the CSE increased with the conflict
similarity between two consecutive trials. The conflict similarity modulation effect
remained significant after regressing out the influence of physical proximity between
the stimuli of consecutive trials (Note S2). As a control analysis, we also compared
this approach to a two-stage analysis that first calculated the CSE for each previous ×
current trial conflict type condition and then tested the modulation of conflict
similarity on the CSEs (Yang et al., 2021). The two-stage analysis also showed a
strong effect of conflict similarity (RT: $\beta = 0.58 \pm 0.04$, $t(67.5) = 14.74$, $p < .001$, η_p^2
$= .388$; ER: $\beta = 0.36 \pm 0.05$, $t(40.3) = 7.01$, $p < .001$, $\eta_p^2 = .320$, Fig. S2A/D).
Importantly, individual modulation effects of conflict similarity were positively
correlated between the two approaches (RT: $r = 0.48$; ER: $r = 0.86$, both $ps < 0.003$,
one-tailed), indicating the consistency of the estimated conflict similarity effects
across the two approaches. In the following texts, we will use the terms "*conflict*
similarity effect" and "*conflict type effect*" interchangeably.
Moreover, to test the continuity and generalizability of the similarity modulation,
we conducted a leave-one-out prediction analysis. We used the behavioral data from
Experiment 1 for this test, due to its larger amount of data than Experiment 2.
Specifically, we removed data from one of the five similarity levels (as illustrated by
the θs in Fig. 1C) and used the remaining data to perform the same mixed-effect
model (i.e., the two-stage analysis). This yielded one pair of beta coefficients
including the similarity regressor and the intercept for each subject, with which we
predicted the CSE for the removed similarity level for each subject. We repeated this
process for each similarity level once. The predicted results were highly correlated
with the original data, with $r = .87$ for the RT and $r = .84$ for the ER, $ps < .001$.

Fig. 2. The conflict similarity modulation on the behavioral CSE in Experiment 1. (A) RT and (B) ER are plotted as a function of congruency types on trial n−1 and trial n. Each column shows one similarity level, as indicated by the defined angular difference between two conflict types. Error bars are standard errors. C = congruent; I = incongruent; RT = reaction time; ER = error rate.

Experiment 2.

Behavioral results. We next conducted an fMRI experiment using a shorter version of the same task with a different sample (n = 35, 17 females) to seek neural evidence of how different conflict types are organized. Using behavioral data, we first validated the experimental design by testing congruency effects in each of the five conflict types (Note S1; Fig. S1 C/D). We then tested the modulation of conflict similarity on the behavioral CSE using the linear mixed effect model as in Experiment 1 (except the two-stage method). Results showed a significant effect of conflict similarity modulation (RT: $\beta = 0.24 \pm 0.04$, $t(71.7) = 6.36$, $p < .001$, $\eta_p^2 = .096$; ER: $\beta = 0.33 \pm 0.06$, $t(175.4) = 5.81$, $p < .001$, $\eta_p^2 = .124$, Fig. S2C/F), thus replicating the results of Experimental 1 and setting the stage for fMRI analysis. As in Experiment 1, the conflict similarity modulation effect remained significant after regressing out the influence of physical proximity between the stimuli of consecutive trials (Note S2).

Fig. 3. The congruency effect and parametric modulation effect detected by uni-voxel analyses.
Results displayed are probabilistic TFCE enhanced and thresholded with voxel-wise $p < .001$ and
cluster-wise $p < .05$, both one-tailed. The congruency effect denotes the higher activation in
incongruent than congruent condition (left panel). The positive parametric modulation effect (I_pm –
C_pm) denotes the higher activation when the conflict type contained a higher ratio of Simon conflict
component (right panel). I = incongruent; C = congruent; pm = parametric modulator.

In the fMRI analysis, we first replicated the classic congruency effect by searching for
brain regions showing higher univariate activation in incongruent than congruent
conditions (GLM1, see Methods). Consistent with the literature (Botvinick et al.,
2004; Fu et al., 2022), this effect was observed in the pre-supplementary motor area
(pre-SMA) (Fig. 3, Table S1). We then tested the encoding of conflict type as a
cognitive space by identifying brain regions with activation levels parametrically
covarying with the coordinates (i.e., axial angle relative to the horizontal/vertical
axes) in the hypothesized cognitive space. As shown in Fig. 1B, change in the angle
corresponds to change in spatial Stroop and Simon conflicts in opposite directions, so
we used opposite contrasts to examine the encoding of spatial Stroop and Simon
strength, respectively (see Methods). Accordingly, we found the right inferior parietal
sulcus (IPS) and the right dorsomedial prefrontal cortex (dmPFC) displayed positive
correlation between fMRI activation and the Simon conflict (Fig. 3, Fig. S3, Table
S1). We did not observe regions showing significant correlation with the spatial
Stroop conflict.
To further test if the univariate results explain the conflict similarity modulation
of the behavioral CSE (slope in Fig. S2C), we conducted brain-behavioral correlation
analyses for regions identified above. Regions with higher spatial Stroop/Simon
modulation effects were expected to trigger higher behavioral conflict similarity
modulation effect on the CSE. However, none of the two regions (i.e., right IPS and
right dmPFC, Fig. 3) were positively correlated with the behavioral performance, both
uncorrected $ps > .28$, one-tailed. In addition, since the conflict type difference covaries

with the orientation of the arrow location at the individual level (e.g., the stimulus in a
higher level of Simon conflict is always closer to the horizontal axis, see Fig. 4A), the
univariate modulation effects may not reflect purely conflict type difference. To
further tease these factors apart, we used multivariate analyses.

Multivariate patterns of the right dlPFC encodes the conflict similarity

Fig. 5. The conflict type effect. (A) Brain regions surviving the Bonferroni correction (*p* < 0.05)
across the 360 regions (criterion 1). Labeled is the region meeting the three criteria. (B) Different
encoding of conflict type effect in the incongruent with congruent conditions (criterion 2). * FDR
corrected *p* < .05; r = right. (C) The brain-behavior correlation of the right 8C (criterion 3). The x-axis
shows the beta coefficient of the conflict type effect from the RSA, and the y-axis shows the beta
coefficient obtained from the behavioral linear model using the conflict similarity to predict the CSE in
Experiment 2. (D) Illustration of the different encoding strength of conflict type similarity in
incongruent versus congruent conditions of right 8C. The y-axis is derived from the z-scored Pearson
correlation coefficient after regressing out other factors. See Fig. S4B for a plot with the raw Pearson
correlation measurement. l = left; r = right.

The hypothesis that the brain encodes conflict types in a cognitive space predicts that
similar conflict types will have similar neural representations. To test this prediction,
we computed the representational similarity matrix (RSM) that encoded correlations

of blood-oxygen-level dependent (BOLD) signal patterns between each pair of
conflict type (Stroop, St_HSm_L, St_MSm_M, St_LSm_H, and Simon, with H, M and L
indicating high, medium and low, respectively, see also Fig. 1B) × congruency
(congruent, incongruent) × arrow direction (up, down) × run × subject combinations
for each of the 360 cortical regions from the Multi-Modal Parcellation (MMP) cortical
atlas (Glasser et al., 2016; Jiang et al., 2020). The RSM was then submitted to a linear
mixed-effect model as the dependent variable to test whether the representational
similarity in each region was modulated by various experimental variables (e.g.,
conflict type, spatial orientation, stimulus, response, etc., see Methods). The linear
mixed-effect model was used to de-correlate conflict type and spatial orientation
leveraging the between-subject manipulation of stimulus locations (Fig. 4A).
To validate this method, we applied this analysis to test the effects of
response/stimulus features and found that representational similarity of the BOLD
signal patterns significantly covaried with whether two response/spatial
location/arrow directions were the same most strongly in bilateral
motor/visual/somatosensory areas, respectively (Fig. S5). We then identified the
cortical regions encoding conflict type as a cognitive space by testing whether their
RSMs can be explained by the similarity between conflict types. Specifically, we
applied three independent criteria: (1) the cortical regions should exhibit a statistically
significant positive conflict similarity effect on the RSM; (2) the conflict similarity
effect should be stronger in incongruent than congruent trials to reflect flexible
adjustment of cognitive control demand when the conflict is present; and (3) the
conflict similarity effect should be positively correlated with the behavioral conflict
similarity modulation effect on the CSE (see *Behavioral Results* of Experiment 2).
The first criterion revealed several cortical regions encoding the conflict similarity,
including the frontal eye field (FEF), region 1, Brodmann 8C area (a subregion of
dlPFC) (Glasser et al., 2016), a47r, posterior inferior frontal junction (IFJp), anterior
intraparietal area (AIP), temporoparietooccipital junction 3 (TPOJ3), PGi, and V3CD
in the right hemisphere, and the superior frontal language (SFL) area, 23c, 24dd,
7Am, p32pr, 6r, FOP1, PF, ventromedial visual area (VMV1/2) areas, area 25, MBelt
in the left hemisphere (Bonferroni corrected $ps < 0.05$, one-tailed, Fig. 5A). We next
tested whether these regions were related to cognitive control by comparing the
strength of conflict similarity effect between incongruent and congruent conditions
(criterion 2) and correlating the strength to behavioral similarity modulation effect
(criterion 3). Given these two criteria pertain to second-order analyses (interaction or
individual analyses) and thus might have lower statistical power (Blake & Gangestad,
2020), we applied a more lenient threshold using false discovery rate (FDR)
correction (Benjamini & Hochberg, 1995) on the above-mentioned regions. Results
revealed that the left SFL, left VMV1, area 1eft 25 and right 8C met this criterion,
FDR corrected ps < .05, one-tailed, suggesting that the representation of conflict type
was strengthened when the conflict was present (e.g., Fig. 5D and Fig. S4). The inter-
subject brain-behavioral correlation analysis (criterion 3) showed that the strength of
conflict similarity effect on RSM scaled with the modulation of conflict similarity on
the CSE (slope in Fig. S2C) in right 8C ($r = .52$, FDR corrected $p = .015$, one-tailed,

Fig. 5C) only. These results are listed in Table 1. In addition, we did not find evidence
supporting the encoding of congruency in the right 8C area (see Note S6), suggesting
that the right 8C area specifically represents conflict similarity.

Table 1. Summary statistics of the cross-subject RSA for regions showing
conflict type and orientation effects identified by the three criteria.

Region	Criterion 1			Criterion 2		Criterion 3	
name	t	$\beta \pm SD$	p	t	p	r	p
Conflict type effect							
left SFL	4.77	0.0061 ± 0.0013	1.9×10^{-6}	2.45	0.007	.35	.021
left 23c	4.42	0.0049 ± 0.0011	9.8×10^{-6}	1.18	0.118	−.15	.800
left 24dd	6.13	0.0079 ± 0.0013	8.9×10^{-10}	1.61	0.053	−.04	.580
left 7Am	6.76	0.0090 ± 0.0013	1.4×10^{-11}	−0.75	0.772	.04	.418
left p32pr	4.00	0.0044 ± 0.0011	6.4×10^{-5}	−3.95	1.000	−.01	.533
left 6r	5.41	0.0071 ± 0.0013	6.3×10^{-8}	−1.94	0.973	−.11	.737
left FOP1	4.37	0.0050 ± 0.0011	1.3×10^{-5}	1.83	0.034	−.25	.926
left PF	4.04	0.0058 ± 0.0014	5.3×10^{-5}	−1.90	0.969	−.24	.921
left VMV1	7.45	0.0091 ± 0.0012	9.6×10^{-14}	2.83	0.002	−.27	.940
left VMV2	4.75	0.0053 ± 0.0011	2.0×10^{-6}	−0.32	0.624	−.06	.630
left 25	3.70	0.0041 ± 0.0011	2.1×10^{-4}	3.26	0.001	.05	.386
left Mbelt	4.25	0.0064 ± 0.0015	2.1×10^{-5}	1.77	0.039	.10	.275
right FEF	3.98	0.0054 ± 0.0014	6.8×10^{-5}	−5.49	1.000	.08	.327
right 1	3.90	0.0045 ± 0.0012	9.7×10^{-5}	−2.34	0.990	−.07	.665
right 8C*	5.41	0.0064 ± 0.0012	6.1×10^{-8}	2.46	0.007	.52	.001
right a47r	5.04	0.0056 ± 0.0011	4.7×10^{-7}	−0.68	0.753	.05	.393
right IFJp	3.78	0.0042 ± 0.0011	1.6×10^{-4}	0.77	0.221	.27	.056
right AIP	4.64	0.0054 ± 0.0012	3.5×10^{-6}	1.86	0.032	−.02	.540
right TPOJ3	4.48	0.0056 ± 0.0012	7.6×10^{-6}	−0.25	0.600	.21	.118
right PGi	4.07	0.0045 ± 0.0011	4.8×10^{-5}	−1.59	0.944	−.01	.523
right V3CD	3.86	0.0043 ± 0.0011	1.2×10^{-4}	1.94	0.026	.02	.451
Orientation effect							
left FEF*	5.17	0.0060 ± 0.0012	2.4×10^{-7}	2.73	0.003	−.01	.518
left POS1	4.35	0.0051 ± 0.0012	1.4×10^{-5}	−1.52	0.936	.00	.500
left 31pv	5.60	0.0103 ± 0.0018	2.1×10^{-8}	−0.48	0.686	.05	.397
left 6ma	4.75	0.0055 ± 0.0012	2.0×10^{-6}	−1.87	0.970	−.00	.500
left 7PC	3.66	0.0042 ± 0.0012	2.5×10^{-4}	0.76	0.223	−.20	.876
left 8BL	4.55	0.0053 ± 0.0012	5.3×10^{-6}	0.10	0.460	.14	.207
left AIP	3.83	0.0044 ± 0.0012	1.3×10^{-4}	0.62	0.266	−.23	.910
left TE1p	3.95	0.0046 ± 0.0012	7.8×10^{-5}	0.14	0.443	.01	.475
left IP2*	4.49	0.0052 ± 0.0012	7.2×10^{-6}	4.02	0.000	.19	.139
right V1*	4.71	0.0083 ± 0.0018	2.5×10^{-6}	2.91	0.002	−.08	.672
right V2*	3.88	0.0172 ± 0.0044	1.1×10^{-4}	3.19	0.001	.02	.462
right V3	3.94	0.0175 ± 0.0045	8.2×10^{-5}	−1.45	0.927	.39	.010
right LO2	5.95	0.0069 ± 0.0012	2.8×10^{-9}	−1.81	0.965	.26	.068
right POS1*	3.70	0.0043 ± 0.0012	2.1×10^{-4}	2.98	0.001	.33	.028

right 5m	5.24	0.0061 ± 0.0012	1.6×10^{-7}	-2.12	0.983	.00	.500
right TF	4.97	0.0058 ± 0.0012	6.7×10^{-7}	-1.08	0.860	$-.07$	.657
right PHT	4.54	0.0053 ± 0.0012	5.5×10^{-6}	0.03	0.486	$-.04$	.589
right PF*	5.57	0.0064 ± 0.0012	2.6×10^{-8}	3.08	0.001	$-.03$	.558
right A4	4.11	0.0048 ± 0.0012	3.9×10^{-5}	-2.68	0.996	$-.09$	.700

Note. all *p* values listed are 1-tailed and uncorrected. The * denotes the regions
meeting all three criteria for each effect.

The model described above employs the cosine similarity measure to define
conflict similarity and will be referred to as the Cognitive-Space model. To examine if
the right 8C specifically encodes the cognitive space rather than the domain-general
or domain-specific organizations, we tested two additional models (see Methods).
Model comparison showed a lower BIC in the Cognitive-Space model (BIC =
5377093) than the Domain-General (BIC = 537126) or Domain-Specific (BIC =
537127) models. Further analysis showed the dimensionality of the representation in
the right 8C was 1.19, suggesting the cognitive space was close to 1D. Moreover, we
replicated the results with only incongruent trials, considering that the pattern of
conflict representations is more manifested when the conflict is present (i.e., on
incongruent trials) than not (i.e., on congruent trials). We found a poorer fitting in
Domain-general (BIC = 1344127), and Domain-Specific (BIC = 1344129) models
than the Cognitive-Space model (BIC = 1344104). These results indicate that the right
8C encodes an integrated cognitive space for resolving Stroop and Simon conflicts.
The more detailed model comparison results are listed in Table 2.
In sum, we found converging evidence supporting that the right dlPFC (8C area)
encoded conflict similarity parametrically, which further supports the hypothesis that
conflict types are represented in a cognitive space.

Table 2. Model comparison results of the right 8C. RSM_I shows results using
incongruent trials only.

Model name	Full RSM			RSM_I		
	t	*p*	BIC	*t*	*p*	BIC
Cognitive-Space	5.41	6.1×10^{-8}	5377093	4.97	3.35×10^{-7}	1345201
Domain-General	0.92	.179	5377126	1.43	.076	1344127
Domain-Specific	0.84	.200	5377127	0.28	.390	1344129

422 *Multivariate patterns of visual and oculomotor areas encode stimulus orientation*

Fig. 6. The orientation effect. (A) Brain regions surviving the Bonferroni correction ($p < 0.05$) across the 360 regions (criterion 1). Labeled regions are those meeting the three criterion. (B) Different encoding of orientation in the incongruent with congruent conditions. * FDR corrected $p < .05$, ** FDR corrected $p < .01$; *** FDR corrected $p < .001$.

To tease apart the representation of conflict type from that of perceptual information, we tested the modulation of the spatial orientations of stimulus locations on RSM using the aforementioned RSA. We also applied three independent criteria: (1) the cortical regions should exhibit a statistically significant orientation effect on the RSM; (2) the conflict similarity effect should be stronger in incongruent than congruent trials; and (3) the orientation effect should not interact with the CSE, since the orientation effect was dissociated from the conflict similarity effect and was not expected to influence cognitive control. We observed increasing fMRI representational similarity between trials with more similar orientations of stimulus location in the occipital cortex, such as right V1, right V2, right V3, bilateral POS1, and right lateral occipital 2 (LO2) areas (Bonferroni corrected $ps < 0.05$). We also found the same effect in the oculomotor related region, i.e., the left frontal eye field (FEF), and other regions including the left 31pv, 6ma, 7PC, 8BL, AIP, TE1p, IP2, right 5m, TF, PHT, A4 and parietal area F (PF) (Fig. 6A). Then we tested if any of these brain regions were related to the conflict representation by comparing their encoding strength between incongruent and congruent conditions. Results showed that the right V1, right V2, right POS1, left IP2, left FEF, and right PF encoded stronger orientation effect in the incongruent than the congruent condition, FDR corrected $ps < .05$, one-tailed (Table1, Fig. 6B). We then tested if any of these regions was related to the behavioral performance, and results showed that none of them positively correlated with the behavioral conflict similarity modulation effect, all uncorrected $ps > .18$, one-tailed. Thus all identified regions are consistent with the criterion 3. Like the right 8C area, none of the reported areas directly encoded congruency (see Note S6). Taken together, we found that the visual and oculomotor regions encoded orientations of stimulus location in a continuous manner and that the encoding strength was stronger when the conflict was present.

We hypothesize that the overlapping spatial information of orientation may have facilitated the encoding of conflict types. To explore the relation between conflict type and orientation representations, we conducted representational connectivity (i.e., the similarity between two within-subject RSMs of two regions) (Kriegeskorte et al., 2008) analyses and found that among the orientation effect regions, the right V1 and right V2 showed significant representational connectivity with the right 8C compared to the controlled regions (including those encoding orientation effect but not showing larger encoding strength in incongruent than congruent conditions, as well as eight other regions encoding none of our defined effects in the main RSA, see Methods). Compared with the largest connectivity strength in the controlled regions (i.e., the left 6ma, $\beta = 0.7991 \pm 0.0299$), we found higher connectivity in the right V1, $\beta = 0.8633 \pm 0.0325$, and right V2, $\beta = 0.8772 \pm 0.0335$ (Fig. S6).

Discussion

Understanding how different types of conflicts are resolved is essential to answer how cognitive control achieves adaptive behavior. However, the dichotomy between domain-general and/or domain-specific processes presents a dilemma (Braem et al., 2014; Egner, 2008). Reconciliation of the two views also suffers from the inability to fully address how different conflicts can be resolved by a limited set of cognitive control processes. In this study, we hypothesized that this issue can be addressed if conflicts are organized as a cognitive space. Leveraging the well-known dissociation between the spatial Stroop and Simon conflicts (Li et al., 2014; Liu et al., 2010; Wang et al., 2014), we designed five conflict types that are systematically different from each other. The cognitive space hypothesis predicted that the representational proximity/distance between two conflict types scales with their similarities/dissimilarities, which was tested at both behavioral and neural levels. Behaviorally, we found that the CSEs were linearly modulated by conflict similarity between consecutive trials, replicating and extending our previous study (Yang et al., 2021). BOLD activity patterns in the right dlPFC further showed that the representational similarity between conflict types was modulated by their conflict similarity, and that strength of the modulation was positively associated with the modulation of conflict similarity on the behavioral CSE. We also observed that activity in two brain regions (right IPS and right dlPFC) was parametrically modulated by the conflict type difference, though they did not directly explain the behavioral results. Additionally, we found that the visual regions encoded the spatial orientation of the stimulus location, which might provide the essential concrete information to determine the conflict type. Together, these results suggest that conflicts may be organized in a cognitive space that enables a limited set of cognitive control processes to resolve a wide variety of distinct types of conflicts.

Conventionally, the domain-general view of control suggests a common representation for different types of conflicts (Fig. 7, left), while the domain-specific view suggests dissociated representations for different types (Fig. 7, right). Previous research on this topic often adopts a binary manipulation of conflicts (Braem et al., 2014) (i.e., each domain only has one conflict type) and gathered evidence for the domain-general/specific view with presence/absence of CSE, respectively. Here, we parametrically manipulated the similarity of conflict types and found the CSE systematically vary with conflict similarity level, demonstrating that cognitive control is neither purely domain-general nor purely domain-specific, but can be reconciled as a cognitive space (Bellmund et al., 2018)(Fig. 7, middle). The model comparison analysis also showed that the Cognitive-Space model explained the representation in right DLPFC better than the Domain-General or Domain-Specific models. Specifically, the cognitive space provides a solution to use a single cognitive space organization to encode different types of conflicts that are close (domain-general) or distant (domain-specific) to each other. It also shows the potential for how various conflict types can be coded using limited resources (i.e., as different points in a low-dimensional cognitive space), as suggested by its out-of-sample predictability.

Moreover, geometry can also emerge in the cognitive space (Fu et al., 2022), which
will allow for decomposition of a conflict type (e.g., how much conflict in each of the
dimensions in the cognitive space) so that it can be mapped into the limited set of
cognitive control processes. Such geometry enables fast learning of cognitive control
settings from similar conflict types by providing a measure of similarity (e.g., as
distance in space).

Fig. 7. Illustration of the hypothesized dimensionalities of different representations. The shade of
the red color indicates the degree of dimensionality (i.e., how many dimensions are needed to represent
different states). The dimensionality of domain-general representation is extremely low, with all
representations compressed to one dot. The dimensionality of domain-specific representation is
extremely high, with each control state encoded in a unique and orthogonal dimension. The
dimensionality of the organized representation is modest, enabling distant states to be separated but
also allowing close states to share representations. The solid arrows show the axes of different
dimensions. The dashed arrows indicate how the representational dimensionality can be reduced by
projecting the independent dimensions to a common dimension.

If the dimensionality of the cognitive space of conflict is extremely high, the
cognitive space solution would suffer the same criticism as the domain-specificity
theory. We argue that the dimensionality is manageable for the human brain, as task
information unrelated to differentiating conflicts can be removed. For example, the
Simon conflict can be represented in a space consisting of spatial location, stimulus
information and responses. Thus, the dimensionality of the cognitive space of
conflicts should not exceed the number of represented features. The dimensionality
can be further reduced, as humans selectively represent a small number of features
when learning task representations (e.g., spatial information is reduced to the
horizontal dimension from the 3D space we live in)(Niv, 2019). Consistently, we
observed a low dimensional (1.19D) space representing the five conflict types. This is
expected since the only manipulated variable is the angular distance between conflict
types. The reduced dimensionality does not only require less effort to represent the
conflict, but also facilitates generalization of cognitive control settings among
different conflict types (Badre et al., 2021).

Although our finding of cognitive space in the right dlPFC differs from other
cognitive space studies (Constantinescu et al., 2016; Park et al., 2020; Schuck et al.,
2016) that highlighted the orbitofrontal and hippocampus regions, it is consistent with
the cognitive control literature. The prefrontal cortex has long been believed to be a
key region of cognitive control representation (Mansouri et al., 2007; Miller & Cohen,
2001; Milner, 1963) and is widely engaged in multiple task demands (Cole et al.,
2013; Duncan, 2010). However, it is not until recently that the multivariate
representation in this region has been examined. For instance, Vaidya et al.(2021)
reported that frontal regions presented latent states that are organized hierarchically.
Freund et al.(2021) showed that dlPFC encoded the target and congruency in a typical
color-word Stroop task. Taken together, we suggest that the right dlPFC might
flexibly encode a variety of cognitive spaces to meet the dynamic task demands. In
addition, we found no such representation in the left dlPFC (Note S8), indicating a
possible lateralization. Previous studies showed that the left dlPFC was related to the
expectancy-related attentional set up-regulation, while the right dlPFC was related to
the online adjustment of control (Friehs et al., 2020; Vanderhasselt et al., 2009),
which is consistent with our findings. Moreover, the right PFC also represents a
composition of single rules (Reverberi et al., 2012), which may explain how the
spatial Stroop and Simon types can be jointly encoded in a single space.
Previous researchers have proposed an "expected value of control (EVC)" theory,
which posits that the brain can evaluate the cost and benefit associated with executing
control for a demanding task, such as the conflict task, and specify the optimal control
strength (Shenhav et al., 2013). For instance, Grahek et al. (2022) found that more
frequently switching goals when doing a Stroop task were achieved by adjusting
smaller control intensity. Our work complements the EVC theory by further
investigating the neural representation of different conflict conditions and how these
representations can be evaluated to facilitate conflict resolution. We found that
different conflict conditions could be efficiently represented in a cognitive space
encoded by the right dlPFC, and participants with stronger cognitive space
representation have also adjusted their conflict control to a greater extent based on the
conflict similarity (Fig 4C). The finding suggests that the cognitive space organization
of conflicts guides cognitive control to adjust behavior. Previous studies have shown
that participants may adopt different strategies to represent a task, with the model-
based strategies benefitting goal-related behaviors more than the model-free strategies
(Rmus et al., 2022). Similarly, we propose that cognitive space could serve as a
mental model to assist fast learning and efficient organization of cognitive control
settings. Specifically, the cognitive space representation may provide a principle for
how our brain evaluates the expected cost of switching and the benefit of
generalization between states and selects the path with the best cost-benefit tradeoff
(Abrahamse et al., 2016; Shenhav et al., 2013). The proximity between two states in
cognitive space could reflect both the expected cognitive demand required to
transition and the useful mechanisms to adapt from. The closer the two conditions are
in cognitive space, the lower the expected switching cost and the higher the
generalizability when transitioning between them. With the organization of a

cognitive space, a new conflict can be quickly assigned a location in the cognitive
space, which will facilitate the development of cognitive control settings for this
conflict by interpolating nearby conflicts and/or projecting the location to axes
representing different cognitive control processes, thus leading to a stronger CSE
when following a more similar conflict condition. On the other hand, without a
cognitive space, there would be no measure of similarity between conflicts on
different trials, hence limiting the ability of fast learning of cognitive control setting
from similar trials.

The cognitive space in the right dlPFC appears to be an abstraction of concrete
information from the visual regions. We found that the right V1 and V2 encoded the
spatial orientation of the target location (Fig. 6) and showed strong representational
connectivity with the right dlPFC (Fig. S6), suggesting that there might be
information exchange between these regions. We speculate that the representation of
spatial orientation may have provided the essential perceptual information to
determine the conflict type (Fig. 1) and thus served as the critical input for the
cognitive space. The conflict type representation further incorporates the stimulus-
response mapping rules to the spatial orientation representation, so that vertically
symmetric orientations can be recognized as the same conflict type (Fig. 7). In other
words, the representation of conflict type involves the compression of perceptual
information (Flesch et al., 2022), which is consistent with the idea of a low-
dimensional representation of cognitive control (Badre et al., 2021; MacDowell et al.,
2022). The compression and abstraction processes might be why the frontoparietal
regions are the top of hierarchy of information processing (Gilbert & Li, 2013) and
why the frontoparietal regions are widely engaged in multiple task demands (Duncan,
2013).

Although the spatial orientation information in our design could be helpful to the
construction of cognitive space, the cognitive space itself was independent of the
stimulus-level representation of the task. We found the conflict similarity modulation
on CSE did not change with more training (see Note S3), indicating that the cognitive
space did not depend on strategies that could be learned through training. Instead, the
cognitive space should be determined by the intrinsic similarity structure of the task
design. For example, a previous study (Freitas & Clark, 2015) has found that the CSE
across different versions of spatial Stroop and flanker tasks was stronger than that
across either of the two conflicts and Simon. In their designs, the stimulus similarity
was controlled at the same level, so the difference in CSE was only attributable to the
similar dimensional overlap between Stroop and flanker tasks, in contrast to the
Simon task. Furthermore, recent studies showed that the cognitive space generally
exists to represent structured latent states (e.g., Vaidya & Badre, 2022), mental
strategy cost (Grahek et al., 2022), and social hierarchies (Park et al., 2020).
Therefore, cognitive space is likely a universal strategy that can be applied to different
scenarios.

With conventional univariate analyses, we observed that the overall congruency
effect was located at the medial frontal region (i.e., pre-SMA), which is consistent
with previous studies (Botvinick et al., 2004; Fu et al., 2022). Beyond that, we also

found regions that can be parametrically modulated by conflict type difference,
including right IPS, right dlPFC (modulated by Simon difference). The right
lateralization of these regions is consistent with a previous finding (Li et al., 2017).
The parametric encoding of conflict also mirrors prior research showing the
parametric encoding of task demands (Dagher et al., 1999; Ritz & Shenhav, 2023).
The scaling of brain activities based on conflict difference is potentially important to
the representational organization of different types of conflicts. However, we didn't
observe their brain-behavioral relevance. One possible reason is that the conflict
(dis)similarity is a combination of (dis)similarity of spatial Stroop and Simon
conflicts, but each univariate region only reflects difference along a single conflict
domain. Also likely, the representational geometry is more of a multivariate problem
than what univariate activities can capture (Freund, Etzel, et al., 2021). Future studies
may adopt approaches such as repetition suppression induced fMRI adaptation (Badre
et al., 2021) to test the role of univariate activities in task representations.
Recently an interesting debate has arisen concerning whether cognitive control
should be considered as a process or a representation (Freund, Etzel, et al., 2021).
Traditionally, cognitive control has been predominantly viewed as a process.
However, the study of its representation has gained more and more attention. While it
may not be as straightforward as the visual representation (e.g., creating a mental
image from a real image in the visual area), cognitive control can have its own form
of representation. An influential theory, Marr's (1982) three-level model proposed
that representation serves as the algorithm of the process to achieve a goal based on
the input. In other words, representation can encompass a dynamic process rather than
being limited to static stimuli. Building on this perspective, we posit that the
representation of cognitive control consists of an array of dynamic representations
embedded within the overall process. A similar idea has been proposed that the
representation of task profiles can be progressively constructed with time in the brain
(Kikumoto & Mayr, 2020). Moreover, we anticipate that the representation of
cognitive space is most prominently involved at two critical stages to guide the
transference of behavioral CSE. The first stage involves the evaluation of control
demands, where the representational distance/similarity between previous and current
trials influences the adjustment of cognitive control. The second stage pertains to
control execution, where the switch from one control state to another follows a path
within the cognitive space. However, we were unable to fully distinguish between
these two stages due to the low temporal resolution of fMRI signals in our study.
Future research seeking to delve deeper into this question may benefit from
methodologies with higher temporal resolutions, such as EEG and MEG.
Several interesting questions remains to be answered. For example, is the
dimension of the unified space across conflict-inducing tasks solely determined by the
number of conflict sources? Is this unified space adaptively adjusted within the same
brain region? Can we effectively map any sources of conflict with completely
different stimuli into a single space? Does the cognitive space vary from population to
population, such as between the normal people and patients?

Methodological implications. Previous studies with mixed conflicts have applied
mainly categorical manipulations of conflict types, such as the multi-source
interference task (Fu et al., 2022) and color Stroop-Simon task (Liu et al., 2010). The
categorical manipulations make it difficult to quantify conceptual similarity between
conflict types and hence limit the ability to test whether neural representations of
conflict capture conceptual similarity. To the best of our knowledge, no previous
studies have manipulated the conflict types parametrically. This gap highlights a
broader challenge within cognitive science: effectively manipulating and measuring
similarity levels for conflicts, as well as other high-level cognitive processes, which
are inherently abstract. The use of an experimental paradigm that permits parametric
manipulation of conflict similarity provides a way to systematically investigate the
organization of cognitive control, as well as its influence on adaptive behaviors.
Moreover, the cross-subject RSA provides high sensitivity to the variables of interest
and the ability to separate confounding factors. For instance, in addition to
dissociating conflict type from orientation, we dissociated target from response, and
spatial Stroop distractor from Simon distractor. We further showed cognitive control
can both enhance the target representation and suppress the distractor representation
(Note S10, Fig. S7), which is in line with previous studies (Polk et al., 2008; Ritz &
Shenhav, 2022).

Limitations. A few limitations of this study need to be noted. To parametrically
manipulate the conflict similarity levels, we adopted the spatial Stroop-Simon
paradigm that enables parametrical combinations of spatial Stroop and Simon
conflicts. However, since this paradigm is a two-alternative forced choice design, the
behavioral CSE is not a pure measure of adjusted control but could be partly
confounded by bottom-up factors such as feature integration (Hommel et al., 2004).
Future studies may replicate our findings with a multiple-choice design (including
more varied stimulus sets, locations and responses) with confound-free trial sequences
(Braem et al., 2019). Another limitation is that in our design, the spatial Stroop and
Simon effects are highly anticorrelated. This constraint may make the five conflict
types represented in a unidimensional space (e.g., a circle) embedded in a 2D space.
This limitation also means we cannot conclusively rule out the possibility of a real
unidimensional space driven solely by spatial Stroop or Simon conflicts. However,
this appears unlikely, as it would imply that our manipulation of conflict types merely
represented varying levels of a single conflict, akin to manipulating task difficulty
when everything else being equal. If task difficulty were the primary variable, we
would expect to see greater representational similarity between task conditions of
similar difficulty, such as the Stroop and Simon conditions, which demonstrates
comparable congruency effects (see Fig. S1). Contrary to this, our findings reveal that
the Stroop-only and Simon-only conditions exhibit the lowest representational
similarity (Fig. S4). Furthermore, Fu et al. (2022) has shown that the representation of
mixtures of Simon and Flanker conflicts was compositional, rather than reflecting
single dimension, which also applies to our cases. Future studies may test the 2D
cognitive space with fully independent conditions. A possible improvement to our
current design would be to include left, right, up, and down arrows represented in a

grid formation across four spatially separate quadrants, with each arrow mapped to its
own response button. Additionally, our study is not a comprehensive test of the
cognitive space hypothesis but aimed primarily to provide original evidence for the
geometry of cognitive space in representing conflict information in cognitive control.
Future research should examine other aspects of the cognitive space such as its
dimensionality, its applicability to other conflict tasks such as Eriksen Flanker task,
and its relevance to other cognitive abilities, such as cognitive flexibility and learning.
In sum, we showed that the cognitive control can be parametrically encoded in
the right dlPFC and guides cognitive control to adjust goal-directed behavior. This
finding suggests that different cognitive control states may be encoded in an abstract
cognitive space, which reconciles the long-standing debate between the domain-
general and domain-specific views of cognitive control and provides a parsimonious
and more broadly applicable framework for understanding how our brains efficiently
and flexibly represents multiple task settings.
731

Materials and Methods

Subjects

In Experiment 1, we enrolled thirty-three college students (ages 19-28, average $21.5 \pm$
2.3 years; 19 males). In Experiment 2, thirty-six college students were recruited, one
of which was excluded due to not following task instructions. The final sample of
Experiment 2 consisted of thirty-five participants (ages 19-29, average 22.3 ± 2.5
years; 17 males). The sample sizes were determined based on our previous study
(Yang et al., 2021). All participants reported no history of psychiatric or neurological
disorders and were right-handed, with normal or corrected-to-normal vision. The
experiments were approved by the Institutional Review Board of the Institute of
Psychology, Chinese Academy of Science. Informed consent was obtained from all
subjects.

Method Details

Experiment 1

Experimental Design. We adopted a modified spatial Stroop-Simon task (Yang et al.,
2021) (Fig. 1). The task was programmed with E-prime 2.0 (Psychological Software
Tools, Inc.). The stimulus was an upward or downward black arrow (visual angle of ~
1°), displayed on a 17-inch LCD monitor with a viewing distance of ~60 cm. The
arrow appeared inside a grey square at one of ten locations with the same distance
from the center of the screen, including two horizontal (left and right), two vertical
(top and bottom), and six corner (orientations of 22.5°, 45° and 67.5°) locations. The
distance from the arrow to the screen center was approximately 3°. To dissociate
orientation of stimulus locations and conflict types (see below), participants were

randomly assigned to two sets of stimulus locations (one included top-right and
bottom-left quadrants, and the other included top-left and bottom-right quadrants).
Each trial started with a fixation cross displayed in the center for $100-300$ ms,
followed by the arrow for 600 ms and another fixation cross for $1100-1300$ ms (the
total trial length was fixed at 2000 ms). Participants were instructed to respond to the
pointing direction of the arrow by pressing a left or right button and to ignore its
location. The mapping between the arrow orientations and the response buttons was
counterbalanced across participants. The task design introduced two possible sources
of conflicts: on one hand, the direction of the arrow is either congruent or incongruent
with the vertical location of the arrow, thus introducing a spatial Stroop conflict (Lu
& Proctor, 1995; MacLeod, 1991), which contains the dimensional overlap between
task-relevant stimulus and task-irrelevant stimulus (Kornblum et al., 1990); on the
other hand, the response (left or right button) is either congruent or incongruent with
the horizontal location of the arrow, thus introducing a Simon conflict (Lu & Proctor,
1995; Simon & Small, 1969), which contains the dimensional overlap between task-
irrelevant stimulus and response (Kornblum et al., 1990). Therefore, the five polar
orientations of the stimulus location (from 0 to 90°) defined five unique combinations
of spatial Stroop and Simon conflicts, with more similar orientations having more
similar composition of conflicts. More generally, the spatial orientation of the arrow
location relative to the center of the screen forms a cognitive space of different
blending of spatial Stroop and Simon conflicts.
The formal task consisted of 30 runs of 101 trials each, divided into three sessions
of ten runs each. The participants completed one session each time and all three
sessions within one week. Before each session, the participants performed training
blocks of 20 trials repeatedly until the accuracy reached 90% in the most recent block.
The trial sequences of the formal task were pseudo-randomly generated to ensure that
each of the task conditions and their transitions occurred with equal number of trials.

Experiment 2

Experimental Design. The apparatus, stimuli and procedure were identical to
Experiment 1 except for the changes below. The stimuli were back projected onto a
screen (with viewing angle being ~3.9° between the arrow and the center of the
screen) behind the subject and viewed via a surface mirror mounted onto the head
coil. Due to the time constraints of fMRI scanning, the trial numbers decreased to a
total of 340, divided into two runs with 170 trials each. To obtain a better
hemodynamic model fitting, we generated two pseudo-random sequences optimized
with a genetic algorithm (Wager & Nichols, 2003) conducted by the NeuroDesign
package (Durnez et al., 2018) (see Note S3 for more detail). In addition, we added 6
seconds of fixation before each run to allow the stabilization of the hemodynamic
signal, and 20 seconds after each run to allow the signal to drop to the baseline.
Before scanning, participants performed two practice sessions. The first one
contained 10 trials of center-displayed arrow and the second one contained 32 trials
using the same design as the main task. They repeated both sessions until their
performance accuracy for each session reached 90%, after which the scanning began.

 fMRI Image acquisition and preprocessing

Functional imaging was performed on a 3T GE scanner (Discovery MR750) using
echo-planar imaging (EPI) sensitive to BOLD contrast [in-plane resolution of 3.5 ×
3.5 mm^2, 64 × 64 matrix, 37 slices with a thickness of 3.5 mm and no interslice skip,
repetition time (TR) of 2000 ms, echo-time (TE) of 30 ms, and a flip angle of 90°]. In
addition, a sagittal T1-weighted anatomical image was acquired as a structural
reference scan, with a total of 256 slices at a thickness of 1.0 mm with no gap and an
in-plane resolution of 1.0 × 1.0 mm^2.
Before preprocessing, the first three volumes of the functional images were
removed due to the instability of the signal at the beginning of the scan. The
anatomical and functional data were preprocessed with the fMRIprep 20.2.0 (Esteban
et al., 2019) (RRID:SCR_016216), which is based on Nipype 1.5.1 (Gorgolewski et
al., 2011) (RRID:SCR_002502). Specifically, BOLD runs were slice-time corrected
using 3dTshift from AFNI 20160207 (Jenkinson et al., 2002) (RRID:SCR_005927).
The BOLD time-series were resampled to the MNI152NLin2009cAsym space
without smoothing. For a more detailed description of preprocessing, see Note S4.
After preprocessing, we resampled the functional data to a spatial resolution of 3 × 3
× 3 mm^3. All analyses were conducted in volumetric space, and surface maps are
produced with Connectome Workbench
(https://www.humanconnectome.org/software/connectome-workbench) for display
purpose only.

Quantification and Statistical Analysis

Behavioral analysis

Experiment 1. RT and ER were the two dependent variables analyzed. As for RTs,
we excluded the first trial of each block (0.9%, for CSE analysis only), error trials
(3.8%), trials with RTs beyond three *SD*s or shorter than 200 ms (1.3%) and post-
error trials (3.4%). For the ER analysis, the first trial of each block and trials after an
error were excluded. To exclude the possible influence of response repetition, we
centered the RT and ER data within the response repetition and response alternation
conditions separately by replacing condition-specific mean with the global mean for
each subject.
To examine the modulation of conflict similarity on the CSE, we organized trials
based on a 5 (previous trial conflict type) × 5 (current trial conflict type) × 2 (previous
trial congruency) × 2 (current trial congruency) factorial design. As conflict similarity
is commutive between conflict types, we expected the previous by current trial
conflict type factorial design to be a symmetrical (e.g., a conflict 1-conflict 2
sequence in theory has the same conflict similarity modulation effect as a conflict 2-
conflict 1 sequence), resulting a total of 15 conditions left for the first two factors of
the design (i.e., previous × current trial conflict type). For each previous × current
trial conflict type condition, the conflict similarity between the two trials can be
quantified as the cosine of their angular difference. In the current design, there were

five possible angular difference levels (0, 22.5°, 42.5°, 67.5° and 90°, see Fig. 1C).
We further coded the previous by current trial congruency conditions (hereafter
abbreviated as CSE conditions) as CC, CI, IC and II, with the first and second letter
encoding the congruency (C) or incongruency (I) on the previous and current trial,
respectively. As the CSE is operationalized as the interaction between previous and
current trial congruency, it can be rewritten as a contrast of (CI – CC) – (II – IC). In
other words, the load of CSE on CI, CC, II and IC conditions is 1, –1, –1 and 1,
respectively. To estimate the modulation of conflict similarity on the CSE, we built a
regressor by calculating the Kronecker product of the conflict similarity scores of the
15 previous × current trial conflict similarity conditions and the CSE loadings of
previous × current trial congruency conditions. This regressor was regressed against
RT and ER data separately, which were normalized across participants and CSE
conditions. The regression was performed using a linear mixed-effect model, with the
intercept and the slope of the regressor for the modulation of conflict similarity on the
CSE as random effects (across both participants and the four CSE conditions). As a
control analysis, we built a similar two-stage model (Yang et al., 2021). In the first
stage, the CSE [i.e., (CI – CC) – (II – IC)] for each of the previous × current trial
conflict similarity condition was computed. In the second stage, CSE was used as the
dependent variable and was predicted using conflict similarity across the 15 previous
× current trial conflict type conditions. The regression was also performed using a
linear mixed effect model with the intercept and the slope of the regressor for the
modulation of conflict similarity on the CSE as random effects (across participants).
Experiment 2. Behavioral data was analyzed using the same linear mixed effect model
as Experiment 1, with all the CC, CI, IC and II trials as the dependent variable. In
addition, to test if fMRI activity patterns may explain the behavioral representations
differently in congruent and incongruent conditions, we conducted the same analysis
to measure behavioral modulation of conflict similarity on the CSE using congruent
(CC and IC) and incongruent (CI and II) trials separately.

Estimation of fMRI activity with univariate general linear model (GLM)

To estimate voxel-wise fMRI activity for each of the experimental conditions, the
preprocessed fMRI data of each run were analyzed with the GLM. We conducted
three GLMs for different purposes. GLM1 aimed to validate the design of our study
by replicating the engagement of frontoparietal activities in conflict processing
documented in previous studies (Jiang & Egner, 2014; Li et al., 2017), and to explore
the cognitive space related regions that were parametrically modulated by the conflict
type. Preprocessed functional images were smoothed using a 6-mm FWHM Gaussian
kernel. We included incongruent and congruent conditions as main regressors and
appended a parametric modulator for each condition. The modulation parameters for
Stroop, St_HSm_L, St_MSm_M, St_LSm_H, and Simon trials were −2, −1, 0, 1 and 2,
respectively. In addition, we also added event-related nuisance regressors, including
error/missed trials, outlier trials (slower than three SDs of the mean or faster than 200
ms) and trials within two TRs of significant head motion (i.e., outlier TRs, defined as
standard DVARS > 1.5 or FD > 0.9 mm from previous TR)(Jiang et al., 2020). On

average there were 1.2 outlier TRs for each run. These regressors were convolved
with a canonical hemodynamic response function (HRF) in SPM 12
(http://www.fil.ion.ucl.ac.uk/spm). We further added volume-level nuisance
regressors, including the six head motion parameters, the global signal, the white
matter signal, the cerebrospinal fluid signal, and outlier TRs. Low-frequency signal
drifts were filtered using a cutoff period of 128 s. The two runs were regarded as
different sessions and incorporated into a single GLM to get more power. This yielded
two beta maps (i.e., a main effect map and a parametric modulation map) for the
incongruent and congruent conditions, respectively and for each subject. At the group
level, paired t-tests were conducted between incongruent and congruent conditions,
one for the main effect and the other for the parametric modulation effect. Since the
spatial Stroop and Simon conflicts change in the opposite direction to each other, a
positive modulation effect would reflect a higher brain activation when there is more
Simon conflict, and a negative modulation effect would reflect a higher brain
activation for more spatial Stroop conflict. To avoid confusion, we converted the
modulation effect of spatial Stroop to positive by using a contrast of $[-(I\_pm -$
$C\_pm)]$ throughout the results presentation. Results were corrected with the
probabilistic threshold-free cluster enhancement (pTFCE) and then thresholded by
3dClustSim function in AFNI (Cox & Hyde, 1997) with voxel-wise $p < .001$ and
cluster-wize $p < .05$, both 1-tailed. To visualize the parametric modulation effects, we
conducted a similar GLM (GLM2), except we used incongruent and congruent
conditions from each conflict type as separate regressors with no parametric
modulation. Then we extracted beta coefficients for each regressor and each
participant with regions observed in GLM1 as regions of interest, and finally got the
incongruent−congruent contrasts for each conflict type at the individual level. We
reported the results in Fig. 3, Table S1, and Fig. S3. Visualization of the uni-voxel
results was made by the MRIcron
(https://www.mccauslandcenter.sc.edu/mricro/mricron/).
The GLM3 aimed to prepare for the representational similarity analysis (see
below). There were several differences compared to GLM1. The unsmoothed
functional images after preprocessing were used. This model included 20 event-
related regressors, one for each of the 5 (conflict type) × 2 (congruency condition) × 2
(arrow direction) conditions. The event-related nuisance regressors were similar to
GLM1, but with additional regressors of response repetition and post-error trials to
account for the nuisance inter-trial effects. To fully expand the variance, we
conducted one GLM analysis for each run. After this procedure, a voxel-wise fMRI
activation map was obtained per condition, run and subject.

Representational similarity analysis (RSA)

To measure the neural representation of conflict similarity, we adopted the RSA.
RSAs were conducted on each of the 360 cortical regions of a volumetric version of
the MMP cortical atlas (Glasser et al., 2016). To de-correlate the factors of conflict
type and orientation of stimulus location, we leveraged the between-subject
manipulation of stimulus locations and conducted RSA in a cross-subject fashion

(Fig. 4). Previous studies (e.g., J. Chen et al., 2017) have demonstrated that consistent multi-voxel activation patterns exist across individuals, and successful applications of cross-subject RSA (see review by Freund, Etzel, et al., 2021) and cross-subject decoding approaches (Jiang et al., 2016; Tusche et al., 2016) have also been reported. The beta estimates from GLM3 were noise-normalized by dividing the original beta coefficients by the square root of the covariance matrix of the error terms (Nili et al., 2014). For each cortical region, we calculated the Pearson's correlations between fMRI activity patterns for each run and each subject, yielding a 1400 (20 conditions × 2 runs × 35 participants) × 1400 RSM. The correlations were calculated in a cross-voxel manner using the fMRI activation maps obtained from GLM3 described in the previous section. We excluded within-subject cells from the RSM (thus also excluding the within-run similarity as suggested by Walther et al., (2016)), and the remaining cells were converted into a vector, which was then z-transformed and submitted to a linear mixed effect model as the dependent variable. The linear mixed effect model also included regressors of conflict similarity and orientation similarity. Importantly, conflict similarity was based on how Simon and spatial Stroop conflicts are combined and hence was calculated by first rotating all subject's stimulus location to the top-right and bottom-left quadrants, whereas orientation was calculated using original stimulus locations. As a result, the regressors representing conflict similarity and orientation similarity were de-correlated (Fig. 4A). Similarity between two conditions was measured as the cosine value of the angular difference. Other regressors included a target similarity regressor (i.e., whether the arrow directions were identical), a response similarity regressor (i.e., whether the correct responses were identical); a spatial Stroop distractor regressor (i.e., vertical distance between two stimulus locations); a Simon distractor regressor (i.e., horizontal distance between two stimulus locations). Additionally, we also included a regressor denoting the similarity of Group (i.e., whether two conditions are within the same subject group, according to the stimulus-response mapping). We also added two regressors including ROI-mean fMRI activations for each condition of the pair to remove the possible uni-voxel influence on the RSM. A last term was the intercept. To control the artefact due to dependence of the correlation pairs sharing the same subject, we included crossed random effects (i.e., row-wise and column-wise random effects) for the intercept, conflict similarity, orientation and the group factors (G. Chen et al., 2017). Individual effects for each regressor were also extracted from the model for brain-behavioral correlation analyses. In brain-behavioral analyses, only the RT was used as behavioral measure to be consistent with the fMRI results, where the error trials were regressed out.

The statistical significance of these beta estimates was based on the outputs of the mixed-effect model estimated with the "fitlme" function in Matlab 2022a. We adjusted the t and p values with the degrees of freedom calculated through the Satterthwaite approximation method (Satterthwaite, 1946). Of note, this approach was applied to all the mixed-effect model analyses in this study. Multiple comparison correction was applied with the Bonferroni approach across all cortical regions at the $p < 0.05$ level. To test if the representation strengths are different between congruent

and incongruent conditions, we also conducted the RSA using only congruent
(RDM_C) and incongruent (RDM_I) trials separately. The contrast analysis was
achieved by an additional model with both RDM_C and RDM_I included, adding the
congruency and the interaction between conflict type (and orientation) and
congruency as both fixed and random factors. The difference between incongruent
and congruent representations was indicated by a significant interaction effect. To
visualize the difference, we plotted the effect-related patterns (the predictor multiplied
by the slope, plus the residual) as a function of the similarity levels (Fig. 5D), and a
summary RSM for incongruent and congruent conditions, respectively (Fig. S4).

Model comparison and representational dimensionality

To estimate if the right 8C specifically encodes the cognitive space, rather than the
domain-general or domain-specific structures, we conducted two more RSAs. We
replaced the cognitive space-based conflict similarity matrix in the RSA we reported
above (hereafter referred to as the Cognitive-Space model) with one of the alternative
model matrices, with all other regressors equal. The domain-general model treats each
conflict type as equivalent, so each two conflict types only differ in the magnitude of
their conflict. Therefore, we defined the domain-general matrix as the absolute
difference in their congruency effects indexed by the group-averaged RT in
Experiment 2. Then the z-scored model vector was sign-flipped to reflect similarity
instead of distance. The domain-specific model treats each conflict type differently, so
we used a diagonal matrix, with within-conflict type similarities being 1 and all cross-
conflict type similarities being 0.
To better capture the dimensionality of the representational space, we estimated
its dimensionality using the participation ratio (Ito & Murray, 2023). Since we
excluded the within-subject cells from the whole RSM, the whole RSM is an
incomplete matrix and could not be used. To resolve this issue, we averaged the cells
corresponding to each pair of conflict types to obtain an averaged 5×5 RSM matrix,
similar to the matrix shown in Fig. 1C. We then estimated the participation ratio using
the formula:

$$\text{dim} = \frac{\left(\sum_i^m \lambda_i\right)^2}{\sum_i^m \lambda_i^2},$$

where λ_i is the eigenvalue of the RSM and m is the number of eigenvalues.

Representational connectivity analysis

To explore the possible relevance between the conflict type and the orientation
effects, we conducted representational connectivity (Kriegeskorte et al., 2008)
between regions showing evidence encoding conflict similarity and orientation
similarity. We hypothesized that this relationship should exist at the within-subject
level, so we conducted this analysis using within-subject RSMs excluding the
diagonal. Specifically, the z-transformed RSM vector of each region were extracted
and submitted to a mixed linear model, with the RSM of the conflict type region (i.e.,
the right 8C) as the dependent variable, and the RSM of one of the orientation regions

(e.g., right V2) as the predictor. Intercept and the slope of the regressor were set as
random effects at the subject level. The mixed effect model was conducted for each
pair of regions, respectively. Considering there might be strong intrinsic correlations
across the RSMs induced by the nuisance factors, such as the within-subject
similarity, we added two sets of regions as control. First, we selected regions without
showing any effects of interest (i.e., uncorrected $ps > 0.3$ for all the conflict type,
orientation, congruency, target, response, spatial Stroop distractor and Simon
distractor effects). Second, we selected regions of orientation effect meeting the first
but not the second criterion, to account for the potential correlation between regions
of the two partly orthogonal regressors (Fig. 4A). Regions adjacent to the orientation
regions were excluded to avoid the inherent strong similarity they may share.
Existence of representational connectivity was defined by a connectivity slope higher
than 95% of the standard error above the mean of any control region.
1022

1023 **Acknowledgement**

1024 We thank Eliot Hazeltine for valuable comments on a previous version of this
1025 manuscript. The work was supported by the National Natural Science Foundation of
1026 China and the German Research Foundation (NSFC 62061136001/DFG TRR-169) to
1027 X.L. and China Postdoctoral Science Foundation (2019M650884) to G.Y.
1028

Reference

Abrahamse, E., Braem, S., Notebaert, W., & Verguts, T. (2016). Grounding cognitive
control in associative learning. *Psychological Bulletin*, *142*(7), 693-728.
https://doi.org/10.1037/bul0000047
Akcay, C., & Hazeltine, E. (2011). Domain-specific conflict adaptation without
feature repetitions. *Psychonomic Bulletin & Review*, *18*(3), 505-511.
https://doi.org/10.3758/s13423-011-0084-y
Assem, M., Glasser, M. F., Van Essen, D. C., & Duncan, J. (2020). A Domain-
General Cognitive Core Defined in Multimodally Parcellated Human Cortex.
Cerebral Cortex, *30*(8), 4361-4380. https://doi.org/10.1093/cercor/bhaa023
Badre, D., Bhandari, A., Keglovits, H., & Kikumoto, A. (2021). The dimensionality
of neural representations for control. *Curr Opin Behav Sci*, *38*, 20-28.
https://doi.org/10.1016/j.cobeha.2020.07.002
Behrens, T. E. J., Muller, T. H., Whittington, J. C. R., Mark, S., Baram, A. B.,
Stachenfeld, K. L., & Kurth-Nelson, Z. (2018). What Is a Cognitive Map?
Organizing Knowledge for Flexible Behavior. *Neuron*, *100*(2), 490-509.
https://doi.org/10.1016/j.neuron.2018.10.002
Bellmund, J. L. S., Gardenfors, P., Moser, E. I., & Doeller, C. F. (2018). Navigating
cognition: Spatial codes for human thinking. *Science (New York, N.Y.)*,
362(6415). https://doi.org/10.1126/science.aat6766

Benjamini, Y., & Hochberg, Y. (1995). Controlling the False Discovery Rate - a
Practical and Powerful Approach to Multiple Testing. *Journal of the Royal*
Statistical Society Series B-Statistical Methodology, *57*(1), 289-300.
https://doi.org/DOI 10.1111/j.2517-6161.1995.tb02031.x
Blake, K. R., & Gangestad, S. (2020). On Attenuated Interactions, Measurement
Error, and Statistical Power: Guidelines for Social and Personality Psychologists.
Pers Soc Psychol Bull, *46*(12), 1702-1711.
https://doi.org/10.1177/0146167220913363
Botvinick, M. M., Cohen, J. D., & Carter, C. S. (2004). Conflict monitoring and
anterior cingulate cortex: an update. *Trends in Cognitive Sciences*, *8*(12), 539-
546. https://doi.org/10.1016/j.tics.2004.10.003
Braem, S., Abrahamse, E. L., Duthoo, W., & Notebaert, W. (2014). What determines
the specificity of conflict adaptation? A review, critical analysis, and proposed
synthesis. *Frontiers in Psychology*, *5*, 1134.
https://doi.org/10.3389/fpsyg.2014.01134
Braem, S., Bugg, J. M., Schmidt, J. R., Crump, M. J. C., Weissman, D. H., Notebaert,
W., & Egner, T. (2019). Measuring Adaptive Control in Conflict Tasks. *Trends in*
Cognitive Sciences, *23*(9), 769-783. https://doi.org/10.1016/j.tics.2019.07.002
Chen, G., Taylor, P. A., Shin, Y.-W., Reynolds, R. C., & Cox, R. W. J. N. (2017).
Untangling the relatedness among correlations, Part II: Inter-subject correlation
group analysis through linear mixed-effects modeling. *147*, 825-840.
Chen, J., Leong, Y. C., Honey, C. J., Yong, C. H., Norman, K. A., & Hasson, U.
(2017). Shared memories reveal shared structure in neural activity across
individuals. *Nature Neuroscience*, *20*(1), 115-125.
https://doi.org/10.1038/nn.4450
Cole, M. W., Reynolds, J. R., Power, J. D., Repovs, G., Anticevic, A., & Braver, T. S.
(2013). Multi-task connectivity reveals flexible hubs for adaptive task control.
Nature Neuroscience, *16*(9), 1348-1355. https://doi.org/10.1038/nn.3470
Constantinescu, A. O., O'Reilly, J. X., & Behrens, T. E. J. (2016). Organizing
conceptual knowledge in humans with a gridlike code. *Science (New York, N.Y.)*,
352(6292), 1464-1468. https://doi.org/10.1126/science.aaf0941
Cosmides, L., & Tooby, J. (1994). Origins of domain specificity: The evolution of
functional organization. In L. A. Hirschfeld & S. A. Gelman (Eds.), *Mapping the*
mind: Domain specificity in cognition and culture (Vol. 853116). Cambridge
University Press.
Cox, R. W., & Hyde, J. S. (1997). Software tools for analysis and visualization of
fMRI data. *NMR in Biomedicine*, *10*(4-5), 171-178.
https://doi.org/10.1002/(sici)1099-1492(199706/08)10:4/5<171::Aid-
nbm453>3.0.Co;2-l
Dagher, A., Owen, A. M., Boecker, H., & Brooks, D. J. (1999). Mapping the network
for planning: a correlational PET activation study with the Tower of London task.
Brain, *122 (Pt 10)*, 1973-1987. https://doi.org/10.1093/brain/122.10.1973

Duncan, J. (2010). The multiple-demand (MD) system of the primate brain: mental
programs for intelligent behaviour. *Trends in Cognitive Sciences*, *14*(4), 172-179.
https://doi.org/10.1016/j.tics.2010.01.004
Duncan, J. (2013). The structure of cognition: attentional episodes in mind and brain.
Neuron, *80*(1), 35-50. https://doi.org/10.1016/j.neuron.2013.09.015
Durnez, J., Blair, R., & Poldrack, R. A. (2018). Neurodesign: Optimal Experimental
Designs for Task fMRI. *bioRxiv*, 119594. https://doi.org/10.1101/119594
Egner, T. (2007). Congruency sequence effects and cognitive control. *Cognitive,*
Affective & Behavioral Neuroscience, *7*(4), 380-390.
https://doi.org/10.3758/cabn.7.4.380
Egner, T. (2008). Multiple conflict-driven control mechanisms in the human brain.
Trends in Cognitive Sciences, *12*(10), 374-380.
https://doi.org/10.1016/j.tics.2008.07.001
Egner, T., Delano, M., & Hirsch, J. (2007). Separate conflict-specific cognitive
control mechanisms in the human brain. *NeuroImage*, *35*(2), 940-948.
https://doi.org/10.1016/j.neuroimage.2006.11.061
Esteban, O., Markiewicz, C. J., Blair, R. W., Moodie, C. A., Isik, A. I., Erramuzpe,
A., . . . Gorgolewski, K. J. (2019). fMRIPrep: a robust preprocessing pipeline for
functional MRI. *Nature Methods*, *16*(1), 111-116. https://doi.org/10.1038/s41592-
018-0235-4
Flesch, T., Juechems, K., Dumbalska, T., Saxe, A., & Summerfield, C. (2022).
Orthogonal representations for robust context-dependent task performance in
brains and neural networks. *Neuron*. https://doi.org/10.1016/j.neuron.2022.01.005
Freitas, A. L., Bahar, M., Yang, S., & Banai, R. (2007). Contextual adjustments in
cognitive control across tasks. *Psychological Science*, *18*(12), 1040-1043.
https://doi.org/10.1111/j.1467-9280.2007.02022.x
Freitas, A. L., & Clark, S. L. (2015). Generality and specificity in cognitive control:
conflict adaptation within and across selective-attention tasks but not across
selective-attention and Simon tasks. *Psychological Research*, *79*(1), 143-162.
https://doi.org/10.1007/s00426-014-0540-1
Freund, M. C., Bugg, J. M., & Braver, T. S. (2021). A Representational Similarity
Analysis of Cognitive Control during Color-Word Stroop. *Journal of*
Neuroscience, *41*(35), 7388-7402. https://doi.org/10.1523/JNEUROSCI.2956-
20.2021
Freund, M. C., Etzel, J. A., & Braver, T. S. (2021). Neural Coding of Cognitive
Control: The Representational Similarity Analysis Approach. *Trends in Cognitive*
Sciences, *25*(7), 622-638. https://doi.org/10.1016/j.tics.2021.03.011
Friehs, M. A., Klaus, J., Singh, T., Frings, C., & Hartwigsen, G. (2020). Perturbation
of the right prefrontal cortex disrupts interference control. *NeuroImage*, *222*,
117279. https://doi.org/10.1016/j.neuroimage.2020.117279
Fu, Z., Beam, D., Chung, J. M., Reed, C. M., Mamelak, A. N., Adolphs, R., &
Rutishauser, U. (2022). The geometry of domain-general performance monitoring
in the human medial frontal cortex. *Science (New York, N.Y.)*, *376*(6593),
eabm9922. https://doi.org/10.1126/science.abm9922

Gilbert, C. D., & Li, W. (2013). Top-down influences on visual processing. *Nat Rev Neurosci*, *14*(5), 350-363. https://doi.org/10.1038/nrn3476

Glasser, M. F., Coalson, T. S., Robinson, E. C., Hacker, C. D., Harwell, J., Yacoub, E., . . . Van Essen, D. C. (2016). A multi-modal parcellation of human cerebral cortex. *Nature*, *536*(7615), 171-178. https://doi.org/10.1038/nature18933

Gorgolewski, K., Burns, C. D., Madison, C., Clark, D., Halchenko, Y. O., Waskom, M. L., & Ghosh, S. S. (2011). Nipype: a flexible, lightweight and extensible neuroimaging data processing framework in python. *Front Neuroinform*, *5*, 13. https://doi.org/10.3389/fninf.2011.00013

Grahek, I., Leng, X., Fahey, M. P., Yee, D., & Shenhav, A. (2022). Empirical and Computational Evidence for Reconfiguration Costs During Within-Task Adjustments in Cognitive Control. Proceedings of the Annual Meeting of the Cognitive Science Society,

Grahek, I., Leng, X., Musslick, S., & Shenhav, A. (2023). Control adjustment costs limit goal flexibility: Empirical evidence and a theoretical account. *bioRxiv*. https://doi.org/10.1101/2023.08.22.554296

Hazeltine, E., Lightman, E., Schwarb, H., & Schumacher, E. H. (2011). The boundaries of sequential modulations: evidence for set-level control. *Journal of Experimental Psychology: Human Perception and Performance*, *37*(6), 1898-1914. https://doi.org/10.1037/a0024662

Hommel, B., Proctor, R. W., & Vu, K. P. (2004). A feature-integration account of sequential effects in the Simon task. *Psychological Research*, *68*(1), 1-17. https://doi.org/10.1007/s00426-003-0132-y

Ito, T., & Murray, J. D. (2023). Multitask representations in the human cortex transform along a sensory-to-motor hierarchy. *Nat Neurosci*, *26*(2), 306-315. https://doi.org/10.1038/s41593-022-01224-0

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved Optimization for the Robust and Accurate Linear Registration and Motion Correction of Brain Images. *NeuroImage*, *17*(2), 825-841. https://doi.org/10.1006/nimg.2002.1132

Jiang, J., & Egner, T. (2014). Using neural pattern classifiers to quantify the modularity of conflict-control mechanisms in the human brain. *Cereb Cortex*, *24*(7), 1793-1805. https://doi.org/10.1093/cercor/bht029

Jiang, J., Summerfield, C., & Egner, T. (2016). Visual Prediction Error Spreads Across Object Features in Human Visual Cortex. *J Neurosci*, *36*(50), 12746-12763. https://doi.org/10.1523/JNEUROSCI.1546-16.2016

Jiang, J., Wang, S. F., Guo, W., Fernandez, C., & Wagner, A. D. (2020). Prefrontal reinstatement of contextual task demand is predicted by separable hippocampal patterns. *Nat Commun*, *11*(1), 2053. https://doi.org/10.1038/s41467-020-15928-z

Kan, I. P., Teubner-Rhodes, S., Drummey, A. B., Nutile, L., Krupa, L., & Novick, J. M. (2013). To adapt or not to adapt: the question of domain-general cognitive control. *Cognition*, *129*(3), 637-651. https://doi.org/10.1016/j.cognition.2013.09.001

Kikumoto, A., & Mayr, U. (2020). Conjunctive representations that integrate stimuli,
responses, and rules are critical for action selection. *Proc Natl Acad Sci U S A*,
117(19), 10603-10608. https://doi.org/10.1073/pnas.1922166117

Kim, C., Chung, C., & Kim, J. (2012). Conflict adjustment through domain-specific
multiple cognitive control mechanisms. *Brain Research*, *1444*, 55-64.
https://doi.org/10.1016/j.brainres.2012.01.023

Kornblum, S., Hasbroucq, T., & Osman, A. (1990). Dimensional overlap: cognitive
basis for stimulus-response compatibility--a model and taxonomy. *Psychological
Review*, *97*(2), 253-270. https://doi.org/10.1037/0033-295x.97.2.253

Kriegeskorte, N., Mur, M., & Bandettini, P. (2008). Representational similarity
analysis - connecting the branches of systems neuroscience. *Front Syst Neurosci*,
2, 4. https://doi.org/10.3389/neuro.06.004.2008

Li, Q., Nan, W., Wang, K., & Liu, X. (2014). Independent processing of stimulus-
stimulus and stimulus-response conflicts. *PloS One*, *9*(2), e89249.
https://doi.org/10.1371/journal.pone.0089249

Li, Q., Yang, G., Li, Z., Qi, Y., Cole, M. W., & Liu, X. (2017). Conflict detection and
resolution rely on a combination of common and distinct cognitive control
networks. *Neuroscience and Biobehavioral Reviews*, *83*, 123-131.
https://doi.org/10.1016/j.neubiorev.2017.09.032

Liu, X., Banich, M. T., Jacobson, B. L., & Tanabe, J. L. (2004). Common and distinct
neural substrates of attentional control in an integrated Simon and spatial Stroop
task as assessed by event-related fMRI. *NeuroImage*, *22*(3), 1097-1106.
https://doi.org/10.1016/j.neuroimage.2004.02.033

Liu, X., Park, Y., Gu, X., & Fan, J. (2010). Dimensional overlap accounts for
independence and integration of stimulus-response compatibility effects.
Attention, Perception, & Psychophysics, *72*(6), 1710-1720.
https://doi.org/10.3758/APP.72.6.1710

Lu, C. H., & Proctor, R. W. (1995). The influence of irrelevant location information
on performance: A review of the Simon and spatial Stroop effects. *Psychonomic
Bulletin & Review*, *2*(2), 174-207. https://doi.org/10.3758/BF03210959

MacDowell, C. J., Tafazoli, S., & Buschman, T. J. (2022). A Goldilocks theory of
cognitive control: Balancing precision and efficiency with low-dimensional
control states. *Curr Opin Neurobiol*, *76*, 102606.
https://doi.org/10.1016/j.conb.2022.102606

MacLeod, C. M. (1991). Half a century of research on the Stroop effect: an integrative
review. *Psychological Bulletin*, *109*(2), 163-203.
http://www.ncbi.nlm.nih.gov/pubmed/2034749

Magen, H., & Cohen, A. (2007). Modularity beyond perception: evidence from single
task interference paradigms. *Cognitive Psychology*, *55*(1), 1-36.
https://doi.org/10.1016/j.cogpsych.2006.09.003

Mansouri, F. A., Buckley, M. J., & Tanaka, K. (2007). Mnemonic function of the
dorsolateral prefrontal cortex in conflict-induced behavioral adjustment. *Science
(New York, N.Y.)*, *318*(5852), 987-990. https://doi.org/10.1126/science.1146384

Marr, D. (1982). *Vision: A Computational Investigation into the Human*
Representation and Processing of Visual Information. Henry Holt and Co., Inc.
Miller, E. K., & Cohen, J. D. (2001). An integrative theory of prefrontal cortex
function. *Annual Review of Neuroscience*, *24*(1), 167-202.
https://doi.org/10.1146/annurev.neuro.24.1.167
Milner, B. (1963). Effects of Different Brain Lesions on Card Sorting - Role of
Frontal Lobes. *Archives of Neurology*, *9*(1), 90-&. https://doi.org/DOI
10.1001/archneur.1963.00460070100010
Musslick, S., & Cohen, J. D. (2021). Rationalizing constraints on the capacity for
cognitive control. *Trends Cogn Sci*, *25*(9), 757-775.
https://doi.org/10.1016/j.tics.2021.06.001
Nili, H., Wingfield, C., Walther, A., Su, L., Marslen-Wilson, W., & Kriegeskorte, N.
(2014). A toolbox for representational similarity analysis. *PLoS Comput Biol*,
10(4), e1003553. https://doi.org/10.1371/journal.pcbi.1003553
Niv, Y. (2019). Learning task-state representations. *Nat Neurosci*, *22*(10), 1544-1553.
https://doi.org/10.1038/s41593-019-0470-8
Park, S. A., Miller, D. S., Nili, H., Ranganath, C., & Boorman, E. D. (2020). Map
Making: Constructing, Combining, and Inferring on Abstract Cognitive Maps.
Neuron, *107*(6), 1226-1238 e1228. https://doi.org/10.1016/j.neuron.2020.06.030
Peterson, B. S., Kane, M. J., Alexander, G. M., Lacadie, C., Skudlarski, P., Leung, H.
C., . . . Gore, J. C. (2002). An event-related functional MRI study comparing
interference effects in the Simon and Stroop tasks. *Brain Research: Cognitive*
Brain Research, *13*(3), 427-440. https://doi.org/10.1016/s0926-6410(02)00054-x
Polk, T. A., Drake, R. M., Jonides, J. J., Smith, M. R., & Smith, E. E. (2008).
Attention enhances the neural processing of relevant features and suppresses the
processing of irrelevant features in humans: a functional magnetic resonance
imaging study of the Stroop task. *Journal of Neuroscience*, *28*(51), 13786-13792.
https://doi.org/10.1523/JNEUROSCI.1026-08.2008
Reverberi, C., Gorgen, K., & Haynes, J. D. (2012). Compositionality of rule
representations in human prefrontal cortex. *Cereb Cortex*, *22*(6), 1237-1246.
https://doi.org/10.1093/cercor/bhr200
Ritz, H., & Shenhav, A. (2022). Humans reconfigure target and distractor processing
to address distinct task demands. *bioRxiv*, 2021.2009. 2008.459546.
https://doi.org/10.1101/2021.09.08.459546
Ritz, H., & Shenhav, A. (2023). Orthogonal neural encoding of targets and distractors
supports multivariate cognitive control.
https://doi.org/10.1101/2022.12.01.518771
Rmus, M., Ritz, H., Hunter, L. E., Bornstein, A. M., & Shenhav, A. (2022). Humans
can navigate complex graph structures acquired during latent learning. *Cognition*,
225, 105103. https://doi.org/10.1016/j.cognition.2022.105103
Satterthwaite, F. E. (1946). An Approximate Distribution of Estimates of Variance
Components. *Biometrics Bulletin*, *2*(6). https://doi.org/10.2307/3002019

Schmidt, J. R., & Weissman, D. H. (2014). Congruency sequence effects without
feature integration or contingency learning confounds. *PloS One*, *9*(7), e102337.
https://doi.org/10.1371/journal.pone.0102337
Schuck, N. W., Cai, M. B., Wilson, R. C., & Niv, Y. (2016). Human Orbitofrontal
Cortex Represents a Cognitive Map of State Space. *Neuron*, *91*(6), 1402-1412.
https://doi.org/10.1016/j.neuron.2016.08.019
Shenhav, A., Botvinick, M. M., & Cohen, J. D. (2013). The expected value of control:
an integrative theory of anterior cingulate cortex function. *Neuron*, *79*(2), 217-
240. https://doi.org/10.1016/j.neuron.2013.07.007
Simon, J. R., & Small, A. M., Jr. (1969). Processing auditory information:
interference from an irrelevant cue. *Journal of Applied Psychology*, *53*(5), 433-
435. https://doi.org/10.1037/h0028034
Torres-Quesada, M., Funes, M. J., & Lupianez, J. (2013). Dissociating proportion
congruent and conflict adaptation effects in a Simon-Stroop procedure. *Acta*
Psychologica, *142*(2), 203-210. https://doi.org/10.1016/j.actpsy.2012.11.015
Tusche, A., Bockler, A., Kanske, P., Trautwein, F. M., & Singer, T. (2016). Decoding
the Charitable Brain: Empathy, Perspective Taking, and Attention Shifts
Differentially Predict Altruistic Giving. *Journal of Neuroscience*, *36*(17), 4719-
4732. https://doi.org/10.1523/JNEUROSCI.3392-15.2016
Vaidya, A. R., & Badre, D. (2022). Abstract task representations for inference and
control. *Trends Cogn Sci*, *26*(6), 484-498.
https://doi.org/10.1016/j.tics.2022.03.009
Vaidya, A. R., Jones, H. M., Castillo, J., & Badre, D. (2021). Neural representation of
abstract task structure during generalization. *Elife*, *10*, 1-26.
https://doi.org/10.7554/eLife.63226
Vanderhasselt, M. A., De Raedt, R., & Baeken, C. (2009). Dorsolateral prefrontal
cortex and Stroop performance: tackling the lateralization. *Psychonomic Bulletin*
& Review, *16*(3), 609-612. https://doi.org/10.3758/PBR.16.3.609
Wager, T. D., & Nichols, T. E. (2003). Optimization of experimental design in fMRI:
a general framework using a genetic algorithm. *NeuroImage*, *18*(2), 293-309.
https://doi.org/10.1016/S1053-8119(02)00046-0
Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., & Diedrichsen, J. (2016).
Reliability of dissimilarity measures for multi-voxel pattern analysis.
Neuroimage, *137*, 188-200. https://doi.org/10.1016/j.neuroimage.2015.12.012
Wang, K., Li, Q., Zheng, Y., Wang, H., & Liu, X. (2014). Temporal and spectral
profiles of stimulus-stimulus and stimulus-response conflict processing.
NeuroImage, *89*, 280-288. https://doi.org/10.1016/j.neuroimage.2013.11.045
Wu, T., Spagna, A., Chen, C., Schulz, K. P., Hof, P. R., & Fan, J. (2020). Supramodal
Mechanisms of the Cognitive Control Network in Uncertainty Processing.
Cerebral Cortex, *30*(12), 6336-6349. https://doi.org/10.1093/cercor/bhaa189 %J
Cerebral Cortex
Yang, G., Nan, W., Zheng, Y., Wu, H., Li, Q., & Liu, X. (2017). Distinct cognitive
control mechanisms as revealed by modality-specific conflict adaptation effects.

Journal of Experimental Psychology: Human Perception and Performance,
43(4), 807-818. https://doi.org/10.1037/xhp0000351
Yang, G., Xu, H., Li, Z., Nan, W., Wu, H., Li, Q., & Liu, X. (2021). The congruency
sequence effect is modulated by the similarity of conflicts. *Journal of*
Experimental Psychology: Learning, Memory, and Cognition, *47*(10), 1705-1719.
https://doi.org/10.1037/xlm0001054
1311