A Unified Pipeline for FISH Spatial Transcriptomics

Cecilia Cisar, Nicholas Keener, Mathew Ruffalo, Benedict Paten

Abstract

In recent years, high-throughput spatial transcriptomics has emerged as a powerful tool for investigating the spatial distribution of mRNA expression and the effects it may have on cellular function. There is a lack of standardized tools for analyzing spatial transcriptomics data, leading many groups to write their own in-house tools that are often poorly documented and not generalizable to other datasets. Currently, the only publicly available tools for extracting annotated transcript locations from raw multiplexed fluorescent *in situ* hybridization (FISH) images are starfish, which is lacking in some key areas, and MERlin, which is restricted to only MERFISH data. To address this, we have expanded and improved the starfish library and used those tools to create PIPEFISH, a semi-automated and generalizable pipeline that performs transcript annotation for FISH-based spatial transcriptomics. PIPEFISH has options for image processing, decoding, and cell segmentation, and calculates quality control metrics on the output to allow the user to assess the pipeline's performance on their data. We used this pipeline to annotate transcript locations from three real datasets from three different common types of FISH image-based experiments: MERFISH, seqFISH, and targeted *in situ* sequencing (ISS), and verified that the results were high quality using the internal quality metrics of the pipeline and also a comparison to a orthogonal method of measuring RNA expression in a similar tissue sample. We have made PIPEFISH publicly available through Github for anyone interested in analyzing data from FISH-based spatial transcriptomic assays.

Background

Development of single cell RNA sequencing (scRNA-seq) over the past decade has allowed researchers to probe the heterogeneous nature of real tissue by characterizing the transcriptome of individual cells. This has led to the discovery of many new cell types and enhanced our understanding of the mechanisms of disease[1]. However, in the process of separating single cells from each other so their transcriptomes can be sequenced individually, the spatial context of each cell with the others, as well as the location of each transcript within cells, both of which contain important biological information, are lost. Spatially resolved transcriptomics methods can be used to characterize transcriptomes on a single cell level such that the spatial context of each transcript and cell is also recovered. This spatial information is incredibly useful biomedically as many diseases can be characterized by abnormal spatial patterns[2] and

in developmental biology, many vital and early processes are driven by spatial relationships between different biological factors[3] and defects in their spatial distributions can have serious consequences for the developing organism.

Named as Nature's "Method of the Year" in 2020[4] , spatially resolved transcriptomics is becoming increasingly prevalent in new published research after the first multiplexed methods were demonstrated in the mid 2010s[5,6], with new methods and discoveries being released at an ever increasing pace. The earliest spatial transcriptomics methods were based on fluorescent *in situ* hybridization (FISH) probes with specific mRNA targets which could then be imaged with a microscope[7]. These early methods were very low throughput, only targeting a handful of genes, but more recent advances in multiplexing of these methods have allowed for nearly whole transcriptome level targeting. Exposing samples to many sequential rounds of hybridization with different sets of FISH probes, called seqFISH, has been used to characterize the expression of over 10,000 different mRNA targets simultaneously and has been shown to be effective in both cell cultures[8] and in tissue samples[9]. A similar approach is used in MERFISH but with more advanced built-in error correction abilities, allowing for increased accuracy of results[10]. Another *in situ* imaging-based technique, called *in situ* sequencing (ISS), takes advantage of short read sequencing technology to image the location of mRNA targets as they are sequenced using traditional sequencing-by-synthesis technology[5]. Experiments based on this method have been able to generate spatial maps of breast cancer tumors that could be useful in clinical diagnostics of cancer patients, leading to improved patient outcomes[11].

As these spatial transcriptomics methods further improve to become higher resolution and throughput while also becoming less complex to perform, the number of researchers who wish to use them will also increase. Thus, it is also important to have available standardized methods for processing and analysis of the results from these spatial methods for the purpose of reproducibility and easy comparison of results between different research groups. Much of the analysis done for published research relies on in-house code with little documentation, making the adoption of these experiments for labs without computational members prohibitively difficult. Existence of publicly-available, open-source computational tools for analysis of spatial data will make these types of experiments more accessible for labs that wish to perform them, facilitating the generation of a larger body of spatial data.

Although some current array-based spatial transcriptomics methods have open source libraries[12,13] or bundled toolkits[14] available, FISH-based methods have significantly fewer options at their disposal[15]. Experimental apparatus must usually be assembled in-house, and most labs write their own analysis code. Starfish[16] is an open-source

Python library containing methods and data types for the processing and analysis of FISH-based spatial imaging results. It is capable of taking raw image files and outputting decoded results detailing the spatial location of each transcript, which cell it is located in and where that cell is located in the original image. These results can then be used in downstream tools such as squidPy[17] or stLearn[18]. While useful, starfish is lacking in several different areas, including requiring a large number of input parameters to carry out a full analysis, having only several basic image pre-processing tools, lacking an adequate seqFISH decoding algorithm and the absence of quality control metrics to determine the significance of the results.

We have created a universal spatial transcriptomics pipeline for FISH-based methods called PIPEFISH using the CWL (Common Workflow Language) framework and an improved version of the starfish package that includes a novel seqFISH decoding method and PoSTcode[19] as an ISS decoding option. PIPEFISH organizes the tools available in our custom starfish module into an ordered pipeline that can take raw image data from the most popular FISH-based methods and extract spatially annotated mRNA transcript counts from them. We have also developed a number of quality control metrics that can be used to assess the performance of the pipeline results. Using the pipeline, we found spatially annotated transcripts from three different in situ image datasets: seqFISH of a mouse embryo, targeted ISS in a mouse brain, and MERFISH of human U2-OS cells, and used both the internal QC metrics and an external metric to show that our results are high quality.

Results

A General Spacetx Pipeline

Figure 1: Overall schematic of processing pipeline.
The workflow divides the processing into multiple discrete steps. (1) Raw images are optionally sorted into pseudorounds and pseudochannels, then converted to the standardized SpaceTx format (**Methods**). (2) Images undergo pre-processing such as registration, white tophat filtering, high-pass and low-pass Gaussian filters, and histogram matching. (3) Transcripts are identified within each image and listed in a table with (x,y,z) coordinate information. (4) If cell images are provided, cell boundaries are identified and transcripts are assigned a cell ID number. (5) QC metrics for the experiment results and processing are calculated from the decoded output.

We have developed PIPEFISH, a general pipeline to extract transcript locations from the raw results of a FISH experiment (**Figure 1**). Input can be accepted in many forms, so long as images are validly encoded tiffs and a codebook describing the expected transcripts is provided. The codebook is expected to have transcript names and their paired "barcodes", which is the list of imaging round and color channel combinations where the transcript is expected to fluoresce. Barcodes can be encoded in a number of ways and still be used within the pipeline, such as linearly multiplexed, one-hot exponentially multiplexed, or exponentially multiplexed. Additional information can be provided in a configuration json file with experimental design details, such as the hamming distance between barcodes if the experiment was designed such that incomplete barcodes can be recovered during decoding.

The configuration json file can also include parameters for running image processing, such as detailing which auxiliary views (if any) should be used for image registration or subtracted from the primary views as a background. Other tunable parameters for image processing, such as the kernel radius for rolling ball background subtraction or a white tophat filter, can also be specified.

There are two primary types of image decoding, pixel-based and spot-based. The pixel-based method treats each intensity at a given (x,y,z) location as a value in a vector across all rounds and channels, and then assigns the barcode (if any) most likely to match that vector. The spot-based method first identifies spots in the image as local intensity peaks, and then applies one of several "decoding" methods to predict which spot locations correspond to transcripts.

Transcripts can then be assigned cell ids by applying a segmentation mask. There are naive methods included to generate a mask from a provided auxiliary view, using either thresholding and watershed or transcript-density based cell approximation. External masks, such as those produced by Fiji or Ilastik, can also be imported.

Should troubleshooting of an individual step be needed, the pipeline has been configured to allow for each step to be run individually from prior output and the same json configuration file. We hope to address the needs of all FISH experiments in this comprehensive and simple-to-use pipeline.

An Improved seqFISH Decoder

We found that starfish decoding of seqFISH spots using starfish's decoding methods consistently produced far fewer mRNA targets than expected, which can reduce the accuracy of many downstream analyses. This is a result of the starfish's seqFISH decoders requiring that spots must be at least mutual nearest neighbors of each other to be connected into a barcode, which is very sensitive to spot-drift, a common problem in seqFISH experiments with high numbers of hybridizations. To address this, we developed the CheckAll decoder which considers all possible spot combinations that could form barcodes and chooses the best non-overlapping set (**Figure S1**).

The CheckAll decoder checks all possible barcodes that could be formed from the given spot set and chooses those most likely to represent true mRNA targets (**Methods**). It is based on the method used by the original seqFISH authors[20] but features some improvements and an additional option that allows for adjustment of the precision/recall tradeoff. This "mode" parameter can take three different values and controls this tradeoff by setting several parameters that are not under user control with high accuracy mode

resulting in higher precision but lower recall, low accuracy mode having lower precision but higher recall and the medium accuracy mode falling somewhere between. Also, unlike the current starfish decoders, the CheckAll decoder is capable of decoding error-corrected barcodes. If each barcode used has a hamming distance of at least two from every other code they can be uniquely identified even without a complete barcode. These error-corrected transcripts found with an incomplete barcode are less accurate (more prone to false positives) than those decoded with complete barcodes but can significantly increase recall if that is preferred.

Cell Segmentation

Segmentation of the cell boundaries in FISH images and assignment of transcripts to individual cells is a crucial step that is required for most cell-level downstream analyses. There are a number of tools that have been developed to address this difficult problem such as CellProfiler[21], Baysor[22], SPARCLE[23] and others, all of which are capable of producing a labeled image of cell segmentation masks that can be uploaded to the pipeline directly. Alternatively, the pipeline offers some cell segmentation tools based on basic thresholding and watersheds that may be used to achieve an initial segmentation of 2D images without resorting to additional tools (**Methods**). This requires a DAPI image (or other nuclei segmentation image) be provided and offers several options and filters for segmentation. The nuclei can be segmented alone or the cytoplasm can also be segmented using a combination of the nuclei image and the decoded transcript distribution. There is also a useful optional filter that can be used to remove cells with overlapping nuclei as the boundary between them becomes difficult to determine due to their proximity making the accuracy of such segmentation calls questionable.

We evaluated the ability of our segmentation tools to segment nuclei images using simulated nuclei images (**Methods**) (**Figure S2**). Across different clustering probabilities and signal-to-noise (SNR) ratios, the pipeline segmentation produces very consistent results with an average recall of 0.98, indicating that all the nuclei are being found and that they are being separated properly. The precision of the pipeline segmentation is lower, with an average value of 0.72 across conditions, though this is primarily due to over-segmentation of each otherwise correctly segmented nucleus, resulting in each nucleus appearing larger than in the truth set. This is a minor problem for segmentation as the high recall shows that this over-segmentation does not result in mis-segmentation of the nuclei. A summary of the results from each condition is shown in **Table 1**.

	c00 high SNR	c00 low SNR	c25 high SNR	c25 low SNR	c50 high SNR	c50 low SNR	c75 high SNR	c75 low SNR
Recall	0.992	0.996	0.985	0.990	0.979	0.984	0.974	0.970
Precision	0.679	0.643	0.737	0.714	0.743	0.753	0.771	0.746

Table 1: Segmentation Validation. Precision/recall statistics for pipeline segmentation of simulated images across multiple clustering probabilities (c00, c25, c50, and c75 where c00 has the lowest clustering probability and c75 the highest) and both high and low SNRs.

Quality Control Metrics

In order to provide qualitative confidence in the results from this pipeline, we defined a set of internal quality control metrics that can be applied to the vast majority of experiment types. These QC results are automatically generated during a pipeline run, and provide a variety of statistics and graphs for each provided field of view (**Figure S5**). Some of these results rely on "blank" barcodes that do not correspond to actual experimental probes included; This can be added to the codebook manually or inserted automatically during the pipeline's initial conversion step. Blank barcodes are treated identically to normal barcodes during decoding and are regarded as false positives in the QC step, something that has been experimentally verified to be functionally identical to including false-positive probes that do not match any transcripts. We have found that these blank-based metrics are particularly useful for directly comparing sets of results (**Figure S3**).

Pipeline Performance on Real FISH Datasets

To show that the tools we have built are capable of obtaining high quality results from a variety of FISH experiment types, we used them to extract spatially localized mRNA molecules from three different FISH experiments, each of a different type: seqFISH of a mouse embryo[9] (**Figure S4a**), targeted ISS of a mouse brain[19] (**Figure S4b**), and MERFISH of human U2-OS cells[24] (**Figure S4c)** and calculated both internal and external quality control metrics to evaluate performance. All images were either downloaded from a public database or shared with us by the original authors.

Internal Quality Check

For each dataset we initially evaluated performance using the internal QC metrics produced by the pipeline. One set of metrics that can be useful for all datasets are those

that estimate the background signal through the quantification of 'blank' barcodes inserted into the provided codebook. While this method is beholden to how densely packed the codebook is, it provides insight into the estimated false positive rate of the experiment, which single handedly can be criteria to rerun the experiment. Our results show that true "on-target" barcodes are found at a significantly higher frequency than the blank "off-target" codes (**Figure 2**), indicating that there are likely to be few false positive transcripts in these results. Additional metrics for each dataset are shown in **Figure S5.**

Figure 2: Quality control figures highlighting false-positive 'blank' barcodes from pipeline output across all FOVs of each dataset. a) Total counts of each barcode, fraction of recovered barcodes that used error correction are colored in orange for

blanks and green for true barcodes. Proposed minimum barcode count threshold is calculated as the upper end of the 95% confidence interval of a normal distribution with the mean and standard deviation of the observed blank tallies. This is calculated for all barcodes (dashed) and uncorrected barcodes (solid) b) Transcript count per cell, with the same color scheme as (a). Median transcript count per cell for ISS, seqFISH, and MERFISH. EC = error-corrected, NC = non-corrected.

Additionally, we verified that the novel CheckAll decoder we developed outperforms the native decoders from starfish. We only compare results from starfish's NearestNeighbor decoding method as the ExactMatch method could only find a handful of targets in our images. Performance was evaluated using the false barcode metric to show that the CheckAll decoder was less prone to false positives while also finding more mRNA targets (**Figure S6** and **Table 2**). The cost for this increase in performance compared to the starfish decoders comes in the form of increased run times and memory requirements. While the starfish decoders are nearly instantaneous and require very little memory, the CheckAll decoder can take many times longer and require more memory to return results depending on the input (**Figure S7**). The CheckAll decoder is capable of taking advantage of Python multiprocessing features in order to mitigate the long run times at the cost of additional memory.

	starfish NN	CA - high	CA - high (% difference)	CA - medium	CA - medium (% difference)	CA - low	CA - low (% difference)
Precision (NC)	0.942	0.972	+3.13%	0.947	+0.53%	0.927	-1.61%
Total On-Target (NC)	1.03×10^6	1.77×10^6	+52.86%	2.02×10^6	+64.92%	2.15×10^6	+70.44%
Precision (NC+EC)	0.942	0.931	-1.17%	0.874	-7.49%	0.858	-9.33%
Total On-Target (NC+EC)	1.03×10^6	2.63×10^6	+87.43%	3.48×10^6	+108.65%	3.57×10^6	+110.44%

Table 2: Summary of CheckAll Decoder Performance. NN = NearestNeighbor, CA = CheckAll, NC = not corrected, EC = error-corrected. starfish NN, CA - high, CA - medium, and CA - low columns show precision and total on-target counts for the starfish NearestNeighbor decoder, CheckAll decoder (high accuracy mode), CheckAll decoder (medium accuracy mode), and CheckAll decoder (low accuracy mode) respectively. Percent difference columns show the performance difference between the starfish NearestNeighbor decoder and the CheckAll decoder for each accuracy mode. The starfish NearestNeighbor decoder is not capable of detecting error-corrected targets so NC and NC+EC values are identical.

External Quality Check

In addition to the internal metrics shown, we validated the results given by the pipeline using a form of orthogonal validation for each dataset. For the mouse embryo seqFISH dataset, in addition to the 351 genes measured by seqFISH there were an additional 36 genes imaged by smFISH that were used to verify predicted expression of genes not measured by seqFISH. This was done by matching each seqFISH cell with one or more similar scRNA-seq cells using the seqFISH gene set and assuming the expression of unmeasured genes will also be similar in those closely matching cells[9]. To achieve high accuracy matching and prediction of unmeasured genes, the seqFISH counts must be accurate and so we can use the accuracy of the predicted expression, using the smFISH counts as a truth set, as a quality metric to assess the performance of the pipeline at identifying transcripts in the images. We used the Python package Tangram[25] to predict expression per cell for the 36 genes measured by smFISH using seqFISH counts from the pipeline and cell-type annotated scRNA-seq counts from the Mouse Gastrulation Atlas[26] (**Methods**) and compared this to the actual expression measured by smFISH in the same cells (**Figure 3a**). The average Pearson correlation between the predicted and measured counts for the 36 smFISH genes was found to be 0.47. This is comparable to the results from the Tangram authors using a MERFISH experiment. The somewhat low correlation is a result of many small single-cell differences so even predictions with lower spatial correlations with the smFISH expression tend to still capture the correct general spatial distribution of the transcript (**Figure S8**).

As the MERFISH images used here were of a cell culture of a single cell type, we could directly compare the average expression per cell from the pipeline with RNA expression values obtained using some other standard method. We obtained FPKM measurements calculated from bulk RNA-seq experiments of the same cell type as used in the MERFISH images[24] (personal communication) and compared these values to the average expression of the cells in the MERFISH images and found them to be highly correlated with a Pearson correlation coefficient of 0.85 (**Methods**) (**Figure 3b**), indicating that the counts the pipeline produced are similar to those obtained by .

There exist abundant expression maps of the mouse brain which allowed us to compare the pipeline results on the targeted ISS images to a trusted reference. We downloaded single gene expression maps from similar sections of mouse brains from the Allen Brain Atlas and found that the spatial distribution of transcripts from the pipeline and the reference atlas images matched for most genes (**Methods**) (**Figure 3c** and **Figure S9**). Out of the fifty genes probed, thirty-four had coronal section images in the Allen Brain

Atlas Mouse Brain reference and nearly all of them showed a strong match between the spatial expression pattern found by our pipeline and in the reference data.

Figure 3: **Orthogonal validation of pipeline results**
a) Comparison of predicted gene expression by Tangram with measured expression of the same gene by smFISH (top six correlating genes shown). Each column corresponds to a gene, with the Tangram predicted expression above and the measured smFISH expression below. Pearson correlation coefficient is printed below each. **b**) Correlation of MERFISH counts with bulk RNA-seq FPKM values. **c**) Comparison of spatial

distribution of four genes found in the targeted ISS dataset by the pipeline with reference expression of the same genes in a similar brain slice from the Allen Brain Atlas.

Discussion

As spatial genomics continues to become more popular as an investigation tool, there will be a growing need for computational tools capable of extracting useful information from the raw image data generated by these methods. We have developed this general and customizable pipeline for those who wish to analyze FISH-based spatial transcriptomics images as part of their research. The pipeline's versatility allows it to be used for any experiment involving targeted barcoding of transcripts and includes options for pre-processing image data, a novel seqFISH decoder, and automated quality metrics that can be used to assess performance. Using real data from three different *in situ* methods and a variety of quality metrics, we showed that the pipeline can be used to obtain high accuracy results that can then be used in a number of downstream applications.

The pipeline is currently capable of obtaining annotated transcript locations from raw images with high fidelity but all subsequent analysis is focused on assessing the quality of the results and not on answering any specific biological question. A future version of the pipeline may include options for downstream analyses that could be automatically performed after the transcripts have been decoded and assigned to cells. This could include imputation of missing gene expression counts based on orthogonal scRNA-seq data, cell type assignment, identification of spatially variable genes, cell neighborhood/communication effects, and general spatial statistics on both the gene and cell level. There already exists a number of tools for any of these analyses so this would involve testing each to find those worth including. This would make the pipeline an end-to-end workflow for FISH-based spatial transcriptomics analysis, streamlining what is typically a difficult and confusing process.

Methods

Conversion to Spacetx Format

While there are a variety of published smFISH-based spatial transcriptomics assays, few have seen use outside their institution of origin[27]. This has resulted in the creation of many in-house codebases, oftentimes poorly documented and not understood by those outside that institution. starfish was created as a universal FISH-analysis tool to address this need, by offering a universal set of tools to format and extract information from all

FISH experiment types. We have taken this one step further by simplifying the process of converting any lab's data into the format natively used by starfish, SpaceTx, by defining a small list of intuitive experiment-specific pipeline parameters that are used to parse the input data files. Image files with any number of dimensions and sorted in any way across folders can be parsed and formatted, so long as parameters are consistent between all files. Auxiliary views of images with non-FISH information, such as a DAPI view, can also be included in the conversion for downstream analysis, such as image registration or segmentation.

In some experiment types, it is common to use a 'pseudocolor' and 'pseudoround' indexing scheme to more efficiently pack barcodes into the experimentally available dye colors. This can offer computational advantages when computing the hamming distance between barcodes, as it can be assumed that there is only one valid pseudocolor channel among the imaging rounds and channels that comprise it[28]. By providing input parameters that describe how the experimental imaging rounds and channels correspond to the pseudocolors and pseudorounds used to define barcodes, the pipeline can automatically sort image channels into the desired pseudocolor scheme.

CheckAll Decoder

Starting from a set of spots of shape (*Round*, *Channel, z, y*, *x*), a codebook of barcodes of shape (*Round*, *Channel)* with no off rounds in any barcode, and a search radius value, the spots are connected into a non-overlapping set of barcodes that each match a barcode in the codebook. Two slightly different algorithms are used to balance the precision and recall. They share the same steps except the order of two are switched between the different versions. The following is for the "filter-first" version:

1. For each spot in each round, find all spot neighbors in other rounds that are within the search radius.
2. For each spot in each round, build all possible full length barcodes based on the channel labels of the spot's neighbors and itself.
3. Choose the "best" barcode of each spot's possible barcodes by calculating a score that is based on minimizing the spatial variance and maximizing the intensities of the spots in the barcode (shown below). Each spot is assigned a "best" barcode in this way.

$$Score \ = \ Q \ + \ Sv \ * \ C$$
$$Q \ = \ - \ log(1 \ / \ (1 \ + \ (RoundNum \ - \ QualSum))$$
$$RoundNum \ = \ Number \ of \ rounds \ in \ experiment$$

$$QualSum \ = \ Sum\ of\ normalized\ intensity\ values\ of\ all\ spots\ in\ barcode$$

$$Sv \ = \ -\ log(1\ /\ 1\ +\ (\Sigma_{i=x,y,z}\ var(coords_i)))$$

$$coords_i \ = \ Vector\ of\ spot\ coordinate\ values\ for\ all\ spots\ in\ the\ i^{th}$$
$$dimension$$

$$C \ = \ constant\ (2\ here)$$

4. Drop "best" barcodes that don't have a matching target in the codebook.
5. Only keep barcodes/targets that were found as "best" using at least n of the spots that make each up (n is determined by the mode parameter).
6. Find an approximate maximum independent set of the spot combinations so no two barcodes use the same spot.
   a. A graph is created where each node is a combination of spots that make up a decoded barcode and edges connect nodes that share at least one spot.
   b. Nodes are eliminated from the graph in order of highest number of edges to lowest, with ties being broken by choosing the barcode with the higher score (described in step three), until there are no longer any edges in the graph.

The other method, called "decode-first", is the same except steps 3 and 4 are switched so that the minimum scoring barcode is chosen from the set of possible codes that have a match to the codebook. The filter-first method will have lower recall but higher precision while the other method will have higher recall but at the cost of lower precision.

Decoding is run in multiple stages with the parameters becoming less strict as it progresses. The high accuracy algorithm (filter-first) is always run first followed by the lower accuracy method (decode-first), each with slightly different parameters based on the choice of "mode" parameter. After each decoding, the spots found to be in decoded barcodes are removed from the original set of spots before they are decoded again with a new set of parameters. In order to simplify the number of parameters to choose from, we have sorted them into three sets of presets ("high", "medium", or "low" accuracy) determined by the "mode" decoding parameter.

Decoding is also done multiple times at multiple search radius values that start at 0 and increase incrementally until they reach the specified search radius. This allows high confidence barcodes to be called first which makes things simpler in subsequent stages as there are less spots to choose from.

If the error_rounds parameter is set to 1, after running all decodings for barcodes that exactly match the codebook, another set of decodings will be run to find barcodes that are missing a spot in exactly one round. If the codes in the codebook all have a hamming distance of at least 2 from all other codes, each can still be uniquely identified using a partial code with a single round dropped. Barcodes decoded with a error-corrected code like this are inherently less accurate and so an extra column was added to the final output table that labels each decoded target with the number of rounds that was used to decode it, allowing you to easily separate these less accurate codes from your high accuracy set if you wish.

Pipeline Cell Segmentation

The pipeline offers an in-house segmentation method based on thresholding and watershed that can be used to obtain a rough segmentation of the nuclear or cytoplasm boundaries. This method requires some sort of images that show the cell nuclei such as a DAPI stain. These nuclei images are processed as follows:
1. Uneven background illumination is corrected by calculating the white tophat transformation of the image with a large structuring element
2. Random noise is reduced by applying a median filter.
3. Low intensity pixels are clipped to zero.
4. Local thresholding using a structuring element of size equal to the expected nucleus size (user parameter) produces a binary image of the nuclei.
5. Edges of objects in binary image are smoothed by calculating reciprocal morphological opening and closing of the binary image and objects whose area falls below or above the outlier threshold are removed.
6. The binary image is converted into a distance map where each pixel's intensity value becomes its distance to the nearest edge in the binary image.
7. Individual objects are identified by a watershed algorithm (skimage.segmentation.watershed) using local intensity peaks found with a structuring element equal to the expected size of the nucleus as initial markers.
8. Objects that are incorrectly split by the watershed method are corrected.
   a. First all objects that are directly adjacent to another object are identified.
   b. For each pair of adjacent objects, the sum of convex hull areas for the two objects taken independently is calculated as well as the convex hull area of the two objects taken together.
   c. If the difference between the separate convex hull area sum and the combined convex hull area is less than a threshold value then the objects were likely to have been incorrectly separated and are then merged into a single object.

9. Overlapping nuclei are identified from the corrected binary image (output of step 5) by segmenting using connected component analysis instead of watershed which will consider any two directly adjacent objects to be a single object.
   a. For each object identified this way, the ratio of its convex hull area to its normal area is calculated and if it is above a threshold value then that object is likely to be made up of one or more overlapping nuclei
   b. Overlapping nuclei are removed from the final segmentation if that option is specified by the user.

The user may choose to use the nuclei segmentation directly to segment the transcripts found in the pipeline but they also have an option to attempt to use the nuclei segmentation in conjunction with the decoded transcripts to segment the cytoplasm of cells. Following nuclei segmentation, the cytoplasm is segmented as follows:
1. An image is created where each pixel that contains a decoded transcript has a value of one while every other pixel has a value of zero.
2. Dilate this binary image to expand the transcript coverage.
3. Smooth transcript map using a gaussian filter.
4. Scale intensities values, setting every pixel with an intensity greater than the 80th percentile of all intensities to the max value.
5. Threshold locally using a structuring element twice as large as the expected nucleus size.
6. Add in the binary nuclei image to ensure they are in the foreground.
7. Apply a small morphological closing to close small gaps.
8. The binary image is converted into a distance map where each pixel's intensity value becomes its distance to the nearest edge in the binary image.
9. Individual objects are identified by a watershed algorithm using the centroid of each nucleus as initial markers.
10. Objects whose area falls below or above the respective outlier threshold are removed.

The method also offers the user options for removal of border cells from the segmentation and for expanding labels after they have been found.

Validation of Pipeline Cell Segmentation

Simulated cell nuclei images were downloaded from image set BBBC034v1 Thirstrup et al. 2018, available from the Broad Bioimage Benchmark Collection[29]. These images had four categories of clustering probability (c00 (no clustering), c25 (low clustering), c50 (some clustering), and c75 (high clustering)) as well as a low and high signal to noise ratio (SNR) version for each. A single central z slice (z=50) was chosen for

segmentation and the pipeline segmentation tool was run for all 30 simulations for each clustering and SNR category with the following parameters:

- area_thresh = 1.05
- thesh_block_size = 31
- watershed_footprint_size = 30

The results were compared to the given ground truth and the average precision and recall was calculated and reported across the 30 simulations for each category.

Quality Control Metrics

QC metrics are automatically computed in the pipeline given the output from prior steps. The values are calculated on a per-fov basis, as described below.

These spot-based metrics are not computed when the primary spot decoder is the PixelSpotDetector. Spots with no cell id assigned from the segmentation mask will be filtered before the following are calculated.

1. Spots per barcode:
   Divide the total number of spots by the length of the codebook.
2. Spatial homogeneity of spots across each FOV:
   a. The AstroPy `RipleyKEstimator` is used, configured to match image size.
   b. A total of 10 radii, r_i are evaluated on a range of 0 to $\sqrt{\frac{image\ area}{2}}$.
   c. The estimator is applied to both the spot data and a poisson process for each r.
   d. A 95% confidence interval for the null hypothesis (random poisson process) is generated by the Monte-Carlo method, sampling from a uniform random distribution over the same FOV size with the same number of spots.
3. Distribution of spot counts across rounds:
   The number of spots in each round of the data is tallied. The standard deviation and skew of these counts are taken.
4. Distribution of spot counts across channels:
   The number of spots in each channel of the data is tallied. The standard deviation and skew of these counts are taken.

Most transcript based metrics are run on all datasets, regardless of which decoding method was used earlier in the pipeline. These statistics can offer more specific insight into how well a given dataset has been processed.

5. Count of transcripts per cell:
   The number of transcripts assigned to each cell id are tallied. The cells with a count lower than $median - 1.5 \times (third\ quartile - first\ quartile)$ are suggested to be removed from analysis.
6. Fraction of spots used for transcripts:
   If a spot-based method was used, the number of spots that were used to decode the transcripts is taken. This is then divided by the total tally of spots found.
7. Distribution of transcript source spot counts across rounds:
   The rounds that were used to decode each transcript are inferred and then tallied. The standard deviation and skew of these counts are taken.
8. Distribution of transcript source spot counts across channels:
   The channels that were used to decode each transcript are inferred and then tallied. The standard deviation and skew of these counts are taken.
9. False positive rate:
   Optionally during the conversion process, blanks are inserted into the codebook that do not overlap within a specified hamming distance of existing codes. On a cell by cell basis, the count of transcripts and blanks are tallied, then the FPR is calculated as $\frac{blanks}{blanks + transcripts}$.
10. Relative abundance of barcodes and blanks:
    The total number of transcripts that match a given target are tallied. The sample average and standard deviation are calculated from the counts of blank barcodes, and a two-tailed 95% confidence interval for the normal distribution with the same average and standard deviation are used to calculate the proposed cutoff for non-blank barcodes. This CI is performed for both the uncorrected barcodes, and again for the combined corrected and uncorrected barcodes.

Addition of Noise for QC Comparison (Figure S3)

Multiplicative gaussian noise was added to images to simulate images acquired with a shorter exposure time. Noise was added as $output = input + n * input$, where n is a gaussian random variable with mean=1.5 and variance=3.0.

Pipeline Parameters Used for Results

The individual parameter values used for each of the three example datasets to obtain the results shown here are specified in the metadata.json files found with the example data (LINK).

Using Pipeline seqFISH Counts to Predict Gene Expression of Gene Measured by smFISH

smFISH images were corrected by subtracting dark-field images from each, applying a Gaussian high pass filter with a sigma value of 3, followed by deconvolution by the Richardson-Lucy method using a Gaussian point-spread-function also with a sigma value of 3 for 15 iterations. Transcript locations were then identified using the *detect_spots* function from the FISH-quant Python package[30] using a voxel size of (0, 110, 110) and a radius of 5. For each transcript all 40 tiles associated with that transcript were passed as a list to *detect_spots* so that an optimal threshold value could be calculated for each for spot finding. The results were combined into a single expression table for all cells across all tiles for the 36 smFISH genes. The E8.5 mouse embryo 10x Genomics scRNA-seq data was downloaded using the MouseGastrulationData Bioconductor package. Cell type assignments for somitic and paraxial mesoderm types were amended with predictions from Guibentif et al[31] (personal communication) and blood subtypes (erythroid 1, 2, and 3 and blood progenitors 1 and 2) were merged into two major groups. Cell types with less than 25 cells were then dropped. We then joined the seqFISH data expression matrices for all forty tiles, dropping any cells with fewer than 10 total transcripts or 5 unique transcripts. The tangram functions *map_cells_to_space* and *project_genes* were used in "clusters" mode to predict full genome expression in the seqFISH cells using the scRNA-seq counts. The predicted expression for the 36 genes measured by smFISH in each cell was compared to measured expression and the mean Pearson correlation coefficient calculated across all cells.

Comparison of Pipeline MERFISH Results to Bulk RNA-seq Counts

The average count of each gene measured by MERFISH per cell was calculated and compared against the FPKM of the same gene measured by bulk RNA-seq in a sample of the same cell type. Bulk RNA-seq FPKMs were obtained from the original MERFISH authors (Jeffrey Moffit, personal communication). The Pearson correlation coefficient of the MERFISH and bulk RNA-seq FPKMs was then calculated and reported.

Comparison of Pipeline ISS Results to Reference Atlas

Pipeline ISS images were created by setting transcript pixel locations to maximum brightness, dilating for 3 iterations (for visibility) and then adding the result to the DAPI image for each transcript. Atlas images were obtained from https://mouse.brain-map.org/ for each transcript that had a coronal section present in the database. The slice used was chosen by identifying the slice in the atlas images

whose Nissl stain was most similar in morphology to the ISS dataset's DAPI stain (both nucleus stains). The "Expression" and "ISH" image for that atlas slice were downloaded and merged and then cropped and rotated to match the pipeline ISS image.

Code and Data Availability

PIPEFISH is available at https://github.com/hubmapconsortium/spatial-transcriptomics-pipeline and example images from each of the three analyzed datasets (seqFISH, ISS, and MERFISH) plus other necessary pipeline input files can be found at https://doi.org/10.5281/zenodo.7647746.

References

1. Papalexi, E., and Satija, R. (2018). Single-cell RNA sequencing to explore immune cell heterogeneity. Nat. Rev. Immunol. *18*, 35–45. 10.1038/nri.2017.76.
2. Ivan Damjanov (1996). Anderson's Pathology-Vol 1.
3. Rao, A., Barkley, D., França, G.S., and Yanai, I. (2021). Exploring tissue architecture using spatial transcriptomics. Nature *596*, 211–220. 10.1038/s41586-021-03634-9.
4. Marx, V. (2021). Method of the Year: spatially resolved transcriptomics. Nat. Methods *18*, 9–14. 10.1038/s41592-020-01033-y.
5. Ke, R., Mignardi, M., Pacureanu, A., Svedlund, J., Botling, J., Wählby, C., and Nilsson, M. (2013). In situ sequencing for RNA analysis in preserved tissue and cells. Nat. Methods *10*, 857–860. 10.1038/nmeth.2563.
6. Ståhl, P.L., Salmén, F., Vickovic, S., Lundmark, A., Navarro, J.F., Magnusson, J., Giacomello, S., Asp, M., Westholm, J.O., Huss, M., et al. (2016). Visualization and analysis of gene expression in tissue sections by spatial transcriptomics. Science *353*, 78–82. 10.1126/science.aaf2403.
7. Martin, K.C., and Ephrussi, A. (2009). mRNA Localization: Gene Expression in the Spatial Dimension. Cell *136*, 719–730. 10.1016/j.cell.2009.01.044.
8. Shah, S., Takei, Y., Zhou, W., Lubeck, E., Yun, J., Eng, C.-H.L., Koulena, N., Cronin, C., Karp, C., Liaw, E.J., et al. (2018). Dynamics and Spatial Genomics of the Nascent Transcriptome by Intron seqFISH. Cell *174*, 363-376.e16. 10.1016/j.cell.2018.05.035.
9. Lohoff, T., Ghazanfar, S., Missarova, A., Koulena, N., Pierson, N., Griffiths, J.A., Bardot, E.S., Eng, C.-H.L., Tyser, R.C.V., Argelaguet, R., et al. (2022). Integration of spatial and single-cell transcriptomic data elucidates mouse organogenesis. Nat. Biotechnol. *40*, 74–85. 10.1038/s41587-021-01006-2.
10. Chen, K.H., Boettiger, A.N., Moffitt, J.R., Wang, S., and Zhuang, X. (2015). Spatially resolved, highly multiplexed RNA profiling in single cells. Science *348*, aaa6090. 10.1126/science.aaa6090.

11. Svedlund, J., Strell, C., Qian, X., Zilkens, K.J.C., Tobin, N.P., Bergh, J., Sieuwerts, A.M., and Nilsson, M. (2019). Generation of in situ sequencing based OncoMaps to spatially resolve gene expression profiles of diagnostic and prognostic markers in breast cancer. EBioMedicine *48*, 212–223. 10.1016/j.ebiom.2019.09.009.

12. Navarro, J.F., Sjöstrand, J., Salmén, F., Lundeberg, J., and Ståhl, P.L. (2017). ST Pipeline: an automated pipeline for spatial mapping of unique transcripts. Bioinformatics *33*, 2591–2593. 10.1093/bioinformatics/btx211.

13. Sztanka-Toth, T.R., Jens, M., Karaiskos, N., and Rajewsky, N. (2022). Spacemake: processing and analysis of large-scale spatial transcriptomics data. GigaScience *11*, giac064. 10.1093/gigascience/giac064.

14. Zheng, G.X.Y., Terry, J.M., Belgrader, P., Ryvkin, P., Bent, Z.W., Wilson, R., Ziraldo, S.B., Wheeler, T.D., McDermott, G.P., Zhu, J., et al. (2017). Massively parallel digital transcriptional profiling of single cells. Nat. Commun. *8*, 14049. 10.1038/ncomms14049.

15. Emanuel, G., Seichhorn, Hazen Babcock, Leonardosepulveda, and Timblosser (2020). ZhuangLab/MERlin: MERlin v0.1.6. 10.5281/ZENODO.3758540.

16. Axelrod, S., Cai, M., Carr, A., Freeman, J., Ganguli, D., Kiggins, J., Long, B., Tung, T., and Yamauchi, K. (2021). starfish: scalable pipelines for image-based transcriptomics. J. Open Source Softw. *6*, 2440. 10.21105/joss.02440.

17. Palla, G., Spitzer, H., Klein, M., Fischer, D., Schaar, A.C., Kuemmerle, L.B., Rybakov, S., Ibarra, I.L., Holmberg, O., Virshup, I., et al. (2022). Squidpy: a scalable framework for spatial omics analysis. Nat. Methods *19*, 171–178. 10.1038/s41592-021-01358-2.

18. Pham, D., Tan, X., Xu, J., Grice, L.F., Lam, P.Y., Raghubar, A., Vukovic, J., Ruitenberg, M.J., and Nguyen, Q. (2020). stLearn: integrating spatial location, tissue morphology and gene expression to find cell types, cell-cell interactions and spatial trajectories within undissociated tissues (Bioinformatics) 10.1101/2020.05.31.125658.

19. Gataric, M., Park, J.S., Li, T., Vaskivskyi, V., Svedlund, J., Strell, C., Roberts, K., Nilsson, M., Yates, L.R., Bayraktar, O., et al. (2021). PoSTcode: Probabilistic image-based spatial transcriptomics decoder (Bioinformatics) 10.1101/2021.10.12.464086.

20. Lubeck, E., Coskun, A.F., Zhiyentayev, T., Ahmad, M., and Cai, L. (2014). Single-cell in situ RNA profiling by sequential hybridization. Nat. Methods *11*, 360–361. 10.1038/nmeth.2892.

21. McQuin, C., Goodman, A., Chernyshev, V., Kamentsky, L., Cimini, B.A., Karhohs, K.W., Doan, M., Ding, L., Rafelski, S.M., Thirstrup, D., et al. (2018). CellProfiler 3.0: Next-generation image processing for biology. PLOS Biol. *16*, e2005970. 10.1371/journal.pbio.2005970.

22. Petukhov, V., Xu, R.J., Soldatov, R.A., Cadinu, P., Khodosevich, K., Moffitt, J.R., and Kharchenko, P.V. (2022). Cell segmentation in imaging-based spatial transcriptomics.

Nat. Biotechnol. *40*, 345–354. 10.1038/s41587-021-01044-w.

23. Prabhakaran, S. (2022). Sparcle: assigning transcripts to cells in multiplexed images. Bioinforma. Adv. *2*, vbac048. 10.1093/bioadv/vbac048.

24. Moffitt, J.R., Hao, J., Wang, G., Chen, K.H., Babcock, H.P., and Zhuang, X. (2016). High-throughput single-cell gene-expression profiling with multiplexed error-robust fluorescence in situ hybridization. Proc. Natl. Acad. Sci. *113*, 11046–11051. 10.1073/pnas.1612826113.

25. Biancalani, T., Scalia, G., Buffoni, L., Avasthi, R., Lu, Z., Sanger, A., Tokcan, N., Vanderburg, C.R., Segerstolpe, Å., Zhang, M., et al. (2021). Deep learning and alignment of spatially resolved single-cell transcriptomes with Tangram. Nat. Methods *18*, 1352–1362. 10.1038/s41592-021-01264-7.

26. Pijuan-Sala, B., Griffiths, J.A., Guibentif, C., Hiscock, T.W., Jawaid, W., Calero-Nieto, F.J., Mulas, C., Ibarra-Soria, X., Tyser, R.C.V., Ho, D.L.L., et al. (2019). A single-cell molecular map of mouse gastrulation and early organogenesis. Nature *566*, 490–495. 10.1038/s41586-019-0933-9.

27. Moses, L., and Pachter, L. (2022). Museum of spatial transcriptomics. Nat. Methods *19*, 534–546. 10.1038/s41592-022-01409-2.

28. Eng, C.-H.L., Shah, S., Thomassie, J., and Cai, L. (2017). Profiling the transcriptome with RNA SPOTs. Nat. Methods *14*, 1153–1155. 10.1038/nmeth.4500.

29. Ljosa, V., Sokolnicki, K.L., and Carpenter, A.E. (2012). Annotated high-throughput microscopy image sets for validation. Nat. Methods *9*, 637–637. 10.1038/nmeth.2083.

30. Imbert, A., Ouyang, W., Safieddine, A., Coleno, E., Zimmer, C., Bertrand, E., Walter, T., and Mueller, F. (2022). FISH-quant v2: a scalable and modular tool for smFISH image analysis. RNA *28*, 786–795. 10.1261/rna.079073.121.

31. Guibentif, C., Griffiths, J.A., Imaz-Rosshandler, I., Ghazanfar, S., Nichols, J., Wilson, V., Göttgens, B., and Marioni, J.C. (2021). Diverse Routes toward Early Somites in the Mouse Embryo. Dev. Cell *56*, 141-153.e6. 10.1016/j.devcel.2020.11.013.