FitMultiCell: Simulating and parameterizing computational models of multi-scale and multi-cellular processes

Emad Alamoudi [1], Yannik Schälte [1,2,3], Robert Müller [4], Jörn Starruß [4], Nils Bundgaard [5], Frederik Graw [5,6,7], Lutz Brusch [4], Jan Hasenauer [1,2,3,*]

February 21, 2023

[1] Life and Medical Sciences Institute, University of Bonn, 53113 Bonn, Germany, [2] Helmholtz Zentrum München - German Research Center for Environmental Health, Institute of Computational Biology, 85764 Neuherberg, Germany, [3] Technische Universität München, Center for Mathematics, Chair of Mathematical Modeling of Biological Systems, 85748 Garching, Germany, [4] Center of Information Services and High Performance Computing (ZIH), Technische Universität Dresden, 01062 Dresden, Germany, [5] BioQuant - Center for Quantitative Biology, Heidelberg University, 69120 Heidelberg, Germany. [6] Interdisciplinary Center for Scientific Computing, Heidelberg University, 69120 Heidelberg, Germany, [7] Friedrich-Alexander-University Erlangen-Nürnberg, Department of Medicine 5, 91054 Erlangen, Germany

*To whom correspondence should be addressed.

Abstract

Motivation: Biological tissues are dynamic and highly organized. Multi-scale models are helpful tools to analyze and understand the processes determining tissue dynamics. These models usually depend on parameters that need to be inferred from experimental data to achieve a quantitative understanding, to predict the response to perturbations, and to evaluate competing hypotheses. However, even advanced inference approaches such as Approximate Bayesian Computation (ABC) are difficult to apply due to the computational complexity of the simulation of multi-scale models. Thus, there is a need for a scalable pipeline for modeling, simulating, and parameterizing multi-scale models of multi-cellular processes.

Results: Here, we present FitMultiCell, a computationally efficient and user-friendly open-source pipeline that can handle the full workflow of modeling, simulating, and parameterizing for multi-scale models of multi-cellular processes. The pipeline is modular

and integrates the modeling and simulation tool Morpheus and the statistical inference tool pyABC. The easy integration of high-performance infrastructure allows to scale to computationally expensive problems. The introduction of a novel standard for the formulation of parameter inference problems for multi-scale models additionally ensures reproducibility and reusability. By applying the pipeline to multiple biological problems, we demonstrate its broad applicability, which will benefit in particular image-based systems biology.

Availability: FitMultiCell is available open-source at `https://gitlab.com/fitmulticell/fit`.

Contact: jan.hasenauer@uni-bonn.de

Supplementary information: Supplementary data are available at `https://doi.org/10.5281/zenodo.7646287` online.

1 Introduction

Biological tissues are complex entities composed of cells and extracellular components. Tissues occur in different developmental stages and compositions, are highly dynamic and often heavily structured. Specific tissue properties are relevant for a broad range of processes, including tissue homeostasis, viral infection, and tumor development and treatment. For the experimental analysis of biological tissues, imaging techniques are widely used. Common approaches include light and fluorescence microscopy, but more recently also imaging mass cytometry, spatial transcriptomics and related methods are employed (see Lewis et al. [2021] for a review). These experimental techniques provide a variety of quantitative information about biological tissues. Yet, mechanisms underlying specific pattern formation or tissue dynamics often remain elusive. To address these aspects, computational modeling has established itself as a key element to obtain a comprehensive understanding of causal relationships in multi-cellular spatio-temporal systems. Computational models of multi-cellular processes usually capture multiple spatial and temporal scales and describe the emergence of the system's behavior based on individual building blocks, e.g. individual cells and their interactions. There are several modeling approaches, including discrete, continuous and hybrid model formalisms [Anderson and Quaranta, 2008, Meyer et al., 2020, Waclaw et al., 2015]. Cells and their interactions can, for instance, be described using (energy-based) Cellular Potts Models (CPM) or (force-based) vertex models. Several software packages have been developed, including MCell [Kerr et al., 2008], FLAME [Richmond et al., 2010], CompuCell3D [Swat et al., 2012], Chaste [Mirams et al., 2013], Morpheus [Starruß et al., 2014], and PhysiCell [Ghaffarizadeh et al., 2018] to simplify and standardize the demanding task of model formulation and implementation. Yet, while computational modeling has substantially improved the understanding of multi-cellular systems, it remains a challenging task [Fletcher

and Osborne, 2022].

For multi-scale models of multi-cellular processes a key challenge is parameter estimation, the process in which values for the unknown model parameters are determined by fitting the model simulations to experimentally observed data. Parameter estimation is necessary to obtain quantitative models of processes, to analyse processes, to compare competing hypotheses about processes, and to predict the dynamics of processes (e.g., in response to perturbations) [Durso-Cain et al., 2021, Imle et al., 2019, Jagiella et al., 2017, MacLean et al., 2014, Toni et al., 2011]. Systematic, rigorous and uncertainty-aware parameter estimation is only just becoming accessible for multi-scale models with advanced methods and growing computational resources. Reasons for this are that (i) the simulation of multi-scale models accounts for different biophysical processes (e.g., intra- and extracellular signalling as well as physical interaction), which requires computationally efficient simulation algorithms (e.g., hybrid discrete-continuum approaches), and that (ii) the stochasticity of most models (e.g. due to randomness arising from small cell numbers) necessitates repeated simulations.

To cope with the challenges of parameter estimation for advanced computational models, Approximate Bayesian Computation (ABC) methods have been developed and applied [Beaumont et al., 2002, Pritchard et al., 1999, Sisson et al., 2018]. These methods generate samples from an approximation of the Bayesian parameter posterior distribution, without evaluating a likelihood function which can quickly become inaccessible for complex stochastic models. To enable the application of ABC methods to multi-scale models, they have been parallelized on high-performance computing (HPC) infrastructure [Babtie and Stumpf, 2017, Jagiella et al., 2017, Johnston et al., 2014, Sottoriva et al., 2015]. Generic implementations are provided by, in particular, pyABC [Klinger et al., 2018], ABCpy [Dutta et al., 2017], and ELFI [Kangasrääsiö et al., 2016]. Yet, while simulation and inference tools are available, the parameter estimation for multi-scale models of multi-cellular processes still requires a high level of technical expertise. The available tools are not interfaced and code from published application examples is often difficult to reuse and extend. Thus, there is a need for a platform that facilitates and streamlines the entire workflow, from the construction of multi-scale models of various types based on biological principles, to systematic uncertainty-aware data-driven parameter estimation [Hasenauer et al., 2015].

In this work, we introduce the FitMultiCell pipeline, an open-source, user-friendly, and scalable end-to-end platform that integrates modeling, simulation, and parameter estimation, to simplify the analysis of multi-scale and multi-cellular systems. FitMultiCell integrates the state-of-the-art tools Morpheus [Starruß et al., 2014] for model building and simulation, and pyABC [Schälte et al., 2022] for parameter estimation. It builds on an extension of the PEtab standard [Schmiester et al., 2021] for the specification of parameter estimation problems which we additionally introduce in this manuscript. We demonstrate and evaluate the FitMultiCell pipeline using models for tumor growth and liver regeneration.

Figure 1: Overview of the FitMultiCell pipeline. First row: User perspective on the biological system, experiment, model formulation, and parameter estimation problem. Second row: Tool and format overview. Third row: Features and details for all components of the workflow. Fourth row: Visualization of the ABC-SMC parameter estimation algorithm.

2 Methods

2.1 Problem description

We consider the problem of developing quantitative computational models of multi-cellular processes. These models might account for a broad range of biochemical and biophysical processes, including

- cellular signal transduction, metabolism and gene regulation,

- cell movement, proliferation and death, and

- cell-cell communication (e.g., via direct cell-cell-contact areas or the secretion/uptake

¹¹² of biochemical substances).

The spectrum of modeling frameworks for such integrated processes is broad and the models are often stochastic, like the behaviours and decisions by individual biological cells are inherently stochastic. Mathematically, we can write any such model as

$$y = \mathcal{M}(\theta, \xi),$$

¹¹³ where y denotes the vector of observed properties and θ denotes the vector of unknown
¹¹⁴ properties of biochemical, biophysical or observation processes (e.g. reaction rates). Process
¹¹⁵ noise – arising, for instance, from low molecular numbers – as well as measurement noise
¹¹⁶ is described via the vector of random variables ξ. Marginalizing the model simulation over
¹¹⁷ the random variables ξ yields the likelihood $\pi(y|\theta)$, which is the conditional probability of
¹¹⁸ observing y given θ.

Quantitative mathematical modeling requires the inference of the unknown parameters θ from data. In this study, we consider Bayesian inference and aim to approximate the Bayesian posterior distribution

$$\pi(\theta|y_{\text{obs}}) \propto \pi(y_{\text{obs}}|\theta) \cdot \pi(\theta)$$

¹¹⁹ of the unknown model parameters for experimentally observed data y_{obs} and prior knowledge
¹²⁰ $\pi(\theta)$. The posterior distribution encodes all available information about the model parameter
¹²¹ and, hence, allows for the assessment of parameter and prediction uncertainties as well as
¹²² for the design of validation experiments. Experimental data used for the parameterization
¹²³ of the considered models are often obtained using imaging techniques. These can provide
¹²⁴ information about e.g. spatial profile, temporal changes and changes between conditions.
¹²⁵ Overall, the spectrum of experimental setups is broad.

¹²⁶ 2.2   FitMultiCell pipeline

¹²⁷ To facilitate quantitative computational modeling of multi-cellular processes, we developed
¹²⁸ the FitMultiCell pipeline (Figure 1). This pipeline supports its users in

¹²⁹ (1) formulating the modeling problem, i.e.

¹³⁰   (a) defining computational models and

¹³¹   (b) defining data obtained from experiments,

¹³² (2) estimating unknown model parameters, and

¹³³ (3) evaluating parameter and model predictions (including planning validation experi-
¹³⁴   ments).

The FitMultiCell pipeline streamlines the parameter estimation process by providing a tight integration of tools for model specification and simulation, and parameter estimation and reporting. This is achieved using a Python interface with a broad spectrum of functionalities. The current version supports (1) multi-scale modeling and simulation using Morpheus [Starruß et al., 2014], and (2) parameter estimation and uncertainty quantification using pyABC [Klinger et al., 2018]. These state-of-the-art tools cover a broad spectrum of modeling applications; yet, other tools for modeling, simulation and parameter estimation can be easily interfaced.

The FitMultiCell pipeline enables parameter estimation for application problems with multiple experimental conditions, data sets and data types. Furthermore, it offers a broad range of built-in visualization and analysis tools. To facilitate reproducibility and reusability, the FitMultiCell pipeline supports the MorpheusML and the PEtab-MS standards.

In the following, we describe the key components of the FitMultiCell pipeline and their features.

2.2.1 Standardization

The FitMultiCell pipeline uses standardized data formats to ensure interoperability, reproducibility and reusability – important aspects of the FAIR principles [Wilkinson et al., 2016]. The multi-cellular models are encoded using MorpheusML, an established XML-based standard at `https://doi.org/10.25504/FAIRsharing.78b6a6`. The parameter estimation problems are encoded using the PEtab-MS format, a newly developed tsv-file-based standard.

We developed PEtab-MS as an extension of the Parameter Estimation tabular format (PEtab) [Schmiester et al., 2021], which was developed in the field of ordinary differential equation (ODE) based modeling and is already supported by various simulators and parameter estimation toolboxes. PEtab-MS conserves most core components of PEtab, including the tables defining model parameters and experimental conditions. Yet, PEtab-MS allows for model expression using MorpheusML, flexible data tables (including references to image files), as well as functions for computing summary statistics. These aspects are essential for multi-cellular processes and were not captured by PEtab. The specification of PEtab-MS and a tool for the validation of files can be found at `https://gitlab.com/fitmulticell/libpetab-python-MS`.

As imaging data are often processed to obtain informative summary statistics, the FitMultiCell pipeline includes a class definition for the construction of summary statistics. Several common summary statistics for imaging data are already provided (see Results section) and customized statistics can be implemented. Furthermore, it is possible to automatically construct informative summary statistics [Fearnhead and Prangle, 2012, Schälte and Hasenauer,

2022].

2.2.2 Simulation

The FitMultiCell pipeline is designed for the simulation-based analysis of multi-cellular processes. Accordingly, we allow for simulation of advanced models $\mathcal{M}$ for cells and tissues (using cellular automata and cellular Potts models), extra-cellular concentration fields (using partial differential equations) and intra-cellular dynamics (using ordinary or stochastic differential equations or continuous-time Markov jump processes).

The FitMultiCell pipeline implements a comprehensive interface to Morpheus, including parameter mapping and simulation result extraction. This renders the functionalities of Morpheus (e.g. model construction, simulation and visualization) as well as features such as a comprehensive GUI for rapid prototyping available within the FitMultiCell pipeline. As Morpheus is broadly applicable, widely used for a variety of biological problems, and computationally efficient (see, e.g., Köhn-Luque et al. [2011], Imle et al. [2019] and Vu et al. [2019]), the tight integration of Morpheus in the FitMultiCell pipeline will be beneficial for users.

Additionally, the modular architecture of the FitMultiCell pipeline allows for the interfacing of additional modeling and simulation toolboxes, as well as user-provided simulation codes.

2.2.3 Inference

The FitMultiCell pipeline is designed for simulation-based inference, a class of approaches circumventing the evaluation of the likelihood function. This is important for the study of stochastic multi-cellular processes, but also allows for the application to deterministic models.

The FitMultiCell pipeline implements a comprehensive interface to pyABC [Schälte et al., 2022], including parameter and condition mapping for multi-experiment and multi-data type inference. This renders the state-of-the-art Approximate Bayesian Computation Sequential Monte Carlo (ABC-SMC) method easily accessible to users of the FitMultiCell pipeline. ABC-SMC methods approximate the posterior distribution by constructing a sequence of particles which resembles the data (in terms of summary statistics) more and more closely [Toni and Stumpf, 2010]. Well-tested adaptation methods, e.g. for acceptance thresholds, proposal distributions, and population sizes, render pyABC accessible to non-expert users. Furthermore, pyABC allows for exact inference [Schälte and Hasenauer, 2020] and we recently implemented automatic data normalization, summary statistics construction, and measurement noise handling to enable the robust estimation of parameters of multi-scale models [Schälte and Hasenauer, 2022, Schälte et al., 2021]. For the combined use of Morpheus and pyABC, we implemented an early rejection mechanism that discards simulations as early as possible, e.g. if they exceed an upper time limit. This makes the analysis robust to unex-

pectedly long-running simulations, e.g. due to an excessive number of cells.

We provided the interface to pyABC as this tool has been successfully used in a broad
spectrum of applications, e.g., cardiac electrophysiology [Cantwell et al., 2019], human atrial
cells [Houston et al., 2020], cancer [Colom et al., 2021], gene expression [Coulier et al., 2021],
universe expansion [Bernardo and Said, 2021], and bee colonies [Minucci et al., 2021]. This
underlines its applicability to a broad spectrum of inference tasks for multi-cellular processes.
Additionally, the modular architecture of the FitMultiCell pipeline allows for the interfacing
of additional inference tools, as well as user-provided inference algorithms.

2.2.4 Distributed execution

Figure 2: Illustration of the parallel framework of FitMultiCell. ***Inference level:*** A main
process manages the pyABC analysis workflow and SQL data storage. ***Population level:***
In each ABC-SMC generation, the main process delegates to a number of distributed worker
processes the task of sampling parameters (from proposal distributions $p(x)$) and synthetic
data sets, until sufficiently many fulfil the generation-specific acceptance criterion (such as
the acceptance thresholds $\mathcal{E}$). Work distribution, communication, and storage of interme-
diate results across various computational nodes and processing units are managed via a
central Redis server. ***Particle level:*** Each single simulation of synthetic data (or groups
of simulations for related perturbation scenarios in a multi-experiment setting) is performed
using Morpheus, optionally with shared-memory parallelization via OpenMP.

213 Parameter estimation often requires thousands to millions of stochastic model simulations,

Figure 3: Several screenshots of the visualization and diagnostics GUI.

which is computationally demanding for complex multi-cellular processes. Distributed execution of the computational tasks is thus paramount (Figure 2). Within the FitMultiCell pipeline, parallelization can happen on three levels to efficiently exploit high-performance computing (HPC) infrastructure:

- *Individual simulations* can be parallelized within the employed simulation toolbox. Morpheus supports the use of multiple threads using OpenMP. In addition to ODEs and PDEs, Morpheus also provides a parallel and exact solver for CPMs.

- *Individual summary statistics evaluations* can be parallelized within the FitMultiCell pipeline if multiple individual simulations are required. This is for instance the case if experimental replicates are available for stochastic processes and multiple experimental conditions are considered. As the respective simulations are independent, they can be trivially parallelized across multiple threads.

- *Parameter estimation* can be parallelized within the employed parameter estimation toolbox. PyABC supports single-machine multi-core execution and multi-machine distributed execution. A main process manages the communication across SMC generations and post-processing of accepted particle populations, while the computation-heavy simulations and summary statistic evaluations are delegated to a set of parallel worker processes (see Figure 2). pyABC provides two parallelization strategies, static and dynamic scheduling, which distribute work across computational resources, aiming to minimize the overall CPU time, or the overall wall time, respectively [Klinger et al.,

2018].

To facilitate the setup of the required server-worker architecture, the FitMultiCell pipeline
comes with bash scripts that handle the resource allocation and communication between
nodes, and which can be used to run the pipeline on HPC clusters with minimum code
modification. While parallelization is available at multiple levels, the most efficient resource
use will often be achieved by dedicating many workers to the particle population and setting
Morpheus to single-threaded simulation mode.

2.2.5 Analysis and visualization

The FitMultiCell pipeline provides a GUI for the analysis of the parameter estimation results.
This GUI can load the shareable SQL database generated by pyABC, but is flexible enough
to visualize the results for other sampling tools after the result files were reformatted. Among
other things, the GUI allows for the visualization of (1) samples using uni- and bi-variate
plots, (2) sampling diagnostics like the decrease of the acceptance threshold over generations,
and (3) the ability to generate the code for any plot that is generated.

2.3 Implementation and development

The FitMultiCell pipeline is written in Python and available on GitLab (`https://gitlab.com/`
`fitmulticell/fit`) and Zenodo (https://doi.org/10.5281/zenodo.7646287) under a BSD-3-
Clause license. It is being developed by contributors from three institutions and others are
invited to contribute. Code quality is monitored via unit tests and continuous integration.
The tool can be installed from the Python Package Index (PyPI). Detailed documentation
of the FitMultiCell platform is available at `https://fitmulticell.readthedocs.io`, which
covers installation, setting up the modeling and estimation problem, and running the param-
eter estimation process, including on HPC and cloud infrastructures.

To ensure ease of use, FitMultiCell pipeline integrates currently only tools which are easy to
install and available under permissive licenses:

• Morpheus is available as a git repository (`https://gitlab.com/morpheus.lab/morpheus`)
under the BSD-3-Clause license. It is written in C++ and available for all major oper-
ating systems as pre-compiled packages together with training materials and a model
repository at (`https://morpheus.gitlab.io/`).

• pyABC is hosted on GitHub (`https://github.com/icb-dcm/pyabc`) under the BSD-
3-Clause license. It is written in Python and can be installed directly via (PyPI). Its
many features are documented at (`https://pyabc.readthedocs.io`).

3   Results

To assess the performance of the FitMultiCell pipeline, we evaluated it using a broad spectrum of test and application examples. In the following, we present its core properties for a few selected models of multi-cellular processes. Several other applications to various multi-cellular problems and different data types have been published separately and are not included here (See Boutillon et al. [2022] Bundgaard et al. [2022]).

All the following results were obtained on the JUWELS standard compute nodes of the Supercomputing Center in Jülich, Germany. Details on the technical specifications are provided in the Supplementary Material.

3.1   Standards supported by FitMultiCell pipeline allow for re-implementation of published application problems

The FitMultiCell pipeline allows for the standardized description of models, datasets and parameter estimation problems. To ensure that the supported standards are practically useful, we assessed to which degree we can implement already published application problems.

We considered three applications capturing different biological and technical problems: (M1) a model of virus transmission via cell-free virions and cell-to-cell contact [Kumberger et al., 2018]; (M2) a model of tumor spheroid growth [Jagiella et al., 2017]; and (M3) a model describing the mechano-sensing of the metabolic status during liver regeneration [Meyer et al., 2020]. The models M1 and M2 were originally not available in MorpheusML and were re-implemented for the purpose of this study, while M3 was already published in MorpheusML. For all applications, we created the PEtab-MS description of the parameter estimation problems. Details on the application problems are provided below and in the Supplementary Material.

We compared the implementation of the models in MorpheusML with the originally published models and found a good resemblance. Furthermore, PEtab-MS was flexible enough to describe all parameter estimation problems. This suggests that the standards employed in the FitMultiCell pipeline are sufficient for a broad spectrum of applications.

3.2   Parallelization in FitMultiCell pipeline provides substantial wall-time reduction

As the efficient use of computing resources is of crucial importance for parameter estimation, we evaluated the parallel efficiency achieved using the FitMultiCell pipeline. We considered a model of the spread of a viral infection within a tissue distinguishing between virus trans-

Figure 4: Performance of the parallelized FitMultiCell pipeline. (A) Illustration of the used model M1 for viral transmission within the host tissue. (B) Wall-time of two different fit scenarios across different numbers of used compute nodes, each consisting of 48 CPU cores. (C) Parallel efficiency of the FitMultiCell pipeline. The dashed line indicates perfect efficiency, i.e. a wall-time directly inversely proportional to the number of nodes, compared to single-node execution. For each choice of nodes, three consecutive ABC-SMC generations were run, with population sizes of $N = 1,000$ (Scenario A) and $N = 10,000$ (Scenario B).

mission via cell-free virions and direct cell-to-cell contact [Kumberger et al., 2018] (Figure 4A and Supplementary Material, Section 4).

In the FitMultiCell pipeline, parallelization is available within and across individual simulation particles. For the considered problems, we parallelize exclusively on the population level to provide the most efficient resource usage; however, this may depend on the specific problem.

To assess the parallel efficiency, we performed parameter estimation using the ABC-SMC algorithm implemented in pyABC with the dynamic scheduling option. The algorithms were run for three generations with two different population sizes: (Scenario A) $1,000$ particles; and (Scenario B) $10,000$ particles. As higher population sizes improve the posterior approximation but are computationally more demanding, both scenarios are relevant. We performed this task using 1, 2, 4, 8 and 16 compute nodes, each consisting of 48 CPU cores.

For both Scenarios A and B, we observed a substantial reduction in wall-time when using higher numbers of nodes, to a fraction of the single-node execution wall-time which already used 48 CPU cores (Figure 4B). Yet, the parallel efficiency (PE), dropped (Figure 4C) – for the case

$$\text{PE} = \frac{\{\text{wall-time for run on single compute node}\}}{\{\text{wall-time for run on } i \text{ compute nodes}\} \cdot i},$$

Figure 5: Result of FitMultiCell pipeline for the model of tumor spheroid growth. Illustration of the model (Left). Experimental data (gray) and simulation results (green) (middle). For the simulations associated with different generations the interval between the 2.5th and the 97.5th percentile are shown. Credible interval for 7 estimated parameters obtained using the original implementation [Jagiella et al., 2017] (gray) and the FitMultiCell pipeline (green) (right).

for the case of 16 nodes (768 cores), we found in Scenario A a parallel efficiency of 49% and in Scenario B a parallel efficiency of 75%. The higher parallel efficiency in Scenario B is plausible as individual generations require more time, which reduces the contributions of the tails of generations in which idle times occur due to differences in computation times for individual particles (see also Klinger et al. [2018]).

In summary, our evaluation confirmed an overall good scaling of the FitMultiCell pipeline, yielding a wall-time reduction of several ten-fold compared to a single-node execution and several hundred-fold compared to single-core execution. As the number of proposed particles required to generate a specific number of accepted particles increases over generations, the parallel efficiency for production runs with the usual 15 to 40 generations should be higher than what has been observed here.

3.3 FitMultiCell pipeline facilitates the study of heterogeneous datasets via automatically tuned algorithms

To assess the benefit of the tight integration of modeling and parameter estimation tools in the FitMultiCell pipeline, and the availability of advanced inference algorithms, we considered the model of tumor spheroid growth [Jagiella et al., 2017] (Figure 5(left)). The original model was used to study growth control mechanisms and the effect of nutrient supply [Jagiella et al.,

Figure 6: Result of FitMultiCell pipeline for the model of mechano-sensing of the metabolic status during liver regeneration. Illustration of the model (left). Experimental data (gray) and simulation results (green) for different combinations of tissue location (from 1-10) and time point (t0-t5.0 days) (middle). For the simulations associated with different generations the interval between the 2.5th and the 97.5th percentile are shown. Credible interval for 14 estimated parameters (right).

2016, 2017]. Yet, the source code of this multi-cellular model entangled with its simulator is highly specific and no longer maintained, complicating the use of this model in further studies.

We implemented the model in MorpheusML and made it available through a public model repository (`https://identifiers.org/morpheus/M0007`). The cell population was described using a stochastic CPM which accounts for cell division and death as well as cell-cell interactions, while the concentrations of extracellular substances were described using partial differential equations (PDEs). The estimation problem for the seven unknown parameters was encoded using PEtab-MS. We considered all available datasets: a time-course for the tumor spheroid radius determined by bright field microscopy; and snapshots for radial profiles of markers for proliferating cells as well as extra-cellular matrix abundance determined from fluorescence microscopy.

In our previous publication considering the parameter estimation problem [Jagiella et al., 2017], we manually defined weights to quantify the relative importance of different summary statistics for the heterogeneous dataset. As this was a time-consuming process, here we employed a fully automatic approach for summary statistics weighting based on inverse regression (see Supplementary Material, Section 2 for details), which is available via the Fit-MultiCell pipeline. The specification of the parameter estimation task does only require a few lines of Python code given MorpheusML and PEtab-MS files.

We ran the ABC-SMC algorithm with a population size of 500 particles and set as stopping condition a maximum wall-time of 48h, within which the pipeline was able to finish 46 generations. The comparison of simulated and observed summary statistics showed that the model is able to fit the data accurately, with substantially improving fit quality in later ABC-SMC generations (Figure 5 (middle)). Exception are, similar to the original model, the fraction of proliferating cells and the ECM density at small distances to the rim, which the model over- and underestimates, respectively, in correspondence to the original analysis [Jagiella et al., 2017], indicating that the model needs to be refined in this regard. The analysis of credible intervals reveals that with the exception of the initial fraction of quiescent cells c_{init}, all parameters are identifiable with small uncertainties. The parameter estimates and uncertainty intervals obtained using our model are in excellent agreement with those in the original analysis (Figure 5(right)). Hence, the FitMultiCell pipeline was able to reproduce the original results, while simplifying implementation and reducing the need for manual tuning.

3.4 FitMultiCell pipeline facilitates parameter estimation for new applications

The parameters of multi-scale processes are often still adapted manually, e.g. due to the difficulty of setting up proper parameter estimation and its computational cost. As this involves manual work, it can lead to non-reproducible results and does not provide any information about parameter uncertainties. We assessed whether the FitMultiCell pipeline can easily replace manual parameter tuning. We studied a model describing the mechano-sensing of the metabolic status during liver regeneration after partial hepatectomy in mice, simulating the reaction network dynamics in hepatocytes along the central-portal axis of a liver lobule by a spatial array of coupled ODEs with spatially heterogeneous inputs [Meyer et al., 2020]. For this model, the parameters were previously determined manually using data for two observables: the concentration of the YAP protein in the nucleus of hepatocytes (NYAP), and the total concentration of YAP protein in hepatocytes (TYAP), see Figure 6 (left).

The model was already implemented in MorpheusML and is available from a public model repository (`https://identifiers.org/morpheus/M7990`). Yet, in exchange with the authors of the original publication, we decided (1) to relax the quasi-steady-state assumption of the intracellular dynamics and performed a full spatio-temporal simulation, (2) to extend the biochemical model by an observer model of the microscopy setup that introduces additional scaling parameters between protein concentration and observed fluorescence intensity, and (3) to account for the measurement noise. Complementary, we created the PEtab-MS files encoding the estimation problem for the 14 unknown parameters. Previously, due to the employed quasi-steady-state assumption, only the ratios of forward and backward rate

constants were identifiable.

We ran the ABC-SMC inference with a population size of $1,000$ particles and a wall-time limit of 24h. To save computational resources, we employed an early rejection strategy to reject particles based on a maximum runtime of 15min for individual simulations not matching the data. The simulated trajectories in later generations of the inference process fitted the data for TYAP and NYAP mostly well (Figure 6 (middle)). An exception were the pericentral locations (CV-PV zones 1-5) at the last time point $t = 5.0 days$, where the simulations couldn't match the low concentrations present in the data, hinting at a transition to homeostasis and a time-dependence of some parameters over longer time scales of many days. The credible intervals indicate that all 14 parameters are identifiable (Figure 6 (right)). Interestingly, the parameter describing the fluorescence intensity normalization ($k14$) was estimated close to one, which supports the hypothesis that both microscopy-based observables can be treated with the same normalization [Meyer et al., 2020]. Moreover, the ratios of rate constants for reversible reactions were found to be on the same order of magnitude as estimated using the quasi-steady state assumption in [Meyer et al., 2020]. Hence, our study underpinned previous conclusions [Meyer et al., 2020], but also demonstrated that the FitMultiCell pipeline allows directly for an uncertainty-aware study of multi-cellular processes.

4 Discussion

Quantitative data-based modeling of multi-cellular processes is challenging, because the models are often stochastic and computationally demanding. Furthermore, due to a lack of standards, the reusability of codes and pipelines is limited. Motivated by these issues, we developed the FitMultiCell pipeline, which covers the entire workflow of model development, simulation, and systematic parameter inference (on HPC or cloud infrastructures) based on standardized input formats. Thereby, it contributes to the accelerated testing of biological hypotheses.

We used the FitMultiCell pipeline to study various application problems. This demonstrated that the proposed pipeline is widely applicable and can recover and confirm previous results. Further, we showed that it can replace manual parameter tuning, thus accelerating and solidifying the quantitative modeling of multi-cellular processes. Its modular implementation scales to HPC infrastructures and thereby facilitates inference for computationally expensive problems.

While the FitMultiCell pipeline already provides the necessary features, there are multiple directions in which it can be developed further. (1) Statistical inference for computationally expensive models can become challenging even when using massive parallelization. To address

this, the use of cheaper surrogate models could be investigated for guiding parameter search and reducing the number of model simulations [Prangle, 2016, Prescott and Baker, 2021]. Furthermore, one could make use of the idle time at the end of generations, e.g. by pre-sampling the next generation and subsequently correcting for bias. (2) Methods for the automatic construction of summary statistics need to be explored. While it is possible to construct summary statistics semi-automatically [Blum et al., 2013] for the type of image data frequently accompanying models of multi-cellular processes, automatic construction based on machine learning approaches, more specifically convolutional networks with prior information gained from transfer learning, could substantially improve statistics quality at decreased training cost. (3) Extension of the FitMultiCell pipeline to additional modeling, simulation and parameter estimation frameworks will increase its applicability. While Morpheus and pyABC cover already a wide range of applications, an integration of further simulation tools (e.g. Ghaffarizadeh et al. [2018], Merks et al. [2011], Mirams et al. [2013], Swat et al. [2012]) and inference tools (e.g. Dutta et al. [2017], Kangasrääsiö et al. [2016]) could facilitate the use of complementary methods and thus grow the application spectrum further.

In conclusion, we illustrated that standardized workflows for the quantitative modeling of multi-cellular processes are feasible. The FitMultiCell pipeline and the standard PEtab-MS provide starting points for further development. Already in its current form, a broad spectrum of projects can profit from them to achieve systematic and scalable inference of unknown parameters.

Acknowledgements

We acknowledge fruitful discussions with colleagues at Morpheus.lab and the Gauss Centre for Supercomputing e.V. (www.gauss-centre.eu) for providing computing time on the GCS Supercomputer JUWELS [Jülich Supercomputing Centre, 2019] at Jülich Supercomputing Centre (JSC).

Funding

This work was supported by the German Federal Ministry of Education and Research (BMBF) (FitMultiCell/031L0159C and EMUNE/031L0293C). JH acknowledges support by the German Research Foundation (DFG) under Germany's Excellence Strategy (EXC 2047 390873048 and EXC 2151 390685813) and via the Schlegel Professorship for JH. FG was additionally supported by the Chica and Heinz Schaller Foundation. YS acknowledges financial support by the German Research Foundation (DFG) (Metaflammation: SFB 1454 - 432325352) and the Joachim Herz Stiftung. LB was supported by the BMBF (LiSyM-Cancer/031L0258A).

References

A. R. A. Anderson and V. Quaranta. Integrative mathematical oncology. *Nat. Rev. Cancer*, 8(3):227–234, Mar. 2008.

A. C. Babtie and M. P. H. Stumpf. How to deal with parameters for whole-cell modelling. *J. R. Soc. Interface*, 14(133), 2017. ISSN 1742-5689. doi: 10.1098/rsif.2017.0237. URL http://rsif.royalsocietypublishing.org/content/14/133/20170237.

M. A. Beaumont, W. Zhang, and D. J. Balding. Approximate Bayesian Computation in Population Genetics. *Genetics*, 162(4): 2025–2035, 12 2002.

R. C. Bernardo and J. L. Said. Towards a model-independent reconstruction approach for late-time hubble data. *J. Cosmol. Astropart. Phys.*, 2021(08):027, 2021.

M. G. Blum, M. A. Nunes, D. Prangle, and S. A. Sisson. A comparative review of dimension reduction methods in approximate Bayesian computation. *Stat. Sci* ., 28(2):189–208, 2013.

A. Boutillon, S. Escot, A. Elouin, D. Jahn, S. González-Tirado, J. Starruß, L. Brusch, and N. B. David. Guidance by followers ensures long-range coordination of cell migration through α-catenin mechanoperception. *Dev. Cell*, 57(12):1529–1544.e5, 2022. doi: 10.1016/j.devcel.2022.05.001.

N. Bundgaard, C. Harmel, A. Imle, S. Sid Ahmed, B. Frey, J. Starruß, O. T. Fackler, and F. Graw. Inferring cell motility in complex environments with incomplete tracking data. *bioRxiv*, 2022. doi: 10.1101/2022.02.10.479738. URL https://www.biorxiv.org/content/early/2022/02/10/2022.02.10.479738.

C. D. Cantwell, Y. Mohamied, K. N. Tzortzis, S. Garasto, C. Houston, R. A. Chowdhury, F. S. Ng, A. A. Bharath, and N. S. Peters. Rethinking multiscale cardiac electrophysiology with machine learning and predictive modelling. *Computers in Biology and Medicine*, 104:339 – 351, 2019. ISSN 0010-4825. doi: https://doi.org/10.1016/j.compbiomed.2018.10.015. URL http://www.sciencedirect.com/science/article/pii/S0010482518303147.

B. Colom, A. Herms, M. Hall, S. Dentro, C. King, R. Sood, M. Alcolea, G. Piedrafita, D. Fernandez-Antoran, S. Ong, et al. Mutant clones in normal epithelium outcompete and eliminate emerging tumours. *Nature*, 598(7881):510–514, 2021.

A. Coulier, S. Hellander, and A. Hellander. A multiscale compartment-based model of stochastic gene regulatory networks using hitting-time analysis. *J. Chem. Phys.*, 154(18):184105, 2021.

K. Durso-Cain, P. Kumberger, Y. Schälte, T. Fink, H. Dahari, J. Hasenauer, S. L. Uprichard, and F. Graw. HCV spread kinetics reveal varying contributions of transmission modes to infection dynamics. *Viruses*, 13(7), July 2021. ISSN 1999-4915. doi: 10.3390/v13071308.

R. Dutta, M. Schoengens, J.-P. Onnela, and A. Mira. Abcpy: A user-friendly, extensible, and parallel library for approximate Bayesian computation. In *Proceedings of the Platform for Advanced Scientific Computing Conference*, PASC '17, pages 8:1–8:9, New York, NY, USA, 2017. ACM. ISBN 978-1-4503-5062-4. doi: 10.1145/3093172.3093233.

P. Fearnhead and D. Prangle. Constructing summary statistics for approximate Bayesian computation: semi-automatic approximate Bayesian computation. *J. R. Stat. Soc. B*, 74(3):419–474, 2012.

A. G. Fletcher and J. M. Osborne. Seven challenges in the multiscale modeling of multicellular tissues. *WIREs Mechanisms of Disease*, 14(1):e1527, 2022. doi: https://doi.org/10.1002/wsbm.1527. URL https://wires.onlinelibrary.wiley.com/doi/abs/10.1002/wsbm.1527.

A. Ghaffarizadeh, R. Heiland, S. H. Friedman, S. M. Mumenthaler, and P. Macklin. Physicell: An open source physics-based cell simulator for 3-d multicellular systems. *PLoS Comput. Biol.*, 14(2):e1005991, Feb 2018. doi: 10.1371/journal.pcbi.1005991.

J. Hasenauer, N. Jagiella, S. Hross, and F. J. Theis. Data-driven modelling of biological multi-scale processes. *J. Coupled Syst. Multiscale Dyn.*, 3(2):101–121, 9 2015.

C. Houston, B. Marchand, L. Engelbert, and C. D. Cantwell. Reducing complexity and unidentifiability when modelling human atrial cells. *Philos. Trans. A Math. Phys. Eng. Sci.*, 378(2173):20190339, 2020. doi: 10.1098/rsta.2019.0339. URL https://royalsocietypublishing.org/doi/abs/10.1098/rsta.2019.0339.

A. Imle, P. Kumberger, N. D. Schnellbächer, J. Fehr, P. Carrillo-Bustamante, J. Ales, P. Schmidt, C. Ritter, W. J. Godinez, B. Müller, et al. Experimental and computational analyses reveal that environmental restrictions shape HIV-1 spread in 3D cultures. *Nat. Commun.*, 10(1):2144, 2019.

N. Jagiella, B. Müller, M. Müller, I. E. Vignon-Clementel, and D. Drasdo. Inferring growth control mechanisms in growing multi-cellular
spheroids of NSCLC cells from spatial-temporal image data. *PLoS Comput. Biol.*, 12(2):e1004412, Feb. 2016. doi: 10.1371/journal.
pcbi.1004412.

N. Jagiella, D. Rickert, F. J. Theis, and J. Hasenauer. Parallelization and high-performance computing enables automated statistical
inference of multi-scale models. *Cell Syst.*, 4(2):194–206, 02 2017.

S. T. Johnston, M. J. Simpson, D. L. McElwain, B. J. Binder, and J. V. Ross. Interpreting scratch assays using pair density dynamics
and approximate Bayesian computation. *Open Biol.*, 4(9):140097, Sept. 2014. doi: 10.1098/rsob.140097.

A. Kangasrääsiö, J. Lintusaari, K. Skytén, M. Järvenpää, H. Vuollekoski, M. Gutmann, A. Vehtari, J. Corander, and S. Kaski. ELFI:
Engine for Likelihood-Free Inference. In *NIPS 2016 Workshop on Advances in Approximate Bayesian Inference*, 2016.

R. A. Kerr, T. M. Bartol, B. Kaminsky, M. Dittrich, J.-C. J. Chang, S. B. Baden, T. J. Sejnowski, and J. R. Stiles. Fast monte carlo
simulation methods for biological reaction-diffusion systems in solution and on surfaces. *SIAM J. Sci. Comput.*, 30(6):3126–3149,
2008.

E. Klinger, D. Rickert, and J. Hasenauer. pyABC: distributed, likelihood-free inference. *Bioinf.*, 34(20):3591–3593, 10 2018.

A. Köhn-Luque, W. de Back, J. Starruß, A. Mattiotti, A. Deutsch, J. M. Pérez-Pomares, and M. A. Herrero. Early embryonic vascular
patterning by matrix-mediated paracrine signalling: A mathematical model study. *PLOS ONE*, 6(9):1–12, 09 2011. doi: 10.1371/
journal.pone.0024175. URL https://doi.org/10.1371/journal.pone.0024175.

P. Kumberger, K. Durso-Cain, S. Uprichard, H. Dahari, and F. Graw. Accounting for space—quantification of cell-to-cell transmission
kinetics using virus dynamics models. *Viruses*, 10(4):200, Apr 2018. ISSN 1999-4915. doi: 10.3390/v10040200. URL http:
//dx.doi.org/10.3390/v10040200.

S. M. Lewis, M.-L. Asselin-Labat, Q. Nguyen, J. Berthelet, X. Tan, V. C. Wimmer, D. Merino, K. L. Rogers, and S. H. Naik. Spatial
omics and multiplexed imaging to explore cancer biology. *Nat. Methods*, 18(9):997–1012, 2021.

A. L. MacLean, S. Filippi, and M. P. H. Stumpf. The ecology in the hematopoietic stem cell niche determines the clinical outcome in
chronic myeloid leukemia. *Proc. Natl. Acad. Sci. USA*, Jan. 2014. doi: pnas.1317072111.

R. M. Merks, M. Guravage, D. Inzé, and G. T. Beemster. Virtualleaf: an open-source framework for cell-based modeling of plant tissue
growth and development. *Plant Physiol.*, 155(2):656–666, 2011.

K. Meyer, H. Morales-Navarrete, S. Seifert, M. Wilsch-Braeuninger, U. Dahmen, E. M. Tanaka, L. Brusch, Y. Kalaidzidis, and M. Zerial.
Bile canaliculi remodeling activates yap via the actin cytoskeleton during liver regeneration. *Mol. Syst. Biol.*, 16(2):e8985, 2020.

J. M. Minucci, R. Curry, G. DeGrandi-Hoffman, C. Douglass, K. Garber, and S. T. Purucker. Inferring pesticide toxicity to honey bees
from a field-based feeding study using a colony model and bayesian inference. *Ecol. Appl.*, 31(8):e02442, 2021.

G. R. Mirams, C. J. Arthurs, M. O. Bernabeu, R. Bordas, J. Cooper, A. Corrias, Y. Davit, S.-J. Dunn, A. Fletcher, D. Harvey, M. Marsh,
J. Osborne, P. Pathmanathan, J. Pitt-Francis, J. Southern, N. Zemzemi, and D. Gavaghan. Chaste: an open source C++ library
for computational physiology and biology. *PLoS Comput. Biol.*, 9(3):e1002970, Mar. 2013. doi: 10.1371/journal.pcbi.1002970.

D. Prangle. Lazy ABC. *Stat. Comput.*, 26(1):171–185, 2016.

T. P. Prescott and R. E. Baker. Multifidelity approximate Bayesian computation with sequential Monte Carlo parameter sampling.
SIAM-ASA J. Uncertain. Quantif., 9(2):788–817, 2021.

J. K. Pritchard, M. T. Seielstad, A. Perez-Lezaun, and M. W. Feldman. Population growth of human y chromosomes: a study of y
chromosome microsatellites. *Mol. Biol. Evol.*, 16(12):1791–1798, 1999.

P. Richmond, D. Walker, S. Coakley, and D. Romano. High performance cellular level agent-based simulation with FLAME for the
GPU. *Brief Bioinform.*, 11(3):334–347, Feb. 2010. doi: 10.1093/bib/bbp073.

Y. Schälte and J. Hasenauer. Efficient exact inference for dynamical systems with noisy measurements using sequential approximate
Bayesian computation. *Bioinf.*, 36(Supplement 1):i551–i559, 7 2020. ISSN 1367-4803. doi: 10.1093/bioinformatics/btaa397.

Y. Schälte and J. Hasenauer. Informative and adaptive distances and summary statistics in sequential approximate Bayesian computa-
tion. *bioRxiv*, 2022. doi: 10.1101/2022.03.18.484896. URL https://www.biorxiv.org/content/early/2022/03/20/2022.03.18.484896.1.

Y. Schälte, E. Alamoudi, and J. Hasenauer. Robust adaptive distance functions for approximate Bayesian inference on outlier-corrupted
data. *bioRxiv*, 2021.

L. Schmiester, Y. Schälte, F. T. Bergmann, T. Camba, E. Dudkin, J. Egert, F. Fröhlich, L. Fuhrmann, A. L. Hauber, S. Kemmer,
P. Lakrisenko, C. Loos, S. Merkt, W. Müller, D. Pathirana, E. Raimúndez, L. Refisch, M. Rosenblatt, P. L. Stapor, P. Städter,
D. Wang, F.-G. Wieland, J. R. Banga, J. Timmer, A. F. Villaverde, S. Sahle, C. Kreutz, J. Hasenauer, and D. Weindl. PEtab—
interoperable specification of parameter estimation problems in systems biology. *PLoS Comput. Biol.*, 17(1):1–10, January 2021.
doi: 10.1371/journal.pcbi.1008646.

Y. Schälte, E. Klinger, E. Alamoudi, and J. Hasenauer. pyabc: Efficient and robust easy-to-use approximate bayesian computation. *J.
Open Source Softw.*, 7(74):4304, 2022. doi: 10.21105/joss.04304. URL https://doi.org/10.21105/joss.04304.

S. A. Sisson, Y. Fan, and M. Beaumont. *Handbook of approximate Bayesian computation*. Chapman and Hall/CRC, 2018.

A. Sottoriva, H. Kang, Z. Ma, T. A. Graham, M. P. Salomon, J. Zhao, P. Marjoram, K. Siegmund, M. F. P. D. Shibata, and C. Curtis.
A Big Bang model of human colorectal tumor growth. *Nat. Gen.*, 47(3):209–216, Mar. 2015. doi: 10.1038/ng.3214.

J. Starruß, W. de Back, L. Brusch, and A. Deutsch. Morpheus: A user-friendly modeling environment for multiscale and multicellular
systems biology. *Bioinf.*, 30(9):1331–1332, Jan. 2014. doi: 10.1093/bioinformatics/btt772.

M. H. Swat, G. L. Thomas, J. M. Belmonte, A. Shirinifard, D. Hmeljak, and J. A. Glazier. Multi-scale modeling of tissues using
CompuCell3D. *Methods Cell Biol.*, 110:325–366, 2012. doi: 10.1016/B978-0-12-388403-9.00013-8.

T. Toni and M. P. H. Stumpf. Simulation-based model selection for dynamical systems in systems and population biology. *Bioinf.*, 26
(1):104–110, 10 2010.

T. Toni, G. Jovanovic, M. Huvet, M. Buck, and M. P. H. Stumpf. From qualitative data to quantitative models: analysis of the phage
shock protein stress response in Escherichia coli. *BMC Syst. Biol.*, 5(69), May 2011.

H. T.-K. Vu, S. Mansour, M. Kücken, C. Blasse, C. Basquin, J. Azimzadeh, E. W. Myers, L. Brusch, and J. C. Rink. Dynamic polarization
of the multiciliated planarian epidermis between body plan landmarks. *Dev. Cell*, 51(4):526 – 542.e6, 2019. ISSN 1534-5807. doi:
https://doi.org/10.1016/j.devcel.2019.10.022. URL http://www.sciencedirect.com/science/article/pii/S153458071930869X.

B. Waclaw, I. Bozic, M. E. Pittman, R. H. Hruban, B. Vogelstein, and M. A. Nowak. A spatial model predicts that dispersal and cell
turnover limit intratumour heterogeneity. *Nature*, 525(7568):261–264, Aug. 2015. doi: 10.1038/nature14971.

M. D. Wilkinson, M. Dumontier, I. J. J. Aalbersberg, G. Appleton, M. Axton, A. Baak, N. Blomberg, J.-W. Boiten, L. B. da Silva Santos,
P. E. Bourne, J. Bouwman, A. J. Brookes, T. Clark, M. Crosas, I. Dillo, O. Dumon, S. Edmunds, C. T. Evelo, R. Finkers, A. Gonzalez-
Beltran, A. J. G. Gray, P. Groth, C. Goble, J. S. Grethe, J. Heringa, P. A. C. 't Hoen, R. Hooft, T. Kuhn, R. Kok, J. Kok, S. J.
Lusher, M. E. Martone, A. Mons, A. L. Packer, B. Persson, P. Rocca-Serra, M. Roos, R. van Schaik, S.-A. Sansone, E. Schultes,
T. Sengstag, T. Slater, G. Strawn, M. A. Swertz, M. Thompson, J. van der Lei, E. van Mulligen, J. Velterop, A. Waagmeester,
P. Wittenburg, K. Wolstencroft, J. Zhao, and B. Mons. The fair guiding principles for scientific data management and stewardship.
Sci Data, 3:160018, Mar 2016. doi: 10.1038/sdata.2016.18.