Title
Transkingdom Network Analysis (TkNA): a systems approach inferring causal factors underlying host-microbiota interactions.

Authors
Nolan K. Newman*, Matthew Macovsky*, Richard R. Rodrigues*, Amanda M. Bruce, Jacob W. Pederson, Sankalp S Patil, Jyothi Padiadpu, Amiran K. Dzutsev, Natalia Shulzhenko, Giorgio Trinchieri[†], Kevin Brown[†], Andrey Morgun[†]

* Co-first author
[†] Co-senior authors

Authors and Affiliations

College of Pharmacy, Oregon State University, Corvallis, OR, USA
Nolan K. Newman, Matthew Macovsky, Amanda M. Bruce, Sankalp S. Patil, Jyothi Padiadpu, Andrey Morgun, Kevin Brown

Basic Science Program, Frederick National Laboratory for Cancer Research, Frederick, MD, USA
Microbiome and Genetics Core, Laboratory of Integrative Cancer Immunology, Center for Cancer Research, National Cancer Institute, Bethesda, MD, USA
Richard R. Rodrigues

Carlson College of Veterinary Medicine, Oregon State University, Corvallis, OR
Jacob W. Pederson and Natalia Shulzhenko

Cancer Immunobiology Section, Laboratory of Integrative Cancer Immunology, Center for Cancer Research, National Cancer Institute, Bethesda, MD, USA
Amiran K. Dzutsev and Giorgio Trinchieri

Abstract
Technological advances have generated tremendous amounts of high-throughput omics data. Integrating data from multiple cohorts and/or several omics types from new and previously published studies can offer a holistic view of a biological system and decipher its critical players and key mechanisms. In this protocol we describe how to use TkNA, a unique causal-inference analytical framework that can perform meta-analysis of cohorts and detect master regulators (causal factors) among measured parameters (e.g., microbes or microbial genes, host genes, metabolites) that govern pathological or physiological responses of host-microbiota interactions in a particular condition or disease.

The first step reconstructs the network that represents a statistical model capturing the complex relationships between the different omics of the biological system. Here, it selects differential features and their per-group correlations by identifying robust and reproducible patterns of fold change direction and sign of correlation across several cohorts. Next, using a causality-reflecting

metric (correlation inequalities), statistical thresholds (per cohort p-values, combined Fisher's p-value, and BH FDR), and a set of topological criteria (e.g., network sparsity, ratio of negative to positive correlations, and strengths of correlations) it selects the final edges that form the Transkingdom Network. The second part of the analysis involves interrogating the network. Using the network's local (degree) and global (Bipartite Betweenness Centrality (BiBC)) topology metrics it detects nodes that are responsible for control of given subnetwork or control of communication between kingdoms and/or subnetworks.

The underlying basis of TkNA approach involves fundamental principles including laws of causality, graph theory and information theory. Hence, TkNA can be used for causal inference via network analysis of any host and/or microbiota multi-omics data. This protocol takes approximately few hours to days to run, depending on size of available data and computational resources. It is targeted towards researchers that might not have access to high-performance computing and requires very basic familiarity with the Unix command-line environment.

Introduction
Complex relationships between genetics and epigenetics are the basis of human health and disease. Advances in experimental and computational capabilities have brought a wide variety of high-throughput data to the study of biological systems. A majority of the efforts are focused towards increasing throughput, reducing financial and personnel costs, and increasing experimental and computational efficiencies. There is a clear interest in computational methods and software that can integrate different types of omics data and perform association analyses to identify important players and mechanisms (e.g., *mixOmics*). TkNA, however, is a unique causal-inference analytical framework that can perform meta-analysis and identify the regulatory relationships between entities. This approach was used in a study of antibiotic-resistant microbes[1] to identify key host genes, microbes and molecular mechanisms in type 2 diabetes[2]. TkNA has also been used to characterize the role of the microbiome in cervical cancer, lymphoma and melanoma[3-6]. Note: Throughout the paper we use the word "integration" to refer to two very different analyses: meta-analysis is integration of data from several independent datasets and network reconstruction involves integration that establishes statistical dependencies between multiple types of omics data.

In this protocol, we describe in detail how to use TkNA to detect master regulators (causal factors) among microbes and microbial genes, host pathways and host genes, and other measured variables that govern pathological or physiological responses of host-microbiota interactions in a particular condition or disease. Note that although the TkNA approach was developed to investigate host-microbiota interactions, its underlying basis involves fundamental principles including laws of causality, graph theory and information theory. Hence, TkNA can be used for causal inference via network analysis of any multi-omics data collected regardless of if those data were measured in the same samples or measured in different organs from the same biological replicates of animals (humans, mice, other animals) and/or environmental niches.

Overview of the procedure

The TkNA pipeline consists of three major sections (**Figure 1**). **Section 1 reconstructs the network**. This involves importing the data, performing calculations, and filtering the data as

specified by the user. Specifically, differentially expressed/abundant variables (genes, microbes, metabolites, etc.) between classes (e.g., disease and control) are found, based on user-defined statistical criteria. Next, per-group correlations are performed within and between each type of omics/kingdom separately. To override the default comparison and correlation methods, appropriate parametric or non-parametric methods can be selected by the user. TkNA additionally identifies robust and reproducible patterns of fold change direction and signs (positive or negative rho coefficient) of correlation across several cohorts (or experimental replicates). Following this, correlations are further filtered based on a causality-reflecting metric, correlation inequalities, where within-class correlations with the opposite sign of coefficient than would be expected by the fold change direction of the variables in the edge[7] are removed (e.g., if both variables of the edge are increased or decreased in the disease class compared to the control class, the expected per-group sign of correlation is positive and therefore negative correlations would be removed). Finally, TkNA calculates a set of topological criteria, including network density, the deviation of observed positive:negative correlations from expected, and the proportion of unexpected correlations[7] (PUC). The user employs these metrics to determine the quality of the reconstructed network by comparison to a "typical" networks (networks we have calculated [5,8-14]). If the network is deemed suitable for downstream analysis, the user moves on to the network analysis step. Otherwise, the user changes their statistical thresholds and performs another reconstruction as described above. Of note, one of the output files of this step is a CSV file of the network, which the user can visualize in an external program such as Cytoscape[15].

Figure 1. Flowchart of the TkNA pipeline.

Section 2 is the interrogation/analysis of the reconstructed network. In this step, the user first has the option to identify clusters of nodes in the network using the Louvain[16] or Infomap[17] algorithms. Using alternative recommended software, they can then perform enrichment analysis of the clusters to identify biological pathways/functions to which the nodes in the cluster contribute. Regardless of whether cluster identification is performed, the next step in TkNA is to perform calculations of a set of network, subnetwork, and node properties. While many different

topological properties are calculated, key among these are node properties that indicate regulatory nodes in the network. This includes calculating bipartite betweenness centrality[18] (BiBC), a global node topology metric, to find the nodes participating highest in the information flow between user-defined regions of the network. Degree is a key local node property that is calculated, which is a measure of how many other nodes to which a single node connects. High BiBC and high degree reflect "bottleneck" and "hub" nodes, respectively. Consequently, a node with a high degree and BiBC is considered to be a strong regulatory candidate in the network. Optionally, the user can also calculate shortest path lengths between each pair of nodes in two separate subnetworks. Two subnetworks with a shorter average shortest path length interact more than subnetworks that are farther away from one another. To wrap up section 2 and evaluate the probability of a given node to show nonrandom values of degree and BiBC, TkNA reconstructs many random networks (10,000 by default) with the same number of nodes and edges as the reconstructed network and compares the top degree/BiBC nodes of those random networks to the reconstructed network.

Section 3 of TkNA creates publication-ready figures from the above analysis of the user's reconstructed network. Multiple **high-quality** figures are created in this step, including dot plots of degree distribution (not shown in figure) and dot plots of nodes and their calculated properties (**Figure 5a**). The abundance (microbial data), expression levels (genes), etc. of the top regulatory candidates are also automatically generated (**Figure 5b**), as well as the 2D density plot previously mentioned (**Figure 5c**). These 2D density plots have the observed values of the top regulatory nodes from the reconstructed network overlayed on top of them. CSV files are also created with all the information needed for plotting if the user wishes to use an alternative software for visualization purposes.

Procedure

Pre-requirements for using TkNA

Currently, TkNA is only supported on Unix based devices. From a Unix device, a user will need to have access to git on their terminal and have an SSH key for their GitHub account (see https://docs.github.com/en/authentication/connecting-to-github-with-ssh/adding-a-new-ssh-key-to-your-github-account for more information). If the user does not already have git downloaded, he or she can do so using the commands found on github's documentation at https://github.com/git-guides/install-git.

Software Setup

1. Obtain TkNA
Download the TkNA code from https://github.com/CAnBioNet/network_calculations.git and enter its directory.

```
git clone git@github.com:CAnBioNet/network_calculations.git
cd network_calculations
```

2. Install Miniconda

We highly recommend that users manage their installation using conda as their package management software. If it is not already installed on the system, you can install Miniconda (which contains both python and conda) from https://docs.conda.io/en/latest/miniconda.html. Since TkNA was written and tested in Python version 3.8.10, we recommend the user installs the Python 3.8 Miniconda version.

3. Set up the TkNA environment

Create a new Python 3.8.10 conda environment. Install the python packages specified in the `requirements.txt` file included with the source code.

```
conda create -n TkNA python=3.8.10
pip install -r requirements.txt
```

Data Preprocessing

4. Normalize data

It is known that non-normalized data leads to bias in the structure of correlation networks[19,20].

Prior to running TkNA, the user needs to perform any appropriate normalizations. Normalization is not performed in TkNA, so data should be normalized using one of these methods. Examples of common normalization methods for different omics data are listed in **Table 1**.

Omics type	Normalization method	Software or Package
Transcriptome (RNA-seq)	Reads per million (relativization); RPKM; FPKM; Quantile; Lowess; Trimmed Mean of M-values (TMM); Relative Log Expression (RLE)	Affy (R)[21]; BRB Array tools; DESeq2 (R)[22]; EdgeR (R)[23]
Microbiome (amplicon or shotgun)	Reads per million (relativization); Rarefaction; CSS; Quantile	Qiime2[24], metagenomeSeq (R)[25]
Metabolomics	Normalization to internal standard; normalization to urine output; normalization to total spectral area; probabilistic quotient normalization[26]; Bridge normalization; Median run normalization[27], EigenMS normalization[28]	MetabR (R)[29], ProteoMM (R)[30], OpenMS[31], pyOpenMS (python)[32]
Proteomics	Linear regression normalization; Local regression normalization; Variance stabilization normalization; Quantile normalization,	proteiNorm[33], OpenMS[31], pyOpenMS (python)[32]

Table 1. Common normalization methods for omics types and examples of packages that perform the normalization methods.

5. Format data

The data must be placed into a directory and arranged as shown in **Figure 2**. This format divides the data and metadata into 4 kinds of files:

a. Processed (normalized and log2 transformed) data tables

Each data table associated with an experiment present in the data must be formatted as comma-separated values (CSV) with one column per experimental unit (i.e. sample) and one row per variable; for example, a gene, microbe, or phenotype. The top left cell must contain only the text "ID".

b. Sample mapping file

Each experimental unit present in the data must be associated with an experimental class (e.g. Disease, Control), identified by a text string. These associations are specified as lists of comma-separated values, with the left column containing the name of the experimental unit and the right column containing the class. All names must match exactly across data files. TkNA is designed to only work with two classes at a time. Note: In the pipeline, the sample mapping file is called "treatmentMapFile" in the metadata .json file and the sample groups to compare are the ones used in "comparisonTreatments" in the config .json file.

c. Omics type mapping file

Each variable (e.g. microbe, gene, metabolite, etc.) present is associated with a type of -omic data, identified by a text string. These associations are specified as lists of comma-separated values, with the left column containing the variable and the right column containing its type. All names must match exactly across data files.

Figure 2. Structure of the network_calculations repository, including all folders and the main scripts required for the user to reference in their commands. We recommend the user creates a directory like the one at the bottom of the figure, where all the input files are stored and where they will direct the output files to write to in their commands.

d. Metadata summary

The dataset must contain a file named `metadata.json` in the JavaScript Object Notation (JSON) format, as shown in **Figure 3**. This file describes each experiment present in the data and indicates the names and locations of the necessary files. At the top-most level, it consists of 3 sections:

i. Dataset name

A name to which the dataset will be referred by.

ii. Experiment descriptions

A list of experiments whose data is present in the dataset. Each description contains a name for the experiment, the relative path of the CSV file containing its data table, and the relative path of the treatment map for its experimental units.

iii. Type map

The relative path of the type map for all of the variables present in the data.

Figure 3. Example metadata and configuration (config) .json files. **a)** The structure required to run the network reconstruction code for a single dataset. In this example, the user has a single experimental dataset (as seen in the metadata file) with two classes they would like to compare: Disease and Control (as seen in the config file). They have then specified which comparison statistical thresholds to apply ("differencePValueThresholds") for individual p-value, Fisher's combined (meta-analysis) p-value, and the Benjamini-Hochberg FDR (called "corrected" in the config file). Additionally, they have specified they want to perform the correlations only in the Disease class ("networkTreatment") and specified the edge statistical criteria ("correlationPValueThresholds") towards the bottom of the file. **b)** The structure required for more complex data with multiple experiments and data types. This user has four total datasets, as well as an additional "pheno" variable type in their input data (genes and phenotypes), so they have added the additional "pheno" variable to the file. They have set the same comparison thresholds for both variable types, though this is not required. Down below, they have specified they want to find only edges that are consistent in the Disease class of three of the four experiments (as can be seen by the 0.75 for "correlationFilterPercentAgreementThreshold" and the "metatreatments" sections). Then they specified the edge thresholds for each pair of data types (gene-gene, gene-pheno, and pheno-pheno). Please note: filtering edges for the same direction across only a fraction of datasets is not a good strategy when using a small number of datasets (less than five), but was done in this example for simplicity. Also note that the structure of .json files is highly specific and the addition of extra characters in the files may cause issues.

Data Import

6. Import data

Import the data into a consolidated format for further processing with the script
`reconstruction/intake_data.py`.

> **Usage**
>> `python3 intake_data.py --data-dir <data directory> --out-file`
>> `<output file>`
>
> **Example command**
>> `python3 intake_data.py --data-dir ./input/all_genes/ --out-file`
>> `./output/all_data_and_metadata.cdf`
>
> **Inputs**
>> `--data-dir`: Path to the directory containing all experimental file(s), metadata file(s),
>> and config file(s)
>>
>> `--out-file`: path to file (with .cdf extension) that will be created
>
> **Outputs**
>> • A single `.cdf` file containing most information required for the next step

Network Reconstruction

7. Reconstruct network

Network reconstruction is performed with the script `reconstruction/run.py` and uses a
configuration file in the JSON format (**Figure 3**).

> **Usage**
>> `python3 run.py --data-source <file_name> --config-file <config`
>> `file> --out-file <zip directory>`
>
> **Example command**
>> `python3 run.py --data-source`
>> `./output/all_genes/all_data_and_metadata.cdf --config-file`
>> `./input/all_genes/cervical_cancer_config.json --out-file`
>> `./output/all_genes/network_output.zip`
>
> **Inputs**
>> `--data-source`: Path to the .cdf file created using intake_data.py
>>
>> `--config-file`: Path to the config file used for intake_data.py
>>
>> `--out-file`: path to zipped directory that will be created
>
> **Outputs**
>> • A single zipped directory containing the analysis performed

Reconstruction takes place in the following steps. For each step, the available configuration
options are described. For examples of the config file, please refer to **Figure 3**.

> **i. Establish differentially expressed/abundant variables (genes, microbes, metabolites, etc.) between classes (e.g., disease and control).**

Setting the appropriate statistical thresholds to apply while reconstructing the network is the most critical step in determining the size and quality of the resulting network. Thus, it is crucial that the user sets statistical thresholds that are best suited for the type of data they are using. For finding differentially expressed/abundant variables between classes, we recommend that the user initially uses the default thresholds supplied in the code: p-value < 0.2, Fisher's combined (meta-analysis) p-value < 0.05, and Benjamini-Hochberg FDR < 0.1. If the reconstructed network is not of sufficient quality (see step 9 "Assessing network quality") or size (an experienced user may consider the network too small) then the user can select different thresholds to apply.

At this stage of analysis, it is not recommended to relax thresholds more than the following: individual p-value, 0.5; Fisher's combined p value, 0.1; and FDR, 0.2. Note that relaxed thresholds can be used at this stage because nodes will be further eliminated in the next step of the analysis.

Required config parameter: `comparisonTreatments`
  A list containing the names of exactly two treatments. Fold change is computed with respect to the first of the two.

  Example: `"comparisonTreatments": ["control", "disease"]`

Optional config parameter : `differencePValueThresholds`
  A mapping between each kind of statistic and its threshold. Can contain:

  individual: Minimum p-value across all experiments
      Default: 0.2
  combined: p-value combined across experiments (e.g. via Fisher's method)
      Default: 0.05
  corrected: p-value after correction (e.g. via FDR)
      Default: 0.1

  NOTE: We strongly recommend using more than one dataset for the TkNA analysis. However, if the user only has one dataset, they need to ensure the individual p-value threshold and combined p-value threshold are the same value.

  Example: `"differencePValueThresholds": {"individual": 0.1, "combined": 0.02, "corrected" 0.15}`

  Optionally, for each kind of statistic, thresholds can be specified per type of variable.
  Example: `"differencePValueThresholds": {"corrected": {"gene": 0.1, "phenotype": 0.15}}`

ii. **Identify robust and reproducible patterns for fold change direction across several experimental replicates (if user has multiple independent experiments)**

Optional config parameter : `foldChangeType`
    Calculate fold change using the median or the mean.

    Choices: `median`, `mean`
    Default: `median`

    Example: "`foldChangeType`": "`mean`"

Optional config parameter : `foldChangeFilterMethod`
    Choose how strictly the fold changes of variables must be consistent across experiments.

    Choices: `allsamesign`, `percentagreement`
    Default: `allsamesign`

    Example: "`foldChangeFilterMethod`": "`percentagreement`"

    If using percent agreement, the following option may also be specified:

    `foldChangeFilterMethodPercentAgreementThreshold`
        A percentage (between 0 and 1) of experiments which must agree in fold change for a variable to pass the filter.

        Default: 0.5

        Example: "`foldChangeFilterMethodPercentAgreement`": 0.75

iii. **Determine significant correlations for a treatment within and between each type of variable (e.g. gene-gene, gene-microbe, microbe-microbe, etc.) separately.**

To calculate correlations between the previously-identified differentially expressed/abundant variables between classes, we recommend that the user initially uses the default thresholds supplied in the code: p-value < 0.2, Fisher's combined (meta-analysis) p-value < 0.05, and Benjamini-Hochberg FDR < 0.1. If the reconstructed network is not of sufficient quality (see step 9 "Assessing network quality") or size (an experienced user may consider the network too small) then the user can select different thresholds to apply.

At this stage of analysis, it is not recommended to relax thresholds more than the following: individual p-value, 0.5; Fisher's combined p value, 0.05; and FDR, 0.15.

    Required config parameter : `networkTreatment`
        The name of a treatment.
        Example: "`networkTreatment`": "`disease`"

Optional config parameter: `correlationMethod`
The method to use for calculating correlations.

Choices: `spearman, pearson`
Default: `spearman`

Optional config parameter: `correlationPValueThresholds`
A mapping between each kind of statistic and its threshold. Can contain:

individual: Minimum raw p-value across all experiments
Default: 0.2
combined: p-value combined across experiments (e.g. via Fisher's method)
Default: 0.05
corrected: p-value after correction (e.g. via FDR)
Default: 0.1

Example: "`correlationPValueThresholds`": {"`individual`":
`0.1, "combined": 0.02, "corrected" 0.15}`

Optionally, for each kind of statistic, thresholds can be specified per combination of types of variable.

Example:

```
"correlationPValueThresholds": {"corrected": {
    "(gene, gene)": 0.1,
    "(gene, phenotype)": 0.15,
    "(phenotype, phenotype)": 0.2
}}
```

iv. **Identify robust and reproducible patterns for correlation direction across several cohorts (or experimental replicates).**

Optional config parameter: `correlationFilterMethod`
Choose how strictly the correlations of variables must be consistent across experiments.

Choices: `allsamesign, percentagreement`
Default: `allsamesign`

Example: "`correlationFilterMethod`": "`percentagreement`"

If using `percentagreement`, the following option may also be specified:

`correlationFilterPercentAgreementThreshold`

A percentage (between 0 and 1) of experiments which must agree in correlations for a variable to pass the filter.

Default: 0.5
Example: "correlationFilterMethodPercentAgreement": 0.75

v. **Eliminate edges that are not related to causes underlying the transition between classes (e.g. between disease and control)**

This step is performed automatically. The edges removed are defined as "unexpected correlations"[7].

8. Write computed data to tables
Write the data obtained during network reconstructing to tables in CSV format with the script `reconstruction/to_csv.py`.

Usage
```
python3 to_csv.py --data-file <zip file> --config-file <config file> --out-dir <output directory>
```
Example command
```
python3 to_csv.py --data-file
./output/all_genes/network_output.zip --config-file
./input/all_genes/cervical_cancer_config.json --out-dir
./output/all_genes/network_output
```
Inputs
`--data-file`: .zip file created with run.py
`--config-file`: Path to the config file used for intake_data.py
`--out-dir`: Path to the directory to output results to
Outputs
- `all_comparisons.csv`: contains all comparisons performed in the analysis, is not filtered for any significant variables
- `correlations_bw_signif_measurables.csv`: all correlations between variables that passed the comparison thresholds. Correlations in this file are not filtered for statistical or causality criteria, but it contains all p-values, whether each edge is unexpected, and whether each edge makes it into the final network after applying statistical and causality criteria
- `network_output_comp.csv`: whole network with nodes/edges under the user-defined statistical thresholds, and edges consistent in direction retained (unless otherwise specified in the configuration file). Unexpected edges are also removed from this file.
- `node_comparisons.csv`: comparisons that were performed and found to be statistically significant (less than the user-defined statistical thresholds).
- `config_values.txt`: All the user-specified options for making the network

Network quality assessment

Once the network has been reconstructed, the next step is to determine whether the network is suitable for downstream analysis. If the network is not suitable for downstream analysis, the user will need to modify their statistical thresholds to reconstruct a better-suited network.

While as yet there is no completely automated method of network optimization, we recommend the user evaluates three network properties that are calculated with TkNA: 1) the proportion of unexpected correlations (PUC); 2) density (the number of edges in the network over the number of edges in a full graph of the same size); and 3) the deviation of the ratio of positive/negative edges from the expected value. In **Table 1** we provide the ranges of each of these criteria from previously published networks that can guide the user's decision process. Note that microbiome data usually presents higher PUC values than diverse host omics data (e.g. transcriptomes, metabolomes, etc.). The user can also compare their values with those of published networks (**Figure 4a-b**).

Figure 4. a) Density of within-omic and between-omic edges in published networks. Each point represents a previously published network. Density is calculated as the number of observed edges over the number of possible edges between all nodes of that type. The blue bar indicates the average of each –omic type. **b)** The deviation from the expected positive/negative edge ratio of published networks. Each point represents a previously published network. The blue bar indicates the average.

We encourage new users to use the **<u>default statistical thresholds</u>** for reconstructing their initial network, then adjust the thresholds accordingly after assessing the network quality. Suggestions for alterations in thresholds based on the resulting network assessment properties can be found in **Table 2**.

Network property	Potential range	If value is too high…	If value is too low…
Departure of ratio positive:negative edges	See figure 4a	Try alternative normalization	Try alternative normalization
Density	Dependent on -omic type, see figure 4b	Reduce statistical thresholds (p-values or FDR) for edges	Relax statistical thresholds (p-values or FDR) for edges

Table 2. Suggestions for changes to make if the network quality metrics are too high or too low compared to those of previously published networks.

9. Assessing Network Quality

Usage
```
python assess_network.py --file <network file>
```
Example command
```
python assess_network.py --file ./output/all_genes/network_out-
put/ correlations_bw_signif_measurables.csv
```
Inputs
--file: `correlations_bw_signif_measurables.csv` file created with to_csv.py
Outputs
- `network_quality_assessment.txt`: Contains the calculations (also sent to standard output) on the quality of the reconstructed network. Outputs to the same directory the input file is stored in.
- `network.pickle`: A pickled file containing the network. Used as input to future steps. Outputs to the same directory the input file is stored in.

Network analysis

Once the user has reconstructed a network from the input data, they can move on to the network analysis stage. In this stage, the user can optionally find clusters (also called subnetworks or modules) of nodes and use alternative tools to determine if these clusters are enriched for particular biological processes. He or she can then further interrogate the network to find key regulatory nodes in the network.

10 (OPTIONAL)

a. Identifying clusters of nodes

One commonly performed technique in network analysis is to identify regions in the network where nodes are clustered together. TkNA allows for the use of two popular algorithms, Infomap[17] and the Louvain[16] method, to detect clusters in the network.

Infomap
Usage

```
python infomap_assignment.py --pickle <file.pickle>
```
Example command
```
python infomap_assignment.py --pickle network.pickle
```
Inputs
--pickle: `network.pickle` file output by assess_network.py
Output
- `network_infomap_partition.csv`: .csv file containing the name of the node in column 1 and the subnetwork number it was assigned in column 2.

Louvain
Usage
```
python infomap_assignment.py --pickle <file.pickle>
```
Example command
```
python Louvain_partition.py --pickle network.pickle
```
Inputs
--pickle: `network.pickle` file output by assess_network.py
Output
- `network_infomap_partition.csv`: .csv file containing the name of the node in column 1 and the subnetwork it was assigned in column 2.

b. Perform functional enrichment analysis for groups of nodes

Following clustering, a user can then perform functional enrichment of either 1) the clusters identified via Infomap/Louvain or 2) any other predefined groups (e.g. microbes, genes), allowing for a biological interpretation of the nodes in that cluster. Single cell RNAseq data can also be used to infer cell type information for the genes in the network. These enrichment methods are not part of TkNA and will need to be performed using alternative software. Examples of common functional enrichment methods for different omics data are listed in Table 2.

Omics type	Enrichment method	Software or Package
Transcriptome (RNA-seq)	Gene ontologies or Functional enrichments; Over representation analysis; Biochemical Pathways; Signaling pathways; Regulatory pathways; Protein -protein interactions	Cytoscape; Metascape; InnateDB; GSEA; KEGG; Reactome; STRING
Microbiome (amplicon or shotgun)	Comprehensive functional content	MicrobiomeAnalyst PICRUSt
Metabolome	Pathways	MetaboAnalyst
Proteome	Gene ontologies or	KEGG;

	Functional enrich-ments; Pathways	Reactome; STRING

11. Finding key regulatory nodes in the network

This step calculates network, subnetwork, and node topological properties[34]. Network properties that are calculated by TkNA include the number of nodes in the network, number of edges, mean degree, average clustering coefficient, the size (number of nodes) of the giant component compared to the size of the whole graph, the number of connected components, mean closeness centrality, degree assortativity[35], maximum modularity[16], network fragmentation[36], and Freeman centralization[37]. Subnetwork properties include the mean degree of the subnetworks/clusters (either pre-defined by the user or identified in the optional step 10) in the network. Finally, calculated node properties include degree, clustering coefficient, closeness centrality, eigenvalue centrality, betweenness centrality, number of second neighbors, and bipartite betweenness centrality (BiBC)[18]. Two of those properties, degree and BiBC, are used to predict nodes with potential regulatory roles in the network. Degree is the number of other nodes a single node connects to. Accordingly, high degree nodes called hubs control the biological pathway/cluster they belong to.

BiBC is a measure of the bottleneck-ness of a node (i.e. which node serves as the best 'bridge') between two pre-defined groups[18]; it is essentially betweenness centrality restricted to particular subsets of the network (i.e., two subgraphs/clusters of biological interest). A node with a high BiBC likely mediates the communication between pathways/clusters. To compute BiBC, the user will need to provide a list of nodes, as well as which cluster they belong to in the network. If the user wishes to perform the BiBC calculation between types of nodes (for example, genes and microbes), they can supply the original sample mapping file. Alternatively, if the user wishes to use the clusters identified with Infomap or Louvain (the optional Step 10), they can supply the output of Step 10 and select two group numbers from the second column as their clusters to use for the BiBC calculation.

Usage
```
python calc_network_properties.py --pickle <file.pickle> --bibc -
-bibc-groups <choice> --bibc-calc-type <choice> --node-map
<file.csv> --node-groups <group 1> <group 2>
```

Example command
```
python calc-network-properties.py --pickle network.pickle --bibc
--bibc-groups node_types --bibc-calc-type rbc --node-map
map_file.csv --node-groups micro pheno
```

Inputs and arguments
```
--pickle
```
: network.pickle file created with assess_network.py

--bibc: Flag for whether to compute Bipartite Betweenness Centrality (BiBC). This is highly recommended and also required for future steps

--bibc-groups: Choice for what to compute BiBC on, either distinct groups (node_types) or on the two most modular regions of the network (found using the Louvain method)

--bibc-calc-type: Choice for whether to normalize based on the amount of nodes in each group (rbc) or not (bibc)

--node-map: csv file containing the name of nodes in the first column and the type of the node (gene, phenotype, microbe, etc.) in the second column

--node-groups: Required if node_types is specified for --bibc-groups. It's the two groups of nodes to calculate BiBC/RBC on. The types must be present in the --node-map file

Outputs
- `network_properties.txt`: Tab-delimited .txt file of calculated network properties
- `subnetwork_properties.txt`: Tab-delimited .txt file of calculated subnetwork properties
- `node_properties.txt`: Tab-delimited .txt file of calculated node properties

Estimating probability to find top nodes (degree, BiBC) randomly

The next step in TkNA is to determine the likelihood of finding the top nodes (degree, BiBC) randomly in the reconstructed network by comparing to size-matched random networks with the same number of nodes and edges[10]. Later on in the pipeline, the user can visualize how top nodes of their reconstructed network compares to the top nodes of these random networks through the creation of a 2D density plot (**Figure 5d**).

12. Creating random networks

This step creates all the random networks and saves them to be analyzed in the next step.

Usage
```
python create_random_networks.py --template-network <file.pickle>
--networks-file <file.pickle>
```
Example command
```
python create_random_networks.py --template-network net-
work.pickle --networks-file all_random_nws.pickle
```
Inputs
--template-network: The pickled network file output by assess_network.py
--networks-file: File to output pickled network list to
Outputs
- A single pickle file containing all created networks

13. Analyze random networks

Each randomly generated network is then analyzed to calculate the degree and BiBC of each node in the network.

Usage
```
python compute_network_stats.py --networks-file <file.pickle> --
bibc-groups <choice> --bibc-calc-type <choice> --stats-file
<file.pickle> --node-map <file.csv> --node-groups <group1>
<group2>
```
Example command
```
python compute_network_stats.py --networks-file all_ran-
dom_nws.pickle --bibc-groups node_types --bibc-calc-type rbc --
stats-file all_rand_network_results.pickle --node-map map.csv --
node-groups gene pheno
```
Inputs

`--networks-file`: pickled file created with create_random_networks.py that contains all random networks previously created

`--bibc-groups`: Group nodes for BiBC based on type or modularity

`--bibc-calc-type`: Compute raw BiBC or normalize (rbc)

`--stats-file`: Pickle file to output the network stats to

`--node-map`: CSV file mapping nodes to their types. Required if node_types is specified for --bibc-groups.

`--node-groups`: Two types of nodes to use for BiBC grouping. Required if node_types is specified for --bibc-groups.

Outputs
- A single .pickle file with degree/BiBC results of all random networks

14. Condense random network results into a single output file

The results of the analysis are then summarized into a single output file containing the node with the highest degree value and its associated BiBC (or vice versa) in the each of the networks.

Usage
```
python synthesize_network_stats.py --network-stats-file
<file.pickle> --synthesized-stats-file <file.csv>
```
Example command
```
python synthesize_network_stats.py --network-stats-file
all_rand_network_results.pickle --synthesized-stats-file
top_node_each_random_nw.csv
```
Inputs

`--network-stats-file`: pickled file created with compute_network_stats.py

`--synthesized-stats-file`: Name of the .csv file that will be created

Outputs

- A single .csv file that contains the top node, sorted first by BiBC and then by Node_degrees (unless otherwise specified with --flip-priority), for each of the random networks

Plot results

15. Create degree distribution and dot plots

In this step, the user specifies which two node properties they would like to visualize for the nodes of the network, as well as selects how many top nodes to focus on and label. Additionally, the `--top-num-per-type` argument is used to specify how many top nodes per data type to zoom in on and label in the resulting plots. Examples of these visualizations can be seen in **Figure 5**.

Usage
```
python dot_plots.py --pickle <file.pickle> --node-props
<file.txt> --network-file <file.csv> --propx BiBC --propy
Node_degrees --top-num <integer> --top-num-per-type <integer>
```
Example command
```
python dot_plots.py --pickle network.pickle --node-props node-
properties.txt --network-file network_output_comp.csv --propx
BiBC --propy Node_degrees --top-num 5 --top-num-per-type 3
```
Inputs
- `--pickle`: pickled file created with assess_network.py
- `--node-props`: node_properties.txt file created with calc_network_properties.py
- `--network-file`: network_output_comp.csv file created with to_csv.py
- `--propx`: Node property to plot on X-axis
- `--propy`: Node property to plot on Y-axis.
- `--top-num`: Number of nodes you want to zoom in to on the property v property plot
- `--top-num-per-type`: The number of nodes to plot for each data type when zoomed in on the plot

Default outputs
- `degree_distribution_dotplot.png`: Distribution of the number of nodes which each degree in the network
- `<propx>_v_<propy>_distribution.png`: A dot plot of user-specified node properties
- `<propx>_v_<propy>_distribution_<node_type>_nodes_only.png`: Same as previous plot, but with just the nodes from each data type. There will be one plot produced for each data type
- `<propx>_v_<propy>_distribution_top_<top-num>_nodes.png`: Same as the second plot, but zoomed in on the top nodes
- `<propx>_v_<propy>_distribution_top_<top-num-per-type>_nodes_<data_type>_only.png`: same as third plot, but zoomed in on the top nodes per data type.

16. Create abundance plots

This step creates abundance/expression plots of the top nodes in the network, which are the same nodes that were labeled in the previous step. These figures can be grouped according to class (called 'Treatment' in the program) or Experiment.

Usage
```
python plot_abundance.py --pickle <file.pickle> --abund-data
<list of files> --metadata <list of files> --color-group <choice>
--x-axis <choice>
```
Example command
```
python plot_abundance.py --pickle inputs_for_down-
stream_plots.pickle --abund-data Expt1.csv Expt2.csv --metadata
Expt1_meta.csv Expt2_meta.csv --color-group Treatment --x-axis
Experiment
```
Inputs

`--pickle`: `inputs_for_downstream_plots.pickle` file output by `dot_plots.py`

`--abund_data`: List of data files containing expressions/abundances

`--metadata`: List of metadata files containing Experiment/Treatment columns

`--color-group`: Variable to color the plot by

`--x-axis`: Variable you wish to group the data by on the x-axis

Outputs
- One boxplot for each of the top nodes (found in dot_plots.py) as well as additional plots if specified with the optional argument --nodes-to-plot

17. Create 2D density plot

The last step of TkNA is to create a 2D density plot using the random network results from step 14. This step will take the nodes that were labeled in step 15 and plot them on top of the density plot. It also labels the nodes with the names and probability of a randomly generated network having a node with a higher degree and BiBC than each plotted node.

Usage
```
python plot_density.py --rand-net <file.csv> --pickle
<file.pickle>
```
Example command
```
python plot_density.py --rand-net synthesized_networks.csv --
pickle inputs_for_downstream_plots.pickle
```
Inputs

`--rand-net`: file output by synthesize_network_stats.py

`--pickle`: inputs_for_downstream_plots.pickle file output by dot_plots.py

Default outputs
- `density_plot_with_top_nodes_from_dotplots.png`: contour plot with the top nodes (found in dot_plots.py) from the real reconstructed network overlaid on top

- `density_plot_with_top_<data_type>_nodes_only.png`: Same as previous, but contains just one data type per output file

Figure 5. a) Left: Example node property visualization, where each point represents a node in the reconstructed network. **Right:** Same graph, zoomed in on the top 5 microbe BiBC nodes **b)** Example abundance/expression plot of the top BiBC node found in b. Legend is the two classes that were in the dataset. In this case, a class of samples named 'high' was compared to a class named 'low' **c)** 2D density plot of the 10,000 random networks with the top nodes from b overlaid.

Applications of the method

Although this methodology was originally designed to uncover the interactions between two kingdoms, this approach can easily be used for the analysis of more general types of multi-omics data. For example, TkNA can be used to analyze the interaction between genetic and transcriptional data, metabolites, proteins, and phenotypes.

Comparison with other methods

The TkNA approach relies on performing meta-analysis of comparisons and correlations. The goal is to identify robust patterns of fold-change or correlations across multiple cohorts. By

default, it uses Fisher's method to combine p-values from several independent tests. Other general R packages (e.g., *meta[38], netmeta[39], mixmeta[40]*) offer several methods for meta-analysis that can be used along with the principals of TkNA. Other well-known R packages (e.g., *MixOmics[41], MOFA2[42,43], iClusterPlus*) use sophisticated statistical methods to combine multiple -omics data measured from the same patients. However, their application to several cohorts simultaneously or their application uniquely to -omics data (where the data composition or distributional assumptions are not met) can be challenging. TkNA provides a framework to achieve simultaneous integration of multiple -omics types and cohorts.

While many tools claim a gene or microbe to be "important" based on association analysis, TkNA specifically identifies **<u>causal</u>** players rather than only associations in host-microbiota interactions.

One of the most popular approaches to determine causality thus far is an application of the Mendelian Randomization[44,45] (MR) method for the inference of microbes causally contributing to a given host trait. Although this method has a robust theoretical framework, it has two main drawbacks. First, because it is based on differences in causal signals between alleles present in the normal human population, it requires huge sample sizes (e.g., thousands, akin to GWAS) that are often not available, particularly when working with mice. Second, allelic differences in humans control a very small amount of microbiome variability, which then limits the approach's utility to a small handful of microbes clearly regulated by common polymorphisms.

More recently, a variety of regression approaches to causal inference in microbiome experiments have been developed, most of which are based on (linear) structural equation models, which have been around in one form or another for more than a century. The Sparse Microbial Causal Mediation Model (SparseMCMM)[46] is a recent example. While promising, these group of methods have not been tested in new studies that would experimentally validate model inferences. These approaches deal with the large number of possible covariates (host genes or genetic markers) via either regularization or PCA-type transformation to a reduced set of covariates, potentially making interpretation of gene mediators difficult. Finally, these methods ignore any structure to the covariates (gene-gene interactions) or the microbes (taxa-taxa interactions).

Experimental design

TkNA requires collection of data from at least two classes (e.g. disease, control). For statistical considerations, we strongly recommended using two or more independent cohorts/experiments, which allow for the implementation of meta-analysis ensuring the robustness of inferences from TkNA.

Furthermore, the inferred pathways and top nodes would be biologically informative under any circumstances. However, if additional information allows for the implementation of an "instrumental variable"[47], the directionality of interactions between kingdoms or pathways can be also established. For example, when someone studies effects of antibiotics on the host, it is a

reasonable assumption that it is mostly mediated by microbes[8,14]; thus microbes in the network can serve as instrumental variables in this case.

Expertise needed to implement the protocol

The target audience for this protocol is researchers working in the host and/or microbiome field with minimal computational expertise. Our method can be also used in biological and biomedical research across **multiple disciplines** ranging from the establishment of new cellular and molecular targets of treatment to fundamental biological questions. This protocol does not require programming expertise; however, users should be comfortable running programs from the command line in the Unix environment, and should learn a bit about the JSON file format in order to be able to customize and modify their run parameters.

Limitations

A basic understanding of statistics is expected from the user to understand the suitability of the software to their experimental setup and any inherent limitations of the approach. For example, Fisher's method is the default method implemented by this software for combining p-values from independent tests with the same null hypothesis. However, if the same control group is used in calculating the effects of different treatments (or over time), the effect sizes are non-independent. Since the tool cannot automatically detect this dependence and will proceed with the analysis, the user will need to realize that alternative methods to conduct a meta-analysis with non-independent effect sizes[48] will be more suitable in this case.

The only aspect of the TkNA approach that can be considered as a critical limitation is related to the fact that it provides inferences of causality only when the appropriate study design is used (this is not unique to TkNA but would be a limitation of any causal inference approach). For example, to define the directionality of a process, as with any other causal inference application (including those mentioned above), it requires study designs that would confer with the assumptions needed for mediation analysis or for instrumental variable analysis. Since most standard biomedical experiments are designed as "double blind randomized studies" or contain an instrumental variable, TkNA is very powerful for causal inference from multi-omic data.

Materials

Required hardware
We recommend the user runs TkNA with a Unix-based machine with at least an i5 processor or similar, 6 cores, and 16 GB of RAM. For large datasets, we recommend a minimum of 100 GB of free space on the user's hard drive.

Required software and modules
- Miniconda with python 3.8.10 - https://docs.conda.io/en/latest/miniconda.html
- git (as well as a GitHub account) - https://github.com/git-guides/install-git
- Cytoscape - https://cytoscape.org/download.html

- All required modules are in the requirements.txt file in the repository. See step 3 in "Software setup" for how to create a virtual environment and install all the necessary modules to run TkNA.
- Text editing software such as Notepad++ (https://notepad-plus-plus.org/downloads/) or a source-code editor (recommended) such as Visual Studio Code (also known as VS Code) for creating the input files. VS Code aids in the process of writing JSON files.

Code availability

Codes used in this protocol are publicly available at https://github.com/CAnBioNet/network_calculations.

Acknowledgements

The funding that supports this work is AI157369 (AM), DK103761 (NS), DK107603 (AM) and BC011153 (GT). SP and MM were supported by the summer fellowships from the College of Pharmacy at Oregon State University.

References:

1. Morgun, A., *et al.* Uncovering effects of antibiotics on the host and microbiota using transkingdom gene networks. *Gut*, gutjnl-2014-308820 (2015).
2. Rodrigues, R.R., *et al.* Transkingdom interactions between Lactobacilli and hepatic mitochondria attenuate western diet-induced diabetes. *Nature communications* **12**, 1-15 (2021).
3. Davar, D., *et al.* Fecal microbiota transplant overcomes resistance to anti–PD-1 therapy in melanoma patients. *Science* **371**, 595-602 (2021).
4. Lam, K.C., *et al.* Microbiota triggers STING-type I IFN-dependent monocyte reprogramming of the tumor microenvironment. *Cell* **184**, 5338-5356. e5321 (2021).
5. McCulloch, J.A., *et al.* Intestinal microbiota signatures of clinical response and immune-related adverse events in melanoma patients treated with anti-PD-1. *Nature Medicine* **28**, 545-556 (2022).
6. Spencer, C.N., *et al.* Dietary fiber and probiotics influence the gut microbiome and melanoma immunotherapy response. *Science* **374**, 1632-1640 (2021).
7. Yambartsev, A., *et al.* Unexpected links reflect the noise in networks. *Biology direct* **11**, 1-12 (2016).
8. Rodrigues, R.R., *et al.* Antibiotic-induced alterations in gut microbiota are associated with changes in glucose metabolism in healthy mice. *Frontiers in microbiology* **8**, 2306 (2017).
9. Shulzhenko, N., *et al.* CVID enteropathy is characterized by exceeding low mucosal IgA levels and interferon-driven inflammation possibly related to the presence of a pathobiont. *Clinical Immunology* **197**, 139-153 (2018).
10. Kahalehili, H.M., *et al.* Dietary indole-3-carbinol activates AhR in the gut, alters Th17-microbe interactions, and exacerbates insulitis in NOD mice. *Frontiers in Immunology* **11**, 606441 (2021).

11.   Zhang, Y., *et al.* Improvements in metabolic syndrome by xanthohumol derivatives are linked to altered gut microbiota and bile acid metabolism. *Molecular nutrition & food research* **64**, 1900789 (2020).

12.   Li, Z., *et al.* Microbiota and adipocyte mitochondrial damage in type 2 diabetes are linked by Mmp12+ macrophages. *Journal of Experimental Medicine* **219**, e20220017 (2022).

13.   Rodrigues, R.R., *et al.* Transkingdom interactions between Lactobacilli and hepatic mitochondria attenuate western diet-induced diabetes. *Nature communications* **12**, 101 (2021).

14.   Morgun, A., *et al.* Uncovering effects of antibiotics on the host and microbiota using transkingdom gene networks. *Gut* **64**, 1732-1743 (2015).

15.   Shannon, P., *et al.* Cytoscape: a software environment for integrated models of biomolecular interaction networks. *Genome research* **13**, 2498-2504 (2003).

16.   Blondel, V.D., Guillaume, J.-L., Lambiotte, R. & Lefebvre, E. Fast unfolding of communities in large networks. *Journal of statistical mechanics: theory and experiment* **2008**, P10008 (2008).

17.   Rosvall, M., Axelsson, D. & Bergstrom, C.T. The map equation. *The European Physical Journal Special Topics* **178**, 13-23 (2009).

18.   Dong, X., *et al.* Reverse enGENEering of regulatory networks from big data: a roadmap for biologists. *Bioinformatics and biology insights* **9**, BBI. S12467 (2015).

19.   Chunikhina, E., *et al.* The C-SHIFT algorithm for normalizing covariances. *IEEE/ACM Transactions on Computational Biology and Bioinformatics* (2022).

20.   Välikangas, T., Suomi, T. & Elo, L.L. A systematic evaluation of normalization methods in quantitative label-free proteomics. *Briefings in bioinformatics* **19**, 1-11 (2018).

21.   Gautier, L., Cope, L., Bolstad, B.M. & Irizarry, R.A. affy—analysis of Affymetrix GeneChip data at the probe level. *Bioinformatics* **20**, 307-315 (2004).

22.   Love, M.I., Huber, W. & Anders, S. Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2. *Genome biology* **15**, 1-21 (2014).

23.   Robinson, M.D., McCarthy, D.J. & Smyth, G.K. edgeR: a Bioconductor package for differential expression analysis of digital gene expression data. *bioinformatics* **26**, 139-140 (2010).

24.   Bolyen, E., *et al.* Reproducible, interactive, scalable and extensible microbiome data science using QIIME 2. *Nature biotechnology* **37**, 852-857 (2019).

25.   Paulson, J.N., Pop, M. & Bravo, H.C. metagenomeSeq: Statistical analysis for sparse high-throughput sequencing. *Bioconductor package* **1**, 191 (2013).

26.   Saccenti, E. Correlation patterns in experimental data are affected by normalization procedures: consequences for data analysis and network inference. *Journal of Proteome Research* **16**, 619-634 (2017).

27.   Wulff, J.E. & Mitchell, M.W. A comparison of various normalization methods for LC/MS metabolomics data. *Advances in Bioscience and Biotechnology* **9**, 339 (2018).

28.   Karpievitch, Y.V., *et al.* Normalization of peak intensities in bottom-up MS-based proteomics using singular value decomposition. *Bioinformatics* **25**, 2573-2580 (2009).

29.   Ernest, B., Gooding, J.R., Campagna, S.R., Saxton, A.M. & Voy, B.H. MetabR: an R script for linear model analysis of quantitative metabolomic data. *BMC research notes* **5**, 1-10 (2012).

30.   Karpievitch, Y., Stuart, T. & Mohamed, S. ProteoMM: multi-dataset model-based differential expression proteomics analysis platform. *R package version* **1**, 34 (2019).

31.   Röst, H.L.*, et al.* OpenMS: a flexible open-source software platform for mass spectrometry data analysis. *Nature methods* **13**, 741-748 (2016).

32.   Röst, H.L., Schmitt, U., Aebersold, R. & Malmström, L. pyOpenMS: a Python-based interface to the OpenMS mass-spectrometry algorithm library. *Proteomics* **14**, 74-77 (2014).

33.   Graw, S.*, et al.* proteiNorm–A user-friendly tool for normalization and analysis of TMT and label-free protein quantification. *ACS omega* **5**, 25625-25633 (2020).

34.   Newman, M. *Networks*, (Oxford university press, 2018).

35.   Newman, M.E. Assortative mixing in networks. *Physical review letters* **89**, 208701 (2002).

36.   Borgatti, S.P. *The key player problem*, (na, 2003).

37.   Freeman, L.C. Centrality in social networks: Conceptual clarification. *Social network: critical concepts in sociology. Londres: Routledge* **1**, 238-263 (2002).

38.   Balduzzi, S., Rücker, G. & Schwarzer, G. How to perform a meta-analysis with R: a practical tutorial. *BMJ Ment Health* **22**, 153-160 (2019).

39.   Schwarzer, G., Carpenter, J.R. & Rücker, G. *Meta-analysis with R*, (Springer, 2015).

40.   Sera, F., Armstrong, B., Blangiardo, M. & Gasparrini, A. An extended mixed-effects framework for meta-analysis. *Statistics in Medicine* **38**, 5429-5444 (2019).

41.   Rohart, F., Gautier, B., Singh, A. & Lê Cao, K.-A. mixOmics: An R package for 'omics feature selection and multiple data integration. *PLoS computational biology* **13**, e1005752 (2017).

42.   Argelaguet, R.*, et al.* MOFA+: a statistical framework for comprehensive integration of multi-modal single-cell data. *Genome biology* **21**, 1-17 (2020).

43.   Argelaguet, R.*, et al.* Multi-Omics Factor Analysis—a framework for unsupervised integration of multi-omics data sets. *Molecular systems biology* **14**, e8124 (2018).

44.   Davey Smith, G. & Hemani, G. Mendelian randomization: genetic anchors for causal inference in epidemiological studies. *Human molecular genetics* **23**, R89-R98 (2014).

45.   Smith, G.D. & Ebrahim, S. Mendelian randomization: genetic variants as instruments for strengthening causal inference in observational studies. in *Biosocial surveys* (National Academies Press (US), 2008).

46.   Wang, C., Hu, J., Blaser, M.J. & Li, H. Estimating and testing the microbial causal mediation effect with high-dimensional and compositional microbiome data. *Bioinformatics* **36**, 347-355 (2020).

47.   Baiocchi, M., Cheng, J. & Small, D.S. Instrumental variable methods for causal inference. *Statistics in medicine* **33**, 2297-2340 (2014).

48.   Cheung, M.W.-L. A guide to conducting a meta-analysis with non-independent effect sizes. *Neuropsychology review* **29**, 387-396 (2019).