# Comparison of concurrent and asynchronous running kinematics and kinetics from marker-based motion capture and markerless motion capture under two clothing conditions

Robert M. Kanko[A, B], Jereme B. Outerleys[A, B], Elise K. Laende[A], W. Scott Selbie[B], Kevin J. Deluzio[A]

**Affiliations:**

[A] Mechanical and Materials Engineering, Queen's University, Kingston, Ontario, Canada

[B] Theia Markerless Inc., Kingston, Ontario, Canada

**Declaration of Interests:**

RMK and JBO are employed by Theia Markerless Inc, and WSS is the CEO of Theia Markerless Inc. Data for this study was collected by RMK in the Human Mobility Research Laboratory at Queen's University under the supervision of KJD, prior to employment with Theia Markerless Inc.

**Acknowledgements:**

We thank Human Mobility Research Laboratory members with participant recruitment, data collection, and data processing. This research was supported by an Ontario Research Fund grant (ORF RE-04-047), Natural Sciences and Engineering Research Council of Canada (NSERC) Individual Discovery Grant, and NSERC Canadian Graduate Scholarship.

**Abstract**

Running gait analysis has been pursued as a potential tool to record and quantify athletes'

movement patterns to predict injury, inform interventions, or improve performance. Limitations

associated with marker-based motion capture have reduced its impact and applications.

Markerless motion capture promises fewer limitations, but examining the relationship between

markerless and marker-based motion capture data is important to understand how markerless

results can be interpreted alongside historical data collected using marker-based motion

capture. Further, markerless motion capture uses automated estimation of landmarks, which

may be influenced by clothing. To investigate these aspects of markerless motion capture, we

compared lower limb kinematic and kinetic measures during treadmill running from concurrent

marker-based and markerless motion capture (Theia3D), and asynchronous markerless motion

capture under realistic clothing conditions. Thirty healthy adults ran at a self-selected speed on

an instrumented treadmill while concurrent marker-based and markerless motion capture data

were recorded. The procedure was repeated with participants wearing athletic clothing while

markerless data were recorded. Kinematic and kinetic measurements were consistent between

markerless clothing conditions, indicating that the markerless system is robust to clothing,

allowing data collection of participants in their preferred attire. Joint center positions between

concurrent marker-based and markerless data differed by 3 cm or less. Sagittal plane joint

angles differed by 5° or less between systems, while frontal and transverse plane joint angles

differed by 5-10°. Similar joint moment patterns were captured except ankle inversion/eversion,

and some moments differed in peak magnitudes. Differences between the marker-based and

markerless systems were sensitive to coordinate system definitions, highlighting the importance

of considering the effects of segment coordinate system definition when comparing against

historical data or data from other motion capture modalities.

## 1. Introduction

Motion capture has long been used to quantify movement patterns, monitor interventions and has potential as a tool for injury prediction. The latter has been a particular focus for those interested in its application to running biomechanics. However, due to the inherent time, cost, environment, and expertise constraints associated with traditional marker-based motion capture approaches, the successes of this tool have been limited. Likewise, wearable sensors such as inertial measurement units (IMUs) have limitations, specifically related to magnetic field effects such as those generated by laboratory treadmills (de Vries et al., 2009; Jeon and Lee, 2018) and are best suited to reporting quantities such as accelerations and angular rates which they measure directly, rather than estimating intersegmental measures such as joint angles.

As emerging technology, markerless motion capture has the potential to capture high resolution three dimension (3D) biomechanical signals of running in a more accessible system that avoids potential effects of applying markers or sensors. Ongoing developments, validations, and applications demonstrate the promise of this form of motion capture technology for increasing the usefulness of motion capture-based running gait analysis. Markerless motion capture systems such as Theia3D (Theia Markerless Inc., Kingston, Ontario, Canada) can measure kinematics using multiple synchronized video cameras with few restrictions on the data collection environment, subject attire, and a significantly reduced collection time compared to marker-based motion capture. Markerless systems have demonstrated success in measuring comparable kinematic signals to those from marker-based motion capture during walking (Kanko et al., 2021a; Riazati et al., 2022), boxing (Lahkar et al., 2022), and running (Tang et al., 2022). While marker-based motion capture may not provide a true gold standard for biomechanical data collection due to issues with soft tissue artefact and marker placement variation, it is a historically accepted technology and forms the basis of much of the running biomechanics literature. Understanding how data collected with markerless motion capture

compares to marker-based data, as well as the factors contributing to any differences between

the two systems, is an important step in the introduction of markerless technology to the field of

running biomechanics. Further, we were motivated to understand the effect of clothing on the

reliability of the markerless system. Therefore, the objectives of this study were to compare

kinematic and kinetic data from concurrent markerless and marker-based motion capture during

treadmill running, examine the impact of clothing on markerless motion capture, and investigate

the sensitivity of kinematic and kinetic data to biomechanical model definitions.

**2. Methods**

*2.1 Data Collection*

Thirty healthy, active young adults (15f/15m, mean (SD) age: 23.0 (3.5) years, height: 1.76

(0.09) m, mass: 69.2 (11.4) kg, BMI: 22.3 (3.0) kg/m$^2$) were recruited from the university

community to participate in this study at the Human Mobility Research Laboratory (Kingston,

Ontario, Canada). Exclusion criteria included having any lower-limb musculoskeletal injury in the

past six months or any neuromuscular or musculoskeletal impairments that could hinder their

performance of running. The research protocol was approved by the institutional research ethics

board, and participants provided written informed consent.

A marker-based motion capture system consisting of seven Qualisys Oqus marker-

based cameras (Qualisys AB, Gothenburg, Sweden) and a markerless motion capture system

of eight Qualisys Miqus video cameras (full HD 1920x1080 resolution, RBG video) were

arranged around an instrumented treadmill (AMTI Inc, Watertown, MA) and were connected to a

single instance of Qualisys Track Manager (QTM), ensuring their temporal synchronization

(Kanko et al., 2021b). Both sets of cameras were calibrated and localized simultaneously

(calibration residual errors < 1 mm), ensuring they shared one global coordinate system (x-axis

pointing right laterally, y-axis pointing in the treadmill direction of progression, and z-axis

pointing vertically). Both camera systems recorded at 85 Hz, which is the maximum frame rate

for the Miqus cameras at full HD resolution, while ground reaction forces were recorded at 425

Hz.

114           For the marker-based system, a static calibration trial was recorded of the subject

115     standing on the treadmill with their feet pointing anteriorly and positioned approximately

116     shoulder-width apart, their elbows flexed to approximately 90 degrees, and their palms facing

117     the floor. The markerless motion capture system does not use a static calibration trial.

118           Participants ran at a self-selected speed under two clothing conditions: (1 - 'MoCap

clothing') wearing typical marker-based motion capture clothing and markers (Kanko et al.,

2021b), and (2 - 'Sport clothing') wearing self-selected athletic clothing which typically consisted

of a short-sleeved or sleeveless shirt and shorts that end at or above the knee. Half of the

participants performed the MoCap condition first and half performed the Sport condition first; the

order was not randomized across the participants. Each participant's self-selected speed was

replicated during both conditions.

125           During the MoCap clothing condition, marker-based motion capture, markerless motion

capture, and ground reaction force data were recorded simultaneously. During the Sport

clothing condition, markerless motion capture and ground reaction force data were recorded.

During both conditions, participants wore their personal running shoes and were allowed to

acclimatize to their self-selected running speed on the treadmill for two minutes before one 10-

second trial was recorded. Concurrent marker-based and markerless walking data under the

MoCap clothing condition also obtained during these data collections have been analyzed and

published previously (Kanko et al., 2021a, 2021b).

***2.2 Data Analysis***

Markerless video data were processed in Theia3D v2022-1-0-2309 (Theia Markerless Inc,

Kingston, Ontario, Canada), using 3 degrees of freedom (DOF) at the hip, knee, and ankle

joints, and a 20 Hz equivalent GCVSPL cut-off frequency (Woltring, 1986). Marker-based

motion capture data were tracked in QTM and exported for further analysis in Visual3D (C-

Motion Inc, Germantown, MD). Marker trajectories were filtered using a 20 Hz equivalent

GCVSPL cut-off frequency, and a skeletal model was manually defined with similar segment

coordinate system definitions to the Theia3D model. Model segment lengths were independent

between systems, being based on the markers for the marker-based model and being

automatically calculated for the markerless model. The marker-based skeletal model used

identical inverse kinematic segment chains and joint constraints to those used by Theia3D

(Table 1).

**Table 1:** Marker-based model lower body segment coordinate system definitions and inverse kinematic

model constraints, selected to best match the segment definitions and constraints of the Theia3D model.

| Segment | Coordinate System | Description |
|---|---|---|
| Pelvis | Origin | Midpoint between mid-ASIS and mid-PSIS |
| | X-Axis | Left ASIS to right ASIS |
| | Y-Axis | Mid-PSIS to mid-ASIS |
| | Z-Axis | Normal to xy-plane |
| | Parent, DOF | Lab, 6 DOF |
| Kinematic (Virtual) Pelvis | Origin | Point at the height of midpoint between left and right iliac crest markers along vector between midpoint between left and right hip and midpoint between C7 and sternal notch markers |
| | X-Axis | Left hip joint center to right hip joint center |
| | Y-Axis | Normal to xz-plane |
| | Z-Axis | Segment origin to midpoint between C7 and sternal notch markers |
| | Parent, DOF | Pelvis, 0 DOF |
| Thigh | Origin | Hip joint center of Pelvis, based on (Bell et al., 1990) |
| | X-Axis | Vector perpendicular to z-axis lying in the plane formed by hip joint center, medial and lateral femoral epicondyles |
| | Y-Axis | Vector normal to plane formed by hip joint center, medial and lateral femoral epicondyles |
| | Z-Axis | Midpoint between medial and lateral femoral epicondyles to hip joint center |
| | Parent, DOF | Pelvis, 3 DOF |
| Shank | Origin | Midpoint between medial and lateral femoral epicondyles |
| | X-Axis | Vector perpendicular to z-axis lying in the plane formed by segment origin, medial and lateral malleoli |
| | Y-Axis | Vector normal to plane formed by segment origin, medial and lateral malleoli |
| | Z-Axis | Midpoint between medial and lateral malleoli to segment origin |
| | Parent, | Thigh, 3 DOF |

| | DOF | |
|------|------|------|
| Foot | Origin | Midpoint between medial and lateral malleoli |
| | X-Axis | Vector normal to y- and z-axes |
| | Y-Axis | Segment origin to segment distal point (point an equivalent distance from metatarsal 2/3 marker along a vector normal to the foot plane formed by the heel, metatarsal 1 marker projected to height of metatarsal 5 marker, and metatarsal 5 marker, as the distance from the segment origin to the same foot plane) |
| | Z-Axis | Metatarsal 2/3 marker to segment distal point (see y-axis) |
| | Parent, DOF | Shank, 3 DOF |

Marker-based and markerless motion capture data were analyzed separately in

Visual3D. Force data from the instrumented treadmill were imported into the markerless MoCap

clothing and Sport clothing .c3d files, allowing these signals to be used with the markerless

kinematics to obtain joint kinetics and create force-based gait events. Force data were filtered

using a low-pass critically-damped filter with a cut-off frequency of 20 Hz to match the kinematic

filter cut-off frequency (Mai and Willwacher, 2019), and the 'FP Auto Baseline' function in

Visual3D was used to clean the force platform signals. A vertical ground reaction force threshold

of 50 N was used to detect foot contact events.

Kinematic and kinetic signals including joint positions, segment angles, joint angles, and

internal net joint moments were calculated in Visual3D, and were time-normalized to 101 data

points, representing one complete running gait cycle (0-100%) from heel strike to ipsilateral heel

strike. Segment angles were calculated using a XYZ Cardan sequence relative to the global

coordinate system. Segment angles were included since they capture the 3D orientation of

individual body segments. Joint angles were calculated using an XYZ Cardan sequence for all

joints except the ankles, for which a XZY Cardan sequence was used. Joint angles were

included since they capture the relative orientation of adjacent segments and are kinematic

measures of interest for most users of motion capture. Joint moments were normalized to

participant mass and resolved in the proximal segment. All data were analyzed further using

python (version 3.10.6).

Four participants' markerless Sport clothing trial videos had an inconsistent number of

frames between cameras, preventing their processing in Theia3D; these participants were

excluded from the kinematic comparisons, which then included 26 participants (12f/14m, mean

(SD) age: 23.5 (4.0) years, height: 1.8 (0.1) m, mass: 69.9 (9.9) kg, BMI: 22.8 (2.9) kg/m$^2$). Six

participants' center-of-pressure data from the instrumented treadmill were found to be

erroneous. The kinetic comparison sample then included 21 participants (10f/11m, mean (SD)

age: 23.3 (3.8) years, height: 1.8 (0.1) m, mass: 69.9 (11.0) kg, BMI: 22.8 (2.8) kg/m$^2$). Running

gait cycles with marker tracking issues were excluded. For comparison between the markerless

and marker-based motion capture, only matched gait cycles were used.

Differences between signals from corresponding running gait cycles for the concurrent

marker-based and markerless MoCap clothing datasets were calculated and summarized

across all participants as root-mean-square differences (RMSD). Participants' mean signals for

the asynchronous markerless MoCap clothing and Sport clothing conditions were used to

assess differences between markerless clothing conditions and were summarized across all

participants as RMSDs. The inter-cycle variability of the signals from each dataset was

calculated (Schwartz et al., 2004), and the inter-condition variability of markerless signals was

also calculated to examine the reliability of markerless measurements across different clothing

conditions (similar to 'inter-session' variability, Schwartz et al., 2004).

***2.3 Alternative Marker-Based Modelling***

To investigate the effect of marker-based model definitions on kinematic and kinetic

comparisons, results were calculated for two additional models. The first alternative model was

our previous standard marker-based model that was used in prior publications (Kanko et al.,

2021a) (Supplementary Materials, Table A). The second alternative model used the same set of

markers but applied atypical segment definitions so that the resulting kinematics best aligned

with the markerless results (Supplementary Materials, Table B).

## 3. Results

The average self-selected running speeds for the participant samples used in the kinematic and kinetic comparisons were 2.42 (0.27) m/s and 2.39 (0.27) respectively.

### 3.1 Kinematics

Joint center positions from the concurrent marker-based and markerless MoCap clothing data had mean differences that remained below 4 cm throughout the running gait cycle. The mean (SD) RMSD across all subjects were 2.12 (0.34) cm, 2.15 (0.63) cm, and 2.96 (0.87) cm for the ankle, knee, and hip joints, respectively (Figure 1). The markerless joint centers were positioned laterally of the marker-based joint centers for the ankle, knee, and hip, and distal relative to the marker-based joint centers for the ankle and hip. The sign of the anterior-posterior component was dependent on the phase of the running gait cycle and was distributed in both directions throughout. The markerless ankle and hip joint centers were distal of their marker-based counterparts, while the knee was proximal during early swing phase and slightly distal at all other times.

**Figure 1:** Mean joint center position differences between concurrent marker-based motion capture and markerless MoCap clothing condition across all participants, for the global x-direction (row 1; lateral/medial), global y-direction (row 2; anterior/posterior), global z-direction (row 3; proximal/distal), and 3D Euclidean distances (row 4). Differences were assessed as markerless joint position - marker-based joint position; inset position descriptors are for the markerless joint center relative to the marker-based joint center. Mean (SD) RMS of the 3D Euclidean distances is inset for each joint.

Lower limb segment angle x-components, which capture the largest magnitude of segment rotation during running, demonstrated high similarity between all three datasets for all lower body segments (Figure 2). Marker-based pelvis segment angle x-components showed greater variability than those from either markerless clothing condition. Segment angle y-components captured similar patterns from all three datasets for the pelvis, thigh, and shank segments, with slight differences between both markerless datasets and the marker-based signals, but excellent consistency between the markerless datasets. The foot segment angle z-component also captured similar patterns between motion capture systems and excellent

consistency between the markerless datasets. The thigh and shank z-components showed the

greatest differences between motion capture systems; these segment angles capture rotations

about the segment longitudinal axes, which are the most challenging rotations to accurately

capture. The pelvis segment angle z-components showed the greatest differences between the

two markerless clothing conditions (MoCap, Sport) of any segment angle.

**Figure 2:** Mean right segment angles from marker-based motion capture (red), markerless motion
capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion
capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap
clothing). Segment angle x-components (left column) represent rotations about the global coordinate
system x-axis, z-components (right column) represent rotations about the segment local coordinate
system z-axis, and y-components (middle column) represent rotations about an axis normal to the global
x-axis and segment z-axis.

Lower limb sagittal plane joint angles and hip ab/adduction (Figure 3) were similar

across all three datasets, with mean RMSDs of 5.2° or lower (Table 2). Ankle toe-in/toe-out

angles were also somewhat consistent between all three datasets, differing more during stance

phase than swing phase (mean RMSD: 8.0°). The remaining joint angles captured different

patterns and levels of variability between motion capture systems but were consistent between

both markerless clothing conditions (mean RMSDs: 5-10°). The frontal and transverse plane

joint angles are influenced by the longitudinal rotation of the thigh and shank segments which

were the least similar segment angles between systems (Figure 2).

The mean RMSD values for the asynchronous markerless data (MoCap clothing, Sport

clothing) were all smaller than those for the concurrent marker-based and markerless data,

indicating that the differences between markerless joint angle measures from different trials and

with different participant clothing remain smaller than the differences between motion capture

systems.

**Figure 4:** Mean right lower limb joint angles from marker-based motion capture (red), markerless motion

capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion

capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap

clothing) using XYZ Cardan sequences for the knee and hip and a XZY Cardan sequence for the ankle.

**Table 2:** Mean lower limb joint angle and moment RMS differences across all participants, for the concurrent data comparison (markerless MoCap signals - marker-based MoCap signals) and the asynchronous comparison (markerless MoCap clothing signals - markerless Sport clothing signals).

| | | Ankle | | | Knee | | | Hip | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | Fl/ Ex | Inv/ Ev | Toe-In/-Out | Fl/ Ex | Ab/ Ad | Int/ Ext Rot | Fl/ Ex | Ab/ Ad | Int/ Ext Rot |
| Joint Angle Differences [deg] | Concurrent Data Mean RMSD | 3.8 | 6.0 | 8.0 | 4.2 | 7.2 | 9.4 | 5.2 | 2.7 | 9.8 |
| | Asynchronous Data Mean RMSD | 3.1 | 1.6 | 2.5 | 3.2 | 1.8 | 3.2 | 3.9 | 1.7 | 2.5 |
| Joint Moment Differences [Nm/kg] | Concurrent Data Mean RMSD | 0.13 | 0.25 | 0.03 | 0.24 | 0.12 | 0.06 | 0.29 | 0.22 | 0.09 |
| | Asynchronous Data Mean RMSD | 0.13 | 0.05 | 0.03 | 0.13 | 0.08 | 0.05 | 0.25 | 0.18 | 0.07 |

Inter-cycle joint angle variability was similar across all three datasets, being within 0.6°
for all joint angles (Table 3). The average inter-cycle variability across all joint angles was
slightly smaller for the marker-based data (1.3°) compared to those for both markerless datasets
(1.5°). The inter-cycle variability is made up of natural stride-to-stride variation in subject
biomechanics, as well as measurement variability inherent to the motion capture systems. Inter-
condition variability for joint angles between markerless conditions (average 2.0°) was slightly
greater than the inter-cycle variability of either dataset, with variability ratios of 1.2-1.7 (mean
1.3). This indicates that the variability in joint angles captured across trials with different
participant clothing is on average 30% greater than the variability between running gait cycles
within a single trial. The inter-condition variability is made up of inter-cycle variability as
described above, plus natural inter-trial variability, measurement variability due to the varying
participant clothing, and measurement variability inherent to the motion capture system.

272 **Table 3:** Joint angle variability measures for each dataset and comparison, including: inter-cycle

273 variability for marker-based MoCap, markerless MoCap clothing, markerless Sport clothing; inter-

274 condition variability for all markerless data; and the variability ratio of markerless inter-condition to mean

275 markerless inter-cycle variability.

| | | Ankle | | | Knee | | | Hip | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Fl/ Ex | Inv/ Ev | Toe -In/- Out | Fl/ Ex | Ab/ Ad | Int/ Ext Rot | Fl/ Ex | Ab/ Ad | Int/ Ext Rot | Avg |
| Inter-Cycle Variability [deg] | Marker-based (MoCap clothing) | 1.5 | 1.2 | 1.4 | 2.1 | 0.8 | 1.3 | 1.3 | 0.9 | 1.3 | 1.3 |
| | Markerless (MoCap clothing) | 1.6 | 1.2 | 1.8 | 2.2 | 1.0 | 1.8 | 1.4 | 0.9 | 1.3 | 1.5 |
| | Markerless (Sport clothing) | 1.8 | 1.2 | 1.8 | 2.3 | 1.0 | 1.9 | 1.5 | 1.0 | 1.3 | 1.5 |
| Inter-Condition Variability [deg] | Markerless (MoCap, Sport clothing conditions) | 2.3 | 1.4 | 2.2 | 2.8 | 1.4 | 2.4 | 2.4 | 1.3 | 1.8 | 2.0 |
| Variability Ratio | Markerless Inter-Condition/Mean Inter-Cycle | 1.4 | 1.2 | 1.2 | 1.2 | 1.3 | 1.3 | 1.7 | 1.3 | 1.4 | 1.3 |

**_3.2 Kinetics_**

Lower limb joint moments from all three datasets captured similar patterns for most joint

moments, with slight differences observed in the knee flexion/extension and ab/adduction

moments, ankle toe-in/toe-out moments, and larger differences observed for the ankle

inversion/eversion moments (Figure 4). The marker-based knee moments had greater peak

magnitudes and greater variability compared to both markerless conditions in all three planes.

The ankle inversion/eversion moments measured by the marker-based system were inversion

moments across all subjects and had considerably greater variability compared to those

measured by the markerless system, which were mostly eversion moments across all subjects

in both conditions. Additionally, the ankle toe-in/toe-out joint moments measured by the marker-

based system had a lower peak magnitude compared to both markerless conditions. The

largest differences between the markerless MoCap clothing and Sport clothing conditions were

observed in the hip internal/external rotation moments and ankle toe-in/toe-out moments, for

both of which the peak magnitude from the Sport clothing condition was slightly greater than

that of the MoCap clothing condition.

292
293     **Figure 4:** Mean right lower limb joint moments from marker-based motion capture (red), markerless

294     motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless

295     motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless

296     MoCap clothing).

### 3.3 Alternative Marker-Based Modelling Results

The results of this study when two alternative marker-based models were applied are included

in the Supplementary Materials (Tables A, B; Figures A-F). The results from the model used in

(Kanko et al., 2021a) were consistent with the results of that study, with slight variations due to

the differences in task (walking versus running) (Supplementary Materials, Figures A, B, C). The

results from the modified version of the model used here showed the same or greater similarity

between marker-based and markerless systems for all segment angles, joint angles, and joint

moments (Supplementary Materials, Figures D, E, F).

## 4. Discussion

The purpose of this study was to compare kinematic and kinetic measures of treadmill running from concurrent marker-based and markerless motion capture, and between asynchronous markerless motion capture under varying clothing conditions. Overall, we found comparable results between the simultaneous marker-based and markerless motion capture data and between clothing conditions for the markerless system.

Joint position differences between marker-based and markerless concurrent data were found to be 3 cm or smaller for all joints, which is consistent with previous comparisons of these systems during treadmill walking (Kanko et al., 2021a). Joint position component differences were also mostly consistent with those of Tang et al., however they did not report 3D Euclidean distances (Tang et al., 2022).

Segment and joint angles demonstrated similar agreement between motion capture systems as in our previous study for treadmill walking gait (Kanko et al., 2021a), and excellent agreement across asynchronous markerless clothing conditions. Sagittal plane joint angles between motion capture systems had mean RMSD of 5.2° or less for all three joints, consistent with the findings of Tang et al. (Tang et al., 2022). The differences between systems measured as mean RMSD over the entire gait cycle are comparable to reported minimal detectable change (MDC) values for marker-based motion capture of treadmill running at initial contact (Bramah et al., 2021). Compared to the marker-based MDC values, the RMSD values between systems are 3.1° smaller (for ankle dorsiflexion) to 4.7° greater (for knee ab/adduction). The between-system agreement observed here is also consistent with previous comparisons of these systems during treadmill walking (Kanko et al., 2021a), which showed larger differences for segment angles about the segment longitudinal axes, and for frontal and transverse plane angles.

Kinematic and kinetic signals were highly consistent between the markerless MoCap

clothing and Sport clothing conditions, except for pelvis segment angle x- and z-components.

Interpreting kinematic differences between the two markerless motion capture clothing

conditions is made challenging by the fact that they may result from actual changes in

movement patterns between the two running trials or due to differences in markerless keypoint

detections as a result of the change in clothing. The former was indeed the case for at least one

participant, whose markerless joint angles were considerably different between the MoCap and

Sport clothing conditions, and were confirmed from raw video data to have visibly greater

ranges of motion in hip, knee, and ankle flexion for the Sport clothing condition (Supplementary

Material, Figure H). The RMSD values between clothing conditions, which could be considered

analogous to a participant returning on a second day in different clothing, were smaller than

published MDC values at initial contact (Bramah et al., 2021), with the exception of hip flexion

(0.2° greater). These findings are consistent with a running repeatability study over three

repeated visits at varying running speeds using the same markerless motion capture software

(Moran et al., 2023). Their findings and ours support the use of markerless motion capture

methods to overcome the limitations of marker placement variability with marker-based motion

capture, which has been a challenge for longitudinal running studies (Hébert-Losier et al.,

2022).

Joint angle inter-cycle variability was small and similar across the marker-based data

(1.3°) and both markerless datasets (1.5°). Inter-condition variability across markerless clothing

conditions was larger than the inter-cycle variabilities, and presented an average increase of

30% in measurement variability. The inter-condition variability was smaller than the mean

RMSD between concurrent motion capture systems for all joint angles, indicating that

differences between markerless clothing conditions remained smaller than differences between

motion capture systems.

Joint moments showed similarity in pattern and magnitude between systems and across

clothing conditions for the ankle, knee, and hip sagittal plane moments, hip ab/adduction

moment, and hip and knee internal/external rotation moments, while similar patterns of different

magnitude were observed for knee ab/adduction and ankle toe-in/toe-out moments. However,

the ankle inversion/eversion moments displayed different patterns, with the marker-based

moments being mostly inversion moments while the markerless moments were mostly eversion

moments. Differences in sagittal plane joint moment peak magnitudes between marker-based

and markerless joint moments were mostly consistent with the findings of Tang et al., but they

did not report frontal or transverse plane joint moments for either system (Tang et al., 2022).

The differences in ankle inversion/eversion and toe-in/toe-out moments between systems can

be explained by differences in the foot and shank segment orientations, as the selection and

orientation of the coordinate system in which joint moments are resolved can entirely change

their direction (O'Connor and Hamill, 2005). For instance, when the ankle joint moments are

resolved in the foot segment coordinate systems (Supplementary Material, Figure I) rather than

the shanks (Figure 2), the marker-based inversion/eversion moments have a considerably

reduced magnitude.

The results of this (and any) concurrent validation study of motion capture systems are

highly dependent on the biomechanical models employed in the comparison. To investigate this,

we applied two alternative models to the marker-based data that differed only in static segment

definitions. Alternative model 1 (Supplementary Materials, Table A; Figures A-C) represented a

standard unmodified marker-based model that has been previously published (Kanko et al.,

2021a). The model in Table 1 represents a slight compromise between standard marker-based

and markerless segment definitions. Alternative model 2 (Supplementary Materials, Table B;

Figures D-F) represents a model that was manually and intentionally modified to improve the

agreement between the marker-based and markerless kinematic and kinetic signals. The

modifications used in alternative model 2 were not extreme and remain within the realm of

plausibility when considering the differences between marker sets and model definitions, and

the variability of marker placement across operators. The results for this last model demonstrate

the strong effects of segment definitions and marker placement on downstream biomechanical

signals, as they demonstrate that a non-negligible portion of the differences in biomechanical

signals can be attributed to local segment coordinate system misalignment and can be changed

through relatively small model or landmark changes. We advocate for the use of the automated

coordinate system definition from Theia3D to facilitate standardization for multi-centre and

longitudinal research, but found this a useful exercise to understand potential differences in how

data has been collected from our historical marker-based approaches. This demonstrated the

sensitivity of concurrent comparisons to these factors, which is an important point that should be

understood when using and evaluating different motion capture solutions. These results

highlight the challenges in combining data collected under different model definitions, and the

potential benefit in using markerless motion capture to provide standardized results that can be

pooled from multiple sites.

There are several limitations of this study. Challenges with data collection resulted in

some lost participants, but without a significant change in the demographics of the study

population. The self-selected treadmill running speed of this group is lower than typical over-

ground running speeds, which is likely due to previously observed perception differences in

treadmill and over-ground running, and is consistent with previous findings (Kong et al., 2012,

2009). Likewise, the framerate for data collection is lower than is usually used in running studies

but was a limitation of the hardware to allow synchronization across both motion capture

systems. Using different markerless motion capture hardware or capturing lower resolution

videos would allow higher frequency data to be collected. We would anticipate that a higher

running speed recorded at a higher framerate would have comparable results to those

presented here. The order of the two clothing conditions was divided evenly across all

participants, but not randomized and not considered in the data analysis. However, this would

have no impact on the comparison of simultaneous marker-based and markerless data, and the

lack of differences observed between clothing conditions implies that this was not an issue.

Furthermore, the precise segment coordinate system definitions used by Theia3D are

not publicly available, so our marker-based definitions that are intended to mimic the markerless

segment definitions could possibly be improved upon; but in any case, the anatomical

landmarks used by the markerless system are also not available and likely differ slightly in

position from equivalent marker positions by nature of how they are created and tracked.

The results of this study indicate that Theia3D can measure treadmill running kinematics

and kinetics with minimal effect of subjects changing running attire, and are comparable to

measures from marker-based motion capture. This study reiterates the influence of segment

definition on resulting biomechanical signals. Careful consideration of these effects should be

taken when conducting comparisons between measurement systems and relative to historical

data that utilized potentially different segment definitions.

**5. Acknowledgements**

We thank Human Mobility Research Laboratory members with participant recruitment, data

collection, and data processing. This research was supported by an Ontario Research Fund

grant (ORF RE-04-047), Natural Sciences and Engineering Research Council of Canada

(NSERC) Individual Discovery Grant, and NSERC Canadian Graduate Scholarship.

**6. References**

Bramah, C., Preece, S.J., Gill, N., Herrington, L., 2021. The between-day repeatability, standard

error of measurement and minimal detectable change for discrete kinematic parameters

during treadmill running. Gait Posture 85, 211–216.

https://doi.org/10.1016/j.gaitpost.2020.12.032

de Vries, W.H.K., Veeger, H.E.J., Baten, C.T.M., van der Helm, F.C.T., 2009. Magnetic

distortion in motion labs, implications for validating inertial magnetic sensors. Gait

Posture 29, 535–541. https://doi.org/10.1016/j.gaitpost.2008.12.004

Hébert-Losier, K., Dai, B., Nunome, H., Kong, P.W., Hobara, H., Hsu, W.-C., Bradshaw, E.J.,

Fong, D.T.P., Vanwanseele, B., 2022. Reporting guidelines for running biomechanics

and footwear studies using three-dimensional motion capture. Sports Biomech. 0, 1–12.

https://doi.org/10.1080/14763141.2022.2110149

Jeon, T.H., Lee, J.K., 2018. IMU-Based Joint Angle Estimation Under Various Walking and

Running Conditions. J. Korean Soc. Precis. Eng. 35, 1199–1204.

https://doi.org/10.7736/KSPE.2018.35.12.1199

Kanko, R.M., Laende, E.K., Davis, E.M., Selbie, W.S., Deluzio, K.J., 2021a. Concurrent

assessment of gait kinematics using marker-based and markerless motion capture. J.

Biomech. 127, 110665. https://doi.org/10.1016/j.jbiomech.2021.110665

Kanko, R.M., Laende, E.K., Strutzenberger, G., Brown, M., Selbie, W.S., DePaul, V., Scott,

S.H., Deluzio, K.J., 2021b. Assessment of spatiotemporal gait parameters using a deep

learning algorithm-based markerless motion capture system. J. Biomech. 122, 110414.

https://doi.org/10.1016/j.jbiomech.2021.110414

Kong, P.W., Candelaria, N.G., Tomaka, J., 2009. Perception of self-selected running speed is

influenced by the treadmill but not footwear. Sports Biomech. 8, 52–59.

https://doi.org/10.1080/14763140802629990

Kong, P.W., Koh, T.M.C., Tan, W.C.R., Wang, Y.S., 2012. Unmatched perception of speed

when running overground and on a treadmill. Gait Posture 36, 46–48.

https://doi.org/10.1016/j.gaitpost.2012.01.001

Lahkar, B.K., Muller, A., Dumas, R., Reveret, L., Robert, T., 2022. Accuracy of a markerless

motion capture system in estimating upper extremity kinematics during boxing. Front.

Sports Act. Living 4, 939980. https://doi.org/10.3389/fspor.2022.939980

Mai, P., Willwacher, S., 2019. Effects of low-pass filter combinations on lower extremity joint

moments in distance running. J. Biomech. 95, 109311.

https://doi.org/10.1016/j.jbiomech.2019.08.005

Moran, M.F., Rogler, I.C., Wager, J.C., 2023. Inter-Session Repeatability of Marker-Less Motion

Capture of Treadmill Running Gait. Appl. Sci. 13, 1702.

https://doi.org/10.3390/app13031702

O'Connor, K.M., Hamill, J., 2005. Frontal Plane Moments Do Not Accurately Reflect Ankle

Dynamics during Running. J. Appl. Biomech. 21, 85–95.

https://doi.org/10.1123/jab.21.1.85

Riazati, S., McGuirk, T.E., Perry, E.S., Sihanath, W.B., Patten, C., 2022. Absolute Reliability of

Gait Parameters Acquired With Markerless Motion Capture in Living Domains. Front.

Hum. Neurosci. 16, 867474. https://doi.org/10.3389/fnhum.2022.867474

Schwartz, M.H., Trost, J.P., Wervey, R.A., 2004. Measurement and management of errors in

quantitative gait data. Gait Posture 20, 196–203.

https://doi.org/10.1016/j.gaitpost.2003.09.011

Tang, H., Pan, J., Munkasy, B., Duffy, K., Li, L., 2022. Comparison of Lower Extremity Joint

Moment and Power Estimated by Markerless and Marker-Based Systems during

Treadmill Running. Bioengineering 9, 574.

https://doi.org/10.3390/bioengineering9100574

Woltring, H.J., 1986. A Fortran package for generalized, cross-validatory spline smoothing and

differentiation. Adv. Eng. Softw. 1978 8, 104–113. https://doi.org/10.1016/0141-

1195(86)90098-7

**Supplementary Materials**

***1. Effects of alternative model definitions for marker-based motion capture***

*1.1 Alternative Model 1*

**Table A:** Marker-based model lower body segment coordinate system definitions and inverse kinematic
model constraints for the model used in (Kanko et al., 2021a), corresponding to results shown in Figures
A, B, C.

| Segment | Coordinate System | Description |
|---------|-------------------|-------------|
| Pelvis | Origin | Midpoint between mid-ASIS and mid-PSIS |
| | X-Axis | Left ASIS to right ASIS |
| | Y-Axis | Mid-PSIS to mid-ASIS |
| | Z-Axis | Normal to xy-plane formed by left ASIS, right ASIS, and mid-PSIS |
| | Parent, DOF | Lab, 6 DOF |
| Thigh | Origin | Hip joint center, based on (Bell et al., 1990) |
| | X-Axis | Vector perpendicular to z-axis lying in the plane formed by hip joint center, medial and lateral femoral epicondyles |
| | Y-Axis | Vector normal to plane formed by hip joint center, medial and lateral femoral epicondyles |
| | Z-Axis | Midpoint between medial and lateral femoral epicondyles to hip joint center |
| | Parent, DOF | Pelvis, 3 DOF |
| Shank | Origin | Midpoint between medial and lateral femoral epicondyles |
| | X-Axis | Vector perpendicular to z-axis lying in the plane formed by medial and lateral femoral epicondyles, midpoint between medial and lateral malleoli |
| | Y-Axis | Vector normal to plane formed by medial and lateral femoral epicondyles, midpoint between medial and lateral malleoli |
| | Z-Axis | Midpoint between medial and lateral malleoli to segment origin |
| | Parent, DOF | Thigh, 3 DOF |
| Foot | Origin | Midpoint between medial and lateral malleoli |
| | X-Axis | Vector perpendicular to z-axis lying in the plane formed by medial and lateral malleoli and metatarsal 2/3 marker |
| | Y-Axis | Vector normal to plane formed by medial and lateral malleoli and metatarsal 2/3 marker |
| | Z-Axis | Metatarsal 2/3 marker to segment origin |

| | Parent, DOF | Shank, 3 DOF |
|---|---|---|
| Kinematic (Virtual) Foot | Origin | Proximal calcaneus (heel) marker |
| | X-Axis | Vector perpendicular to plane formed by segment origin, metatarsal 2/3 marker, and a virtual landmark positioned 0.1 m vertically above segment origin |
| | Y-Axis | Segment origin to metatarsal 2/3 marker |
| | Z-Axis | Vector perpendicular to y-axis lying in the plane formed by segment origin, metatarsal 2/3 marker, and a virtual landmark positioned 0.1 m vertically above segment origin |
| | Parent, DOF | Lab, 6 DOF (tracked using Foot) |

486    **Figure A:** Mean lower limb right segment angles from marker-based motion capture (red), markerless

487    motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless

488    motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless

489    MoCap clothing), using the marker-based model employed in (Kanko et al., 2021a).

**Figure B:** Mean lower limb right joint angles from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model employed in (Kanko et al., 2021a).

**Figure C:** Mean lower limb right joint moments from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model employed in (Kanko et al., 2021a).

 *1.2 Alternative Model 2*

501 **Table B:** Marker-based model lower body segment coordinate system definitions and inverse kinematic

502 model constraints based on the model described in Table 1 and artificially modified to better match the

503 results from Theia3D for demonstration purposes, corresponding to results shown in Figures D, E, F.

| Segment | Coordinate System | Description |
|---|---|---|
| Pelvis | Origin | Midpoint between mid-ASIS and mid-PSIS |
| | X-Axis | Left ASIS to right ASIS |
| | Y-Axis | Mid-PSIS to mid-ASIS |
| | Z-Axis | Normal to xy-plane |
| | Parent, DOF | Lab, 6 DOF |
| Kinematic (Virtual) Pelvis | Origin | Point at the height of midpoint between left and right iliac crest markers along vector between midpoint between left and right hip and midpoint between C7 and sternal notch markers. |
| | X-Axis | Left hip joint center to right hip joint center |
| | Y-Axis | Normal to xz-plane |
| | Z-Axis | Segment origin to midpoint between C7 and sternal notch markers |
| | Parent, DOF | Lab, 6 DOF (tracked using Pelvis) |
| Thigh | Origin | Hip joint center, based on <u>(Bell et al., 1990)</u> |
| | X-Axis | Vector perpendicular to z-axis lying in the plane formed by segment origin, medial femoral epicondyle shifted 0.008 m anteriorly, and lateral femoral epicondyle shifted 0.008 m posteriorly |
| | Y-Axis | Vector normal to plane formed by segment origin, medial femoral epicondyle shifted 0.008 m anteriorly, and lateral femoral epicondyle shifted 0.008 m posteriorly |
| | Z-Axis | Midpoint between medial femoral epicondyle shifted 0.008 m anteriorly and lateral femoral epicondyle shifted 0.008 m posteriorly to segment origin |
| | Parent, DOF | Pelvis, 3 DOF |
| Shank | Origin | Midpoint between medial femoral epicondyle shifted 0.02 m anteriorly and lateral femoral epicondyle shifted 0.02 m posteriorly |
| | X-Axis | Vector perpendicular to z-axis lying in the plane formed by medial femoral epicondyle shifted 0.02 m anteriorly, lateral femoral epicondyle shifted 0.02 m posteriorly, and midpoint between medial and lateral malleoli |
| | Y-Axis | Vector normal to plane formed by medial femoral epicondyle shifted 0.02 m anteriorly, lateral femoral epicondyle shifted 0.02 m posteriorly, and midpoint between medial and lateral malleoli |

| | Z-Axis | Midpoint between medial and lateral malleoli to midpoint between medial femoral epicondyle shifted 0.02 m anteriorly and lateral femoral epicondyle shifted 0.02 m posteriorly |
|---|---|---|
| | Parent, DOF | Thigh, 3 DOF |
| Foot | Origin | Midpoint between medial and lateral malleoli |
| | X-Axis | Vector perpendicular to z-axis lying in the plane formed by segment origin, segment distal point (see y-axis), and a shifted lateral malleoli marker (shifted vertically by the height of the medial malleoli marker – 0.95* height of the lateral malleoli marker - 0.0186 m) |
| | Y-Axis | Segment origin to segment distal point (point an equivalent distance from metatarsal 2/3 marker along a vector normal to the foot plane formed by the heel, metatarsal 1 marker projected to height of metatarsal 5 marker, and metatarsal 5 marker, as the distance from the segment origin to the same foot plane) |
| | Z-Axis | Vector perpendicular to y-axis lying in the plane formed by segment origin, segment distal point (see y-axis), and a shifted lateral malleoli marker (shifted vertically by the height of the medial malleoli marker – 0.95* height of the lateral malleoli marker - 0.0186 m) |
| | Parent, DOF | Shank, 3 DOF |

**Figure D:** Mean lower limb right segment angles from marker-based motion capture (red), markerless

motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless

motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless

MoCap clothing), using the marker-based model defined in Table B to better match the results from

Theia3D for demonstration purposes.

**Figure E:** Mean lower limb right joint angles from marker-based motion capture (red), markerless motion

capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion

capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap

clothing), using the marker-based model defined in Table B to better match the results from Theia3D for

demonstration purposes.

**Figure F:** Mean lower limb right joint moments from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model defined in Table B to better match the results from Theia3D for demonstration purposes.

***2. Example individual participant kinematic waveforms***

Raw joint angle data for a representative participant with consistent running biomechanics

(Figure G) and a participant with altered running biomechanics when wearing MoCap clothing

compared to their self-selected Sport clothing (Figure H).

**Figure G:** Raw lower limb right joint angles for one representative participant, from marker-based motion
capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-
based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-
based and markerless MoCap clothing).

**Figure H:** Raw lower limb right joint angles for one participant who used different biomechanical patterns between the MoCap and Sport clothing conditions, as visually confirmed from the raw markerless videos. Joint angles shown from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing).

538 ***3. Effect of ankle moments resolved in foot segment coordinate system***

540 **Figure I:** Mean lower limb right joint moments from marker-based motion capture (red), markerless
541 motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless
542 motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless
543 MoCap clothing), with the ankle joint moments resolved in the foot segment coordinate system.
544