Comparison of concurrent and asynchronous running kinematics and kinetics from marker-based motion capture and markerless motion capture under two clothing conditions

Robert M. Kanko[A, B], Jereme B. Outerleys[A, B], Elise K. Laende[A], W. Scott Selbie[B], Kevin J. Deluzio[A]

Affiliations:

[A] Mechanical and Materials Engineering, Queen's University, Kingston, Ontario, Canada

[B] Theia Markerless Inc., Kingston, Ontario, Canada

Declaration of Interests:

RMK and JBO are employed by Theia Markerless Inc, and WSS is the CEO of Theia Markerless Inc. Data for this study was collected by RMK in the Human Mobility Research Laboratory at Queen's University under the supervision of KJD, prior to employment with Theia Markerless Inc.

Acknowledgements:

We thank Human Mobility Research Laboratory members with participant recruitment, data collection, and data processing. This research was supported by an Ontario Research Fund grant (ORF RE-04-047), Natural Sciences and Engineering Research Council of Canada (NSERC) Individual Discovery Grant, and NSERC Canadian Graduate Scholarship.

Abstract

As markerless motion capture is increasingly used to measure three-dimensional human pose, it

is important to understand how markerless results can be interpreted alongside historical marker-

based data and how they are impacted by clothing. We compared concurrent running kinematics

and kinetics between marker-based and markerless motion capture, and between two markerless

clothing conditions. Thirty adults ran on an instrumented treadmill wearing motion capture clothing

while concurrent marker-based and markerless data were recorded, and ran a second time

wearing athletic clothing (shorts and t-shirt) while markerless data were recorded. Differences

calculated between the concurrent signals from both systems, and also between each

participant's mean signals from both asynchronous clothing conditions were summarized across

all participants using root-mean-square differences. Most kinematic and kinetic signals were

visually consistent between systems and markerless clothing conditions. Between systems, joint

center positions differed by 3 cm or less, sagittal plane joint angles differed by 5° or less, and

frontal and transverse plane angles differed by 5°-10°. Joint moments differed by 0.3 Nm/kg or

less between systems. Differences were sensitive to segment coordinate system definitions,

highlighting the effects of these definitions when comparing against historical data or other motion

capture modalities.

1. Introduction

Motion capture has long been used to quantify movement patterns, monitor interventions and has potential as a tool for injury prediction. The latter has been a particular focus for those interested in its application to running biomechanics. However, due to the inherent time, cost, environment, and expertise constraints associated with traditional marker-based motion capture approaches, the successes of this tool have been limited. Likewise, wearable sensors such as inertial measurement units (IMUs) have limitations, specifically related to magnetic field effects such as those generated by laboratory treadmills[1,2] and are best suited to reporting quantities such as accelerations and angular rates which they measure directly, rather than estimating intersegmental measures such as joint angles.

As emerging technology, markerless motion capture has the potential to capture high resolution three dimension (3D) biomechanical signals of running in a more accessible system that avoids potential effects of applying markers or sensors. Ongoing developments, validations, and applications demonstrate the promise of this form of motion capture technology for increasing the usefulness of motion capture-based running gait analysis. Markerless motion capture systems such as Theia3D (Theia Markerless Inc., Kingston, Ontario, Canada) can measure kinematics using multiple synchronized video cameras with few restrictions on the data collection environment, subject attire, and a significantly reduced collection time compared to marker-based motion capture. Markerless systems have demonstrated success in measuring comparable kinematic signals to those from marker-based motion capture during walking[3,4], boxing[5], and running[6]. While marker-based motion capture may not provide a true gold standard for biomechanical data collection due to issues with soft tissue artefact and marker placement variation, it is a historically accepted technology and forms the basis of much of the running biomechanics literature. Understanding how data collected with markerless motion capture compares to marker-based data, as well as the factors contributing to any differences between

the two systems, is an important step in the introduction of markerless technology to the field of

running biomechanics. Further, we were motivated to understand the effect of clothing on the

reliability of the markerless system. Therefore, the objectives of this study were to compare

kinematic and kinetic data from concurrent markerless and marker-based motion capture during

treadmill running, examine the impact of clothing on markerless motion capture, and investigate

the sensitivity of kinematic and kinetic data to biomechanical model definitions.

2. Methods

2.1 Data Collection

Thirty healthy, active young adults (15f/15m, mean (SD) age: 23.0 (3.5) years, height: 1.76 (0.09)

m, mass: 69.2 (11.4) kg, BMI: 22.3 (3.0) kg/m^2) were recruited from the university community to

participate in this study at the Human Mobility Research Laboratory (Kingston, Ontario, Canada)

(Figure 1). Exclusion criteria included having any lower-limb musculoskeletal injury in the past six

months or any neuromuscular or musculoskeletal impairments that could hinder their performance

of running. The research protocol was approved by the institutional research ethics board, and

participants provided written informed consent.

A marker-based motion capture system consisting of seven Qualisys Oqus marker-based

cameras (Qualisys AB, Gothenburg, Sweden) and a markerless motion capture system of eight

Qualisys Miqus video cameras (full HD 1920x1080 resolution, RBG video) were arranged around

an instrumented treadmill (AMTI Inc, Watertown, MA) and were connected to a single instance of

Qualisys Track Manager (QTM), ensuring their temporal synchronization[7]. Both sets of cameras

were calibrated and localized simultaneously (calibration residual errors < 1 mm), ensuring they

shared one global coordinate system (y-axis pointing in the treadmill direction of progression, x-

axis pointing right laterally from the direction of progression, and z-axis pointing vertically). Both

camera systems recorded at 85 Hz, the maximum frame rate for the Miqus cameras at Full HD

(1920x1080) resolution. This camera resolution and frame rate combination was selected to

maximize the resolution used to capture participants, which limited the frame rate to 85 Hz.

Ground reaction forces were recorded at 425 Hz.

For the marker-based system, a static calibration trial was recorded of the subject standing

on the treadmill with their feet pointing anteriorly and positioned approximately shoulder-width

apart, their elbows flexed to approximately 90 degrees, and their palms facing the floor. The

markerless motion capture system does not use a static calibration trial.

Participants ran at a self-selected speed under two clothing conditions: (1 - 'MoCap

clothing') wearing typical marker-based motion capture clothing and markers[7], and (2 - 'Sport

clothing') wearing self-selected athletic clothing which typically consisted of a short-sleeved or

sleeveless shirt and shorts that end at or above the knee. Half of the participants performed the

MoCap condition first and half performed the Sport condition first; the order was not randomized

across the participants. Participants selected their running speed by starting from stationary and

providing feedback to the experimenters to increase or decrease the speed until they were

satisfied with the current speed. The current speed was recorded by the experimenters and was

replicated during the second condition without conveying its value to the participant at any time.

During the MoCap clothing condition, marker-based motion capture, markerless motion

capture, and ground reaction force data were recorded simultaneously. During the Sport clothing

condition, markerless motion capture and ground reaction force data were recorded. During both

conditions, participants wore their personal running shoes and were allowed to acclimatize to their

self-selected running speed on the treadmill for two minutes before one 10-second trial was

recorded. Concurrent marker-based and markerless walking data under the MoCap clothing

condition also obtained during these data collections have been analyzed and published

previously[3,7].

2.2 Data Analysis

Markerless video data were processed in Theia3D v2022-1-0-2309 (Theia Markerless Inc,

Kingston, Ontario, Canada), using 3 degrees of freedom (DOF) at the hip, knee, and ankle

joints, and a 20 Hz equivalent GCVSPL cut-off frequency[8]. Marker-based motion capture data

were tracked in QTM and exported for further analysis in Visual3D (C-Motion Inc, Germantown,

MD). Marker trajectories were filtered using a 20 Hz equivalent GCVSPL cut-off frequency, and

a skeletal model was manually defined with similar segment coordinate system definitions to the

Theia3D model. Model segment lengths were independent between systems, being based on

the markers for the marker-based model and being automatically generated for the markerless

model. The marker-based skeletal model used identical inverse kinematic segment chains and

joint constraints to those used by Theia3D (Table 1).

Table 1: Marker-based model lower body segment coordinate system definitions and inverse kinematic

model constraints, selected to best match the segment definitions and constraints of the Theia3D model.

Segment	Coordinate System	Description
Pelvis	Origin	Midpoint between mid-ASIS and mid-PSIS
	X-Axis	Left ASIS to right ASIS
	Y-Axis	Mid-PSIS to mid-ASIS
	Z-Axis	Normal to xy-plane
	Parent, DOF	Lab, 6 DOF
Kinematic (Virtual) Pelvis	Origin	Point at the height of midpoint between left and right iliac crest markers along vector between midpoint between left and right hip and midpoint between C7 and sternal notch markers
	X-Axis	Left hip joint center to right hip joint center
	Y-Axis	Normal to xz-plane
	Z-Axis	Segment origin to midpoint between C7 and sternal notch markers
	Parent, DOF	Pelvis, 0 DOF
Thigh	Origin	Hip joint center of Pelvis, based on (Bell et al., 1990)
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by hip joint center, medial and lateral femoral epicondyles
	Y-Axis	Vector normal to plane formed by hip joint center, medial and lateral femoral epicondyles
	Z-Axis	Midpoint between medial and lateral femoral epicondyles to hip joint center
	Parent, DOF	Pelvis, 3 DOF

Shank	Origin	Midpoint between medial and lateral femoral epicondyles
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by segment origin, medial and lateral malleoli
	Y-Axis	Vector normal to plane formed by segment origin, medial and lateral malleoli
	Z-Axis	Midpoint between medial and lateral malleoli to segment origin
	Parent, DOF	Thigh, 3 DOF
Foot	Origin	Midpoint between medial and lateral malleoli
	X-Axis	Vector normal to y- and z-axes
	Y-Axis	Segment origin to segment distal point (point an equivalent distance from metatarsal 2/3 marker along a vector normal to the foot plane formed by the heel, metatarsal 1 marker projected to height of metatarsal 5 marker, and metatarsal 5 marker, as the distance from the segment origin to the same foot plane)
	Z-Axis	Metatarsal 2/3 marker to segment distal point (see y-axis)
	Parent, DOF	Shank, 3 DOF

Marker-based and markerless motion capture data were analyzed separately in Visual3D.

Analog signals (force data) from the instrumented treadmill were imported into the markerless

MoCap clothing and Sport clothing .c3d files using the Visual3D 'Import_Signals_From_C3D_File'

pipeline command, allowing these signals to be used with the markerless kinematics to obtain

joint kinetics and create force-based gait events. Analog signals were filtered using a low-pass

critically-damped filter with a cut-off frequency of 20 Hz to match the kinematic filter cut-off

frequency[9], and the Visual3D 'FP Auto Baseline' pipeline command was used to clean the force

platform signals. A vertical ground reaction force threshold of 50 N was used to detect foot contact

events.

Kinematic and kinetic signals including joint positions, segment angles, joint angles, and

internal net joint moments were calculated in Visual3D, and were time-normalized to 101 data

points, representing one complete running gait cycle (0-100%) from heel strike to ipsilateral heel

strike. Segment angles were calculated using a XYZ Cardan sequence relative to the global

coordinate system and were included since they capture the 3D orientation of individual body

segments. Joint angles were calculated using an XYZ Cardan sequence for all joints except the

ankles, for which a XZY Cardan sequence was used. Joint angles were included since they

capture the relative orientation of adjacent segments and are kinematic measures of interest for

most users of motion capture. Joint moments were normalized to participant mass and resolved

in the proximal segment. All data were analyzed further using python (version 3.10.6).

Four participants' markerless Sport clothing trial videos had an inconsistent number of

frames between cameras, preventing their processing in Theia3D; these participants were

excluded from the kinematic comparisons, which then included 26 participants (12f/14m, mean

(SD) age: 23.5 (4.0) years, height: 1.8 (0.1) m, mass: 69.9 (9.9) kg, BMI: 22.8 (2.9) kg/m^2). Six

participants' center-of-pressure data from the instrumented treadmill were found to be erroneous,

one of which was also part of the previously described kinematic exclusion group. The kinetic

comparison sample therefore included 21 participants (10f/11m, mean (SD) age: 23.3 (3.8) years,

height: 1.8 (0.1) m, mass: 69.9 (11.0) kg, BMI: 22.8 (2.8) kg/m^2). Running gait cycles with marker

tracking issues were excluded. For comparison between the markerless and marker-based

motion capture, only matched gait cycles were used.

Differences between signals from corresponding running gait cycles for the concurrent marker-

based and markerless MoCap clothing datasets were calculated and summarized across all

participants as root-mean-square differences (RMSD). Participants' mean signals for the

asynchronous markerless MoCap clothing and Sport clothing conditions were used to assess

differences between markerless clothing conditions and were summarized across all

participants as RMSDs. The inter-cycle variability of the signals from each dataset was

calculated[10], and the inter-condition variability of markerless signals was also calculated to

examine the reliability of markerless measurements across different clothing conditions (similar

to 'inter-session' variability[10]).

2.3 Alternative Marker-Based Modelling

To investigate the effect of marker-based model definitions on kinematic and kinetic

comparisons, results were calculated for two additional models. The first alternative model was

our previous standard marker-based model that was used in prior publications[3] (Supplementary

Materials, Table A). The second alternative model used the same set of markers but applied

atypical segment definitions so that the resulting kinematics best aligned with the markerless

results (Supplementary Materials, Table B). The modifications made to arrive at this model

definition were selected on the basis of improving the agreement between the marker-based

and markerless signals, and serve a purely illustrative purpose. This model was created by

modifying the primary model used in the analysis, using techniques such as virtual markers that

are offset relative to their real counterparts to define segment axes.

3. Results

The average self-selected running speeds for the participant samples used in the kinematic and

kinetic comparisons were 2.42 (0.27) m/s and 2.39 (0.27) respectively.

3.1 Kinematics

Joint center positions from the concurrent marker-based and markerless MoCap clothing data

had mean differences of less than 4 cm throughout the running gait cycle. The mean (SD) RMSD

across all subjects were 2.12 (0.34) cm, 2.15 (0.63) cm, and 2.96 (0.87) cm for the ankle, knee,

and hip joints, respectively (Figure 2). The markerless joint centers were positioned laterally of

the marker-based joint centers for the ankle, knee, and hip, and distal relative to the marker-based

joint centers for the ankle and hip. The sign of the anterior-posterior component was dependent

on the phase of the running gait cycle and was distributed in both directions. The markerless ankle

and hip joint centers were distal of their marker-based counterparts, while the knee was proximal

during early swing phase and slightly distal during late swing and early stance.

Figure 1: Mean joint center position differences between concurrent marker-based motion capture and markerless MoCap clothing condition across all participants, for the global x-direction (row 1; lateral/medial), global y-direction (row 2; anterior/posterior), global z-direction (row 3; proximal/distal), and 3D Euclidean distances (row 4). Differences were assessed as markerless joint position - marker-based joint position; inset position descriptors are for the markerless joint center relative to the marker-based joint center. Mean (SD) RMS of the 3D Euclidean distances is inset for each joint.

Lower limb segment angle x-components capture the largest magnitude of segment rotation during running, and showed very high visual similarity for the thigh, shank, and foot segments (Figure 3). Marker-based pelvis segment angle x-components showed greater variability than those from either markerless clothing condition. Segment angle y-component patterns were visually very similar for the pelvis, thigh, and shank segments, with larger differences between systems than between markerless conditions. The foot segment angle z-component patterns were also visually similar between all three datasets. The thigh and shank z-components, which capture rotations about the segment longitudinal axes, showed the greatest

differences between motion capture systems. The pelvis segment angle z-components showed

the greatest differences between the two markerless clothing conditions (MoCap, Sport) of any

segment angle.

Figure 2: Mean right segment angles from marker-based motion capture (red), markerless motion

capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion

capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap

clothing). Segment angle x-components (left column) represent rotations about the global coordinate

system x-axis, z-components (right column) represent rotations about the segment local coordinate

system z-axis, and y-components (middle column) represent rotations about an axis normal to the global

x-axis and segment z-axis.

Lower limb sagittal plane joint angles and hip ab/adduction (Figure 4) were visually similar

across all three datasets, and had mean RMSDs of 5.2° or lower (Table 2). Ankle toe-in/toe-out

patterns were also somewhat visually consistent between all three datasets during the swing

phase, and had a mean RMSD of 8.0°. The hip internal/external rotation, knee ab/adduction and

internal/external rotation, and ankle inversion/eversion angles captured different patterns and

levels of variability between motion capture systems but were consistent between both markerless

clothing conditions (mean RMSDs: 5-10°). The mean RMSD values for the asynchronous

markerless data (MoCap clothing, Sport clothing) were all smaller than those for the concurrent

marker-based and markerless data, indicating that the differences between markerless joint angle

measures from different trials with different participant clothing were smaller than the differences

between joint angles from marker-based and markerless systems from the same running gait

cycles.

246
247 **Figure 4:** Mean right lower limb joint angles from marker-based motion capture (red), markerless motion
248 capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion
249 capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap
250 clothing) using XYZ Cardan sequences for the knee and hip and a XZY Cardan sequence for the ankle.

Table 2: Mean lower limb joint angle and moment RMS differences across all participants, for the concurrent data comparison (markerless MoCap signals - marker-based MoCap signals) and the asynchronous comparison (markerless MoCap clothing signals - markerless Sport clothing signals).

		Ankle			Knee			Hip		
		Fl/ Ex	Inv/ Ev	Toe-In/-Out	Fl/ Ex	Ab/ Ad	Int/ Ext Rot	Fl/ Ex	Ab/ Ad	Int/ Ext Rot
Joint Angle Differences [deg]	Concurrent Data Mean RMSD	3.8	6.0	8.0	4.2	7.2	9.4	5.2	2.7	9.8
	Asynchronous Data Mean RMSD	3.1	1.6	2.5	3.2	1.8	3.2	3.9	1.7	2.5
Joint Moment Differences [Nm/kg]	Concurrent Data Mean RMSD	0.13	0.25	0.03	0.24	0.12	0.06	0.29	0.22	0.09
	Asynchronous Data Mean RMSD	0.13	0.05	0.03	0.13	0.08	0.05	0.25	0.18	0.07

Inter-cycle joint angle variability values were within 0.6° across all three datasets for all joint angles (Table 3). The average inter-cycle variability across all joint angles was slightly smaller for the marker-based data (1.3°) compared to those for both markerless datasets (1.5°). The inter-condition variability for joint angles between markerless conditions ranged from 1.3°-2.8° (mean 2.0°), leading to variability ratios of 1.2-1.7 (mean 1.3).

Table 3: Joint angle variability measures for each dataset and comparison, including: inter-cycle variability for marker-based MoCap, markerless MoCap clothing, markerless Sport clothing; inter-condition variability for all markerless data; and the variability ratio of markerless inter-condition to mean markerless inter-cycle variability.

		Ankle			Knee			Hip			
		Fl/ Ex	Inv/ Ev	Toe -In/- Out	Fl/ Ex	Ab/ Ad	Int/ Ext Rot	Fl/ Ex	Ab/ Ad	Int/ Ext Rot	Avg
Inter-Cycle Variability [deg]	Marker-based (MoCap clothing)	1.5	1.2	1.4	2.1	0.8	1.3	1.3	0.9	1.3	1.3
	Markerless (MoCap clothing)	1.6	1.2	1.8	2.2	1.0	1.8	1.4	0.9	1.3	1.5
	Markerless (Sport clothing)	1.8	1.2	1.8	2.3	1.0	1.9	1.5	1.0	1.3	1.5
Inter-Condition Variability [deg]	Markerless (MoCap, Sport clothing conditions)	2.3	1.4	2.2	2.8	1.4	2.4	2.4	1.3	1.8	2.0
Variability Ratio	Markerless Inter-Condition/Mean Inter-Cycle	1.4	1.2	1.2	1.2	1.3	1.3	1.7	1.3	1.4	1.3

3.2 Kinetics

Lower limb joint moments from all three datasets captured visually similar patterns for most joint moments, with differences observed in the knee flexion/extension and ab/adduction moments, ankle toe-in/toe-out moments, and large differences observed for the ankle inversion/eversion moments (Figure 5). The marker-based knee moments had greater peak magnitudes and greater variability compared to both markerless conditions in all three planes. The ankle inversion/eversion moments measured by the marker-based system were inversion moments across all subjects and had considerably greater variability compared to those measured by the markerless system, which were primarily eversion moments across all subjects in both conditions. Additionally, the ankle toe-in/toe-out joint moments measured by the marker-based system had a lower peak magnitude compared to both markerless conditions. The markerless MoCap clothing and Sport clothing conditions showed the biggest differences in the hip internal/external rotation moments, ankle inversion/eversion moments, and ankle toe-in/toe-

out moments, for all of which the peak magnitude from the Sport clothing condition was greater

than that of the MoCap clothing condition.

Figure 4: Mean right lower limb joint moments from marker-based motion capture (red), markerless

motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless

motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless

MoCap clothing).

3.3 Alternative Marker-Based Modelling Results

The results of this study when two alternative marker-based models were applied are

included in the Supplementary Materials (Tables A, B; Figures A-F). The results from the model

used in previous studies[3] were consistent with the results of that study, with slight variations due

to the differences in task (walking versus running) (Supplementary Materials, Figures A, B, C).

The results from the modified version of the model used here showed the same or greater

similarity between marker-based and markerless systems for all segment angles, joint angles,

and joint moments (Supplementary Materials, Figures D, E, F).

4. Discussion

The purpose of this study was to compare kinematic and kinetic measures of treadmill running from concurrent marker-based and markerless motion capture, and between asynchronous markerless motion capture under varying clothing conditions. Overall, we found comparable results between the simultaneous marker-based and markerless motion capture data and between clothing conditions for the markerless system.

There are several limitations of this study. Challenges with data collection resulted in some lost participants, but without a significant change in the demographics of the study population. The self-selected treadmill running speed of this group is lower than typical over-ground running speeds, which is likely due to previously observed perception differences in treadmill and over-ground running, and is consistent with previous findings[11,12]. Likewise, the framerate of 85 Hz for data collection is lower than is usually used in running studies but was a limitation of the hardware to allow maximum image resolution and synchronization across both motion capture systems. Although this is a relatively lower frame rate than is typically used to capture running, the purpose was to compare motion capture modalities rather than to study running biomechanics. Using different markerless motion capture hardware or capturing lower resolution videos would allow higher frequency data to be collected. We would anticipate that a higher running speed recorded at a higher framerate would have comparable results to those presented here. The order of the two clothing conditions was divided evenly across all participants, but not randomized and not considered in the data analysis. However, this would have no impact on the comparison of simultaneous marker-based and markerless data, and the lack of differences observed between clothing conditions implies that this was not an issue. Furthermore, the precise segment coordinate system definitions used by Theia3D are not publicly available, so our marker-based definitions that are intended to mimic the markerless segment definitions could possibly be improved upon; but in any case, the anatomical landmarks used by the markerless system are

also not available and likely differ slightly in position from equivalent marker positions by nature

of how they are created and tracked.

Joint position differences between marker-based and markerless concurrent data were

found to be 3 cm or smaller for all joints, which is consistent with previous comparisons of these

systems during treadmill walking[3]. Joint position component differences were also mostly

consistent with those of Tang et al., however they did not report 3D Euclidean distances[6].

Segment and joint angles demonstrated similar agreement between motion capture

systems as in our previous study for treadmill walking gait[3], and excellent agreement across

asynchronous markerless clothing conditions. Sagittal plane joint angles between motion capture

systems had mean RMSD of 5.2° or less for all three joints, consistent with the findings of Tang

et al.[6]. The differences between systems measured as mean RMSD over the entire gait cycle are

comparable to reported minimal detectable change (MDC) values for marker-based motion

capture of treadmill running at initial contact[13]. Compared to the marker-based MDC values, the

RMSD values between systems are 3.1° smaller (for ankle dorsiflexion) to 4.7° greater (for knee

ab/adduction). The between-system agreement observed here is also consistent with previous

comparisons of these systems during treadmill walking[3], which showed larger differences for

segment angles about the segment longitudinal axes, and for frontal and transverse plane angles.

Kinematic and kinetic signals were highly consistent between the markerless MoCap

clothing and Sport clothing conditions, except for pelvis segment angle x- and z-components.

Interpreting kinematic differences between the two markerless motion capture clothing conditions

is made challenging by the fact that they may result from actual changes in movement patterns

between the two running trials or due to differences in markerless keypoint detections as a result

of the change in clothing. The former was indeed the case for at least one participant, whose

markerless joint angles were considerably different between the MoCap and Sport clothing

conditions, and were confirmed from raw video data to have visibly greater ranges of motion in

hip, knee, and ankle flexion for the Sport clothing condition (Supplementary Material, Figure H).

The RMSD values between clothing conditions, which could be considered analogous to a

participant returning on a second day in different clothing, were smaller than published MDC

values at initial contact[13], with the exception of hip flexion (0.2° greater). These findings are

consistent with a running repeatability study over three repeated visits at varying running speeds

using the same markerless motion capture software[14]. Their findings and ours support the use of

markerless motion capture methods to overcome the limitations of marker placement variability

with marker-based motion capture, which has been a challenge for longitudinal running studies[15].

Joint angle inter-cycle variability was small and similar across the marker-based data

(1.3°) and both markerless datasets (1.5°). Inter-cycle variability is made up of natural stride-to-

stride variation in subject biomechanics, as well as measurement variability inherent to the motion

capture systems. Inter-condition variability across markerless clothing conditions was larger than

the inter-cycle variabilities, and presented an average increase of 30% in measurement variability.

The inter-condition variability is made up of inter-cycle variability as described above, plus natural

inter-trial variability, measurement variability due to the varying participant clothing, and

measurement variability inherent to the motion capture system. The inter-condition variability was

smaller than the mean RMSD between concurrent motion capture systems for all joint angles,

indicating that differences between markerless clothing conditions remained smaller than

differences between motion capture systems.

Joint moments showed similarity in pattern and magnitude between systems and across

clothing conditions for the ankle, knee, and hip sagittal plane moments, hip ab/adduction moment,

and hip and knee internal/external rotation moments, while similar patterns of different magnitude

were observed for knee ab/adduction and ankle toe-in/toe-out moments. However, the ankle

inversion/eversion moments displayed different patterns, with the marker-based moments being

mostly inversion moments while the markerless moments were mostly eversion moments.

Differences in sagittal plane joint moment peak magnitudes between marker-based and

markerless joint moments were mostly consistent with the findings of Tang et al., but they did not

report frontal or transverse plane joint moments for either system[6]. The differences in ankle inversion/eversion and toe-in/toe-out moments between systems can be explained by differences in the foot and shank segment orientations, as the selection and orientation of the coordinate system in which joint moments are resolved can entirely change their direction[16]. For instance, when the ankle joint moments are resolved in the foot segment coordinate systems (Supplementary Material, Figure I) rather than the shanks (Figure 3), the marker-based inversion/eversion moments have a considerably reduced magnitude.

The results of this (and any) concurrent validation study of motion capture systems are highly dependent on the biomechanical models employed in the comparison. To investigate this, we applied two alternative models to the marker-based data that differed only in static segment definitions. Alternative model 1 (Supplementary Materials, Table A; Figures A-C) represented a standard unmodified marker-based model that has been previously published[3]. The model in Table 1 represents a slight compromise between standard marker-based and markerless segment definitions. Alternative model 2 (Supplementary Materials, Table B; Figures D-F) represents a model that was manually and intentionally modified to improve the agreement between the marker-based and markerless kinematic and kinetic signals. The modifications used in alternative model 2 were not extreme and remain within the realm of plausibility when considering the differences between marker sets and model definitions, and the variability of marker placement across operators. The results for this last model demonstrate the strong effects of segment definitions and marker placement on downstream biomechanical signals, as they demonstrate that a non-negligible portion of the differences in biomechanical signals can be attributed to local segment coordinate system misalignment and can be changed through relatively small model or landmark changes. The goal of this model was not to create or identify an optimally-modified model for matching marker-based and markerless signals, and it is entirely possible that different modifications could be implemented to greater success in matching the signals between systems. We advocate for the use of the automated coordinate system definition

from Theia3D to facilitate standardization for multi-centre and longitudinal research, but found this

a useful exercise to understand potential differences in how data has been collected from our

historical marker-based approaches. This demonstrated the sensitivity of concurrent comparisons

to these factors, which is an important point that should be understood when using and evaluating

different motion capture solutions. These results highlight the challenges in combining data

collected under different model definitions, and the potential benefit in using markerless motion

capture to provide standardized results that can be pooled from multiple sites.

The results of this study indicate that Theia3D can measure treadmill running kinematics

and kinetics with minimal effects from differing attire, and which are comparable to measures from

marker-based motion capture. This study reiterates the influence of segment definition on

resulting biomechanical signals. Careful consideration of these effects should be taken when

conducting comparisons between measurement systems and relative to historical data that

utilized potentially different segment definitions.

5. Acknowledgements

We thank Human Mobility Research Laboratory members with participant recruitment, data

collection, and data processing. This research was supported by an Ontario Research Fund

grant (ORF RE-04-047), Natural Sciences and Engineering Research Council of Canada

(NSERC) Individual Discovery Grant, and NSERC Canadian Graduate Scholarship.

6. References

1.   de Vries WHK, Veeger HEJ, Baten CTM, van der Helm FCT. Magnetic distortion in

motion labs, implications for validating inertial magnetic sensors. *Gait Posture*.

2009;29(4):535-541. doi:10.1016/j.gaitpost.2008.12.004

2. Jeon TH, Lee JK. IMU-Based Joint Angle Estimation Under Various Walking and

Running Conditions. *J Korean Soc Precis Eng*. 2018;35(12):1199-1204.

doi:10.7736/KSPE.2018.35.12.1199

3. Kanko RM, Laende EK, Davis EM, Selbie WS, Deluzio KJ. Concurrent assessment of

gait kinematics using marker-based and markerless motion capture. *J Biomech*.

2021;127:110665. doi:10.1016/j.jbiomech.2021.110665

4. Riazati S, McGuirk TE, Perry ES, Sihanath WB, Patten C. Absolute Reliability of Gait

Parameters Acquired With Markerless Motion Capture in Living Domains. *Front Hum*

Neurosci. 2022;16:867474. doi:10.3389/fnhum.2022.867474

5. Lahkar BK, Muller A, Dumas R, Reveret L, Robert T. Accuracy of a markerless motion

capture system in estimating upper extremity kinematics during boxing. *Front Sports Act*

Living. 2022;4:939980. doi:10.3389/fspor.2022.939980

6. Tang H, Pan J, Munkasy B, Duffy K, Li L. Comparison of Lower Extremity Joint Moment

and Power Estimated by Markerless and Marker-Based Systems during Treadmill

Running. *Bioengineering*. 2022;9(10):574. doi:10.3390/bioengineering9100574

7. Kanko RM, Laende EK, Strutzenberger G, et al. Assessment of spatiotemporal gait

parameters using a deep learning algorithm-based markerless motion capture system. *J*

Biomech. 2021;122:110414. doi:10.1016/j.jbiomech.2021.110414

8. Woltring HJ. A Fortran package for generalized, cross-validatory spline smoothing and

differentiation. *Adv Eng Softw 1978*. 1986;8(2):104-113. doi:10.1016/0141-

1195(86)90098-7

9. Mai P, Willwacher S. Effects of low-pass filter combinations on lower extremity joint

moments in distance running. *J Biomech*. 2019;95:109311.

doi:10.1016/j.jbiomech.2019.08.005

10.   Schwartz MH, Trost JP, Wervey RA. Measurement and management of errors in

quantitative gait data. *Gait Posture*. 2004;20(2):196-203.

doi:10.1016/j.gaitpost.2003.09.011

11.   Kong PW, Koh TMC, Tan WCR, Wang YS. Unmatched perception of speed when

running overground and on a treadmill. *Gait Posture*. 2012;36(1):46-48.

doi:10.1016/j.gaitpost.2012.01.001

12.   Kong PW, Candelaria NG, Tomaka J. Perception of self-selected running speed is

influenced by the treadmill but not footwear. *Sports Biomech*. 2009;8(1):52-59.

doi:10.1080/14763140802629990

13.   Bramah C, Preece SJ, Gill N, Herrington L. The between-day repeatability, standard

error of measurement and minimal detectable change for discrete kinematic parameters

during treadmill running. *Gait Posture*. 2021;85:211-216.

doi:10.1016/j.gaitpost.2020.12.032

14.   Moran MF, Rogler IC, Wager JC. Inter-Session Repeatability of Marker-Less Motion

Capture of Treadmill Running Gait. *Appl Sci*. 2023;13(3):1702.

doi:10.3390/app13031702

15.   Hébert-Losier K, Dai B, Nunome H, et al. Reporting guidelines for running biomechanics

and footwear studies using three-dimensional motion capture. *Sports Biomech*.

2022;0(0):1-12. doi:10.1080/14763141.2022.2110149

16.   O'Connor KM, Hamill J. Frontal Plane Moments Do Not Accurately Reflect Ankle

Dynamics during Running. *J Appl Biomech*. 2005;21(1):85-95. doi:10.1123/jab.21.1.85

 Supplementary Materials

464 ***1. Effects of alternative model definitions for marker-based motion capture***

465 *1.1 Alternative Model 1*

466 **Table A:** Marker-based model lower body segment coordinate system definitions and inverse kinematic

467 model constraints for the model used in (Kanko et al., 2021a), corresponding to results shown in Figures

468 A, B, C.

Segment	Coordinate System	Description
Pelvis	Origin	Midpoint between mid-ASIS and mid-PSIS
	X-Axis	Left ASIS to right ASIS
	Y-Axis	Mid-PSIS to mid-ASIS
	Z-Axis	Normal to xy-plane formed by left ASIS, right ASIS, and mid-PSIS
	Parent, DOF	Lab, 6 DOF
Thigh	Origin	Hip joint center, based on (Bell et al., 1990)
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by hip joint center, medial and lateral femoral epicondyles
	Y-Axis	Vector normal to plane formed by hip joint center, medial and lateral femoral epicondyles
	Z-Axis	Midpoint between medial and lateral femoral epicondyles to hip joint center
	Parent, DOF	Pelvis, 3 DOF
Shank	Origin	Midpoint between medial and lateral femoral epicondyles
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by medial and lateral femoral epicondyles, midpoint between medial and lateral malleoli
	Y-Axis	Vector normal to plane formed by medial and lateral femoral epicondyles, midpoint between medial and lateral malleoli
	Z-Axis	Midpoint between medial and lateral malleoli to segment origin
	Parent, DOF	Thigh, 3 DOF
Foot	Origin	Midpoint between medial and lateral malleoli
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by medial and lateral malleoli and metatarsal 2/3 marker
	Y-Axis	Vector normal to plane formed by medial and lateral malleoli and metatarsal 2/3 marker
	Z-Axis	Metatarsal 2/3 marker to segment origin

	Parent, DOF	Shank, 3 DOF
Kinematic (Virtual) Foot	Origin	Proximal calcaneus (heel) marker
	X-Axis	Vector perpendicular to plane formed by segment origin, metatarsal 2/3 marker, and a virtual landmark positioned 0.1 m vertically above segment origin
	Y-Axis	Segment origin to metatarsal 2/3 marker
	Z-Axis	Vector perpendicular to y-axis lying in the plane formed by segment origin, metatarsal 2/3 marker, and a virtual landmark positioned 0.1 m vertically above segment origin
	Parent, DOF	Lab, 6 DOF (tracked using Foot)

Figure A: Mean lower limb right segment angles from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model employed in (Kanko et al., 2021a).

Figure B: Mean lower limb right joint angles from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model employed in (Kanko et al., 2021a).

Figure C: Mean lower limb right joint moments from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model employed in (Kanko et al., 2021a).

 1.2 Alternative Model 2

486   **Table B:** Marker-based model lower body segment coordinate system definitions and inverse

487   kinematic model constraints based on the model described in Table 1 determined through trial

488   and error to better match the results from Theia3D for illustrative purposes, corresponding to

489   results shown in Figures D, E, F.

Segment	Coordinate System	Description
Pelvis	Origin	Midpoint between mid-ASIS and mid-PSIS
	X-Axis	Left ASIS to right ASIS
	Y-Axis	Mid-PSIS to mid-ASIS
	Z-Axis	Normal to xy-plane
	Parent, DOF	Lab, 6 DOF
Kinematic (Virtual) Pelvis	Origin	Point at the height of midpoint between left and right iliac crest markers along vector between midpoint between left and right hip and midpoint between C7 and sternal notch markers.
	X-Axis	Left hip joint center to right hip joint center
	Y-Axis	Normal to xz-plane
	Z-Axis	Segment origin to midpoint between C7 and sternal notch markers
	Parent, DOF	Lab, 6 DOF (tracked using Pelvis)
Thigh	Origin	Hip joint center, based on (Bell et al., 1990)
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by segment origin, medial femoral epicondyle shifted 0.008 m anteriorly, and lateral femoral epicondyle shifted 0.008 m posteriorly
	Y-Axis	Vector normal to plane formed by segment origin, medial femoral epicondyle shifted 0.008 m anteriorly, and lateral femoral epicondyle shifted 0.008 m posteriorly
	Z-Axis	Midpoint between medial femoral epicondyle shifted 0.008 m anteriorly and lateral femoral epicondyle shifted 0.008 m posteriorly to segment origin
	Parent, DOF	Pelvis, 3 DOF
Shank	Origin	Midpoint between medial femoral epicondyle shifted 0.02 m anteriorly and lateral femoral epicondyle shifted 0.02 m posteriorly
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by medial femoral epicondyle shifted 0.02 m anteriorly, lateral femoral epicondyle shifted 0.02 m posteriorly, and midpoint between medial and lateral malleoli

	Y-Axis	Vector normal to plane formed by medial femoral epicondyle shifted 0.02 m anteriorly, lateral femoral epicondyle shifted 0.02 m posteriorly, and midpoint between medial and lateral malleoli
	Z-Axis	Midpoint between medial and lateral malleoli to midpoint between medial femoral epicondyle shifted 0.02 m anteriorly and lateral femoral epicondyle shifted 0.02 m posteriorly
	Parent, DOF	Thigh, 3 DOF
Foot	Origin	Midpoint between medial and lateral malleoli
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by segment origin, segment distal point (see y-axis), and a shifted lateral malleoli marker (shifted vertically by the height of the medial malleoli marker – 0.95* height of the lateral malleoli marker - 0.0186 m)
	Y-Axis	Segment origin to segment distal point (point an equivalent distance from metatarsal 2/3 marker along a vector normal to the foot plane formed by the heel, metatarsal 1 marker projected to height of metatarsal 5 marker, and metatarsal 5 marker, as the distance from the segment origin to the same foot plane)
	Z-Axis	Vector perpendicular to y-axis lying in the plane formed by segment origin, segment distal point (see y-axis), and a shifted lateral malleoli marker (shifted vertically by the height of the medial malleoli marker – 0.95* height of the lateral malleoli marker - 0.0186 m)
	Parent, DOF	Shank, 3 DOF

Figure D: Mean lower limb right segment angles from marker-based motion capture (red), markerless
motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless
motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless
MoCap clothing), using the marker-based model defined in Table B to better match the results from
Theia3D for demonstration purposes.

Figure E: Mean lower limb right joint angles from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model defined in Table B to better match the results from Theia3D for demonstration purposes.

Figure F: Mean lower limb right joint moments from marker-based motion capture (red), markerless
motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless
motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless
MoCap clothing), using the marker-based model defined in Table B to better match the results from
Theia3D for demonstration purposes.

2. Example individual participant kinematic waveforms

Raw joint angle data for a representative participant with consistent running biomechanics

(Figure G) and a participant with altered running biomechanics when wearing MoCap clothing

compared to their self-selected Sport clothing (Figure H).

Figure G: Raw lower limb right joint angles for one representative participant, from marker-based motion
capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-
based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-
based and markerless MoCap clothing).

Figure H: Raw lower limb right joint angles for one participant who used different biomechanical patterns
between the MoCap and Sport clothing conditions, as visually confirmed from the raw markerless videos.
Joint angles shown from marker-based motion capture (red), markerless motion capture under MoCap
clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport
clothing condition (green; asynchronous with marker-based and markerless MoCap clothing).

524   *3. Effect of ankle moments resolved in foot segment coordinate system*

Figure I: Mean lower limb right joint moments from marker-based motion capture (red), markerless
motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless
motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless
MoCap clothing), with the ankle joint moments resolved in the foot segment coordinate system.