Comparison of concurrent and asynchronous running kinematics and kinetics from marker-based motion capture and markerless motion capture under two clothing conditions

Robert M. Kanko[A, B], Jereme B. Outerleys[A, B], Elise K. Laende[A], W. Scott Selbie[B], Kevin J. Deluzio[A]

Affiliations:

[A] Mechanical and Materials Engineering, Queen's University, Kingston, Ontario, Canada

[B] Theia Markerless Inc., Kingston, Ontario, Canada

Declaration of Interests:

RMK and JBO are employed by Theia Markerless Inc, and WSS is the CEO of Theia Markerless Inc. Data for this study was collected by RMK in the Human Mobility Research Laboratory at Queen's University under the supervision of KJD, prior to employment with Theia Markerless Inc.

Acknowledgements:

We thank Human Mobility Research Laboratory members with participant recruitment, data collection, and data processing. This research was supported by an Ontario Research Fund grant (ORF RE-04-047), Natural Sciences and Engineering Research Council of Canada (NSERC) Individual Discovery Grant, and NSERC Canadian Graduate Scholarship.

Abstract

Running gait analysis has been pursued as a potential tool to record and quantify athletes' movement

patterns to predict injury, inform interventions, or improve performance. Limitations associated with

marker-based motion capture have reduced its impact and applications. Markerless motion capture

promises fewer limitations, but examining the relationship between markerless and marker-based

motion capture data is important to understand how markerless results can be interpreted alongside

historical data collected using marker-based motion capture. Further, markerless motion capture uses

automated estimation of landmarks, which may be influenced by clothing. To investigate these aspects

of markerless motion capture, we compared lower limb kinematic and kinetic measures during treadmill

running from concurrent marker-based and markerless motion capture (Theia3D), and asynchronous

markerless motion capture under realistic clothing conditions. Thirty healthy adults ran at a self-selected

speed on an instrumented treadmill while concurrent marker-based and markerless motion capture

data were recorded. The procedure was repeated with participants wearing athletic clothing while

markerless data were recorded. Kinematic and kinetic measurements were consistent between

markerless clothing conditions, indicating that the markerless system is robust to clothing, allowing data

collection of participants in their preferred attire. Joint center positions between concurrent marker-

based and markerless data differed by 3 cm or less. Sagittal plane joint angles differed by 5° or less

between systems, while frontal and transverse plane joint angles differed by 5-10°. Similar joint moment

patterns were captured except ankle inversion/eversion, and some moments differed in peak

magnitudes. Differences between the marker-based and markerless systems were sensitive to

coordinate system definitions, highlighting the importance of considering the effects of segment

coordinate system definition when comparing against historical data or data from other motion capture

modalities.

1. Introduction

Motion capture has long been used to quantify movement patterns, monitor interventions and has potential as a tool for injury prediction. The latter has been a particular focus for those interested in its application to running biomechanics. However, due to the inherent time, cost, environment, and expertise constraints associated with traditional marker-based motion capture approaches, the successes of this tool have been limited. Likewise, wearable sensors such as inertial measurement units (IMUs) have limitations, specifically related to magnetic field effects such as those generated by laboratory treadmills (de Vries et al., 2009; Jeon and Lee, 2018) and are best suited to reporting quantities such as accelerations and angular rates which they measure directly, rather than estimating intersegmental measures such as joint angles.

As emerging technology, markerless motion capture has the potential to capture high resolution three dimension (3D) biomechanical signals of running in a more accessible system that avoids potential effects of applying markers or sensors. Ongoing developments, validations, and applications demonstrate the promise of this form of motion capture technology for increasing the usefulness of motion capture-based running gait analysis. Markerless motion capture systems such as Theia3D (Theia Markerless Inc., Kingston, Ontario, Canada) can measure kinematics using multiple synchronized video cameras with few restrictions on the data collection environment, subject attire, and a significantly reduced collection time compared to marker-based motion capture. Markerless systems have demonstrated success in measuring comparable kinematic signals to those from marker-based motion capture during walking (Kanko et al., 2021a; Riazati et al., 2022), boxing (Lahkar et al., 2022), and running (Tang et al., 2022). While marker-based motion capture may not provide a true gold standard for biomechanical data collection due to issues with soft tissue artefact and marker placement variation, it is a historically accepted technology and forms the basis of much of the running biomechanics literature. Understanding how data collected with markerless motion capture compares to marker-

based data, as well as the factors contributing to any differences between the two systems, is an

important step in the introduction of markerless technology to the field of running biomechanics.

Further, we were motivated to understand the effect of clothing on the reliability of the markerless

system. Therefore, the objectives of this study were to compare kinematic and kinetic data from

concurrent markerless and marker-based motion capture during treadmill running, examine the impact

of clothing on markerless motion capture, and investigate the sensitivity of kinematic and kinetic data to

biomechanical model definitions.

2. Methods

2.1 Data Collection

Thirty healthy, active young adults (15f/15m, mean (SD) age: 23.0 (3.5) years, height: 1.76 (0.09) m,

mass: 69.2 (11.4) kg, BMI: 22.3 (3.0) kg/m^2) were recruited from the university community to participate

in this study at the Human Mobility Research Laboratory (Kingston, Ontario, Canada). Exclusion criteria

included having any lower-limb musculoskeletal injury in the past six months or any neuromuscular or

musculoskeletal impairments that could hinder their performance of running. The research protocol was

approved by the institutional research ethics board, and participants provided written informed

consent.

A marker-based motion capture system consisting of seven Qualisys Oqus marker-based

cameras (Qualisys AB, Gothenburg, Sweden) and a markerless motion capture system of eight Qualisys

Miqus video cameras (full HD 1920x1080 resolution, RBG video) were arranged around an instrumented

treadmill (AMTI Inc, Watertown, MA) and were connected to a single instance of Qualisys Track

Manager (QTM), ensuring their temporal synchronization (Kanko et al., 2021b). Both sets of cameras

were calibrated and localized simultaneously (calibration residual errors < 1 mm), ensuring they shared

one global coordinate system (x-axis pointing right laterally, y-axis pointing in the treadmill direction of

progression, and z-axis pointing vertically). Both camera systems recorded at 85 Hz, which is the

maximum frame rate for the Miqus cameras at full HD resolution, while ground reaction forces were

recorded at 425 Hz.

For the marker-based system, a static calibration trial was recorded of the subject standing on

the treadmill with their feet pointing anteriorly and positioned approximately shoulder-width apart,

their elbows flexed to approximately 90 degrees, and their palms facing the floor. The markerless

motion capture system does not use a static calibration trial.

Participants ran at a self-selected speed under two clothing conditions: (1 - 'MoCap clothing')

wearing typical marker-based motion capture clothing and markers (Kanko et al., 2021b), and (2 - 'Sport

clothing') wearing self-selected athletic clothing which typically consisted of a short-sleeved or

sleeveless shirt and shorts that end at or above the knee. Half of the participants performed the MoCap

condition first and half performed the Sport condition first; the order was not randomized across the

participants. Each participant's self-selected speed was replicated during both conditions.

During the MoCap clothing condition, marker-based motion capture, markerless motion

capture, and ground reaction force data were recorded simultaneously. During the Sport clothing

condition, markerless motion capture and ground reaction force data were recorded. During both

conditions, participants wore their personal running shoes and were allowed to acclimatize to their self-

selected running speed on the treadmill for two minutes before one 10-second trial was recorded.

Concurrent marker-based and markerless walking data under the MoCap clothing condition also

obtained during these data collections have been analyzed and published previously (Kanko et al.,

2021a, 2021b).

2.2 Data Analysis

Markerless video data were processed in Theia3D v2022-1-0-2309 (Theia Markerless Inc, Kingston,

Ontario, Canada), using 3 degrees of freedom (DOF) at the hip, knee, and ankle joints, and a 20 Hz

equivalent GCVSPL cut-off frequency (Woltring, 1986). Marker-based motion capture data were tracked

in QTM and exported for further analysis in Visual3D (C-Motion Inc, Germantown, MD). Marker

trajectories were filtered using a 20 Hz equivalent GCVSPL cut-off frequency, and a skeletal model was

manually defined with similar segment coordinate system definitions to the Theia3D model. Model

segment lengths were independent between systems, being based on the markers for the marker-based

model and being automatically calculated for the markerless model. The marker-based skeletal model

used identical inverse kinematic segment chains and joint constraints to those used by Theia3D (Table

1).

Table 1: Marker-based model lower body segment coordinate system definitions and inverse kinematic model
constraints, selected to best match the segment definitions and constraints of the Theia3D model.

Segment	Coordinate System	Description
Pelvis	Origin	Midpoint between mid-ASIS and mid-PSIS
	X-Axis	Left ASIS to right ASIS
	Y-Axis	Mid-PSIS to mid-ASIS
	Z-Axis	Normal to xy-plane
	Parent, DOF	Lab, 6 DOF
Kinematic (Virtual) Pelvis	Origin	Point at the height of midpoint between left and right iliac crest markers along vector between midpoint between left and right hip and midpoint between C7 and sternal notch markers
	X-Axis	Left hip joint center to right hip joint center
	Y-Axis	Normal to xz-plane
	Z-Axis	Segment origin to midpoint between C7 and sternal notch markers
	Parent, DOF	Pelvis, 0 DOF
Thigh	Origin	Hip joint center of Pelvis, based on (Bell et al., 1990)
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by hip joint center, medial and lateral femoral epicondyles
	Y-Axis	Vector normal to plane formed by hip joint center, medial and lateral femoral epicondyles
	Z-Axis	Midpoint between medial and lateral femoral epicondyles to hip joint center
	Parent, DOF	Pelvis, 3 DOF
Shank	Origin	Midpoint between medial and lateral femoral epicondyles
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by segment origin, medial

		and lateral malleoli
	Y-Axis	Vector normal to plane formed by segment origin, medial and lateral malleoli
	Z-Axis	Midpoint between medial and lateral malleoli to segment origin
	Parent, DOF	Thigh, 3 DOF
Foot	Origin	Midpoint between medial and lateral malleoli
	X-Axis	Vector normal to y- and z-axes
	Y-Axis	Segment origin to segment distal point (point an equivalent distance from metatarsal 2/3 marker along a vector normal to the foot plane formed by the heel, metatarsal 1 marker projected to height of metatarsal 5 marker, and metatarsal 5 marker, as the distance from the segment origin to the same foot plane)
	Z-Axis	Metatarsal 2/3 marker to segment distal point (see y-axis)
	Parent, DOF	Shank, 3 DOF

144  Marker-based and markerless motion capture data were analyzed separately in Visual3D. Force

145 data from the instrumented treadmill were imported into the markerless MoCap clothing and Sport

146 clothing .c3d files, allowing these signals to be used with the markerless kinematics to obtain joint

147 kinetics and create force-based gait events. Force data were filtered using a low-pass critically-damped

148 filter with a cut-off frequency of 20 Hz to match the kinematic filter cut-off frequency (Mai and

149 Willwacher, 2019), and the 'FP Auto Baseline' function in Visual3D was used to clean the force platform

150 signals. A vertical ground reaction force threshold of 50 N was used to detect foot contact events.

151  Kinematic and kinetic signals including joint positions, segment angles, joint angles, and internal

152 net joint moments were calculated in Visual3D, and were time-normalized to 101 data points,

153 representing one complete running gait cycle (0-100%) from heel strike to ipsilateral heel strike.

154 Segment angles were calculated using a XYZ Cardan sequence relative to the global coordinate system.

155 Segment angles were included since they capture the 3D orientation of individual body segments. Joint

156 angles were calculated using an XYZ Cardan sequence for all joints except the ankles, for which a XZY

157 Cardan sequence was used. Joint angles were included since they capture the relative orientation of

158 adjacent segments and are kinematic measures of interest for most users of motion capture. Joint

159 moments were normalized to participant mass and resolved in the proximal segment. All data were

160 analyzed further using python (version 3.10.6).

Four participants' markerless Sport clothing trial videos had an inconsistent number of frames

between cameras, preventing their processing in Theia3D; these participants were excluded from the

kinematic comparisons, which then included 26 participants (12f/14m, mean (SD) age: 23.5 (4.0) years,

height: 1.8 (0.1) m, mass: 69.9 (9.9) kg, BMI: 22.8 (2.9) kg/m^2). Six participants' center-of-pressure data

from the instrumented treadmill were found to be erroneous. The kinetic comparison sample then

included 21 participants (10f/11m, mean (SD) age: 23.3 (3.8) years, height: 1.8 (0.1) m, mass: 69.9 (11.0)

kg, BMI: 22.8 (2.8) kg/m^2). Running gait cycles with marker tracking issues were excluded. For

comparison between the markerless and marker-based motion capture, only matched gait cycles were

used.

Differences between signals from corresponding running gait cycles for the concurrent marker-

based and markerless MoCap clothing datasets were calculated and summarized across all participants

as root-mean-square differences (RMSD). Participants' mean signals for the asynchronous markerless

MoCap clothing and Sport clothing conditions were used to assess differences between markerless

clothing conditions and were summarized across all participants as RMSDs. The inter-cycle variability of

the signals from each dataset was calculated (Schwartz et al., 2004), and the inter-condition variability

of markerless signals was also calculated to examine the reliability of markerless measurements across

different clothing conditions (similar to 'inter-session' variability, Schwartz et al., 2004).

2.3 Alternative Marker-Based Modelling

To investigate the effect of marker-based model definitions on kinematic and kinetic comparisons,

results were calculated for two additional models. The first alternative model was our previous standard

marker-based model that was used in prior publications (Kanko et al., 2021a) (Supplementary Materials,

Table A). The second alternative model used the same set of markers but applied atypical segment

definitions so that the resulting kinematics best aligned with the markerless results (Supplementary

Materials, Table B).

3. Results

The average self-selected running speeds for the participant samples used in the kinematic and kinetic

comparisons were 2.42 (0.27) m/s and 2.39 (0.27) respectively.

3.1 Kinematics

Joint center positions from the concurrent marker-based and markerless MoCap clothing data had mean

differences that remained below 4 cm throughout the running gait cycle. The mean (SD) RMSD across all

subjects were 2.12 (0.34) cm, 2.15 (0.63) cm, and 2.96 (0.87) cm for the ankle, knee, and hip joints,

respectively (Figure 1). The markerless joint centers were positioned laterally of the marker-based joint

centers for the ankle, knee, and hip, and distal relative to the marker-based joint centers for the ankle

and hip. The sign of the anterior-posterior component was dependent on the phase of the running gait

cycle and was distributed in both directions throughout. The markerless ankle and hip joint centers were

distal of their marker-based counterparts, while the knee was proximal during early swing phase and

slightly distal at all other times.

Figure 1: Mean joint center position differences between concurrent marker-based motion capture and markerless MoCap clothing condition across all participants, for the global x-direction (row 1; lateral/medial), global y-direction (row 2; anterior/posterior), global z-direction (row 3; proximal/distal), and 3D Euclidean distances (row 4). Differences were assessed as markerless joint position - marker-based joint position; inset position descriptors are for the markerless joint center relative to the marker-based joint center. Mean (SD) RMS of the 3D Euclidean distances is inset for each joint.

Lower limb segment angle x-components, which capture the largest magnitude of segment rotation during running, demonstrated high similarity between all three datasets for all lower body segments (Figure 2). Marker-based pelvis segment angle x-components showed greater variability than those from either markerless clothing condition. Segment angle y-components captured similar patterns from all three datasets for the pelvis, thigh, and shank segments, with slight differences between both markerless datasets and the marker-based signals, but excellent consistency between the markerless datasets. The foot segment angle z-component also captured similar patterns between motion capture

214 systems and excellent consistency between the markerless datasets. The thigh and shank z-components

215 showed the greatest differences between motion capture systems; these segment angles capture

216 rotations about the segment longitudinal axes, which are the most challenging rotations to accurately

217 capture. The pelvis segment angle z-components showed the greatest differences between the two

218 markerless clothing conditions (MoCap, Sport) of any segment angle.

Figure 2: Mean right segment angles from marker-based motion capture (red), markerless motion capture under
MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport
clothing condition (green; asynchronous with marker-based and markerless MoCap clothing). Segment angle x-
components (left column) represent rotations about the global coordinate system x-axis, z-components (right
column) represent rotations about the segment local coordinate system z-axis, and y-components (middle column)
represent rotations about an axis normal to the global x-axis and segment z-axis.

Lower limb sagittal plane joint angles and hip ab/adduction (Figure 3) were similar across all

three datasets, with mean RMSDs of 5.2° or lower (Table 2). Ankle toe-in/toe-out angles were also

somewhat consistent between all three datasets, differing more during stance phase than swing phase

(mean RMSD: 8.0°). The remaining joint angles captured different patterns and levels of variability

between motion capture systems but were consistent between both markerless clothing conditions

(mean RMSDs: 5-10°). The frontal and transverse plane joint angles are influenced by the longitudinal

rotation of the thigh and shank segments which were the least similar segment angles between systems

(Figure 2).

The mean RMSD values for the asynchronous markerless data (MoCap clothing, Sport clothing)

were all smaller than those for the concurrent marker-based and markerless data, indicating that the

differences between markerless joint angle measures from different trials and with different participant

clothing remain smaller than the differences between motion capture systems.

Figure 4: Mean right lower limb joint angles from marker-based motion capture (red), markerless motion capture

under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under

Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing) using XYZ

Cardan sequences for the knee and hip and a XZY Cardan sequence for the ankle.

Table 2: Mean lower limb joint angle and moment RMS differences across all participants, for the concurrent data

comparison (markerless MoCap signals - marker-based MoCap signals) and the asynchronous comparison

(markerless MoCap clothing signals - markerless Sport clothing signals).

		Ankle			Knee			Hip		
		Fl/ Ex	Inv/ Ev	Toe-In/-Out	Fl/ Ex	Ab/ Ad	Int/ Ext Rot	Fl/ Ex	Ab/ Ad	Int/ Ext Rot
Joint Angle Differences [deg]	Concurrent Data Mean RMSD	3.8	6.0	8.0	4.2	7.2	9.4	5.2	2.7	9.8
	Asynchronous Data Mean RMSD	3.1	1.6	2.5	3.2	1.8	3.2	3.9	1.7	2.5
Joint Moment Differences [Nm/kg]	Concurrent Data Mean RMSD	0.13	0.25	0.03	0.24	0.12	0.06	0.29	0.22	0.09
	Asynchronous Data Mean RMSD	0.13	0.05	0.03	0.13	0.08	0.05	0.25	0.18	0.07

Inter-cycle joint angle variability was similar across all three datasets, being within 0.6° for all

joint angles (Table 3). The average inter-cycle variability across all joint angles was slightly smaller for

the marker-based data (1.3°) compared to those for both markerless datasets (1.5°). The inter-cycle

variability is made up of natural stride-to-stride variation in subject biomechanics, as well as

measurement variability inherent to the motion capture systems. Inter-condition variability for joint

angles between markerless conditions (average 2.0°) was slightly greater than the inter-cycle variability

of either dataset, with variability ratios of 1.2-1.7 (mean 1.3). This indicates that the variability in joint

angles captured across trials with different participant clothing is on average 30% greater than the

variability between running gait cycles within a single trial. The inter-condition variability is made up of

inter-cycle variability as described above, plus natural inter-trial variability, measurement variability due

to the varying participant clothing, and measurement variability inherent to the motion capture system.

Table 3: Joint angle variability measures for each dataset and comparison, including: inter-cycle variability for
marker-based MoCap, markerless MoCap clothing, markerless Sport clothing; inter-condition variability for all
markerless data; and the variability ratio of markerless inter-condition to mean markerless inter-cycle variability.

		Ankle			Knee			Hip			
		Fl/ Ex	Inv/ Ev	Toe-In/-Out	Fl/ Ex	Ab/ Ad	Int/ Ext Rot	Fl/ Ex	Ab/ Ad	Int/ Ext Rot	Avg
Inter-Cycle Variability [deg]	Marker-based (MoCap clothing)	1.5	1.2	1.4	2.1	0.8	1.3	1.3	0.9	1.3	1.3
	Markerless (MoCap clothing)	1.6	1.2	1.8	2.2	1.0	1.8	1.4	0.9	1.3	1.5
	Markerless (Sport clothing)	1.8	1.2	1.8	2.3	1.0	1.9	1.5	1.0	1.3	1.5
Inter-Condition Variability [deg]	Markerless (MoCap, Sport clothing conditions)	2.3	1.4	2.2	2.8	1.4	2.4	2.4	1.3	1.8	2.0
Variability Ratio	Markerless Inter-Condition/Mean Inter-Cycle	1.4	1.2	1.2	1.2	1.3	1.3	1.7	1.3	1.4	1.3

3.2 Kinetics

Lower limb joint moments from all three datasets captured similar patterns for most joint moments,

with slight differences observed in the knee flexion/extension and ab/adduction moments, ankle toe-

in/toe-out moments, and larger differences observed for the ankle inversion/eversion moments (Figure

4). The marker-based knee moments had greater peak magnitudes and greater variability compared to

both markerless conditions in all three planes. The ankle inversion/eversion moments measured by the

marker-based system were inversion moments across all subjects and had considerably greater

variability compared to those measured by the markerless system, which were mostly eversion

moments across all subjects in both conditions. Additionally, the ankle toe-in/toe-out joint moments

measured by the marker-based system had a lower peak magnitude compared to both markerless

conditions. The largest differences between the markerless MoCap clothing and Sport clothing

conditions were observed in the hip internal/external rotation moments and ankle toe-in/toe-out

moments, for both of which the peak magnitude from the Sport clothing condition was slightly greater

than that of the MoCap clothing condition.

Figure 4: Mean right lower limb joint moments from marker-based motion capture (red), markerless motion

capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture

under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing).

3.3 Alternative Marker-Based Modelling Results

The results of this study when two alternative marker-based models were applied are included in the

Supplementary Materials (Tables A, B; Figures A-F). The results from the model used in (Kanko et al.,

2021a) were consistent with the results of that study, with slight variations due to the differences in task

(walking versus running) (Supplementary Materials, Figures A, B, C). The results from the modified

version of the model used here showed the same or greater similarity between marker-based and

markerless systems for all segment angles, joint angles, and joint moments (Supplementary Materials,

Figures D, E, F).

4. Discussion

The purpose of this study was to compare kinematic and kinetic measures of treadmill running from concurrent marker-based and markerless motion capture, and between asynchronous markerless motion capture under varying clothing conditions. Overall, we found comparable results between the simultaneous marker-based and markerless motion capture data and between clothing conditions for the markerless system.

Joint position differences between marker-based and markerless concurrent data were found to be 3 cm or smaller for all joints, which is consistent with previous comparisons of these systems during treadmill walking (Kanko et al., 2021a). Joint position component differences were also mostly consistent with those of Tang et al., however they did not report 3D Euclidean distances (Tang et al., 2022).

Segment and joint angles demonstrated similar agreement between motion capture systems as in our previous study for treadmill walking gait (Kanko et al., 2021a), and excellent agreement across asynchronous markerless clothing conditions. Sagittal plane joint angles between motion capture systems had mean RMSD of 5.2° or less for all three joints, consistent with the findings of Tang et al. (Tang et al., 2022). The differences between systems measured as mean RMSD over the entire gait cycle are comparable to reported minimal detectable change (MDC) values for marker-based motion capture of treadmill running at initial contact (Bramah et al., 2021). Compared to the marker-based MDC values, the RMSD values between systems are 3.1° smaller (for ankle dorsiflexion) to 4.7° greater (for knee ab/adduction). The between-system agreement observed here is also consistent with previous comparisons of these systems during treadmill walking (Kanko et al., 2021a), which showed larger differences for segment angles about the segment longitudinal axes, and for frontal and transverse plane angles.

Kinematic and kinetic signals were highly consistent between the markerless MoCap clothing

and Sport clothing conditions, except for pelvis segment angle x- and z-components. Interpreting

kinematic differences between the two markerless motion capture clothing conditions is made

challenging by the fact that they may result from actual changes in movement patterns between the

two running trials or due to differences in markerless keypoint detections as a result of the change in

clothing. The former was indeed the case for at least one participant, whose markerless joint angles

were considerably different between the MoCap and Sport clothing conditions, and were confirmed

from raw video data to have visibly greater ranges of motion in hip, knee, and ankle flexion for the Sport

clothing condition (Supplementary Material, Figure H). The RMSD values between clothing conditions,

which could be considered analogous to a participant returning on a second day in different clothing,

were smaller than published MDC values at initial contact (Bramah et al., 2021), with the exception of

hip flexion (0.2° greater). These findings are consistent with a running repeatability study over three

repeated visits at varying running speeds using the same markerless motion capture software (Moran et

al., 2023). Their findings and ours support the use of markerless motion capture methods to overcome

the limitations of marker placement variability with marker-based motion capture, which has been a

challenge for longitudinal running studies (Hébert-Losier et al., 2022).

Joint angle inter-cycle variability was small and similar across the marker-based data (1.3°) and

both markerless datasets (1.5°). Inter-condition variability across markerless clothing conditions was

larger than the inter-cycle variabilities, and presented an average increase of 30% in measurement

variability. The inter-condition variability was smaller than the mean RMSD between concurrent motion

capture systems for all joint angles, indicating that differences between markerless clothing conditions

remained smaller than differences between motion capture systems.

Joint moments showed similarity in pattern and magnitude between systems and across

clothing conditions for the ankle, knee, and hip sagittal plane moments, hip ab/adduction moment, and

hip and knee internal/external rotation moments, while similar patterns of different magnitude were

observed for knee ab/adduction and ankle toe-in/toe-out moments. However, the ankle

inversion/eversion moments displayed different patterns, with the marker-based moments being mostly

inversion moments while the markerless moments were mostly eversion moments. Differences in

sagittal plane joint moment peak magnitudes between marker-based and markerless joint moments

were mostly consistent with the findings of Tang et al., but they did not report frontal or transverse

plane joint moments for either system (Tang et al., 2022). The differences in ankle inversion/eversion

and toe-in/toe-out moments between systems can be explained by differences in the foot and shank

segment orientations, as the selection and orientation of the coordinate system in which joint moments

are resolved can entirely change their direction (O'Connor and Hamill, 2005). For instance, when the

ankle joint moments are resolved in the foot segment coordinate systems (Supplementary Material,

Figure I) rather than the shanks (Figure 2), the marker-based inversion/eversion moments have a

considerably reduced magnitude.

350   The results of this (and any) concurrent validation study of motion capture systems are highly

dependent on the biomechanical models employed in the comparison. To investigate this, we applied

two alternative models to the marker-based data that differed only in static segment definitions.

Alternative model 1 (Supplementary Materials, Table A; Figures A-C) represented a standard unmodified

marker-based model that has been previously published (Kanko et al., 2021a). The model in Table 1

represents a slight compromise between standard marker-based and markerless segment definitions.

Alternative model 2 (Supplementary Materials, Table B; Figures D-F) represents a model that was

manually and intentionally modified to improve the agreement between the marker-based and

markerless kinematic and kinetic signals. The modifications used in alternative model 2 were not

extreme and remain within the realm of plausibility when considering the differences between marker

sets and model definitions, and the variability of marker placement across operators. The results for this

last model demonstrate the strong effects of segment definitions and marker placement on

downstream biomechanical signals, as they demonstrate that a non-negligible portion of the differences

in biomechanical signals can be attributed to local segment coordinate system misalignment and can be

changed through relatively small model or landmark changes. We advocate for the use of the

automated coordinate system definition from Theia3D to facilitate standardization for multi-centre and

longitudinal research, but found this a useful exercise to understand potential differences in how data

has been collected from our historical marker-based approaches. This demonstrated the sensitivity of

concurrent comparisons to these factors, which is an important point that should be understood when

using and evaluating different motion capture solutions. These results highlight the challenges in

combining data collected under different model definitions, and the potential benefit in using

markerless motion capture to provide standardized results that can be pooled from multiple sites.

There are several limitations of this study. Challenges with data collection resulted in some lost

participants, but without a significant change in the demographics of the study population. The self-

selected treadmill running speed of this group is lower than typical over-ground running speeds, which

is likely due to previously observed perception differences in treadmill and over-ground running, and is

consistent with previous findings (Kong et al., 2012, 2009). Likewise, the framerate for data collection is

lower than is usually used in running studies but was a limitation of the hardware to allow

synchronization across both motion capture systems. Using different markerless motion capture

hardware or capturing lower resolution videos would allow higher frequency data to be collected. We

would anticipate that a higher running speed recorded at a higher framerate would have comparable

results to those presented here. The order of the two clothing conditions was divided evenly across all

participants, but not randomized and not considered in the data analysis. However, this would have no

impact on the comparison of simultaneous marker-based and markerless data, and the lack of

differences observed between clothing conditions implies that this was not an issue.

Furthermore, the precise segment coordinate system definitions used by Theia3D are not

publicly available, so our marker-based definitions that are intended to mimic the markerless segment

definitions could possibly be improved upon; but in any case, the anatomical landmarks used by the

markerless system are also not available and likely differ slightly in position from equivalent marker

positions by nature of how they are created and tracked.

The results of this study indicate that Theia3D can measure treadmill running kinematics and

kinetics with minimal effect of subjects changing running attire, and are comparable to measures from

marker-based motion capture. This study reiterates the influence of segment definition on resulting

biomechanical signals. Careful consideration of these effects should be taken when conducting

comparisons between measurement systems and relative to historical data that utilized potentially

different segment definitions.

5. Acknowledgements

We thank Human Mobility Research Laboratory members with participant recruitment, data collection,

and data processing. This research was supported by an Ontario Research Fund grant (ORF RE-04-047),

Natural Sciences and Engineering Research Council of Canada (NSERC) Individual Discovery Grant, and

NSERC Canadian Graduate Scholarship.

6. References

Bramah, C., Preece, S.J., Gill, N., Herrington, L., 2021. The between-day repeatability, standard error of

measurement and minimal detectable change for discrete kinematic parameters during

treadmill running. Gait Posture 85, 211–216. https://doi.org/10.1016/j.gaitpost.2020.12.032

de Vries, W.H.K., Veeger, H.E.J., Baten, C.T.M., van der Helm, F.C.T., 2009. Magnetic distortion in motion

labs, implications for validating inertial magnetic sensors. Gait Posture 29, 535–541.

https://doi.org/10.1016/j.gaitpost.2008.12.004

Hébert-Losier, K., Dai, B., Nunome, H., Kong, P.W., Hobara, H., Hsu, W.-C., Bradshaw, E.J., Fong, D.T.P.,

Vanwanseele, B., 2022. Reporting guidelines for running biomechanics and footwear studies

using three-dimensional motion capture. Sports Biomech. 0, 1–12.

https://doi.org/10.1080/14763141.2022.2110149

Jeon, T.H., Lee, J.K., 2018. IMU-Based Joint Angle Estimation Under Various Walking and Running

Conditions. J. Korean Soc. Precis. Eng. 35, 1199–1204.

https://doi.org/10.7736/KSPE.2018.35.12.1199

Kanko, R.M., Laende, E.K., Davis, E.M., Selbie, W.S., Deluzio, K.J., 2021a. Concurrent assessment of gait

kinematics using marker-based and markerless motion capture. J. Biomech. 127, 110665.

https://doi.org/10.1016/j.jbiomech.2021.110665

Kanko, R.M., Laende, E.K., Strutzenberger, G., Brown, M., Selbie, W.S., DePaul, V., Scott, S.H., Deluzio,

K.J., 2021b. Assessment of spatiotemporal gait parameters using a deep learning algorithm-

based markerless motion capture system. J. Biomech. 122, 110414.

https://doi.org/10.1016/j.jbiomech.2021.110414

Kong, P.W., Candelaria, N.G., Tomaka, J., 2009. Perception of self-selected running speed is influenced

by the treadmill but not footwear. Sports Biomech. 8, 52–59.

https://doi.org/10.1080/14763140802629990

Kong, P.W., Koh, T.M.C., Tan, W.C.R., Wang, Y.S., 2012. Unmatched perception of speed when running

overground and on a treadmill. Gait Posture 36, 46–48.

https://doi.org/10.1016/j.gaitpost.2012.01.001

Lahkar, B.K., Muller, A., Dumas, R., Reveret, L., Robert, T., 2022. Accuracy of a markerless motion

429   capture system in estimating upper extremity kinematics during boxing. Front. Sports Act. Living

430   4, 939980. https://doi.org/10.3389/fspor.2022.939980

431   Mai, P., Willwacher, S., 2019. Effects of low-pass filter combinations on lower extremity joint moments

432   in distance running. J. Biomech. 95, 109311. https://doi.org/10.1016/j.jbiomech.2019.08.005

433   Moran, M.F., Rogler, I.C., Wager, J.C., 2023. Inter-Session Repeatability of Marker-Less Motion Capture

434   of Treadmill Running Gait. Appl. Sci. 13, 1702. https://doi.org/10.3390/app13031702

435   O'Connor, K.M., Hamill, J., 2005. Frontal Plane Moments Do Not Accurately Reflect Ankle Dynamics

436   during Running. J. Appl. Biomech. 21, 85–95. https://doi.org/10.1123/jab.21.1.85

437   Riazati, S., McGuirk, T.E., Perry, E.S., Sihanath, W.B., Patten, C., 2022. Absolute Reliability of Gait

438   Parameters Acquired With Markerless Motion Capture in Living Domains. Front. Hum. Neurosci.

439   16, 867474. https://doi.org/10.3389/fnhum.2022.867474

440   Schwartz, M.H., Trost, J.P., Wervey, R.A., 2004. Measurement and management of errors in quantitative

441   gait data. Gait Posture 20, 196–203. https://doi.org/10.1016/j.gaitpost.2003.09.011

442   Tang, H., Pan, J., Munkasy, B., Duffy, K., Li, L., 2022. Comparison of Lower Extremity Joint Moment and

443   Power Estimated by Markerless and Marker-Based Systems during Treadmill Running.

444   Bioengineering 9, 574. https://doi.org/10.3390/bioengineering9100574

445   Woltring, H.J., 1986. A Fortran package for generalized, cross-validatory spline smoothing and

446   differentiation. Adv. Eng. Softw. 1978 8, 104–113. https://doi.org/10.1016/0141-

447   1195(86)90098-7

449   **Supplementary Materials**

450   ***1. Effects of alternative model definitions for marker-based motion capture***

451   *1.1 Alternative Model 1*

452   **Table A:** Marker-based model lower body segment coordinate system definitions and inverse kinematic model

453   constraints for the model used in (Kanko et al., 2021a), corresponding to results shown in Figures A, B, C.

Segment	Coordinate System	Description
Pelvis	Origin	Midpoint between mid-ASIS and mid-PSIS
	X-Axis	Left ASIS to right ASIS
	Y-Axis	Mid-PSIS to mid-ASIS
	Z-Axis	Normal to xy-plane formed by left ASIS, right ASIS, and mid-PSIS
	Parent, DOF	Lab, 6 DOF
Thigh	Origin	Hip joint center, based on (Bell et al., 1990)
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by hip joint center, medial and lateral femoral epicondyles
	Y-Axis	Vector normal to plane formed by hip joint center, medial and lateral femoral epicondyles
	Z-Axis	Midpoint between medial and lateral femoral epicondyles to hip joint center
	Parent, DOF	Pelvis, 3 DOF
Shank	Origin	Midpoint between medial and lateral femoral epicondyles
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by medial and lateral femoral epicondyles, midpoint between medial and lateral malleoli
	Y-Axis	Vector normal to plane formed by medial and lateral femoral epicondyles, midpoint between medial and lateral malleoli
	Z-Axis	Midpoint between medial and lateral malleoli to segment origin
	Parent, DOF	Thigh, 3 DOF
Foot	Origin	Midpoint between medial and lateral malleoli
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by medial and lateral malleoli and metatarsal 2/3 marker
	Y-Axis	Vector normal to plane formed by medial and lateral malleoli and metatarsal 2/3 marker
	Z-Axis	Metatarsal 2/3 marker to segment origin

	Parent, DOF	Shank, 3 DOF
Kinematic (Virtual) Foot	Origin	Proximal calcaneus (heel) marker
	X-Axis	Vector perpendicular to plane formed by segment origin, metatarsal 2/3 marker, and a virtual landmark positioned 0.1 m vertically above segment origin
	Y-Axis	Segment origin to metatarsal 2/3 marker
	Z-Axis	Vector perpendicular to y-axis lying in the plane formed by segment origin, metatarsal 2/3 marker, and a virtual landmark positioned 0.1 m vertically above segment origin
	Parent, DOF	Lab, 6 DOF (tracked using Foot)

Figure A: Mean lower limb right segment angles from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model employed in (Kanko et al., 2021a).

Figure B: Mean lower limb right joint angles from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model employed in (Kanko et al., 2021a).

Figure C: Mean lower limb right joint moments from marker-based motion capture (red), markerless motion

capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture

under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using

the marker-based model employed in (Kanko et al., 2021a).

1.2 Alternative Model 2

Table B: Marker-based model lower body segment coordinate system definitions and inverse kinematic model

constraints based on the model described in Table 1 and artificially modified to better match the results from

Theia3D for demonstration purposes, corresponding to results shown in Figures D, E, F.

Segment	Coordinate System	Description
Pelvis	Origin	Midpoint between mid-ASIS and mid-PSIS
	X-Axis	Left ASIS to right ASIS
	Y-Axis	Mid-PSIS to mid-ASIS
	Z-Axis	Normal to xy-plane
	Parent, DOF	Lab, 6 DOF
Kinematic (Virtual) Pelvis	Origin	Point at the height of midpoint between left and right iliac crest markers along vector between midpoint between left and right hip and midpoint between C7 and sternal notch markers.
	X-Axis	Left hip joint center to right hip joint center
	Y-Axis	Normal to xz-plane
	Z-Axis	Segment origin to midpoint between C7 and sternal notch markers
	Parent, DOF	Lab, 6 DOF (tracked using Pelvis)
Thigh	Origin	Hip joint center, based on (Bell et al., 1990)
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by segment origin, medial femoral epicondyle shifted 0.008 m anteriorly, and lateral femoral epicondyle shifted 0.008 m posteriorly
	Y-Axis	Vector normal to plane formed by segment origin, medial femoral epicondyle shifted 0.008 m anteriorly, and lateral femoral epicondyle shifted 0.008 m posteriorly
	Z-Axis	Midpoint between medial femoral epicondyle shifted 0.008 m anteriorly and lateral femoral epicondyle shifted 0.008 m posteriorly to segment origin
	Parent, DOF	Pelvis, 3 DOF
Shank	Origin	Midpoint between medial femoral epicondyle shifted 0.02 m anteriorly and lateral femoral epicondyle shifted 0.02 m posteriorly
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by medial femoral epicondyle shifted 0.02 m anteriorly, lateral femoral epicondyle shifted 0.02 m posteriorly, and midpoint between medial and lateral malleoli
	Y-Axis	Vector normal to plane formed by medial femoral epicondyle shifted 0.02 m anteriorly, lateral femoral epicondyle shifted 0.02 m posteriorly, and midpoint

		between medial and lateral malleoli
	Z-Axis	Midpoint between medial and lateral malleoli to midpoint between medial femoral epicondyle shifted 0.02 m anteriorly and lateral femoral epicondyle shifted 0.02 m posteriorly
	Parent, DOF	Thigh, 3 DOF
Foot	Origin	Midpoint between medial and lateral malleoli
	X-Axis	Vector perpendicular to z-axis lying in the plane formed by segment origin, segment distal point (see y-axis), and a shifted lateral malleoli marker (shifted vertically by the height of the medial malleoli marker – 0.95* height of the lateral malleoli marker - 0.0186 m)
	Y-Axis	Segment origin to segment distal point (point an equivalent distance from metatarsal 2/3 marker along a vector normal to the foot plane formed by the heel, metatarsal 1 marker projected to height of metatarsal 5 marker, and metatarsal 5 marker, as the distance from the segment origin to the same foot plane)
	Z-Axis	Vector perpendicular to y-axis lying in the plane formed by segment origin, segment distal point (see y-axis), and a shifted lateral malleoli marker (shifted vertically by the height of the medial malleoli marker – 0.95* height of the lateral malleoli marker - 0.0186 m)
	Parent, DOF	Shank, 3 DOF

Figure D: Mean lower limb right segment angles from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model defined in Table B to better match the results from Theia3D for demonstration purposes.

Figure E: Mean lower limb right joint angles from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model defined in Table B to better match the results from Theia3D for demonstration purposes.

Figure F: Mean lower limb right joint moments from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), using the marker-based model defined in Table B to better match the results from Theia3D for demonstration purposes.

  2. Example individual participant kinematic waveforms

491   Raw joint angle data for a representative participant with consistent running biomechanics (Figure G)

492   and a participant with altered running biomechanics when wearing MoCap clothing compared to their

493   self-selected Sport clothing (Figure H).

Figure G: Raw lower limb right joint angles for one representative participant, from marker-based motion capture

496   (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and

497   markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and

498   markerless MoCap clothing).

Figure H: Raw lower limb right joint angles for one participant who used different biomechanical patterns between the MoCap and Sport clothing conditions, as visually confirmed from the raw markerless videos. Joint angles shown from marker-based motion capture (red), markerless motion capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing).

505 *3. Effect of ankle moments resolved in foot segment coordinate system*

Figure I: Mean lower limb right joint moments from marker-based motion capture (red), markerless motion

capture under MoCap clothing condition (blue; concurrent with marker-based), and markerless motion capture

under Sport clothing condition (green; asynchronous with marker-based and markerless MoCap clothing), with the

ankle joint moments resolved in the foot segment coordinate system.