Leading and Following: Noise Differently Affects Semantic and Acoustic Processing during Naturalistic Speech Comprehension

Xinmiao Zhang[a, b], Jiawei Li[c], Zhuoran Li[a, b], Bo Hong[b, d], Tongxiang Diao[e], Xin Ma[e],

Guido Nolte[f], Andreas K. Engel[f], Dan Zhang[a, b, *]

a Department of Psychology, School of Social Sciences, Tsinghua University, Beijing 100084, China

b Tsinghua Laboratory of Brain and Intelligence, Tsinghua University, Beijing 100084, China

c Department of Education and Psychology, Freie Universität Berlin, 14195 Berlin, Germany

d Department of Biomedical Engineering, School of Medicine, Tsinghua University, Beijing 100084, China

e Department of Otolaryngology, Head and Neck Surgery, People's Hospital, Peking University, Beijing 100044, China

f Department of Neurophysiology and Pathophysiology, University Medical Center Hamburg-Eppendorf, 20246 Hamburg, Germany

* Corresponding author: Dan Zhang, dzhang@tsinghua.edu.cn

Abstract

Despite the distortion of speech signals caused by unavoidable noise in daily life, our ability to comprehend speech in noisy environments is relatively stable. However, the neural mechanisms underlying reliable speech-in-noise comprehension remain to be elucidated. The present study investigated the neural tracking of acoustic and semantic speech information during noisy naturalistic speech comprehension. Participants listened to narrative audios mixed with spectrally matched stationary noise at three signal-to-ratio (SNR) levels (no noise, 3 dB, -3 dB), and 60-channel electroencephalography (EEG) signals were recorded. A temporal response function (TRF) method was employed to derive event-related-like responses to the continuous speech stream at both the acoustic and the semantic levels. Whereas the amplitude envelope of the naturalistic speech was taken as the acoustic feature, word entropy and word surprisal were extracted via the natural language processing method as two semantic features. Theta-band frontocentral TRF responses to the acoustic feature were observed at around 400 ms following speech fluctuation onset over all three SNR levels, and the response latency was more delayed with increasing noise. Delta-band frontal TRF responses to the semantic feature of word entropy were observed at around 200 to 600 ms leading to speech fluctuation onset over all three SNR levels. The response latency became more leading with increasing noise and was correlated with the perceived speech intelligibility. While the following responses to speech acoustics were consistent with previous studies, our study revealed the robustness of leading responses to speech semantics, which suggests a possible predictive mechanism at the semantic level for maintaining reliable speech comprehension in noisy environments.

Keywords: speech-in-noise comprehension, semantic processing, neural tracking, temporal response function, EEG

Highlights

1. Leading responses were observed in the semantic-level neural tracking across all noise levels, with more leading latency for increasing noises.

2. Following responses were observed in the acoustic-level neural tracking, with more delayed latency for increasing noises.

3. Semantic-level neural tracking is correlated with perceived intelligibility.

4. Distinct frequency bands were involved in speech semantic and acoustic processing.

1 Introduction

Noise is an inevitable part of daily life, from car horns on the streets to background music at parties, and it presents a significant challenge to verbal communication. Reliable speech comprehension in noisy environments is crucial in various situations such as education or emergency service. Despite the distortion of auditory information, individuals with normal hearing can comprehend speech with ease. Understanding the adaptive neural mechanisms that enable robust speech-in-noise comprehension is essential for clinical intervention for hearing/language-impaired groups and for developing hearing-aid techniques.

Neurophysiological studies have revealed important insights into how noise affects speech processing. Using the event-related techniques, cortical auditory evoked potentials (CAEP) elicited by auditory and speech stimuli have been found to show delayed latency and reduced amplitude under adverse conditions, including the early component P1-N1-P2 complex related to primary sound processing (Billings et al., 2009, 2011), and the later components such as N2 component related to phonological analysis (Billings et al., 2009; Martin & Stapells, 2005; Tomé et al., 2015; Whiting et al., 1998) and P3 component related to speech discrimination (Kaplan-Neeman et al., 2006; Koerner et al., 2017; Martin & Stapells, 2005; Whiting et al., 1998). In recent years, studies have focused more on the neural tracking of continuous speeches. i.e., the synchronization between oscillatory neural activity and the quasi-rhythmic fluctuations of continuous speech (see reviews, Brodbeck & Simon, 2020; Ding & Simon, 2014; Giraud & Poeppel, 2012; Lakatos et al., 2019; Obleser & Kayser, 2019). Specific temporal dynamics of neural tracking can be described via system identification methods such as the temporal response function (TRF; Crosse et al., 2016, 2021) by relating neural signals with speech features such as acoustic envelope. Neural speech tracking has been found to remain stable under mild and moderate noise, and it is regarded as an essential tool for segregating speech from the noisy background (Ding & Simon, 2013). Nevertheless, the TRF-based studies have reported delayed latency and/or reduced amplitude of the neural tracking in noise conditions (Gillis, Decruy, et al., 2022; Mirkovic et al., 2019; Muncke et al., 2022; Zou et al., 2019), similar to previous event-related studies. These results suggested an impaired acoustic processing efficiency in noisy environments (Gillis, Decruy, et al., 2022; Kaplan-Neeman et al., 2006). In addition to auditory processing, semantic processing also plays a vital role in speech-in-noise comprehension and has been paid substantial emphasis.

Semantic processing could be a crucial factor in robust speech comprehension against noisy

environments. Numerous research has shown that coherent semantic context enabling anticipating

upcoming stimuli contributes to an effective understanding of degraded speech (Miller et al., 1951; Obleser

& Kotz, 2010, 2011; Sohoglu et al., 2012; Zekveld et al., 2011). For example, Miller et al. (1951) found

that words in coherent sentences had higher intelligibility compared with the same words in unrelated word

lists during speech-in-noise comprehension. Regarding the influence of noise on semantic processing, such

as the N400 component (Kutas & Federmeier, 2011; Kutas & Hillyard, 1984), several studies have reported

robust or increased amplitude of N400 under mild degradation, which might be related to additional

cognitive effort (Jamison et al., 2016; Romei et al., 2011; Zendel et al., 2015), while other studies reported

reduced/delayed N400 for degraded speech, which might be related to damaged signal quality (Aydelott et

al., 2006; Connolly et al., 1992; Daltrozzo et al., 2012; Obleser & Kotz, 2011; Strauß et al., 2013). These

mixed results provided valuable information on the complex relationship between noise and semantic

processing. Moreover, it was discovered that semantic processing includes early responses before the onset

of the stimulus, which is considered to be associated with semantic prediction (Grisoni et al., 2017, 2021;

Pulvermüller & Grisoni, 2020). Nevertheless, it is still unknown how this pre-onset response is affected by

noise at different SNRs. These inconsistent results and inadequate explorations of noise effect on semantic

processing may be due to limitations inherent in the event-related design. This design typically uses highly-

controlled and short-duration speech units, such as individual words (e.g., Romei et al., 2011) or

disconnected sentences (e.g., Strauß et al., 2013), which only contain limited semantic/contextual

information.

The recent rise of the naturalistic speech paradigm is expected to expand our knowledge of the neural

mechanisms of semantic processing during speech-in-noise comprehension (Z. Li & Zhang, 2023).

Compared to the highly-controlled and short-duration speech units, continuous naturalistic speech stimuli

provide a better resemblance to our daily communications because of a longer duration, more flexible

content, and less deliberate semantic violation (Alday, 2019; Alexandrou et al., 2020; Hartley & Poeppel,

2020; Sonkusare et al., 2019; Willems et al., 2020; Wöstmann et al., 2017). Most of all, the continuous

naturalistic speech stimuli provide rich context-based semantic information (Alday, 2019; Alexandrou et

al., 2020; Hamilton & Huth, 2020; Sonkusare et al., 2019), which is indispensable for semantic prediction

and reliable speech comprehension in chaotic daily environment. In addition, via state-of-art computational

linguistic models, the semantic information of naturalistic speech can be quantified, and the semantic-level

neural tracking can be directly measured (e.g., Broderick et al., 2018, 2019, 2021; Gillis et al., 2021;

Koskinen et al., 2020; Mesik et al., 2021; Weissbart et al., 2020), presenting a powerful tool to investigating

how semantic processing is affected by noise at different SNRs.

The two frequently adopted semantic features in speech-related neuroscience research are entropy and

surprisal derived from information theory (e.g., Brodbeck et al., 2022; Donhauser & Baillet, 2020;

Goldstein et al., 2022; Heilbron et al., 2022), which respectively measures the semantic uncertainty of the

upcoming stimuli and the unexpectedness of the current stimulus (Pickering & Gambi, 2018; Willems et

al., 2016). The word surprisal was found to be associated with the superior temporal gyrus and inferior

frontal sulcus, etc. (Willems et al., 2016), and is linked to an N400-like neural response, i.e., negativity at

around 400 ms within central-parietal electrodes (Broderick et al., 2021; Gillis et al., 2021; Heilbron et al.,

2022). The word entropy was associated with neural activity within the left ventral premotor cortex, left

middle frontal gyrus and right inferior frontal gyrus, etc. (Willems et al., 2016). Furthermore, Goldstein et

al. (2022) derived word entropy from deep language models (GPT-2) and correlated them with

electrocorticography (ECoG) signals. The results indicated that entropy was related to neural activation in

left-lateralized channels at several hundred milliseconds before the word onset. This leading/pre-onset

response is consistent with the semantic prediction potential (SPP) in event-related studies as a direct neural

signature for semantic prediction (Grisoni et al., 2021; Pulvermüller & Grisoni, 2020). A recent study by

Yasmin et al. (2023) discovered that the N400-like response in semantic-level neural tracking remained

robust at mild and moderate noise levels and declined abruptly at high-noise level (SNR = -3 dB). However,

the noise effect on the pre-onset response in semantic-level neural tracking is still unexplored.

The current study aimed to investigate the neural mechanisms of speech-in-noise comprehension by

simultaneously focusing on both the acoustic and semantic levels as well as both the pre-onset and the post-

onset stages. A naturalistic speech comprehension paradigm was employed, as the naturalistic speech

stimuli were expected to provide better ecological validity and contextual information (Alday, 2019;

Sonkusare et al., 2019). 60-channel EEGs were recorded while the participants listened to spoken narratives

at three SNRs (no noise, 3 dB, -3 dB). Following previous studies, the amplitude envelopes of the speech

stimuli were extracted as the acoustic feature (Di Liberto et al., 2015; O'Sullivan et al., 2015). Two typical

semantic features were calculated by a Chinese NLP model, i.e., word entropy and word surprisal (Gillis et

al., 2021; Weissbart et al., 2020; Willems et al., 2016; Koskinen et al., 2020; Mesik et al., 2021; Broderick

et al., 2021). The neural responses to the acoustic and semantic features were estimated using the TRF

method (Crosse et al., 2016), which yielded the spatiotemporal dynamics of how our brain tracked these

features in naturalistic speeches. We hypothesize that the acoustic-level TRF could be related to delayed

peak or reduced amplitude under noisy conditions as in previous studies (Gillis, Decruy, et al., 2022;

Mirkovic et al., 2019; Muncke et al., 2022; Zou et al., 2019). As for the semantic-level TRF, we hypothesize

that both the pre-onset and post-onset response could show resilience against noise (Goldstein et al., 2022;

Yasmin et al., 2023). By exploring the pre-onset and post-onset temporal dynamics of low- and high-level

processing, this study hopes to gain a more complete overview of the noise effect on neural processing

during naturalistic speech comprehension.

2 Methods

2.1 Participants

Twenty college students (10 females, ages ranging from 19 to 28 years old) participated in the study. The sample size was determined to be sufficient by reference to previous TRF-based studies on the human speech processing (Broderick et al., 2018; Di Liberto et al., 2015). One male participant was excluded due to technical problems during data recording. The data of the remaining nineteen participants (age: mean $\pm$ SD $= 21.79 \pm 1.99$) were included in the subsequent analyses. All participants were native Chinese speakers, right-handed, with normal hearing and normal or corrected-to-normal vision by self-report. The study was conducted in accordance with the Declaration of Helsinki and was approved by the local Ethics Committee of Tsinghua University. Written informed consent was obtained from all participants.

2.2 Materials

Thirty narrative audios from our previous studies (Z. Li et al., 2021, 2022) were used as stimuli. These audios were recorded from six native Chinese speakers with professional training in broadcasting. The participants were unfamiliar with the content of these narrative audios, which were about speakers' personal experiences on daily-life topics adapted from the National Mandarin Proficiency Test. Each narrative audio lasted for around 90 s and was recorded by a regular microphone at a sampling rate of 44,100 Hz in a sound-attenuated room.

These speech stimuli were further processed into three versions at three different SNR levels: no-noise (NN), low-noise (SNR = 3 dB), and high-noise (SNR = -3 dB) by adding spectrally matched stationary noise. The spectrally matched stationary noise was generated based on a 50th-order linear predictive coding (LPC) model estimated from the original speech recording (Broderick et al., 2018). The SNR levels were selected following previous studies (Ding & Simon, 2013), and were produced by varying the noise intensity while keeping the intensity of original speech (measured by its root mean square) constant (Ding & Simon, 2013).

For each narrative audio, two four-choice questions were prepared by the experimenters to assess one's speech comprehension performance. These questions and the corresponding choices were targeted at detailed narrative contents that would demand significant attentional efforts. For instance, one question

following a narrative audio about one's major was, "What is the speaker's most likely major as a graduate

student? (说话人的研究生专业最可能是什么？)" and the four choices were 1) Social science, 2)

International politics, 3) Pedagogy and 4) Psychology (1. 社会科学, 2. 国际政治, 3. 教育学 and 4. 心理学).

2.3 Procedure

Before the start of the experiment, the participants had one practice trial to get familiar with the

procedure, with an additional speech audio stimulus not used in the formal experiment at the no-noise level.

The formal experiment consisted of 30 trials, with 10 trials per noise level. In each trial, the participants

listened to narrative audios at one of the three noise levels. The participants were required to maintain visual

fixation on a fixation cross displayed on the computer screen in front of them and to minimize eye blinks

and all other motor activities during listening. The order of the narrative audios and their assigned noise

levels was randomized for each participant.

After each trial, the participants were instructed to answer two four-choice questions about the content

of the narrative audio using the computer keyboard. The averaged accuracies across all trials (separately

for each noise level) were used to reflect the participants' comprehension performance. After completing

these questions, the participants were instructed to rate the clarity and intelligibility of the narrative audio

on a 100-point rating scale and rested for at least 5 s before moving on to the next trial. No feedback was

given to the participants about their comprehension performance during the experiment.

The experimental procedure was programmed in MATLAB using the Psychophysics Toolbox 3.0

(Brainard, 1997). The speech stimuli were delivered to listeners seated in a sound-attenuated room via an

air-tube earphone (Etymotic ER2, Etymotic Research, Elk Grove Village, IL, USA) to avoid environmental

noise and equipment electromagnetic interference. All speech stimuli were presented at a comfortable level.

The experimental procedure is illustrated in Figure 1.

Figure 1. Experimental procedure. The participants listened to 30 naturalistic narrative audios which each
lasted around 90 s. These audios were mixed with three levels of spectrally matched stationary noise: no-
noise (NN), low-noise (SNR = 3 dB), and high-noise (SNR = -3 dB). The 60-channel EEG signals were
recorded during listening. After listening to each audio, the participants were required to complete a
comprehension test and report the clarity and intelligibility rating. In the comprehension test, two four-
choice questions per speech audio based on the narrative content were used.

2.4 EEG recording and preprocessing

EEG signals were recorded from 60 channels with a NeuroScan amplifier (SynAmp II, NeuroScan,

Compumedics, USA) at a sampling rate of 1000 Hz. Electrodes were positioned according to the

international 10–20 system, including FP1/2, FPZ, AF3/4, F7/8, F5/6, F3/4, F1/2, FZ, FT7/8, FC5/6, FC3/4,

FC1/2, FCZ, T7/8, C5/6, C3/4, C1/2, CZ, TP7/8, CP5/6, CP3/4, CP1/2, CPZ, P7/8, P5/6, P3/4, P1/2, PZ,

PO7/8, PO5/6, PO3/4, POZ, Oz, O1/2, referenced to an electrode between CZ and CPZ with a forehead

ground at FZ. Electrode impedances were kept below 10 kOhm for all electrodes throughout the experiment.

The recorded EEG data were first notch filtered to remove the 50 Hz powerline noise. Independent

Component Analysis (ICA) was performed to remove artifacts such as eye blinks and eye movements based

on visual inspection. Around 4–12 independent components (ICs; mean = 6.6) were removed per participant.

The remaining ICs were then back-projected onto the scalp EEG channels to reconstruct the artifact-free

EEG signals. The EEG signals were then re-referenced to the average of all scalp channels and down-

sampled to 128 Hz. Afterward, EEG signals were filtered into delta (1–4 Hz) and theta (4–8 Hz) bands,

which have been previously reported to be important for speech processing (Ding et al., 2014; Ding &

Simon, 2014; Etard & Reichenbach, 2019; Fiedler et al., 2019; Keitel et al., 2017; Koskinen et al., 2020;

Lu et al., 2022; Peelle et al., 2013). Causal FIR (Finite Impulse Response) filters were employed to ensure

that the filtered EEG signals were determined only by the current and previous data samples, which was

important for the present study focusing on the fine-grained time course, particularly considering the pre-

onset neural responses (de Cheveigné & Nelken, 2019).

These preprocessed EEG signals were segmented into 30 trials, from 5 to 90 s (duration = 85 s),

relative to the speech onsets of each trial to avoid possible onset and offset effects. All preprocessing was

conducted offline using MATLAB and the Fieldtrip toolbox (Oostenveld et al., 2011).

2.5 Feature extraction

Three types of features were extracted to represent the acoustic (amplitude envelope) and semantic

(word entropy, word surprisal) information for each narrative audio. An example of these speech features

is illustrated in Figure 2A.

Acoustic feature. The amplitude envelope for each narrative audio was calculated as the absolute

values after a Hilbert transform and then down-sampled to the sampling rate of 128 Hz to match that of the

EEG signals.

Semantic features. Before feature extraction, the narrative audios were converted to text by Iflyrec

software (Iflytek Co., Ltd, Hefei, Anhui) and then segmented into words based on the THU Lexical

Analyzer for Chinese (THULAC) toolbox (Sun et al., 2016).

Two semantic features, word entropy and word surprisal, were extracted. Word entropy measures the

uncertainty of predicting the upcoming word based on the context so far and was calculated as equation (1):

$$Entropy(t) = -\sum_{w_{t+1}} P(w_{t+1}|w_1, \dots, w_t) log P(w_{t+1}|w_1, \dots, w_t) \tag{1}$$

242 Word surprisal measures how surprising the current word is given the previously encountered words and

243 was calculated as equation (2):

$$Surprisal(t) = -log P(w_t|w_1, \dots, w_{t-1}) \tag{2}$$

Where $w_1, \dots, w_{t-1}$ are the existing word sequence and $P(w_t|w_1, \dots, w_{t-1})$ is the conditional probability of

next word (Willems et al., 2016). These NLP calculations were conducted by ADAM, a widely accepted

Long-Short Term Memory (LSTM) Neural Network model (Kingma & Ba, 2015). The model was trained

on the corpora corpus of the People's Daily with 534,246 Chinese words. See Supplementary Table S1 for

more information about the model.

After extracting the semantic features of each word, the word onset timings were estimated via Iflyrec

software. Impulses at the word onset time were manipulated with corresponding semantic feature values to

generate one-dimensional "semantic vectors" (Broderick et al., 2018; Gillis et al., 2021). The sampling rate

of the semantic vectors was 128 Hz to match the EEG signals.

Figure 2. Speech feature extraction and Temporal Response Function analysis. (A) Three types of speech

features were extracted, including one acoustic feature (amplitude envelope) and two semantic features

(word entropy and word surprisal). The two semantic features were derived from a computational linguistic

model and one-dimensional vectors were generated with impulses manipulated with semantic feature values

at the corresponding word onsets time. (B) Forward modeling. TRFs were extracted by regressing each of

the three types of speech features against the EEG signals separately. The significance of these TRFs was

estimated by comparing them with the corresponding null TRFs, which were modeled based on EEG signals

and shuffled speech features. The resulting spatiotemporal ranges were identified as regions of interest

(ROIs) and time of interest (TOIs). (C) Backward modeling. These three types of speech features were

separately reconstructed through backward TRF models and the reconstruction accuracy (Pearson's *r*)

depicted the strength of neural tracking. Null backward models were constructed with EEG signals and

shuffled features.

2.6 Modeling of the stimulus-response relationship

The Temporal Response Function (TRF) based modeling method was adopted to explore the

relationship between the neural activities and the three types of stimulus features (Crosse et al., 2016, 2021).

Forward modeling was first used to illustrate the specific spatial-temporal response patterns and identify

key electrodes and time windows in TRF responses of the corresponding speech feature, and then backward

modeling was adopted to verify the possible contribution of these identified neural correlates (Broderick et

al., 2019; Etard & Reichenbach, 2019). The overall procedure of the modeling analysis is shown in Figure

2B and 2C.

Forward modeling. With a forward modeling approach, we described neural response patterns to

different speech features by linear spatiotemporal filters called TRFs, which measure how the neural signals

from different regions are modulated by stimulus features at different time lags (Crosse et al., 2016). The

estimated TRF together with the corresponding speech feature was used to predict the EEG response from

each electrode. The prediction accuracy measured as Pearson's correlation between the actual and predicted

EEG signals represented the performance of the forward model. The TRF, *w*, can be expressed by equation

(3):

$$w = (S^T S + \lambda I)^{-1} S^T r \tag{3}$$

Where *S* is the lagged time series of the stimulus features and *I* is the identity matrix. The time lags

for forward modeling were chosen to cover a relatively broad time range, from -1000 to 1000 ms (Goldstein

et al., 2022; J. Li et al., 2021, 2022). The λ is the ridge parameter used to prevent overfitting and ranged

between 0.1 and 1000 in steps of the powers of 10 empirically (Gillis, Van Canneyt, et al., 2022). The cross-

validation procedure was implemented in a leave-one-trial-out procedure within each participant: each time,

the model was trained based on 9 trials and tested on the left-out trial, which was repeated for each of the

10 trials at three noise levels separately. The λ value that produced the highest prediction accuracy averaged

across trials after cross-validation was selected as the regularization parameter for all trials at a certain noise

level per participant. TRF amplitude was further transformed into *z*-scores before the statistical analysis (Di

Liberto et al., 2015; Ding et al., 2014; Gillis et al., 2021; J. Li et al., 2021).

The statistical significance of the estimated TRFs was estimated by constructing null TRF models

(Gillis et al., 2021; Weissbart et al., 2020). We built the chance-level null models by constructing TRF

models using shuffled stimulus features and the EEG recordings in the same way as for the computation of

the actual TRFs. The shuffled amplitude envelope was constructed by randomly shuffling the feature value

within a trial while keeping the timing of the quiet fragments. The shuffled word entropy and word surprisal

were constructed by randomly shuffling the feature value within a trial while keeping the timing of impulses.

Therefore the speech features that described acoustic and linguistic word onsets were not altered and thus

left no impact on TRFs' significance (Crosse et al., 2021; Weissbart et al., 2020). The shuffling was

repeated 1,000 times and resulted in 1,000 null TRFs for a corresponding actual TRF.

Two-tailed one-sample *t*-tests were used to examine whether the amplitude on an electrode-time bin

for the actual and null TRFs significantly differed from 0 (Gillis et al., 2021). We got the *p*-value of the

actual TRF amplitude on a certain electrode-time bin based on the actual *t*-value and the distribution of the

1,000 corresponding *t*-values from 1,000 null TRFs. The same procedure was conducted on each electrode-

time bin, and a cluster-based analysis was employed for the multi-comparison correction (Maris &

Oostenveld, 2007). In this procedure, neighboring channel-time bins with an uncorrected *p*-value below

0.01 were clustered together. Cluster-level statistics were calculated by summing the *t*-values in each cluster

separately. The corrected *p*-values for each cluster were calculated on the permutation distribution of the

maximum cluster-level statistic by the Monte Carlo method. We implemented the same statistical analysis

procedure for each of the 18 TRFs (3 stimulus features × 2 frequency bands × 3 noise levels). The EEG

electrodes and time windows from significant clusters were regarded as ROI/TOIs. Then peaks were

estimated within these ROI/TOIs, and peak amplitude and peak latency were compared across different

SNRs.

Backward modeling. With a backward modeling approach, we simultaneously took neural signals from

several electrodes to reconstruct stimulus features with a decoder. The reconstruction accuracy was

measured as Pearson's correlation between the actual and reconstructed stimulus features. The decoder, *g,*

can be expressed by equation (4), where R is the lagged time series of the EEG data. The reconstructed

feature, $\hat{s}(t)$, be calculated by equation (5) where n is the EEG electrodes, and τ is the time lags (Broderick

et al., 2019).

320
$$g = (R^T R + \lambda I)^{-1} R^T s \tag{4}$$

321
$$\hat{s}(t) = \sum_n \sum_\tau r_n(t + \tau) g_n(\tau) \tag{5}$$

The ROI/TOIs from significant clusters found in the forward modeling analysis participated in

backward modeling. EEG signals and stimulus features were down-sampled to 64 Hz for better

computational efficiency. The same regularization and cross-validation procedure as in the forward

modeling approach was conducted. We also estimated the null decoders using the same shuffling methods

in forward modeling. The reconstruction accuracy from the 1,000 null decoders was averaged and compared

with the actual decoder via a one-tailed paired t-test, and the p values for all clusters were corrected via the

false discovery rate (FDR) method (Benjamini & Hochberg, 1995).

In sum, the analysis of neural tracking followed two main steps. (1) We calculated the actual forward

model and null forward models and identified ROIs/TOIs according to clusters with significant differences

between them. (2) We estimated the reconstruction accuracy based on these ROIs/TOIs. This procedure

resulted in (1) the specific spatiotemporal TRF response pattern and (2) the strength of neural tracking

(reconstruction accuracy) for analysis. To avoid missing any results, significant clusters in acoustic- and

semantic-level TRF responses at each of the three noise levels were detected separately. We classified these

clusters into two types based on their spatiotemporal dynamics: those with largely overlapped

spatiotemporal patterns across all noise levels, which could represent a reliable response across all noise

levels, and those with unique patterns at a certain noise level, which may signify distinct processing

mechanisms under certain circumstances. The consistent clusters were compared to explore how the

commonly shared neural signature was affected by noise, while the unique clusters received less attention

in subsequent analysis. Spearman's correlation was conducted to examine the relationship between neural

tracking and behavioral performances.

Before modeling, the three types of stimulus features across all trials and EEG signals across all

channels were z-scored as recommended to ensure consistent scaling (Crosse et al., 2016, 2021). Modeling

and analysis for different stimulus features were conducted independently. Considering we focused on the

neural tracking of underlying hierarchical information in speech rather than physical stimulus, we adopted

the same stimulus features of no-noise speech for noise levels (Ding & Simon, 2013; Fuglsang et al., 2017).

The forward and backward modeling was conducted in MATLAB using the Multivariate Temporal

Response Function (mTRF) toolbox (Crosse et al., 2016). The cluster-based correction was conducted in

the FieldTrip toolbox (Oostenveld et al., 2011). Other statistical analysis was conducted via MATLAB

functions and JASP (JASP Team, 2022).

3 Results

3.1 Behavioral performance

The speech comprehension performance was measured as the averaged response accuracy of the four-choice questions and was found to be significantly different among the three noise levels (rmANOVA, $F_{(2, 36)} = 6.74$, $p = .003$). The speech comprehension performances were $95.26 \pm 1.05\%$, $90.79 \pm 2.10\%$, and $85.26 \pm 2.63\%$ (mean $\pm$ SE) at the no-noise level, low-noise level (3 dB), and high-noise level (-3 dB), respectively. The comprehension performance at the high-noise level was significantly lower than that at the no-noise level (post-hoc t-test, $p = .002$, Bonferroni corrected). In addition, it should be noted that the comprehension performance was still well above chance level even at the high-noise level (one-tailed t-test, $t(18) = 22.86$, $p < .001$).

The subjective ratings of clarity and intelligibility showed a similar pattern with significant differences among the noise levels (rmANOVA, $F_{(2, 36)} = 148.32$ and 35.31, ps $< .001$). The normalized clarity rating scores were 0.94 ± 0.01, 0.66 ± 0.04, and 0.35 ± 0.04 (mean $\pm$ SE), and the normalized intelligibility rating scores were 0.93 ± 0.01, 0.88 ± 0.02, and 0.73 ± 0.03 (mean $\pm$ SE) at the no-noise, low-noise and high-noise level, respectively. Post hoc t-tests revealed significant pairwise differences for all possible comparisons (ps $< .001$, Bonferroni corrected) except for the intelligibility ratings between the no-noise and low-noise levels. The behavioral performances are illustrated in Figure 3. These results suggested that the effect of noise on speech comprehension and perception was effectively manipulated.

Figure 3. Behavioral results. Black dots indicate data from each participant. Error bars denote the standard error. n.s. means not significant, † $p < .1$, * $p < .05$, ** $p < .01$, *** $p < .001$.

3.2 All significant clusters of acoustic- and semantic-level TRF responses

All significant clusters of acoustic- and semantic-level TRF responses are summarized in Figure 4 (see Supplementary Figure S1 for more information). Clusters with large overlapped spatiotemporal patterns across all noise levels were found in that-band acoustic-level TRFs (i.e., A1, A2, A3) and delta-band entropy-based semantic-level TRFs (i.e., E1, E2, E3). Detailed analyses of them are demonstrated in section 3.3 and 3.4, respectively.

Several clusters with similar spatiotemporal patterns shared by certain noise conditions, such as the acoustic-level TRF response within the occipital electrodes (i.e., A4 and A5) and post-onset entropy-based semantic-level TRF responses within the central electrodes (i.e., E5 and E6). Analyses of them are demonstrated in Supplementary Figure S2 and S3. No further analysis was done for the other unique clusters (i.e., E4, E7, E8) in the no-noise condition. No significant TRF responses to word surprisal were found.

Figure 4. Significant clusters in TRF responses to (A) amplitude envelope, (B) word entropy, and (C) word surprisal at different noise levels and frequency bands. They are numbered A1−A5 and E1−E8. Clusters

with similar spatiotemporal patterns are organized in the same row. ROIs of clusters are shown as black

dots in the corresponding topography. The colored curves are the mean of TRFs averaged among ROIs

across participants. The shaded areas denote the standard error of TRFs. The colored horizontal line below

the TRF curve indicates the TOIs of the cluster. n.s. means no significant cluster is found.

3.3 Acoustic-level TRF responses with delayed latencies as noise increases

Significant acoustic-level TRF responses in the theta band were found at all noise levels and showed

a similar positivity within central electrodes at around 300−500 ms, as demonstrated in Figure 5A. At the

no-noise level, the TRF showed positivity in central electrodes with a latency of around 400 ms (cluster-

level $p < .01$). At the low-noise and high-noise levels, the TRF showed similar positivity in central

electrodes with a latency of around 430 (cluster-level $p < .01$) and 440 ms (cluster-level $p < .01$). We

estimated the peak amplitude and peak latency for the positive peak from TRF averaged among the central

ROIs in three conditions. The peak latency was significantly different among the three noise levels

(rmANOVA, $F(2, 36) = 21.42$, $p < .001$), and post-hoc t-tests revealed significantly delayed peak latency

as the noise level increases ($ps < .05$, Bonferroni corrected), as shown in Figure 5C. No significant

differences were found in the peak amplitude (rmANOVA, $F(2, 36) = 0.64$, $p = .294$).

The reconstruction accuracy from the corresponding ROI/TOI was significantly higher in the actual decoder than in the null decoder (ps < .01, FDR corrected, Figure 5B). Comparing the reconstruction accuracy levels revealed significant differences among the three noise levels (rmANOVA, $F(2, 36) = 6.19$, $p = .010$ with Greenhouse-Geisser correction), and post-hoc t-tests revealed significantly weakened neural tracking in high-noise condition compared with the no-noise condition and low-noise condition ($p = .007$ and .029, Bonferroni corrected, Figure 5C).

Figure 5. Acoustic-level TRF responses on the theta band under different noise conditions. (A) The bold curves in different shades of red are the mean of TRFs averaged among ROIs across participants in the three noise levels. The grey curves are TRFs averaged among the ROIs of each participant. The colored horizontal line at the bottom of each plot indicates TOIs over which TRFs differed significantly from the null models. Dots in the corresponding topographies depicted the ROIs. (B) Reconstruction accuracy calculated from the ROI/TOI in (A). AM means actual models. NM means null models. (C) Noise effect

412   on peak amplitude, peak latency, and reconstruction accuracy. Grey dots indicate data from each participant.

413   Error bars denote the standard error. n.s. means not significant, † $p < .1$, * $p < .05$, ** $p < .01$, *** $p < .001$.

414   3.4 Semantic-level TRF responses with earlier latencies as noise increases

Significant semantic-level TRF responses to word entropy in the delta band were found at all noise

levels. They showed similar negativity at around 200–600 ms leading to speech fluctuation onset, as

demonstrated in Figure 6A. The time window of pre-onset processing to word entropy showed a gradual

advance trend as the increase of noise level. The time window was approximately from -300 ms to -180 ms

at the no-noise level (cluster-level $p < .05$) and was from around -400 ms to -250 ms at the low-noise level

(cluster-level $p < .05$), from -630 ms to -360 ms at the high-noise level (cluster-level $p < .01$). We estimated

the peak amplitude and peak latency for the pre-onset negative peak from TRF averaged among the central

ROIs. The peak latency was significantly different among the three noise levels (peak latency, rmANOVA,

$F(2, 36) = 58.08$, $p < .001$), and post-hoc t-tests revealed that as the noise level increased the peak latency

was gradually earlier (ps $< .05$, Bonferroni corrected), as shown in Figure 6C. No significant differences

were found in the peak amplitude (peak amplitude, rmANOVA, $F(2, 36) = 0.63$, $p = .538$).

The pre-onset TRF responses to word entropy exhibited different spatiotemporal patterns in three noise

conditions. At the no-noise level, the ROI included frontal-parietal electrodes and exhibited obvious left

lateralization. At the low-noise level, the ROI showed similar left-lateralized topological distribution but

included more electrodes, while in the high-noise condition no obvious lateralization was observed in the

frontal-parietal ROI.

The reconstruction accuracy from corresponding ROI/TOI was significantly higher in the actual

decoder than in the null decoder at both low-noise level (*p* < .05, FDR corrected) and high-noise level (*p*

< .001, FDR corrected) but only marginally significant at the no-noise level (*p* = .078, FDR corrected), as

shown in Figure 6B. Comparing the reconstruction accuracy among different noise levels revealed no

significant difference (rmANOVA, *F*(2, 36) = 1.64, *p* = .208, Figure 6C).

Figure 6. Semantic-level TRF responses to word entropy on the delta band under different noise conditions.

(A) The bold curves in different shades of green are the mean of TRFs averaged among ROIs across

participants in the three noise levels. The grey curves are TRFs averaged among the ROIs of each

participant. The colored horizontal line at the bottom of each plot indicates TOIs over which TRFs differed

significantly from the null models. Dots in the corresponding topographies depicted the ROIs. (B)

Reconstruction accuracy calculated from the ROI/TOI in (A). AM means actual models. NM means null

models. (C) Noise effect on peak amplitude, peak latency, and reconstruction accuracy. Grey dots indicate

data from each participant. Error bars denote the standard error. n.s. means not significant, † *p* < .1, * *p*

< .05, ** *p* < .01, *** *p* < .001.

3.5 Correlation between TRF responses and behavioral performances

As peak latency of both post-onset positive peak of acoustic-level TRF and pre-onset negative peak of

semantic-level TRFs show significant differences among SNR levels, we then conducted correlation

analysis to explore whether peak latency is a sensitive predictor of behavioral performance (i.e.,

comprehension accuracy, clarity rating, and intelligibility rating) during speech-in-noise. Before correlation

analysis, the corresponding peak latency and behavioral performances at the no-noise level were subtracted

as a baseline. Then spearman's correlation was conducted between behavioral performances and peak

latency. Results showed that at the high-noise level, the earlier the pre-onset peak of semantic-level TRF,

the higher the behavioral intelligibility score (Spearman's *r* = 0.62, uncorrected *p* = 0.004), as shown in

Figure 7. The relationship between reconstruction accuracy and behavioral performances was also

examined and summarized in Supplementary Table S1 and Table S2.

Figure 7. Correlation between behavioral intelligibility ratings and peak latency of (A) acoustic-level post-

onset TRF and (B) semantic-level pre-onset TRF. Both peak latency and behavioral intelligibility ratings

at the no-noise level were subtracted as a baseline before correlation analysis. Colored dots indicate data

from each participant. n.s. means not significant, † *p* < .1, * *p* < .05, ** *p* < .01, *** *p* < .001.

4 Discussion

The current study investigated the neural tracking of hierarchical features of naturalistic speech in noisy situations using a TRF-based technique. Significant post-onset acoustic-level TRF responses were found within central electrodes at around 400 ms, and the peak latency was delayed as noise increased. Significant pre-onset semantic-level TRF responses were found within frontal electrodes at around -600–-200 ms. The peak latency showed a gradually advanced trend as noise increased, and this advancement can predict increasement in intelligibility ratings. These findings indicated that noise affects acoustic and semantic processing differently and suggested that robust and adaptive semantic pre-activation could play a vital role in reliable speech comprehension in noisy environments.

The delayed acoustic-level TRF response' peak latency with increasing noise level was in line with several previous studies, suggesting an impaired efficiency in challenging conditions with background noise (Gillis, Decruy, et al., 2022; Mirkovic et al., 2019; Muncke et al., 2022; Yasmin et al., 2023; Zou et al., 2019). As the frontally and centrally distributed channels (corresponding to the primary auditory cortex, superior temporal gyrus, premotor cortex, etc.) have been frequently reported to be related to the processing of speech acoustics (Bidelman & Howell, 2016; Broderick et al., 2019; Hickok & Poeppel, 2007; Pérez et al., 2022; Zou et al., 2019), the present TRF results would imply similar recruitment of these brain regions for acoustic-level processing for naturalistic speech under various noise levels. However, the post-onset 400-ms latency was later compared to the commonly reported latency of < 300 ms in previous studies (Gillis, Decruy, et al., 2022; Yasmin et al., 2023). This discrepancy could be due to the causal filter used for EEG signal preprocessing in the present study, possibly resulting in a delayed TRF compared to previous studies using noncausal filters, similar as reported by Etard and Reichenbach (2019). Alternatively, it could be possible that the latency modulation started earlier but only reached significance later for the present dataset, as the observed TRF responses actually exhibited an oscillatory pattern starting much earlier than 400 ms (Figure 5C). While an impaired processing efficiency has been associated with both amplitude and latency modulation by noise in previous studies (Muncke et al., 2022; Zion Golumbic et al., 2013; Zou et al., 2019), the present study together with a series of other studies reporting latency-only results would suggest latency as a more sensitive candidate for noisy speech processing at the acoustic level (Ding & Simon, 2013; Kaplan-Neeman et al., 2006; Whiting et al., 1998).

More importantly, increasingly advanced pre-onset TRF responses to word entropy with increasing

noises suggest a distinct mechanism for speech-in-noise comprehension at the semantic level. While both

the pre-onset latency and the left-lateralization spatial pattern of the TRF responses to word entropy under

the no-noise condition were similar to recent studies on semantic prediction (Goldstein et al., 2022;

Weissbart et al., 2020; Willems et al., 2016), our results further extend the present understanding of the

predictive mechanism with the manipulation of the noise levels: significant pre-onset response appeared at

all noise levels. This finding would imply that semantic pre-activation showed robustness against noise.

Moreover, we found that the pre-onset latency became earlier with increasing noises, and the earlier peak

latency was associated with higher intelligibility ratings. One possible explanation for this phenomenon is

that our brain may adjust the timing of predictive processing in response to adverse environments. As

semantic prediction can facilitate speech comprehension (Mattys et al., 2012; Miller et al., 1951; Obleser

& Kotz, 2010; Pickering & Gambi, 2018; Zekveld et al., 2011), the brain relies on it more heavily as the

noise level increases to counteract distorted auditory input. Nevertheless, noise can increase the processing

load and decrease the processing efficiency (Gillis, Decruy, et al., 2022; Kaplan-Neeman et al., 2006; Kong

et al., 2014; Mirkovic et al., 2019). To compensate for the interference, the neural system initiates the pre-

onset response earlier and extends it for a longer duration, giving our brain more time for the preparation

of the upcoming speech information. These findings suggest that the brain has a temporally active

adaptation mechanism for reliable speech comprehension in noisy environments. As such a pre-onset

signature was not observed at the acoustic level, our results suggest the predictive mechanism might be

mainly focused at the semantic level (Goldstein et al., 2022; Grisoni et al., 2021), where the speech

information is expected to be more abstract and more robust against noises (Yasmin et al., 2023).

Interestingly, the spatial patterns of TRF responses to word entropy showed left-lateralization in the

no-and low-noise conditions and recruited bilateral hemispheres in the high-noise condition. The left-

lateralization has been reported in studies on speech-in-noise comprehension (Z. Li et al., 2021) and was

found to be sensitive to linguistic content (Peelle et al., 2013), word entropy (Willems et al., 2016), and

semantic expectancy (Golestani et al., 2013; Obleser & Kotz, 2010). Our results would support the left-

lateralized brain regions for predictive speech processing at the semantic level. Meanwhile, research has

reported that regions from the right hemisphere, such as the right inferior frontal gyrus, are sensitive to

semantic features such as entropy (Willems et al., 2016) and that the involvement of the right hemisphere

increased under degraded conditions (Bidelman & Howell, 2016), which was hypothesized as the possible

recruitment of additional regions for compensation (Shtyrov et al., 1998, 1999). Accordingly, our results

suggest that the involvement of bilateral hemispheric in adverse environments might reflect a semantic-

related compensation mechanism.

Our results regarding the TRF-based representation of speech acoustics and semantics in different

frequency bands provide further evidence for the frequency-specificity of speech processing. In this study,

acoustic-level TRF response was primarily associated with the theta band whereas semantic-level TRF

neural response was dominated by the delta band (Figure 4). These findings correspond to previous studies

indicating that theta-band neural tracking was related to acoustic processing and delta-band neural tracking

was associated with semantic and syntactic processing (Dai et al., 2022; Ding et al., 2014; Etard &

Reichenbach, 2019; J. Li et al., 2022; see a review, Kösem & van Wassenhove, 2017). Our study provides

straightforward evidence for this functional differentiation of frequency bands with an NLP-based semantic

quantification method. Additionally, the present study paid attention to the pre-onset stage of TRFs and

discovered that the semantic predictive responses also occurred on the delta band even in noisy conditions.

This finding further suggests that delta-band neural tracking is involved in predictive processes, which

echoes the previous finding that temporal predictions were encoded in the delta oscillations (Herbst &

Obleser, 2019; Stefanics et al., 2010), extending our comprehension of the functional role of delta-band

speech tracking.

Admittedly, the present study has some limitations to be noted. First, there were several significant

TRF responses to word entropy not included in the above analysis and discussions, which were primarily

observed in the no-noise condition. As the focus of the present study was speech-in-noise comprehension,

these responses were not further discussed. Nevertheless, they also reflected speech information processing

that would deserve investigations in future studies. Second, while the present study only adopted word

entropy and word surprisal as semantic-prediction-related features (Gillis et al., 2021; Goldstein et al., 2022;

Heilbron et al., 2022; Weissbart et al., 2020; Willems et al., 2016), rapid development in NLP methods

present us with a broader range of options (Caucheteux et al., 2023). Thus, future studies could employ

additional indexes to fully demonstrate the semantic-level adaptation mechanism. Third, despite the

advantage of the high temporal resolution of EEG in exploring temporal dynamics, the relatively poor

spatial resolution limits the ability to investigate brain regions involved in predictive mechanisms. A more

fine-grained analysis of the spatial-temporal dynamics of semantic prediction would require techniques

such as fMRI, ECoG, or multimodal approaches.

In summary, the current study investigated how noise affected acoustic and semantic processing during

naturalistic speech comprehension. With increasing noises, acoustic processing became increasingly

delayed whereas semantic processing became increasingly advanced. Our results suggest that, while the

efficiency of brain processing of speech information is indeed impaired by noise, the brain can compensate

for the associated effects through active prediction at the semantic level. Overall, the present findings are

expected to contribute to the growing research on the neural mechanisms of naturalistic speech

comprehension in noisy environments.

Funding

This work was supported by the National Natural Science Foundation of China (NSFC) and the German Research Foundation (DFG) in project Crossmodal Learning (NSFC 62061136001/DFG TRR-169/C1, B1), and the National Natural Science Foundation of China (61977041).

Author contributions

Xinmiao Zhang: Conceptualization, Methodology, Formal analysis, Investigation, Data curation, Writing – original draft, Writing – review & editing. **Jiawei Li**: Conceptualization, Methodology, Investigation, Writing – review & editing. **Zhuoran Li**: Conceptualization, Methodology, Investigation, Writing – review & editing. **Bo Hong**: Writing – review & editing, Funding acquisition. **Tongxiang Diao**: Writing – review & editing. **Xin Ma**: Writing – review & editing. **Guido Nolte**: Writing – review & editing, Funding acquisition. **Andreas K. Engel**: Writing – review & editing, Funding acquisition. **Dan Zhang**: Writing – review & editing, Funding acquisition, Supervision.

Declaration of competing interest

All the co-authors declare that they have no conflict of interest.

Data availability statement

Data in the current study are openly available in the Open Science Framework at https://osf.io/de9p6/, reference number DOI 10.17605/OSF.IO/DE9P6.

Acknowledgment

The authors would like to thank Prof. Xiaoqin Wang for providing the shielded room for the experiment. The authors would like to thank Prof. Zhiyuan Liu and members of his lab for computing the NLP models. The authors would like to thank Lingyi Tao and Xuelin Wang for their help with data collection.

References

Alday, P. M. (2019). M/EEG analysis of naturalistic stories: A review from speech to language processing. *Language, Cognition and Neuroscience*, *34*(4), 457–473. https://doi.org/10.1080/23273798.2018.1546882

Alexandrou, A. M., Saarinen, T., Kujala, J., & Salmelin, R. (2020). Cortical entrainment: What we can learn from studying naturalistic speech perception. *Language, Cognition and Neuroscience*, *35*(6), 681–693. https://doi.org/10.1080/23273798.2018.1518534

Aydelott, J., Dick, F., & Mills, D. L. (2006). Effects of acoustic distortion and semantic context on event-related potentials to spoken words. *Psychophysiology*, *43*(5), 454–464. https://doi.org/10.1111/j.1469-8986.2006.00448.x

Benjamini, Y., & Hochberg, Y. (1995). Controlling the False Discovery Rate: A Practical and Powerful Approach to Multiple Testing. *Journal of the Royal Statistical Society: Series B (Methodological)*, *57*(1), 289–300. https://doi.org/10.1111/j.2517-6161.1995.tb02031.x

Bidelman, G. M., & Howell, M. (2016). Functional changes in inter- and intra-hemispheric cortical processing underlying degraded speech perception. *NeuroImage*, *124*(Pt A), 581–590. https://doi.org/10.1016/j.neuroimage.2015.09.020

Billings, C. J., Bennett, K. O., Molis, M. R., & Leek, M. R. (2011). Cortical encoding of signals in noise: Effects of stimulus type and recording paradigm. *Ear and Hearing*, *32*(1), 53–60. https://doi.org/10.1097/AUD.0b013e3181ec5c46

Billings, C. J., Tremblay, K. L., Stecker, G. C., & Tolin, W. M. (2009). Human evoked cortical activity to signal-to-noise ratio and absolute signal level. *Hearing Research*, *254*(1), 15–24. https://doi.org/10.1016/j.heares.2009.04.002

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*(4), 433–436.

Brodbeck, C., Bhattasali, S., Cruz Heredia, A. A., Resnik, P., Simon, J. Z., & Lau, E. (2022). Parallel processing in speech perception with local and global representations of linguistic context. *ELife*, *11*, e72056. https://doi.org/10.7554/eLife.72056

Brodbeck, C., & Simon, J. Z. (2020). Continuous speech processing. *Current Opinion in Physiology*, *18*, 25–31. https://doi.org/10.1016/j.cophys.2020.07.014

Broderick, M. P., Anderson, A. J., Di Liberto, G. M., Crosse, M. J., & Lalor, E. C. (2018). Electrophysiological Correlates of Semantic Dissimilarity Reflect the Comprehension of Natural, Narrative Speech. *Current Biology*, *28*(5), 803-809.e3. https://doi.org/10.1016/j.cub.2018.01.080

Broderick, M. P., Anderson, A. J., & Lalor, E. C. (2019). Semantic Context Enhances the Early Auditory Encoding of Natural Speech. *Journal of Neuroscience*, *39*(38), 7564–7575. https://doi.org/10.1523/JNEUROSCI.0584-19.2019

Broderick, M. P., Di Liberto, G. M., Anderson, A. J., Rofes, A., & Lalor, E. C. (2021). Dissociable electrophysiological measures of natural language processing reveal differences in speech

comprehension strategy in healthy ageing. *Scientific Reports*, *11*(1), 4963. https://doi.org/10.1038/s41598-021-84597-9

Caucheteux, C., Gramfort, A., & King, J.-R. (2023). Evidence of a predictive coding hierarchy in the human brain listening to speech. *Nature Human Behaviour*, 1–12. https://doi.org/10.1038/s41562-022-01516-2

Connolly, J. F., Phillips, N. A., Stewart, S. H., & Brake, W. G. (1992). Event-related potential sensitivity to acoustic and semantic properties of terminal words in sentences. *Brain and Language*, *43*(1), 1–18. https://doi.org/10.1016/0093-934X(92)90018-A

Crosse, M. J., Di Liberto, G. M., Bednar, A., & Lalor, E. C. (2016). The Multivariate Temporal Response Function (mTRF) Toolbox: A MATLAB Toolbox for Relating Neural Signals to Continuous Stimuli. *Frontiers in Human Neuroscience*, *10*. https://doi.org/10.3389/fnhum.2016.00604

Crosse, M. J., Zuk, N. J., Di Liberto, G. M., Nidiffer, A. R., Molholm, S., & Lalor, E. C. (2021). Linear Modeling of Neurophysiological Responses to Speech and Other Continuous Stimuli: Methodological Considerations for Applied Research. *Frontiers in Neuroscience*, *15*, 1350. https://doi.org/10.3389/fnins.2021.705621

Dai, B., McQueen, J. M., Terporten, R., Hagoort, P., & Kösem, A. (2022). Distracting Linguistic Information Impairs Neural Tracking of Attended Speech. *Current Research in Neurobiology*, 100043. https://doi.org/10.1016/j.crneur.2022.100043

Daltrozzo, J., Wioland, N., & Kotchoubey, B. (2012). The N400 and Late Positive Complex (LPC) Effects Reflect Controlled Rather than Automatic Mechanisms of Sentence Processing. *Brain Sciences*, *2*(3), Article 3. https://doi.org/10.3390/brainsci2030267

de Cheveigné, A., & Nelken, I. (2019). Filters: When, Why, and How (Not) to Use Them. *Neuron*, *102*(2), 280–293. https://doi.org/10.1016/j.neuron.2019.02.039

Di Liberto, G. M., O'Sullivan, J. A., & Lalor, E. C. (2015). Low-frequency cortical entrainment to speech reflects phoneme-level processing. *Current Biology*, *25*(19), 2457–2465. https://doi.org/10.1016/j.cub.2015.08.030

Ding, N., Chatterjee, M., & Simon, J. Z. (2014). Robust cortical entrainment to the speech envelope relies on the spectro-temporal fine structure. *NeuroImage*, *88*, 41–46. https://doi.org/10.1016/j.neuroimage.2013.10.054

Ding, N., & Simon, J. Z. (2013). Adaptive temporal encoding leads to a background-insensitive cortical representation of speech. *Journal of Neuroscience*, *33*(13), 5728–5735. https://doi.org/10.1523/JNEUROSCI.5297-12.2013

Ding, N., & Simon, J. Z. (2014). Cortical entrainment to continuous speech: Functional roles and interpretations. *Frontiers in Human Neuroscience*, *8*, 311. https://doi.org/10.3389/fnhum.2014.00311

Donhauser, P. W., & Baillet, S. (2020). Two distinct neural timescales for predictive speech processing. *Neuron*, *105*(2), 385–393. https://doi.org/10.1016/j.neuron.2019.10.019

Etard, O., & Reichenbach, T. (2019). Neural Speech Tracking in the Theta and in the Delta Frequency Band
Differentially Encode Clarity and Comprehension of Speech in Noise. *Journal of Neuroscience*,
39(29), 5750–5759. https://doi.org/10.1523/JNEUROSCI.1828-18.2019

Fiedler, L., Wöstmann, M., Herbst, S. K., & Obleser, J. (2019). Late cortical tracking of ignored speech
facilitates neural selectivity in acoustically challenging conditions. *NeuroImage*, *186*, 33–42.
https://doi.org/10.1016/j.neuroimage.2018.10.057

Fuglsang, S. A., Dau, T., & Hjortkjær, J. (2017). Noise-robust cortical tracking of attended speech in real-
world acoustic scenes. *NeuroImage*, *156*, 435–444. https://doi.org/10.1016/j.neuroimage.2017.04.026

Gillis, M., Decruy, L., Vanthornhout, J., & Francart, T. (2022). Hearing loss is associated with delayed
neural responses to continuous speech. *European Journal of Neuroscience*, *55*(6), 1671–1690.
https://doi.org/10.1111/ejn.15644

Gillis, M., Van Canneyt, J., Francart, T., & Vanthornhout, J. (2022). Neural tracking as a diagnostic tool to
assess the auditory pathway. *Hearing Research*, 108607.
https://doi.org/10.1016/j.heares.2022.108607

Gillis, M., Vanthornhout, J., Simon, J. Z., Tom Francart, & Brodbeck, C. (2021). Neural markers of speech
comprehension: Measuring EEG tracking of linguistic speech representations, controlling the speech
acoustics. *Journal of Neuroscience*. https://doi.org/10.1523/JNEUROSCI.0812-21.2021

Giraud, A.-L., & Poeppel, D. (2012). Cortical oscillations and speech processing: Emerging computational
principles and operations. *Nature Neuroscience*, *15*(4), 511–517. https://doi.org/10.1038/nn.3063

Goldstein, A., Zada, Z., Buchnik, E., Schain, M., Price, A., Aubrey, B., Nastase, S. A., Feder, A., Emanuel,
D., Cohen, A., Jansen, A., Gazula, H., Choe, G., Rao, A., Kim, C., Casto, C., Fanda, L., Doyle, W.,
Friedman, D., … Hasson, U. (2022). Shared computational principles for language processing in
humans and deep language models. *Nature Neuroscience*, *25*(3), 369–380.
https://doi.org/10.1038/s41593-022-01026-4

Golestani, N., Hervais-Adelman, A., Obleser, J., & Scott, S. K. (2013). Semantic versus perceptual
interactions in neural processing of speech-in-noise. *NeuroImage*, *79*, 52–61.
https://doi.org/10.1016/j.neuroimage.2013.04.049

Grisoni, L., Miller, T. M., & Pulvermüller, F. (2017). Neural Correlates of Semantic Prediction and
Resolution in Sentence Processing. *Journal of Neuroscience*, *37*(18), 4848–4858.
https://doi.org/10.1523/JNEUROSCI.2800-16.2017

Grisoni, L., Tomasello, R., & Pulvermüller, F. (2021). Correlated Brain Indexes of Semantic Prediction
and Prediction Error: Brain Localization and Category Specificity. *Cerebral Cortex*, *31*(3), 1553–1568.
https://doi.org/10.1093/cercor/bhaa308

Hamilton, L. S., & Huth, A. G. (2020). The revolution will not be controlled: Natural stimuli in speech
neuroscience. *Language, Cognition and Neuroscience*, *35*(5), 573–582.
https://doi.org/10.1080/23273798.2018.1499946

Hartley, C. A., & Poeppel, D. (2020). Beyond the Stimulus: A Neurohumanities Approach to Language,
Music, and Emotion. *Neuron*, *108*(4), 597–599. https://doi.org/10.1016/j.neuron.2020.10.021

Heilbron, M., Armeni, K., Schoffelen, J.-M., Hagoort, P., & de Lange, F. P. (2022). A hierarchy of linguistic
predictions during natural language comprehension. *Proceedings of the National Academy of Sciences*
of the United States of America, *119*(32), e2201968119. https://doi.org/10.1073/pnas.2201968119

Herbst, S. K., & Obleser, J. (2019). Implicit temporal predictability enhances pitch discrimination
sensitivity and biases the phase of delta oscillations in auditory cortex. *NeuroImage*, *203*, 116198.
https://doi.org/10.1016/j.neuroimage.2019.116198

Hickok, G., & Poeppel, D. (2007). The cortical organization of speech processing. *Nature Reviews*
Neuroscience, *8*(5), 393–402. https://doi.org/10.1038/nrn2113

Jamison, C., Aiken, S. J., Kiefte, M., Newman, A. J., Bance, M., & Sculthorpe, -Petley Lauren. (2016).
Preliminary Investigation of the Passively Evoked N400 as a Tool for Estimating Speech-in-Noise
Thresholds. *American Journal of Audiology*, *25*(4), 344–358. https://doi.org/10.1044/2016_AJA-15-
0080

JASP Team. (2022). *JASP (version 0.16.3)[Computer software]*. https://jasp-stats.org/

Kaplan-Neeman, R., Kishon-Rabin, L., Henkin, Y., & Muchnik, C. (2006). Identification of syllables in
noise: Electrophysiological and behavioral correlates. *The Journal of the Acoustical Society of*
America, *120*(2), 926–933. https://doi.org/10.1121/1.2217567

Keitel, A., Ince, R. A., Gross, J., & Kayser, C. (2017). Auditory cortical delta-entrainment interacts with
oscillatory power in multiple fronto-parietal networks. *Neuroimage*, *147*, 32–42.
https://doi.org/10.1016/j.neuroimage.2016.11.062

Kingma, D., & Ba, J. (2015). Adam: A method for stochastic optimization3rd international conference on
learning representations, ICLR 2015. *International Conference on Learning Representations, ICLR*.

Koerner, T. K., Zhang, Y., Nelson, P. B., Wang, B., & Zou, H. (2017). Neural indices of phonemic
discrimination and sentence-level speech intelligibility in quiet and noise: A P3 study. *Hearing*
Research, *350*, 58–67. https://doi.org/10.1016/j.heares.2017.04.009

Kong, Y.-Y., Mullangi, A., & Ding, N. (2014). Differential modulation of auditory responses to attended
and unattended speech in different listening conditions. *Hearing Research*, *316*, 73–81.
https://doi.org/10.1016/j.heares.2014.07.009

Kösem, A., & van Wassenhove, V. (2017). Distinct contributions of low- and high-frequency neural
oscillations to speech comprehension. *Language, Cognition and Neuroscience*, *32*(5), 536–544.
https://doi.org/10.1080/23273798.2016.1238495

Koskinen, M., Kurimo, M., Gross, J., Hyvärinen, A., & Hari, R. (2020). Brain activity reflects the
predictability of word sequences in listened continuous speech. *NeuroImage*, *219*, 116936.
https://doi.org/10.1016/j.neuroimage.2020.116936

Kutas, M., & Federmeier, K. D. (2011). Thirty Years and Counting: Finding Meaning in the N400
Component of the Event-Related Brain Potential (ERP). *Annual Review of Psychology*, *62*(1), 621–
647. https://doi.org/10.1146/annurev.psych.093008.131123

Kutas, M., & Hillyard, S. A. (1984). Brain potentials during reading reflect word expectancy and semantic
association. *Nature*, *307*(5947), 161–163. https://doi.org/10.1038/307161a0

Lakatos, P., Gross, J., & Thut, G. (2019). A New Unifying Account of the Roles of Neuronal Entrainment.
Current Biology, *29*(18), R890–R905. https://doi.org/10.1016/j.cub.2019.07.075

Li, J., Hong, B., Nolte, G., Engel, A. K., & Zhang, D. (2021). Preparatory delta phase response is correlated
with naturalistic speech comprehension performance. *Cognitive Neurodynamics*.
https://doi.org/10.1007/s11571-021-09711-z

Li, J., Hong, B., Nolte, G., Engel, A. K., & Zhang, D. (2022). *An integrative view on attentional modulation*
in naturalistic speech (p. 2022.10.02.510499). bioRxiv. https://doi.org/10.1101/2022.10.02.510499

Li, Z., Hong, B., Wang, D., Nolte, G., Engel, A. K., & Zhang, D. (2022). Speaker–listener neural coupling
reveals a right-lateralized mechanism for non-native speech-in-noise comprehension. *Cerebral Cortex*,
bhac302. https://doi.org/10.1093/cercor/bhac302

Li, Z., Li, J., Hong, B., Nolte, G., Engel, A. K., & Zhang, D. (2021). Speaker–Listener Neural Coupling
Reveals an Adaptive Mechanism for Speech Comprehension in a Noisy Environment. *Cerebral Cortex*,
bhab118. https://doi.org/10.1093/cercor/bhab118

Li, Z., & Zhang, D. (2023). How does the human brain process noisy speech in real life? Insights from the
second-person neuroscience perspective. *Cognitive Neurodynamics*. https://doi.org/10.1007/s11571-
022-09924-w

Lu, Y., Jin, P., Pan, X., & Ding, N. (2022). Delta-band neural activity primarily tracks sentences instead of
semantic properties of words. *NeuroImage*, 118979.
https://doi.org/10.1016/j.neuroimage.2022.118979

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-data. *Journal of*
Neuroscience Methods, *164*(1), 177–190. https://doi.org/10.1016/j.jneumeth.2007.03.024

Martin, B. A., & Stapells, D. R. (2005). Effects of low-pass noise masking on auditory event-related
potentials to speech. *Ear and Hearing*, *26*(2), 195–213. https://doi.org/10.1097/00003446-200504000-
00007

Mattys, S. L., Davis, M. H., Bradlow, A. R., & Scott, S. K. (2012). Speech recognition in adverse conditions:
A review. *Language and Cognitive Processes*, *27*(7–8), 953–978.
https://doi.org/10.1080/01690965.2012.705006

Mesik, J., Ray, L., & Wojtczak, M. (2021). Effects of Age on Cortical Tracking of Word-Level Features of
Continuous Competing Speech. *Frontiers in Neuroscience*, *15*.
https://doi.org/10.3389/fnins.2021.635126

Miller, G. A., Heise, G. A., & Lichten, W. (1951). The intelligibility of speech as a function of the context
of the test materials. *Journal of Experimental Psychology*, *41*(5), 329.

Mirkovic, B., Debener, S., Schmidt, J., Jaeger, M., & Neher, T. (2019). Effects of directional sound
processing and listener's motivation on EEG responses to continuous noisy speech: Do normal-
hearing and aided hearing-impaired listeners differ? *Hearing Research*, *377*, 260–270.
https://doi.org/10.1016/j.heares.2019.04.005

Muncke, J., Kuruvila, I., & Hoppe, U. (2022). Prediction of Speech Intelligibility by Means of EEG
Responses to Sentences in Noise. *Frontiers in Neuroscience*, *16*.
https://doi.org/10.3389/fnins.2022.876421

Obleser, J., & Kayser, C. (2019). Neural entrainment and attentional selection in the listening brain. *Trends
in Cognitive Sciences*, *23*(11), 913–926. https://doi.org/10.1016/j.tics.2019.08.004

Obleser, J., & Kotz, S. A. (2010). Expectancy Constraints in Degraded Speech Modulate the Language
Comprehension Network. *Cerebral Cortex*, *20*(3), 633–640. https://doi.org/10.1093/cercor/bhp128

Obleser, J., & Kotz, S. A. (2011). Multiple brain signatures of integration in the comprehension of degraded
speech. *NeuroImage*, *55*(2), 713–723. https://doi.org/10.1016/j.neuroimage.2010.12.020

Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J.-M. (2011). FieldTrip: Open Source Software for
Advanced Analysis of MEG, EEG, and Invasive Electrophysiological Data. *Computational
Intelligence and Neuroscience*, *2011*, 1–9. https://doi.org/10.1155/2011/156869

O'Sullivan, Power, A. J., Mesgarani, N., Rajaram, S., Foxe, J. J., Shinn-Cunningham, B. G., Slaney, M.,
Shamma, S. A., & Lalor, E. C. (2015). Attentional selection in a cocktail party environment can be
decoded from single-trial EEG. *Cerebral Cortex*, *25*(7), 1697–1706.

Peelle, J. E., Gross, J., & Davis, M. H. (2013). Phase-Locked Responses to Speech in Human Auditory
Cortex are Enhanced During Comprehension. *Cerebral Cortex*, *23*(6), 1378–1387.
https://doi.org/10.1093/cercor/bhs118

Pérez, A., Davis, M. H., Ince, R. A. A., Zhang, H., Fu, Z., Lamarca, M., Lambon Ralph, M. A., & Monahan,
P. J. (2022). Timing of brain entrainment to the speech envelope during speaking, listening and self-
listening. *Cognition*, *224*, 105051. https://doi.org/10.1016/j.cognition.2022.105051

Pickering, M. J., & Gambi, C. (2018). Predicting while comprehending language: A theory and review.
Psychological Bulletin, *144*(10), 1002–1044. https://doi.org/10.1037/bul0000158

Pulvermüller, F., & Grisoni, L. (2020). Semantic Prediction in Brain and Mind. *Trends in Cognitive
Sciences*, *24*(10), 781–784. https://doi.org/10.1016/j.tics.2020.07.002

Romei, L., Wambacq, I. J. A., Besing, J., Koehnke, J., & Jerger, J. (2011). Neural indices of spoken word
processing in background multi-talker babble. *International Journal of Audiology*, *50*(5), 321–333.
https://doi.org/10.3109/14992027.2010.547875

Shtyrov, Y., Kujala, T., Ahveninen, J., Tervaniemi, M., Alku, P., Ilmoniemi, R. J., & Näätänen, R. (1998).
Background acoustic noise and the hemispheric lateralization of speech processing in the human brain:
Magnetic mismatch negativity study. *Neuroscience Letters*, *251*(2), 141–144.
https://doi.org/10.1016/S0304-3940(98)00529-1

Shtyrov, Y., Kujala, T., Ilmoniemi, R. J., & Näätänen, R. (1999). Noise affects speech-signal processing
differently in the cerebral hemispheres. *NeuroReport*, *10*(10), 2189–2192. Scopus.
https://doi.org/10.1097/00001756-199907130-00034

Sohoglu, E., Peelle, J. E., Carlyon, R. P., & Davis, M. H. (2012). Predictive Top-Down Integration of Prior
Knowledge during Speech Perception. *Journal of Neuroscience*, *32*(25), 8443–8453.
https://doi.org/10.1523/JNEUROSCI.5069-11.2012

Sonkusare, S., Breakspear, M., & Guo, C. (2019). Naturalistic Stimuli in Neuroscience: Critically
Acclaimed. *Trends in Cognitive Sciences*, *23*(8), 699–714. https://doi.org/10.1016/j.tics.2019.05.004

Stefanics, G., Hangya, B., Hernádi, I., Winkler, I., Lakatos, P., & Ulbert, I. (2010). Phase Entrainment of
Human Delta Oscillations Can Mediate the Effects of Expectation on Reaction Speed. *Journal of
Neuroscience*, *30*(41), 13578–13585. https://doi.org/10.1523/JNEUROSCI.0703-10.2010

Strauß, A., Kotz, S. A., & Obleser, J. (2013). Narrowed Expectancies under Degraded Speech: Revisiting
the N400. *Journal of Cognitive Neuroscience*, *25*(8), 1383–1395.
https://doi.org/10.1162/jocn_a_00389

Sun, M., Chen, X., Zhang, K., Guo, Z., & Liu, Z. (2016). *THULAC: An Efficient Lexical Analyzer for
Chinese*.

Tomé, D., Barbosa, F., Nowak, K., & Marques-Teixeira, J. (2015). The development of the N1 and N2
components in auditory oddball paradigms: A systematic review with narrative analysis and suggested
normative values. *Journal of Neural Transmission*, *122*(3), 375–391. https://doi.org/10.1007/s00702-
014-1258-3

Weissbart, H., Kandylaki, K. D., & Reichenbach, T. (2020). Cortical Tracking of Surprisal during
Continuous Speech Comprehension. *Journal of Cognitive Neuroscience*, *32*(1), 155–166.
https://doi.org/10.1162/jocn_a_01467

Whiting, K. A., Martin, B. A., & Stapells, D. R. (1998). The Effects of Broadband Noise Masking on
Cortical Event-Related Potentials to Speech Sounds /ba/ and /da/. *Ear and Hearing*, *19*(3), 218–231.
https://journals.lww.com/ear-
hearing/Abstract/1998/06000/The_Effects_of_Broadband_Noise_Masking_on_Cortical.5.aspx

Willems, R. M., Frank, S. L., Nijhof, A. D., Hagoort, P., & van den Bosch, A. (2016). Prediction During
Natural Language Comprehension. *Cerebral Cortex*, *26*(6), 2506–2516.
https://doi.org/10.1093/cercor/bhv075

Willems, R. M., Nastase, S. A., & Milivojevic, B. (2020). Narratives for Neuroscience. *Trends in
Neurosciences*, *43*(5), 271–273. https://doi.org/10.1016/j.tins.2020.03.003

Wöstmann, M., Fiedler, L., & Obleser, J. (2017). Tracking the signal, cracking the code: Speech and speech
comprehension in non-invasive human electrophysiology. *Language, Cognition and Neuroscience*,
32(7), 855–869. https://doi.org/10.1080/23273798.2016.1262051

Yasmin, S., Irsik, V. C., Johnsrude, I. S., & Herrmann, B. (2023). *The Effects of Speech Masking on Neural*
Tracking of Acoustic and Semantic Features of Natural Speech (p. 2023.02.10.527537). bioRxiv.
https://doi.org/10.1101/2023.02.10.527537

Zekveld, A. A., Rudner, M., Johnsrude, I. S., Festen, J. M., van Beek, J. H. M., & Rönnberg, J. (2011). The
Influence of Semantically Related and Unrelated Text Cues on the Intelligibility of Sentences in Noise.
Ear and Hearing, *32*(6), e16. https://doi.org/10.1097/AUD.0b013e318228036a

Zendel, B. R., Tremblay, C.-D., Belleville, S., & Peretz, I. (2015). The Impact of Musicianship on the
Cortical Mechanisms Related to Separating Speech from Background Noise. *Journal of Cognitive*
Neuroscience, *27*(5), 1044–1059. https://doi.org/10.1162/jocn_a_00758

Zion Golumbic, E. M., Ding, N., Bickel, S., Lakatos, P., Schevon, C. A., McKhann, G. M., Goodman, R.
R., Emerson, R., Mehta, A. D., & Simon, J. Z. (2013). Mechanisms underlying selective neuronal
tracking of attended speech at a "cocktail party." *Neuron*, *77*(5), 980–991.
http://dx.doi.org/10.1016/j.neuron.2012.12.037

Zou, J., Feng, J., Xu, T., Jin, P., Luo, C., Zhang, J., Pan, X., Chen, F., Zheng, J., & Ding, N. (2019). Auditory
and language contributions to neural encoding of speech features in noisy environments. *NeuroImage*,
192, 66–75. https://doi.org/10.1016/j.neuroimage.2019.02.047

848
849

850 **5 Supplementary materials**

851 **Figure S1.** Clusters in TRF responses for different speech features, noise levels, and frequency bands. The
852 grey histograms show the distribution of the cluster-level *t*-statistics from 1000 permutations. The colored
853 lines indicate significant clusters and the black lines indicate nonsignificant clusters. n.c. means no cluster
854 is formed. * *p* < .05, ** *p* < .01, *** *p* < .001.

Figure S2. Cluster A4 and A5 of acoustic-level TRF response on the theta-band. (A) The bold curves in different shades of red are the mean of TRFs averaged among ROIs across participants at the low- and high-noise levels. The grey curves are TRFs averaged among the ROIs of each participant. The colored horizontal line at the bottom of each plot indicates TOIs over which TRFs differed significantly from the null models. Dots in the corresponding topographies depicted the ROIs. (B) Reconstruction accuracy calculated from the ROI/TOI in (A). AM means actual models. NM means null models. (C) Noise effect on peak amplitude, peak latency, and reconstruction accuracy. Peak latency was significantly longer at the high-noise level than that at the low-noise level (paired-samples *t*-test, *t*(18) = 4.72, *p* < .001). Reconstruction accuracy was significantly lower at the high-noise level than that at the low-noise level (paired-samples *t*-test, *t*(18) = 2.54, *p* < .05). No significant difference was found in peak amplitude (paired-samples *t*-test, *t*(18) = 0.60, *p* = .558). Grey dots indicate data from each participant. Error bar denotes the standard error. n.s. means not significant, † *p* < .1, * *p* < .05, ** *p* < .01, *** *p* < .001.

Figure S3. Cluster E5 and E6 of semantic-level TRF responses to word entropy on the delta-band. (A) The

bold curves in different shades of green are the mean of TRFs averaged among ROIs across participants at

the no- and low-noise levels. The grey curves are TRFs averaged among the ROIs of each participant. The

colored horizontal line at the bottom of each plot indicates TOIs over which TRFs differed significantly

from the null models. Dots in the corresponding topographies depicted the ROIs. (B) Reconstruction

accuracy calculated from the ROI/TOI (A), AM means actual models. NM means null models. (C) Noise

effect on peak amplitude, peak latency, and reconstruction accuracy. No significant difference was found

in peak amplitude (paired-samples t-test, $t(18) = 0.02$, $p = .981$), peak latency (paired-samples t-test, $t(18)$

$= -0.21$, $p = .834$), and reconstruction accuracy (paired-samples t-test, $t(18) = 0.95$, $p = .357$). Grey dots

indicate data from each participant. Error bar denotes the standard error. n.s. means not significant, † $p < .1$,

* $p < .05$, ** $p < .01$, *** $p < .001$.

Table S1. Details of the Natural Language Processing model used to extract semantic features.

Type	Parameter
Model type	Long-Short Term Memory (LSTM)
Embedding size	200
Hidden units per layer	200
Number of layers	2
Initial learning rate	3
Gradient clipping	0.25
Sequence length	35
Drop out	0.2
Epoch	50
batch size	3

880 **Table S2.** Spearman's correlation between reconstruction accuracy from each ROI/TOI in acoustic-level

881 TRF responses and behavioral performance. Significant correlation results are bolded (uncorrected).

	Clarity Ratings	Intelligibility Ratings	Comprehension Performance
A1	$r = -.11$	$r = .10$	$r = .11$
	$p = .662$	$p = .694$	$p = .647$
A2a	$r = -.46$	$r = -.04$	$r = .05$
	$p = .047$	$p = .858$	$p = .831$
A2b	$r = -.50$	$r = .02$	$r = .25$
	$p = .032$	$p = .926$	$p = .309$
A3a	$r = -.52$	$r = .05$	$r = .09$
	$p = .025$	$p = .854$	$p = .702$
A3b	$r = -.51$	$r = -.06$	$r = -.002$
	$p = .028$	$p = .798$	$p = .994$
A4a	$r = -.47$	$r = -.08$	$r = .08$
	$p = .043$	$p = .734$	$p = .757$
A4b	$r = -.42$	$r = .004$	$r = .18$
	$p = .071$	$p = .986$	$p = .465$
A5a	$r = -.46$	$r = .002$	$r = .03$
	$p = .048$	$p = .997$	$p = .918$
A5b	$r = -.52$	$r = .15$	$r = .22$
	$p = .026$	$p = .541$	$p = .361$

883 **Table S3.** Spearman's correlation between reconstruction accuracy from each cluster in semantic-level
884 TRF responses and behavioral performance. Significant correlation results are bolded (uncorrected).

	Clarity Ratings	Intelligibility Ratings	Comprehension Performance
E1	$r = -.21$ $p = .394$	$r = .14$ $p = .560$	$r = -.09$ $p = .714$
E2	$r = .23$ $p = .339$	$r = -.07$ $p = .762$	$r = .11$ $p = .668$
E3	$r = -.30$ $p = .206$	$r = -.31$ $p = .203$	$r = -.01$ $p = .997$
E4	$r = -.24$ $p = .332$	$r = .09$ $p = .721$	$r = -.02$ $p = .928$
E5	$r = .15$ $p = .527$	$r = .37$ $p = .121$	**$r = .51$** **$p = .027$**
E6	$r = -.22$ $p = .365$	$r = -.30$ $p = .215$	$r = .13$ $p = .594$
E7	$r = .04$ $p = .881$	$r = .15$ $p = .551$	$r = .20$ $p = .404$
E8	$r = -.28$ $p = .237$	$r = -.14$ $p = .575$	$r = .20$ $p = .411$