1 Full Title:

Domain-adaptive neural networks improve supervised machine learning based on simulated population genetic data

4 Short Title:

Domain adaptation for supervised population genetic inference

Ziyi Mo[1,2], Adam Siepel[1,2,*]

7 [1]Simons Center for Quantitative Biology, Cold Spring Harbor Laboratory, Cold Spring
8 Harbor, NY
9 [2]School of Biological Sciences, Cold Spring Harbor Laboratory, Cold Spring Harbor, NY

10 *Corresponding author: Adam Siepel (asiepel@cshl.edu)

Abstract

Investigators have recently introduced powerful methods for population genetic inference that rely on supervised machine learning from simulated data. Despite their performance advantages, these methods can fail when the simulated training data does not adequately resemble data from the real world. Here, we show that this "simulation mis-specification" problem can be framed as a "domain adaptation" problem, where a model learned from one data distribution is applied to a dataset drawn from a different distribution. By applying an established domain-adaptation technique based on a gradient reversal layer (GRL), originally introduced for image classification, we show that the effects of simulation mis-specification can be substantially mitigated. We focus our analysis on two state-of-the-art deep-learning population genetic methods—SIA, which infers positive selection from features of the ancestral recombination graph (ARG), and ReLERNN, which infers recombination rates from genotype matrices. In the case of SIA, the domain adaptive framework also compensates for ARG inference error. Using the **d**omain-**ada**ptive SIA (dadaSIA) model, we estimate improved selection coefficients at selected loci in the 1000 Genomes CEU population. We anticipate that domain adaptation will prove to be widely applicable in the growing use of supervised machine learning in population genetics.

Author Summary

Population genetic simulation is a powerful tool in the study of evolution. A number of supervised machine learning methods have been developed that take advantage of inexpensive simulations as training data. Despite their outstanding performance in benchmarks, these models can fail when the simulated training data deviate from the real data. In this work, we employed domain adaptation techniques to address this "simulation mis-specification" problem by training the machine learning model jointly with simulated and real data. We performed extensive benchmark experiments to demonstrate the improvement of the domain-adaptive models over standard machine learning models in the presence of different types of mis-specification. In addition, we applied *dadaSIA*, a domain-adaptive selection inference model, to improve the estimates of selection coefficients at selected loci in a European population. The domain adaptation framework proposed in our work is widely applicable to models relying on synthetic training data and therefore opens the door to many more applications in population genetics.

Introduction

Advances in genome sequencing have allowed population genetic analyses to be applied to many thousands of individual genome sequences [1–3]. Given adequately rigorous and scalable computational tools for analysis, these rich catalogs of genetic variation provide opportunities for addressing many important questions in areas such as human evolution, plant genetics, and the ecology of non-model organisms. Deep-learning methods, already well-established in other application areas [4], have proven to be good matches for these analytical tasks and have recently been successfully applied to many problems in population genetics [5–14].

The key to the success of deep learning in population genetics has been the use of large amounts of simulated data for training. Under simplifying, yet largely realistic, assumptions, evolution plays by relatively straightforward rules. By exploiting these rules and advances in computing power, a new generation of computational simulators has made it possible to efficiently produce large quantities of perfectly labeled synthetic data across a wide range of evolutionary scenarios [15–17]. At the same time, programming libraries such as stdpopsim have made these simulators accessible to a broad community of researchers while improving the reproducibility of simulation workflows [18,19]. The facility of generating synthetic training data serves as the foundation of the new simulate-and-train paradigm of supervised machine learning for population genetics inference (**Fig. 1A;** [7,13]).

At the same time, this paradigm is highly dependent on well-specified models for simulation [13]. If the simulation assumptions do not match the underlying generative process of the real data—that is, in the presence of *simulation mis-specification*—the

trained deep-learning model may reflect the biases in the simulated data and perform

poorly on real data. Indeed, previous studies have shown that, despite being robust to

mild to moderate levels of mis-specification, performance inevitably degrades when the

mismatch becomes severe [10,12].

In a typical workflow, key simulation parameters such as the mutation rate,

recombination rate, and parameters of the demographic model are either estimated from

the data or obtained from the literature (**Fig. 1A;** [18,19]). Sometimes these parameters

are allowed to vary during simulation, and sometimes investigators evaluate the

sensitivity of predictions to departures from the assumed range, but there is typically no

way to ensure that the ranges considered are adequately large. Moreover, these

benchmarks do not usually account for under-parameterization of the demographic

model. Particularly in the case of non-model organisms, the quality of the estimates can

be further limited by the availability of data. Overall, some degree of mis-specification in

the simulated training data is impossible to avoid.

One way to mitigate the effects of simulation mis-specification would be to

engineer a simulator to force the simulated data to be compatible with real data. For

example, one could simulate from an overdispersed distribution of parameters followed

by a rejection sampling step (based on summary statistics) as in Approximate Bayesian

Computation (ABC) methods, or one could use a Generative Adversarial Network (GAN)

[20] to mimic the real data. These methods tend to be costly, however. For example, ABC

methods scale poorly with the dimensionality of the parameter space, and GANs are

notoriously hard to train.

Here we consider the alternative approach of adopting a deep-learning model that

is explicitly designed to account for and mitigate the mismatch between simulated and

real data (**Fig. 1A**). A standard machine learning model aims to make accurate

predictions on data following the same probability distribution as the training instances.

In contrast, the task of building well-performing models for a target dataset that has a

different distribution from the training dataset is termed "domain adaptation" in the

machine-learning literature [21,22]. A typical setting of interest for domain adaptation is

image classification (**Fig. 1B**). For example, suppose a digit-recognition model is needed

for the Street View House Numbers (SVHN) dataset (the "target domain"), but abundant

labeled training data is only available from the MNIST dataset of handwritten digits (the

"source domain"). In this case, a method needs to train on one data set and perform well

on another, despite systematic differences between the two data distributions.

Various strategies for domain adaptation have been introduced. Prior to the advent

of deep learning, early methods focused on reweighting training instances according to

their likelihoods of being a source or target example [23,24] or explicitly manipulating a

feature space through augmentation [25], alignment [26,27] or transformation [28].

Recently, specialized neural network architectures have been developed for deep domain

adaptation. Most model architectures of this kind share the common goal of learning a

"domain-invariant" representation of the data through a feature extractor neural network,

for example, by minimizing domain divergence [29], by adversarial training [30,31] or

through an auxiliary reconstruction task [32]. Domain adaptation so far has been most

widely applied in the fields of computer vision (e.g., using stock photos for semantic

segmentation of real photos) and natural language processing (e.g., using Amazon

product reviews for sentiment analysis of movies and TV shows) where large,

heterogeneous datasets are common but producing labeled training examples can be

labor intensive [22]. More recently, deep domain adaptation has been used in regulatory

genomics to enable cross-species transcription-factor-binding-site prediction [33].

In this work, we reframe the simulation mis-specification problem in population

genetics as an unsupervised domain adaptation problem—unsupervised in the sense that

data from the target domain is not labeled (**Fig. 1B**). In particular, we use population-

genetic simulations to obtain large amounts of perfectly labeled training data in the source

domain. We then seek to apply the trained model to unlabeled real data in the target

domain. We use domain adaptation techniques to explicitly account for the mismatch

between these two domains when training the model.

To demonstrate the feasibility of this approach, we incorporated a domain-adaptive

neural network architecture into two published deep learning models for population

genetic inference: 1) SIA [12], which identifies selective sweeps based on the Ancestral

Recombination Graph (ARG), and 2) ReLERNN [10], which infers recombination rates

from raw genotypic data. Through extensive simulation studies, we demonstrated that the

domain adaptive versions of the models significantly outperformed the standard versions

under realistic scenarios of simulation mis-specification. Our domain-adaptive framework

for utilizing mis-specified synthetic data for supervised learning opens the door to many

more applications in population genetics.

Results

Experimental Design

We created domain-adaptive versions of the SIA and ReLERNN models, each of which employed a gradient reversal layer (GRL) [30] (**Fig. 2A&B**). As noted, the goal of domain adaptation is to establish a "domain-invariant" representation of the data (**Fig. 1A**). Our neural networks consist of two major components: the original networks ("feature extractor" in green and "label predictor" in blue in **Fig. 2A&B**), which are applied only to labeled examples from the "source" (simulated) domain; and alternative branches ("domain classifier" in yellow in **Fig. 2A&B**), which use the same feature-extraction portions of the first networks but have the distinct goal of distinguishing data from the "source" (simulated) and "target" (real) domains (they are applied to both). When the neural network is trained by back-propagation, the GRL reverses the sign of the gradient for the feature extractor with respect to the domain-classifier loss. By doing so, the GRL systematically undermines this secondary goal of distinguishing the two domains (**Fig. 2**, see **Methods** for details), and therefore promotes domain invariance in feature extraction.

We designed two sets of benchmark experiments to assess the performance of the domain-adaptive models relative to the standard models. In both cases, we tested the methods using "real" data in the target domain that was actually generated by simulation, but included features not considered by the simpler simulator used for the source domain. In the first set of experiments, background selection was present in the target domain but not the source domain. In the second set of experiments, the demographic model used for the source-domain simulations was estimated from "real" data generated under a more

153 complex demographic model and was therefore somewhat mis-specified (as detailed

154 below). Below we refer to these as the "background selection" and "demography mis-

155 specification" experiments.

Performance of Domain-Adaptive SIA Model

We compared the performance of the **d**omain-**ada**ptive SIA (dadaSIA) model to

that of the standard SIA model on held-out "real" data, considering both a classification

(distinguishing selective sweeps from neutrality) and a regression (inferring selection

coefficients) task. In all cases, we focused on a comparison of the domain-adaptive model

to the standard case where a model is simply trained on data from the source domain

and then applied to the target domain ("standard model"; **Fig. 1C**). For additional context,

we also considered the two cases where the training and testing domains matched

("source-matched" or "target-matched"; **Fig. 1C**)—although we note that these cases are

not achievable with real data and provide only hypothetical upper bounds on

performance. Notably, in the source-matched (or "simulation benchmark") case, the

standard model is both trained and tested with true genealogies from source-domain

simulations. By contrast, in the target-matched (or "hypothetical true model") case, the

standard model is trained as if target-domain data with ground-truth selection coefficient

labels were available. Since genealogies need to be inferred in the target domain (**Fig.

1B**), the hypothetical true model is both trained and tested with inferred genealogies (see

Setup of benchmarking experiments in **Methods** for details).

As noted, we considered two types of mis-specification, background selection and

demographic mis-specification. In the background selection experiments, the target

domain experienced selection in a central "genic" region (following a DFE from [34]),

leading to background selection in flanking regions. This genic region was omitted in the

source domain. In the demographic mis-specification experiments, the demographic

model for source-domain simulations was inferred from "real" data using G-PhoCS [35].

Both the real (target domain) and inferred (source domain) models assumed three

populations with migration, but the inferred model was under-parameterized and its

parameters differed substantially from the real model (**Fig. S1A**) (see **Methods** for

details).

Notably, in the course of this work, we made several minor improvements to the

previously published version of SIA [12], including both its neural network architecture

and its input features, that led to modest gains in performance (**Fig. S1B&C**). These

improvements were applied to both the baseline and domain-adaptive SIA models in all

experiments in this study (see *Updates to genealogical features and deep learning*

architecture for the SIA model in **Methods** for details). The codebase of the original SIA

model has been updated accordingly.

In both the background selection and demography mis-specification experiments,

and in both the classification and regression tasks, the domain-adaptive SIA model

substantially improved on the standard model (**Fig. 3**). Indeed, in all cases, the domain-

adaptive model (turquoise lines in **Fig. 3A&C**) nearly achieved the upper bound of the

hypothetical true model (dashed gray lines) and clearly outperformed the standard model

(gold lines), suggesting that domain adaptation had largely "rescued" SIA from the effects

of simulation mis-specification (see also **Fig. S2C&D**). The standard model performed

particularly poorly on the regression task (**Fig. 3B&D**), but the domain-adaptive model

achieved substantial improvements, reducing both the absolute error as well as the

upward bias of the estimation (**Fig. S2C&D**).

The comparisons with the simulation benchmark and hypothetical true model were

also informative in other ways. Notice that performance in the simulation benchmark case

was considerably better than that in all other cases, including the hypothetical true model.

For SIA in particular, the ARG is "known" (fixed in simulation) in the source domain,

whereas in the target domain it must be inferred (**Fig. 1B**). Thus, the difference between

the simulation benchmark (source-matched) and hypothetical true model (target-

matched) cases represents a rough measure of the importance of ARG inference error

(see **Discussion**). In addition, note that in many studies, benchmarking of population-

genetic models is performed using the same, or similar, simulations as those used for

training, as with our hypothetical true model. Thus, the difference between the

hypothetical true model and the standard model is representative of the degree to which

benchmarks of this kind may be overly optimistic about performance, depending on the

degree to which the simulations are mis-specified.

We further investigated the effect of imbalanced training data from the target

domain on the performance of the domain-adaptive model in the context of sweep

classification. Despite the ability to simulate perfectly class-balanced labeled data in the

source domain, in practice we have no control over whether real data are balanced. Using

simulations for the background selection mis-specification experiments, we tested the

performance of the domain-adaptive SIA model classifying sweeps when trained with

unlabeled "real" data under different proportions of sweep vs. neutral examples. While a

balanced dataset yielded the best performance, significantly skewed datasets (20% or

80% sweep examples) still provided the domain-adaptive model with reasonable

improvement upon the standard model (**Fig. S3A&B**). The exception appeared to be

when the target domain data consisted entirely of sweep examples (100% sweep).

Although highly unrealistic, this scenario demonstrates that the domain-adaptive model

can underperform the standard model when the target domain data follow a radically

different distribution.

Another type of imbalance arises if only a limited amount of target domain data is

available to train the domain-adaptive model. Using the same set of simulations for the

background selection mis-specification experiments, we tested the performance of the

domain-adaptive SIA model when trained with less target domain data. With the target

domain data at only 10% of the source domain data (source:target ratio = 10:1), the model

suffered a noticeable drop in performance yet still maintained a clear advantage over the

standard model (**Fig. S3C-E**). We did not examine the case where there is more target

domain than source domain data, since one could always simulate additional source

domain data to match the size of the target domain. In summary, our experiments suggest

that domain adaptation can accommodate reduced or imbalanced data for the target

domain but there is a cost in performance if the reduction or imbalance is extreme.

Performance of Domain-Adaptive ReLERNN Model

We performed a parallel set of experiments with a domain-adaptive version of

ReLERNN. In this case, the background selection experiment was essentially the same

as for SIA, but we used a simpler design for the demography mis-specification

experiment, following [10]. Briefly, the "real" (target domain) data was generated

according to the out-of-Africa European demographic model estimated by [36]. By

contrast, the simulated data for the source domain simply assumed a constant-sized

panmictic population at equilibrium with $N_e = \frac{\hat{\theta}_W}{4\mu}$, where $\hat{\theta}_W$ is the Watterson estimator

obtained from the "real" data (see **Methods** for details).

Similar to our results for SIA, the domain-adaptive ReLERNN model both reduced

the mean absolute error (MAE) and corrected for the downward bias in recombination-

rate estimates compared to the standard model (**Fig. 4, Fig. S4**). In the background-

selection experiment, the standard ReLERNN model performed quite well (**Fig. 4A, S4A,**

MAE $= 5.60 \times 10^{-9}$), but the domain-adaptive ReLERNN model nonetheless further

reduced the MAE to 4.41×10^{-9} (**Fig. S4C**, Welch's *t*-test: $n = 25{,}000$, $t = 31.0$, $p <$

10^{-208}). The advantage of the domain-adaptive model was more apparent in the

demography-mis-specification experiment (**Fig. 4B, S4B**), where it reduced the MAE from

8.06×10^{-9} to 5.45×10^{-9} (**Fig. S4D**, Welch's t-test, $n = 25{,}000$, $t = 72.4$, $p < 10^{-323}$).

Notably, our results for the standard model in the demography-mis-specification

experiment were highly similar to those reported by [10], including the approximate mean

and range of the raw error (compare **Fig. 4A** from [10] and **Fig. S4D**), as well as the

downward bias.

Interestingly, Adrion et al. [10] observed that ReLERNN was sometimes more

strongly influenced by demographic mis-specification than unsupervised methods such

as LDhelmet, even though it still performed better in terms of absolute error. The addition

of domain adaptation appears to considerably mitigate this susceptibility to demographic

mis-specification, making an excellent method even stronger.

Efficacy of Domain Adaptation under Various Degrees of Simulation Mis-specification

So far, we have examined scenarios of relatively modest simulation mis-specification, likely to be encountered in real applications. While domain adaptation appeared to be effective in these cases, we expect a limit to its capability when mis-specification is extreme. We therefore carried out a series of experiments to probe the performance of the dadaSIA model under increasingly severe simulation mis-specification (**Fig. S4**, also see **Methods**).

We found that dadaSIA exhibited good performance when mis-specification was caused by genealogy inference alone or by light to moderate bottlenecks. As the bottleneck became more severe, its performance deteriorated, but even with a 5% bottleneck, dadaSIA still outperformed the standard model (**Fig. 5**). To examine the limits of the method, we tested an extreme scenario with the 5% bottleneck, background selection and an 8-fold mis-specification of recombination rate. In this case, the model performed poorly, having virtually no power to classify sweeps and large errors in its selection coefficient estimates (**Fig. 5**). This example demonstrates that, while domain adaptation is useful over a broad range of mis-specification levels, it eventually does fail when mis-specification becomes extreme.

Does domain adaptation compromise performance at the opposite extreme, where there is little or no simulation mis-specification? To address this question, we tested the standard and domain-adaptive ReLERNN models in a setting without any simulation mis-specification. We focused here on ReLERNN, which directly uses raw genotypic data, as opposed to SIA, which always has some mis-specification due to genealogy inference

error. We observed that the standard and domain-adaptive ReLERNN models performed

nearly identically when no mis-specification was present, with only minor decreases in

performance (**Fig. S7**). Thus, there is perhaps some cost in using domain adaptation

when it is not needed, but, at least in our case, that cost appears to be slight.

Application of Domain-Adaptive SIA to Real Data

In applications to real data, the true selection coefficient is not known, so it is

impossible to perform a definitive comparison of methods. Nevertheless, it can be

informative to evaluate the degree to which alternative methods are concordant,

especially with consideration of their relative performance in simulation studies.

Toward this end, we re-applied our **d**omain-**ada**ptive SIA model (dadaSIA) to

several loci in the human genome that we previously analyzed with SIA [12], using whole-

genome sequence data from the 1000 Genomes CEU population [1]. For the target

domain, we sampled genealogies from genome-wide ARGs inferred from the individual

sequences (see **Methods**). The putative causal loci analyzed included single nucleotide

polymorphisms (SNPs) at the *LCT* gene [37], one of the best-studied cases of selective

sweeps in the human genome; at the disease-associated genes *TCF7L2* [38], *ANKK1*

[39] and *FTO* [40]; at the pigmentation genes *KITLG* [41], *ASIP* [42], *TYR* [41,42], *OCA2*

[43,44], *TYRP1* [45] and *TTC3* [46], which were also analyzed by [47]; and at the genes

MC1R [41,43] and *ABCC11* [48], where SIA reported novel signals of selection.

We found that dadaSIA generally made similar predictions to SIA at these SNPs,

but there were some notable differences. The seven loci predicted by SIA to be sweeps

were also predicted by dadaSIA to be sweeps (**Table 1**), although dadaSIA always

reported higher confidence in these predictions (with probability of neutrality, $P_{\mathrm{neu}} < 10^{-2}$

in all cases) than did SIA (P_{neu} up to 0.384 for *TYR*). The five loci predicted by SIA not to

be sweeps were also predicted by dadaSIA not to be sweeps ($P_{neu} > 0.5$). At *LCT*, the

strongest sweep considered, the selection coefficient (*s*) estimated by dadaSIA remained

very close to SIA's previous estimate of $s = 0.01$ and also close to several prior estimates

[37,49,50]. In all other cases, the estimate from SIA was somewhat revised by dadaSIA,

generally by factors of about 2–3. Importantly, in all cases, the estimates from dadaSIA

remained much closer to those from SIA than to estimates by other methods (**Table 1**).

Together, these observations suggest that the addition of domain adaptation does not

radically alter SIA's predictions for real data but may in some cases improve them (see

Discussion).

Discussion

Standard approaches to supervised machine learning rest on the assumption that

the data they are used to analyze follow essentially the same distribution as the data used

for training. In applications in population genetics, the training data are typically generated

by simulation, leading to concerns about potential biases from simulation mis-

specification when supervised machine-learning methods are used in place of more

traditional summary-statistic- or model-based methods [11,13]. In this article, we have

shown that techniques from the "domain adaptation" literature can effectively be used to

address this problem. In particular, we showed that the addition of a gradient reversal

layer (GRL) to two recently developed deep-learning methods for population genetic

analysis—SIA and ReLERNN—led to clear improvements in performance on "real" data

that differed in subtle but important ways from the data used to train the models. These

improvements were observed both when the demographic models were mis-specified

and when background selection was included in the simulations of "real" data but un-

modeled in the training data.

While we observed performance improvements in all of our experiments, they were

especially pronounced in the case where SIA was used to predict specific selection

coefficients, rather than simply to identify sweeps. The standard model (with training on

simulated data and testing on "real" data) performed particularly poorly in this regression

setting and domain adaptation produced striking improvements (**Fig. 3B&D**). This

selection-coefficient inference problem appears to be a harder task than either sweep

classification or recombination-rate inference, and the performance in this case proves to

be more sensitive to simulation mis-specification (cf. **Fig. 3A&C**). In general, we

anticipate considerable differences across population-genetic applications in the value of

domain adaptation, with some applications being more sensitive to simulation mis-

specification and therefore more apt to benefit from domain adaptation, and others being

less so.

We also observed some interesting differences in the ways SIA and ReLERNN

responded to domain adaptation. For example, the performance gap between the

"simulation benchmark" (trained and tested on simulated data) and "hypothetical true"

(trained and tested on real data) models was considerably greater for SIA than for

ReLERNN (**Figs. S2C&D, S4C&D**). This difference appears to be driven by ARG

inference, which is required by SIA in the hypothetical true case but not the simulation

benchmark case, and for which no analog exists for ReLERNN. For SIA, the uncertainty

about genealogies given sequence data makes the prediction task fundamentally harder

in the real world (target domain) than in simulation (source domain) (**Fig. 1B**). By contrast,

ReLERNN does not depend on a similar inference task, and therefore the target and

source domains are more or less symmetric. This same factor contributed to the much

more dramatic drop in performance for SIA than ReLERNN under the "standard model,"

where the model is trained on simulated data and naively applied to "real" data (**Figs.**

3B&D, 4). It is, of course, also conceivable that simulation mis-specification has more

impact on selection inference than recombination rate inference, rendering the standard

SIA model less robust than the standard ReLERNN model. Regardless of the exact

cause, the result is more potential for improvement from domain adaptation with SIA than

with ReLERNN (**Figs. 3, 4, S2, S4**). In effect, in SIA, domain adaptation not only mitigates

simulation mis-specification but also compensates for ARG inference error, as directly

evidenced by the observation that domain adaptation improves model performance when

mis-specification is due to genealogy inference alone (**Fig. 5**, "Tree inference only"). More

broadly, we expect domain adaptation to be especially effective in applications that

depend not only on the simulated data itself but also on nontrivial inferences of latent

quantities that are known for simulated but not real data.

In addition, we performed a series of experiments to probe the limits of domain

adaptation. As expected, the dadaSIA model gradually lost its power as simulation mis-

specification became more severe. In an extreme case where mis-specification involved

demography, selection and recombination rate, the dadaSIA model had virtually no power

to classify sweeps and exhibited high error of selection coefficient inference (**Fig. 5**). In

practice, simulation models themselves are inferred from real data. With high quality data,

state-of-the-art inference tools are unlikely to fail completely (e.g., by missing a 5%

bottleneck completely, or under-estimating recombination rate by an order of magnitude).

We thus expect the most extreme scenario tested here to be fairly uncommon.

Nevertheless, this experiment demonstrated that there are reasonable limits to the

efficacy of domain adaptation. Consequently, it is important in real-world applications to

begin with the best possible simulation model, before using domain adaptation to further

optimize performance.

Because the accuracy of the simulation model is typically not known a priori, it is

tempting to apply domain adaptation in all cases, regardless of the true degree of mis-

specification. Indeed, we found that the domain-adaptive model performed very similarly

to the standard model in the absence of mis-specification (**Fig. S7**), suggesting little risk

in applying the approach liberally. When the target domain is mis-specified, the domain

classifier appears to "unlearn" the mis-specification, with its loss increasing steadily

before plateauing where the source and target domains are no longer distinguishable. In

contrast, when there is no mis-specification, the domain classifier starts with a high loss

and this loss remains high (**Figs. 2B, S8**). In this case, because the source and target

domains are effectively indistinguishable, the domain classifier can never do much better

than randomly guessing, leading to near-zero gradients along the domain classifier

branch. In effect, the training process ignores the domain-classifier branch in this case,

and improves only the feature-extractor and label-predictor portions of the model. For this

reason, the domain-adaptive model behaves nearly identically to the standard model in

the absence of mis-specification.

The accuracy of even the best current selection-coefficient inference methods

appears limited [8,9,12,47]. More work is needed on models and methods for inference

as well as on the problem of simulation mis-specification. Nevertheless, current methods

can still be valuable in approximately characterizing the strength of selection. In our re-

analysis of several loci in the 1000 Genomes CEU population, we found that dadaSIA

made similar predictions to SIA, but it tended to exhibit higher confidence in its predictions

(**Table 1**). Considering the extensive previous work on demography inference for the CEU

population, we expect that simulation mis-specification is limited in severity for this

analysis, but that some mis-specification is inevitable. Given the similar performance on

benchmarks of SIA and other leading methods such as CLUES, their similar sensitivity to

moderate levels of simulation mis-specification [12], and the improvements offered by

domain adaptation that are demonstrated in this work, we find it likely that dadaSIA

improves on previous estimates of selection coefficients in this setting.

In a typical application of domain adaptation, the distribution shift between the

source and target domains is treated as a nuisance. However, for certain population

genetic questions, the gap between the simulated and real data could in principle help to

reveal unmodeled evolutionary processes. We observed that the domain classifier

generally tended to start with a lower loss and took more epochs to train when the mis-

specification is more severe (**Fig. S9**). It might be worthwhile, as a future endeavor, to try

to identify the features driving this loss, understand their evolutionary significance, and,

perhaps, incorporate them into a new set of simulations. In such a way, domain adaptation

could be used to discover evolutionary processes and improve the models used for

simulation.

Although our experiments were limited to background selection and demographic

mis-specification, we expect that the domain adaptation framework would also be

effective in addressing many other forms of simulation mis-specification, involving factors

such as mutation or recombination rates, or the presence of gene conversion. Another

interesting application may be to use domain adaptation to accommodate admixed

populations. Each ancestry component could be modeled as a distinct target domain

using a multi-target domain adaptation technique [51–53]. It is also worth noting that our

experiments considered only one, rather simple, strategy for domain adaptation. Since

the GRL was proposed, several other architectures for deep domain adaptation have

achieved even better empirical performance on computer vision tasks (see: [54]).

Our domain-adaptation approach leaves simulations unchanged and attempts to

"unlearn" their mis-specification, in contrast to other strategies that aim to improve the

simulations themselves. For example, the original SIA model was trained with inferred

genealogies from the simulated sequences, rather than the true genealogies used to

generate the data, to mitigate the effect of genealogy inference error [12]. An alternative

approach is to use a GAN to train a simulator that accurately mimics the real data [20].

These methods can require costly preprocessing steps, but they have the advantage of

explicitly addressing the simulation mis-specification in an interpretable manner.

It is perhaps worth distinguishing mis-specification *along* the axis of inference—

that is, of target parameters such as the selection coefficient—from mis-specification of

other "nuisance" parameters (such as demographic parameters), or similarly, other

unmodeled aspects of the data-generating process (such as background selection).

From our observations, domain adaptation appears to be effective at addressing mis-

specification of nuisance parameters or processes, at least if it is not too severe. Mis-

specification of the target parameters, however, is clearly a more challenging problem.

For example, it seems unlikely that domain adaptation will ever be able to "extrapolate"

beyond the range of the training examples (as it fails to do in **Fig. S5**). Hence, it is

essential in practical applications to simulate the parameter of interest from an adequately

large range. Notably, Burger et al. [55] recently developed a method that addresses mis-

specification in the distribution (but not the range) of a target parameter. Their method

improves inference of the scaled mutation rate when regions of the parameter space are

under-sampled in the training simulations by adaptively reweighing the training data,

effectively improving interpolation (but not extrapolation) from the training distribution. We

view these interrelated questions of how to accommodate mis-specification of both

nuisance and target parameters as promising areas for future work.

Mis-specification is not only a problem in the simulation-based supervised machine

learning setting explored in this work (*simulation* mis-specification), but also arises in

many unsupervised methods (such as maximum likelihood, Bayesian or Approximate

Bayesian). In these cases, mis-specification typically results from simplified or incorrect

assumptions built into a probabilistic model (*model* mis-specification, reviewed in detail

by [56]). Such model mis-specification can be difficult and time-consuming to identify and

address, usually calling for careful experimental design and model comparison [56]. In

some ways, the simulation mis-specification problem is more straightforward to address

through fully empirical, data-driven solutions such as domain adaptation. It remains to be

seen whether these empirical techniques can be used to improve probabilistic-model-

based inference methods. Overall, there is rich potential for new work to address a wide

variety of mis-specification challenges in population genetics, leading to improved

accuracy and robustness in inference.

Methods

Methodological summary of unsupervised domain adaptation

To build domain-adaptive versions of SIA and ReLERNN, we opted for the neural network architecture proposed by Ganin & Lempitsky [30], which involved attaching a domain classifier branch via a gradient reversal layer (GRL) to a layer of the original neural network where a latent representation of the data is presumably obtained. For example, in a CNN, the attachment point is usually immediately after the convolutional and pooling layers, which are primarily responsible for feature extraction. One possible heuristic for picking the attachment point is to look for a "bottleneck layer" in the original network corresponding to the lowest-dimensional representation of the input. The GRL-containing networks consist of three components – a label predictor branch, a domain classifier branch and a feature extractor common to both branches (**Fig. 2A&B**). During the feedforward step, when data is fed to the neural network to obtain prediction outputs in both branches, the GRL is inactive; it simply passes along any input to the next layer. However, during backpropagation, when the gradient of the loss function with respect to the weights of the network is calculated iteratively backward from the output layer, the GRL inverts the sign of any incoming gradient before passing it back to the previous layer. This operation has the effect of driving the feature extractor away from distinguishing the source and target domains, and consequently encourages it to extract "domain-invariant" features of the data. We implemented the GRLs in TensorFlow (v2.4.1) using the 'tf.custom_gradient' decorator. On top of each custom GRL, the rest of the model was built using the 'tf.keras' functional API (see the GitHub repository for details).

All models were trained with the Adam optimizer using a batch size of 64. For the

domain-adaptive models, training consisted of both (1) feeding labeled data from the

source domain through the label predictor and obtaining a label prediction loss (cross

entropy for classification task, mean squared error for regression task); and (2) feeding a

mixture of unlabeled data from both the source and target domains through the domain

classifier, obtaining a domain classification loss (cross entropy) (**Fig. 2C**). In each

minibatch, back-propagation from these two steps occurred simultaneously (i.e. the

weights of the feature extractor were updated according to the combination of gradient

from the label predictor and reversed gradient from the domain classifier). Note that the

same source-domain data (but shuffled differently) were used for both steps. Training

was accomplished using a custom data generator implemented with

'tf.keras.utils.Sequence'. In this study, we simply assigned equal weights to the label-

prediction and domain-classification loss functions (following [30]). Nonetheless, the

relative weights of the two branches can be tuned via a hyper-parameter λ, with potential

implications for performance. Intuitively, the domain classifier should be penalized more

when the simulations are more mis-specified. One potential strategy is to leverage the

losses and gradients of the domain classifier to guide the choice of λ. Each training epoch

took around 300 s for the domain-adaptive SIA model and around 800 s for the domain-

adaptive ReLERNN model on a single NVIDIA Tesla V100 GPU. With early-stopping, the

models in this study were trained on average for tens of epochs. The runtimes for domain-

adaptive SIA and ReLERNN models were therefore on par with their standard versions

(on the order of hours) [10,12].

Setup of benchmarking experiments

We designed four benchmarking scenarios to contextualize the performance of the

domain-adaptive models (**Fig. 1C**). *i*) In the *simulation benchmark* (*source-matched*)

case, we tested the original model trained with source domain data on held-out samples

in the source domain. This is how model benchmarks are usually run, with the test data

following the same distribution as the training data. Note that for the SIA model, the source

domain consists of true genealogies and therefore both training and testing were

performed with true trees. *ii*) In the *hypothetical true model* (*target-matched*) case, the

original model was trained and tested with labeled target domain data. Here, both training

and testing were performed with inferred genealogies for the SIA model. This is a

hypothetical case because it is unlikely in the evolution setting to have large quantities of

labeled data from the target domain for training (i.e. real population data with known

ground truth of evolutionary parameters). This case represents the performance ceiling

of a standard machine learning model trained in-domain. *iii*) The *standard model*

application recapitulated the usual workflow of supervised machine learning methods,

where the model trained with source domain simulations was applied directly to "real"

data in the target domain. This was the baseline case to which we compared the domain-

adaptive model. *iv*) *Domain-adaptive application* of supervised machine learning models

is the novel approach introduced in this study (see above and **Fig. 1A**).

Background selection experiment with SIA

To assess the robustness of domain-adaptive SIA (dadaSIA) to background

selection, we simulated labeled examples (250,000 neutral and 250,000 sweep) in the

source domain under demographic equilibrium with $N_e = 10,000$ and $\mu = \rho = 1.25 \times$

10^{-8}/bp/gen. The sweep simulations consisted of 100kb chromosomal segments with a

hard sweep at the central nucleotide having selection coefficient $s \in [0.002, 0.01]$.

Simulations were performed in SLiM 3 [15,16] followed by recapitation with msprime [17],

and we kept the true genealogies as source domain data. The unlabeled data in the target

domain (with the exception of held-out test dataset with labels retained) were simulated

in a similar fashion, albeit with a 10kb segment ("gene") under purifying selection at the

center of each 100kb chromosomal segment. All mutations in the central 10kb segment

that arose during the forward stage of the simulations (in SLiM), other than the beneficial

mutation in sweep simulations, followed a DFE parameterized by a gamma distribution

with a mean $\bar{s} = -0.03$, a shape parameter $\alpha = 0.2$ and had dominance coefficient $h =$

0.25 [34]. We retained only the sequence data from the target domain simulations and

inferred genealogies using Relate [57]. The datasets were partitioned following a

90%:2%:8% train-validation-test split.

Demography mis-specification experiment with SIA

In a second set of simulations, we gauged whether domain adaptation also

protects SIA against demographic mis-specification. In this case, instead of specifying the

degree of mis-specification *a priori*, we designed an end-to-end workflow that

recapitulated how demographic mis-specification arises in a realistic population genetic

analysis (**Fig. S1A**). First, we simulated "real" data (in the target domain) using an

assumed demography (**Fig. S1A**, loosely based on the three-population model in [58]).

Similar to what one would do with actual sequence data, we then used the "real" samples

to infer a demography with G-PhoCS [35], pretending that the true demography and

genealogies were unknown. The G-PhoCS model assumed constant population sizes

between split events and a single pulse migration from population C to B, and therefore

was under-parameterized. As shown in **Fig. S1A**, the inferred demography was

consequently somewhat mis-specified. In addition to errors in population sizes, the split

between B and C was inferred to be much more recent compared to the true demographic

model. This mis-specified demographic model was then used to simulate labeled training

data (in the source domain) for SIA.

With the goal of using SIA to infer selection in population B, we simulated a soft

sweep site at the center of a 100kb chromosomal segment with selection coefficient $s \in$

$[0.003, 0.02]$ and initial sweep frequency $f_{init} \in [0.01, 0.1]$, under positive selection only in

population B. To improve computational efficiency, simulations were performed with a

hybrid approach where the neutral demographic processes were simulated first with

msprime [17], followed by positive selection simulated with SLiM 3 [15,16]. We produced

200,000 balanced (between neutral and sweep) simulations of "real" data, 10,000 of

which were randomly held out as ground-truth test data for benchmarking with their labels

preserved (**Fig. S1A**). The rest remained unlabeled. This corresponded to a train-

validation-test split of 93%:2%:5%. We preserved only the sequences and used Relate

[57] to infer the ARG of population B from the "real" data. SIA works with a single

population and thus the central genealogies containing only samples from population B

were encoded as input to the model. For demographic inference, we randomly

downsampled 10,000 5kb loci and analyzed them with G-PhoCS, keeping 4 (diploid)

individuals from population A and 16 (diploid) individuals each from populations B and C.

We took the median of 90,000 MCMC samples (after 10,000 burn-in iterations) as the

inferred demography (shown in **Fig. S1A**). The control file used to run G-PhoCS is

available in the GitHub repository. We then simulated true genealogies of population B

using the inferred demography, yielding 200,000 balanced samples with neutral/sweep

and selection coefficient labels. All SIA models in this study used 64 diploid samples (128

taxa).

Running SIA under varying degrees of simulation mis-specification

To probe the limit of domain adaptation in mitigating simulation mis-specification,

we performed a series of experiments that gradually increased the severity of mis-

specification. In all cases, the source domain consisted of 400,000 balanced samples of

true genealogies simulated under a constant N_e of 10,000. The target domain had a

matching size of 400,000 balanced samples of *inferred* genealogies. We used $\mu = \rho =$

1.25×10^{-8}/bp/gen unless otherwise specified. The datasets were partitioned following

an 87.5%:2.5%:10% train-validation-test split. In the "tree inference only" case, the target

domain consisted of *inferred* genealogies simulated under a constant N_e of 10,000 with

no demographic mis-specification. In addition, we tested four cases with N_e = 8,000,

5,000, 2,000 or 500 bottlenecks between 1,000 and 2,000 generations before the present,

respectively (**Fig. S4**). Finally, we tested an "extreme" case with the N_e = 500 bottleneck,

a mis-specified $\rho = 1 \times 10^{-7}$, as well as background selection in the central 10kb region

following a DFE parameterized by a gamma distribution with a mean $\bar{s} = -0.03$, a shape

parameter $\alpha = 0.2$ and a dominance coefficient $h = 0.25$.

Updates to genealogical features and deep learning architecture for the SIA model

For this study, we adopted a richer encoding of genealogies than the one used

previously for SIA. Instead of simply counting the lineages remaining in the genealogy at

discrete time points [12], we fully encoded the topology and branch lengths of the tree

using the scheme introduced by [59]. Under this scheme, a genealogy with *n* taxa is

uniquely encoded by an (*n*-1) × (*n*-1) lower-triangular matrix *F* and a weight matrix *W* of

the same shape. Each cell (*i*, *j*) of *F* records the lineage count between coalescent times

t_{n-j} and t_{n-1-i}, whereas each cell (*i*, *j*) of *W* records the corresponding interval between

coalescent times, $t_{n-j} - t_{n-1-i}$ (see **Fig. S1B** and [59] for details). In addition, we used a

third matrix *R* to identify the subtree carrying the derived alleles at the site of interest,

following the same logic as *F* (see **Fig. S1B** for an example). The *F*, *W* and *R* matrices

have the same shape and therefore can easily be stacked as input to a convolutional

layer with three channels (**Fig. 2A**, 128 taxa yield a 127 x 127 x 3 input tensor).

Unlike the previous reductive encoding of lineage counts, the new scheme is

bijective [59] and therefore contains the entirety of information in the genealogy. To utilize

the improved input feature consisting of stacks of matrices, we modified the neural

network architecture of SIA and used convolutional layers (**Fig. 2A**). The new feature

encoding and convolutional neural network (CNN) architecture resulted in modest gain in

performance compared to the original encoding and recurrent neural network (RNN)

architecture (**Fig. S1C**). In this study, both the standard and domain-adaptive SIA models

use convolutional layers with the improved feature encoding. The original SIA codebase

(github.com/CshlSiepelLab/arg-selection) has been updated to take advantage of the

new feature encoding and model architecture as well.

Simulation study of recombination rate inference with ReLERNN

We conducted two sets of simulation experiments to test the same two types of

mis-specification as previously described for SIA. Each simulation consisted of 32 haploid

samples of 300kb genomic segment with uniformly sampled mutation rate $\mu \sim$

$U[1.875 \times 10^{-8}, 3.125 \times 10^{-8}]$ and recombination rate $\rho \sim U[0, 6.25 \times 10^{-8}]$. To test the

effect of background selection, the labeled source domain data (with true values of ρ)

were simulated under demographic equilibrium with $N_e = 10,000$, whereas the unlabeled

target domain data were simulated under the same demography, but with the central

100kb region under purifying selection, as with SIA. To test the effect of demographic

mis-specification, we conducted simulations similar to those of [10] where labeled source

domain data were generated under demographic equilibrium (with $N_e = 6,000$, calculated

approximately by $\frac{\hat{\theta}_W}{4\mu}$ where $\hat{\theta}_W$ was estimated from the target domain data) and unlabeled

target domain data were generated under a European demography [36]. For each

domain, 500,000 simulations were generated with SLiM 3 (background selection

experiment) or msprime (demography experiment), and partitioned following an

88%:2%:10% train-validation-test composition. We modified the ReLERNN model to be

domain-adaptive (**Fig. 2B**) and used the simulated data to benchmark its performance

against the original version of the model.

Application of domain-adaptive SIA model to 1000 Genomes CEU population

Labeled training data (source domain) for SIA were simulated with discoal [60]

under the European demographic model from [36]. Following [12], we simulated 500,000

100-kb regions of 198 haploid sequences. The per-base per-generation mutation rate (μ)

and recombination rate (ρ) of each simulation were sampled uniformly from the interval

$[1.25 \times 10^{-8}, 2.5 \times 10^{-8}]$; the segregating frequency of the beneficial allele (*f*) was

sampled uniformly from $[0.05, 0.95]$; the selection coefficient (*s*) was sampled from an

equal mixture of a uniform and a log-uniform distribution with the support

$[1 \times 10^{-4}, 2 \times 10^{-2}]$. An additional 500,000 neutral regions were simulated to train the

classification model, under the identical setup sans the positively selected site.

We curated target domain data from the 1000 Genomes CEU population to train

the domain-adaptive SIA model (dadaSIA). The genome was first divided into 2Mb

windows 1,111 of which passed three data-quality filters: 1) contained at least 5,000

variants, 2) at least 80% of these variants had ancestral allele information, and 3) at least

60% of nucleotide sites in the window passed *both* the 1000 Genomes strict accessibility

mask [1] and the deCODE recombination hotspot mask (standardized recombination rate

> 10; [61]). In each of these 1,111 windows, we randomly sampled 1,000 variants and

extracted genealogical features at those variants from Relate-inferred ARGs [57], yielding

around 1 million samples that constituted the unlabeled target domain data. Finally,

domain-adaptive SIA models for classifying sweeps and inferring selection coefficients

were trained as described previously and applied to a collection of loci of interest (**Table**

1).

Code Availability

The code for this study is available in a GitHub repository at github.com/ziyimo/popgen-

dom-adapt.

Acknowledgements

This research was supported, in part, by US National Institutes of Health grant R35-

GM127070 (A.S.), the Gladys & Roland Harriman Fellowship (Z.M.), and the Simons

Center for Quantitative Biology at Cold Spring Harbor Laboratory. We would like to thank

Jesse Gillis, Peter Koo, David McCandlish, Armin Scheben, and Xander Xue for useful

discussion.

References

1. Auton A, Abecasis GR, Altshuler DM, Durbin RM, Abecasis GR, Bentley DR, et al. A global reference for human genetic variation. Nature. 2015;526: 68–74. doi:10.1038/nature15393
2. Sudlow C, Gallacher J, Allen N, Beral V, Burton P, Danesh J, et al. UK Biobank: An Open Access Resource for Identifying the Causes of a Wide Range of Complex Diseases of Middle and Old Age. PLOS Med. 2015;12: e1001779. doi:10.1371/journal.pmed.1001779
3. Karczewski KJ, Francioli LC, Tiao G, Cummings BB, Alföldi J, Wang Q, et al. The mutational constraint spectrum quantified from variation in 141,456 humans. Nature. 2020;581: 434–443. doi:10.1038/s41586-020-2308-7
4. LeCun Y, Bengio Y, Hinton G. Deep learning. Nature. 2015;521: 436–444. doi:10.1038/nature14539
5. Sheehan S, Song YS. Deep Learning for Population Genetic Inference. PLOS Comput Biol. 2016;12: e1004845. doi:10.1371/journal.pcbi.1004845
6. Kern AD, Schrider DR. diploS/HIC: An Updated Approach to Classifying Selective Sweeps. G3 GenesGenomesGenetics. 2018;8: 1959–1970. doi:10.1534/g3.118.200262
7. Schrider DR, Kern AD. Supervised Machine Learning for Population Genetics: A New Paradigm. Trends Genet. 2018;34: 301–312. doi:10.1016/j.tig.2017.12.005
8. Flagel L, Brandvain Y, Schrider DR. The Unreasonable Effectiveness of Convolutional Neural Networks in Population Genetic Inference. Mol Biol Evol. 2019;36: 220–238. doi:10.1093/molbev/msy224
9. Torada L, Lorenzon L, Beddis A, Isildak U, Pattini L, Mathieson S, et al. ImaGene: a convolutional neural network to quantify natural selection from genomic data. BMC Bioinformatics. 2019;20: 337. doi:10.1186/s12859-019-2927-x
10. Adrion JR, Galloway JG, Kern AD. Predicting the Landscape of Recombination Using Deep Learning. Mol Biol Evol. 2020;37: 1790–1808. doi:10.1093/molbev/msaa038
11. Caldas IV, Clark AG, Messer PW. Inference of selective sweep parameters through supervised learning. bioRxiv; 2022. p. 2022.07.19.500702. doi:10.1101/2022.07.19.500702
12. Hejase HA, Mo Z, Campagna L, Siepel A. A Deep-Learning Approach for Inference of Selective Sweeps from the Ancestral Recombination Graph. Mol Biol Evol. 2022;39: msab332. doi:10.1093/molbev/msab332
13. Korfmann K, Gaggiotti OE, Fumagalli M. Deep Learning in Population Genetics. Genome Biol Evol. 2023;15: evad008. doi:10.1093/gbe/evad008
14. Huang X, Rymbekova A, Dolgova O, Lao O, Kuhlwilm M. Harnessing deep learning for population genetic inference. Nat Rev Genet. 2023; 1–18. doi:10.1038/s41576-023-00636-

15. Haller BC, Galloway J, Kelleher J, Messer PW, Ralph PL. Tree-sequence recording in SLiM opens new horizons for forward-time simulation of whole genomes. Mol Ecol Resour. 2019;19: 552–566. doi:10.1111/1755-0998.12968

16. Haller BC, Messer PW. SLiM 3: Forward Genetic Simulations Beyond the Wright–Fisher Model. Mol Biol Evol. 2019;36: 632–637. doi:10.1093/molbev/msy228

17. Baumdicker F, Bisschop G, Goldstein D, Gower G, Ragsdale AP, Tsambos G, et al. Efficient ancestry and mutation simulation with msprime 1.0. Genetics. 2022;220: iyab229. doi:10.1093/genetics/iyab229

18. Adrion JR, Cole CB, Dukler N, Galloway JG, Gladstein AL, Gower G, et al. A community-maintained standard library of population genetic models. Coop G, Wittkopp PJ, Novembre J, Sethuraman A, Mathieson S, editors. eLife. 2020;9: e54967. doi:10.7554/eLife.54967

19. Lauterbur ME, Cavassim MIA, Gladstein AL, Gower G, Pope NS, Tsambos G, et al. Expanding the stdpopsim species catalog, and lessons learned for realistic genome simulations. bioRxiv; 2022. p. 2022.10.29.514266. doi:10.1101/2022.10.29.514266

20. Wang Z, Wang J, Kourakos M, Hoang N, Lee HH, Mathieson I, et al. Automatic inference of demographic parameters using generative adversarial networks. Mol Ecol Resour. 2021;21: 2689–2705. doi:10.1111/1755-0998.13386

21. Csurka G. A Comprehensive Survey on Domain Adaptation for Visual Applications. In: Csurka G, editor. Domain Adaptation in Computer Vision Applications. Cham: Springer International Publishing; 2017. pp. 1–35. doi:10.1007/978-3-319-58347-1_1

22. Wilson G, Cook DJ. A Survey of Unsupervised Deep Domain Adaptation. ACM Trans Intell Syst Technol. 2020;11: 51:1-51:46. doi:10.1145/3400066

23. Shimodaira H. Improving predictive inference under covariate shift by weighting the log-likelihood function. J Stat Plan Inference. 2000;90: 227–244. doi:10.1016/S0378-3758(00)00115-4

24. Dai W, Yang Q, Xue G-R, Yu Y. Boosting for transfer learning. Proceedings of the 24th international conference on Machine learning. New York, NY, USA: Association for Computing Machinery; 2007. pp. 193–200. doi:10.1145/1273496.1273521

25. Daumé III H. Frustratingly Easy Domain Adaptation. arXiv; 2009. doi:10.48550/arXiv.0907.1815

26. Fernando B, Habrard A, Sebban M, Tuytelaars T. Unsupervised Visual Domain Adaptation Using Subspace Alignment. 2013 IEEE International Conference on Computer Vision. 2013. pp. 2960–2967. doi:10.1109/ICCV.2013.368

27. Sun B, Feng J, Saenko K. Return of frustratingly easy domain adaptation. Proceedings of the Thirtieth AAAI Conference on Artificial Intelligence. Phoenix, Arizona: AAAI Press; 2016. pp. 2058–2065.

28. Pan SJ, Tsang IW, Kwok JT, Yang Q. Domain Adaptation via Transfer Component Analysis. IEEE Trans Neural Netw. 2011;22: 199–210. doi:10.1109/TNN.2010.2091281

29. Rozantsev A, Salzmann M, Fua P. Beyond Sharing Weights for Deep Domain Adaptation. IEEE Trans Pattern Anal Mach Intell. 2019;41: 801–814. doi:10.1109/TPAMI.2018.2814042

30. Ganin Y, Lempitsky V. Unsupervised Domain Adaptation by Backpropagation. 2014 [cited 19 Jul 2022]. doi:10.48550/arXiv.1409.7495

31. Liu M-Y, Tuzel O. Coupled Generative Adversarial Networks. Advances in Neural Information Processing Systems. Curran Associates, Inc.; 2016. Available: https://papers.nips.cc/paper/2016/hash/502e4a16930e414107ee22b6198c578f-Abstract.html

32. Ghifary M, Kleijn WB, Zhang M, Balduzzi D, Li W. Deep Reconstruction-Classification Networks for Unsupervised Domain Adaptation. In: Leibe B, Matas J, Sebe N, Welling M, editors. Computer Vision – ECCV 2016. Cham: Springer International Publishing; 2016.

pp. 597–613. doi:10.1007/978-3-319-46493-0_36

33. Cochran K, Srivastava D, Shrikumar A, Balsubramani A, Hardison RC, Kundaje A, et al. Domain-adaptive neural networks improve cross-species prediction of transcription factor binding. Genome Res. 2022;32: 512–523. doi:10.1101/gr.275394.121

34. Boyko AR, Williamson SH, Indap AR, Degenhardt JD, Hernandez RD, Lohmueller KE, et al. Assessing the Evolutionary Impact of Amino Acid Mutations in the Human Genome. PLOS Genet. 2008;4: e1000083. doi:10.1371/journal.pgen.1000083

35. Gronau I, Hubisz MJ, Gulko B, Danko CG, Siepel A. Bayesian inference of ancient human demography from individual genome sequences. Nat Genet. 2011;43: 1031–1034. doi:10.1038/ng.937

36. Tennessen JA, Bigham AW, O'Connor TD, Fu W, Kenny EE, Gravel S, et al. Evolution and Functional Impact of Rare Coding Variation from Deep Sequencing of Human Exomes. Science. 2012;337: 64–69. doi:10.1126/science.1219240

37. Bersaglieri T, Sabeti PC, Patterson N, Vanderploeg T, Schaffner SF, Drake JA, et al. Genetic Signatures of Strong Recent Positive Selection at the Lactase Gene. Am J Hum Genet. 2004;74: 1111–1120. doi:10.1086/421051

38. Lyssenko V, Lupi R, Marchetti P, Guerra SD, Orho-Melander M, Almgren P, et al. Mechanisms by which common variants in the *TCF7L2* gene increase risk of type 2 diabetes. J Clin Invest. 2007;117: 2155–2163. doi:10.1172/JCI30706

39. Spellicy CJ, Harding MJ, Hamon SC, Mahoney JJ, Reyes JA, Kosten TR, et al. A variant in ANKK1 modulates acute subjective effects of cocaine: a preliminary study. Genes Brain Behav. 2014;13: 559–564. doi:10.1111/gbb.12121

40. Frayling TM, Timpson NJ, Weedon MN, Zeggini E, Freathy RM, Lindgren CM, et al. A common variant in the FTO gene is associated with body mass index and predisposes to childhood and adult obesity. Science. 2007;316: 889–894. doi:10.1126/science.1141634

41. Sulem P, Gudbjartsson DF, Stacey SN, Helgason A, Rafnar T, Magnusson KP, et al. Genetic determinants of hair, eye and skin pigmentation in Europeans. Nat Genet. 2007;39: 1443–1452. doi:10.1038/ng.2007.13

42. Eriksson N, Macpherson JM, Tung JY, Hon LS, Naughton B, Saxonov S, et al. Web-Based, Participant-Driven Studies Yield Novel Genetic Associations for Common Traits. PLOS Genet. 2010;6: e1000993. doi:10.1371/journal.pgen.1000993

43. Han J, Kraft P, Nan H, Guo Q, Chen C, Qureshi A, et al. A Genome-Wide Association Study Identifies Novel Alleles Associated with Hair Color and Skin Pigmentation. PLOS Genet. 2008;4: e1000074. doi:10.1371/journal.pgen.1000074

44. Sturm RA, Duffy DL, Zhao ZZ, Leite FPN, Stark MS, Hayward NK, et al. A Single SNP in an Evolutionary Conserved Region within Intron 86 of the HERC2 Gene Determines Human Blue-Brown Eye Color. Am J Hum Genet. 2008;82: 424–431. doi:10.1016/j.ajhg.2007.11.005

45. Kenny EE, Timpson NJ, Sikora M, Yee M-C, Moreno-Estrada A, Eng C, et al. Melanesian blond hair is caused by an amino acid change in TYRP1. Science. 2012;336: 554. doi:10.1126/science.1217849

46. Liu F, Wollstein A, Hysi PG, Ankra-Badu GA, Spector TD, Park D, et al. Digital Quantification of Human Eye Color Highlights Genetic Association of Three New Loci. PLOS Genet. 2010;6: e1000934. doi:10.1371/journal.pgen.1000934

47. Stern AJ, Wilton PR, Nielsen R. An approximate full-likelihood method for inferring selection and allele frequency trajectories from DNA sequence data. PLOS Genet. 2019;15: e1008384. doi:10.1371/journal.pgen.1008384

48. Yoshiura K, Kinoshita A, Ishida T, Ninokata A, Ishikawa T, Kaname T, et al. A SNP in the ABCC11 gene is the determinant of human earwax type. Nat Genet. 2006;38: 324–330. doi:10.1038/ng1733

49. Mathieson S, Mathieson I. FADS1 and the Timing of Human Adaptation to Agriculture. Mol

Biol Evol. 2018;35: 2957–2970. doi:10.1093/molbev/msy180

50. Mathieson I. Estimating time-varying selection coefficients from time series data of allele frequencies. 2020 Nov p. 2020.11.17.387761. doi:10.1101/2020.11.17.387761

51. Isobe T, Jia X, Chen S, He J, Shi Y, Liu J, et al. Multi-Target Domain Adaptation With Collaborative Consistency Learning. 2021. pp. 8187–8196. Available: https://openaccess.thecvf.com/content/CVPR2021/html/Isobe_Multi-Target_Domain_Adaptation_With_Collaborative_Consistency_Learning_CVPR_2021_paper.html

52. Nguyen-Meidine LT, Belal A, Kiran M, Dolz J, Blais-Morin L-A, Granger E. Unsupervised Multi-Target Domain Adaptation Through Knowledge Distillation. 2021. pp. 1339–1347. Available: https://openaccess.thecvf.com/content/WACV2021/html/Le_Thanh_Nguyen-Meidine_Unsupervised_Multi-Target_Domain_Adaptation_Through_Knowledge_Distillation_WACV_2021_paper.html

53. Roy S, Krivosheev E, Zhong Z, Sebe N, Ricci E. Curriculum Graph Co-Teaching for Multi-Target Domain Adaptation. 2021. pp. 5351–5360. Available: https://openaccess.thecvf.com/content/CVPR2021/html/Roy_Curriculum_Graph_Co-Teaching_for_Multi-Target_Domain_Adaptation_CVPR_2021_paper.html

54. Papers with Code. Domain Adaptation. [cited 1 Mar 2023]. Available: https://paperswithcode.com/task/domain-adaptation

55. Burger KE, Pfaffelhuber P, Baumdicker F. Neural networks for self-adjusting mutation rate estimation when the recombination rate is unknown. PLOS Comput Biol. 2022;18: e1010407. doi:10.1371/journal.pcbi.1010407

56. Johri P, Aquadro CF, Beaumont M, Charlesworth B, Excoffier L, Eyre-Walker A, et al. Recommendations for improving statistical inference in population genomics. PLOS Biol. 2022;20: e3001669. doi:10.1371/journal.pbio.3001669

57. Speidel L, Forest M, Shi S, Myers SR. A method for genome-wide genealogy estimation for thousands of samples. Nat Genet. 2019;51: 1321–1329. doi:10.1038/s41588-019-0484-x

58. Campagna L, Mo Z, Siepel A, Uy JAC. Selective sweeps on different pigmentation genes mediate convergent evolution of island melanism in two incipient bird species. PLOS Genet. 2022;18: e1010474. doi:10.1371/journal.pgen.1010474

59. Kim J, Rosenberg NA, Palacios JA. Distance metrics for ranked evolutionary trees. Proc Natl Acad Sci. 2020;117: 28876–28886. doi:10.1073/pnas.1922851117

60. Kern AD, Schrider DR. Discoal: flexible coalescent simulations with selection. Bioinformatics. 2016;32: 3839–3841. doi:10.1093/bioinformatics/btw556

61. Kong A, Thorleifsson G, Gudbjartsson DF, Masson G, Sigurdsson A, Jonasdottir A, et al. Fine-scale recombination rate differences between sexes, populations and individuals. Nature. 2010;467: 1099–1103. doi:10.1038/nature09525

62. Wilde S, Timpson A, Kirsanow K, Kaiser E, Kayser M, Unterländer M, et al. Direct evidence for positive selection of skin, hair, and eye pigmentation in Europeans during the last 5,000 y. Proc Natl Acad Sci. 2014;111: 4832–4837. doi:10.1073/pnas.1316513111

63. Harding RM, Healy E, Ray AJ, Ellis NS, Flanagan N, Todd C, et al. Evidence for Variable Selective Pressures at MC1R. Am J Hum Genet. 2000;66: 1351–1361. doi:10.1086/302863

64. Ohashi J, Naka I, Tsuchiya N. The Impact of Natural Selection on an ABCC11 SNP Determining Earwax Type. Mol Biol Evol. 2011;28: 849–857. doi:10.1093/molbev/msq264

 Figures

Figure 1. Unsupervised domain adaptation in the context of population genetic
inference. A) A high-level overview of the supervised machine-learning approach for
population genetic inference and how domain adaptation fits into the paradigm. **B)**
Example formulations of the unsupervised domain adaptation problem with application to
computer vision and population genetics. Note that in the specific case of SIA, which uses
features of the ARG, the source domain data always consist of *true* genealogies
generated in simulations, whereas the target domain data always consist of *inferred*
genealogies reconstructed from observed sequence data. **C)** Four benchmarking
scenarios considered in this study. The original model was both trained and tested on
source domain data (simulation benchmark), both trained and tested on target domain
data (hypothetical true model), or trained on source domain data but applied to target
domain data (standard model application). These three cases contextualize the
performance of the domain-adaptive model (see **Methods** for details). Gold squares
represent source domain data, blue circles represent target domain data and crosses (**x**)
represent labels.

Figure 2. Neural network architecture for domain adaptation. The model
architectures incorporating gradient reversal layers (GRLs) for **A)** SIA and **B)** ReLERNN.
The feature extractor of SIA contains 1.49×10^5 trainable parameters, whereas the label
predictor and domain classifier contains 1.22×10^8 each. The feature extractor of
ReLERNN contains 1.52×10^6 trainable parameters, whereas the label predictor and
domain classifier contains 1.49×10^5 each. Note that batch normalization layers, which
contain trainable parameters, are not shown in the figure. **C)** When training the networks,
each minibatch of training data consists of two components: (1) labeled data from the
source domain fed through the feature extractor and the label predictor; and (2) a mixture
of unlabeled data from both the source and target domains fed through the feature
extractor and the domain classifier. The first component trains the model to perform its
designated task. However, the GRL inverts the loss function for the second component,
discouraging the model from differentiating the two domains and leading to the extraction
of "domain-invariant" features.

Figure 3. Performance of domain-adaptive SIA models. Results are shown from (**A, B**) the background-selection and (**C, D**) the demography-mis-specification experiments. (**A, C**) Precision-recall curves for sweep classification. (**B, D**) Contour plots summarizing true (horizontal axis) vs. inferred (vertical axis) selection coefficients (*s*) for the standard (gold) and domain adaptive (turquoise) models as evaluated on the held-out test dataset. The ridge along the horizontal axis of each contour is traced by a dashed line, representing the mode of the inferred value for each true value of *s*. Raw data underlying the contour plots are presented in **Fig. S2**. See **Fig. 1C** for definition of the model labels.

Figure 4. Performance of domain-adaptive ReLERNN models. Results are shown
from (**A**) the background-selection and (**B**) the demography-mis-specification
experiments. Each contour plot summarizes true (horizontal axis) vs. inferred (vertical
axis) recombination rates (ρ) for the standard (gold) and domain adaptive (turquoise)
models as evaluated on the held-out test dataset. The ridge along the horizontal axis of
each contour is traced by a dashed line, representing the mode of the inferred value for
each true value of ρ. Raw data underlying the contour plots are presented in **Fig. S4**.

Figure 5. Performance of domain-adaptive SIA (dadaSIA) model with different degrees of mis-specification. The performance of the model on the sweep classification task is quantified by the area under the precision-recall curve (AUPRC) (**A**). Performance on the selection-coefficient inference task is quantified by root mean squared error (RMSE) (**B**). In the "tree inference only" case, there is no mis-specification other than that caused by error in genealogy inference. In the "extreme" case, mis-specification consists of a 5% bottleneck, background selection and an 8-fold mis-specification in recombination rate. See **Fig. S4** for illustrations of the different bottlenecks and **Methods** for details.

Tables

Table 1. Selection coefficients in the European population estimated by domain-adaptive SIA compared to previous estimates

Gene	SNP	Estimates of selection coefficient		
		Domain-adaptive SIA	SIA* [12]	Previous estimates
KITLG	rs12821256	0.0035	0.0019	0.0161 [47]
ASIP	rs619865	0.0057	0.0019	0.0974 [47]
TYR	rs1393350	0.0028	0.0011	0.0112 [47]
OCA2	rs12913832	0.0093	0.0056	0.002 [47]; 0.036 [62]
MC1R	rs1805007	0.0027	0.0037	No selection [63]
ABCC11	rs17822931	0.0020	0.00035	~ 0.01 in East Asian [64]
LCT	rs4988235	0.0097	0.010	~ 0.01 [37,49,50]
TYRP1	rs13289810	$P_{neu} > 0.5$	$P_{neu} > 0.5$	No selection [47]
TTC3	rs1003719	$P_{neu} > 0.5$	$P_{neu} > 0.5$	No selection [47]
TCF7L2	rs7903146	$P_{neu} > 0.5$	$P_{neu} > 0.5$	N/A
ANKK1	rs1800497	$P_{neu} > 0.5$	$P_{neu} > 0.5$	N/A
FTO	rs9939609	$P_{neu} > 0.5$	$P_{neu} > 0.5$	N/A

* The original SIA model in [12] uses genealogies *inferred* from simulations for training, despite the availability of ground truth genealogies.