Predicting individual traits from models of brain dynamics accurately and reliably using the Fisher kernel

Ahrends C[1], Woolrich M[2], & Vidaurre D[1,2]

[1] Center of Functionally Integrative Neuroscience, Department of Clinical Medicine, Aarhus University, Aarhus, Denmark

[2] Oxford Centre for Human Brain Activity, Department of Psychiatry, University of Oxford, Oxford, United Kingdom

Abstract

Predicting an individual's cognitive traits or clinical condition using brain signals is a central goal in modern neuroscience. This is commonly done using either structural aspects, or aggregated measures of brain activity that average over time. But these approaches are missing what can be the most representative aspect of these complex human features: the uniquely individual ways in which brain activity unfolds over time, that is, the dynamic nature of the brain. The reason why these dynamic patterns are not usually taken into account is that they have to be described by complex, high-dimensional models; and it is unclear how best to use information from these models for a prediction. We here propose an approach that describes dynamic functional connectivity and amplitude patterns using a Hidden Markov model (HMM) and combines it with the Fisher kernel, which can be used to predict individual traits. The Fisher kernel is constructed from the HMM in a mathematically principled manner, thereby preserving the structure of the underlying HMM. In this way, the unique, individual signatures of brain dynamics can be explicitly leveraged for prediction. We here show in fMRI data that the HMM-Fisher kernel approach is not only more accurate, but also more reliable than other methods, including ones based on time-averaged functional connectivity. This is important because reliability is critical for many practical applications, especially if we want to be able to meaningfully interpret model errors, like for the concept of brain age. In summary, our approach makes it possible to leverage information about an individual's brain dynamics for prediction in cognitive neuroscience and personalised medicine.

1 Introduction

Observing a person's behaviour over time is how we understand the individual's personality, cognitive traits, or psychiatric condition such as schizophrenia or depression. The same applies at the brain level, by observing the patterns by which its activity unfolds over time. However, although research into brain dynamics has gained traction over the last years, there is currently no established methodology to use this level of description to characterise subject differences or predict individual traits. Since brain dynamics are not an explicit feature of the data, intermediate representations of the dynamics are used as features for prediction. These representations can be estimated from modalities such as fMRI or MEG using models of varying complexity (Lurie et al., 2019), and are usually parametrised by a high number of parameters with complex mathematical relationships between them that reflect the model assumptions. How to leverage these parameters for prediction is an open question.

We here propose the Fisher kernel for predicting individual traits from brain dynamics, using information of how brain activity fluctuates over time during unconstrained cognition —that is, during wakeful rest. We focus on models of brain dynamics that capture within-session changes in functional connectivity and amplitude from fMRI scans, and how the parameters from these models can be used to predict behavioural variables or traits. In particular, we use the Hidden Markov Model (HMM) as a model of time-varying amplitude and functional connectivity (FC) dynamics (Vidaurre et al., 2017), which was previously shown to be able to predict certain subject traits, such as fluid intelligence, more accurately than structural or static (time-averaged) FC representations (Vidaurre et al., 2021). Specifically, the Fisher kernel allows using the entire set of parameters of a generative probabilistic model of brain dynamics in a computationally efficient way. It takes the complex relationships between the parameters into account, preserving the structure of the underlying model of brain dynamics (here, the HMM) (Jaakkola et al., 1999; Jaakkola & Haussler, 1998).

For empirical evaluation, we consider two criteria that are important in both scientific and practical applications. First, predictions should be as accurate as possible; i.e., the correlation between predicted and actual values should be high. Second, they should be reliable, in the sense that a predictive model should never produce excessively large errors, and the outcome should be robust to the choice of which subjects are included in the training set. The latter criterion is especially important if we want to be able to meaningfully interpret prediction errors, e.g., in assessing brain age (Cole & Franke, 2017; Denissen et al., 2022; Smith et al., 2019). Despite this crucial role in interpreting model errors, reliability is not often taken into account in models predicting individual traits from neuroimaging features.

In summary, we show that using the Fisher kernel approach, which preserves the complex
structure of the underlying HMM, we can predict individual traits from brain dynamics
accurately and reliably. We show that our approach significantly outperforms methods that
do not take the mathematical structure of the model into account, as well as methods based
on time-averaged FC that do not consider brain dynamics. For interpretation, we also
investigate which aspects of the brain dynamics drive the prediction accuracy. Bringing
accuracy, reliability and interpretation together, this work therefore opens possibilities for
practical applications such as the development of biomarkers and the investigation of
individual differences in cognitive traits.

77   **2   Methods**

We here aim to predict behavioural and demographic variables from a model of brain
dynamics using different kernel functions. The general workflow is illustrated in **Figure 1**. We
start with the concatenated fMRI time-series of a group of subjects (**Figure 1**, step 1). We
estimate a state-space model of brain dynamics at the group level, where the state
descriptions, initial state probabilities, and the state transition probability matrix are shared
across subjects (**Figure 1**, step 2). Next, we estimate subject-specific versions of this group-
level brain dynamics model by dual estimation, where the group-level HMM parameters are
re-estimated to fit the individual-level timeseries (Vidaurre et al., 2021) (**Figure 1**, step 3).
Next, we use this description of the individuals' brain dynamics to predict their individual
traits. For this, we first map the parameters from the model of brain dynamics into a feature
space (**Figure 1**, step 4). This works in different ways for the different kernels: In the naïve
kernel (step 4a), the features are simply the parameters in the Euclidean space; while in the
Fisher kernel (step 4b), the features are mapped into the gradient space. We then estimate
the similarity between each pair of subjects in this feature space using kernel functions.
Finally, we use these kernels to predict the behavioural variables using kernel ridge
regression (**Figure 1**, step 5). The first three steps are identical for all kernels and therefore
carried out only once. The fourth step (mapping the examples and constructing the kernels)
is carried out once for each of the different kernels. The last step is repeated 3,500 times for
each kernel to predict a set of 35 different behavioural variables using 100 randomised
iterations of 10-fold nested cross validation. We evaluate 24,500 predictive models using
different kernels constructed from the same model of brain dynamics in terms of their ability
to predict phenotypes, as well as 14,000 predictive models based on time-averaged
features.

Figure 1 Workflow of the Fisher kernel prediction approach. To generate a description of brain dynamics, we (1) concatenate all subjects' individual timeseries; then (2) estimate a Hidden Markov Model (HMM) on these timeseries to generate a group-level description of brain dynamics; then (3) dual-estimate into subject-level HMM models. Steps 1-3 are the same for all kernels. In order to then use this description of all subjects' individual brain dynamics, we map each subject into a feature space (4). This mapping can be done in different ways: In the naïve kernels (a), the manifold on which the parameters lie is ignored and examples are treated as if they were in Euclidean space. The Fisher kernel (b), on the other hand, reflects the structure of the parameters in their original Riemannian manifold by working in the gradient space. We then construct kernel matrices κ, where each pair of subjects has a similarity value given their parameters in the respective embedding space. Finally, we feed κ to kernel ridge regression to predict a variety of demographic and behavioural traits in a cross-validated fashion (5).

2.1 HCP imaging and behavioural data

We used data from the open-access Human Connectome Project (HCP) S1200 release (Smith, Beckmann, et al., 2013; Van Essen et al., 2013), which contains MR imaging data and various demographic and behavioural data from 1,200 healthy, young adults (age 22-35). All data described below, i.e., timecourses of the resting-state fMRI data and demographic and behavioural variables, are publicly available at https://db.humanconnectome.org.

Specifically, we used resting state fMRI data of 1,001 subjects, for whom any of the

behavioural variables of interest were available. Each participant completed four resting

state scanning sessions of 14 mins and 33 seconds duration each. This resulted in 4,800

timepoints per subject. For the main results, we used all four resting state scanning sessions

of each participant to fit the model of brain dynamics (but see **Supplementary Figure 1** for

results with just one session). The acquisition parameters are described in the HCP

acquisition protocols and in Van Essen et al. (2013); Van Essen et al. (2012). Briefly,

structural and functional MRI data were acquired on a 3T MRI scanner. The resting state

fMRI data was acquired using multiband echo planar imaging sequences with an

acceleration factor of 8 at 2 mm isotropic spatial resolution and a repetition time (TR) of 0.72

seconds. The preprocessing and timecourse extraction pipeline is described in detail in

Smith, Beckmann, et al. (2013). For the resting state fMRI scans, preprocessing consisted of

minimal spatial preprocessing and surface projection (Glasser et al., 2013), followed by

temporal preprocessing. Temporal preprocessing consisted of single-session Independent

Component Analysis (ICA) (Beckmann, 2012) and removal of noise components (Griffanti et

al., 2014; Salimi-Khorshidi et al., 2014). Data were high-pass-filtered with a cut-off at 2,000

seconds to remove linear trends.

The parcellation was estimated from the data using multi-session spatial ICA on the

temporally concatenated data from all subjects. Using this approach, a data-driven functional

parcellation with 50 parcels was estimated, where all voxels are weighted according to their

activity in each parcel, resulting in a weighted, overlapping parcellation. While other

parcellations are available for the resting-state fMRI HCP dataset, we chose this parcellation

because dynamic changes in FC can be better detected in this parcellation compared to

other functional or anatomical parcellations or more fine-grained parcellations (Ahrends et

al., 2022). Timecourses were extracted using dual regression (Beckmann et al., 2009),

where group-level components are regressed onto each subject's fMRI data to obtain

subject-specific versions of the parcels and their timecourses. We normalised the

timecourses of each subject to ensure that the model of brain dynamics and, crucially, the

kernels were not driven by (averaged) amplitude and variance differences between subjects.

Subjects in the HCP study completed a range of demographic and behavioural

questionnaires. Following Vidaurre et al. (2021), we here focus on a subset of those items,

including age and various cognitive variables. The cognitive variables span items assessing

memory, executive function, fluid intelligence, language, processing speed, spatial

orientation, and attention. The full list of the 35 behavioural variables used here, as well as

their categorisation within the HCP dataset can be found in **Supplementary Table 1**.

2.2 The Hidden Markov Model as a model of brain dynamics

To estimate brain dynamics, we here use the Hidden Markov Model (Vidaurre et al., 2016; Vidaurre et al., 2017). However, the kernels, which are explained in detail in the following section, can be constructed from any generative probabilistic model.

The Hidden Markov model (HMM) is a generative probabilistic model, which assumes that an observed time-series, such as BOLD signal in a given parcellation, was generated by a sequence of "hidden states" (Baum & Eagon, 1967; Baum & Petrie, 1966). We here model the states as Gaussian distributions, defined both in terms of mean and covariance —which can be interpreted as distinct patterns of amplitude and FC (Vidaurre et al., 2017). Since we are often interested in modelling time-varying FC specifically, we repeated all computations for a variety of the HMM where state means were pinned to zero (given that the data was demeaned and the global average is zero) and only the covariance was allowed to vary across states (Vidaurre et al., 2017), which is shown in **Supplementary Figure 2**.

The HMM is described by a set of parameters θ, containing the state probabilities π, the transition probabilities A, the mean vectors μ of all states, and the covariance matrices σ of all states:

$$\theta = [\pi, A, \mu, \sigma] \qquad \pi \in \mathbb{R}^{1 \mathrm{x} K}, A \in \mathbb{R}^{K \mathrm{x} K}, \mu \in \mathbb{R}^{K \mathrm{x} M}, \sigma \in \mathbb{R}^{K \mathrm{x} M \mathrm{x} M}$$

where K is the number of states and M is the number of parcels in the parcellation. The entire set of parameters θ is estimated from the data. Here, we chose a small number of states, $K = 6$, to ensure that the group-level HMM states are general enough to be found in all subjects, since a larger number of states increases the chances of certain states being present only in a subset of subjects. Note that the same HMM estimation is used for all kernels.

The HMM is a generative model. The generative process in this case works by sampling from a Gaussian distribution with mean μ_k and covariance σ_k when state k is active:

$$X_t | q_t = k \sim N(\mu_k, \sigma_k)$$

where q_t is the currently active state. Which state is active depends on the previous state q_{t-1} and is determined by the transition probabilities A, so that the generated state sequence is sampled from a categorical distribution with parameters:

$$q_t | q_{t-1} = k \sim Cat(A_k)$$

where A_k indicates the k-th row of the transition probability matrix.

The space of parameters θ forms a Riemannian manifold R_θ, where the relationships

between the different parameters of the HMM are acknowledged by construction. The Fisher

kernel, as described below, is built upon a projection on this manifold, so predictions based

on this kernel account for the mathematical structure of the HMM.

Here, we fit the HMM to the concatenated timeseries of all N subjects (see **Figure 1a**, step

1). We refer to the group-level estimate as HMM^0, which is defined by the parameters θ^0

(see **Figure 1a**, step 2):

$$\theta^0 = [\pi^0, A^0, \mu^0, \sigma^0]$$

In order to use the information from the HMM to predict subjects' phenotypes, we estimate

subject-specific versions of the group-level HMM (see **Figure 1a**, step 3) through dual

estimation (Vidaurre et al., 2017). Dual estimation refers to the process of fitting the

previously estimated group-level model again to a single subject's timeseries, so that the

parameters from the group-level model HMM^0 are adapted to fit the individual. We will refer

to the subject-specific estimate for subject n as HMM^n, with parameters θ^n.

These subject-specific HMM parameters are the features that we construct kernels from. To

understand which features are most important for the predictions, we also construct versions

of the kernels that include only subsets of the features. Specifically, we can group the

features into two subsets: 1. the state features, describing *what* states look like, containing

the mean vectors μ, and the covariance matrices σ of all states, and 2. the transition

features, describing *how* individuals transition between these states, containing the initial

state probabilities π and the transition probabilities A. By removing one or the other set of

features and evaluating how model performance changes compared to the full kernels, we

can draw conclusions about the importance of these two different types of changes for the

predictions. Since the state features are considerably more numerous than the transition

features (15,300 state features compared to 42 transition features in this case), we also

construct a version of the kernels where state features have been reduced to the same

number as the transition features using PCA, i.e., we use all 42 transition features and the

first 42 PCs of the state features.

2.3 Kernels from Hidden Markov Models

Kernels (Shawe-Taylor & Cristianini, 2004) are a convenient approach to work with high-

dimensional, complex features, such as parameters from a model of brain dynamics. In

general, kernels are similarity functions between subjects, and they can be used

straightforwardly in a prediction algorithm. While feature matrices can be very high

dimensional, a kernel is represented by a (no. of subjects by no. of subjects) matrix. Kernel

methods can readily be adapted to deal with nonlinear decision boundaries in prediction, by

projecting the data into a high-dimensional (possibly infinite-dimensional) space through an

embedding $x \rightarrow \phi_x$; then, by estimating a linear separating hyperplane on this space, we can

effectively have a nonlinear estimator on the original space (Shawe-Taylor & Cristianini,

2004). In practice, instead of working explicitly in a higher-dimensional embedding space,

the so-called kernel trick uses a kernel function $\kappa(n, m)$ containing the similarity between

data points n and m (here, subjects) in the higher-dimensional embedding space (Schölkopf

et al., 2002; Shawe-Taylor & Cristianini, 2004), which can be simpler to calculate. Once $\kappa(\cdot, \cdot)$

is computed for each pair of subjects, this is all that is needed for the prediction. This makes

kernels computationally very efficient, since in most cases the number of subjects will be

smaller than the number of features —which, in the case of HMMs, can be very large

(potentially, in the order of millions). However, finding the right kernel can be a challenge

because there are many available alternatives for the embedding.

Here, in combination with a linear predictive model, we apply a kernel that is specifically

conceived to be used to compare instances of a generative model like the HMM. We

expected that this will result in better predictions than existing methods. Using the same

HMM estimate, we compare three different kernels, which map the HMM parameters into

three distinct spaces, corresponding to different embeddings (see **Figure 1b**, step 4): the

naïve kernel, the naïve normalised kernel, and the Fisher kernel. While the first two kernels

(naïve and naïve normalised kernel) do not take the relationships between the HMM's

parameters into account, the Fisher kernel preserves the structure of the HMM and weights

the parameters according to how much they contribute to generating a particular subject's

timeseries. We then construct linear and Gaussian versions of the different kernels (see

Figure 1b, step 5), which take the general form $\kappa_l(n, m) = {\phi_x}_n^T {\phi_x}_m$ for the linear kernel and

$\kappa_g(n, m) = exp\left(-\frac{\|{\phi_x}_n - {\phi_x}_m\|^2}{2\tau^2}\right)$ for the Gaussian kernel. We compare these to a kernel

constructed using Kullback-Leibler divergence, previously used for predicting behavioural

phenotypes (Vidaurre et al., 2021).

2.3.1   Naïve kernel

The naïve kernel is based on a simple vectorisation of the subject-specific version of the

HMM's parameters, each on their own scale. This means that the kernel does not take

relationships between the parameters into account and the parameters are here on different

scales. This procedure can be thought of as computing Euclidean distances between two

sets of HMM parameters, ignoring the actual geometry of the space of parameters. For each

subject n, we vectorise parameters θ^n obtained through dual estimation of the group-level

parameters θ^0 to map the example $x^n \rightarrow \phi_{x^n}$ to:

$$\theta^n = (\pi^n, A^n, \mu^n, \sigma^n) \qquad\qquad \theta^n \in \mathbb{R}^{1x(K+K*K+K*M+K*M*M)}$$

We will refer to this vectorised version of the subject-specific HMM parameters as "naïve θ".

The naïve θ are the features used in the naïve kernel κ_N. We first construct a linear kernel

from the naïve θ features using the inner product of the feature vectors. The linear naïve

kernel κ_{Nl} between subjects n and m is thus defined as:

$$\kappa_{Nl}(n,m) = \langle \theta^n, \theta^m \rangle \qquad\qquad \kappa_{Nl} \in \mathbb{R}^{NxN}$$

where $\langle \theta^n, \theta^m \rangle$ denotes the inner product between θ^n and θ^m. Using the same feature

vectors, we can also construct a Gaussian kernel from the naïve θ. The Gaussian naïve

kernel κ_{Ng} for subjects n and m is defined as:

$$\kappa_{Ng}(n,m) = \exp\left(-\frac{\|\theta^n - \theta^m\|^2}{2\tau^2}\right) \qquad\qquad \kappa_{Ng} \in \mathbb{R}^{NxN}$$

where τ is the radius of the radial basis function, and $\|\theta^n - \theta^m\|$ is the L$_2$-norm of the

difference of the feature vectors (naïve θ for subjects n and m). Compared to a linear kernel,

a Gaussian kernel embeds the features into a more complex space, which can potentially

improve the accuracy. However, this kernel has an additional parameter τ that needs to be

chosen, typically through cross-validation. This makes a Gaussian kernel computationally

more expensive and, if the additional parameter τ is poorly estimated, more error prone. The

effect of the hyperparameters on errors is shown in **Supplementary Figure 3**.

While the naïve kernel takes all the information from the HMM into account by using all

parameters from a subject-specific version of the model, it uses these parameters in a way

that ignores the structure of the model that these parameters come from. In this way, the

different parameters in the feature vector are difficult to compare, since e.g., a change of 0.1

in the transition probabilities between two states is not of the same magnitude as a change

of 0.1 in one entry of the covariance matrix of a specific state. In the naïve kernel, these two

very different types of changes would be treated indistinctly.

2.3.2 Naïve normalised kernel

To address the problem of parameters being on different scales, the naïve normalised kernel

makes the scale of the subject-specific vectorised parameters (i.e., the naïve θ) comparable

across parameters. Here, the mapping $x \rightarrow \phi_x$ consists of a vectorisation and normalisation

across subjects of the subject-specific HMM parameters, by subtracting the mean over

subjects from each parameter and dividing by the standard deviation. This kernel does not
respect the geometry of the space of parameters either.

As for the naïve kernel, we can then construct a linear kernel from these vectorised,
normalised parameters $\tilde{\theta}$ by computing the inner product for all pairs of subjects n and m to
obtain the linear naïve normalised kernel κ_{NNl}:

285
$$\kappa_{NNl}(n, m) = \langle \tilde{\theta}^n, \tilde{\theta}^m \rangle \qquad\qquad \kappa_{NNl} \in \mathbb{R}^{NxN}$$

286 We can also compute a Gaussian kernel from the naïve normalised feature vectors to obtain
287 the Gaussian version of the naïve normalised kernel κ_{NNg}:

288
$$\kappa_{NNg}(n, m) = \exp\left(-\frac{\|\tilde{\theta}^n - \tilde{\theta}^m\|^2}{2\tau^2}\right) \qquad\qquad \kappa_{NNg} \in \mathbb{R}^{NxN}$$

In this way, we have constructed a kernel in which parameters are all on the same scale, but
which still ignores the complex relationships between parameters originally encoded by the
underlying model of brain dynamics.

2.3.3 Fisher kernel

The Fisher kernel (Jaakkola et al., 1999; Jaakkola & Haussler, 1998) is specifically designed
to preserve the structure of a generative probabilistic model (here, the HMM). This can be
thought of as a "proper" projection on the manifold, as illustrated in **Figure 1b**, step 4b.
Similarity between subjects is here defined in reference to a group-level model of brain
dynamics. The mapping $x \rightarrow \phi_x$ is given by the "Fisher score", which indicates how (i.e., in
which direction in the Riemannian parameter space) we would have to change the group-
level model to better explain a particular subject's timeseries. The similarity between
subjects can then be described based on this score, so that two subjects are defined as
similar if the group-level model would have to be changed in a similar direction for both, and
dissimilar otherwise.

More precisely, the Fisher score is given by the gradient of the log-likelihood with respect to
each model parameter:

305
$$g(\theta^0, x^n) = \left(\frac{\partial \log \mathcal{L}_{\theta^0}(x^n)}{\partial \theta^0}\right) \qquad\qquad g \in \mathbb{R}^{1x(K+K*K+K*M+K*M*M)}$$

where x^n is the timeseries of subject n, and $\mathcal{L}_\theta(x) = P(x|\theta)$ represents the likelihood of the
timeseries x given the model parameters θ. This way, the Fisher score maps an example
(i.e., a subject's timeseries) x^n into a point in the gradient space of the Riemannian manifold
R_θ defined by the HMM parameters.

The invariant Fisher kernel κ_{F-} is the inner product of the Fisher score g, scaled by the

Fisher information matrix F, which gives a local metric on the Riemannian manifold R_θ:

$$\kappa_{F-}(n, m) = g(\theta^0, x^n)^{\mathrm{T}} F_{R_\theta}^{-1} g(\theta^0, x^m) \qquad \kappa_{F-} \in \mathbb{R}^{NxN}$$

for subjects n and m. F_{R_θ} is the Fisher information matrix, defined as

$$F_{R_\theta} = \mathbb{E}_x[g(\theta^0, x)g(\theta^0, x)^{\mathrm{T}}]$$

314 where the expectation is with respect to x under the distribution $P(x|\theta)$. The Fisher

315 information matrix F_{R_θ} can be approximated empirically:

$$\hat{F}_{R_\theta} = \frac{1}{N}\sum_{i=1}^{N} g(\theta^0, x^i)g(\theta^0, x^i)^{\mathrm{T}}$$

which is simply the covariance matrix of the gradients g. Using $\hat{F}_{R_\theta}$ essentially serves to

whiten the gradients; therefore, given the large computational cost associated with $\hat{F}_{R_\theta}$, we

here disregard the Fisher information matrix and reduce the invariant Fisher kernel to the so-

called practical Fisher kernel (Jaakkola et al., 1999; Jaakkola & Haussler, 1998; van der

Maaten, 2011), for which the linear version κ_{Fl} takes the form:

$$\kappa_{Fl}(n, m) = \langle g(\theta^0, x^n), g(\theta^0, x^m) \rangle \qquad \kappa_{Fl} \in \mathbb{R}^{NxN}$$

In this study, we will use the practical Fisher kernel for all computations.

One issue when working with the linear Fisher kernel is that the gradients of typical

examples (i.e., subjects whose timeseries can be described by similar parameters as the

group-level model) are close to zero, while gradients of atypical examples (i.e., subjects who

are very different from the group-level model) can be very large. This may lead to an

underestimation of the similarity between two typical examples because their inner product is

very small, although they are very similar. To mitigate this, we can plug the gradient features

(i.e., the Fisher scores g) into a Gaussian kernel, which essentially normalises the kernel.

For subjects n and m, where x^n is the timeseries of subject n and x^m is the timeseries of

subject m, the Gaussian Fisher kernel κ_{Fg} is defined as

$$\kappa_{Fg}(n, m) = \exp\left(-\frac{\|g(\theta^0, x^n) - g(\theta^0, x^m)\|^2}{2\tau^2}\right) \quad \kappa_{Fg} \in \mathbb{R}^{NxN}$$

where $\|g(\theta^0, x^n) - g(\theta^0, x^m)\|$ is the distance between examples n and m in the gradient

space, and τ is the width of the Gaussian kernel.

 2.3.4   Kullback-Leibler divergence

Kullback-Leibler (KL) divergence is an information-theoretic distance measure which

estimates divergence between probability distributions —in this case between subject-

specific versions of the HMM. Here, KL divergence of subject n from subject m,

$\mathrm{KL}(\mathrm{HMM}^n || \mathrm{HMM}^m)$ can be interpreted as how much new information the HMM of subject n

contains if the true distribution was the HMM of subject m. KL divergence is not symmetric,

i.e., $\mathrm{KL}(\mathrm{HMM}^n || \mathrm{HMM}^m)$ is different than $\mathrm{KL}(\mathrm{HMM}^m || \mathrm{HMM}^n)$. We use an approximation of KL

divergence which is described in detail in Do (2003), as in Vidaurre et al. (2021). That is,

given two models HMM^n from HMM^m for subject n and subject m, we have

$$\mathrm{KL}(\mathrm{HMM}^n || \mathrm{HMM}^m) = \sum_k v_k KL(A_k^n, A_k^m) \ + \ v_k KL(G_k^n, G_k^m)$$

Where A_k^n are the transition probabilities from state k into any other state according to HMM^n

and G_k^n are the state Gaussian distributions for state k and HMM^n (respectively A_k^m and G_k^m

for HMM^m) (see MacKay et al. (2003)). Since the transition probabilities are Dirichlet-

distributed and the state distributions are Gaussian distributed, KL divergence for those has

a closed-form solution. Variables v_k can be computed numerically such that

$$vA^n = v,$$

$$\lim_{x \to \infty} \pi^n A^{n^x} = v$$

To be able to use KL divergence as a kernel, we symmetrise the KL divergence matrix as

$$\mathcal{D}_{KL}(n, m) = 0.5 \, \mathrm{KL}(\mathrm{HMM}^n || \mathrm{HMM}^m) + 0.5 \, \mathrm{KL}(\mathrm{HMM}^m || \mathrm{HMM}^n) \qquad \mathcal{D}_{KL} \in \mathbb{R}^{NxN}$$

This symmetrised KL divergence can be plugged into a radial basis function, analogous to

the Gaussian kernels to obtain a similarity matrix κ_{KL}

$$\kappa_{KL}(n, m) = \exp\left(-\frac{(\mathcal{D}_{KL}(n,m))^2}{2\tau^2}\right) \qquad \kappa_{KL} \in \mathbb{R}^{NxN}$$

The resulting KL similarity matrix can be used in the predictive model in a similar way as the

kernels described above.

2.4   Predictive model: Kernel ridge regression

Similarly to Vidaurre et al. (2021), we use kernel ridge regression (KRR) to predict

demographic and behavioural variables from the different kernels, although these could be

used in any kernel-based prediction model or classifier, such as a support vector machine,

which we demonstrate in simulations. KRR is the kernelised version of ridge regression
(Saunders et al., 1998):

$$\hat{y} = h\alpha \qquad \alpha \in \mathbb{R}^{S_{train}x1}, h \in \mathbb{R}^{S_{test}xS_{train}}$$

where α are the regression weights; h is the (number of subjects in test set by number of
subjects in training set) kernel matrix between the subjects in the training set and the
subjects in the test set; $\hat{y}$ are the predictions in the (out-of-sample) test set; S_{train} are the
number of subjects in the training set; and S_{test} are the number of subjects in the test set.
The regression weights α can be estimated using the kernels specified above as

$$\alpha = (\kappa + \lambda I)^{-1} * y \qquad \kappa \in \mathbb{R}^{S_{train}xS_{train}}$$

where λ is a regularisation parameter that we can choose through cross-validation; I is the
identity matrix; κ is the (S_{train} by S_{train}) kernel matrix of the subjects in the training set; and
y are the training examples.

We use KRR to separately predict each of the 35 demographic and behavioural variables
from each of the different methods, removing subjects with missing entries from the
prediction. The hyperparameters λ (and τ in the case of Gaussian kernels) were selected in
a nested cross-validated (CV) fashion using 10 folds for both inner and outer loops assigning
90% of the data to the training set and 10% to the test set for each fold. We used a CV
scheme to account for family structure in the HCP dataset so that subjects from the same
family were never split across folds (Winkler et al., 2015). We repeated the nested 10-fold
CV 100 times, so that different combinations of subjects were randomly assigned to the folds
at each new CV iteration to obtain a distribution of model performance values for each
variable. This is to explicitly show how susceptible each model was to changes in the
training folds, which we can take as a measure of the robustness of the estimators, as
described below.

2.4.1 Evaluation criteria

We evaluate the models in terms of two outcome criteria: prediction accuracy and reliability.
The first criterion, prediction accuracy, concerns how close the model's predictions were to
the true values on average. We here quantify prediction accuracy as Pearson's correlation
coefficient $r(\hat{y}, y)$ between the model-predicted values $\hat{y}$ and the actual values y of each
variable.

The second criterion, reliability, concerns two aspects: i) that the model will never show
excessively large errors for single subjects that could harm interpretation; and ii) that the
model's accuracy will be consistent across random variations of the training set —in this

case by using different (random) partitions for the CV folds. As mentioned, this is important if

we want to interpret prediction errors for example in clinical contexts, which assumes that

the error size of a model in a specific subject reflects something biologically meaningful, e.g.,

whether a certain disease causes the brain to "look" older to a model than the actual age of

the subject (Denissen et al., 2022). Maximum errors inform us about single cases where a

model (that may typically perform well) fails. The maximum absolute error (MAXAE) is the

single largest error made by the kernel ridge regression model in each iteration, i.e.,

$$MAXAE \ = \ \max_{i \in N}(|y_i - \hat{y}_i|)$$

401   Since the traits we predict are on different scales, the MAXAE is difficult to interpret, e.g., a

402   MAXAE of 10 would be considered small if the true range of the variable we are predicting

403   was 1,000, while it would be considered large if the true range of the variable was 1. To

404   make the results comparable across the different traits, we therefore normalise the MAXAE

405   by dividing it by the range of the respective variable. In this way, we obtain the NMAXAE:

$$NMAXAE \ = \ \frac{MAXAE}{y_{max} - y_{min}}$$

Since the NMAXAEs follow extreme value distributions, it is more meaningful to consider the

proportion of the values exceeding relevant thresholds than testing for differences in the

means of these distributions (Gumbel, 1958). We here consider the risk of large errors

(NMAXAE > 10), very large errors (NMAXAE > 100), and extreme errors (NMAXAE > 1,000)

as the percentage of runs (across variables and CV iterations) where the model's NMAXAE

exceeds the given threshold. Since NMAXAE is normalised by the range of the actual

variable, these thresholds correspond to one, two, and three orders of magnitude of the

actual variable's range. If we are predicting age, for instance, and the true ages of the

subjects range from 25 years to 35 years, an NMAXAE of 1 would mean that the model's

least accurate prediction is off by 10 years, an NMAXAE of 10 would mean that the least

accurate prediction is off by 100 years, an NMAXAE of 100 would be off by 1,000 years, and

an NMAXAE of 1,000 would be off by 10,000 years. A model that makes such large errors,

even in single cases, would be unusable for interpretation. Our reliability criterion in terms of

maximum errors is therefore that the risk of large errors (NMAXAE > 10) should be 0%.

For a model to be reliable, it should also be robust in the sense of susceptibility to changes

in the training examples. Robustness is an important consideration in prediction studies, as it

determines how reproducible a study or method is —which is often a shortcoming in

neuroimaging-based prediction studies (Varoquaux et al., 2017). We evaluated the

robustness by iterating nested 10-fold CV 100 times for each variable, randomising the

subjects in the folds at each iteration, so that the models would encounter a different

combination of subjects in the training and test sets each time they are run. Looking at this

range of 100 predictions for each variable, we can assess whether the model's performance

changes drastically depending on which combinations of subjects it encountered in the

training phase, or whether the performance is the same regardless of the subjects

encountered in the training phase. The former would be an example of a model that is

susceptible to changes in training examples and the latter an example of a model that is

robust. We here quantify robustness as the standard deviation (S.D.) of the prediction

accuracy r across the 100 CV iterations of each variable, where a small mean S.D. over

variables indicates higher robustness.

We test for significant differences in mean prediction accuracy and robustness between the

methods using permutation t-tests with 20,000 permutations across variables and iterations.

For maximum errors, we test whether NMAXAE distributions are significantly different

between the methods using permutation-based Kolmogorov-Smirnov tests. P-Values are

corrected across multiple comparisons using Bonferroni-correction to control the family-wise

error rate (FWER). To compare the Fisher kernel to the naïve and the naïve normalised

kernels, we first evaluate the linear and Gaussian versions of the kernels together. We then

compare the linear and Gaussian versions of each kernel with each other. We also compare

each kernel to the KL divergence model. Finally, we compare the linear Fisher kernel with

the methods based on time-averaged FC features described in the following section.

2.5   Regression models based on time-averaged FC features

To compare our approach's performance to simpler methods that do not take dynamics into

account, we compared them to four different regression models based on time-averaged FC

features. For each subject, time-averaged FC was computed as z-transformed Pearson's

correlation between each pair of regions. The first time-averaged model is, analogous to the

HMM-derived KL divergence model, a time-averaged KL divergence model. The model is

described in detail in Vidaurre et al. (2021). Briefly, we construct symmetrised KL divergence

matrices of each subject's time-averaged FC and predict from these matrices using the KRR

pipeline described above. We refer to this model as time-averaged KL divergence. The other

three time-averaged FC benchmark models do not involve kernels but predict directly from

the features instead. Namely, we use two variants of an Elastic Net model (Zou & Hastie,

2005), one using the unwrapped time-averaged FC matrices as input, and one using the

time-averaged FC matrices in Riemannian space (Barachant et al., 2013; Smith, Vidaurre, et

al., 2013), which we refer to as Elastic Net and Elastic Net (Riem.), respectively. Finally, we

compare our models to the approach taken in Rosenberg et al. (2016), where relevant edges

of the time-averaged FC matrices are first selected, and then used as predictors in a

regression model. We refer to this model as Selected Edges. All time-averaged FC models

are fitted using the (nested) cross-validation strategy, accounting for family structure in the

dataset, and repeated 100 times with randomised folds, as described above.

464   *2.6 Simulations*

465   To further understand the behaviour of the different kernels, we simulate data and compare

466   the kernels' ability to recover the ground truth. Specifically, we aim to understand which type

467   of parameter change the kernels are most sensitive to. We generate timeseries for two

468   groups of subjects, timeseries X^1 for group 1 and timeseries X^2 for group 2, from two

469   separate HMMs with respective sets of parameters θ^1 and θ^2:

$$X^1 \sim HMM(\theta^1)$$

$$X^2 \sim HMM(\theta^2)$$

We simulate timeseries from HMMs with these parameters through the generative process

described in 2.2.

For the simulations, we use the group-level HMM of the real dataset with $K = 6$ states used

in the main text as basis for group 1, i.e., $HMM(\theta^1) = HMM(\theta^0)$. We then manipulate two

different types of parameters, the state means μ and the transition probabilities A, while

keeping all remaining parameters the same between the groups. In the first case, we

manipulate one state's mean between the groups, i.e.:

$$\theta^1 = [\pi^1, A^1, \mu^1, \sigma^1]$$

$$\theta^2 = [\pi^1, A^1, \mu^2, \sigma^1]$$

477   where μ^2 is obtained by simply adding a Gaussian noise vector to the state mean vector of

478   one state:

$$\mu_1^2 = \mu_1^1 + \varphi$$

Here, φ is the Gaussian noise vector of size 1 x M, M is the number of parcels, here 50, and

μ_1^1 and μ_1^2 are the first rows (corresponding to the first state) of the state mean matrices for

groups 1 and 2, respectively. We control the amplitude of φ so that the difference between

μ_1^2 and μ_1^1 is smaller than the minimum distance between any pair of states within one HMM.

This is to ensure that the HMM recovers the difference between groups as difference in one

state's mean vector, rather than detecting a new state for group 2 that does not occur in

group 1 and consequently collapsing two other states. Since the state means μ and the state

covariances σ are the first- and second-order parameters of the same respective

distributions, it is to be expected that, although we only directly manipulate μ, σ changes as

well.

In the second case, we manipulate the transition probabilities for one state between the

groups, while keeping all other parameters the same, i.e.:

$$\theta^1 = [\pi^1, A^1, \mu^1, \sigma^1]$$

$$\theta^2 = [\pi^1, A^2, \mu^1, \sigma^1]$$

491   where A^2 is obtained by randomly permuting the probabilities of one state to transition into

492   any of the other states, excluding self-transition probability:

$$A^2_{1,1} = A^1_{1,1}$$

$$A^2_{1,2:K} = p A^1_{1,2:K}$$

493   Here, p is a random permutation vector of size (K-1) x 1, $A^1_{1,1}$ and $A^2_{1,1}$ are the self-transition

494   probabilities of state 1, and $A^1_{1,2:K}$ and $A^2_{1,2:K}$ are the probabilities of state 1 to transition into

495   each of the other states.

496   We then concatenate the generated timeseries

$$X = [X^1, X^2]$$

containing 100 subjects for group 1 and 100 subjects for group 2, with 1,200 timepoints and

50 parcels per subject. Note that we do not introduce any differences between subjects

within a group, so that the between-group difference in HMM parameters should be the most

dominant distinction and easily recoverable by the classifiers. We then apply the pipelines

described above, running a new group-level HMM and constructing the linear versions of the

naïve kernel, the naïve normalised kernel, and the Fisher kernel on these synthetic

timeseries. The second case of simulations, manipulating the transition probabilities, only

introduces a difference in few (K - 1) features and keeps the majority of the features the

same between the groups, while the first case introduces a difference in a large number of

features (M features directly, by changing one state's mean vector, and an additional M x M

features indirectly, as this state's covariance matrix will also be affected). To account for this

difference, we additionally construct a version of the kernels for the second case of

simulations that includes only π and A, removing the state parameters μ and σ. Finally, we

use a support vector machine (SVM) in combination with the different kernels to recover the

group labels and measure the error produced by each kernel. We repeat the whole process

(generating timeseries, constructing kernels, and running the SVM) 10 times, in each

iteration randomising on 3 levels: generating new random noise/permutation vectors to
simulate the timeseries, randomly initialising the HMM parameters when fitting the group-
level HMM to the simulated timeseries, and randomly assigning subjects to 10 CV folds in
the SVM.

2.7 Implementation

The code used in this study was implemented in Matlab and is publicly available within the
repository of the HMM-MAR toolbox at https://github.com/OHBA-analysis/HMM-MAR. A
Python-version of the Fisher kernel is also available at https://github.com/vidaurre/glhmm.
Code for Elastic Net prediction from time-averaged FC features is available at
https://github.com/vidaurre/NetsPredict/blob/master/nets_predict5.m. The procedure for
Selected Edges time-averaged FC prediction is described in detail in Shen et al. (2017) and
code is provided at https://www.nitrc.org/projects/bioimagesuite/behavioralprediction.m. All
code used in this paper, including scripts to reproduce the figures and additional application
examples of the Fisher Kernel can be found in the repository
https://github.com/ahrends/FisherKernel.

3   Results

We compared different prediction methods derived from a model of brain dynamics with
each other, and with models that do not account for dynamics. We assess the performance
of the predictive models in terms of two outcome criteria: prediction accuracy and reliability.
We show the superiority in both accuracy and reliability of the Fisher kernel, a principled
approach for prediction using brain dynamics, because of its capacity to preserve the
underlying structure of the brain dynamics model.

3.1 The Fisher kernel predicts more accurately than other methods

We found that the Fisher kernel has the highest prediction accuracy on average across the
range of variables and CV iterations, as shown in **Figure 2a**. Specifically, the Fisher kernel
has a significantly higher correlation coefficient between model-predicted and actual values
than the naïve kernel (mean $r\,\kappa_F$: 0.196 vs. mean $r\,\kappa_N$: 0.127, p=0.0008) and the naïve
normalised kernel (mean $r\,\kappa_{NN}$: 0.159, p=0.0008). Comparing the two naïve kernels, the
normalised version significantly improved upon the non-normalised naïve kernel (κ_N vs. κ_{NN}:
p=0.0008).

We next compared the linear with the Gaussian versions of each kernel. The linear versions

performed significantly better than the Gaussian versions for the Fisher kernel (mean $r\kappa_{Fl}$:

0.204 vs. mean $r\kappa_{Fg}$: 0.187, p=0.0008) and the naïve normalised kernel (mean $r\kappa_{NNl}$ 0.187

vs. mean $r\kappa_{NNg}$: 0.131, p=0.0008). The opposite was the case for the naïve kernel, where

the Gaussian version significantly outperformed the linear version (mean $r\kappa_{Nl}$: 0.103 vs.

mean $r\kappa_{Ng}$: 0.150, p=0.0008).

We next compared all models to the KL divergence model. The linear and the Gaussian

Fisher kernels and the linear version of the naïve normalised kernel significantly

outperformed the KL divergence model (mean $r\kappa_{KL}$:0.154 vs. κ_{Fl}: p=0.0008; vs. κ_{Fg}:

p=0.0008; vs. κ_{NNl}: p=0.0008). The Gaussian version of the naïve normalised kernel

performed significantly worse than the KL divergence model (p=0.0008). Both versions of

the naïve kernel were less accurate than the KL divergence model in terms of correlation

between model-predicted and actual values: This comparison was significant for the linear

version of the naïve kernel (p=0.0008), but not for the Gaussian version (p=0.856).

The models based on time-averaged features had significantly lower accuracies than the

linear Fisher kernel (κ_{Fl} vs. time-averaged KL div.: p=0.0008; vs. Elastic Net: p=0.0008; vs.

Elastic Net Riem.: p=0.0008; vs. Selected Edges: p=0.0008), as shown in **Figure 2a**. We

observed that the non-kernel-based time-averaged FC models, i.e., the two Elastic Net

models and the Selected Edges model, make predictions at a smaller range than the actual

variables, close to the variables' means. This leads to weak relationships between predicted

and actual variables but smaller errors, as shown in **Supplementary Figure 3**. The

distributions of correlation coefficients for the different methods are shown in **Figure 2a**. The

performance of all methods is also summarised in **Supplementary Table 2**.

We found that the Fisher kernel also predicted more accurately than other kernels when

fitting the HMM to only the first resting-state session of each subject, as shown in

Supplementary Figure 1. However, the overall accuracies of all kernels were lower in this

case, indicating that predicting traits benefits from a large amount of available data per

subject. Similarly, the Fisher kernel outperformed the other kernels when HMM states were

defined only in terms of covariance (not mean) at comparable accuracy, as shown in

Supplementary Figure 2.

Figure 2 *Distributions of model performance by kernel. The best-performing methods are highlighted by grey columns in each plot. **a)** Pearson's correlation coefficients (r) between predicted and actual variable values as a measure of prediction accuracy (y-axis) of each method (x-axis). Larger values indicate that the model predicts more accurately. The linear Fisher kernel has the highest average accuracy. **b)** Normalised maximum errors (NMAXAE) as a measure of excessive errors (y-axis) by kernel (x-axis). Large maximum errors indicate that the model predicts very poorly in single cases. Differences between the kernels mainly lie in the tails of the distributions, where the KL divergence model produces extreme maximum errors in some runs (NMAXAE > 1,000), while the linear naïve normalised kernel and the linear Fisher kernel have the smallest risk of excessive errors (NMAXAE < 10). The y-axis is plotted on the log-scale. Asterisks here indicate significant results of Kolmogorov-Smirnov permutation tests. **c)** Robustness of correlation between model-predicted and actual values. The plot shows the distribution across variables of the standard deviation of correlation coefficients over CV iterations on the y-axis for each kernel (on the x-axis). Smaller values indicate greater robustness. The linear naïve normalised kernel and the linear Fisher kernel are most robust. a),b) Each violin plot shows the distribution over 3,500 runs (100 iterations of 10-fold CV for all 35 variables) that were predicted from each kernel. c) Each*

As shown in **Figure 3**, there are differences in how well these demographic or behavioural

variables *can* be predicted from a model of brain dynamics. While there are some variables

which may show a strong link to brain dynamics, other variables may be more related to

static or structural measures (Liégeois et al., 2019; Vidaurre et al., 2021), or just be difficult

to predict in general. **Table 1** shows the variables that can be predicted at relatively high

accuracy by at least one of the time-varying methods. We here consider a mean Pearson's *r*

across CV iterations greater than 0.3 as "relatively high" accuracy. Among these, five

variables (variables ReadEng_AgeAdj, PicVocab_Unadj, PicVocab_AgeAdj, VSPLOT_OFF,

and WM_Task_Acc) are best predicted by the Fisher kernel, one variable is best predicted

by the naïve normalised kernel (variable VSPLOT_TC), and two variables are best predicted

by the time-averaged KL divergence model (variables Age and ReadEng_Unadj). The linear

naïve kernel and the time-averaged Elastic Net models produce the least accurate

predictions in these variables. Examples of best-predicted variables for all HMM-derived

kernels can be found in **Supplementary Figure 6**.

Table 1 *Variables predicted at relatively high accuracy by at least one method. The table shows mean correlation*
coefficients for all methods in those variables that could be predicted at relatively high accuracy (correlation
coefficient > 0.3) by at least one method. The best performing model is highlighted in bold.

Method		Mean correlation coefficient *r*							
		Age	ReadEng _Unadj	ReadEng _AgeAdj	PicVocab _AgeAdj	PicVocab _Unadj	WM_Task _Acc	VSPLOT _TC	VSPLOT _OFF
Naïve	Linear	0.06	0.193	0.2	0.189	0.131	0.234	0.227	0.223
	Gaussian	0.43	0.329	0.318	0.33	0.288	0.254	0.282	0.277
Naïve norm.	Linear	0.47	0.383	0.38	0.372	0.346	0.341	**0.32**	0.342
	Gaussian	0.37	0.267	0.252	0.245	0.242	0.269	0.228	0.296
Fisher	Linear	0.46	0.399	**0.401**	**0.42**	**0.392**	**0.375**	0.305	**0.362**
	Gaussian	0.44	0.396	0.4	0.419	0.388	0.37	0.295	0.352
KL div.		0.47	0.357	0.351	0.338	0.314	0.283	0.248	0.235
ta KL div.		**0.47**	**0.418**	0.378	0.265	0.297	0.298	0.246	0.245
Elastic Net		0.39	0.359	0.348	0.347	0.355	0.241	0.17	0.189
Elastic Net (Riem.)		0.39	0.358	0.348	0.347	0.353	0.241	0.173	0.188
Selected Edges		0.27	0.264	0.271	0.32	0.268	0.223	0.24	0.248

Figure 3 *Model performance estimates over CV iterations by behavioural variable and method. Boxplots show the distribution over 100 iterations of 10-fold CV of correlation coefficient values (x-axis) of each method, separately for each of the 35 predicted variables (y-axes). The Fisher kernel (green) not only predicts at higher accuracy for many variables, but also shows the narrowest range, indicating high robustness. Black lines within each boxplot represent the median.*

In summary, the linear Fisher kernel has the highest prediction accuracy, significantly outperforming the naïve kernels, Gaussian version of the Fisher kernel, and the KL divergence model. The linear Fisher kernel also has a higher prediction accuracy than benchmark methods using time-averaged FC features. The linear Fisher kernel, closely

621 followed by its Gaussian version, is the kernel that produces the best predictions in the traits
622 that can be predicted well by any one kernel.

3.2 The Fisher kernel has a lower risk of excessive errors and is more
robust than other methods

We now show empirically that the Fisher kernel is more reliable than other kernels, both in
terms of risk of large errors and in terms of robustness over CV iterations.

The linear versions of the Fisher kernel and the naïve normalised kernel have the overall
lowest risk of large errors, as shown in **Figure 2b**. We assessed the risk of large errors
(NMAXAE > 10), very large errors (NMAXAE > 100), and extreme errors (NMAXAE >
1,000), corresponding to one, two, and three orders of magnitude of the range of the actual
variable. For the Fisher kernel, the risk of large errors is low: 0.057% in the Gaussian version
κ_{Fg} and 0% in the linear version κ_{Fl}. That means that the linear Fisher kernel never makes
large errors exceeding the range of the actual variable by orders of magnitude. In the naïve
kernel, both the linear κ_{Nl} and the Gaussian version κ_{Ng} have a low risk of large errors at
0.029% for the linear version and 0.057% for the Gaussian version. The Gaussian naïve
normalised kernel κ_{NNg} on the other hand has a slightly higher risk of large errors at 1.140%
and a risk of very large errors at 0.057%, while its linear version κ_{NNl} has a 0% risk of large
errors. The risk of large errors was highest in the KL divergence model κ_{KL} at 0.890% risk of
large errors, 0.110% risk of very large errors, and even 0.057% risk of extreme errors. While
the time-averaged KL divergence model had similarly large maximum errors as the time-
varying KL divergence model, the three other time-averaged models had no risk of
excessive errors, similar to the linear Fisher kernel. The maximum error distributions are
shown in **Figure 2b**. The summary of maximum errors is also reported in **Supplementary**
Table 2 and **Supplementary Table 3**. **Supplementary Figure 4** also shows the quantile-
quantile plots of the normalised maximum errors.

A reason for the higher risk of large errors in the Gaussian versions of the kernels is likely
that the radius τ of the radial basis function needs to be selected (using cross-validation),
introducing an additional factor of variability and leaving more room for error.
Supplementary Figure 5 shows the relation between the estimated hyperparameters (the
regularisation parameter λ and the radius τ of the radial basis function) and how large errors
in the predictions may be related to poor estimation of these parameters.

With respect to robustness, we found that the linear Fisher kernel κ_{Fl} and the linear naïve

normalised kernel κ_{NNl} had the most robust performance on average across the range of

variables tested, as shown in **Figure 2c**. Robustness was quantified as the standard

deviation of the correlation between model-predicted and actual values over 100 iterations of

10-fold CV. A low standard deviation indicates high robustness, since the method's

performance does not differ greatly depending on the specific subjects it was trained and

tested on. The Fisher kernel was significantly more robust than both the naïve kernel and the

naïve normalised kernel (κ_F mean S.D. *r.* 0.015 vs. naïve kernel κ_N mean S.D. *r.* 0.019,

p=0.02; vs. naïve normalised kernel κ_{NN} mean S.D. *r.* 0.024, *p*=0.0008). The naïve kernel

and the naïve normalised kernel did not significantly differ from each other (*p*=0.49). We

found that the linear versions of the Fisher kernel and the naïve normalised kernel were

significantly more robust than their respective Gaussian versions (κ_{Fl} mean S.D. *r.* 0.011 vs.

κ_{Fg} mean S.D. *r.* 0.018, *p*=0.0008; κ_{NNl} mean S.D. *r.* 0.011 vs. κ_{NNg} mean S.D. *r.* 0.036,

p=0.0008), while there was no significant difference between the linear and the Gaussian

naïve kernel (κ_{Nl} S.D. *r.* 0.020 vs. κ_{Ng} S.D. *r.* 0.018, *p*>1). All but the Gaussian naïve

normalised kernel κ_{NNg} significantly outperformed the KL divergence model κ_{KL} in terms of

robustness (κ_{KL} mean S.D. *r.* 0.042 vs. κ_{Nl} *p*=0.0008; vs. κ_{Ng} *p*=0.0008; vs. κ_{NNl} *p*=0.0008;

vs. κ_{NNg} *p*>1; vs. κ_{Fl} *p*=0.0008; vs. κ_{Fg} *p*=0.0008). This large variation in model performance

depending on the CV fold structure in the KL divergence model is problematic. The same

problem occurs, even more drastically, when using time-averaged FC features in a KL

divergence model, indicating robustness issues of the KL divergence measure in this type of

predictive model independent of the underlying features. Like the time-varying KL

divergence model, the time-averaged KL divergence model was significantly less robust than

the linear Fisher kernel (*p*=0.0008). Also the other time-averaged models were significantly

less robust than the linear Fisher kernel (κ_{Fl} vs. Elastic Net: *p*=0.0008; vs. Elastic Net Riem.:

p=0.0008; vs. Selected Edges: *p*=0.007). The ranges in model performance across CV

iterations for each variable of the different kernels are shown in **Figure 3**. Robustness of all

kernels is also summarised in **Supplementary Table 3**.

Overall, the linear Fisher kernel and the linear naïve normalised kernel were the most

reliable: For both kernels, the risk of large errors was zero and the variability over CV

iterations was the smallest. The Gaussian versions of all kernels had higher risks of large

errors and a larger range in model performance over CV iterations, indicating that their

performance was less reliable. The KL divergence model was the most problematic in terms

of reliability with a risk of extreme errors ranging up to three orders of magnitude of the

actual variable's range and considerable susceptibility to changes in CV folds.

3.3 Fisher kernel predictions are driven by individual differences in state features

The Fisher kernel is most sensitive to individual differences in state parameters, both in simulated timeseries and in the real data. That means that it is more relevant for the predictions what states look like in the individuals than how the individuals transition between states. However, the Fisher kernel can be modified to recover differences in transition probabilities if these are relevant for specific traits.

As shown in **Figure 4a**, panel 1, when we simulated two groups of subjects that are different in terms of the mean amplitude of one state, the Fisher kernel was able to recover this difference in all runs with 0% error, meaning that it identified all subjects correctly in all runs. The Fisher kernel significantly outperformed the other two kernels (Fisher kernel κ_{Fl} vs. naïve kernel κ_{Nl}: p=0.0003, vs. naïve normalised kernel κ_{NNl}: p=0.0001), while there was no significant difference between the naïve and the naïve normalised kernel (p>1). Both the naïve kernel and the naïve normalised kernel (**Figure 4a**, panels 2, 3) do not show a group-difference (i.e., there is no clear dissimilarity between the first and the second half of subjects) and are prone to producing outliers. In the Fisher kernel, there are no outliers in the features or kernels, and the group difference is obvious with a strong checkerboard pattern in the kernels (**Figure 4a**, panel 4).

When we simulated differences in transition probabilities between two groups, neither of the kernels were able to reliably recover this difference and the Fisher kernel performed significantly worse than the other two kernels on average (compared to naïve kernel: p=0.006, compared to naïve normalised kernel: p=0.004), as shown in **Figure 4b**, panel 1. Like the previous case, where we simulated differences in state means, the naïve kernel and the naïve normalised kernel did not significantly differ from each other (p>1), and they produced outliers in features and kernels (**Figure 4b**, panels 2-3).

This indicates that all kernels, but particularly the Fisher kernel, are most sensitive to differences in state parameters rather than differences in transition probabilities. To understand whether the difference in transition probabilities can be recovered when it is not overshadowed by the more dominant state parameters, we run the second case of simulations again, where we introduce a group difference in terms of transition probabilities, but this time we exclude the state parameters when we construct the kernels. As shown in **Figure 4c**, panel 1, the Fisher kernel is now able to recover the group difference with minimal errors, while the naïve normalised kernel improves but does not perform as well as the Fisher kernel, and the naïve kernel performs below chance. Here, the Fisher kernel

722 significantly outperformed both the naïve kernel (*p*=0.0001) and the naïve normalised kernel

723 (*p*=0.02), and the naïve normalised kernel was significantly more accurate than the naïve

724 kernel (*p*=0.0004). This shows that the Fisher kernel is able to recover the group difference

725 in transition probabilities, if this difference is not overshadowed by the state parameters.

Figure 4 Simulations. If the group difference was apparent in the features, there would be a clear difference
between red and blue dots in the feature plot. If the group difference was apparent in the kernels, there would be
a checkerboard-pattern with four squares in the kernel matrices: high similarity within the first half and within the
second half of subjects, and low similarity between the first and the second half of subjects. Each kernel should
also have the strongest similarity on the diagonal because each subject should be more similar to themselves
than to any other subject. In the second kernel plots, we remove the diagonal for visualisation purposes to show
the group difference more clearly. *a)* Simulating two groups of subjects that are different in their state means. The
error distributions of all 10 iterations show that the Fisher kernel recovers the simulated group difference in all
runs with 0% error (1). Features, kernel matrices, and kernel matrices with the diagonal removed for the first
iteration for the linear naïve kernel (2), the linear naïve normalised kernel (3), and the linear Fisher kernel (4). The
Fisher kernel matrices show an obvious checkerboard pattern corresponding to the within-group similarity and
the between-group dissimilarity of the first and the second half of subjects. *b)* Simulating two groups of subjects
that are different in their transition probabilities. Neither kernel is able to reliably recover the group difference, as
shown in the error distribution of all 10 iterations (1), and the features and kernel matrices of one example
iteration (2-4). *c)* Simulating two groups of subjects that are different in their transition probabilities but excluding
state parameters when constructing the kernels. The Fisher kernel performs best in recovering the group
difference as shown by the error distributions of all 10 iterations (1).

In real data, the features driving the prediction may differ from trait to trait: For some traits,

state parameters may be more relevant, while for other traits, transitions may be more

relevant. We therefore compare the effects of removing state features and the effects of

removing transition features in all traits in the real data.

We found that state parameters were the most relevant features for the Fisher kernel

predictions in all traits: As shown in **Figure 5a**, the prediction accuracy of the Fisher kernel

significantly suffered when state features were removed (p=0.0009), while removing

transition features had no significant effect (p>1). We observed the same effect in the naïve

normalised kernel (no state features: p=0.0009; no transition features: p>1), while the naïve

kernel was on average improved by removing state features (no state features: p=0.0009; no

transition features: p>1). One reason for the dominance of state parameters may simply be

that the state parameters outnumber the other parameters: In the full kernels, we have

15,300 state features (300 features associated with the state means and 15,000 features

associated with the state covariances), but only 42 transition features (6 features associated

with the state probabilities and 36 features associated with the transition probabilities). To

compensate for this imbalance, we also constructed a version of the kernels where state

parameters were reduced to the same amount as transition features using PCA, so that we

have 84 features in total (42 transition features and the first 42 PCs of the 15,300 state

features). These PCA-kernels performed significantly better than the ones where state

features were removed in the Fisher kernel (p=0.0009), but worse than the kernels including

all features at the original dimensionality (p=0.0009). This indicates that the fact that state

parameters are more numerous than transition parameters does not explain why kernels

including state features perform better. Instead, the content of the state features is more

relevant for the prediction than the content of the transition features.

When looking at the performance separately for each variable (**Figure 5b and c**), we found

that all but one variable were better predicted by the version of the kernel which included

state features than the ones where state features were removed, while it did not seem to

matter whether transition features were included. This indicates that the simulation case

described above, where the relevant changes are in the transition probabilities, did not occur

in the real data. In certain variables, reducing state features using PCA improved the

accuracy compared to the full kernels, which is not unexpected since feature dimensionality

reduction is known to be able to improve prediction accuracy by removing redundant

features (Mwangi et al., 2014).

4 Discussion

We showed that the Fisher kernel accurately and reliably predicts traits from brain dynamics

models trained on neuroimaging data, resulting in better generalisability and interpretability

compared to other methods. It preserves the structure of the underlying brain dynamics

model, making it ideal for combining generative and predictive models. We have compared

the Fisher kernel to kernels which ignore the structure of the brain dynamics model ("naïve"

kernels), to a previously used model based on Kullback-Leibler divergence (Vidaurre et al.,

2021), and to models based on time-averaged FC. The linear Fisher kernel had a higher

prediction accuracy than all other methods and was among the most reliable methods: It

never produced excessive errors and was robust to changes in training sets.

We here focussed on fMRI, but the method can also be applied to other modalities like MEG

or EEG and it can straightforwardly be implemented in any kernel-based prediction model or

classifier, including kernel ridge regression, support vector machines (SVM), kernel fisher

discriminant analysis (k-FDA), kernel logistic regression (KLR), or nonlinear PCA.

Our results were consistent in two alternative settings: when using less data per subject and

when modelling brain dynamics only in terms of functional connectivity. This supports the

generalisability of the results. It should be noted though that we observed overall lower

accuracies when using only one scanning session consisting of 1,200 timepoints per subject,

indicating that predicting phenotypes from models of brain dynamics requires a sufficiently

large amount of data for each individual. Using a set of 35 different demographic and

cognitive traits, we found that the traits that were best predicted by kernels from models of

brain dynamics were language and spatial orientation skills, and here the Fisher kernel was

generally the most accurate. We also found that the Gaussian version of the kernels are

generally more error-prone and susceptible to changes in the training set, although they may

predict more accurately in certain runs. Implementing Gaussian kernels in a predictive model

is also computationally more expensive, making them less practical. While we here only

tested robustness in terms of susceptibility to changes in CV folds, it remains to be shown to

what extent model performance is sensitive to the random initialisation of the HMM, which

affects the parameter estimation (Alonso & Vidaurre, 2023). Finally, we showed that the

Fisher kernel is most sensitive to changes in state descriptions, i.e., individual differences in

the amplitude or functional connectivity of certain brain states. While this could be a
disadvantage if a trait was more closely related to how an individual transitions between
brain states, we found that this was not the case in any of the traits we tested here. This is
surprising, given that we predicted a variety of cognitive traits, expecting that some traits
would, for instance, be more closely related to an individual's FC in a certain brain state,
while other traits would be better explained by their temporal pattern of switching between
brain states. Other constructs than the ones we tested here may of course be more related
to individual transition patterns. For this case, we showed in simulations that the Fisher
kernel can be modified to recognise changes in transitions if they are of interest for the
specific research question.

Models of brain dynamics in unconstrained cognition do not directly lend themselves to
being used as linear predictors, because of the high number of parameters and their
complex relationships. Kernels are a computationally efficient approach that allow working
with nonlinear, high-dimensional features, such as parameters from a model of brain
dynamics, in a simple linear predictive model. How to construct a kernel is however not
always straightforward (Azim & Ahmed, 2018; Shawe-Taylor & Cristianini, 2004). We here
demonstrated that constructing a kernel that preserves the structure of the underlying model,
like the Fisher kernel, can achieve better, more reliable performance than other methods
when using models of brain dynamics to predict subject traits.

Such a kernel can be useful in various applications. For instance, there is growing interest in
combining different data types or modalities, such as structural, static, and dynamic
measures to predict phenotypes (Engemann et al., 2020; Schouten et al., 2016). While
directly combining the features from each modality can be problematic, kernels that are
properly derived for each modality can be easily combined using approaches such as Multi
Kernel Learning (MKL) (Gönen & Alpaydın, 2011), which can improve prediction accuracy of
multimodal studies (Vaghari et al., 2022). In a clinical context, describing individual variability
for diagnosis and individual patients' outcome prediction is the ultimate goal (Marquand et
al., 2016; Stephan et al., 2017; Wen et al., 2022; Wolfers et al., 2015), but the focus so far
has mostly been on static or structural information, leaving the potentially crucial information
from brain dynamics untapped. In order to be able to use predictive models from brain
dynamics in a clinical context, predictions must be reliable, particularly if we want to interpret
model errors, as in models of "brain age". As we demonstrated, there can be extreme errors
and large variation in some predictive models, and these issues are not resolved by
estimating model performance in a standard cross-validated fashion. We here showed that
taking the structure of the underlying model into account, and thoroughly assessing not only
accuracy but also errors and robustness, we can reliably use information from brain

dynamics to predict individual traits. This will allow gaining crucial insights into cognition and

behaviour from how brain function changes over time, beyond structural and static

information.

Acknowledgements

853 DV is supported by a Novo Nordisk Foundation Emerging Investigator Fellowship

854 (NNF19OC-0054895) and an ERC Starting Grant (ERC-StG-2019-850404). We thank Ben

855 Griffin and Steve Smith for useful discussions and technical collaboration.

References

Ahrends, C., Stevner, A., Pervaiz, U., Kringelbach, M. L., Vuust, P., Woolrich, M. W., &
Vidaurre, D. (2022). Data and model considerations for estimating time-varying
functional connectivity in fMRI. *Neuroimage*, *252*, 119026.
https://doi.org/10.1016/j.neuroimage.2022.119026

Alonso, S., & Vidaurre, D. (2023). Towards stability of dynamic FC estimates in
neuroimaging and electrophysiology: solutions and limits. *bioRxiv*,
2023.2001.2018.524539. https://doi.org/10.1101/2023.01.18.524539

Azim, T., & Ahmed, S. (2018). *Composing Fisher Kernels from Deep Neural Models*.
Springer.

Barachant, A., Bonnet, S., Congedo, M., & Jutten, C. (2013). Classification of covariance
matrices using a Riemannian-based kernel for BCI applications. *Neurocomputing*,
112, 172-178. https://doi.org/https://doi.org/10.1016/j.neucom.2012.12.039

Baum, L. E., & Eagon, J. A. (1967). An inequality with applications to statistical estimation for
probabilistic functions of Markov processes and to a model for ecology. *Bulletin of the*
American Mathematical Society, *73*(3), 360-363, 364. https://doi.org/

Baum, L. E., & Petrie, T. (1966). Statistical Inference for Probabilistic Functions of Finite
State Markov Chains. *The Annals of Mathematical Statistics*, *37*(6), 1554-1563,
1510. https://doi.org/10.1214/aoms/1177699147

Beckmann, C. F. (2012). Modelling with independent components. *Neuroimage*, *62*(2), 891-
901. https://doi.org/10.1016/j.neuroimage.2012.02.020

Beckmann, C. F., Mackay, C. E., Filippini, N., & Smith, S. M. (2009). Group comparison of
resting-state FMRI data using multi-subject ICA and dual regression. *Neuroimage*,
47, S148. https://doi.org/10.1016/S1053-8119(09)71511-3

Cole, J. H., & Franke, K. (2017). Predicting Age Using Neuroimaging: Innovative Brain
Ageing Biomarkers. *Trends Neurosci*, *40*(12), 681-690.
https://doi.org/10.1016/j.tins.2017.10.001

Denissen, S., Engemann, D. A., De Cock, A., Costers, L., Baijot, J., Laton, J., Penner, I. K.,
Grothe, M., Kirsch, M., D'Hooghe M, B., D'Haeseleer, M., Dive, D., De Mey, J., Van
Schependom, J., Sima, D. M., & Nagels, G. (2022). Brain age as a surrogate marker
for cognitive performance in multiple sclerosis. *Eur J Neurol*, *29*(10), 3039-3049.
https://doi.org/10.1111/ene.15473

Do, M. N. (2003). Fast approximation of Kullback-Leibler distance for dependence trees and
hidden Markov models [Article]. *IEEE Signal Processing Letters*, *10*(4), 115-118.
https://doi.org/10.1109/LSP.2003.809034

Engemann, D. A., Kozynets, O., Sabbagh, D., Lemaître, G., Varoquaux, G., Liem, F., &
Gramfort, A. (2020). Combining magnetoencephalography with magnetic resonance
imaging enhances learning of surrogate-biomarkers. *eLife*, *9*, e54055.
https://doi.org/10.7554/eLife.54055

Glasser, M. F., Sotiropoulos, S. N., Wilson, J. A., Coalson, T. S., Fischl, B., Andersson, J. L.,
896   Xu, J., Jbabdi, S., Webster, M., Polimeni, J. R., Van Essen, D. C., Jenkinson, M., &
897   Consortium, W. U.-M. H. (2013). The minimal preprocessing pipelines for the Human
898   Connectome Project. *Neuroimage*, *80*, 105-124.
899   https://doi.org/10.1016/j.neuroimage.2013.04.127
900   Griffanti, L., Salimi-Khorshidi, G., Beckmann, C. F., Auerbach, E. J., Douaud, G., Sexton, C.
901   E., Zsoldos, E., Ebmeier, K. P., Filippini, N., Mackay, C. E., Moeller, S., Xu, J.,
902   Yacoub, E., Baselli, G., Ugurbil, K., Miller, K. L., & Smith, S. M. (2014). ICA-based
903   artefact removal and accelerated fMRI acquisition for improved resting state network
904   imaging. *Neuroimage*, *95*, 232-247.
905   https://doi.org/10.1016/j.neuroimage.2014.03.034
906   Gumbel, E. J. (1958). *Statistics of Extremes*. Columbia University Press.
907   https://doi.org/doi:10.7312/gumb92958
908   Gönen, M., & Alpaydın, E. (2011). Multiple kernel learning algorithms. *J Mach Learn Res*,
909   *12*, 2211-2268. https://doi.org/10.5555/1953048.2021071
910   Jaakkola, T., Diekhans, M., & Haussler, D. (1999). Using the Fisher kernel method to detect
911   remote protein homologies. *Proc Int Conf Intell Syst Mol Biol*, 149-158.
912   Jaakkola, T., & Haussler, D. (1998). Exploiting Generative Models in Discriminative
913   Classifiers. NIPS,
914   Liégeois, R., Li, J., Kong, R., Orban, C., Van De Ville, D., Ge, T., Sabuncu, M. R., & Yeo, B.
915   T. T. (2019). Resting brain dynamics at different timescales capture distinct aspects
916   of human behavior. *Nat Commun*, *10*(1), 2317. https://doi.org/10.1038/s41467-019-
917   10317-7
918   Lurie, D. J., Kessler, D., Bassett, D. S., Betzel, R. F., Breakspear, M., Kheilholz, S., Kucyi,
919   A., Liégeois, R., Lindquist, M. A., McIntosh, A. R., Poldrack, R. A., Shine, J. M.,
920   Thompson, W. H., Bielczyk, N. Z., Douw, L., Kraft, D., Miller, R. L., Muthuraman, M.,
921   Pasquini, L., . . . Calhoun, V. D. (2019). Questions and controversies in the study of
922   time-varying functional connectivity in resting fMRI. *Netw Neurosci*, *4*(1), 30-69.
923   https://doi.org/10.1162/netn_a_00116
924   MacKay, D. J. C., Kay, D. J. C. M., & Press, C. U. (2003). *Information Theory, Inference and
925   Learning Algorithms*. Cambridge University Press.
926   https://books.google.dk/books?id=AKuMj4PN_EMC
927   Marquand, A. F., Rezek, I., Buitelaar, J., & Beckmann, C. F. (2016). Understanding
928   Heterogeneity in Clinical Cohorts Using Normative Models: Beyond Case-Control
929   Studies. *Biological psychiatry*, *80*(7), 552-561.
930   https://doi.org/10.1016/j.biopsych.2015.12.023
931   Mwangi, B., Tian, T. S., & Soares, J. C. (2014). A Review of Feature Reduction Techniques
932   in Neuroimaging. *Neuroinformatics*, *12*(2), 229-244. https://doi.org/10.1007/s12021-
933   013-9204-3
934   Rosenberg, M. D., Finn, E. S., Scheinost, D., Papademetris, X., Shen, X., Constable, R. T.,
935   & Chun, M. M. (2016). A neuromarker of sustained attention from whole-brain
936   functional connectivity. *Nat Neurosci*, *19*(1), 165-171. https://doi.org/10.1038/nn.4179
937   Salimi-Khorshidi, G., Douaud, G., Beckmann, C. F., Glasser, M. F., Griffanti, L., & Smith, S.
938   M. (2014). Automatic denoising of functional MRI data: combining independent
939   component analysis and hierarchical fusion of classifiers. *Neuroimage*, *90*, 449-468.
940   https://doi.org/10.1016/j.neuroimage.2013.11.046
941   Saunders, C., Gammerman, A., & Vovk, V. (1998). Ridge regression learning algorithm in
942   dual variables.
943   Schouten, T. M., Koini, M., de Vos, F., Seiler, S., van der Grond, J., Lechner, A.,
944   Hafkemeijer, A., Möller, C., Schmidt, R., de Rooij, M., & Rombouts, S. A. R. B.
945   (2016). Combining anatomical, diffusion, and resting state functional magnetic
946   resonance imaging for individual classification of mild and moderate Alzheimer's
947   disease. *NeuroImage: Clinical*, *11*, 46-51. https://doi.org/10.1016/j.nicl.2016.01.002
948   Schölkopf, B., Smola, A. J., & Bach, F. (2002). *Learning with kernels: support vector
949   machines, regularization, optimization, and beyond*. MIT press.

Shawe-Taylor, J., & Cristianini, N. (2004). *Kernel Methods for Pattern Analysis*. Cambridge
University Press. https://doi.org/10.1017/CBO9780511809682
Shen, X., Finn, E. S., Scheinost, D., Rosenberg, M. D., Chun, M. M., Papademetris, X., &
Constable, R. T. (2017). Using connectome-based predictive modeling to predict
individual behavior from brain connectivity. *Nat Protoc*, *12*(3), 506-518.
https://doi.org/10.1038/nprot.2016.178
Smith, S. M., Beckmann, C. F., Andersson, J., Auerbach, E. J., Bijsterbosch, J., Douaud, G.,
Duff, E., Feinberg, D. A., Griffanti, L., Harms, M. P., Kelly, M., Laumann, T., Miller, K.
L., Moeller, S., Petersen, S., Power, J., Salimi-Khorshidi, G., Snyder, A. Z., Vu, A. T.,
. . . Consortium, W. U.-M. H. (2013). Resting-state fMRI in the Human Connectome
Project. *Neuroimage*, *80*, 144-168. https://doi.org/10.1016/j.neuroimage.2013.05.039
Smith, S. M., Vidaurre, D., Alfaro-Almagro, F., Nichols, T. E., & Miller, K. L. (2019).
Estimation of brain age delta from brain imaging. *Neuroimage*, *200*, 528-539.
https://doi.org/https://doi.org/10.1016/j.neuroimage.2019.06.017
Smith, S. M., Vidaurre, D., Beckmann, C. F., Glasser, M. F., Jenkinson, M., Miller, K. L.,
Nichols, T. E., Robinson, E. C., Salimi-Khorshidi, G., Woolrich, M. W., Barch, D. M.,
Uğurbil, K., & Van Essen, D. C. (2013). Functional connectomics from resting-state
fMRI. *Trends Cogn Sci*, *17*(12), 666-682. https://doi.org/10.1016/j.tics.2013.09.016
Stephan, K. E., Schlagenhauf, F., Huys, Q. J. M., Raman, S., Aponte, E. A., Brodersen, K.
H., Rigoux, L., Moran, R. J., Daunizeau, J., Dolan, R. J., Friston, K. J., & Heinz, A.
(2017). Computational neuroimaging strategies for single patient predictions.
Neuroimage, *145*, 180-199.
https://doi.org/https://doi.org/10.1016/j.neuroimage.2016.06.038
Vaghari, D., Kabir, E., & Henson, R. N. (2022). Late combination shows that MEG adds to
MRI in classifying MCI versus controls. *Neuroimage*, *252*, 119054.
https://doi.org/10.1016/j.neuroimage.2022.119054
van der Maaten, L. (2011). Learning Discriminative Fisher Kernels. Proceedings of the 28th
International Conference on Machine Learning, Bellevue, WA, USA.
Van Essen, D. C., Smith, S. M., Barch, D. M., Behrens, T. E., Yacoub, E., & Ugurbil, K.
(2013). The WU-Minn Human Connectome Project: an overview. *Neuroimage*, *80*,
62-79. https://doi.org/10.1016/j.neuroimage.2013.05.041
Van Essen, D. C., Ugurbil, K., Auerbach, E., Barch, D., Behrens, T. E. J., Bucholz, R.,
Chang, A., Chen, L., Corbetta, M., Curtiss, S. W., Della Penna, S., Feinberg, D.,
Glasser, M. F., Harel, N., Heath, A. C., Larson-Prior, L., Marcus, D., Michalareas, G.,
Moeller, S., . . . Consortium, W. U.-M. H. (2012). The Human Connectome Project: a
data acquisition perspective. *Neuroimage*, *62*(4), 2222-2231.
https://doi.org/10.1016/j.neuroimage.2012.02.018
Varoquaux, G., Raamana, P. R., Engemann, D. A., Hoyos-Idrobo, A., Schwartz, Y., &
Thirion, B. (2017). Assessing and tuning brain decoders: Cross-validation, caveats,
and guidelines. *Neuroimage*, *145*, 166-179.
https://doi.org/https://doi.org/10.1016/j.neuroimage.2016.10.038
Vidaurre, D., Llera, A., Smith, S. M., & Woolrich, M. W. (2021). Behavioural relevance of
spontaneous, transient brain network interactions in fMRI. *Neuroimage*, *229*, 117713.
https://doi.org/10.1016/j.neuroimage.2020.117713
Vidaurre, D., Quinn, A. J., Baker, A. P., Dupret, D., Tejero-Cantero, A., & Woolrich, M. W.
(2016). Spectrally resolved fast transient brain states in electrophysiological data.
Neuroimage, *126*, 81-95. https://doi.org/10.1016/j.neuroimage.2015.11.047
Vidaurre, D., Smith, S. M., & Woolrich, M. W. (2017). Brain network dynamics are
hierarchically organized in time. *Proc Natl Acad Sci U S A*, *114*(48), 12827-12832.
https://doi.org/10.1073/pnas.1705120114
Wen, J., Varol, E., Sotiras, A., Yang, Z., Chand, G. B., Erus, G., Shou, H., Abdulkadir, A.,
Hwang, G., Dwyer, D. B., Pigoni, A., Dazzan, P., Kahn, R. S., Schnack, H. G.,
Zanetti, M. V., Meisenzahl, E., Busatto, G. F., Crespo-Facorro, B., Rafael, R. G., . . .
Alzheimer's Disease Neuroimaging, I. (2022). Multi-scale semi-supervised clustering

of brain images: Deriving disease subtypes. *Med Image Anal*, *75*, 102304.
https://doi.org/10.1016/j.media.2021.102304
Winkler, A. M., Webster, M. A., Vidaurre, D., Nichols, T. E., & Smith, S. M. (2015). Multi-level
block permutation. *Neuroimage, 123*, 253-268.
https://doi.org/https://doi.org/10.1016/j.neuroimage.2015.05.092
Wolfers, T., Buitelaar, J. K., Beckmann, C. F., Franke, B., & Marquand, A. F. (2015). From
estimating activation locality to predicting disorder: A review of pattern recognition for
neuroimaging-based psychiatric diagnostics. *Neurosci Biobehav Rev*, *57*, 328-349.
https://doi.org/10.1016/j.neubiorev.2015.08.001
Zou, H., & Hastie, T. (2005). Regularization and Variable Selection Via the Elastic Net.
Journal of the Royal Statistical Society Series B: Statistical Methodology, *67*(2), 301-
320. https://doi.org/10.1111/j.1467-9868.2005.00503.x

1016