Deep convolutional and conditional neural networks for large-scale genomic data generation

Burak Yelmen[1,2,*], Aurélien Decelle[1,3], Leila Lea Boulos[1,4], Antoine Szatkownik[1], Cyril Furtlehner[1], Guillaume Charpiat[1], Flora Jay[1]

1 Université Paris-Saclay, CNRS, INRIA, LISN, Paris, France
2 University of Tartu, Institute of Genomics, Tartu, Estonia
3 Universidad Complutense de Madrid, Departamento de Física Teórica, Madrid, Spain
4 Université d'Évry Val-d'Essonne, Évry-Courcouronnes, France

*burakyelmen@gmail.com

Abstract

Applications of generative models for genomic data have gained significant momentum in the past few years, with scopes ranging from data characterization to generation of genomic segments and functional sequences. In our previous study, we demonstrated that generative adversarial networks (GANs) and restricted Boltzmann machines (RBMs) can be used to create novel high-quality artificial genomes (AGs) which can preserve the complex characteristics of real genomes such as population structure, linkage disequilibrium and selection signals. However, a major drawback of these models is scalability, since the large feature space of genome-wide data increases computational complexity vastly. To address this issue, we implemented a novel convolutional Wasserstein GAN (WGAN) model along with a novel conditional RBM (CRBM) framework for generating AGs with high SNP number. These networks implicitly learn the varying landscape of haplotypic structure in order to capture complex correlation patterns along the genome and generate a wide diversity of plausible haplotypes. We performed comparative analyses to assess both the quality of these generated haplotypes and the amount of possible privacy leakage from the training data.

Significance: As the importance of genetic privacy becomes more prevalent, the need for effective privacy protection measures for genomic data increases. We used generative neural networks to create large artificial genome segments which possess many characteristics of real genomes without any apparent privacy leakage from the training dataset. In the near future, large-scale artificial genome databases can be assembled to provide easily accessible surrogates of real databases, allowing researchers to conduct studies with diverse genomic data within a safe ethical framework in terms of donor privacy.

Introduction

Machine learning is an important staple in modern genomic studies. There have been numerous applications in demographic inference [1], detecting natural selection [2] , genome-wide association studies [3] and functional genomics [4], many of which became state of the art [5]. In the recent few years, generative machine learning approaches for the genomics field have also begun to gain research interest thanks to algorithmic advances and widespread availability of computational resources [6, 7, 8, 9, 10]. Broadly speaking, generative machine learning involves the utilisation of generative models which are trained to model the distribution of a given dataset so that new data instances with similar characteristics to the real data can be sampled from this learned distribution. Especially since the introduction of generative adversarial networks (GANs) in the preceding decade [11], generative modelling has become a widely-researched subject with a diverse scope of applications such as image and text generation [12, 13], dimensionality reduction [14] and imputation [15].

The amount of genetic data, both in sequence and SNP array formats, is now increasing at an unmatched rate, yet its accessibility remains relatively low. The main reason for this is the crucial protocols prepared to protect the privacy of donors. Genetic data belongs to a special category similar to private medical records in the General Data Protection Regulation (GDPR) [16] and is defined as protected health information in the Health Insurance Portability and Accountability Act (HIPAA) [17]. Although these protective measures are vital, they create an accessibility issue for researchers who must go through these protocols and, in many circumstances, might have to commit to collaborations to conduct research or simply test ideas. In our previous study, we introduced the concept of high quality artificial genomes (AGs) created by generative models as a possible future solution for this problem and as an alternative to other methods such as differential privacy [18] and federated learning [19]. We demonstrated that AGs can mimic the characteristics of real data such as allele frequency distribution, haplotypic integrity and population structure, and can be used in applications such as genomic imputation and natural selection scans [20]. However, our previous models lacked the capacity to generate large-scale genomic regions due to the computational requirements caused by the high number of parameters defining the fully connected architectures. In this study, we present two novel implementations better adapted to large sequential genomic data: (i) generative adversarial networks with convolutional architecture and Wasserstein loss (WGAN) [21], and (ii) restricted Boltzmann machines with conditional training (CRBM) [22] used together with an out-of-equilibrium procedure [23]. In more detail, we implemented a WGAN with gradient penalty (WGAN-GP) [24] which involved a deep generator and a deep critic architecture, multiple noise inputs at different resolutions for the generator [25], trainable location-specific vectors for preserving the positional information [26], residual blocks to prevent vanishing gradients [27] and packing for the critic to eliminate mode collapse [28]. For the CRBM, we used the more efficient out-of-equilibrium training scheme differently from our previous study and developed a novel procedure for conditionally training multiple RBMs based on shared genomic regions (see Materials and Methods for more details). We assessed the AGs generated by these models with multiple statistics measuring data quality and possible privacy leakage.

Results

Comparisons with the previous models

As our GAN concept has changed substantially compared to the previous models both in terms of architecture and loss functions, we initially performed training and analysis on 1000 Genomes data with the same 10,000 SNPs as [20] to be able to conduct one-to-one comparisons. For these tests, we additionally implemented a new RBM scheme along with a new variational autoencoder (VAE) [29] which has a very similar architecture to our WGAN model. We used the VAE as a supplementary benchmark since the encoder-decoder form of the VAE can be seen as an analogue to the critic-generator form of the WGAN model. The objective function of VAE, on the other hand, is substantially different, which allows us to assess the robustness of the architecture we used (see Materials and Methods).

Based on the PCAs, all models generated AGs which could capture the population structure of the data, albeit new WGAN and RBM models were better at representing the real PC densities compared to the other models (Fig 1a). In our previous study, we reported that the GAN model had difficulty learning low frequency alleles observed in real genomes. The new WGAN and RBM showed improvement in capturing the real allele frequency distribution, especially for the low frequency ($<=0.2$) alleles with correlation coefficients for previous GAN (GAN_prev), previous RBM (RBM_prev), VAE, WGAN and RBM being 0.94, 0.83, 0.94, 0.96 and 0.99, respectively (Fig 1b). In terms of LD structure, RBM generated AGs seemed to have the closest decay scheme to the real data while WGAN, GAN and VAE generated AGs all had similar results without substantial difference (Supp fig S1). In addition, the new WGAN and RBM models preserved 3-point correlations better than the other models (Supp fig S2).

Figure 1. Principal component and allele frequency analyses of artificial genomes with 10,000-SNP size. a) Density plot of the PCA of combined real and artificial genome datasets. Density increases from red to blue. (**b**) Allele frequency correlation between real (x-axis) and artificial (y-axis) genome datasets. Bottom figures are zoomed at low frequency alleles (from 0 to 0.2 overall frequency in the real dataset).

None of the models have produced identical sequences and no full sequences were copied from the training dataset (Supp fig S3). The AA_{TS} scores for GAN_prev, RBM_prev, VAE, WGAN and RBM were 0.73 ($AA_{truth} = 0.57$, $AA_{syn} = 0.89$), 0.49 ($AA_{truth} = 0.46$, $AA_{syn} = 0.52$), 0.48 ($AA_{truth} = 0.47$, $AA_{syn} = 0.50$), 0.82 ($AA_{truth} = 0.77$, $AA_{syn} = 0.87$) and 0.47 ($AA_{truth} = 0.47$, $AA_{syn} = 0.47$), respectively. These values indicate underfitting (a hypothetical extreme case demonstrated in Fig 2a) for

GAN generated AGs, and slight overfitting (a hypothetical extreme case demonstrated in Fig 2b) for the RBM and VAE generated AGs (Supp fig S4). Although the new WGAN demonstrated slightly more underfitting than the previous GAN, the gap between the two components of AA_{TS} (AA_{truth} and AA_{syn}) was decreased (see Materials and Methods for the details of the terminology). We previously hypothesised that the low value of AA_{truth} and high value of AA_{syn} for the previous GAN might be due to the generator creating AGs based on averages from a local set of samples in small pockets (extreme case demonstrated in Fig 2c). This can be seen as a generative aberration which does not generalise to the whole dataset but is observed only regionally in small subsections of the data. We do not observe this behaviour in the new WGAN model. A general comparison of all the models based on multiple aggregated statistics is provided in Supp. Fig S5.

Figure 2. Schematic representation of different problematic training outcomes for generative models. Distances to the nearest neighbours are denoted by d_{xx} where x can be T (truth/real) and S (synthetic/generated). **a)** An extreme case of underfitting (or optimization issue) in which the nearest neighbours of real data points are real and the nearest neighbours of synthetic data points are synthetic, revealing two distinct clusters ($AA_{TS} >> 0.5$). **b)** An extreme case of overfitting in which the nearest neighbours of real data points are systematically synthetic and vice versa ($AA_{TS} << 0.5$). **c)** An extreme case of a specific type of generative aberration in which the nearest neighbours of both real and synthetic data points are synthetic ($AA_{syn} >> 0.5$ and $AA_{truth} << 0.5$). Hypothetically, this might occur when the generator generates new instances based on average information from a small collection of samples, causing low local variation. **d)** An extreme case of a specific type of generative aberration in which the nearest neighbours of both real and synthetic data points are real ($AA_{syn} << 0.5$ and $AA_{truth} >> 0.5$). This might possibly be observed when the generative model learns the main modes in real data but fails to mimic the densities and generates instances in the axes of the main modes with high variance.

Generating large-scale genomic data

Following the main motivation of the study, we trained the new WGAN and CRBM models on 1000 Genomes data with 65,535 SNPs. The WGAN model for this data was deeper compared to the model used for the 10,000-SNP data (see Materials and Methods). We again implemented a VAE similar to the WGAN architecture yet we could not train this model with satisfactory results (see Discussion). Both WGAN and CRBM generated AGs were able to capture the real population structure and PCA modes quite well (Fig 3a) along with allele frequencies (correlation coefficient for low frequency alleles being 0.97 for both models; Fig 3b), yet WGAN AGs had substantially more fixed alleles which had low frequency in the real dataset (Supp fig S6). Since computation of the full correlation matrix is very intensive due to large sequence size, we calculated an approximation of the LD decay based on a subset of SNP pairs (see Materials and Methods). AGs generated by both models had on average lower LD than real genomes, similarly to our previous findings (Fig 3c). In 3-point correlation analysis, CRBM performed better than WGAN for SNP triplets seperated by 1, 4, 16, 64, 256, 512 and 1024 SNPs. However, the score was similar for SNP triplets seperated by random distances (WGAN = 0.43, CRBM = 0.41; Supp fig S7).

Similarly to the 10,000-SNP dataset, neither of the models produced identical sequences and no full

Figure 3. Principal component, allele frequency and linkage disequilibrium (LD) analyses of artificial genomes with 65,535-SNP size. a) Density plot of the PCA of combined real genomes and artificial genomes generated by WGAN and CRBM. Density increases from red to blue. **b)** Allele frequency correlation between real and artificial genome datasets. Bottom figures are zoomed at low frequency alleles (from 0 to 0.2 overall frequency in the real dataset). **c)** LD decay approximation for real (grey), WGAN generated (blue) and CRBM generated (red) genomes (see Materials and Methods for details).

sequences were copied from the training dataset. WGAN captured the haplotypic pairwise distribution better than CRBM (pairwise distance radar score for WGAN = 1.00, CRBM = 0.94; Supp fig S8) but the two main peaks in real data were correctly represented by both models (Supp fig S9). The AA_{TS} value for WGAN AGs showed underfitting ($AA_{TS} = 0.91$) whereas the value for CRBM was slightly above the 0.5 sweet spot ($AA_{TS} = 0.56$; Supp fig S10). However, there was a huge contrast between AA_{truth} and AA_{syn} values for CRBM AGs ($AA_{truth} = 0.86$, $AA_{syn} = 0.26$), which might be an

indication of the anomaly depicted in Fig 2d. This is the opposite of what we observed for the previous   95
GAN (GAN_prev) model and might be due to AGs which exist outside the real data space as can be   96
seen from the PCA analysis (Fig 2a, Supp fig S11). A general comparison of the two models based on   97
multiple aggregated statistics is provided in Supp fig S8.   98

Discussion   99

In this study, we implemented generative neural networks for large-scale genomic data generation and   100
assessed various characteristics of the artificial genomes (AGs) generated by these networks. Initially, we   101
generated AGs from the 10,000-SNP dataset to be able to compare to the previous results from [20]. For   102
this dataset, we introduced a new RBM training scheme, a convolutional WGAN and a convolutional   103
VAE. Both WGAN and new RBM models substantially improved the quality of AGs in terms of all   104
summary statistics. For the 65,535-SNP dataset, we used a similar WGAN architecture (which is   105
essentially deeper in comparison to the architecture for the 10,000-SNP dataset) and a conditional RBM   106
(CRBM) protocol. AGs generated by these new models preserve population structure, allele frequency   107
distribution and haplotypic integrity of real genomes reasonably well with little or no privacy leakage   108
from the training data. Generative models trained with similar-sized genomic data have been reported in   109
the literature but the main goal of these studies was characterization of population structure via   110
dimensionality reduction and the generated genomes did not possess good haplotypic integrity [26, 30].   111
There have been other studies focusing on demographic parameter estimation [31] and data generation   112
[7, 8, 9, 10] for population genetics but these only included training with smaller genomic segments.   113
    The upscaling to a larger sequence size in comparison to our previous study is an essential step for   114
AGs to be utilised in real-life applications as publicly accessible alternatives for sensitive genomic   115
samples, yet obstacles remain. Although we could generate substantially larger sequences by   116
incorporating convolutions for the WGAN and a conditional approach for the RBM, training these large   117
models requires computational time and fine-tuning in most cases. The WGAN is usually preferred over   118
naive GAN in literature as it mitigates hyperparameter optimization and provide more stable training   119
[21]. However, we had to go through multiple combinations of architectures and hyperparameter values   120
to reach satisfying results. Even then, the training in our application involved further adjustment of the   121
generator learning rate after a certain epoch to capture the details of the population structure observable   122
in higher PC dimensions. This second round of training was helpful but some of the runs did not reach   123
an acceptable equilibrium (i.e., generated genomes had low quality after training), especially when   124
experimenting with reduced training sample sizes. For future applications, automated architecture and   125
hyperparameter tuning methods can help significantly for finding the optimal combinations without   126
extensive trial and error [32, 33]. VAEs might be seen as better alternatives in terms of training stability   127
compared to GANs since they do not suffer from the difficulty of balancing two networks in an   128
adversarial manner, yet we could not obtain high-quality AGs for the 65,535-SNP dataset. Presumably,   129
considerably better outcomes can be achieved with further architectural, hyperparameter and loss   130
function exploration, which is outside the scope of this study.   131
    The other approach we presented to incorporate large-scale data was the conditional training of   132
RBMs. Instead of a single training of a large and deep model as in the case of WGAN, CRBM training   133
includes multiple training runs of a small model. A main advantage of this method is that any sequence   134
size can theoretically be generated as long as the positional conditionality is not broken over the target   135
genome segment. Therefore, the only bottleneck in terms of computation is the time needed to train all   136
the RBMs. Currently, the learned weights are specific to each machine and no parameters are shared   137
between RBMs. This advantageously allows parallel training when needed, but produces a large number   138
of parameters to be optimized since the number of weights and biases has to be multiplied by the   139
number of machines. Further studies could investigate whether parameter sharing between machines (i.e.,   140
between regions) and/or within each machine (through convolutions) is advantageous or instead   141
complicates training. In addition, many datasets also present a difficulty during training, because the   142
equilibrating time for Markov chains diverges as the training goes on, causing issues for sampling (and   143
re-sampling) [34]. To overcome this, we relied on out-of-equilibrium training as described in Materials   144

and Methods. While this approach improved training stability and also the quality of the generated samples with respect to other approaches, it has the disadvantage that the learned features cannot be easily interpreted.

For the assessment of overfitting and underfitting, we utilised the AA_{TS} score and haplotypic pairwise distances as in [20]. An interesting finding was the large difference between two terms of the AA_{TS} score (AA_{truth} and AA_{syn}) for AGs generated by the CRBM even though the averaged AA_{TS} score was good. Interestingly, this is the opposite of what we had observed for our previously published GAN model and possibly points to the type of generative aberration demonstrated in Fig 2d. In fact, it is known that the likelihood function used to infer the parameters of RBMs tends to create potentially spurious modes -that do not match any region of the dataset-, which might explain these patterns. For further investigation, we performed a nearest neighbour chain analysis since we would expect the nearest neighbours of the nearest neighbours for CRBM AGs to be mostly real genomes with this anomaly. For this analysis, we computed the frequencies of all observable patterns for the nearest neighbour chains of size 2 to 5. A pattern indicates the succession of data type (synthetic/S or truth/T) when starting from a point (the first letter) and moving successively to the nearest neighbour, then the nearest neighbour of the nearest neighbour, and so on until reaching the chain size. (Table 1). High frequency of ST, STT, STTT, STTTT and low frequency of SS, SSS, SSSS, SSSSS measurements provide additional evidence that what we observe for the CRBM AGs is possibly similar to the scenario seen in Fig 2d. To the best of our knowledge, this type of anomaly for generative models has not been reported in literature and could have been missed by classical evaluation metrics. Such complex overfitting/underfitting phenomena require vigilance and further investigation in future generative studies.

Despite these issues which remain to be further studied, additional improvements in model training and increased privacy guarantees for generated genomes can pave the way for the first artificial genome banks in the near future, accelerating global access to the vast amount of restricted genomic data.

Table 1. Nearest neighbour chain analysis. Frequencies of series of generated (synthetic - S) and real (truth - T) samples in chains of nearest neighbours (from size 2 to 5). To avoid loops, a sample was removed once reached in the chain. Expected frequency for chains of size 2 is 0.25, size 3 is 0.125, size 4 is 0.0625 and size 5 is 0.03125.

SS	ST	SSS	SST	STT
0.1258	0.3742	0.0519	0.0739	0.3267
TT	**TS**	**TTT**	**TTS**	**TSS**
0.4389	0.0611	0.3965	0.0424	0.0167
STS	**SSSS**	**STTT**	**SSSSS**	**STTTT**
0.0475	0.0356	0.3081	0.0313	0.2996
TST	**TTTT**	**TSSS**	**TTTTT**	**TSSSS**
0.0444	0.3799	0.0107	0.3712	0.0085

Materials and Methods

Data

We used two sets of 1000 Genomes [35] data: (i) 10,000 SNPs from chromosome 15 identical to the ones picked by [20], and (ii) 65,535 SNPs from chromosome 1 within the Omni 2.5 genotyping array framework. Further downsampling of the array framework was performed to create a dataset with a reasonable SNP number for faster training trials and the specific number of 65,535 SNPs was decided to be in the form of (2n - 1) for easy implementation of convolutional scaling. For the 10,000-SNP dataset, we used padding with zeros to match the (2n - 1) form. Both datasets have the same 2504 individuals and 5008 phased haplotypes used for training the models. The data format is the same as [20] where the rows are phased haplotypes and columns are positions which hold alleles represented by 0 (reference) and 1 (alternative).

WGAN implementation

WGAN models were coded with python-3.9 and pythorch-1.11 [36]. Our implementation is a Wasserstein
GAN with gradient penalty (WGAN-GP) consisting of a critic which estimates the earth mover's
distance between real and generated data distributions, and a generator which generates new genomic
data from Gaussian noise (Fig 4). Unlike the discriminator in naive GAN which performs a classification
task, the critic provides a "realness" score (an approximation of Earth-mover's distance) for generated
and real samples. WGAN loss function is as follows:

$$E_x[C(x)] - E_z[C(G(z)]$$

where C is the critic, G is the generator, x is real data point and z is Gaussian noise. The critic function
C must be Lipschitz continuous; thus, the original study relied on weight clipping to enforce an upper
bound for the gradient [21]. However, we designed a WGAN with gradient penalty (WGAN-GP) rather
than weight clipping, as GP was shown to be a better alternative [24]. In our implementation, the critic
uses convolution layers whereas the generator uses convolution and transposed convolution layers (Fig
4a). Both the generator and the critic have trainable location-specific vectors as additional channels at
every block except for the residual blocks. These vectors, similar to the ones integrated by [26] in their
autoencoder, consist of trainable variables that allow the models to preserve positional information which
would otherwise diminish due to the invariance of convolution operations. In addition to this, the
generator has two noise channels at every block. This gives the generator flexibility to decide at which
depth the mapping to latent space can occur. We also implemented "packing" to overcome mode
collapse by adjusting the discriminator to take multiple samples as input [28]. In our implementation,
the input sample number for the discriminator was set to 3 intuitively, to match the 3 main population
modes (Africa, West Eurasia, Asia) observable in the 1000 Genomes data. The initial length of the input
for the generator is 4, which is gradually transformed into features of larger sizes until it reaches the
sequence size of 65,535 or 16,383 in the output (Fig 4b).

Figure 4. Wasserstein GAN (WGAN) model for the 65,535-SNP dataset. a) Representation of the generator, critic and residual blocks. Channel dimensions are not proportional and do not reflect the real implementation. The generator block has one trainable location-specific variable (blue) and two latent space vectors (red) as additional channels concatenated to the input. The critic block has one trainable location-specific variable (blue) as an additional channel concatenated to the input. **b)** Architecture of the WGAN model. White rectangles correspond to generic generator and critic blocks whereas grey rectangles correspond to generic residual blocks. Numbers in parentheses above blocks show channels and length, respectively (C, L). Dotted connections are residual connections where the input value is added to the output value of the block before passing to the next block. Yellow input and output blocks differ from the generic ones for proper dimension adjustments.

The generator layers are followed by batch normalisation and leaky ReLU activation (alpha = 0.01) except for the final layer which has a sigmoid activation. The critic layers are followed by instance normalisation and leaky ReLU activation (alpha = 0.01) except for the final layer which is a fully connected layer with no activation. We used Adam optimizer to train both the generator and the critic with a learning rate of 0.0005 and β_1, β_2 = (0.5, 0,9). β_1 was set to 0.5 as suggested by [12]. For each batch training of the generator, the critic was trained 10 times as suggested by the authors of the original WGAN [21]. We assessed the outputs of the generator at each epoch during training via PCA. We stopped training when generated and real genome clusters visually overlapped in PC space (components 1 to 4). In the case of 65,535-SNP data, this initial training was not sufficient to reach a good overlap of higher degree principal components, thus, we performed a second brief training (up to 200 epochs) with 10-fold lower generator learning rate (0.00005). Our WGAN architecture for the 10,000-SNP data was conceptually the same as for the 65,535-SNP data, but shallower with fewer blocks. The detailed python

scripts can be accessed at `https://gitlab.inria.fr/ml_genetics/public/artificial_genomes`.

RBM implementation

For the out-of-equilibrium RBM, the algorithm was coded using the pytorch library, and an example of the code can be found at `https://github.com/AurelienDecelle/TorchRBM`. This implementation handles GPU to perform both the training and the sampling. In RBM, the learning consists in maximising the likelihood of the model using gradient descent. We used both binary units 0,1 for the visible and hidden nodes, and the number of hidden units was chosen to be about the same order as the number of visible ones. The RBM is therefore defined as a probability distribution over the set of visible units, $\underline{s}$, and hidden units, $\underline{\tau}$, where both type of variables interact via a pairwise weight matrix $\underline{w}$ and the local biases $\underline{\theta}$ and η help to adjust the mean value of each unit:

$$p(\underline{s}, \underline{\tau}) = \frac{1}{Z} exp(\sum_{ia} w_{ia} s_i \tau_a + \sum_i \theta_i s_i + \sum_a \eta_a \tau_a)$$

And the likelihood of such model is given by:

$$L = \sum_{m=1}^{M} \left[\sum_i \theta_i s_i^{(m)} + \sum_a \log(1 + \exp(\sum_i w_{ia} s_i^{(m)} + \eta_a)) \right] - M \log(Z)$$

where the index m is indexing the samples of the dataset (M being the total number of samples) and Z is the normalization constant, or partition function, of the probability distribution. We optimize the weights and biases w, θ and η during the learning. In this implementation, the training was based on the out-of-equilibrium method [37, 23]. The main difference with the more conventional learning is that the sampling which is done to compute the correlation of the model is performed in a very precise way: a given random initial condition is chosen amongst a certain probability distribution $p_0(x)$ (kept fixed during all the learning), and a fix (all along learning) number of Monte Carlo steps is done during the training. When using this particular training procedure, in order to sample new data, it is enough to generate the Monte Carlo chains following the same dynamical process: same initial conditions $p_0(x)$ and same number of MC steps. In the provided experiments, the initial conditions were chosen uniformly at random (each unit having equal probability to be 0 or 1) and the number of MC steps was either 100 (for the 65,535-SNP dataset) or 200 (for the 10,000-SNP dataset) but the qualitative results were mostly not affected. The learning rate of the model was chosen such that the eigenvalues of the learning weight matrix are smoothly increasing during the first epochs from almost zero to values of $\sim O(1)$.

For the generation of very long sequences, we designed a novel procedure based on conditional-RBMs (CRBMs) [38, 22] (Fig 5). The CRBM consists in the learning of correlation patterns conditionally to some input variables. Hence, instead of considering all the dataset X, we separate it into two parts $X = X_P \cup X_I$, and the CRBM will learn to generate X_I (the inferred variables) based on X_P (the pinned variables). Therefore, we design a gradient that will learn how to generate the variables X_I given that we provide the variables X_p. In practice, denoting $\underline{s}$ as the variables to be inferred and $\underline{x}$ as the pinned ones, we will maximize the following quantity:

$$p(\underline{s} \in I, \underline{x} \in P) = \frac{1}{Z} exp(\sum_{ia} w_{ia} s_i \tau_a + \sum_i \theta_i s_i + \sum_a \eta_a \tau_a + \sum_a \tau_a \sum_j w_{ja} x_j)$$

Therefore, for each sample of the dataset, this construction is similar to a classical RBM with additional biases for the hidden nodes which depend on the pinned variables. During the learning, we infer the parameters of the model such that when showing a configuration of pinned variables X_P, the model will generate a sample that is correlated to it accordingly. This conditional model can be used to learn very long chains of variables. Let us consider that we have a dataset with 100,000 input variables. We can learn initially a regular RBM on the first 10,000 input variables. In parallel, we can also learn a conditional RBM on the input variables s_i with i in [5,000:15,000] using the first 5,000 variables as pinned variables. Therefore, this second RBM will, given 5,000 pinned variables, learn how to generate the 5,000 following ones. The same procedure is repeated with various input sets, always using the first 5,000 input nodes as pinned variables. Once learning is completed for all the RBMs, we can proceed using the following sequential method to generate new data:

1. Use the first RBM (non-conditional) to generate the first 10,000 input. ₂₆₁

2. Use the first CRBM to generate the next [10,000:15,000] inputs. To do that, we use the generated ₂₆₂
nodes [5,000:10,000] as pinned variables and generate the rest. ₂₆₃

3. We follow the same procedure until we finally generate the whole 100,000 variables. ₂₆₄

Figure 5. Illustration of the learning and sampling of a large sequence using a "classical" and a conditional RBM (CRBM). Initially, we train RBM1 (left) and RBM2 (right) in parallel. Both RBMs are essentially trained in a similar manner: random inputs are drawn and k MC steps are performed before computing the gradient and updating the weights using gradient descent. The difference for the CRBM (RBM2) is that half of the variables in the visible layer are pinned (crossed squares) to the real data during training while the rest is generated conditionally on these pinned variables. After training both machines, we can sample a complete new sequence. To do so, we start from random input and perform k MC steps to generate the first part of the sequence (light yellow-red) using RBM1. Then, we use half of this generated sequence (light red) as the pinned visible variables of the RBM2 (crossed squares) and initialise the rest as random input. We perform k MC steps on RBM2 while keeping the pinned variables fixed to generate the rest of the sequence (light blue). The letters next to arrows show the order of this sampling procedure.

This method was used to generate the large-scale 65,535-SNP dataset. We first trained a "normal" ₂₆₅
RBM on the first 5,000 input variables. Then, we made a set of 10,000 conditional RBM, where the first ₂₆₆
5,000 variables were used as pinned variables. All the models were trained with 1000 hidden nodes, and ₂₆₇
a learning rate of $\beta = 0.005$. The learning dynamics uses the Rdm-k method: each chain was generated ₂₆₈
starting from the uniform Bernoulli distribution, with k=100 for the training of the RBM and the ₂₆₉
CRBMs. ₂₇₀

VAE implementation ₂₇₁

VAE models were coded with python-3.9 and pythorch-1.11 [36]. The VAE architecture is very similar to ₂₇₂
the GAN architecture but somehow reversed: the encoder is an analogue to the critic and the decoder is ₂₇₃
an analogue to the generator (Supp fig S12). The last layer of the encoder outputs two vectors containing ₂₇₄
means (μ) and standard deviations (σ) so that the latent space can be sampled based on these values and ₂₇₅
fed to the decoder. The loss function consists of the reconstruction term, which measures the likelihood ₂₇₆
of the generated genomes (via log loss in our implementation), and the regularisation term which is the ₂₇₇
Kullback-Leibler divergence between the standard normal distribution and the prior distribution of the ₂₇₈
latent space. The regularisation term directs the latent space towards a standard normal distribution. ₂₇₉
After training completion, this allows sampling of new latent points from the standard distribution which ₂₈₀
are further transformed into new data points (new genomic sequences) through the decoder. ₂₈₁

Each layer in our implementation is followed by batch normalisation and leaky ReLU with alpha set to 0.01, except for the final layers. The decoder final layer is followed by a sigmoid function, whereas the encoder final μ and σ layers have linear activation. We used Adam optimizer with default settings and the learning rate set to 0.001. Similarly to the WGAN, we evaluated the training based on coherence of the PCA performed on real and generated genomes (components 1 to 4). We could not successfully train a VAE model which generates plausible AGs for the 65,535-SNP dataset. Further architecture and hyperparameter optimization is needed to better assess VAE models in this context. The detailed python scripts can be accessed at `https://gitlab.inria.fr/ml_genetics/public/artificial_genomes`.

Nearest Neighbour Adversarial Accuracy (AA_{TS})

Similarly to [20], we assessed the overfitting/underfitting characteristics of AGs using the AA_{TS} score [39]. AA_{TS} is calculated as follows:

$$AA_{truth} = \frac{1}{n} \sum_{i=1}^{n} \mathbf{1}(d_{TS}(i) > d_{TT}(i))$$

$$AA_{syn} = \frac{1}{n} \sum_{i=1}^{n} \mathbf{1}(d_{ST}(i) > d_{SS}(i))$$

$$AA_{TS} = \frac{1}{2}(AA_{truth} + AA_{syn})$$

where n is the number of samples in each dataset (real and generated), $d_{TS}(i)$ is the distance between the real (truth - T) sample index by i and its nearest neighbour in the generated (synthetic - S) dataset, $d_{TT}(i)$ is the distance between a real sample i and its nearest neighbour in the real dataset, $d_{ST}(i)$ is the distance between a generated sample i and its nearest neighbour in the real dataset, $d_{SS}(i)$ is the distance between a generated sample i and its nearest neighbour in the generated dataset, and $\mathbf{1}$ is the indicator function which returns 1 if the argument is true and 0 otherwise. Based on this equation, an AA_{TS} value below 0.5 indicates overfitting and an AA_{TS} value above 0.5 indicates underfitting.

Summary statistics

For the 65,535-SNP dataset, LD was computed only on a subset of pairs in order to fasten computation. To sample these pairs in an efficient way (i.e. approximately uniformly along the SNP distance log scale without computing the full matrix of SNP distances), we used the script from [40]. The remaining summary statistics (allele frequencies, haplotypic pairwise distances, PC scores, 3-point correlations and LD for the 10,000-SNP dataset) were computed as in [20] using the publicly available scripts at `https://gitlab.inria.fr/ml_genetics/public/artificial_genomes`. For the radar plots, we transformed the scores so that they span values between 0 and 1, where 0 represents poor performance and 1 high or perfect performance. Precisely, we used the allele frequency correlation for alleles with low frequency ($<= 0.2$) for the *Allele frequency* score and correlation of SNPs separated by random distances for the $3-point\ correlations$ score. For the *Pairwise distance* score, we used the Wasserstein distance between the distributions of haplotypic pairwise distances of real and generated data. We performed min-max scaling, using the value for a simple binomial generator model (from [20]) for the lowest bound 0. For the other scores, we used the following equations:

$$Overfitting = 1 - (0.5 - \min(AA_{truth}, 0.5)) - (0.5 - \min(AA_{syn}, 0.5))$$

$$Underfitting = 1 - (\max(AA_{truth}, 0.5) - 0.5) - (\max(AA_{syn}, 0.5) - 0.5)$$

$$LD = 1 - \sum (LD_{real} - LD_{generated})^2 / \sum LD_{real}^2$$

where $LD_{generated}$ and LD_{real} are average LD values for bins in the LD decay analyses (Fig 3c, Supp fig S1b). *Overfitting* and *Underfitting* equations were formulated to focus on below and above 0.5 AA_{TS} sweet spot, respectively, to provide a better resolution in terms of overfitting/underfitting assessment.

Acknowledgments 324

Funding by ANR-20-CE45-0010-01 RoDAPoG (B.Y., L.B., A.S., C.F., G.C., F.J.); the Comunidad de 325
Madrid and the Complutense University of Madrid (Spain) through the Atracción de Talento programs 326
(Refs. 2019-T1/TIC-13298), the Banco Santander and the UCM (grant PR44/21-29937), and the 327
Ministerio de Economía y Competitividad, Agencia Estatal de Investigación and Fondo Europeo de 328
Desarrollo Regional (FEDER) (Spain and European Union) through the grant PID2021-125506NA-I00 329
(A.D.); Labex DigiCosme (project ANR-11-LABEX-0045-DIGICOSME) operated by ANR as part of the 330
program "Investissement d'Avenir" Idex Paris-Saclay (ANR-11-IDEX-0003-02) (L.B.). Thanks to the 331
Inria TAU team of the University of Paris-Saclay and the High Performance Computing Center of the 332
University of Tartu for providing computational resources. 333

References

1. T. Sanchez, J. Cury, G. Charpiat, and F. Jay, "Deep learning for population size history inference: Design, comparison and combination with approximate Bayesian computation," *Molecular Ecology Resources*, 2020.

2. A. Koropoulis, N. Alachiotis, and P. Pavlidis, "Detecting Positive Selection in Populations Using Genetic Data," in *Statistical Population Genomics* (J. Y. Dutheil, ed.), Methods in Molecular Biology, pp. 87–123, New York, NY: Springer US, 2020.

3. H. L. Nicholls, C. R. John, D. S. Watson, P. B. Munroe, M. R. Barnes, and C. P. Cabrera, "Reaching the End-Game for GWAS: Machine Learning Approaches for the Prioritization of Complex Disease Loci," *Frontiers in Genetics*, vol. 11, 2020.

4. C. Caudai, A. Galizia, F. Geraci, L. Le Pera, V. Morea, E. Salerno, A. Via, and T. Colombo, "AI applications in functional genomics," *Computational and Structural Biotechnology Journal*, vol. 19, pp. 5762–5790, Jan. 2021.

5. K. Korfmann, O. E. Gaggiotti, and M. Fumagalli, "Deep learning in population genetics," *Genome Biology and Evolution*, Jan. 2023.

6. N. Killoran, L. J. Lee, A. Delong, D. Duvenaud, and B. J. Frey, "Generating and designing DNA with deep generative models," Dec. 2017. arXiv:1712.06148.

7. W. W. Booker, D. D. Ray, and D. R. Schrider, "This population doesn't exist: learning the distribution of evolutionary histories with generative adversarial networks," Sept. 2022.

8. M. Perera, D. M. Montserrat, M. Barrabés, M. Geleta, X. Giró-I-Nieto, and A. G. Ioannidis, "Generative Moment Matching Networks for Genotype Simulation," in *2022 44th Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC)*, pp. 1379–1383, July 2022.

9. S. Das and X. Shi, "Offspring GAN augments biased human genomic data," in *Proceedings of the 13th ACM International Conference on Bioinformatics, Computational Biology and Health Informatics*, BCB '22, (New York, NY, USA), pp. 1–10, Aug. 2022.

10. D. M. Montserrat, C. Bustamante, and A. Ioannidis, "Class-Conditional VAE-GAN for Local-Ancestry Simulation," Nov. 2019. arXiv:1911.13220.

11. I. J. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio, "Generative Adversarial Networks," June 2014. arXiv:1406.2661.

12. A. Radford, L. Metz, and S. Chintala, "Unsupervised Representation Learning with Deep Convolutional Generative Adversarial Networks," Jan. 2016. arXiv:1511.06434.

13. J. Guo, S. Lu, H. Cai, W. Zhang, Y. Yu, and J. Wang, "Long Text Generation via Adversarial Training with Leaked Information," Dec. 2017. arXiv:1709.08624.

14. L. Seninge, I. Anastopoulos, H. Ding, and J. Stuart, "VEGA is an interpretable generative model for inferring biological network activity in single-cell transcriptomics," *Nature Communications*, vol. 12, p. 5684, Sept. 2021.

15. J. Yoon, J. Jordon, and M. van der Schaar, "GAIN: Missing Data Imputation using Generative Adversarial Nets," June 2018. arXiv:1806.02920.

16. M. Shabani and L. Marelli, "Re-identifiability of genomic data and the GDPR," *EMBO reports*, vol. 20, p. e48316, June 2019.

17. B. J. Evans and G. P. Jarvik, "Impact of HIPAA's minimum necessary standard on genomic data sharing," *Genetics in Medicine*, vol. 20, pp. 531–535, May 2018.

18. S. Wang, N. Mohammed, and R. Chen, "Differentially private genome data dissemination through top-down specialization," *BMC Medical Informatics and Decision Making*, vol. 14, p. S2, Dec. 2014.

19. N. Boscarino, R. A. Cartwright, K. Fox, and K. S. Tsosie, "Federated learning and Indigenous genomic data sovereignty," *Nature Machine Intelligence*, vol. 4, pp. 909–911, Nov. 2022.

20. B. Yelmen, A. Decelle, L. Ongaro, D. Marnetto, C. Tallec, F. Montinaro, C. Furtlehner, L. Pagani, and F. Jay, "Creating artificial human genomes using generative neural networks," *PLOS Genetics*, vol. 17, Feb. 2021.

21. M. Arjovsky, S. Chintala, and L. Bottou, "Wasserstein GAN," Dec. 2017. arXiv:1701.07875.

22. G. W. Taylor, G. E. Hinton, and S. Roweis, "Modeling Human Motion Using Binary Latent Variables," in *Advances in Neural Information Processing Systems*, vol. 19, MIT Press, 2006.

23. A. Decelle, C. Furtlehner, and B. Seoane, "Equilibrium and non-Equilibrium regimes in the learning of Restricted Boltzmann Machines," in *Advances in Neural Information Processing Systems*, vol. 34, pp. 5345–5359, Curran Associates, Inc., 2021.

24. I. Gulrajani, F. Ahmed, M. Arjovsky, V. Dumoulin, and A. Courville, "Improved training of wasserstein GANs," in *Proceedings of the 31st International Conference on Neural Information Processing Systems*, NIPS'17, (Red Hook, NY, USA), pp. 5769–5779, Dec. 2017.

25. T. Karras, S. Laine, and T. Aila, "A Style-Based Generator Architecture for Generative Adversarial Networks," Mar. 2019. arXiv:1812.04948.

26. K. Ausmees and C. Nettelblad, "A deep learning framework for characterization of genotype data," *G3 Genes|Genomes|Genetics*, vol. 12, Mar. 2022.

27. K. He, X. Zhang, S. Ren, and J. Sun, "Deep Residual Learning for Image Recognition," Dec. 2015. arXiv:1512.03385.

28. Z. Lin, A. Khetan, G. Fanti, and S. Oh, "PacGAN: The power of two samples in generative adversarial networks," Nov. 2018. arXiv:1712.04086.

29. D. P. Kingma and M. Welling, "Auto-Encoding Variational Bayes," Dec. 2022. arXiv:1312.6114.

30. C. J. Battey, G. C. Coffing, and A. D. Kern, "Visualizing population structure with variational autoencoders," *G3 Genes|Genomes|Genetics*, vol. 11, Jan. 2021.

31. Z. Wang, J. Wang, M. Kourakos, N. Hoang, H. H. Lee, I. Mathieson, and S. Mathieson, "Automatic inference of demographic parameters using generative adversarial networks," *Molecular Ecology Resources*, vol. 21, pp. 2689–2705, Nov. 2021.

32. F. Isensee, P. F. Jäger, S. A. A. Kohl, J. Petersen, and K. H. Maier-Hein, "Automated Design of Deep Learning Methods for Biomedical Image Segmentation," *Nature Methods*, vol. 18, pp. 203–211, Feb. 2021. arXiv:1904.08128.

33. L. Wu, G. Perin, and S. Picek, "I Choose You: Automated Hyperparameter Tuning for Deep Learning-based Side-channel Analysis," *IEEE Transactions on Emerging Topics in Computing*, pp. 1–12, 2022.

34. N. Béreux, A. Decelle, C. Furtlehner, and B. Seoane, "Learning a Restricted Boltzmann Machine using biased Monte Carlo sampling," Oct. 2022. arXiv:2206.01310.

35. T. . G. P. Consortium, "A global reference for human genetic variation," *Nature*, vol. 526, pp. 68–74, Oct. 2015.

36. A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Köpf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala, "PyTorch: An Imperative Style, High-Performance Deep Learning Library," Dec. 2019. arXiv:1912.01703.

37. E. Agoritsas, G. Catania, A. Decelle, and B. Seoane, "Explaining the effects of non-convergent sampling in the training of Energy-Based Models," Jan. 2023. arXiv:2301.09428.

38. G. Fissore, A. Decelle, C. Furtlehner, and Y. Han, "Robust Multi-Output Learning with Highly Incomplete Data via Restricted Boltzmann Machines," Dec. 2019. arXiv:1912.09382.

39. A. Yale, S. Dash, R. Dutta, I. Guyon, A. Pavao, and K. P. Bennett, "Privacy Preserving Synthetic Health Data," Apr. 2019.

40. J. Cury, B. C. Haller, G. Achaz, and F. Jay, "Simulation of bacterial populations with SLiM," *Peer Community Journal*, vol. 2, 2022.

Supplementary Figures

Figure S1. Comparative linkage disequilibrium (LD) analysis of artificial genomes generated by different models for the 10,000-SNP data. a) LD heatmap based on r^2 matrices. Sections below diagonals correspond to LD in real genomes and sections above diagonals correspond to LD in artificial genomes. **b)** LD decay as a function of SNP distance. SNPs were binned based on distance and average LD was calculated. **c)** LD decay correlation between real and artificial datasets. x axis corresponds to real LD bins and y axis corresponds to generated LD bins. Sites fixed in any of the datasets were removed for all the LD calculations.

Figure S2. 3-point correlation analysis of SNP triplets for the 10,000-SNP data with inter-SNP distances of 1, 4, 16, 64, 256, 512 and 1024 (from left to right, top to bottom). The last panel (bottom right) shows correlation for triplets of SNPs drawn randomly.

Figure S3. Distribution of haplotypic pairwise difference within (left figure) and between (right figure) 10,000-SNP datasets.

Figure S4. Nearest neighbour adversarial accuracy (AATS) of artificial genomes generated by different models for the 10,000-SNP dataset. Values below 0.5 (black line) indicate overfitting and values above indicate underfitting. See Materials and Methods for the details of the metrics.

Figure S5. Radar plot comparing artificial genomes generated by different models for the 10,000-SNP dataset. Values closer to 0 indicate poor performance whereas values closer to 1 indicate good performance. See Materials and Methods for the details of the representative statistics.

Figure S6. Analysis of fixed alleles in artificial genomes with 65,535 SNPs. Left figures show the number of fixed alleles in artificial genomes (x axis) versus the frequency of these alleles in the real dataset (y axis). Right figures show the distribution of the frequency of alleles fixed in the artificial dataset but not fixed in the real dataset.

Figure S7. 3-point correlation analysis of SNP triplets for the 65,535-SNP data with inter-SNP distances of 1, 4, 16, 64, 256, 512 and 1024 (from left to right, top to bottom). The last panel (bottom right) shows correlation for triplets of SNPs drawn randomly.

Figure S8. Radar plot comparing artificial genomes generated by WGAN and CRBM models for the 65,535-SNP dataset. Values closer to 0 indicate poor performance whereas values closer to 1 indicate good performance. See Materials and Methods for the details of the representative statistics.

Figure S9. Distribution of haplotypic pairwise difference within (left figure) and between (right figure) 65,535-SNP datasets.

Figure S10. Nearest neighbour adversarial accuracy (AATS) of artificial genomes generated by different models for the 65,535-SNP dataset. Values below 0.5 (black line) indicate overfitting and values above indicate underfitting. See Materials and Methods for the details of the metrics.

Figure S11. Principal component analysis (PCA) of combined real and artificial genomes with 65,535 SNPs.

Figure S12. Architecture of the variational autoencoder (VAE) model for the 10,000 SNP dataset. Generic blocks of the encoder and decoder (white rectangles) are conceptually the same with the generic critic and generator blocks respectively (Fig 4a), except that there are no latent space channels concatenated to the input and no additional noise vectors at each block. The major difference from WGAN in terms of architecture is the last block of the encoder, which encodes mu and sigma as the mean and the standard deviation of the generated distribution, which are used to sample the latent space. Dotted connections are residual connections where the input value is added to the output value of the block before passing to the next block. Numbers in parentheses above blocks show channels and length, respectively (C, L).