A computationally informed comparison between the strategies of rodents and humans in visual object recognition

1 Anna Elisabeth Schnell[1*], Maarten Leemans[1], Kasper Vinken[2], Hans Op de Beeck[1]

[1] Department of Brain and Cognition & Leuven Brain Institute, KU Leuven, Leuven, Belgium

[2] Department of Neurobiology, Harvard Medical School, Boston, Massachusetts, United States of America

* Corresponding author

E-mail: annaelisabeth.schnell@kuleuven.be

Data availability:

The data has been made publicly available via the Open Science Framework and can be accessed at https://osf.io/9eqyz/ .

Abstract

Many species are able to recognize objects, but it has been proven difficult to pinpoint and compare how different species solve this task. Recent research suggested to combine computational and animal modelling in order to obtain a more systematic understanding of task complexity and compare strategies between species. In the present study, we created a large multidimensional stimulus set and designed a visual discrimination task partially based upon modelling with a convolutional deep neural network (CNN). Experiments included rats (N = 11; 1115 daily sessions in total for all rats together) and humans (N = 45). Each species was able to master the task and generalize to a variety of new images. Nevertheless, rats and humans showed very little convergence in terms of which object pairs were associated with high and low performance, suggesting the use of different strategies. There was an interaction between species and whether stimulus pairs favoured early or late processing in a CNN. A direct comparison with CNN representations and visual feature analyses revealed that rat performance was best captured by late convolutional layers and partially by visual features such as brightness and pixel-level similarity, while human performance related more to the higher-up fully connected layers. These findings highlight the additional value of using a computational approach for the design of object recognition tasks. Overall, this computationally informed investigation of object recognition behaviour reveals a strong discrepancy in strategies between rodent and human vision.

1 Introduction

Humans show high proficiency in invariant object recognition, the ability to recognize the same objects from different viewpoints or in different scenes. This ability is supported by the ventral visual stream, the so-called *what stream* (Logothetis & Sheinberg, 1996). A question that is repeatedly addressed in vision studies is whether and how we can model this stream by means of animal models or computational models to further examine and quantify the representations along the ventral visual stream. Computationally, researchers have recently modelled this stream by using convolutional deep neural networks (CNNs), as for example done by Avberšek and colleagues (2021), Cadieu and colleagues (2014), Duyck and colleagues (2021), Güçlü & Gerven (2015), Kalfas and colleagues (2018), Kar and colleagues (2019), Kubilius and colleagues (2016), Pospisil and colleagues (2018) and Vinken & Op de Beeck (2021). Lately, the rodent model has become an important animal model in vision studies, motivated by the applicability of molecular and genetic tools rather than by the visual capabilities of rodents. Past studies have examined behavioural (Alemi-Neissi et al., 2013; De Keyser et al., 2015; Djurdjevic et al., 2018; Schnell et al., 2019; Tafazoli et al., 2012; Vermaercke & Op de Beeck, 2012; Vinken et al., 2014; Zoccolan, 2015) (for a review see Zoccolan, 2015) as well as neural (Matteucci et al., 2019; Tafazoli et al., 2017; Vermaercke et al., 2014; Vinken et al., 2016) data of rodents (rats and mice) performing in visual pattern recognition tasks. The behavioural findings suggested that rats are capable of learning complex visual discrimination tasks. Here we plan to integrate computational and animal modelling approaches, by using data about information processing in artificial neural networks when designing the animal experiments.

One aspect that almost all rodent studies have in common is that the exact task and stimuli are chosen based on what we know from human and monkey studies. Earlier research showed that the intuition of researchers about the complexity of visual tasks can be misleading (Vinken & Op de Beeck, 2021). Through computational CNN modelling of the tasks from previous studies, they showed that behavioural strategies that seem complex at first hand might be best modelled through relatively early

levels of processing in CNNs. They recommended that future studies could obtain more direct

information about the complexity of visual tasks and behavioural strategies by incorporating neural

network models in the design phase of the experiment. One way of implementing this is to train

rodents in a challenging and multidimensional visual task and use CNNs to select stimulus examples

targeting strategies with different levels of complexity.

In the present study, we implemented this approach and created a large stimulus set that can be used

for a variety of visual experiments. We decided to create the stimuli in a way that they are adaptable

to different types of tasks, such as a "simple" discrimination task or non-linear tasks (e.g. Bossens &

Op de Beeck, 2016). We then took a subset of these stimuli and performed a visual discrimination

experiment in rats (see Figure 1 for the design). The task itself was defined in a stimulus space with

two dimensions, here referred to as concavity and alignment. The stimuli consisted of a base shape

that varied in concavity, with three spheres attached to it that were either horizontally aligned or

misaligned. The task was then further complicated by transforming the stimuli along several

dimensions that preserve the identity of the object. We started by training the animals in a base

stimulus pair, with the target being the concave object with horizontally aligned spheres. Once the

animals were trained in this base stimulus pair, we used the identity-preserving transformations to

test for generalization. After a number of transformation phases, we selected a final stimulus set by

choosing a combination of transformations based on the outcomes of a trained CNN. Using the neural

network as a (basic) model for the different stages of ventral visual stream processing, we chose

stimulus pairs that require either higher or lower levels of processing and thus allow us to maximally

differentiate between the task strategies used by the animals. As a final part of the current study, we

performed an online human experiment with the same stimuli and design as the experiment for the

rats, providing us with a rich three-way comparison of rat behavioural data with human behavioural

data and with CNN data.

Figure 1 The design of the animal study, including the stimuli. Animals started with a standardized shaping procedure,

followed by three training protocols, as indicated by the dashed outline. In these protocols, animals received real reward, i.e.

reward for touching the target. The target corresponds to the concave object in all training protocols. The rats received

correction trials for incorrect answers, i.e. touching the convex object. After the three training protocols, the animals went

through a number of testing protocols. The order of the first six protocols (*) and the last two testing protocols (**) was

counterbalanced between the animals. During testing protocols, animals received one third old trials, and two third new

trials. In the new trials, they received random reward in 80% of the trials whereas in the old trials, they received real reward

and correction trials if necessary. Again, the target in the testing protocols correspond to the concave objects whereas the

distractors correspond to the convex objects.

2   Results

In this study, we trained and tested 11 rats and 45 humans on a complex two-dimensional discrimination task (see Figure 1 for the design of the rat study, and Supplemental Figure 7 for the design of the human study). Rats and humans were first trained in a base pair. Next we tested their ability to generalize across several image transformations. In the last two protocols of the design, we used a computational approach to select stimuli that require different visual strategies.

2.1   Animal study

Training. We first checked the variation in performance across phases and stimulus pairs during training. In the first *Training Phase*, animals were trained in the base stimulus pair, which were the maximally different target and distractor in a concavity x alignment stimulus space where each dimension was varied with 4 values (4 x 4 space). This training was successful for all twelve animals and lasted on average for 8.62 sessions (SD = 1.61). Animals were trained until they reached 80% performance for two consecutive sessions.

Once the animals were successfully trained, we examined whether they use both dimensions (concavity and alignment) by presenting them with two additional stimuli pairs where the target and distractor differ in only one dimension (see Figure 1, *Dimension learning).* Performance on the old pair was similar to training performance (85.83%). The animals performed well with the stimuli that differ only along the concavity dimension (78.79%), although it was significantly lower than the performance on the base pair (paired t-test on rat performance, t(11) = 3.77, p = 0.003). Performance dropped to 67.83% for the alignment-only pair, yet also significantly higher than chance level (one-sample t-test, p < .0001). Overall, the *Dimension learning* protocol provides evidence that the animals have picked up each of the two dimensions. This finding already excludes trivial explanations in terms of simple visual dimensions. For example, while concavity is correlated with horizontal size (distractor wider) and with overall brightness (distractor brighter, thus the opposite relevance as in the shaping phase), these simple dimensions cannot explain above-chance performance on the alignment dimension.

The third training protocol consisted of a number of small transformations, as visualized in Figure 1 (*Transformations*). Rats learned these transformations very well, with an average performance of 83.05% (see Figure 2). The pairwise percentage matrix in Figure 2 shows that the distractor with the Size transformation (most right column in the matrix) affected the rat performance the most.

The variation in performance across targets and distractors can be due to a variety of factors. This can include simple dimensions such as brightness. In the base pair, the distractor is brighter than the target. While this is the opposite from the shaping task of detecting a shape versus a black screen, visual inspection of Figure 2 suggests that the animals perform poorer on trials in which the distractor display is not so much brighter (e.g., when it is small). To quantify this effect of brightness, we calculated the correlation between the performances in the matrix and the difference in pixel values (and thus brightness) of the stimulus pairs. This resulted in a (Pearson) correlation of -0.59 ($p < 0.01$), suggesting that there is indeed an effect of brightness. Yet, brightness is at best a partial explanation because all percentages in the matrix are above chance, with the lowest percentage in the matrix being 68.83%, even though in some pairs the difference in pixel values is abolished or even opposite from the base pair.

Overall the findings from the training phase and the above-chance performance on a variety of dimensions and transformations suggest that the rats have learned a pattern classification task with a level of complexity that might be competitive with other tasks in the rodent literature.

<div align="center">(a)</div>

<div align="center">(b)</div>

Figure 2 (a) Results of the Dimension learning training protocol. The black dashed horizontal line indicates chance level performance and the red dashed line represents the 80% performance threshold. The blue circles on top of each bar represent individual rat performances. The three bars represent the average performance of all animals on the old pair (Old), the pair that differs only in concavity (Conc) and on the pair that differs only in alignment (Align). **(b) Results of the Transformations training protocol.** Each cell of the matrix indicates the average performance per stimulus pair, pooled over all animals. The columns represent the distractors, whereas the rows separate the targets. The colour bar indicates the performance correct.

Testing across transformations. The six protocols that test generalization to various transformations with new, untrained images are associated with performances lower than 80% (binomial test, see Supplemental Table 5 (lower table) for detailed table with results), but significantly higher than chance level (see Supplemental Table 5 (lower table)). The pairwise percentage matrices of the animals in Figure 3 provide a more detailed view of what is happening in every test, and Supplemental Figure 2 shows the individual accuracy for each animal. The distractor has a higher impact on performance than the target in some tests. Supplemental Table 6 shows the marginal means and standard deviation for each target and distractor for these two test protocols. From these means it is clear that there is a higher variation in the performance between distractors in *Rotation X* (52%-65%) and *Rotation Z* (56%-73%) than between targets (55%-60% resp. 60%-66%). The same happens in the size test protocol.

Figure 3 Pairwise percentage matrices of all nine testing protocols for the rat data. The colour bar indicates the percentage correct of the pooled responses of all animals together. The more red a cell is, the higher the average performance. Values below 40% accuracy are indicated in the highest intensity of blue. Cells with an 'o' marker indicate a below chance performance, whereas cells with an *, ** or *** marker indicate a performance that is significantly higher than chance level (p-value < 0.05, < 0.01 or < 0.001 respectively). This was calculated with a binomial test on pooled performance of all animals.

After these first six test protocols, the animals were presented with a schedule where all three rotations are combined (see Figure 1). On the new stimuli, the animals performed 58.56%, which is rather low, but still significantly different from chance level (binomial test on pooled performance of all animals: p < 0.0001; 95% CI [0.57;0.60]).

Testing computational levels of complexity. For the final two test protocols, we used a CNN to find image pairs that would contrast strategies based upon a different stage in visual processing, with either early layers having lower performance than high layers (*Zero vs. high*), or early layers having better performance than high layers (*High vs. zero*). Rat performance was particularly low for *Zero vs. high*

(56.47%), yet still significantly different from chance level when averaged across all stimulus pairs

(binomial test on pooled performance of all animals; p < 0.0001; 95% CI [0.55;0.58]). In contrast, rats

were able to solve the *High vs. zero* pairs not only better than chance (average: 64.84%; binomial test

on pooled performance of all animals; p < 0.0001; 95% CI [0.63;0.66]), but also significantly better than

Zero vs. high (paired t-test on rat performance, t(10) = -4.49, p = 0.0012). This suggests that rats align

with lower levels of processing when we purposely select image pairs that are optimized to contrast

different levels of the visual processing hierarchy.

Next we checked how much individual CNN layers can predict the variation in behavioural performance

across image pairs when we take all test protocols together. We calculated the correlation of the

generalization across image pairs between the CNN classifier (summarized in Figure 8) and the rat

performance of all nine test protocols. This correlation includes a total of 287 image pairs, i.e. all image

pairs of all nine test protocols together. We did this by concatenating all performances of the animals

into one array and all Classification Scores of the network into another array, and calculating the

correlation between these two arrays to retrieve a correlation for each network layer. The results are

displayed in Figure 4. Overall, we see quite low correlations, but several convolutional layers

nevertheless show a significant positive correlation (permutation test) with the behavioural pattern of

performance at the image pair level.

Even though some of the correlations are significant, they are low. This could indicate that no CNN layer is able to capture what rats do. Alternatively, it could be caused by a very low reliability of the behavioural data. To test the reliability of the variations in behavioural performance between stimulus pairs in all nine test protocols, we calculated the split-half reliability, as previously done in (Schnell et al., 2023), resulting in a correlation of 0.40. By applying the Spearman-Brown correction, we obtain a full-set reliability correlation of 0.58. This correlation is much higher than the correlations with individual CNN layers.

It is possible that rat performance would be based upon multiple levels of processing, in which case we would need a combination of layers in order to explain the variation in performance across stimulus pairs. Given the low correlation between neighbouring layers (Supplemental Table 7), a multiple linear regression was calculated with the Classification Scores of the 13 layers as 13 regressors, and the rat performances as response vector. The results of this regression indicate a significant effect of the Classification Scores ($F(287,273) = 2.22$, $p = 0.00907$, $R^2 = 0.10$). Further investigating the 13 predictors showed that the later convolutional layers 8, 9 and 10 of the network were significant predictors in the regression model (see Supplemental Table 8 for results of the regression model). The $R^2 = 10$ of the full model would correspond to a correlation of around 0.32. This is better than the correlation of single layers, but still clearly smaller than the reliability of the rat data of 0.58. In conclusion, the CNN model provides a partial explanation of how the performance of rats varies across image pairs.

Given the relevance of convolutional layers, we can expect that relatively basic visual features might

partially explain the behavioural strategy of rats. This includes dimensions such as brightness and pixel-

based similarity. To get a first indication of the relevance of these features, we calculated the

correlation across image pairs between rat performance and brightness and pixel similarity. Here we

found a correlation of 0.34 for pixel similarity and 0.39 for brightness, suggesting that these two visual

features partially explain our results when compared to the full-set reliability of rat performance (0.58).

2.2 Human study

A final part of this study was to include an online human study that follows the same design as the

animal part. Figure 5 shows the average performance of humans (dark blue) versus rats (light blue) for

all nine test protocols, as well as their performance on the old stimuli that were added in (or during)

the testing protocols as quality control. Overall, humans performed better on all tests protocols than

rats, with an average performance over all tests of 94.34% (humans) and 62.29% (rats). There was

already a difference in terms of training performance (humans: 92.86% vs. rats: 77.84%), but the

difference on the test protocols is larger. We subtracted the training performance of humans or rats

from the testing performance of humans or rats, respectively, and even with this normalization for

training performance there is still a significantly higher test performance in humans compared to rats

$(t(16) = -6.47, p < 0.0001)$. Thus, not surprisingly, the degree of invariance in this object classification

task is higher for humans compared to rat.

The variation in performance across test protocols and across image pairs can give an indication of the strategies that each species follows. Overall, humans and rats show a mild correspondence in terms of which image pairs are more difficult, with a human-rat correlation of 0.18 across all image pairs of the nine test protocols (p < 0.001 with permutation test). Albeit significant, this correlation is clearly lower than the maximum value that could be obtained given the reliability of the data. The split-half reliability of the human data was 0.46, corresponding to a full-set reliability of 0.63. We reported above that full-set reliability is 0.58 for the rat data, resulting in a combined reliability of 0.60 (calculated as described in Op de Beeck et al., 2008). Thus, after taking data reliability into account there remains a pronounced discrepancy between rats and humans in terms of how performance varies across image pairs.

The main question of the present study is how this discrepancy relates to computationally informed strategies. If we take a closer look specifically at the two CNN-informed test protocols (*Zero vs. high* and *High vs. zero*), we see an opposite behaviour between animals and humans. Humans performed significantly better in the *Zero vs. high* protocol, i.e. where we used stimuli where the earlier layers of the network perform worse than the higher layers, than in the *High vs. zero* protocol (paired t-test: t(44) = 2.85, p = 0.0067). Rats, however, show the opposite (see above for statistics). There even is a

significant interaction between species and test protocol (unpaired t-test: t(54) = 2.50, p = 0.016). This

suggests a different strategy between animals and humans: rats use strategies that are captured in the

lower layers of the network, and thus correspond more to low level visual processing. Humans,

however, tend to rely more on strategies captured by the higher layers of the network, and thus we

are looking at more high-level visual processing.

As a next step, we calculated the correlation between the generalization across image pairs between

the CNN classifier and the human performance of all nine test protocols in an identical manner as for

the rat performance (Figure 4). The results are displayed in Figure 6. Overall, we see quite high

correlations, especially in the higher layers. This pattern across layers is very different from the pattern

in rats where the highest layers showed no correlations, which again suggests that, despite successful

generalization, rats rely on decisively lower-level strategies than humans in the same discrimination

task.

Figure 6 Correlation of the Classification Score for single target/distractor pairs between single CNN layers and the human

performance, for all nine test protocols together. The naming convention on the x axis corresponds to the layers of the

network, identical as in Figure 4. The black and grey horizontal lines on the x-axis indicated the layer blocks (block 1 consisting

of conv1, norm1, pool1; block 2 consisting of conv2, norm2, pool2; block 3-4 corresponding to conv3-4 (respectively); block

A multiple linear regression was calculated in an identical manner as we did with the rat performance.

The results of this regression indicate a significant effect of the Classification Scores ($F_{(287,273)}$ = 6.8,

$p < 0.0001$, R^2 = 0.25). Further investigating the 13 predictors showed that in particular the fully

connected layers 11, 12 and 13 of the network were strong predictors in the regression model (see

Supplemental Table 9 for results of the regression model).

Given the high correlations with fully connected layers, we would expect to not find much evidence

for an influence of basic visual dimensions such as brightness and pixel-based similarity. Indeed, we

find small correlations with variation in human behavioural performance across image pairs for pixel

similarity (0.12) and for brightness (-0.12).

3 Discussion

In the current study, we trained and tested rats and humans in a discrimination task using two-dimensional stimuli, with the two dimensions being concavity and alignment. We tested generalization across a range of viewing conditions. For the last two testing protocols, we used a computational approach to select the stimuli in terms of specifically dissociating low and high stages of processing. Rats were able to learn both dimensions (concavity and alignment) and showed a preference for concavity. Their performance on the testing protocols revealed a wide variety in percentage correct: for some test protocols they performed just above chance level, e.g. *Zero vs. high*, whereas for others they could easily reach about 70% correct (*Position*). Humans, on the other hand, performed better overall, with performances of 80% or higher on the testing protocols. Addressing the question of the complexity of the underlying strategies, rats performed best on the test protocol designed to specifically target lower levels of processing whereas humans performed best on the high-level processing protocol. Likewise, direct comparisons with artificial neural network layers showed that the variation of rat performance across images was best explained by late convolutional layers, whereas human performance was most associated with representations in fully connected layers.

All animals started by being trained in three training protocols. The first *Training* protocol only included one image pair, the base pair, containing the most different target and distractor without any further transformations. Learning of the individual dimensions of concavity and alignment was investigated through the *Dimension learning* protocol. The results from this *Dimension learning* protocol indicate that our rats have more difficulties learning the alignment dimension as opposed to the concavity dimension. One possible explanation for the superior performance on the concavity dimension could be that the animals were partially solving the task such that the brighter stimulus, i.e. the convex base shape, is the distractor and that their strategy is to pick the stimulus with the lowest brightness. This was confirmed by analyses on the third training protocol (*Transformations*) that included small transformations along various dimensions. Nevertheless, the rats still performed above chance level for trials in which the brightness differences were reversed, indicating that other dimensions are

involved and overrule a contribution from brightness. Similar findings have been obtained in human

behaviour and neuroscience. For example, despite the clear category selectivity in regions such as the

fusiform face area, the selectivity in these regions is also modulated very strongly by various low-level

dimensions (Yue et al., 2011). With regard to the size and position transformations it is important to

keep in mind that the animals were freely moving in the touchscreen chambers, and so even for the

original base pair was already undergoing changes in retinal size and retinal position. What we

manipulate, is rather the size and position relative to the rest of the set-up (e.g., relative to screen

position and size).

After these three training protocols, the animals were tested for generalization in a variety of testing

protocols, each testing a separate transformation on the stimuli. The first six test protocols included

rotation along all the three axes, size, position and light location, following by a test protocol in which

we combined the rotation along the three axes. Overall, we found that the performance of the animals

on these test protocols is affected by these transformations, but still significantly above chance in each

protocol. Studies in the literature would often stop here, or proceed by systematically testing even

larger transformations. Stimulus choices are based upon intuitions of what strategy animals might be

using, and upon theories of how visual perception works. However, in some cases, a further

computational modelling of the task and stimuli finds that what intuitively seems like a task of a

particular complexity might not be so complex after all. The first tests of invariant object recognition

seemed impressive, but were found to be easily solved with earlier layers of processing (Minini &

Jeffery, 2006; Vinken & Op de Beeck, 2021). This was recently also highlighted by relatively simple

pixel-based analyses (Kell et al., 2020). As another example, Vinken & Op de Beeck (2021) have used a

computational approach to further investigate the levels of information processing in rodents by

comparing three hallmark studies that provided evidence for higher order visual processing in rodents

(Djurdjevic et al., 2018; Vinken et al., 2014; Zoccolan et al., 2009) with CNNs. They found that for all

three studies, the low and mid-level layers captured the rat performances best, providing thus

evidence against the previously concluded high level visual processing in rodents.

For these reasons, we decided to directly test image pairs through computational modelling with CNNs

and select pairs that are particularly suited of dissociating different levels of processing. Stimuli were

chosen by a CNN from a very large set of possible stimuli and combinations, such that the higher layers

and the lower layers of the network make distinct errors on classifying the stimuli (*Zero vs. high* and

High vs. zero protocol), and thus are diagnostic of the level of underlying visual strategies. We chose

to work with Alexnet, as this is a network that has been used as a benchmark in many previous studies

(e.g. (Cadieu et al., 2014; Groen et al., 2018; Kalfas et al., 2018; Nayebi et al., 2023; Zeman et al., 2020)),

including studies that used more complex stimuli than the stimulus space in our current study. The

stimuli of the *Zero vs. high* protocol included stimuli where the higher layers of the network performed

better than the lower layers, and thus they address higher level visual processing. The opposite can be

said for the *High vs. zero* protocol, which includes stimuli that specifically target lower level visual

processing, given that the lower layers of the network perform best on these stimuli. After presenting

these stimuli to the animals, we found that our rats performed best in the *High vs. zero* protocol,

suggesting that they focus on low level visual cues to solve this discrimination task. We found the

opposite CNN pattern for humans, indicating that they use high level visual processing. These findings

provide more direct information about the level of processing that underlies the behavioural strategies

compared to overall performance or to effects of image manipulations.

This is a new promising way to design experiments in a way that is computationally informed rather

than based on researcher intuitions or qualitative predictions. It is in line with the literature that a

typical deep neural network, AlexNet and also more complex ones, can explain human and animal

behaviour to a certain extent but not fully. The explained variance might differ among DNNs, and there

might be DNNs that can explain a higher proportion of rat or human behaviour. Most relevant for our

current study is that DNNs tend to agree in terms of how representations change from lower to higher

hierarchical layers, because this is the transformation that we have targeted in the Zero vs. high and

High vs. zero testing protocols. (Pinto et al., 2008) already revealed that a simple V1-like model can

sometimes result in surprisingly good object recognition performance. This aspect of our findings is

also in line with the observation of Vinken & Op de Beeck (2021) that the performance of rats in many

previous tasks might not be indicative of highly complex representations. Nevertheless, there is still a

relative difference in complexity between lower and higher levels in the hierarchy. That is what we

capitalize upon with the Zero vs. high and High vs. zero protocols. Thus, it might be more fruitful to

explicitly contrast different levels of processing in a relative way rather than trying to pinpoint

behaviour to specific levels of processing.

Partially thanks to these computationally inspired tests, our total dataset finds a marked dissociation

between how humans and rats solve this object recognition task. Even in the sessions where only the

old pairs are shown, the animals performed lower than humans. This was most likely due to motivation

and/or distractibility. Our analyses show dissociation between humans and rats most convincingly by

correlating the variation in performance across image trials with the predictions of CNN layers. There

were significant correlations with multiple layers in both species. In humans, the most pronounced

correlations were present for the highest, fully connected layers, while in rats correlations were limited

to low and middle convolutional layers. This is the most direct evidence available in the literature that

rats resolve object recognition tasks through a very different and computationally simpler strategy

compared to humans. The CNN approach does not inform us how we can verbalize this simpler

strategy, but based upon earlier work (Schnell and colleagues, 2023); Vermaercke & Op de Beeck,

2012) we would hypothesize that rats rely upon visual contrast features (e.g., this area is darker/lighter

than that other area). Such contrast features are also used by humans and monkeys, e.g. for face

detection (Ohayon et al., 2012; Sinha, 2002), but in addition humans have access to more complex

strategies that e.g. refer to complex shape features such as aspect ratio and symmetry (Bossens & Op

de Beeck, 2016). Tests in the present study reveal that other features that partially explain rat

performance include basic dimensions such as brightness and pixel-based similarity, the latter being a

proxy for retinotopically based computations that are expected to be present in convolutional layers.

Our analyses of rat behaviour and DNN modelling do not take into account potential trial-to-trial

variability in the distance and position of the rat's head. From earlier work we can derive that rats

typically make their decision from about 12 cm from the stimulus display (Crijns & Op de Beeck, 2019),

but we have no information on trial-to-trial variability. We can hypothesize about the possible effect.

If such variability would exist, then it would artificially increase the variation in distance and position

during training, and thus help the animals to achieve higher levels of invariance during testing. As a

consequence, the difference between rat and human performance in terms of inferred level of

processing might even increase under more controlled circumstances.

For future studies, it will be highly valuable to use this computational informed strategy on a wider

battery of behavioural tasks, as well as a wider range of species such as tree shrews and marmosets

(Callahan & Petry, 2000; Kell et al., 2020, 2021; Meyer et al., 2022; Petry et al., 2012; Petry & Bickford,

2019). One step further, we can use the information from computational modelling together with

behaviour and how it differs among stimuli to further select stimuli for neurophysiological

investigations of neuronal response properties along the visual information processing hierarchy, in

this way following experimental designs that are optimized for highlighting the primary differences

between processing stages and between species.

4 Methods

4.1 Animal study

4.1.1 Animals

A total of twelve male outbred Long Evans rats (Janvier Labs, Le Genest-Saint-Isle, France) started this behavioural study. Out of these twelve animals, two were tested extensively in a first pilot study, and were included in the remainder of the study as well. All animals were 11 weeks old at the start of shaping and were housed in groups of four per cage. Each cage was enriched with a plastic toy (Bio-Serv, Flemington, NJ), paper cage enrichment and wooden blocks. Near the end of the experiment, one animal had to be excluded because of health issues. During training and testing, the animals were food restricted to maintain a body weight between 85% and 90% of their underprived body weight. They received water ad libitum. All experiments and procedures involving living animals were approved by the Ethical Committee of the University of Leuven and were in accordance with the European Commission Directive of September 22, 2010 (2010/63/EU).

4.1.2 Setup

The setup is identical to the one used by Schnell and colleagues (2019) and Schnell and colleagues (2023). A short description will follow here. The animals were trained and tested in four automated touch-screen rat-testing chambers (Campden Instruments, Ltd., Leicester, UK) with ABET II controller software (v2.18, WhiskerServer v4.5.0). The animals performed one session per day and each session lasted for 100 trials or 60 minutes, whichever came first. A reward tray in which sugar pellets (45-mg sucrose pellets, TestDiet, St. Louis, MO) could be delivered was installed on one side of the chamber. On the other side of the chamber, an infrared touchscreen monitor was installed. This monitor was covered with a black Perspex mask containing two square response windows (10.0 x 10.0 cm). A shelf (5.4cm wide) was installed onto this black mask (16.5cm above the floor) to force the animals to attend to the stimuli and to view the stimuli within their central visual fields. Close proximity to the screen was enough to elicit a response because the screens are infrared. As the position of the rats in the

423   touchscreen setup is not fixed, the actual size and position of the stimuli might vary in retinal

424   coordinates. In a previous study we manipulate the cycles per degree of stimuli in an orientation

425   discrimination task, and estimated that the decision distance of rats in this setup lies around 12.5 cm

426   from the screen (Crijns & Op de Beeck, 2019). Supplemental Figure 1 shows the timeline graphic of a

427   correct and incorrect trial as well as images of the experimental setup.

4.1.3 Stimuli

Stimuli were created using the Python scripting implementation of the 3D modelling software Blender

3D (version 2.93.3) and measured 100 x 100 pixel. In general, the stimuli were objects that consisted

of a body (base) with three spheres attached to it. A first step was to alter two dimensions of the

object, namely the concavity of the base and the alignment of the three spheres. The base was made

either concave or convex by increasing (convex) or decreasing (concave) the base parameter. The

alignment of the spheres was altered by changing the placement of the left and the right spheres.

These spheres could either be horizontally aligned or misaligned. In the misaligned case, the spheres

were placed diagonally from upper left to lower right. Figure 7a shows two example stimuli, the ones

that later were selected as the so-called "base pair". Next, additional exemplars were created by

uniformly tiling the two-dimensional stimulus space between these two example stimuli. We decided

to create eleven levels of the concavity dimension and four levels of alignment. This already yields 44

stimuli (see Supplemental Figure 3). We chose these levels of concavity and alignment based on the

pixel dissimilarity of the stimuli (see Supplemental Figure 4). The final goal was to construct a 4x4

stimulus grid (Figure 7b) by selecting a subset of the 4x11 stimulus grid. We chose a large number of

concavity levels, as this ensures flexibility in the calibration of the two dimensions relative to each

other.

Figure 7 Illustration of the base pair and our stimulus grid. (a) The base pair of the main experiment. **(b)** The chosen 4x4

stimulus grid. The red diagonal dotted line indicates the ambiguous stimuli that can be seen as target as well as distractor. All

stimuli below this line (green triangle) indicate the distractor sub-grid, whereas all stimuli above this line (yellow triangle)

highlight the target sub-grid.

We added identity-preserving transformations to the stimuli, such as rotation among the x-axis, y-axis

and z-axis in six different angles (0° to 180° in steps of 30°), as well as changing the light location (left,

under, up, right, front) and finally the size and position. The latter two transformations were

implemented using Python (3.7.3). Excluding the size and position transformation, these

transformations resulted in a total set of 75460 stimuli (4 (alignment) * 11 (concavity) * 7 (x-axis

rotation) * 7 (y-axis rotation) * 7 (z-axis rotation) * 5 (light location) = 75460 stimuli). Supplemental

Figure 5 shows examples of these transformations and Figure 1 shows an overview of all image pairs

that were used in this study.

4.1.4 Protocols

Once the pilot was finished (see supplementary for details), we set up the experiment and chose our

stimuli. We started by reducing the 4x11 stimulus grid to a 4x4 stimulus grid (see Figure 7b). All stimuli

on the diagonal can be seen as ambiguous stimuli (four stimuli in total), as they can be identified as a

target as well as a distractor. The six stimuli above this diagonal create the target part of the grid, and

the six stimuli below this diagonal resemble the distractor sub-grid.

The different phases of the experiment are shown in Figure 1 and this figure shows all stimuli that were

used. In the main Training phase, we trained the animals in the maximally different stimuli that are

placed at the very ends of the corners (Figure 7a). We refer to this as the base pair. After this Training

phase, the experiment consisted of two further training protocols. In the Dimension learning training

phase, we pushed the animals to learn both dimensions (concavity and alignment) by presenting them

two additional stimuli pairs from Figure 7b in which the target and distractor differ in only one

dimension. A third training protocol (*Transformations*) consisted of stimuli with some small

transformations, such as 30° rotation along the x-axis, 30° rotation along the y-axis, 30° rotation along

the z-axis, light location below, and size reduction of 80%, resulting in a total of 25 possible stimulus

pairs (every combination of target-distractor with the 5 transformed stimuli). During these two training

protocols, one third of the trials were so-called "old trials" with the base pair. Correction trials were

given if an animal answered incorrectly, i.e. the same trial was repeated until the animal answered

correctly. These correction trials were excluded from the analyses. In all trials, rats received a reward

for touching the correct screen, i.e. the screen with the target.

After these three training protocols, the testing part of the experiment included nine test protocols.

The crucial defining difference between these test protocols and the prior training protocols is that

rats received a reward randomly in 80% of the trials with new stimulus pairs, and no correction trials

were given for an incorrect response. This random reward is important to keep the animals motivated

during the testing protocols and to measure real generalization, and not training behaviour. We have

used a similar approach in the past, where we rewarded the animals in every testing trial (Schnell et

al., 2019; Vinken et al., 2014). One third of the trials in all test protocols consisted of old trials with the

base pair, and here, the animals received reward for touching the target and correction trials were

shown if necessary. Regularly, we inserted a *Dimension learning* session in between two test sessions

to maintain the performance high enough on training stimuli, especially for the animals in which we

saw a drop in performance on the base pair. We excluded any test sessions where the performance on

the base pair stimuli dropped to below 65% and the performance on this base pair was not included

in the accuracy calculations.

The first six test protocols included one protocol for each transformation, i.e. *Rotation X, Rotation Y,*

Rotation Z, Light Location, Size and *Position.* The order in which these first six test protocols were given

to the animals was counterbalanced between the animals. The stimuli that were used in these six test

protocols can be seen in Figure 1 and every combination of target-distractor per test protocol was

presented to the animals. For the rotation protocols, we used rotation degrees in steps of 30°, ranging

from 30° to 180°. This resulted in 36 possible stimulus pairs for each of the three rotation protocols. In

the *Light Location* protocol, we used stimuli where the light location was set at four different positions

(below, left, right and up), resulting in 16 possible stimulus pairs for this protocol. In the *Size* protocol,

we selected targets and distractors that were 80% and 60% reduced in size compared to the original,

training pair. This protocol included 4 possible stimulus pairs. And finally, in the *Position* protocol, we

changed the position of the 80% reduced in size stimuli and placed the objects in the lower left corner,

lower right corner, centre, upper left corner and upper right corner. We have a total of 25 possible

stimulus pairs for this protocol.

After these six test protocols, we presented the animals with six targets and six distractors where all

three rotations were combined (*Combination rotation*), i.e. x-, y- and z-axis were rotated with the same

degree (ranging from 30° to 180°, in steps of 30°). This resulted in a total of 36 new stimulus pairs.

Again, no correction trials were included after the trials where rotated stimuli were shown and animals

received random reward in 80% of the trials. One third of the trials consisted of the stimulus pair from

the first *Training* phase (i.e. the base pair), and here, correction trials were given after an incorrect

response and real reward was given to the animals.

In a final set of two test protocols, we created a CNN-informed stimulus set. The details of the

computational modelling are explained in the next section. The first protocol (*Zero vs. high*) included

stimuli in which the lower layers of the network performed around chance level (i.e. target-distractor

difference in Classification Scores (difference in signed distance to hyperplane) of about 0), whereas

the higher layers scored high (see section 4.2). The second protocol (*High vs. zero)* included stimuli

where the network did the opposite. That is, the earlier layers performed well whereas the higher

layers performed around chance level. The order of the two test protocols was counterbalanced

between the animals. Each of these test protocols included 7 targets and 7 distractors, giving a total

of 49 new stimulus pairs.

Animals stayed in each session for 60 minutes or until they reached 100 training trials or 120 testing

trials. We used an intertrial interval (ITI) of 20s and a time-out of 5s during training sessions. This time-

out was only used in incorrect trials. From another pilot study in the lab, we noticed we could decrease

the ITI and time-out without affecting the rats' performance. Therefore, we decided to use an ITI of

15s and time-out of 3s during testing, and to increase the number of trials during a testing session to

120 trials. The stimuli remained on the screen until the animals made a choice and so there was no

time limit for the animals.

Each protocol was run for multiple sessions per animal. Given that we were interested in how

performance would vary across stimulus pairs, we completed more sessions for the protocols that

included more stimulus pairs. Supplemental Table 1 indicates the average number of trials per test

protocol for all rats together.

One animal was not placed in the *Transformations* phase as it was the slowest animal during training.

However, its performance on the test protocols did not significantly differ from the other animals. We

tested this by calculating the correlation of the variation of performance across stimulus pairs for each

rat with the pooled responses of all other rats. The average correlation for each of the other animals

with the pooled response was 0.24 (±0.09), and the correlation of this slowest animal with the others

was very similar, 0.23.

To further examine the visual features that could explain rat performance, we calculated the

correlation between the rat performances and image brightness of the transformations. We did this

by calculating the difference in brightness of the base pair (brightness base target – brightness base

distractor), and subtracting the difference in brightness of every test target-distractor pair for each

test protocol (brightness test target – brightness test distractor for each test pair). We then correlated

these 287 brightness values (1 for each test image pair) with the average rat performance for each test

image pair. We performed a similar correlation analysis for pixel similarity to investigate the correlation

between pixel similarity of the test stimuli in relation to the base stimuli with the average performance

of the animals on all nine test protocols. We did this by calculating the pixel similarity between the

base target with every other testing distractor (A), the pixel similarity between the base target with

every other testing target (B), the pixel similarity between the base distractor with every other testing

distractor (C) and the pixel similarity between the base distractor with every other testing target (D).

For each test image pair, we then calculated the average of (A) and (D), and subtracted the average of

(C) and (B) from it. We correlated these 287 values (one for each image pair) with the average rat

performance on all test image pairs.

4.2   Computational modelling

One important goal of this study was to create a CNN-informed stimulus set to present to the animals.

To do so, we followed the steps of Schnell and colleagues (2023) and Vinken & Op de Beeck (2021) to

train a CNN on the same stimuli on which our animals were trained. The steps of training the network

are identical to Schnell and colleagues (2023) and a short description will follow here. We used the

standard AlexNet CNN architecture that was pre-trained on ImageNet to classify images into 1000

object categories (MATLAB 2021b Deep Learning Toolbox). Following Vinken & Op de Beeck (2021),

we applied principal component analysis to calculate the activations in every layer, to standardize the

values across inputs and to reduce the dimensionality. We then trained a linear support vector

machine classifier by using the MATLAB function fitclinear, with limited-memory BFGS solver and

default regularization. We performed this with the standardized DNN layer activations in the principal

component space as inputs, before ReLU, to our 24 training stimuli (see Figure 1**Error! Reference s**

ource not found.), i.e. all stimuli of the *Training, Dimension* learning and *Transformations* protocols.

The layers of AlexNet were divided into 13 sublayers, similar as in Schnell and colleagues (2023) and

Vinken & Op de Beeck (2021).

Figure 8 shows the performance of the network for each of the test protocols after training classifiers

on the training stimuli using the different CNN layers. We added noise to the inputs of the network

such that the average training performance, averaged over 100 iterations, lies around 75%. By adding

noise in this way, the performance on the training pairs matches overall with rat performance on those

pairs, otherwise the performance of the network would be at 100% on the training pairs and this would

complicate comparisons with the animal data (see also Vinken & Op de Beeck, 2021). Note that the

results for the *Size* test are unreliable given the low number of stimulus pairs in that test. The

performance of the network on the tests (green line in Figure 8) differs among the tests and across

layers, but typically the network had no problems to achieve a training performance of about 85% in

all test protocols in at least some layers. The change in performance across layers is variable across

test protocols.

Figure 8 The performance of the CNN after training on our training stimuli, with noise added to its input. The naming convention on the x axis corresponds to the layers of the network, identical as in Figure 4. The performance (y-axis) illustrates that each layer is challenged by at least part of the test protocols. The purple line indicates the training performance and the green line indicates the test performance of the neural network. The x axis on each subplot indicates the block of the layer: layer blocks 1-8 correspond to (convolutional layer 1, normalization layer 1, pool layer 1), (convolutional layer 2, normalization layer 2, pool layer 2), convolutional layer 3, convolutional layer 4, (convolutional layer 5, pool layer 5), fully connected layer 6, fully connected layer 7 and fully connected layer 8, respectively. The black and grey horizontal lines on the x-axis indicated the layer blocks (block 1 consisting of conv1, norm1, pool1; block 2 consisting of conv2, norm2, pool2; block 3-4 corresponding to conv3-4 (respectively); block 5 consisting of conv5, pool5; block 6-7-8 corresponding to fc6-7-8, respectively. The vertical grey dashed line indicates the division between convolutional and fully connected layer blocks. The horizontal dashed line indicates chance level. The shaded error bounds correspond to 95% confidence intervals calculated using Jackknife standard error estimates, as done previously in *(Vinken & Op de Beeck, 2021)*. The different markers indicate different sorts of layers: circle for convolutional layers, triangle for normalization layers, point for pool layers, and squares for fully connected layers.

To examine the performance of the model for specific image pairs during training and testing in more detail than possible with a binary categorization decision, we calculate the distance to the classifier's

hyperplane (decision boundary) of the targets and distractors. We do this by computing the difference

in signed distance to the hyperplane between target and distractor (target – distractor). This is referred

to as the Classification Score. For each stimulus pair in the test protocols we computed this

Classification Score and we have such a score per layer.

We used this Classification Score to select image pairs for a CNN-informed stimulus set. To do so, we

randomly chose one target and one distractor from a subset of the pool of all 4x4 stimuli, including all

possible transformations on these stimuli. This resulted in a stimulus pool of 10.290 stimuli (5145

targets, 5145 distractors) to randomly choose two from, and 5145*5145 (26 471 025) possible resulting

pairs of two stimuli. Once one random target and one random distractor was chosen, the DNN was

tested in a similar manner as we did for the six test protocols. We performed a total of 10000 iterations

of randomly choosing a target and distractor pair. For each iteration, we calculated the average

Classification Score of layers 1-3 and of layers 11-13 as we wanted to compare those two levels of

processing (earlier layers vs higher layers). After these 10000 iterations, we finetuned and filtered the

results according to the profile of performance across earlier and higher layers (see Supplemental

Table 2). This finetuning started by calculating the distribution and standard deviation for two profiles

of interest, i.e. (i) where early layers show an average Classification Score close to zero but higher

layers show high Classification Scores (Zero vs High), and (ii) where early layers show high Classification

Scores but higher layers show close to zero Classification Scores (High vs Zero). The performance was

expressed relative to the distribution of values across all pairs, summarized by de standard deviation

of the average target-distractor difference in Classification Scores of the early layers and the higher

layers. We found a total of 48 stimulus pairs for these two criteria, and we ended up choosing 14 pairs,

7 of each criterion, that we used for the final part of the animal and human study (see lower two rows

in Figure 1).

Afterwards we also calculated the binary target-distractor CNN decision performance for the image

pairs in the Zero vs High and High vs Zero tests, which is shown in Figure 8 (bottom row). The image

pairs in the Zero vs High protocol are more difficult than the other protocols, in particular for the first

half of the CNN layers. In contrast, the *High vs Zero* protocol is the only protocol associated with chance

performance in the last three layers. These analyses confirm that the CNN-based image pair selection

resulted in protocols that are very different from protocols that zoom in on intuitively chosen

transformations and their combinations.

Comparing the rat performances to the Classification Scores of the network was done by calculating

the correlation across image pairs between these model scores and the rat performances averaged

across animals. We concatenated the performance of the animals on all nine test protocols, as well as

the distance to hyperplane of the network on all nine test protocols. Correlating these two arrays

resulted in the correlations as visualized in Figure 4. To test whether these correlations are significant,

we performed a permutation test. We permutated these arrays 1000 times, resulting in a normal

distribution of permutated data per layer. We then calculated, per layer, how many of the permutated

values are higher than or equal to the correlation that is presented in Figure 4, and divided this by the

number of permutations.

4.3 Human study

4.3.1 Participants

Data was collected from 50 participants (average age 33.24 ± 12.23; 34 females) who participated in

return for a gift voucher of 10 euro. Out of these 50 participants, 5 were excluded because of outlying

behaviour during the quality check protocols (see Section 4.3.3). All participants had normal or

corrected-to-normal vision. The experiment was approved by the ethical commission of KU Leuven (G-

2020-1902-R3) and each participant digitally signed an informed consent before the start of the

experiment.

4.3.2 Setup

642 For the human part of this study, we developed an online experiment using PsychoPy3 (v2020.1.3,

643 Python version 3.8.10) and placed it on the online platform Pavlovia. All participants received the link

644 and their individual participant number by e-mail with which they could participate in the experiment

645 on their own computer. It took 30-45 minutes to complete the online study.

4.3.3 Stimuli and protocols

We used the same stimuli as in the animal study. The human experiment underwent the same phases

as depicted in Figure 1, albeit with small changes. We dropped the 1/3rd old trials in the test protocols

and included two additional *Dimension Learning* protocols in between the first counterbalanced tests

as quality check (see Supplemental Figure 7). Supplemental Table 3 provides an overview of the

number of trials during the human experiment for each phase. Supplemental Figure 7 shows an

overview of all image pairs that were presented in the human study.

Similar as in Bossens & Op de Beeck (2016), we presented the targets and distractors briefly to the left

and right side of a white fixation cross on a grey background. Each stimulus was presented for three

frames, followed by a mask (a noise image with 1/f frequency spectrum for three frames). We used

this fast and eccentric stimulus presentation with a mask to resemble the stimulus perception more

closely to that of rats. Vermaercke & Op de Beeck (2012) have found that human visual acuity in these

fast and eccentric presentations is not significantly better than the reported visual acuity of rats. By

using this approach we avoid that differences in strategies between humans and rats would be

explained by such a difference in acuity. Participants could then answer using the 'f' and 'j' keys to

indicate which position they thought was the correct position. If they thought the target was on the

left side of the fixation cross, they had to press 'f', and 'j' if they thought the target was on the right

side. Participants received feedback during the shaping and the three training phases. This happened

by colouring the fixation cross green if they answered correctly, and red if they answered incorrectly.

Each trial was followed by an intertrial interval (ITI) of 0.5s. During the *Shaping* and *Training* phase, we

kept a running average of the past 20 (*Shaping*) and 40 (*Training*) trials and participants continued to

the next phase when they reached a performance of 80% or higher on the last 20 or 40 trials, similar

as in Bossens & Op de Beeck (2016). There was no time limit for the participants for providing a

response. The order of the first six test protocols (*Rotation X, Rotation Y, Rotation Z, Size, Light Location*

and *Position)* was counterbalanced between the participants based on the participant number, as well

as the order of the last two test protocols (*Zero vs. high* and *High vs. zero*), similar as the approach in

the rat study. Supplemental Table 1 indicates the average number of trials per test protocol for all

human participants together.

In terms of instructions, we explained to participants that they would see two figures appearing at the

same time very quickly next to a fixation cross, and they would have to make a decision of which figure

is the correct one. We mentioned that during training, the fixation cross would turn green if they

answered correctly, and red if they answered incorrectly. Participants were informed that during

testing, they would not get feedback (changing colour of the fixation cross) anymore and that they

would have to use the knowledge they gained throughout training to make their decision in the testing.

We performed a similar correlation analysis as with rat performance to investigate the correlation

between pixel similarity and brightness with human performance. We followed the exact same steps

as we did for rat performance.

References

Alemi-Neissi, A., Rosselli, F. B., & Zoccolan, D. (2013). Multifeatural Shape Processing in Rats Engaged in Invariant Visual Object Recognition. *Journal of Neuroscience*, *33*(14), 5939–5956. https://doi.org/10.1523/JNEUROSCI.3629-12.2013

Avberšek, L. K., Zeman, A., & Op de Beeck, H. (2021). Training for object recognition with increasing spatial frequency: A comparison of deep learning with human vision. *Journal of Vision*, *21*(10), 14. https://doi.org/10.1167/jov.21.10.14

Bossens, C., & Op de Beeck, H. P. (2016). Linear and Non-Linear Visual Feature Learning in Rat and Humans. *Frontiers in Behavioral Neuroscience*, *10*. https://doi.org/10.3389/fnbeh.2016.00235

Cadieu, C. F., Hong, H., Yamins, D. L. K., Pinto, N., Ardila, D., Solomon, E. A., Majaj, N. J., & DiCarlo, J. J. (2014). Deep Neural Networks Rival the Representation of Primate IT Cortex for Core Visual Object Recognition. *PLOS Computational Biology*, *10*(12), e1003963. https://doi.org/10.1371/journal.pcbi.1003963

Callahan, T. L., & Petry, H. M. (2000). Psychophysical measurement of temporal modulation sensitivity in the tree shrew (Tupaia belangeri). *Vision Research*, *40*(4), 455–458. https://doi.org/10.1016/S0042-6989(99)00194-7

Crijns, E., & Op de Beeck, H. (2019). The Visual Acuity of Rats in Touchscreen Setups. *Vision*, *4*, 4. https://doi.org/10.3390/vision4010004

De Keyser, R., Bossens, C., Kubilius, J., & Op de Beeck, H. P. (2015). Cue-invariant shape recognition in rats as tested with second-order contours. *Journal of Vision*, *15*(15), 14. https://doi.org/10.1167/15.15.14

Djurdjevic, V., Ansuini, A., Bertolini, D., Macke, J. H., & Zoccolan, D. (2018). Accuracy of Rats in Discriminating Visual Objects Is Explained by the Complexity of Their Perceptual Strategy. *Current Biology*, *28*(7), 1005-1015.e5. https://doi.org/10.1016/j.cub.2018.02.037

Duyck, S., Martens, F., Chen, C.-Y., & Op de Beeck, H. (2021). How Visual Expertise Changes

Representational Geometry: A Behavioral and Neural Perspective. *Journal of Cognitive*

Neuroscience, *33*(12), 2461–2476. https://doi.org/10.1162/jocn_a_01778

Groen, I. I., Greene, M. R., Baldassano, C., Fei-Fei, L., Beck, D. M., & Baker, C. I. (2018). Distinct

contributions of functional and deep neural network features to representational similarity of

scenes in human brain and behavior. *ELife*, *7*, e32962. https://doi.org/10.7554/eLife.32962

Güçlü, U., & Gerven, M. A. J. van. (2015). Deep Neural Networks Reveal a Gradient in the Complexity

of Neural Representations across the Ventral Stream. *Journal of Neuroscience*, *35*(27), 10005–

10014. https://doi.org/10.1523/JNEUROSCI.5023-14.2015

Kalfas, I., Vinken, K., & Vogels, R. (2018). Representations of regular and irregular shapes by deep

Convolutional Neural Networks, monkey inferotemporal neurons and human judgments. *PLOS*

Computational Biology, *14*(10), e1006557. https://doi.org/10.1371/journal.pcbi.1006557

Kar, K., Kubilius, J., Schmidt, K., Issa, E. B., & DiCarlo, J. J. (2019). Evidence that recurrent circuits are

critical to the ventral stream's execution of core object recognition behavior. *Nature*

Neuroscience, *22*(6), Article 6. https://doi.org/10.1038/s41593-019-0392-5

Kell, A. J. E., Bokor, S. L., Jeon, Y.-N., Toosi, T., & Issa, E. B. (2020). *Conserved core visual object*

recognition across simian primates: Marmoset image-by-image behavior mirrors that of

humans and macaques.

Kell, A. J. E., Bokor, S. L., Jeon, Y.-N., Toosi, T., & Issa, E. B. (2021). *Brain organization, not size alone, as*

key to high-level vision: Evidence from marmoset monkeys (p. 2020.10.19.345561). bioRxiv.

https://doi.org/10.1101/2020.10.19.345561

Kubilius, J., Bracci, S., & Op de Beeck, H. (2016). Deep Neural Networks as a Computational Model for

Human Shape Sensitivity. *PLOS Computational Biology*, *12*(4), e1004896.

https://doi.org/10.1371/journal.pcbi.1004896

Logothetis, N. K., & Sheinberg, D. L. (1996). *Visual Object Recognition*. 45.

Matteucci, G., Marotti, R., Riggi, M., Rosselli, F. B., & Zoccolan, D. (2019). Nonlinear Processing of Shape

Information in Rat Lateral Extrastriate Cortex | Journal of Neuroscience. *Journal of*

Neuroscience. https://doi.org/10.1523/JNEUROSCI.1938-18.2018

Meyer, E. E., Ong, W. S., Balboa, M., & Arcaro, M. J. (2022). *Assessing tree shrew high-level visual*

behavior using conventional and natural paradigms [Poster]. Society for Neuroscience.

Minini, L., & Jeffery, K. J. (2006). Do rats use shape to solve "shape discriminations"? *Learning &*

Memory, *13*(3), 287–297. https://doi.org/10.1101/lm.84406

Nayebi, A., Zhuang, C., Norcia, A. M., Kong, N. C. L., Gardner, J. L., & Yamins, D. L. K. (2023). *Mouse*

visual cortex as a limited resource system that self-learns an ecologically-general

representation (p. 2021.06.16.448730). bioRxiv. https://doi.org/10.1101/2021.06.16.448730

Ohayon, S., Freiwald, W. A., & Tsao, D. Y. (2012). What Makes a Cell Face Selective? The Importance of

Contrast. *Neuron*, *74*(3), 567–581. https://doi.org/10.1016/j.neuron.2012.03.024

Op de Beeck, H., Torfs, K., & Wagemans, J. (2008). Perceived Shape Similarity among Unfamiliar Objects

and the Organization of the Human Object Vision Pathway. *Journal of Neuroscience*, *28*(40),

10111–10123. https://doi.org/10.1523/JNEUROSCI.2511-08.2008

Petry, H. M., & Bickford, M. E. (2019). The Second Visual System of The Tree Shrew. *Journal of*

Comparative Neurology, *527*(3), 679–693. https://doi.org/10.1002/cne.24413

Petry, H. M., Clark, C., Day-Brown, J., Bolin, R. T., & Bickford, M. (2012). Behavioral measurement of

RDK velocity discrimination thresholds in the tree shrew. *Journal of Vision*, *12*(9), 1223.

https://doi.org/10.1167/12.9.1223

Pinto, N., Cox, D. D., & DiCarlo, J. J. (2008). Why is Real-World Visual Object Recognition Hard? *PLOS*

Computational Biology, *4*(1), e27. https://doi.org/10.1371/journal.pcbi.0040027

Pospisil, D. A., Pasupathy, A., & Bair, W. (2018). "Artiphysiology" reveals V4-like shape tuning in a deep

network trained for image classification. *ELife*, *7*, e38242. https://doi.org/10.7554/eLife.38242

756 Schnell, A. E., Bergh, G. V. den, Vermaercke, B., Gijbels, K., Bossens, C., & Op de Beeck, H. (2019). Face

757   categorization and behavioral templates in rats. *Journal of Vision*, *19*(14), 9–9.

758   https://doi.org/10.1167/19.14.9

759 Schnell, A. E., Vinken, K., & Op de Beeck, H. (2023). The importance of contrast features in rat vision.

760   *Scientific Reports*, *13*(1), Article 1. https://doi.org/10.1038/s41598-023-27533-3

761 Sinha, P. (2002). Qualitative Representations for Recognition. In H. H. Bülthoff, C. Wallraven, S.-W. Lee,

762   & T. A. Poggio (Eds.), *Biologically Motivated Computer Vision* (pp. 249–262). Springer.

763   https://doi.org/10.1007/3-540-36181-2_25

764 Tafazoli, S., Filippo, A. D., & Zoccolan, D. (2012). Transformation-Tolerant Object Recognition in Rats

765   Revealed by Visual Priming. *Journal of Neuroscience*, *32*(1), 21–34.

766   https://doi.org/10.1523/JNEUROSCI.3932-11.2012

767 Tafazoli, S., Safaai, H., De Franceschi, G., Rosselli, F. B., Vanzella, W., Riggi, M., Buffolo, F., Panzeri, S.,

768   & Zoccolan, D. (2017). Emergence of transformation-tolerant representations of visual objects

769   in rat lateral extrastriate cortex. *ELife*, *6*, e22794. https://doi.org/10.7554/eLife.22794

770 Vermaercke, B., Gerich, F. J., Ytebrouck, E., Arckens, L., Op de Beeck, H. P., & Van den Bergh, G. (2014).

771   Functional specialization in rat occipital and temporal visual cortex. *Journal of*

772   *Neurophysiology*, *112*(8), 1963–1983. https://doi.org/10.1152/jn.00737.2013

773 Vermaercke, B., & Op de Beeck, H. P. (2012). A Multivariate Approach Reveals the Behavioral

774   Templates Underlying Visual Discrimination in Rats. *Current Biology*, *22*(1), 50–55.

775   https://doi.org/10.1016/j.cub.2011.11.041

776 Vinken, K., & Op de Beeck, H. (2021). Using deep neural networks to evaluate object vision tasks in

777   rats. *PLOS Computational Biology*, *17*(3), e1008714.

778   https://doi.org/10.1371/journal.pcbi.1008714

779 Vinken, K., Van den Bergh, G., Vermaercke, B., & Op de Beeck, H. P. (2016). Neural Representations of

780   Natural and Scrambled Movies Progressively Change from Rat Striate to Temporal Cortex.

781   *Cerebral Cortex*, *26*(7), 3310–3322. https://doi.org/10.1093/cercor/bhw111

Vinken, K., Vermaercke, B., & Op de Beeck, H. (2014). Visual Categorization of Natural Movies by Rats.

Journal of Neuroscience, *34*(32), 10645–10658. https://doi.org/10.1523/JNEUROSCI.3663-

13.2014

Yue, X., Cassidy, B. S., Devaney, K. J., Holt, D. J., & Tootell, R. B. H. (2011). Lower-Level Stimulus Features

Strongly Influence Responses in the Fusiform Face Area. *Cerebral Cortex*, *21*(1), 35–47.

https://doi.org/10.1093/cercor/bhq050

Zeman, A. A., Ritchie, J. B., Bracci, S., & Op de Beeck, H. (2020). Orthogonal Representations of Object

Shape and Category in Deep Convolutional Neural Networks and Human Visual Cortex.

Scientific Reports, *10*(1), Article 1. https://doi.org/10.1038/s41598-020-59175-0

Zoccolan, D. (2015). Invariant visual object recognition and shape processing in rats. *Behavioural Brain*

Research, *285*, 10–33. https://doi.org/10.1016/j.bbr.2014.12.053

Zoccolan, D., Oertelt, N., DiCarlo, J. J., & Cox, D. D. (2009). A rodent model for the study of invariant

visual object recognition. *Proceedings of the National Academy of Sciences*, *106*(21), 8748–

8753. https://doi.org/10.1073/pnas.0811583106

Supplementary

Information about the pilot study

The goal of the pilot was to adjust the range of the two dimensions (concavity and alignment) in order to assure that the animals would use the two dimensions. Using the large stimulus set described in the previous paragraph, we tested a subset of them in a behavioural categorization experiment with two rats. This pilot study consisted of seven phases (see Supplemental Figure 6 for an overview). We started by training rats in a base pair. This pair consists of a target and distractor that are maximally different in terms of concavity and alignment, and thus are placed at the very corners of the 4x11 stimulus grid. After *Training*, we tested them in a *Dimension learning* protocol, to investigate whether the animals use both dimensions (concavity and alignment) in this discrimination task. A total of two pairs were presented to the animals. One pair consisted of the original, base pair, whereas the other pair consisted of stimuli where the alignment dimension was the opposite as in the base pair. In the third phase, *Push towards concavity,* we pushed the animals to learn the concavity dimension. A total of three pairs were presented to the animals. One pair consisted of the original training pair, whereas for the other two stimulus pairs the target and distractor differed in only one of the two dimensions, that is either concavity or alignment. The fourth pilot phase (*Push towards concavity, only new)* consisted of only the two new pairs where the target and distractor differ in only one dimension. A next phase (*More pronounced dimensions)* included stimuli where the concavity dimension was more pronounced than the base pair we started with. We changed the concavity parameter, and again the target and distractor differed in only one dimension. The sixth phase was identical to the *Dimension learning* phase, i.e. checking whether the animals use both dimensions, but this time we used the stimuli where the concavity dimension was more pronounced. In the final phase, we decided to show all four possible combinations of the stimuli.

Tables

Supplemental Table 1 Average number of trials (SD) per test protocol and also per stimulus pair (SP). In the second column, the average number of trials per stimulus pair, for all rats together, are indicated with the standard deviation between brackets. The third column shows the total number of trials per test protocol. The fourth and fifth columns indicate the same data but for the human participants.

Protocol	Rats		Humans	
	Ø # trials per SP (SD)	Total # trials	Ø # trials per SP (SD)	Total # trials
Rotation X	87.50 (± 9.66)	3150	111.11 (± 2.55)	4000
Rotation Y	88.22 (± 8.90)	3176	111.11 (± 2.44)	4000
Rotation Z	88.25 (± 9.55)	3177	111.11 (± 3.01)	4000
Light location	94.00 (± 11.35)	1504	125 (± 3.72)	2000
Size	205.75 (± 194.86)	823	250 (± 3.16)	1000
Position	91.28 (± 9.06)	2282	120 (± 3.45)	3000
Combination rotation	122.81 (± 12.06)	4421	111.11 (± 3.45)	4000
Zero vs. high	95.53 (± 8.76)	4681	122.45 (± 4.07)	6000
High vs. zero	109.92 (± 10.85)	5386	122.45 (± 4.00)	6000

827 **Supplemental Table 2 The two criteria of choosing a CNN-informed stimulus set.** We calculated the standard deviation for

828 the early layers and the higher layers. Based on their standard deviation, we then filtered the data and ensured that we had

829 enough pairs per criterion.

Criterion	Early layers	Higher layers	# pairs found
1	Close to zero [-0.4*sd … 0.4*sd]	Very high > 3*sd	22
2	Very high > 3*sd	Close to zero [-0.4*sd … 0.4*sd]	26

832 **Supplemental Table 3 Overview of the human experiment.** The left table indicates the number of trials for each training

833 protocol. Note that for the first two phases the participants stayed in these protocols until they reached a performance of

834 80% or higher on the last 20 trials. The number of trials in the testing protocol is proportional to the number of pairs tested

835 per protocol.

Training protocol	# trials
Shaping	80% performance or higher in the last 20 trials
Training	80% performance or higher in the last 40 trials
Dimension learning	80
Transformations	100
Dimension learning (extra)	20

Testing protocol	# trials
Size	20
Position	60
Light location	40
Rotation X	80
Rotation Y	80
Rotation Z	80
Combination rotation	80
Zero vs. high	120
High vs. zero	120

Supplemental Table 4 An overview of the performance of the animals on the first six test protocols. The second column

indicates the planned number of sessions per animal, and between brackets the average number of sessions per animal. We

excluded some sessions if the performance on the old stimuli of that session was too low. The third and fourth column

provides an overview of the average performance on the old and new pairs, respectively, with the total number of trials for

all rats together between brackets. We excluded the correction trials in the analysis of the old pairs. For the new pairs, no

correction trials were given and reward in 80% of the trials was given.

Test protocol	Planned # of sessions / animal (average # sessions / animal)	Mean performance on old stimuli (# old trials)	Mean performance on all new trials (# new trials)
Rotation (x-axis)	4 (3.50)	79.39% (1922)	56.49% (3083)
Rotation (y-axis)	4 (3.92)	75.86% (2138)	66.49% (3246)
Rotation (z-axis)	4 (3.83)	79.85% (2092)	63.33% (3315)
Light location	2 (1.92)	79.56% (1043)	72.95% (1645)
Size	1 (1.00)	82.73% (546)	63.49% (895)
Position	3 (2.83)	76.44% (1593)	64.65% (2423)

846 **Supplemental Table 5 Results of binomial test on the six test protocols with the pooled data of all animals together, on the**

847 **old trials (upper table) and new trials (lower table).** Here we test whether the average performance of all animals together

848 differs significantly from chance level (indicated by *p-value (50%)*) or 80% (indicated by *p-value (80%)*) on both the old trials

849 (upper table) as well as new trials (lower table).

Test protocol	Mean % (old trials)	p-value (80%)	95% CI
Rotation (x-axis)	79.39%	0.50	[0.78;0.81]
Rotation (y-axis)	75.86%	< .0001	[0.74;0.78]
Rotation (z-axis)	79.85%	0.87	[0.78;0.82]
Light location	79.56%	0.74	[0.77;082]
Size	82.73%	0.13	[0.79;0.86]
Position	76.44%	< .0001	[0.74;0.79]

Test protocol	Mean % (new trials)	p-value (80%?)	p-value (50%?)	95% CI
Rotation (x-axis)	56.49%	< 0.0001	< 0.0001	[0.55;0.58]
Rotation (y-axis)	66.49%	< .0001	< 0.0001	[0.65;0.68]
Rotation (z-axis)	63.33%	< 0.0001	< 0.0001	[0.62;0.65]
Light location	72.95%	< 0.0001	< 0.0001	[0.71;0.75]
Size	63.49%	< .0001	< 0.0001	[0.57;0.64]
Position	64.65%	< .0001	< 0.0001	[0.63;0.67]

852   **Supplemental Table 6 Marginal means and standard deviation of the *Rotation X* and *Rotation Z* protocols.**

Rotation X	Target	56.06 ± 8.54	56.60 ± 3.73	59.70 ± 5.01	55.66 ± 6.87	55.53 ± 9.54	55.37 ± 5.71
	Distractor	64.98 ± 2.12	59.21 ± 6.15	55.07 ± 5.64	52.05 ± 5.64	56.04 ± 5.81	51.55 ± 4.35
Rotation Z	Target	65.40 ± 9.54	63.42 ± 6.03	62.88 ± 10.66	60.20 ± 8.48	62.58 ± 6.78	65.52 ± 6.91
	Distractor	72.69 ± 4.47	68.25 ± 3.97	65.31 ± 6.27	60.27 ± 5.65	57.83 ± 6.83	55.64 ± 4.38

854   **Supplemental Table 7 Correlation between neighbouring layers of the deep neural network.**

Layers	Correlation
1-2	0.11
2-3	-0.13
3-4	0.05
4-5	0.09
5-6	0.12
6-7	0.04
7-8	0.17
8-9	0.06
9-10	0.01
10-11	0.003
11-12	0.11
12-13	0.12

856   **Supplemental Table 8 Results of the linear regression model with rat performances.** A linear regression was calculated with

857   the Classification Scores of the 13 layers as predictors and the rat performances as response vector. Each row indicates one

858   predictor, i.e. one layer, the middle and right column indicate the t-statistic and p-value of the associated predictor,

859   respectively.

Predictor	T statistic	p-value
(Intercept)	82.15	< 0.0001
Layer 1	1.19	0.23
Layer 2	0.56	0.57
Layer 3	0.91	0.37
Layer 4	0.52	0.60
Layer 5	-0.28	0.78
Layer 6	1.38	0.17
Layer 7	0.59	0.55
Layer 8	2.26	0.025
Layer 9	2.00	0.047
Layer 10	2.35	0.019
Layer 11	-0.46	0.64
Layer 12	-0.82	0.41
Layer 13	1.38	0.17

Supplemental Table 9 Results of the linear regression model with human performances. A linear regression was calculated with the Classification Scores of the 13 layers as predictors and the human performances as response vector. Each row indicates one predictor, i.e. one layer, the middle and right column indicate the t-statistic and p-value of the associated predictor, respectively.

Predictor	T statistic	p-value
(Intercept)	145.94	< 0.0001
Layer 1	0.63	0.53
Layer 2	-1.82	0.07
Layer 3	0.61	0.54
Layer 4	1.40	0.16
Layer 5	1.61	0.11
Layer 6	-1.23	0.22
Layer 7	0.14	0.89
Layer 8	0.62	0.54
Layer 9	0.80	0.43
Layer 10	1.18	0.24
Layer 11	2.90	< 0.01
Layer 12	5.08	< 0.0001
Layer 13	4.72	< 0.0001

868 ## Figures

(a) Correct trial

(b) Incorrect trial

(c) Experimental setup

Supplemental Figure 1 Timeline of a correct trial (a) and an incorrect trial (b). In case of a correct trial, animals receive a
reward in the form of sugar pellets for touching the target. If they answer incorrectly, they do not receive sugar pellets but
instead the house light is turned on. For training protocols, a correction trial is added.(c) shows images of the experimental
setup.

Supplemental Figure 2 Individual rat accuracy for each testing protocol. The black circle indicates the average accuracy

across all rats together. Each coloured cross represents the accuracy of one rat.

Supplemental Figure 3 Illustration of the 4x11 stimulus grid. We chose eleven values for concavity, ranging between -0.5 and 0.8, and four values for alignment, ranging between 0 and 1.

Supplemental Figure 4 The pixel dissimilarity matrix of the 4x11 stimulus grid. This matrix is calculated in the exact same way as *(Schnell et al., 2023)*. The colourbar indicates pixel dissimilarity values, normalized between 0 and 100. The higher this value, and thus the more red a cell, the more dissimilar two stimuli are. The naming convention of the stimuli is as follows: XX-alYYsmZZZ.png where XX is an ordering number, YY indicates the alignment level and ZZZ indicates the concavity (smoothness) level.

Rotation (x-axis)

Rotation (y-axis)

Rotation (z-axis)

Light location

Combination of
transformations

Supplemental Figure 5 Identity-preserving transformations on one of the basic stimuli. (a), (b) and (c) show the rotation

along the x-axis, y-axis and z-axis respectively, always in angles of 30°, 60°, 90°, 120°, 150°, and 180°. (d) illustrates the light

location transformation. (e) shows some combinations of transformations, with different values for the alignment and

concavity parameter.

Supplemental Figure 6 Design of the pilot study.

Supplemental Figure 7 Design of the online human study. The design of the human study resembles the design of the animal

study, with minor adaptions. We removed the 1/3rd old trials in the test protocols, but included two additional *Dimension*

Learning protocols.