A computationally informed comparison between the strategies of rodents and humans in visual object recognition

Anna Elisabeth Schnell[1*], Maarten Leemans[1], Kasper Vinken[2], Hans Op de Beeck[1]

[1] Department of Brain and Cognition & Leuven Brain Institute, KU Leuven, Leuven, Belgium

[2] Department of Neurobiology, Harvard Medical School, Boston, Massachusetts, United States of America

* Corresponding author

E-mail: annaelisabeth.schnell@kuleuven.be

Data availability:

The data has been made publicly available via the Open Science Framework and can be accessed at

https://osf.io/9eqyz/ .

Abstract

Many species are able to recognize objects, but it has been proven difficult to pinpoint and compare how different species solve this task. Recent research suggested to combine computational and animal modelling in order to obtain a more systematic understanding of task complexity and compare strategies between species. In the present study, we created a large multidimensional stimulus set and designed a visual discrimination task partially based upon modelling with a convolutional deep neural network (CNN). Experiments included rats (N = 11; 1115 daily sessions in total for all rats together) and humans (N = 45). Each species was able to master the task and generalize to a variety of new images. Nevertheless, rats and humans showed very little convergence in terms of which object pairs were associated with high and low performance, suggesting the use of different strategies. There was an interaction between species and whether stimulus pairs favoured early or late processing in a CNN. A direct comparison with CNN representations and visual feature analyses revealed that rat performance was best captured by late convolutional layers and partially by visual features such as brightness and pixel-level similarity, while human performance related more to the higher-up fully connected layers. These findings highlight the additional value of using a computational approach for the design of object recognition tasks. Overall, this computationally informed investigation of object recognition behaviour reveals a strong discrepancy in strategies between rodent and human vision.

1   Introduction

Humans show high proficiency in invariant object recognition, the ability to recognize the same objects from different viewpoints or in different scenes. This ability is supported by the ventral visual stream, the so-called *what stream* (Logothetis & Sheinberg, 1996). A question that is repeatedly addressed in vision studies is whether and how we can model this stream by means of animal models or computational models to further examine and quantify the representations along the ventral visual stream. Computationally, researchers have recently modelled this stream by using convolutional deep neural networks (CNNs), as for example done by Avberšek and colleagues (2021), Cadieu and colleagues (2014), Duyck and colleagues (2021), Güçlü & Gerven (2015), Kalfas and colleagues (2018), Kar and colleagues (2019), Kubilius and colleagues (2016), Pospisil and colleagues (2018) and Vinken & Op de Beeck (2021). Lately, the rodent model has become an important animal model in vision studies, motivated by the applicability of molecular and genetic tools rather than by the visual capabilities of rodents. Past studies have examined behavioural (Alemi-Neissi et al., 2013; De Keyser et al., 2015; Djurdjevic et al., 2018; Schnell et al., 2019; Tafazoli et al., 2012; Vermaercke & Op de Beeck, 2012; Vinken et al., 2014; Zoccolan, 2015) (for a review see Zoccolan, 2015) as well as neural (Matteucci et al., 2019; Tafazoli et al., 2017; Vermaercke et al., 2014; Vinken et al., 2016) data of rodents (rats and mice) performing in visual pattern recognition tasks. The behavioural findings suggested that rats are capable of learning complex visual discrimination tasks. Here we plan to integrate computational and animal modelling approaches, by using data about information processing in artificial neural networks when designing the animal experiments.

One aspect that almost all rodent studies have in common is that the exact task and stimuli are chosen based on what we know from human and monkey studies. Earlier research showed that the intuition of researchers about the complexity of visual tasks can be misleading (Vinken & Op de Beeck, 2021). Through computational CNN modelling of the tasks from previous studies, they showed that behavioural strategies that seem complex at first hand might be best modelled through

relatively early levels of processing in CNNs. They recommended that future studies could obtain

more direct information about the complexity of visual tasks and behavioural strategies by

incorporating neural network models in the design phase of the experiment. One way of

implementing this is to train rodents in a challenging and multidimensional visual task and use CNNs

to select stimulus examples targeting strategies with different levels of complexity.

In the present study, we implemented this approach and created a large stimulus set that can be

used for a variety of visual experiments. We decided to create the stimuli in a way that they are

adaptable to different types of tasks, such as a "simple" discrimination task or non-linear tasks (e.g.

Bossens & Op de Beeck, 2016). We then took a subset of these stimuli and performed a visual

discrimination experiment in rats (see Figure 1 for the design). The task itself was defined in a

stimulus space with two dimensions, here referred to as concavity and alignment. The stimuli

consisted of a base shape that varied in concavity, with three spheres attached to it that were either

horizontally aligned or misaligned. The task was then further complicated by transforming the stimuli

along several dimensions that preserve the identity of the object. We started by training the animals

in a base stimulus pair, with the target being the concave object with horizontally aligned spheres.

Once the animals were trained in this base stimulus pair, we used the identity-preserving

transformations to test for generalization. After a number of transformation phases, we selected a

final stimulus set by choosing a combination of transformations based on the outcomes of a trained

CNN. Using the neural network as a (basic) model for the different stages of ventral visual stream

processing, we chose stimulus pairs that require either higher or lower levels of processing and thus

allow us to maximally differentiate between the task strategies used by the animals. As a final part

of the current study, we performed an online human experiment with the same stimuli and design as

the experiment for the rats, providing us with a rich three-way comparison of rat behavioural data

with human behavioural data and with CNN data.

Figure 1 The design of the animal study, including the stimuli. Animals started with a standardized shaping procedure,

followed by three training protocols, as indicated by the dashed outline. In these protocols, animals received real reward,

i.e. reward for touching the target. The target corresponds to the concave object in all training protocols. The rats received

correction trials for incorrect answers, i.e. touching the convex object. After the three training protocols, the animals went

through a number of testing protocols. The order of the first six protocols (*) and the last two testing protocols (**) was

counterbalanced between the animals. During testing protocols, animals received one third old trials, and two third new

trials. In the new trials, they received random reward in 80% of the trials whereas in the old trials, they received real reward

and correction trials if necessary. Again, the target in the testing protocols correspond to the concave objects whereas the

distractors correspond to the convex objects.

2   Results

In this study, we trained and tested 11 rats and 45 humans on a complex two-dimensional discrimination task (see Figure 1 for the design of the rat study, and Supplemental Figure 7 for the design of the human study). Rats and humans were first trained in a base pair. Next we tested their ability to generalize across several image transformations. In the last two protocols of the design, we used a computational approach to select stimuli that require different visual strategies.

2.1   Animal study

Training. We first checked the variation in performance across phases and stimulus pairs during training. In the first *Training Phase*, animals were trained in the base stimulus pair, which were the maximally different target and distractor in a concavity x alignment stimulus space where each dimension was varied with 4 values (4 x 4 space). This training was successful for all twelve animals and lasted on average for 8.62 sessions (SD = 1.61). Animals were trained until they reached 80% performance for two consecutive sessions.

Once the animals were successfully trained, we examined whether they use both dimensions (concavity and alignment) by presenting them with two additional stimuli pairs where the target and distractor differ in only one dimension (see Figure 1, *Dimension learning).* Performance on the old pair was similar to training performance (85.83%). The animals performed well with the stimuli that differ only along the concavity dimension (78.79%), although it was significantly lower than the performance on the base pair (paired t-test on rat performance, $t(11) = 3.77$, $p = 0.003$). Performance dropped to 67.83% for the alignment-only pair, yet also significantly higher than chance level (one-sample t-test, $p < .0001$). Overall, the *Dimension learning* protocol provides evidence that the animals have picked up each of the two dimensions. This finding already excludes trivial explanations in terms of simple visual dimensions. For example, while concavity is correlated with horizontal size (distractor wider) and with overall brightness (distractor brighter, thus the opposite relevance as in the shaping phase), these simple dimensions cannot explain above-chance performance on the alignment dimension.

The third training protocol consisted of a number of small transformations, as visualized in Figure 1

(*Transformations*). Rats learned these transformations very well, with an average performance of

83.05% (see Figure 2). The pairwise percentage matrix in Figure 2 shows that the distractor with the

Size transformation (most right column in the matrix) affected the rat performance the most.

The variation in performance across targets and distractors can be due to a variety of factors. This

can include simple dimensions such as brightness. In the base pair, the distractor is brighter than the

target. While this is the opposite from the shaping task of detecting a shape versus a black screen,

visual inspection of Figure 2 suggests that the animals perform poorer on trials in which the

distractor display is not so much brighter (e.g., when it is small). To quantify this effect of brightness,

we calculated the correlation between the performances in the matrix and the difference in pixel

values (and thus brightness) of the stimulus pairs. This resulted in a (Pearson) correlation of -0.59 (p <

0.01), suggesting that there is indeed an effect of brightness. Yet, brightness is at best a partial

explanation because all percentages in the matrix are above chance, with the lowest percentage in

the matrix being 68.83%, even though in some pairs the difference in pixel values is abolished or

even opposite from the base pair.

Overall the findings from the training phase and the above-chance performance on a variety of

dimensions and transformations suggest that the rats have learned a pattern classification task with

a level of complexity that might be competitive with other tasks in the rodent literature.

(a)   (b)

Figure 2 (a) Results of the Dimension learning training protocol. The black dashed horizontal line indicates chance level performance and the red dashed line represents the 80% performance threshold. The blue circles on top of each bar represent individual rat performances. The three bars represent the average performance of all animals on the old pair (Old), the pair that differs only in concavity (Conc) and on the pair that differs only in alignment (Align). **(b) Results of the Transformations training protocol.** Each cell of the matrix indicates the average performance per stimulus pair, pooled over all animals. The columns represent the distractors, whereas the rows separate the targets. The colour bar indicates the performance correct.

Testing across transformations. The six protocols that test generalization to various transformations with new, untrained images are associated with performances lower than 80% (binomial test, see Supplemental Table 5 (lower table) for detailed table with results), but significantly higher than chance level (see Supplemental Table 5 (lower table)). The pairwise percentage matrices of the animals in Figure 3 provide a more detailed view of what is happening in every test, and Supplemental Figure 2 shows the individual accuracy for each animal. The distractor has a higher impact on performance than the target in some tests. Supplemental Table 6 shows the marginal means and standard deviation for each target and distractor for these two test protocols. From these means it is clear that there is a higher variation in the performance between distractors in *Rotation X* (52%-65%) and *Rotation Z* (56%-73%) than between targets (55%-60% resp. 60%-66%). The same happens in the size test protocol.

Figure 3 Pairwise percentage matrices of all nine testing protocols for the rat data. The colour bar indicates the percentage correct of the pooled responses of all animals together. The more red a cell is, the higher the average performance. Values below 40% accuracy are indicated in the highest intensity of blue. Cells with an 'o' marker indicate a below chance performance, whereas cells with an *, ** or *** marker indicate a performance that is significantly higher than chance level (p-value < 0.05, < 0.01 or < 0.001 respectively). This was calculated with a binomial test on pooled performance of all animals.

After these first six test protocols, the animals were presented with a schedule where all three rotations are combined (see Figure 1). On the new stimuli, the animals performed 58.56%, which is rather low, but still significantly different from chance level (binomial test on pooled performance of all animals: p < 0.0001; 95% CI [0.57;0.60]).

Testing computational levels of complexity. For the final two test protocols, we used a CNN to find image pairs that would contrast strategies based upon a different stage in visual processing, with either early layers having lower performance than high layers (*Zero vs. high*), or early layers having

better performance than high layers (*High vs. zero*). Rat performance was particularly low for *Zero vs.*

high (56.47%), yet still significantly different from chance level when averaged across all stimulus

pairs (binomial test on pooled performance of all animals; $p < 0.0001$; 95% CI [0.55;0.58]). In

contrast, rats were able to solve the *High vs. zero* pairs not only better than chance (average:

64.84%; binomial test on pooled performance of all animals; $p < 0.0001$; 95% CI [0.63;0.66]), but also

significantly better than *Zero vs. high* (paired t-test on rat performance, $t(10) = -4.49$, $p = 0.0012$).

This suggests that rats align with lower levels of processing when we purposely select image pairs

that are optimized to contrast different levels of the visual processing hierarchy.

Next we checked how much individual CNN layers can predict the variation in behavioural

performance across image pairs when we take all test protocols together. We calculated the

correlation of the generalization across image pairs between the CNN classifier (summarized in

Figure 8) and the rat performance of all nine test protocols. This correlation includes a total of 287

image pairs, i.e. all image pairs of all nine test protocols together. We did this by concatenating all

performances of the animals into one array and all Classification Scores of the network into another

array, and calculating the correlation between these two arrays to retrieve a correlation for each

network layer. The results are displayed in Figure 4. Overall, we see quite low correlations, but

several convolutional layers nevertheless show a significant positive correlation (permutation test)

with the behavioural pattern of performance at the image pair level.

CNN layer distance to hyperplane ~ rat performances

Figure 4 Correlation of the Classification Score for single target/distractor pairs between single CNN layers and the rat

performance, for all nine test protocols together. The black and grey horizontal lines on the x-axis indicated the layer

blocks (block 1 consisting of conv1, norm1, pool1; block 2 consisting of conv2, norm2, pool2; block 3-4 corresponding to

conv3-4 (respectively); block 5 consisting of conv5, pool5; block 6-7-8 corresponding to fc6-7-8, respectively. The vertical

grey dashed line indicates the division between convolutional and fully connected layer blocks. The horizontal dashed line

indicates a correlation of 0. The different markers indicate different sorts of layers: circle for convolutional layers, triangle

for normalization layers, point for pool layers, and squares for fully connected layers. The asterisks indicate significant

correlations according to a permutation test (* < 0.05, ** < 0.01 and *** < 0.001).

Even though some of the correlations are significant, they are low. This could indicate that no CNN

layer is able to capture what rats do. Alternatively, it could be caused by a very low reliability of the

behavioural data. To test the reliability of the variations in behavioural performance between

stimulus pairs in all nine test protocols, we calculated the split-half reliability, as previously done in

(Schnell et al., 2023), resulting in a correlation of 0.40. By applying the Spearman-Brown correction,

we obtain a full-set reliability correlation of 0.58. This correlation is much higher than the

correlations with individual CNN layers.

It is possible that rat performance would be based upon multiple levels of processing, in which case

we would need a combination of layers in order to explain the variation in performance across

stimulus pairs. Given the low correlation between neighbouring layers (Supplemental Table 7), a

multiple linear regression was calculated with the Classification Scores of the 13 layers as 13

regressors, and the rat performances as response vector. The results of this regression indicate a

significant effect of the Classification Scores ($F(287,273) = 2.22$, $p = 0.00907$, $R^2 = 0.10$). Further

investigating the 13 predictors showed that the later convolutional layers 8, 9 and 10 of the network

were significant predictors in the regression model (see Supplemental Table 8 for results of the

regression model). The $R^2 = 10$ of the full model would correspond to a correlation of around 0.32.

This is better than the correlation of single layers, but still clearly smaller than the reliability of the rat

data of 0.58. In conclusion, the CNN model provides a partial explanation of how the performance of

rats varies across image pairs.

Given the relevance of convolutional layers, we can expect that relatively basic visual features might

partially explain the behavioural strategy of rats. This includes dimensions such as brightness and

pixel-based similarity. To get a first indication of the relevance of these features, we calculated the

correlation across image pairs between rat performance and brightness and pixel similarity. Here we

found a correlation of 0.34 for pixel similarity and 0.39 for brightness, suggesting that these two

visual features partially explain our results when compared to the full-set reliability of rat

performance (0.58).

2.2   Human study

A final part of this study was to include an online human study that follows the same design as the

animal part. Figure 5 shows the average performance of humans (dark blue) versus rats (light blue)

for all nine test protocols, as well as their performance on the old stimuli that were added in (or

during) the testing protocols as quality control. Overall, humans performed better on all tests

protocols than rats, with an average performance over all tests of 94.34% (humans) and 62.29%

(rats). There was already a difference in terms of training performance (humans: 92.86% vs. rats:

77.84%), but the difference on the test protocols is larger. We subtracted the training performance

of humans or rats from the testing performance of humans or rats, respectively, and even with this

normalization for training performance there is still a significantly higher test performance in humans

compared to rats (t(16) = -6.47, p < 0.0001). Thus, not surprisingly, the degree of invariance in this

object classification task is higher for humans compared to rat.

Figure 5 Average performance of humans versus rats. On the x-axis, the nine test protocols in addition to the performance

on all old stimuli are presented in the following order: rotation x (RotX), rotation y (RotY), rotation z (RotZ), size, position

(Pos), light location (LL), Combination rotation (CR), Zero vs. high (ZVH), High vs. zero (HVZ) and All Old. The dashed

horizontal line indicates chance level. The error bars indicate standard error over humans/rats.

The variation in performance across test protocols and across image pairs can give an indication of

the strategies that each species follows. Overall, humans and rats show a mild correspondence in

terms of which image pairs are more difficult, with a human-rat correlation of 0.18 across all image

pairs of the nine test protocols (p < 0.001 with permutation test). Albeit significant, this correlation is

clearly lower than the maximum value that could be obtained given the reliability of the data. The

split-half reliability of the human data was 0.46, corresponding to a full-set reliability of 0.63. We

reported above that full-set reliability is 0.58 for the rat data, resulting in a combined reliability of

0.60 (calculated as described in Op de Beeck et al., 2008). Thus, after taking data reliability into

account there remains a pronounced discrepancy between rats and humans in terms of how

performance varies across image pairs.

The main question of the present study is how this discrepancy relates to computationally informed

strategies. If we take a closer look specifically at the two CNN-informed test protocols (*Zero vs. high*

and *High vs. zero*), we see an opposite behaviour between animals and humans. Humans performed

significantly better in the *Zero vs. high* protocol, i.e. where we used stimuli where the earlier layers of

the network perform worse than the higher layers, than in the *High vs. zero* protocol (paired t-test:

t(44) = 2.85, p = 0.0067). Rats, however, show the opposite (see above for statistics). There even is a

significant interaction between species and test protocol (unpaired t-test: t(54) = 2.50, p = 0.016).

This suggests a different strategy between animals and humans: rats use strategies that are captured

in the lower layers of the network, and thus correspond more to low level visual processing. Humans,

however, tend to rely more on strategies captured by the higher layers of the network, and thus we

are looking at more high-level visual processing.

As a next step, we calculated the correlation between the generalization across image pairs between

the CNN classifier and the human performance of all nine test protocols in an identical manner as for

the rat performance (Figure 4). The results are displayed in Figure 6. Overall, we see quite high

correlations, especially in the higher layers. This pattern across layers is very different from the

pattern in rats where the highest layers showed no correlations, which again suggests that, despite

successful generalization, rats rely on decisively lower-level strategies than humans in the same

discrimination task.

Figure 6 Correlation of the Classification Score for single target/distractor pairs between single CNN layers and the human performance, for all nine test protocols together. The naming convention on the x axis corresponds to the layers of the network, identical as in Figure 4. The black and grey horizontal lines on the x-axis indicated the layer blocks (block 1 consisting of conv1, norm1, pool1; block 2 consisting of conv2, norm2, pool2; block 3-4 corresponding to conv3-4 (respectively); block 5 consisting of conv5, pool5; block 6-7-8 corresponding to fc6-7-8, respectively. The vertical grey dashed line indicates the division between convolutional and fully connected layer blocks. The horizontal dashed line indicates a correlation of 0. The different markers indicate different sorts of layers: circle for convolutional layers, triangle for normalization layers, point for pool layers, and squares for fully connected layers. The asterisks indicate significant correlations according to a permutation test (* < 0.05, ** < 0.01 and *** < 0.001).

A multiple linear regression was calculated in an identical manner as we did with the rat

performance. The results of this regression indicate a significant effect of the Classification Scores

$(F(287,273) = 6.8, p < 0.0001, R^2 = 0.25)$. Further investigating the 13 predictors showed that in

particular the fully connected layers 11, 12 and 13 of the network were strong predictors in the

regression model (see Supplemental Table 9 for results of the regression model).

Given the high correlations with fully connected layers, we would expect to not find much evidence

for an influence of basic visual dimensions such as brightness and pixel-based similarity. Indeed, we

find small correlations with variation in human behavioural performance across image pairs for pixel

similarity (0.12) and for brightness (-0.12).

3   Discussion

In the current study, we trained and tested rats and humans in a discrimination task using two-dimensional stimuli, with the two dimensions being concavity and alignment. We tested generalization across a range of viewing conditions. For the last two testing protocols, we used a computational approach to select the stimuli in terms of specifically dissociating low and high stages of processing. Rats were able to learn both dimensions (concavity and alignment) and showed a preference for concavity. Their performance on the testing protocols revealed a wide variety in percentage correct: for some test protocols they performed just above chance level, e.g. *Zero vs. high*, whereas for others they could easily reach about 70% correct (*Position*). Humans, on the other hand, performed better overall, with performances of 80% or higher on the testing protocols. Addressing the question of the complexity of the underlying strategies, rats performed best on the test protocol designed to specifically target lower levels of processing whereas humans performed best on the high-level processing protocol. Likewise, direct comparisons with artificial neural network layers showed that the variation of rat performance across images was best explained by late convolutional layers, whereas human performance was most associated with representations in fully connected layers.

All animals started by being trained in three training protocols. The first *Training* protocol only included one image pair, the base pair, containing the most different target and distractor without any further transformations. Learning of the individual dimensions of concavity and alignment was investigated through the *Dimension learning* protocol. The results from this *Dimension learning* protocol indicate that our rats have more difficulties learning the alignment dimension as opposed to the concavity dimension. One possible explanation for the superior performance on the concavity dimension could be that the animals were partially solving the task such that the brighter stimulus, i.e. the convex base shape, is the distractor and that their strategy is to pick the stimulus with the lowest brightness. This was confirmed by analyses on the third training protocol (*Transformations*) that included small transformations along various dimensions. Nevertheless, the rats still performed

above chance level for trials in which the brightness differences were reversed, indicating that other

dimensions are involved and overrule a contribution from brightness. Similar findings have been

obtained in human behaviour and neuroscience. For example, despite the clear category selectivity

in regions such as the fusiform face area, the selectivity in these regions is also modulated very

strongly by various low-level dimensions (Yue et al., 2011). With regard to the size and position

transformations it is important to keep in mind that the animals were freely moving in the

touchscreen chambers, and so even for the original base pair was already undergoing changes in

retinal size and retinal position. What we manipulate, is rather the size and position relative to the

rest of the set-up (e.g., relative to screen position and size).

After these three training protocols, the animals were tested for generalization in a variety of testing

protocols, each testing a separate transformation on the stimuli. The first six test protocols included

rotation along all the three axes, size, position and light location, following by a test protocol in which

we combined the rotation along the three axes. Overall, we found that the performance of the

animals on these test protocols is affected by these transformations, but still significantly above

chance in each protocol. Studies in the literature would often stop here, or proceed by systematically

testing even larger transformations. Stimulus choices are based upon intuitions of what strategy

animals might be using, and upon theories of how visual perception works. However, in some cases,

a further computational modelling of the task and stimuli finds that what intuitively seems like a task

of a particular complexity might not be so complex after all. The first tests of invariant object

recognition seemed impressive, but were found to be easily solved with earlier layers of processing

(Minini & Jeffery, 2006; Vinken & Op de Beeck, 2021). This was recently also highlighted by relatively

simple pixel-based analyses (Kell et al., 2020). As another example, Vinken & Op de Beeck (2021)

have used a computational approach to further investigate the levels of information processing in

rodents by comparing three hallmark studies that provided evidence for higher order visual

processing in rodents (Djurdjevic et al., 2018; Vinken et al., 2014; Zoccolan et al., 2009) with CNNs.

They found that for all three studies, the low and mid-level layers captured the rat performances

best, providing thus evidence against the previously concluded high level visual processing in

rodents.

For these reasons, we decided to directly test image pairs through computational modelling with

CNNs and select pairs that are particularly suited of dissociating different levels of processing. Stimuli

were chosen by a CNN from a very large set of possible stimuli and combinations, such that the

higher layers and the lower layers of the network make distinct errors on classifying the stimuli (*Zero*

vs. high and *High vs. zero* protocol), and thus are diagnostic of the level of underlying visual

strategies. We chose to work with Alexnet, as this is a network that has been used as a benchmark in

many previous studies (e.g. (Cadieu et al., 2014; Groen et al., 2018; Kalfas et al., 2018; Nayebi et al.,

2023; Zeman et al., 2020)), including studies that used more complex stimuli than the stimulus space

in our current study. The stimuli of the *Zero vs. high* protocol included stimuli where the higher layers

of the network performed better than the lower layers, and thus they address higher level visual

processing. The opposite can be said for the *High vs. zero* protocol, which includes stimuli that

specifically target lower level visual processing, given that the lower layers of the network perform

best on these stimuli. After presenting these stimuli to the animals, we found that our rats

performed best in the *High vs. zero* protocol, suggesting that they focus on low level visual cues to

solve this discrimination task. We found the opposite CNN pattern for humans, indicating that they

use high level visual processing. These findings provide more direct information about the level of

processing that underlies the behavioural strategies compared to overall performance or to effects of

image manipulations.

This is a new promising way to design experiments in a way that is computationally informed rather

than based on researcher intuitions or qualitative predictions. It is in line with the literature that a

typical deep neural network, AlexNet and also more complex ones, can explain human and animal

behaviour to a certain extent but not fully. The explained variance might differ among DNNs, and

there might be DNNs that can explain a higher proportion of rat or human behaviour. Most relevant

for our current study is that DNNs tend to agree in terms of how representations change from lower

to higher hierarchical layers, because this is the transformation that we have targeted in the Zero vs.

high and High vs. zero testing protocols. (Pinto et al., 2008) already revealed that a simple V1-like

model can sometimes result in surprisingly good object recognition performance. This aspect of our

findings is also in line with the observation of Vinken & Op de Beeck (2021) that the performance of

rats in many previous tasks might not be indicative of highly complex representations. Nevertheless,

there is still a relative difference in complexity between lower and higher levels in the hierarchy. That

is what we capitalize upon with the Zero vs. high and High vs. zero protocols. Thus, it might be more

fruitful to explicitly contrast different levels of processing in a relative way rather than trying to

pinpoint behaviour to specific levels of processing.

Partially thanks to these computationally inspired tests, our total dataset finds a marked dissociation

between how humans and rats solve this object recognition task. Even in the sessions where only the

old pairs are shown, the animals performed lower than humans. This was most likely due to

motivation and/or distractibility. Our analyses show dissociation between humans and rats most

convincingly by correlating the variation in performance across image trials with the predictions of

CNN layers. There were significant correlations with multiple layers in both species. In humans, the

most pronounced correlations were present for the highest, fully connected layers, while in rats

correlations were limited to low and middle convolutional layers. This is the most direct evidence

available in the literature that rats resolve object recognition tasks through a very different and

computationally simpler strategy compared to humans. The CNN approach does not inform us how

we can verbalize this simpler strategy, but based upon earlier work (Schnell and colleagues, 2023);

Vermaercke & Op de Beeck, 2012) we would hypothesize that rats rely upon visual contrast features

(e.g., this area is darker/lighter than that other area). Such contrast features are also used by humans

and monkeys, e.g. for face detection (Ohayon et al., 2012; Sinha, 2002), but in addition humans have

access to more complex strategies that e.g. refer to complex shape features such as aspect ratio and

symmetry (Bossens & Op de Beeck, 2016). Tests in the present study reveal that other features that

partially explain rat performance include basic dimensions such as brightness and pixel-based

similarity, the latter being a proxy for retinotopically based computations that are expected to be

present in convolutional layers.

Our analyses of rat behaviour and DNN modelling do not take into account potential trial-to-trial

variability in the distance and position of the rat's head. From earlier work we can derive that rats

typically make their decision from about 12 cm from the stimulus display (Crijns & Op de Beeck,

2019), but we have no information on trial-to-trial variability. We can hypothesize about the possible

effect. If such variability would exist, then it would artificially increase the variation in distance and

position during training, and thus help the animals to achieve higher levels of invariance during

testing. As a consequence, the difference between rat and human performance in terms of inferred

level of processing might even increase under more controlled circumstances.

For future studies, it will be highly valuable to use this computational informed strategy on a wider

battery of behavioural tasks, as well as a wider range of species such as tree shrews and marmosets

(Callahan & Petry, 2000; Kell et al., 2020, 2021; Meyer et al., 2022; Petry et al., 2012; Petry &

Bickford, 2019). One step further, we can use the information from computational modelling

together with behaviour and how it differs among stimuli to further select stimuli for

neurophysiological investigations of neuronal response properties along the visual information

processing hierarchy, in this way following experimental designs that are optimized for highlighting

the primary differences between processing stages and between species.

4   Methods

4.1   Animal study

4.1.1 Animals

A total of twelve male outbred Long Evans rats (Janvier Labs, Le Genest-Saint-Isle, France) started

this behavioural study. Out of these twelve animals, two were tested extensively in a first pilot study,

and were included in the remainder of the study as well. All animals were 11 weeks old at the start of

shaping and were housed in groups of four per cage. Each cage was enriched with a plastic toy (Bio-

Serv, Flemington, NJ), paper cage enrichment and wooden blocks. Near the end of the experiment,

one animal had to be excluded because of health issues. During training and testing, the animals

were food restricted to maintain a body weight between 85% and 90% of their underprived body

weight. They received water ad libitum. All experiments and procedures involving living animals were

approved by the Ethical Committee of the University of Leuven and were in accordance with the

European Commission Directive of September 22, 2010 (2010/63/EU).

4.1.2 Setup

The setup is identical to the one used by Schnell and colleagues (2019) and Schnell and colleagues

(2023). A short description will follow here. The animals were trained and tested in four automated

touch-screen rat-testing chambers (Campden Instruments, Ltd., Leicester, UK) with ABET II controller

software (v2.18, WhiskerServer v4.5.0). The animals performed one session per day and each session

lasted for 100 trials or 60 minutes, whichever came first. A reward tray in which sugar pellets (45-mg

sucrose pellets, TestDiet, St. Louis, MO) could be delivered was installed on one side of the chamber.

On the other side of the chamber, an infrared touchscreen monitor was installed. This monitor was

covered with a black Perspex mask containing two square response windows (10.0 x 10.0 cm). A shelf

(5.4cm wide) was installed onto this black mask (16.5cm above the floor) to force the animals to

attend to the stimuli and to view the stimuli within their central visual fields. Close proximity to the

screen was enough to elicit a response because the screens are infrared. As the position of the rats in

434   the touchscreen setup is not fixed, the actual size and position of the stimuli might vary in retinal

435   coordinates. In a previous study we manipulate the cycles per degree of stimuli in an orientation

436   discrimination task, and estimated that the decision distance of rats in this setup lies around 12.5 cm

437   from the screen (Crijns & Op de Beeck, 2019). Supplemental Figure 1 shows the timeline graphic of a

438   correct and incorrect trial as well as images of the experimental setup.

439   4.1.3 Stimuli

Stimuli were created using the Python scripting implementation of the 3D modelling software

Blender 3D (version 2.93.3) and measured 100 x 100 pixel. In general, the stimuli were objects that

consisted of a body (base) with three spheres attached to it. A first step was to alter two dimensions

of the object, namely the concavity of the base and the alignment of the three spheres. The base was

made either concave or convex by increasing (convex) or decreasing (concave) the base parameter.

The alignment of the spheres was altered by changing the placement of the left and the right

spheres. These spheres could either be horizontally aligned or misaligned. In the misaligned case, the

spheres were placed diagonally from upper left to lower right. Figure 7a shows two example stimuli,

the ones that later were selected as the so-called "base pair". Next, additional exemplars were

created by uniformly tiling the two-dimensional stimulus space between these two example stimuli.

We decided to create eleven levels of the concavity dimension and four levels of alignment. This

already yields 44 stimuli (see Supplemental Figure 3). We chose these levels of concavity and

alignment based on the pixel dissimilarity of the stimuli (see Supplemental Figure 4). The final goal

was to construct a 4x4 stimulus grid (Figure 7b) by selecting a subset of the 4x11 stimulus grid. We

chose a large number of concavity levels, as this ensures flexibility in the calibration of the two

dimensions relative to each other.

457
458
459
460

We added identity-preserving transformations to the stimuli, such as rotation among the x-axis, y-

axis and z-axis in six different angles (0° to 180° in steps of 30°), as well as changing the light location

(left, under, up, right, front) and finally the size and position. The latter two transformations were

implemented using Python (3.7.3). Excluding the size and position transformation, these

transformations resulted in a total set of 75460 stimuli (4 (alignment) * 11 (concavity) * 7 (x-axis

rotation) * 7 (y-axis rotation) * 7 (z-axis rotation) * 5 (light location) = 75460 stimuli). Supplemental

Figure 5 shows examples of these transformations and Figure 1 shows an overview of all image pairs

that were used in this study.

4.1.4 Protocols

Once the pilot was finished (see supplementary for details), we set up the experiment and chose our

stimuli. We started by reducing the 4x11 stimulus grid to a 4x4 stimulus grid (see Figure 7b). All

stimuli on the diagonal can be seen as ambiguous stimuli (four stimuli in total), as they can be

identified as a target as well as a distractor. The six stimuli above this diagonal create the target part

of the grid, and the six stimuli below this diagonal resemble the distractor sub-grid.

The different phases of the experiment are shown in Figure 1 and this figure shows all stimuli that

were used. In the main Training phase, we trained the animals in the maximally different stimuli that

are placed at the very ends of the corners (Figure 7a). We refer to this as the base pair. After this

Training phase, the experiment consisted of two further training protocols. In the Dimension learning

training phase, we pushed the animals to learn both dimensions (concavity and alignment) by

presenting them two additional stimuli pairs from Figure 7b in which the target and distractor differ

in only one dimension. A third training protocol (*Transformations*) consisted of stimuli with some

small transformations, such as 30° rotation along the x-axis, 30° rotation along the y-axis, 30°

rotation along the z-axis, light location below, and size reduction of 80%, resulting in a total of 25

possible stimulus pairs (every combination of target-distractor with the 5 transformed stimuli).

During these two training protocols, one third of the trials were so-called "old trials" with the base

pair. Correction trials were given if an animal answered incorrectly, i.e. the same trial was repeated

until the animal answered correctly. These correction trials were excluded from the analyses. In all

trials, rats received a reward for touching the correct screen, i.e. the screen with the target.

After these three training protocols, the testing part of the experiment included nine test protocols.

The crucial defining difference between these test protocols and the prior training protocols is that

rats received a reward randomly in 80% of the trials with new stimulus pairs, and no correction trials

were given for an incorrect response. This random reward is important to keep the animals

motivated during the testing protocols and to measure real generalization, and not training

behaviour. We have used a similar approach in the past, where we rewarded the animals in every

testing trial (Schnell et al., 2019; Vinken et al., 2014). One third of the trials in all test protocols

consisted of old trials with the base pair, and here, the animals received reward for touching the

target and correction trials were shown if necessary. Regularly, we inserted a *Dimension learning*

session in between two test sessions to maintain the performance high enough on training stimuli,

especially for the animals in which we saw a drop in performance on the base pair. We excluded any

test sessions where the performance on the base pair stimuli dropped to below 65% and the

performance on this base pair was not included in the accuracy calculations.

The first six test protocols included one protocol for each transformation, i.e. *Rotation X, Rotation Y,*

Rotation Z, Light Location, Size and *Position.* The order in which these first six test protocols were

given to the animals was counterbalanced between the animals. The stimuli that were used in these

six test protocols can be seen in Figure 1 and every combination of target-distractor per test protocol

was presented to the animals. For the rotation protocols, we used rotation degrees in steps of 30°,

ranging from 30° to 180°. This resulted in 36 possible stimulus pairs for each of the three rotation

protocols. In the *Light Location* protocol, we used stimuli where the light location was set at four

different positions (below, left, right and up), resulting in 16 possible stimulus pairs for this protocol.

In the *Size* protocol, we selected targets and distractors that were 80% and 60% reduced in size

compared to the original, training pair. This protocol included 4 possible stimulus pairs. And finally, in

the *Position* protocol, we changed the position of the 80% reduced in size stimuli and placed the

objects in the lower left corner, lower right corner, centre, upper left corner and upper right corner.

We have a total of 25 possible stimulus pairs for this protocol.

After these six test protocols, we presented the animals with six targets and six distractors where all

three rotations were combined (*Combination rotation*), i.e. x-, y- and z-axis were rotated with the

same degree (ranging from 30° to 180°, in steps of 30°). This resulted in a total of 36 new stimulus

pairs. Again, no correction trials were included after the trials where rotated stimuli were shown and

animals received random reward in 80% of the trials. One third of the trials consisted of the stimulus

pair from the first *Training* phase (i.e. the base pair), and here, correction trials were given after an

incorrect response and real reward was given to the animals.

In a final set of two test protocols, we created a CNN-informed stimulus set. The details of the

computational modelling are explained in the next section. The first protocol (*Zero vs. high*) included

stimuli in which the lower layers of the network performed around chance level (i.e. target-distractor

difference in Classification Scores (difference in signed distance to hyperplane) of about 0), whereas

the higher layers scored high (see section 4.2). The second protocol (*High vs. zero)* included stimuli

where the network did the opposite. That is, the earlier layers performed well whereas the higher

layers performed around chance level. The order of the two test protocols was counterbalanced

between the animals. Each of these test protocols included 7 targets and 7 distractors, giving a total

of 49 new stimulus pairs.

Animals stayed in each session for 60 minutes or until they reached 100 training trials or 120 testing

trials. We used an intertrial interval (ITI) of 20s and a time-out of 5s during training sessions. This

time-out was only used in incorrect trials. From another pilot study in the lab, we noticed we could

decrease the ITI and time-out without affecting the rats' performance. Therefore, we decided to use

an ITI of 15s and time-out of 3s during testing, and to increase the number of trials during a testing

session to 120 trials. The stimuli remained on the screen until the animals made a choice and so

there was no time limit for the animals.

Each protocol was run for multiple sessions per animal. Given that we were interested in how

performance would vary across stimulus pairs, we completed more sessions for the protocols that

included more stimulus pairs. Supplemental Table 1 indicates the average number of trials per test

protocol for all rats together.

One animal was not placed in the *Transformations* phase as it was the slowest animal during training.

However, its performance on the test protocols did not significantly differ from the other animals.

We tested this by calculating the correlation of the variation of performance across stimulus pairs for

each rat with the pooled responses of all other rats. The average correlation for each of the other

animals with the pooled response was 0.24 (±0.09), and the correlation of this slowest animal with

the others was very similar, 0.23.

To further examine the visual features that could explain rat performance, we calculated the

correlation between the rat performances and image brightness of the transformations. We did this

by calculating the difference in brightness of the base pair (brightness base target – brightness base

distractor), and subtracting the difference in brightness of every test target-distractor pair for each

test protocol (brightness test target – brightness test distractor for each test pair). We then

correlated these 287 brightness values (1 for each test image pair) with the average rat performance

for each test image pair. We performed a similar correlation analysis for pixel similarity to investigate

the correlation between pixel similarity of the test stimuli in relation to the base stimuli with the

average performance of the animals on all nine test protocols. We did this by calculating the pixel

similarity between the base target with every other testing distractor (A), the pixel similarity between

the base target with every other testing target (B), the pixel similarity between the base distractor

with every other testing distractor (C) and the pixel similarity between the base distractor with every

other testing target (D). For each test image pair, we then calculated the average of (A) and (D), and

subtracted the average of (C) and (B) from it. We correlated these 287 values (one for each image

pair) with the average rat performance on all test image pairs.

4.2   Computational modelling

One important goal of this study was to create a CNN-informed stimulus set to present to the

animals. To do so, we followed the steps of Schnell and colleagues (2023) and Vinken & Op de Beeck

(2021) to train a CNN on the same stimuli on which our animals were trained. The steps of training

the network are identical to Schnell and colleagues (2023) and a short description will follow here.

We used the standard AlexNet CNN architecture that was pre-trained on ImageNet to classify images

into 1000 object categories (MATLAB 2021b Deep Learning Toolbox). Following Vinken & Op de

Beeck (2021), we applied principal component analysis to calculate the activations in every layer, to

standardize the values across inputs and to reduce the dimensionality. We then trained a linear

support vector machine classifier by using the MATLAB function fitclinear, with limited-memory BFGS

solver and default regularization. We performed this with the standardized DNN layer activations in

the principal component space as inputs, before ReLU, to our 24 training stimuli (see Figure 1**Error!**

eference source not found.), i.e. all stimuli of the *Training, Dimension* learning and *Transformations*

protocols. The layers of AlexNet were divided into 13 sublayers, similar as in Schnell and colleagues

(2023) and Vinken & Op de Beeck (2021).

Figure 8 shows the performance of the network for each of the test protocols after training

classifiers on the training stimuli using the different CNN layers. We added noise to the inputs of the

network such that the average training performance, averaged over 100 iterations, lies around 75%.

By adding noise in this way, the performance on the training pairs matches overall with rat

performance on those pairs, otherwise the performance of the network would be at 100% on the

training pairs and this would complicate comparisons with the animal data (see also Vinken & Op de

Beeck, 2021). Note that the results for the *Size* test are unreliable given the low number of stimulus

pairs in that test. The performance of the network on the tests (green line in Figure 8) differs among

the tests and across layers, but typically the network had no problems to achieve a training

performance of about 85% in all test protocols in at least some layers. The change in performance

across layers is variable across test protocols.

Figure 8 The performance of the CNN after training on our training stimuli, with noise added to its input. The naming convention on the x axis corresponds to the layers of the network, identical as in Figure 4. The performance (y-axis) illustrates that each layer is challenged by at least part of the test protocols. The purple line indicates the training performance and the green line indicates the test performance of the neural network. The x axis on each subplot indicates the block of the layer: layer blocks 1-8 correspond to (convolutional layer 1, normalization layer 1, pool layer 1), (convolutional layer 2, normalization layer 2, pool layer 2), convolutional layer 3, convolutional layer 4, (convolutional layer 5, pool layer 5), fully connected layer 6, fully connected layer 7 and fully connected layer 8, respectively. The black and grey horizontal lines on the x-axis indicated the layer blocks (block 1 consisting of conv1, norm1, pool1; block 2 consisting of conv2, norm2, pool2; block 3-4 corresponding to conv3-4 (respectively); block 5 consisting of conv5, pool5; block 6-7-8 corresponding to fc6-7-8, respectively. The vertical grey dashed line indicates the division between convolutional and fully connected layer blocks. The horizontal dashed line indicates chance level. The shaded error bounds correspond to 95% confidence intervals calculated using Jackknife standard error estimates, as done previously in *(Vinken & Op de Beeck, 2021)*. The different markers indicate different sorts of layers: circle for convolutional layers, triangle for normalization layers, point for pool layers, and squares for fully connected layers.

To examine the performance of the model for specific image pairs during training and testing in more

detail than possible with a binary categorization decision, we calculate the distance to the classifier's

hyperplane (decision boundary) of the targets and distractors. We do this by computing the

difference in signed distance to the hyperplane between target and distractor (target – distractor).

This is referred to as the Classification Score. For each stimulus pair in the test protocols we

computed this Classification Score and we have such a score per layer.

We used this Classification Score to select image pairs for a CNN-informed stimulus set. To do so, we

randomly chose one target and one distractor from a subset of the pool of all 4x4 stimuli, including

all possible transformations on these stimuli. This resulted in a stimulus pool of 10.290 stimuli (5145

targets, 5145 distractors) to randomly choose two from, and 5145*5145 (26 471 025) possible

resulting pairs of two stimuli. Once one random target and one random distractor was chosen, the

DNN was tested in a similar manner as we did for the six test protocols. We performed a total of

10000 iterations of randomly choosing a target and distractor pair. For each iteration, we calculated

the average Classification Score of layers 1-3 and of layers 11-13 as we wanted to compare those two

levels of processing (earlier layers vs higher layers). After these 10000 iterations, we finetuned and

filtered the results according to the profile of performance across earlier and higher layers (see

Supplemental Table 2). This finetuning started by calculating the distribution and standard deviation

for two profiles of interest, i.e. (i) where early layers show an average Classification Score close to

zero but higher layers show high Classification Scores (Zero vs High), and (ii) where early layers show

high Classification Scores but higher layers show close to zero Classification Scores (High vs Zero). The

performance was expressed relative to the distribution of values across all pairs, summarized by de

standard deviation of the average target-distractor difference in Classification Scores of the early

layers and the higher layers. We found a total of 48 stimulus pairs for these two criteria, and we

ended up choosing 14 pairs, 7 of each criterion, that we used for the final part of the animal and

human study (see lower two rows in Figure 1).

Afterwards we also calculated the binary target-distractor CNN decision performance for the image

pairs in the Zero vs High and High vs Zero tests, which is shown in Figure 8 (bottom row). The image

pairs in the Zero vs High protocol are more difficult than the other protocols, in particular for the first

half of the CNN layers. In contrast, the *High vs Zero* protocol is the only protocol associated with

chance performance in the last three layers. These analyses confirm that the CNN-based image pair

selection resulted in protocols that are very different from protocols that zoom in on intuitively

chosen transformations and their combinations.

Comparing the rat performances to the Classification Scores of the network was done by calculating

the correlation across image pairs between these model scores and the rat performances averaged

across animals. We concatenated the performance of the animals on all nine test protocols, as well

as the distance to hyperplane of the network on all nine test protocols. Correlating these two arrays

resulted in the correlations as visualized in Figure 4. To test whether these correlations are

significant, we performed a permutation test. We permutated these arrays 1000 times, resulting in a

normal distribution of permutated data per layer. We then calculated, per layer, how many of the

permutated values are higher than or equal to the correlation that is presented in Figure 4, and

divided this by the number of permutations.

4.3 Human study

4.3.1 Participants

Data was collected from 50 participants (average age 33.24 ± 12.23; 34 females) who participated in

return for a gift voucher of 10 euro. Out of these 50 participants, 5 were excluded because of

outlying behaviour during the quality check protocols (see Section 4.3.3). All participants had normal

or corrected-to-normal vision. The experiment was approved by the ethical commission of KU Leuven

(G-2020-1902-R3) and each participant digitally signed an informed consent before the start of the

experiment.

4.3.2 Setup

For the human part of this study, we developed an online experiment using PsychoPy3 (v2020.1.3, Python version 3.8.10) and placed it on the online platform Pavlovia. All participants received the link and their individual participant number by e-mail with which they could participate in the experiment on their own computer. It took 30-45 minutes to complete the online study.

4.3.3 Stimuli and protocols

We used the same stimuli as in the animal study. The human experiment underwent the same phases as depicted in Figure 1, albeit with small changes. We dropped the $1/3^{rd}$ old trials in the test protocols and included two additional *Dimension Learning* protocols in between the first counterbalanced tests as quality check (see Supplemental Figure 7). Supplemental Table 3 provides an overview of the number of trials during the human experiment for each phase. Supplemental Figure 7 shows an overview of all image pairs that were presented in the human study.

Similar as in Bossens & Op de Beeck (2016), we presented the targets and distractors briefly to the left and right side of a white fixation cross on a grey background. Each stimulus was presented for three frames, followed by a mask (a noise image with 1/f frequency spectrum for three frames). We used this fast and eccentric stimulus presentation with a mask to resemble the stimulus perception more closely to that of rats. Vermaercke & Op de Beeck (2012) have found that human visual acuity in these fast and eccentric presentations is not significantly better than the reported visual acuity of rats. By using this approach we avoid that differences in strategies between humans and rats would be explained by such a difference in acuity. Participants could then answer using the 'f' and 'j' keys to indicate which position they thought was the correct position. If they thought the target was on the left side of the fixation cross, they had to press 'f', and 'j' if they thought the target was on the right side. Participants received feedback during the shaping and the three training phases. This happened by colouring the fixation cross green if they answered correctly, and red if they answered incorrectly. Each trial was followed by an intertrial interval (ITI) of 0.5s. During the *Shaping* and *Training* phase,

we kept a running average of the past 20 (*Shaping*) and 40 (*Training*) trials and participants

continued to the next phase when they reached a performance of 80% or higher on the last 20 or 40

trials, similar as in Bossens & Op de Beeck (2016). There was no time limit for the participants for

providing a response. The order of the first six test protocols (*Rotation X, Rotation Y, Rotation Z, Size,*

Light Location and *Position)* was counterbalanced between the participants based on the participant

number, as well as the order of the last two test protocols (*Zero vs. high* and *High vs. zero*), similar as

the approach in the rat study. Supplemental Table 1 indicates the average number of trials per test

protocol for all human participants together.

In terms of instructions, we explained to participants that they would see two figures appearing at

the same time very quickly next to a fixation cross, and they would have to make a decision of which

figure is the correct one. We mentioned that during training, the fixation cross would turn green if

they answered correctly, and red if they answered incorrectly. Participants were informed that

during testing, they would not get feedback (changing colour of the fixation cross) anymore and that

they would have to use the knowledge they gained throughout training to make their decision in the

testing.

We performed a similar correlation analysis as with rat performance to investigate the correlation

between pixel similarity and brightness with human performance. We followed the exact same steps

as we did for rat performance.

References

Alemi-Neissi, A., Rosselli, F. B., & Zoccolan, D. (2013). Multifeatural Shape Processing in Rats Engaged in Invariant Visual Object Recognition. *Journal of Neuroscience*, *33*(14), 5939–5956. https://doi.org/10.1523/JNEUROSCI.3629-12.2013

Avberšek, L. K., Zeman, A., & Op de Beeck, H. (2021). Training for object recognition with increasing spatial frequency: A comparison of deep learning with human vision. *Journal of Vision*, *21*(10), 14. https://doi.org/10.1167/jov.21.10.14

Bossens, C., & Op de Beeck, H. P. (2016). Linear and Non-Linear Visual Feature Learning in Rat and Humans. *Frontiers in Behavioral Neuroscience*, *10*. https://doi.org/10.3389/fnbeh.2016.00235

Cadieu, C. F., Hong, H., Yamins, D. L. K., Pinto, N., Ardila, D., Solomon, E. A., Majaj, N. J., & DiCarlo, J. J. (2014). Deep Neural Networks Rival the Representation of Primate IT Cortex for Core Visual Object Recognition. *PLOS Computational Biology*, *10*(12), e1003963. https://doi.org/10.1371/journal.pcbi.1003963

Callahan, T. L., & Petry, H. M. (2000). Psychophysical measurement of temporal modulation sensitivity in the tree shrew (Tupaia belangeri). *Vision Research*, *40*(4), 455–458. https://doi.org/10.1016/S0042-6989(99)00194-7

Crijns, E., & Op de Beeck, H. (2019). The Visual Acuity of Rats in Touchscreen Setups. *Vision*, *4*, 4. https://doi.org/10.3390/vision4010004

De Keyser, R., Bossens, C., Kubilius, J., & Op de Beeck, H. P. (2015). Cue-invariant shape recognition in rats as tested with second-order contours. *Journal of Vision*, *15*(15), 14. https://doi.org/10.1167/15.15.14

Djurdjevic, V., Ansuini, A., Bertolini, D., Macke, J. H., & Zoccolan, D. (2018). Accuracy of Rats in Discriminating Visual Objects Is Explained by the Complexity of Their Perceptual Strategy. *Current Biology*, *28*(7), 1005-1015.e5. https://doi.org/10.1016/j.cub.2018.02.037

Duyck, S., Martens, F., Chen, C.-Y., & Op de Beeck, H. (2021). How Visual Expertise Changes

Representational Geometry: A Behavioral and Neural Perspective. *Journal of Cognitive*

Neuroscience, *33*(12), 2461–2476. https://doi.org/10.1162/jocn_a_01778

Groen, I. I., Greene, M. R., Baldassano, C., Fei-Fei, L., Beck, D. M., & Baker, C. I. (2018). Distinct

contributions of functional and deep neural network features to representational similarity

of scenes in human brain and behavior. *ELife*, *7*, e32962. https://doi.org/10.7554/eLife.32962

Güçlü, U., & Gerven, M. A. J. van. (2015). Deep Neural Networks Reveal a Gradient in the Complexity

of Neural Representations across the Ventral Stream. *Journal of Neuroscience*, *35*(27),

10005–10014. https://doi.org/10.1523/JNEUROSCI.5023-14.2015

Kalfas, I., Vinken, K., & Vogels, R. (2018). Representations of regular and irregular shapes by deep

Convolutional Neural Networks, monkey inferotemporal neurons and human judgments.

PLOS Computational Biology, *14*(10), e1006557.

https://doi.org/10.1371/journal.pcbi.1006557

Kar, K., Kubilius, J., Schmidt, K., Issa, E. B., & DiCarlo, J. J. (2019). Evidence that recurrent circuits are

critical to the ventral stream's execution of core object recognition behavior. *Nature*

Neuroscience, *22*(6), Article 6. https://doi.org/10.1038/s41593-019-0392-5

Kell, A. J. E., Bokor, S. L., Jeon, Y.-N., Toosi, T., & Issa, E. B. (2020). *Conserved core visual object*

recognition across simian primates: Marmoset image-by-image behavior mirrors that of

humans and macaques.

Kell, A. J. E., Bokor, S. L., Jeon, Y.-N., Toosi, T., & Issa, E. B. (2021). *Brain organization, not size alone,*

as key to high-level vision: Evidence from marmoset monkeys (p. 2020.10.19.345561).

bioRxiv. https://doi.org/10.1101/2020.10.19.345561

Kubilius, J., Bracci, S., & Op de Beeck, H. (2016). Deep Neural Networks as a Computational Model for

Human Shape Sensitivity. *PLOS Computational Biology*, *12*(4), e1004896.

https://doi.org/10.1371/journal.pcbi.1004896

Logothetis, N. K., & Sheinberg, D. L. (1996). *Visual Object Recognition*. 45.

Matteucci, G., Marotti, R., Riggi, M., Rosselli, F. B., & Zoccolan, D. (2019). Nonlinear Processing of

Shape Information in Rat Lateral Extrastriate Cortex | Journal of Neuroscience. *Journal of*

Neuroscience. https://doi.org/10.1523/JNEUROSCI.1938-18.2018

Meyer, E. E., Ong, W. S., Balboa, M., & Arcaro, M. J. (2022). *Assessing tree shrew high-level visual*

behavior using conventional and natural paradigms [Poster]. Society for Neuroscience.

Minini, L., & Jeffery, K. J. (2006). Do rats use shape to solve "shape discriminations"? *Learning &*

Memory, *13*(3), 287–297. https://doi.org/10.1101/lm.84406

Nayebi, A., Zhuang, C., Norcia, A. M., Kong, N. C. L., Gardner, J. L., & Yamins, D. L. K. (2023). *Mouse*

visual cortex as a limited resource system that self-learns an ecologically-general

representation (p. 2021.06.16.448730). bioRxiv. https://doi.org/10.1101/2021.06.16.448730

Ohayon, S., Freiwald, W. A., & Tsao, D. Y. (2012). What Makes a Cell Face Selective? The Importance

of Contrast. *Neuron*, *74*(3), 567–581. https://doi.org/10.1016/j.neuron.2012.03.024

Op de Beeck, H., Torfs, K., & Wagemans, J. (2008). Perceived Shape Similarity among Unfamiliar

Objects and the Organization of the Human Object Vision Pathway. *Journal of Neuroscience*,

28(40), 10111–10123. https://doi.org/10.1523/JNEUROSCI.2511-08.2008

Petry, H. M., & Bickford, M. E. (2019). The Second Visual System of The Tree Shrew. *Journal of*

Comparative Neurology, *527*(3), 679–693. https://doi.org/10.1002/cne.24413

Petry, H. M., Clark, C., Day-Brown, J., Bolin, R. T., & Bickford, M. (2012). Behavioral measurement of

RDK velocity discrimination thresholds in the tree shrew. *Journal of Vision*, *12*(9), 1223.

https://doi.org/10.1167/12.9.1223

Pinto, N., Cox, D. D., & DiCarlo, J. J. (2008). Why is Real-World Visual Object Recognition Hard? *PLOS*

Computational Biology, *4*(1), e27. https://doi.org/10.1371/journal.pcbi.0040027

Pospisil, D. A., Pasupathy, A., & Bair, W. (2018). "Artiphysiology" reveals V4-like shape tuning in a

deep   network   trained   for   image   classification.   *ELife*,   *7*,   e38242.

https://doi.org/10.7554/eLife.38242

Schnell, A. E., Bergh, G. V. den, Vermaercke, B., Gijbels, K., Bossens, C., & Op de Beeck, H. (2019).

Face categorization and behavioral templates in rats. *Journal of Vision*, *19*(14), 9–9.

https://doi.org/10.1167/19.14.9

Schnell, A. E., Vinken, K., & Op de Beeck, H. (2023). The importance of contrast features in rat vision.

Scientific Reports, *13*(1), Article 1. https://doi.org/10.1038/s41598-023-27533-3

Sinha, P. (2002). Qualitative Representations for Recognition. In H. H. Bülthoff, C. Wallraven, S.-W.

Lee, & T. A. Poggio (Eds.), *Biologically Motivated Computer Vision* (pp. 249–262). Springer.

https://doi.org/10.1007/3-540-36181-2_25

Tafazoli, S., Filippo, A. D., & Zoccolan, D. (2012). Transformation-Tolerant Object Recognition in Rats

Revealed by Visual Priming. *Journal of Neuroscience*, *32*(1), 21–34.

https://doi.org/10.1523/JNEUROSCI.3932-11.2012

Tafazoli, S., Safaai, H., De Franceschi, G., Rosselli, F. B., Vanzella, W., Riggi, M., Buffolo, F., Panzeri, S.,

& Zoccolan, D. (2017). Emergence of transformation-tolerant representations of visual

objects in rat lateral extrastriate cortex. *ELife*, *6*, e22794.

https://doi.org/10.7554/eLife.22794

Vermaercke, B., Gerich, F. J., Ytebrouck, E., Arckens, L., Op de Beeck, H. P., & Van den Bergh, G.

(2014). Functional specialization in rat occipital and temporal visual cortex. *Journal of*

Neurophysiology, *112*(8), 1963–1983. https://doi.org/10.1152/jn.00737.2013

Vermaercke, B., & Op de Beeck, H. P. (2012). A Multivariate Approach Reveals the Behavioral

Templates Underlying Visual Discrimination in Rats. *Current Biology*, *22*(1), 50–55.

https://doi.org/10.1016/j.cub.2011.11.041

Vinken, K., & Op de Beeck, H. (2021). Using deep neural networks to evaluate object vision tasks in

rats. *PLOS Computational Biology*, *17*(3), e1008714.

https://doi.org/10.1371/journal.pcbi.1008714

Vinken, K., Van den Bergh, G., Vermaercke, B., & Op de Beeck, H. P. (2016). Neural Representations

of Natural and Scrambled Movies Progressively Change from Rat Striate to Temporal Cortex.

Cerebral Cortex, *26*(7), 3310–3322. https://doi.org/10.1093/cercor/bhw111

Vinken, K., Vermaercke, B., & Op de Beeck, H. (2014). Visual Categorization of Natural Movies by

Rats. *Journal of Neuroscience*, *34*(32), 10645–10658.

https://doi.org/10.1523/JNEUROSCI.3663-13.2014

Yue, X., Cassidy, B. S., Devaney, K. J., Holt, D. J., & Tootell, R. B. H. (2011). Lower-Level Stimulus

Features Strongly Influence Responses in the Fusiform Face Area. *Cerebral Cortex*, *21*(1), 35–

47. https://doi.org/10.1093/cercor/bhq050

Zeman, A. A., Ritchie, J. B., Bracci, S., & Op de Beeck, H. (2020). Orthogonal Representations of Object

Shape and Category in Deep Convolutional Neural Networks and Human Visual Cortex.

Scientific Reports, *10*(1), Article 1. https://doi.org/10.1038/s41598-020-59175-0

Zoccolan, D. (2015). Invariant visual object recognition and shape processing in rats. *Behavioural*

Brain Research, *285*, 10–33. https://doi.org/10.1016/j.bbr.2014.12.053

Zoccolan, D., Oertelt, N., DiCarlo, J. J., & Cox, D. D. (2009). A rodent model for the study of invariant

visual object recognition. *Proceedings of the National Academy of Sciences*, *106*(21), 8748–

8753. https://doi.org/10.1073/pnas.0811583106

Supplementary

Information about the pilot study

The goal of the pilot was to adjust the range of the two dimensions (concavity and alignment) in order to assure that the animals would use the two dimensions. Using the large stimulus set described in the previous paragraph, we tested a subset of them in a behavioural categorization experiment with two rats. This pilot study consisted of seven phases (see Supplemental Figure 6 for an overview). We started by training rats in a base pair. This pair consists of a target and distractor that are maximally different in terms of concavity and alignment, and thus are placed at the very corners of the 4x11 stimulus grid. After *Training*, we tested them in a *Dimension learning* protocol, to investigate whether the animals use both dimensions (concavity and alignment) in this discrimination task. A total of two pairs were presented to the animals. One pair consisted of the original, base pair, whereas the other pair consisted of stimuli where the alignment dimension was the opposite as in the base pair. In the third phase, *Push towards concavity,* we pushed the animals to learn the concavity dimension. A total of three pairs were presented to the animals. One pair consisted of the original training pair, whereas for the other two stimulus pairs the target and distractor differed in only one of the two dimensions, that is either concavity or alignment. The fourth pilot phase (*Push towards concavity, only new)* consisted of only the two new pairs where the target and distractor differ in only one dimension. A next phase (*More pronounced dimensions)* included stimuli where the concavity dimension was more pronounced than the base pair we started with. We changed the concavity parameter, and again the target and distractor differed in only one dimension. The sixth phase was identical to the *Dimension learning* phase, i.e. checking whether the animals use both dimensions, but this time we used the stimuli where the concavity dimension was more pronounced. In the final phase, we decided to show all four possible combinations of the stimuli.

Tables

838   **Supplemental Table 1 Average number of trials (SD) per test protocol and also per stimulus pair (SP).** In the second

839   column, the average number of trials per stimulus pair, for all rats together, are indicated with the standard deviation

840   between brackets. The third column shows the total number of trials per test protocol. The fourth and fifth columns

841   indicate the same data but for the human participants.

Protocol	Rats		Humans	
	Ø # trials per SP (SD)	Total # trials	Ø # trials per SP (SD)	Total # trials
Rotation X	87.50 (± 9.66)	3150	111.11 (± 2.55)	4000
Rotation Y	88.22 (± 8.90)	3176	111.11 (± 2.44)	4000
Rotation Z	88.25 (± 9.55)	3177	111.11 (± 3.01)	4000
Light location	94.00 (± 11.35)	1504	125 (± 3.72)	2000
Size	205.75 (± 194.86)	823	250 (± 3.16)	1000
Position	91.28 (± 9.06)	2282	120 (± 3.45)	3000
Combination rotation	122.81 (± 12.06)	4421	111.11 (± 3.45)	4000
Zero vs. high	95.53 (± 8.76)	4681	122.45 (± 4.07)	6000
High vs. zero	109.92 (± 10.85)	5386	122.45 (± 4.00)	6000

844   **Supplemental Table 2 The two criteria of choosing a CNN-informed stimulus set.** We calculated the standard deviation for

845   the early layers and the higher layers. Based on their standard deviation, we then filtered the data and ensured that we had

846   enough pairs per criterion.

Criterion	Early layers	Higher layers	# pairs found
1	Close to zero [-0.4*sd … 0.4*sd]	Very high > 3*sd	22
2	Very high > 3*sd	Close to zero [-0.4*sd … 0.4*sd]	26

849 **Supplemental Table 3 Overview of the human experiment.** The left table indicates the number of trials for each training

850 protocol. Note that for the first two phases the participants stayed in these protocols until they reached a performance of

851 80% or higher on the last 20 trials. The number of trials in the testing protocol is proportional to the number of pairs tested

852 per protocol.

Training protocol	# trials
Shaping	80% performance or higher in the last 20 trials
Training	80% performance or higher in the last 40 trials
Dimension learning	80
Transformations	100
Dimension learning (extra)	20

Testing protocol	# trials
Size	20
Position	60
Light location	40
Rotation X	80
Rotation Y	80
Rotation Z	80
Combination rotation	80
Zero vs. high	120
High vs. zero	120

856 **Supplemental Table 4 An overview of the performance of the animals on the first six test protocols.** The second column

857 indicates the planned number of sessions per animal, and between brackets the average number of sessions per animal.

858 We excluded some sessions if the performance on the old stimuli of that session was too low. The third and fourth column

859 provides an overview of the average performance on the old and new pairs, respectively, with the total number of trials for

860 all rats together between brackets. We excluded the correction trials in the analysis of the old pairs. For the new pairs, no

861 correction trials were given and reward in 80% of the trials was given.

Test protocol	Planned # of sessions / animal (average # sessions / animal)	Mean performance on old stimuli (# old trials)	Mean performance on all new trials (# new trials)
Rotation (x-axis)	4 (3.50)	79.39% (1922)	56.49% (3083)
Rotation (y-axis)	4 (3.92)	75.86% (2138)	66.49% (3246)
Rotation (z-axis)	4 (3.83)	79.85% (2092)	63.33% (3315)
Light location	2 (1.92)	79.56% (1043)	72.95% (1645)
Size	1 (1.00)	82.73% (546)	63.49% (895)
Position	3 (2.83)	76.44% (1593)	64.65% (2423)

862

863 **Supplemental Table 5 Results of binomial test on the six test protocols with the pooled data of all animals together, on**

864 **the old trials (upper table) and new trials (lower table).** Here we test whether the average performance of all animals

865 together differs significantly from chance level (indicated by *p-value (50%)*) or 80% (indicated by *p-value (80%)*) on both the

866 old trials (upper table) as well as new trials (lower table).

Test protocol	Mean % (old trials)	p-value (80%)	95% CI
Rotation (x-axis)	79.39%	0.50	[0.78;0.81]
Rotation (y-axis)	75.86%	< .0001	[0.74;0.78]
Rotation (z-axis)	79.85%	0.87	[0.78;0.82]
Light location	79.56%	0.74	[0.77;082]
Size	82.73%	0.13	[0.79;0.86]
Position	76.44%	< .0001	[0.74;0.79]

Test protocol	Mean % (new trials)	p-value (80%?)	p-value (50%?)	95% CI
Rotation (x-axis)	56.49%	< 0.0001	< 0.0001	[0.55;0.58]
Rotation (y-axis)	66.49%	< .0001	< 0.0001	[0.65;0.68]
Rotation (z-axis)	63.33%	< 0.0001	< 0.0001	[0.62;0.65]
Light location	72.95%	< 0.0001	< 0.0001	[0.71;0.75]
Size	63.49%	< .0001	< 0.0001	[0.57;0.64]
Position	64.65%	< .0001	< 0.0001	[0.63;0.67]

869   **Supplemental Table 6 Marginal means and standard deviation of the *Rotation X* and *Rotation Z* protocols.**

Rotation X	Target	56.06 ± 8.54	56.60 ± 3.73	59.70 ± 5.01	55.66 ± 6.87	55.53 ± 9.54	55.37 ± 5.71
	Distractor	64.98 ± 2.12	59.21 ± 6.15	55.07 ± 5.64	52.05 ± 5.64	56.04 ± 5.81	51.55 ± 4.35
Rotation Z	Target	65.40 ± 9.54	63.42 ± 6.03	62.88 ± 10.66	60.20 ± 8.48	62.58 ± 6.78	65.52 ± 6.91
	Distractor	72.69 ± 4.47	68.25 ± 3.97	65.31 ± 6.27	60.27 ± 5.65	57.83 ± 6.83	55.64 ± 4.38

871   **Supplemental Table 7 Correlation between neighbouring layers of the deep neural network.**

Layers	Correlation
1-2	0.11
2-3	-0.13
3-4	0.05
4-5	0.09
5-6	0.12
6-7	0.04
7-8	0.17
8-9	0.06
9-10	0.01
10-11	0.003
11-12	0.11
12-13	0.12

873   **Supplemental Table 8 Results of the linear regression model with rat performances.** A linear regression was calculated

874   with the Classification Scores of the 13 layers as predictors and the rat performances as response vector. Each row indicates

875   one predictor, i.e. one layer, the middle and right column indicate the t-statistic and p-value of the associated predictor,

876   respectively.

Predictor	T statistic	p-value
(Intercept)	82.15	< 0.0001
Layer 1	1.19	0.23
Layer 2	0.56	0.57
Layer 3	0.91	0.37
Layer 4	0.52	0.60
Layer 5	-0.28	0.78
Layer 6	1.38	0.17
Layer 7	0.59	0.55
Layer 8	2.26	0.025
Layer 9	2.00	0.047
Layer 10	2.35	0.019
Layer 11	-0.46	0.64
Layer 12	-0.82	0.41
Layer 13	1.38	0.17

879   **Supplemental Table 9 Results of the linear regression model with human performances.** A linear regression was

880   calculated with the Classification Scores of the 13 layers as predictors and the human performances as response vector.

881   Each row indicates one predictor, i.e. one layer, the middle and right column indicate the t-statistic and p-value of the

882   associated predictor, respectively.

Predictor	T statistic	p-value
(Intercept)	145.94	< 0.0001
Layer 1	0.63	0.53
Layer 2	-1.82	0.07
Layer 3	0.61	0.54
Layer 4	1.40	0.16
Layer 5	1.61	0.11
Layer 6	-1.23	0.22
Layer 7	0.14	0.89
Layer 8	0.62	0.54
Layer 9	0.80	0.43
Layer 10	1.18	0.24
Layer 11	2.90	< 0.01
Layer 12	5.08	< 0.0001
Layer 13	4.72	< 0.0001

885 Figures

(a) Correct trial

(b) Incorrect trial

(c) Experimental setup

887 **Supplemental Figure 1** Timeline of a correct trial (a) and an incorrect trial (b). In case of a correct trial, animals receive a
888 reward in the form of sugar pellets for touching the target. If they answer incorrectly, they do not receive sugar pellets but
889 instead the house light is turned on. For training protocols, a correction trial is added.(c) shows images of the experimental
890 setup.

Supplemental Figure 2 Individual rat accuracy for each testing protocol. The black circle indicates the average accuracy

across all rats together. Each coloured cross represents the accuracy of one rat.

Supplemental Figure 3 Illustration of the 4x11 stimulus grid. We chose eleven values for concavity, ranging between -0.5 and 0.8, and four values for alignment, ranging between 0 and 1.

Supplemental Figure 4 The pixel dissimilarity matrix of the 4x11 stimulus grid. This matrix is calculated in the exact same way as *(Schnell et al., 2023)*. The colourbar indicates pixel dissimilarity values, normalized between 0 and 100. The higher this value, and thus the more red a cell, the more dissimilar two stimuli are. The naming convention of the stimuli is as follows: XX-alYYsmZZZ.png where XX is an ordering number, YY indicates the alignment level and ZZZ indicates the concavity (smoothness) level.

Rotation (x-axis)

Rotation (y-axis)

Rotation (z-axis)

Light location

Combination of
transformations

Supplemental Figure 5 Identity-preserving transformations on one of the basic stimuli. (a), (b) and (c) show the rotation

along the x-axis, y-axis and z-axis respectively, always in angles of 30°, 60°, 90°, 120°, 150°, and 180°. (d) illustrates the light

location transformation. (e) shows some combinations of transformations, with different values for the alignment and

concavity parameter.

Supplemental Figure 6 Design of the pilot study.

Supplemental Figure 7 Design of the online human study. The design of the human study resembles the design of the

animal study, with minor adaptions. We removed the 1/3[rd] old trials in the test protocols, but included two additional

Dimension Learning protocols.