A machine-readable specification for genomics assays

A. Sina Booeshaghi[1*], Xi Chen[2], and Lior Pachter[1,3*]

1. Division of Biology and Biological Engineering, California Institute of Technology, Pasadena, California
2. School of Life Sciences, Southern University of Science and Technology, Shenzhen, China
3. Department of Computing and Mathematical Sciences, California Institute of Technology, Pasadena, California

*Address correspondence to abooesha@caltech.edu & lpachter@caltech.edu

Abstract

Understanding the structure of sequenced fragments from genomics libraries is essential for accurate read preprocessing. Currently, different assays and sequencing technologies require custom scripts and programs that do not leverage the common structure of sequence elements present in genomics libraries. We present *seqspec,* a machine-readable specification for libraries produced by genomics assays that facilitates standardization of preprocessing and enables tracking and comparison of genomics assays. The specification and associated *seqspec* command line tool is available at https://github.com/IGVF/seqspec.

Introduction

The proliferation of genomics assays (Ogbeide et al. 2022) has resulted in a corresponding increase in software for processing the data (Zappia, Phipson, and Oshlack 2018). Frequently, custom scripts must be created and tailored to the specifics of assays, where developers reimplement solutions for common preprocessing tasks such as adapter trimming, barcode identification, error correction, and read alignment (Wu et al. 2022; Ma et al. 2020; Cheow et al. 2016; Healey, Bassham, and Cresko 2022). When software tools are assay specific, parameter choices in these methods can diverge, making it difficult to perform apples-to-apples comparisons of data produced by different assays. Furthermore, the lack of preprocessing standardization makes reanalysis of published data in the context of new data challenging.

While genomics protocols can vary greatly from each other, the libraries they generate share many common elements. Typically, sequenced fragments will contain one or several "technical sequences" such as barcodes and unique molecular identifiers (UMIs), as well as biological sequences that may be aligned to a genome or transcriptome. Standard library preparation kits generally require that DNA from the libraries is cut, repaired, and ligated to sequencing adapters (Figure 1). Primers bind to the sequencing adapters, and initiate DNA sequencing whereby reads are subsequently generated. Illumina sequencing employs a sequencing by synthesis approach where fluorescently labeled nucleotides are incorporated into single-stranded DNA, and imaged, while PacBio uses zero-mode waveguides for single-molecule detection of dNTP incorporation. Oxford Nanopore on the other hand binds sequencing adapters to pores in a flow cell and DNA is sequenced by changes in electrical resistance across the pore (Iizuka, Yamazaki, and Uemura 2022).

Figure 1: The structure of reads sequenced from genomics libraries. Sequencing libraries are constructed by combining Atomic *Regions* to form an adapter-insert-adapter construct. The *seqspec* for the assay annotates the construct with *Regions* and *Meta Regions.*

Many single-cell genomics assays introduce additional library complexity further complicating preprocessing. For example, the inDropsv3 (Klein et al. 2015) assay produces variable length barcodes while the 10x Genomics scRNA-seq assay (Zheng et al. 2017) produces fixed-length barcodes that are derived from a known list of possibilities.

Current file formats such as FASTQ, Genbank, FASTA, and workflow-specific files (Parekh et al. 2018) lack the flexibility to annotate sequenced reads that contain these complex features. In the absence of sequence annotations, processing can be challenging, limiting the reuse of data that is stored in publicly accessible databases such as the Sequence Read Archive (Katz et al. 2022). To facilitate utilization of genomics data, a database of assays along with a description of their associated library structures was assembled in (Chen 2020). While this database has proved to be very useful, the HTML descriptors are not machine readable. Moreover, the lack of a formal specification limits the utility and expandability of the database.

Results

The *seqspec* specification defines a machine-readable file format, based on YAML, that enables sequence read annotation. Reads are annotated by *Regions* which can be nested and appended to create a *seqspec*. *Regions* are annotated with a variety of properties that simplify the downstream identification of sequenced elements. The following are a list of properties that can be associated with a *Region*:

- Region ID: unique identifier for the *Region* in the *seqspec*
- Region type: the type of region
- Name: A descriptive name for the *Region*
- Sequence: The specific nucleotide sequence for the *Region*
- Sequence type: The type of sequence (fixed, onlist, random, joined)
- Minimum length: The minimum length of the sequence for the *Region*
- Maximum length: The maximum length of the sequence for the *Region*
- Onlist: The list of permissible sequences from which the Sequence is derived

Importantly, *Regions*, known as meta *Regions*, can contain *Regions*; a property that is useful for grouping and identifying sequence types that are contained in reads. The YAML format is a natural language to represent nested meta-*Regions* in a human-readable fashion. Python-style indentation and syntax can be used to create a human-readable file format without the excessive grouping delimiters of alternative languages such as JSON. Additionally, nested *Regions* allow Assays to be represented as an Ordered Tree where the ordering of subtrees is significant: atomic *Regions* are "glued" together in an order that is concordant with the design of the sequencing library.

Importantly, *seqspec* files are machine-readable, and *Region* data can be parsed, processed, and extracted with the *seqspec* command-line tool. The tool contains six subcommands that enable various tasks such as specification checking, finding, formatting, and indexing,

1. *seqspec check*: check the correctness of attributes against the *seqspec* shema
2. *seqspec find*: print *Region* metadata
3. *seqspec format*: auto populate *Region* metadata for meta *Regions*
4. *seqspec index*: extract the 0-indexed position of *Regions*
5. *seqspec print*: print an html or markdown file that visualizes the *seqspec*
6. *seqspec split*: split a FASTQ file by *Regions*

```
# kb-python
kb count \
    -i index.idx -g t2g.txt \
    -x $(seqspec index -t kb -m RNA -r R1.fastq.gz,R2.fastq.gz spec.yaml) \
    -o out/ -w onlist.txt R1.fastq.gz R2.fastq.gz

# simpleaf
simpleaf quant -r cr-like \
    -i index/ -m t2g.txt \
    -c $(seqspec index -t simpleaf -m RNA -r R1.fastq.gz,R2.fastq.gz spec.yaml) \
    -o out/ -x onlist.txt -1 R1.fastq.gz -2 R2.fastq.gz

# STARsolo
star --soloFeatures Gene \
    --genomeDir index --soloType Droplet --soloCBwhitelist onlist.txt \
    $(seqspec index -t starsolo -m RNA -r R1.fastq.gz,R2.fastq.gz spec.yaml) \
    --readFilesCommand zcat --readFilesIn R1.fastq.gz R2.fastq.gz
```

Figure 2: Uniform processing enabled with *seqspec*. The *seqspec index* command produces a technology string that identifies appropriate sequence elements and can be passed into processing tools.

To illustrate how *seqspec* can be used to facilitate processing and analysis of single-cell RNA-seq reads, we implemented in the *seqspec index* command the facility to produce the relevant technology string for three single-cell RNA-seq preprocessing tools: kallisto bustools (Melsted et al. 2021), simpleaf/alevin-fry (He et al. 2022), and STARsolo (Kaminow, Yunusov, and Dobin 2021) (Figure 2). *Regions* associated with barcodes, UMIs, and cDNA are extracted, positionally indexed and formatted on a per-tool basis. The modularity of *seqspec* makes it simple to produce tool-compatible technology strings for other assay types.

Discussion

Standardized annotation of sequencing reads in a human- and machine-readable format serves several purposes including the enablement of uniform processing, organization of sequencing assays by constitutive components, and transparency for users. The flexibility of *seqspec* should allow it to be used for all current sequence census assays (Wold and Myers 2008), and specifications should be readily adaptable to different sequencing platforms; our initial release of *seqspec* contains specifications for 38 assays (see https://igvf.github.io/seqspec/).

Comparison of *seqspec*s for different assays, immediately reveals shared similarities and differences. For example, the SPLiT-seq single-cell RNA and the multimodal SHARE-seq single-cell assays are aimed at different modalities and utilize different protocols to produce libraries, but the resultant structures are very similar (Figure 1) since they both rely on split-pool barcoding (Rosenberg et al. 2018). The *seqspec* for the sci-CAR-seq assay (Cao et al. 2018), from which split-pool assays such as SHARE-seq are derived, shows that the cell barcoding is encoded in the Illumina indices. It should be possible to develop an ontology of assays by comparing the *seqspec* specifications of assays and quantifying their similarities and differences.

In demonstrating that *seqspec* can be used to define options for preprocessing tools, we have shown that *seqspec* is immediately useful for uniform processing of genomics data. The preprocessing applications will hopefully incentivize data generators to define and deposit *seqspec* files alongside sequencing reads in public archives such as the Sequence Read Archive. While *seqspec* is not a suitable format for general metadata storage, the precise specification of sequence elements present in reads, including sequencer-specific constructs, should be helpful in identifying batch effects even when metadata is missing or inaccurate.

Acknowledgements

We thank Delaney Sullivan for helpful discussions and Rahma Elsiesy for helpful feedback on Figure 1. Discussions with the Impact of Genomics Variation on Function (IGVF) Single-Cell Focus Group helped to shape some features of *seqspec*. Thanks to Idan Gabdank for useful feedback on *seqspec* and for suggesting the md5 checksum. Meichen Fang contributed the sci-RNA-seq3 *seqspec*. A.S.B. and L.P. were supported in part by NIH 5UM1HG012077-02.

References

Cao, Junyue, Darren A. Cusanovich, Vijay Ramani, Delasa Aghamirzaie, Hannah A. Pliner, Andrew J. Hill, Riza M. Daza, et al. 2018. "Joint Profiling of Chromatin Accessibility and Gene Expression in Thousands of Single Cells." *Science* 361 (6409): 1380–85.

Chen, Xi. 2020. *Collections of Library Structure and Sequence of Popular Single Cell Genomic Methods*. Github. https://github.com/Teichlab/scg_lib_structs.

Cheow, Lih Feng, Elise T. Courtois, Yuliana Tan, Ramya Viswanathan, Qiaorui Xing, Rui Zhen Tan, Daniel S. W. Tan, et al. 2016. "Single-Cell Multimodal Profiling Reveals Cellular Epigenetic Heterogeneity." *Nature Methods* 13 (10): 833–36.

Healey, Hope M., Susan Bassham, and William A. Cresko. 2022. "Single-Cell Iso-Sequencing Enables Rapid Genome Annotation for scRNAseq Analysis." *Genetics* 220 (3). https://doi.org/10.1093/genetics/iyac017.

He, Dongze, Mohsen Zakeri, Hirak Sarkar, Charlotte Soneson, Avi Srivastava, and Rob Patro. 2022. "Alevin-Fry Unlocks Rapid, Accurate and Memory-Frugal Quantification of Single-Cell RNA-Seq Data." *Nature Methods* 19 (3): 316–22.

Iizuka, Ryo, Hirohito Yamazaki, and Sotaro Uemura. 2022. "Zero-Mode Waveguides and Nanopore-Based Sequencing Technologies Accelerate Single-Molecule Studies." *Biophysics and Physicobiology* 19 (August): e190032.

Kaminow, Benjamin, Dinar Yunusov, and Alexander Dobin. 2021. "STARsolo: Accurate, Fast and Versatile Mapping/quantification of Single-Cell and Single-Nucleus RNA-Seq Data." *bioRxiv*. https://doi.org/10.1101/2021.05.05.442755.

Katz, Kenneth, Oleg Shutov, Richard Lapoint, Michael Kimelman, J. Rodney Brister, and Christopher O'Sullivan. 2022. "The Sequence Read Archive: A Decade More of Explosive Growth." *Nucleic Acids Research* 50 (D1): D387–90.

Klein, Allon M., Linas Mazutis, Ilke Akartuna, Naren Tallapragada, Adrian Veres, Victor Li, Leonid Peshkin, David A. Weitz, and Marc W. Kirschner. 2015. "Droplet Barcoding for Single-Cell Transcriptomics Applied to Embryonic Stem Cells." *Cell* 161 (5): 1187–1201.

Ma, Sai, Bing Zhang, Lindsay M. LaFave, Andrew S. Earl, Zachary Chiang, Yan Hu, Jiarui Ding, et al. 2020. "Chromatin Potential Identified by Shared Single-Cell Profiling of RNA and Chromatin." *Cell* 183 (4): 1103–16.e20.

Melsted, Páll, A. Sina Booeshaghi, Lauren Liu, Fan Gao, Lambda Lu, Kyung Hoi Joseph Min, Eduardo da Veiga Beltrame, Kristján Eldjárn Hjörleifsson, Jase Gehring, and Lior Pachter. 2021. "Modular, Efficient and Constant-Memory Single-Cell RNA-Seq Preprocessing."

Nature Biotechnology 39 (7): 813–18.

Ogbeide, Silvia, Francesca Giannese, Laura Mincarelli, and Iain C. Macaulay. 2022. "Into the Multiverse: Advances in Single-Cell Multiomic Profiling." *Trends in Genetics: TIG* 38 (8): 831–43.

Parekh, Swati, Christoph Ziegenhain, Beate Vieth, Wolfgang Enard, and Ines Hellmann. 2018. "zUMIs - A Fast and Flexible Pipeline to Process RNA Sequencing Data with UMIs." *GigaScience* 7 (6). https://doi.org/10.1093/gigascience/giy059.

Rosenberg, Alexander B., Charles M. Roco, Richard A. Muscat, Anna Kuchina, Paul Sample, Zizhen Yao, Lucas T. Graybuck, et al. 2018. "Single-Cell Profiling of the Developing Mouse Brain and Spinal Cord with Split-Pool Barcoding." *Science* 360 (6385): 176–82.

Wold, Barbara, and Richard M. Myers. 2008. "Sequence Census Methods for Functional Genomics." *Nature Methods* 5 (1): 19–21.

Wu, Honggui, Xiang Li, Fanchong Jian, Ayijiang Yisimayi, Yinghui Zheng, Longzhi Tan, Dong Xing, and X. Sunney Xie. 2022. "Highly Sensitive Single-Cell Chromatin Accessibility Assay and Transcriptome Coassay with METATAC." *Proceedings of the National Academy of Sciences of the United States of America* 119 (40): e2206450119.

Zappia, Luke, Belinda Phipson, and Alicia Oshlack. 2018. "Exploring the Single-Cell RNA-Seq Analysis Landscape with the scRNA-Tools Database." *PLoS Computational Biology* 14 (6): e1006245.

Zheng, Grace X. Y., Jessica M. Terry, Phillip Belgrader, Paul Ryvkin, Zachary W. Bent, Ryan Wilson, Solongo B. Ziraldo, et al. 2017. "Massively Parallel Digital Transcriptional Profiling of Single Cells." *Nature Communications* 8 (January): 14049.