`escheR`: Unified multi-dimensional visualizations with Gestalt principles

Boyi Guo[1] and Stephanie C. Hicks[*1,2]

[1]Department of Biostatistics, Johns Hopkins Bloomberg School of Public Health, MD, USA, [2]Malone Center for Engineering in Healthcare, Johns Hopkins University, MD, USA

March 19, 2023

Abstract

The creation of effective visualizations is a fundamental component of data analysis. In biomedical research, new challenges are emerging to visualize multi-dimensional data in a 2D space, but current data visualization tools have limited capabilities. To address this problem, we leverage Gestalt principles to improve the design and interpretability of multi-dimensional data in 2D data visualizations, layering aesthetics to display multiple variables. The proposed visualization can be applied to spatially-resolved transcriptomics data, but also broadly to data visualized in 2D space, such as embedding visualizations. We provide an open source R package `escheR`, which is built off of the state-of-the-art `ggplot2` visualization framework and can be seamlessly integrated into genomics toolboxes and workflows.

Availability and implementation

The open source R package `escheR` is freely available on GitHub and is being submitted to Bioconductor (https://github.com/boyiguo1/escheR).

1 Introduction

Visualization is an indispensable component of data analysis, providing clarity that connects quantitative evidence to key conclusions [1]. In biomedical research, visualization receives growing recognition as essential: many scientists rely on visualization to complete their cognitive process from analysis to insight, including analytic validation of automated pipelines and scientific communication [2]. However, an important challenge in biomedical research is how to visualize increasingly complex, multi-dimensional data [3].

Here, we focus on two types of visualizations in biomedical research, but note that the proposed ideas could be extended beyond these applications: (i) embedding visualizations, which project data into some low-dimensional embedding or mathematical space (e.g. Principal Components Analysis (PCA) [4], t-distributed Stochastic Neighbor Embedding (t-SNE) [5], or Uniform Manifold Approximation and Projection (UMAP) [6]) and (ii) *in situ* visualizations [2, 7, 8], which aim to visualize molecules captured from *in situ* imaging or sequencing technologies where *in situ* refers to 'in its original place'. Both of these visualizations represent data in a 2D space and are motivated by recent advances in experimental technologies that profile molecules, including DNA, RNA, and proteins, at a single-cell or spatial resolution [9, 10]. Some most popular technologies include single-cell/nucleus RNA-sequencing (sc/snRNA-seq) [11] and *in situ* spatially-resolved transcriptomics [12].

A common and fundamental challenge with both of these visualizations is how to visualize multi-dimensional information in a 2D space. For example, in *in situ* visualizations, we often want to create a spatial map to visualize a continuous (e.g. gene expression) or discrete (e.g. cell type or spatial domain) variable representing molecular information in the original spatial location. However, it is challenging to simultaneously visualize multi-dimensional data, such as information from disparate data domains (such as expression domain and spatial domain) or disparate data modalities (such as transcriptomics and proteomics) in the same plot. Currently, best practices for this include making two different plots displayed side-by-side (**Figure 1A-B**), one for gene expression and one for spatial domains. This creates cognitive gaps on how to associate the disparate information or how to interpret the biological findings of this multi-dimensional information regarding their (micro-)environment or colocalization. While interactive visualizations [13–15] have the potential to mitigate this challenge, they are infeasible for scientific communications in static media, such as printed work. Developing a static and unified visualization that enables the simultaneous display of multiple dimensions of information is crucial for biomedical research.

2 Results

To address these challenges, here we leverage the Gestalt (German for "unified whole") principles for design [17, 18] as a way to visualize multi-dimensional data in 2D visualizations. We focus on the two types of data visualizations previously introduced that are widely used in biomedical research: (i) embedding visualizations and (ii) *in situ* visualizations. We provide an R package, `escheR`, implementing these ideas, which is built on the state-of-the-art data visualization framework `ggplot2` in the R programming language.

---

*Correspondence to shicks19@jhu.edu

Figure 1: **escheR enables multi-dimensional spatial visualizations following the Gestalt principles of design**. (**A-B**) The traditional visualization displays the colocalization plot of the expression of two genes *EFNA5* and EPHA5 (**A**) and the spatial domains from the dorsolateral prefrontal cortex (DLPFC) in postmorteum human brain [16] (**B**) side-by-side, creating challenges to cognitively connecting colocalization status to spatial domains. (**C**) The watercolor effect enables displaying spatial domains by color-coding only outlines of circles. (**D**) escheR enables the multi-dimensional *in situ* visualization that simultaneously displays the cortex layers and the colocalization status, substantially improving interpretability.

Finally, we comment on how these ideas could be extended to other types of visualization in biomedical research.

2.1 Multi-dimensional 2D visualizations with ggplot2 and Gestalt principles

Gestalt principles [17, 18] refer to a set of rules describing how humans perceive and interpret visual information and are commonly applied in art and designs. Developed in the 1920s by German psychologists Max Wertheimer, Kurt Koffka and Wolfgang Kohler, these principles help humans perceive a set of individual elements as a whole.

Here, we leverage the principles to be able to visualize multi-dimensional data in a unified 2D plot. Our approach is to use the state-of-art data visualization framework `ggplot2` [19] following the Grammar of Graphics [20] and map individual variables to different aesthetics to simultaneously display disparate variables. Specifically, we apply the figure-ground segmentation [21] in displaying two variables: one variable (e.g. expression) can be plotted as color-filled circles, serving as the *figure*; one variable (e.g. spatial domains) can be plotted as the backgrounds of the circles, creating a *ground* for the figure. In practice, we use the combination of `color` and `fill="transparent"` to create the background layer and `fill` to create the figure layer.

When necessary to display an additional layer for a third variable, `shape` can be used to add symbols such as cross (+) and asterisk (*) to highlight in the spatial map.

For adjacent circles with limited space between them to display the background color, we use an economic implementation, colored outlines for these circles (**Figure 1C**), inspired by watercolor effect [22, 23]. Watercolor effect describes the phenomenon in visual perception that surface color arises from thin boundaries and hence is applied here to perceive the background color in tight space. Overall, the figure-ground segmentation creates two isolated layers in visual perception to display the two variables while maintaining the relative spatial relationship serving as a reference between the two. In addition, other fundamental principles [17], such as proximity, similarity, continuity, and closure, incentivize the brain to group elements and dimensions in the visualization, guaranteeing an integrative perception of the complex multi-dimensional spatial map.

Here, we provide an open-source package called `escheR` (named after the graphic artist M.C. Escher) in the R programming language [24], leading to a simplified interface to navigate the implementation of the multi-dimensional visualization in 2D space. By adapting `ggplot2` standard, `escheR` can be seamlessly integrated into many popular spatial resolved toolboxes, such as `SpatialLIBD`[14],

Seurat[25], Giotto[7] to name a few, and allow further theme customization with ease.

Next, we give two use cases to exemplify some utility of the proposed spatial visualization: (i) the spatially differential gene colocalization in the human dorsolateral prefrontal cortex (DLPFC) using spatial transcriptomics data [16]; (ii) multi-dimensional UMAP highlighting differential gene expression in data-driven cell clusters [26].

2.2 Multi-dimensional *in situ* visualization

In a recent study investigating the molecular organization of human dorsolateral prefrontal cortex [16], two schizophrenia risk genes, membrane-bound ligand ephrin A5 (*EFNA5*) and ephrin type-A receptor 5 (*EPHA5*), were identified to colocalize via cell-cell communication analysis. In addition, data suggested Layer 6 was the most highly co-localized layer compared to other cortex layers. To visually examine the inference, we applied escheR to create a multi-dimensional *in situ* spatial map that simultaneously exhibits the cortex layers (displayed with color-coded spot outlines) and the categorized colocalization status of genes *EFNA5* and *EPHA5* (displayed with color-coded spot fill). Compared to the traditional visualization where the cortex layers and the colocalization status are visualized in two side-by-side figures (**Figure 1A-B**), our proposed visualization (**Figure 1D**) enables directly mapping colocalization status to the spatial domain, simplifying the perception of two sources of information and allowing cognitive comparison across cortex layers.

2.3 Multi-dimensional embedding visualizations

The application of the proposed framework is not limited to *in situ* visualizations of spatially-resolved transcriptomics data. It is broadly applicable to data mapped to any 2-dimensional coordinate system to simultaneously display multiple variables. Such systems include euclidean space (including spatial coordinate as a special case) and data-driven embedding space, for example, UMAP and *t*-SNE. To demonstrate, we applied the proposed visualization to address the challenge of simultaneously displaying cluster membership and gene expression in a single-cell UMAP plot. To address the overplotting problem, previous work proposed to apply hexagonal binning strategy to display the gene expression [26]. Here, the color-coded convex hulls are used to annotate different clusters of cells (**Figure ??A**). However, the convex hulls create substantial overlapping areas, creating confusion when interpreting cluster memberships of hexagons in the overlapping areas. To improve the interpretability of the visualization, we replace the convex hulls with color-coded hexagons boundaries (**Figure ??B**) to avoid possible membership confusion. We note that our contribution to improving the visualization is easily implemented without any modification of schex as both are built upon the Grammar of Graphics [20] standard.

3 Discussion

Here, we propose an innovative multi-dimensional spatial visualization that simultaneously displays multiple variables in a 2D coordinate system. Specifically, our design leverages Gestalt principles from visual perception to create multiple visual dimensions in a spatial map by iterative layering aesthetics. Built upon ggplot2, we provide an open-source R package escheR that is seamlessly compatible with popular spatially-resolved transcriptomics and single-cell data analysis toolboxes.

Adding a third dimension to 2D plots has been a longstanding challenge in visualization [3]. Our proposal addresses this fundamental challenge by introducing simple but effective design principles. Unlike computer-based interactive visualizations, the proposed visualization is free from any platform and technology restriction, creating an accessible and economic solution. In addition, the proposed visualization is easily scalable and hence can be applied to all types of spatially resolved data. Combining with a binning strategy, similar to schex [26], to avoid possible overplotting, the proposed visualization can be also applied to visualized image-based spatially resolved data [27], in addition to aforementioned spot-based spatially resolved data (**Figure 1**).

Beyond the scope of biomedical research, the proposed visualization can be broadly translated to any visual analytic highlighting differentiation with respect to another measurement(s). To name a few, such visual analytics include examining differential tests, explaining clustering, and visualizing subgroups. However, one of the most rewarding fields to apply the proposed visualization is the rapidly expanding field of biomedical multi-omics research [28], where connecting different omics (data modalities) is the fundamental goal and hence greatly appreciating innovative multi-dimensional visualization.

In summary, we propose a novel multi-dimensional visualization, implemented in an R package escheR, to address the simultaneous exhibition of multiple variables in 2D plots. The proposed visualization can be broadly applicable to the visual analytics of growingly complex biomedical data and beyond.

Abbreviations

- **PCA**: principal component analysis
- *t*-**SNE**: *t*-distributed stochastic neighbor embedding
- **UMAP**: uniform manifold approximation and projection
- **scRNA-seq**: single-cell RNA-sequencing
- **snRNA-seq**: single-nucleus RNA-sequencing
- **SRT**: spatially-resolved transcriptomics
- **EFNA5**: membrane-bound ligand ephrin A5
- **EPHA5**: ephrin type-A receptor 5
- **DLPFC**: dorsolateral prefrontal cortex

Author contributions

- **Boyi Guo**: Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Data Curation, Writing, Visualization
- **Stephanie C. Hicks**: Conceptualization, Resources, Writing - Review & Editing, Visualization, Supervision, Project administration, Funding acquisition

Declarations

Ethics approval and consent to participate

Not applicable.

Competing interests

The authors declare that they have no competing interests.

Availability of data and materials

The spatial transcriptomics dataset was obtained from `spatialLIBD` (research.libd.org/spatialLIBD). The UMAP example follows the 'using_schex' vignette in the `schex` package (bioconductor.org/packages/schex). The code that generates these figures is deposited at github.com/boyiguo1/Manuscript_escheR (*v1.0*).

Funding

This project was supported by the National Institute of Mental Health R01MH126393 (BG, SCH), and CZF2019-002443 (SCH) from the Chan Zuckerberg Initiative DAF, an advised fund of Silicon Valley Community Foundation. All funding bodies had no role in the design of the study and collection, analysis, and interpretation of data and in writing the manuscript.

Acknowledgements

BG would like to acknowledge Dr. Leonardo Collado-Torres, Louise Huuki-Myers, Dr. Lukas M. Weber, and Leon Di Stefano for their helpful comments, feedback and suggestions on `escheR` functionality.

Author's information

- Boyi Guo (ORCiD: 0000-0003-2950-2349)
- Stephanie C. Hicks (ORCiD: 0000-0002-7858-0231)

Conflict of Interest

None declared.

References

[1] Lucy D McGowan, Roger D. Peng, and Stephanie C. Hicks. Design principles for data analysis. *Journal of Computational and Graphical Statistics*, pages 1–14, jul 2022. ISSN 1061-8600. doi:10.1080/10618600.2022.2104290. URL https://www.tandfonline.com/doi/full/10.1080/10618600.2022.2104290.

[2] Seán I O'Donoghue. Grand challenges in bioinformatics data visualization. *Frontiers in Bioinformatics*, 1:669186, jun 2021. ISSN 2673-7647. doi:10.3389/fbinf.2021.669186. URL https://www.frontiersin.org/articles/10.3389/fbinf.2021.669186/full.

[3] Seán I O'Donoghue, Anne-Claude Gavin, Nils Gehlenborg, David S Goodsell, Jean-Karim Hériché, Cydney B Nielsen, Chris North, Arthur J Olson, James B Procter, David W Shattuck, Thomas Walter, and Bang Wong. Visualizing biological data-now and in the future. *Nature Methods*, 7(3 Suppl):S2–4, mar 2010. doi:10.1038/nmeth.f.301. URL http://dx.doi.org/10.1038/nmeth.f.301.

[4] Harold Hotelling. Analysis of a complex of statistical variables into principal components. *Journal of educational psychology*, 24(6):417, 1933.

[5] Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-SNE. *Journal of Machine Learning Research*, 2008. URL https://www.jmlr.org/papers/v9/vandermaaten08a.html.

[6] Etienne Becht, Leland McInnes, John Healy, Charles-Antoine Dutertre, Immanuel WH Kwok, Lai Guan Ng, Florent Ginhoux, and Evan W Newell. Dimensionality reduction for visualizing single-cell data using umap. *Nature biotechnology*, 37(1):38–44, 2019.

[7] Ruben Dries, Jiaji Chen, Natalie Del Rossi, Mohammed Muzamil Khan, Adriana Sistig, and Guo-Cheng Yuan. Advances in spatial transcriptomic data analysis. *Genome Research*, 31(10):1706–1718, oct 2021. doi:10.1101/gr.275224.121. URL http://dx.doi.org/10.1101/gr.275224.121.

[8] Sabrina M Lewis, Marie-Liesse Asselin-Labat, Quan Nguyen, Jean Berthelet, Xiao Tan, Verena C Wimmer, Delphine Merino, Kelly L Rogers, and Shalin H Naik. Spatial omics and multiplexed imaging to explore cancer biology. *Nature Methods*, 18(9):997–1012, sep 2021. ISSN 1548-7091. doi:10.1038/s41592-021-01203-6. URL https://www.nature.com/articles/s41592-021-01203-6.

[9] Yukie Kashima, Yoshitaka Sakamoto, Keiya Kaneko, Masahide Seki, Yutaka Suzuki, and Ayako Suzuki. Single-cell sequencing techniques from individual to multiomics analyses. *Experimental & Molecular Medicine*, 52(9):1419–1427, 2020.

[10] Jeffrey R Moffitt, Emma Lundberg, and Holger Heyn. The emerging landscape of spatial profiling technologies. *Nature Reviews. Genetics*, 23(12):741–759, dec 2022. ISSN 1471-0056. doi:10.1038/s41576-022-00515-3. URL https://www.nature.com/articles/s41576-022-00515-3.

[11] Sarah Aldridge and Sarah A Teichmann. Single cell transcriptomics comes of age. *Nature Communications*, 11(1):4307, aug 2020. ISSN 2041-1723. doi:10.1038/s41467-020-18158-5. URL http://www.nature.com/articles/s41467-020-18158-5.

[12] Ludvig Larsson, Jonas Frisén, and Joakim Lundeberg. Spatially resolved transcriptomics adds a new dimension to genomics. *Nature Methods*, 18(1):15–18, jan 2021. ISSN 1548-7091. doi:10.1038/s41592-020-01038-7. URL http://www.nature.com/articles/s41592-020-01038-7.

[13] Mark S Keller, Ilan Gold, Chuck McCallum, Trevor Manz, Peter V Kharchenko, and Nils Gehlenborg. Vitessce: a framework for integrative visualization of multi-modal and spatially-resolved single-cell data. Oct 2021. doi:10.31219/osf.io/y8thv.

[14] Brenda Pardo, Abby Spangler, Lukas M Weber, Stephanie C Page, Stephanie C Hicks, Andrew E Jaffe, Keri Martinowich, Kristen R Maynard, and Leonardo Collado-Torres. spatiallibd: an r/bioconductor package to visualize spatially-resolved transcriptomics data. *BMC genomics*, 23(1):434, 2022.

[15] Chaichontat Sriworarat, Annie Nguyen, Nicholas J Eagles, Leonardo Collado-Torres, Keri Martinowich, Kristen R Maynard, and Stephanie C Hicks. Performant web-based interactive visualization tool for spatially-resolved transcriptomics experiments. *BioRxiv*, jan 2023. doi:10.1101/2023.01.28.525943. URL http://biorxiv.org/lookup/doi/10.1101/2023.01.28.525943.

[16] Louise Huuki-Myers, Abby Spangler, Nick Eagles, Kelsey D Montgomery, Sang Ho Kwon, Boyi Guo, Melissa Grant-Peters, Heena R Divecha, Madhavi Tippani, Chaichontat Sriworarat, Annie B Nguyen, Prashanthi Ravichandran, Matthew N Tran, Arta Seyedian, PsychENCODE consortium, Thomas M Hyde, Joel E Kleinman, Alexis Battle, Stephanie C Page, Mina Ryten, Stephanie C Hicks, Keri Martinowich, Leonardo Collado-Torres, and Kristen R Maynard. Integrated single cell and unsupervised spatial transcriptomic analysis defines molecular anatomy of the human dorsolateral prefrontal cortex. *BioRxiv*, feb 2023. doi:10.1101/2023.02.15.528722. URL http://biorxiv.org/lookup/doi/10.1101/2023.02.15.528722.

[17] Dejan Todorovic. Gestalt principles. *Scholarpedia*, 3(12):5345, 2008. ISSN 1941-6016. doi:10.4249/scholarpedia.5345. URL http://www.scholarpedia.org/article/Gestalt_principles.

[18] Stephen E. Palmer. *Vision Science: Photons to Phenomenology*. The MIT Press, Cambridge, Mass, illustrated edition, 1999. ISBN 9780262161831.

[19] Hadley Wickham. *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York, 2016. ISBN 978-3-319-24277-4. URL https://ggplot2.tidyverse.org.

[20] Leland Wilkinson. *The grammar of graphics*. Springer, 2012.

[21] Mary Peterson and Elizabeth Salvagio. Figure-ground perception. *Scholarpedia*, 5(4):4320, 2010. ISSN 1941-6016. doi:10.4249/scholarpedia.4320. URL http://www.scholarpedia.org/article/Figure-ground_perception.

[22] B Pinna. Un effetto di colorazione. In *Il laboratorio e la città. XXI Congresso degli Psicologi Italiani*, page 158. Edizioni SIPs, Societá Italiana di Psiocologia, Milano, 1987.

[23] Baingio Pinna, Gavin Brelstaff, and Lothar Spillmann. Surface color from boundaries: a new 'watercolor'illusion. *Vision research*, 41(20):2669–2676, 2001.

[24] R Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria, 2022. URL https://www.R-project.org/.

[25] Yuhan Hao, Stephanie Hao, Erica Andersen-Nissen, William M Mauck, Shiwei Zheng, Andrew Butler, Maddie J Lee, Aaron J Wilk, Charlotte Darby, Michael Zager, et al. Integrated analysis of multimodal single-cell data. *Cell*, 184(13):3573–3587, 2021.

[26] Saskia Freytag and Ryan Lister. schex avoids overplotting for large single-cell RNA-sequencing datasets. *Bioinformatics*, 36(7):2291–2292, apr 2020. doi:10.1093/bioinformatics/btz907. URL http://dx.doi.org/10.1093/bioinformatics/btz907.

[27] Juan C Caicedo, Sam Cooper, Florian Heigwer, Scott Warchal, Peng Qiu, Csaba Molnar, Aliaksei S Vasilevich, Joseph D Barry, Harmanjit Singh Bansal, Oren Kraus, et al. Data-analysis strategies for image-based cell profiling. *Nature methods*, 14(9):849–863, 2017.

[28] Yehudit Hasin, Marcus Seldin, and Aldons Lusis. Multi-omics approaches to disease. *Genome Biology*, 18 (1):83, may 2017. doi:10.1186/s13059-017-1215-1. URL http://dx.doi.org/10.1186/s13059-017-1215-1.

A Colocalization

B Spatial domain

C Watercolor effect creates a background displaying spatial domain

D Multi-dimensional *in situ* visualization

- L1
- L2
- L3
- L4
- L5
- L6
- WM

- EFNA5&EPHA5
- EFNA5
- EPHA5
- Neither