1 **Title:** Body size as a metric for the affordable world
2 **Running title**: body-scaled metric for affordance.

3
4 Xinran Feng[1†], Shan Xu[2†], Yuannan Li[1], & Jia Liu[1*]

5
6 [1]Department of Psychology & Tsinghua Laboratory of Brain and Intelligence, Tsinghua
7 University, Beijing, China.
8 [2]Faculty of Psychology, Beijing Normal University, Beijing, China
9 [†]Equal contribution
10 [*]Correspondence to: liujiathu@tsinghua.edu.cn (J. Liu)
11

12 Abstract

The physical body of an organism serves as a vital interface for interactions with its

environment. Here we investigated the impact of human body size on the perception of action

possibilities (affordances) offered by the environment. We found that the body size

delineated a distinct boundary on affordances, dividing objects of continuous real-world sizes

into two discrete categories with each affording distinct action sets. Additionally, the

boundary shifted with imagined body sizes, suggesting a causal link between body size and

affordance perception. Intriguingly, ChatGPT, a large language model lacking physical

embodiment, exhibited a modest yet comparable affordance boundary at the scale of human

body size, suggesting the boundary is not exclusively derived from organism-environment

interactions. A subsequent fMRI experiment revealed evidence of affordance processing

exclusively for objects within the body size range, but not for those beyond. This suggests

that only objects capable of being manipulated are the objects capable of offering affordance

in the eyes of an organism. In summary, our study suggests a novel definition of object-ness

in an affordance-based context, advocating the concept of embodied cognition in

understanding the emergence of intelligence constrained by an organism's physical attributes.

28
29 Keywords: embodied cognition; affordance; body-scaled metric; affordance boundary;

30 ChatGPT;

Introduction

Man is the measure of all things. - Protagoras

The assertion by the ancient Greek philosopher Protagoras highlights the notion that reality is defined by how the world is perceived by humans. A contemporary interpretation of this statement is the embodied theory of cognition (e.g., Chemero, 2013; Gallagher, 2017; Gibbs, 2005; Wilson, 2002; Varela et al., 2017), which, diverging from the belief that size and shape are inherent object features (e.g., de Beeck et al., 2008; Konkle & Oliva, 2011), posits that human body scale (e.g., size) constrains the perception of objects and the generation of motor responses. For instance, humans evaluate the climbability of steps based on their leg length (Mark, 1987; Warren,1984), and determine the navigability of apertures according to the critical aperture-to-shoulder-width ratio (Warren & Whang, 1987). Additionally, grasping strategies have been shown to be contingent upon object size relative to one's body (Cesari & Newell, 2000; Newell et al., 1989) or hand size (Castiello et al., 1993; Tucker & Ellis, 2004). However, the question of how object perception is influenced by the relative size of objects in relation to the human body remains open. Specifically, it is unclear whether this relative size simply acts as a continuous variable for locomotion reference, or if it affects differentiating and organizing object representation based on their ensued affordances.

To underscore the latter point, Gibson (1979), the pioneer of embodied cognition research, stated that "Detached objects must be comparable in size to the animal under consideration if they are to afford behavior (p.124)." This implies that an object's affordance, encompassing all action possibilities offered to an animal, is determined by the object's size relative to the animal's size rather than its real-world size. For instance, in a naturalistic environment, such as a picnic scene shown in Fig. 1a, there may exist a qualitative distinction between objects within (the objects with warm tints in Fig. 1a) and beyond (those with cold tints) the size range of humans. Only objects within the range, such as the apple, the umbrella, and the bottles, may afford actions, while those beyond this range, such as the trees and the tent, are largely viewed as part of the environment. Consequently, visual perception may be ecologically constrained, and the body may serve as a metric that facilitates

meaningful engagement with the environment by differentiating objects that are accessible

for interactions from those not. Further, grounded cognition theory (see Barsalou, 2008 for a

review) suggests that the outputs of such differentiation might transcend sensorimotor

processes and integrate into supramodal concepts and language. From this perspective, we

proposed two hypotheses: first, the affordance of objects will exhibit a qualitative difference

between objects within and beyond the size range of an organism's body; second, affordance-

related neural activity will emerge exclusively for objects within the organism's size range.

To test these hypotheses, we first measured the affordance of a diverse array of objects

varying in real-world sizes (e.g., Konkle, & Oliva, 2011). We found a dramatic decline in

affordance similarity between objects within and beyond the human body size range, as these

objects afforded distinct sets of action possibilities. Notably, the affordance boundary varied

in response to the imagined body sizes and showed supramodality. It could also be attained

solely through language, as evidenced by the large language model (LLM), ChatGPT

(OpenAI, 2022). A subsequent fMRI experiment corroborated the qualitative difference in

affordances demarcated by the body size, as affordances of objects within humans' size

range, but not those beyond, were represented in both dorsal and ventral visual streams of the

brain. This study advances our understanding of the role of body size in shaping object

representation and underscores the significance of body size as a metric for determining

object affordances that facilitates meaningful engagement with the environment.

Results

To illustrate how human body size affects object affordances with different sizes, we first

characterized the affordances of a set of daily objects. In each trial, we presented a matrix

consisting of nine objects and asked participants to report which objects afforded a specific

action (e.g., sit-able: a chair, a bed, a skateboard, but not a phone, a laptop, an umbrella, a

kettle, a plate, or a hammer) (Fig. 1b). In this task, there were 14 actions commonly executed

in daily life and 24 object images from the THINGS database (Hebart et al., 2019), with sizes

ranging from size rank 2 to 8 according to Konkle and Oliva (2011)'s classification. These

objects covered real-world sizes from much smaller (17 cm on average, rank 2) to orders of

magnitude larger (5,317 cm on average, rank 8) than the human body size (see Methods for

details). Consequently, affordances for each object were indexed by a 14-dimensional action

vector, with the value for each dimension representing the percentage of participants who

agreed on a certain action being afforded by the object (e.g., 88% for the action of grasping

on a hammer indicating 88% of participants agreed that a hammer affords grasping).

Supplementary Fig. S1 shows the affordances of two example objects.

An affordance similarity matrix was then constructed where each cell corresponded to

the similarity in affordances between a pair of objects (Fig. 1c). A clustering analysis

revealed a two-cluster structure. Visual inspection suggested that the upper-left cluster

consisted of objects smaller than human body size (red labels), and the lower-right cluster

contained objects larger than human body size (green labels). Critically, the between-cluster

similarity in the affordance similarity matrix approached zero, suggesting a division in

affordances located near the body size. To quantify this observation, we calculated the

similarity in affordances between each neighboring size rank. Indeed, we identified a clear

trough in affordance similarity, dropping to around zero, between size rank 4 (77cm on

average) and 5 (146cm on average), which was significantly smaller than that between size

rank 3 and 4 ($Z = 3.91$, $p < .001$) and that between size rank 5 and 6 ($Z = 1.66$, $p = .048$). This

trough suggested an affordance boundary between size rank 4 and 5, while affordance

similarities between neighboring ranks remained high (rs > 0.45) and did not significantly

differ from each other (ps > 0.05, all $BF_{10} < 10$) on either side of the boundary (Fig. 1d, left

panel, green lines). This pattern was evident for both genders, indicating no gender

difference. Note that the abrupt change in affordance similarity across the boundary cannot be

explained by changes in objects' real-world size, as the similarity in objects' real-world size

was relatively stable across ranks, without any trend of a trough-shape curve (Fig. 1d, left

panel, yellow line). Intriguingly, rank 4 and rank 5 correspond to 80 cm to 150 cm, a

boundary situated between these two ranks is within the range of the body size of a typical

human adult. This finding suggested that objects were classified into two categories based on

their affordances, with the boundary aligning with human body size.

To better locate the boundary, we focused on the affordance similarity between

individual objects within size rank 3 to 6 (approximately ranging from 30cm to 220cm in

real-world size, the area with grey shade in Fig. 1d), where the trough-shape curve was

identified. Specifically, we traversed all pairs of objects with similar real-world diagonal

sizes (from either the same rank or from neighboring ranks), calculated their average real-

world size as an index of the approximate location of the boundary between this pair of

objects, and plotted the affordance similarity against the average real-world size of each

object pair. As shown in the inset (grey box) of Fig. 1d, consistent with the rank-wise

analysis, the abrupt decrease in affordance similarity exclusively happened between objects

from size rank 4 and 5 (light green dots). The averaged real-world size in these object pairs

was 104 cm (95% CI, 105 to 130 cm) and the affordance similarity in such object pairs was

around zero. This result further narrowed the location estimation of the boundary, and

demonstrated that the affordance boundary persisted at the level of individual objects.

Fig 1. An affordance boundary in the affordable world. a, An illustration of a picnic

scene, featuring objects of various sizes relative to human body. Example objects within the

normal body size range are painted red, and those beyond green. We hypothesized qualitative

differences between perceived affordances of these two kinds of objects. **b**, A demonstration

of the object-action relation judgement task for human participants (top) and AI models

(bottom). The question in the task for human participants was presented in Chinese. **c**, The

representational similarity matrix (RSM) for objects based on human rating of affordance

similarity. Object sizes are denoted with red to green. Two primary clusters emerged in the

clustering analysis of the similarity pattern are outlined with black boxes. **d**, *Left panel*: The

overall affordance similarity and that of each gender (left y-axis) as well as real-world size

similarity (right y-axis) between neighboring size ranks. The error bars represent the standard

error (SE). *Right panel*: The point clouds of pairwise correlations between objects from the

same rank or neighboring ranks. Each colored dot represents the affordance similarity (y-

axis) and the average real-world size (x-axis) of a specific object pair. The grey dots indicate

the averaged size (x-axis) and pairwise similarity (y-axis) of object pairs in different rank

compositions. Left to right: both from size rank 3, from size rank 3 and 4, both from size rank

4, from size rank 4 and 5, both from size rank 5, from size rank 5 and 6, and both from size

rank 6. The horizontal error bars represent 95% confidence interval (CI) of the averaged

object size in each pair, and the vertical error bars denote the CI of pairwise affordance

similarity.

One may argue that the location of the affordance boundary coincidentally fell within the

range of human body size, rather than being directly influenced by it. To rule out this

possibility, we directly manipulated participants' body schema, referring to an experiential

and dynamic functioning of the living body within its environment (Merleau-Ponty & Smith,

1962). This experimental approach was able to establish a causal link between body size and

affordance boundary, as other potential factors remained constant. Specifically, we instructed

a new group of participants to imagine themselves as small as a cat (typical diagonal size:

77cm, size rank 4, referred to as the "cat condition"), and another new group to envision

themselves as large as an elephant (typical diagonal size: 577 cm, size rank 7, referred to as

the "elephant condition") throughout the task (Fig. 2a). A between-subject design was

adopted to minimize contamination between conditions. This manipulation was effective, as

evidenced by the participants' reported imagined heights in the cat condition being 42 cm

(SD = 25.6) and 450 cm (SD = 426.8) in the elephant condition on average, respectively,

when debriefed at the end of the task.

With exactly the same set of objects, a distinct shift in the affordance boundary was

observed for each condition (Fig. 2b). In the cat condition, the affordance boundary was

identified between size rank 3 and 4, with affordance similarity between size rank 3 and 4

being significantly lower than that between size rank 2 and 3 ($Z = 1.76$, $p = .039$) and that

between size rank 4 and 5 ($Z = 1.68$, $p = .047$). In contrast, in the elephant condition, the

affordance boundary shifted to the right, as demonstrated by a decrease in affordance

similarity between size rank 6 and 7, and that between size rank 7 and 8 as compared to that

between size rank 5 and 6, with a trend towards significance (with size rank 6-7: $Z = 1.28$, p

$= .099$; with size rank 7-8: $Z = 1.48$, $p = .069$). The observation that the affordance boundary

shifted to the left under the cat condition and to the right under the elephant condition

suggests that affordance perception is influenced even by imagined body size. Furthermore,

the cognitive penetrability (Pylyshyn, 1999) of affordance perception implies potential

susceptibility of affordance perception to semantic or conceptual transformation or

modification.

To test the further speculation that the affordance boundary can be derived solely from

conceptual knowledge without direct sensorimotor experience, we employed a disembodied

agent, the large language model (LLM) ChatGPT (Chat Generative Pre-trained Transformer;

https://openai.com/blog/chatgpt/). This model was trained on a massive corpus of language

materials originated from humans, yet it can not receive any sensorimotor information from

the environment. Here we asked whether language alone would be sufficient to form an

affordance boundary in ChatGPT models as well as in smaller LLMs, BERT (Devlin et al.,

2018) and GPT-2 (Radford et al., 2018).

The experimental procedure was similar to that conducted with human participants,

except that images were replaced by the corresponding words (see Methods). Given the

randomness embedded in response generation, each model was tested 20 times to simulate

the sampling of human participants. We found that the affordance similarity curves

demonstrated by the ChatGPT models were both trough-shaped between size rank 4 and 5,

the same location where the boundary emerged in human participants (Fig. 2c, green lines).

Further statistical analyses showed a significant difference in affordance similarity between

size rank 3 and 4, and that between size rank 4 and 5 (ChatGPT (GPT-3.5): Z = 1.98, p

= .024; ChatGPT (GPT-4): Z = 2.73, p = .003). The affordance similarity between size rank 4

and 5 was also lower than that between size rank 5 and 6, yet the difference did not reach the

significance (ChatGPT (GPT-3.5): Z = 0.96, p = .17; ChatGPT (GPT-4): Z = 1.27, p = .10).

In contrast, no trough-shaped boundary was observed in either BERT or GPT-2 (Fig. 2c,

yellow lines), despite an apparent but non-significant decrease in affordance similarity in

GPT-2 between size rank 5 and 6 (ps > .20). To further quantify the magnitude of the

decrease in affordance similarity between the size rank 4 and 5, we measured the decrease by

subtracting the similarity value at the trough from the neighboring similarity values and then

subjected it to a permutation test (see Methods). We found a significant decrease in

affordance similarity in humans (permutation N = 5000, $p(T > T_{obs}) = 0.015$) and ChatGPT

(GPT-4) (permutation N = 5000, $p(T > T_{obs}) = 0.046$), a marginal significant decrease in

ChatGPT (GPT-3.5) (permutation N = 5000, $p(T > T_{obs}) = 0.061$), and no significance in

either BERT or GPT-2 (ps > .46, Fig. 2d). Thus, the affordance boundary can be derived

from language solely without sensorimotor information from environment. Interestingly, it

appears to spontaneously emerge when the language processing ability of the LLMs

surpasses a certain threshold (i.e., GPT-2/ BERT < ChatGPT models).

Fig 2. A disembodied origin of the affordance boundary. a, The schematic diagram of the

imagined size in the cat condition (top) and the elephant condition (bottom), with the mean

estimated height reported by participants for each condition. **b**, The affordance similarity

between neighboring size ranks for manipulated body sizes (Red line: cat-size body; Green

line: elephant-size body). The dashed line marks the boundary of the human-size body. The

red and green arrows indicate the corresponding boundary shift in each condition. **c**, The

affordance similarity between neighboring size ranks for different large language models, and

human data from Fig. 1d was re-drawn as a reference. The stars indicate significant contrasts

between affordance similarities between neighboring data points. **d**, The trough value of each

model at between size rank 4-5. The stars here indicate the significant trough value compared

to zero. The error bars represent the estimated standard error (SE). *$p<.05$, **$p<.01$,

***$p<.001$.

A further analysis on the affordances separated by the boundary revealed that objects

within human body size range were primarily subjected to hand-related actions such as

grasping, holding, and throwing. These affordances typically involve object manipulation

with humans' effectors. In contrast, objects beyond the size range of human body

predominantly afforded actions such as sitting and standing, which typically require

locomotion or posture change of the whole body around or within the objects. The distinct

categories of reported affordances demarcated by the boundary imply that the objects on

either side of the boundary may be represented differently in the brain. We thus speculated

that the observed behavioral discontinuity is likely underpinned by distinct neural activities,

which give rise to these discrete 'representations' separated by the boundary.

To test this speculation, we ran an fMRI experiment with a small number of participants

to preliminarily investigate the neural basis of the affordance boundary in the brain by

measuring neural activity in the dorsal and ventral visual streams when participants were

instructed to evaluate whether an action was affordable by an object (Fig. 3a). Four objects

were chosen from the behavioral experiment: two within the body size range (i.e., bottle and

football, WITHIN condition) and the two beyond (i.e., bed and piano, BEYOND condition).

Accordingly, four representative actions (to grasp, to kick, to sit, and to lift) were selected in

relation to the respective objects. During the scan, the participants were asked to decide

whether a probe action was affordable (e.g., grasp-able – bottle, Congruent condition) or not

(e.g., sit-able – bottle, Incongruent condition) by each subsequently-presented object. The

congruency effect, derived from the contrast of Congruent versus Incongruent conditions, is a

well-established measure of affordance processing (e.g., Kourtis et al., 2018).

We examined the congruency effect in two object-selective regions defined by the

contrast of objects against baseline (see Methods), each representing a corresponding visual

stream: the posterior fusiform (pFs) in the ventral stream, which is involved in object

recognition (e.g., Grill-Spector et al., 2000; Malach et al., 1995) and objects' real-world size

processing (Konkle, & Oliva, 2012; Snow et al., 2011), and the superior parietal lobule (SPL)

in the dorsal stream, one of the core tool network regions (e.g., Filimon et al. 2007; Matić et

al., 2020). For the rest object-selective regions identified in this experiment, see

Supplementary Fig. S2 and Supplementary Table S1. A repeated-measures ANOVA with

object type (WITHIN versus BEYOND) and congruency (Congruent versus Incongruent) as

within-subject factors was performed for each ROI, respectively. A significant interaction

between object type and congruency was observed in both ROIs (SPL: $F(1,11) = 15.47$, p

$=.002$, $\eta^2=.58$; pFs: $F(1,11) = 24.93$, $p <.001$, $\eta^2=.69$), suggesting that these regions

represented affordances differentially based on object type (Fig. 3c). A *post hoc* simple effect

analysis revealed the congruency effect solely for objects within body size range (SPL: p

$<.001$; pFs: $p =.021$), not for objects beyond (ps $>.41$). In addition, the main effect of object

type was not significant in either ROI (ps $>.17$), suggesting that the absence of the

congruency effect for objects beyond the body size cannot be attributable to compromised

engagement in viewing these objects. In addition, a whole-brain analysis was performed, and

no region showed the congruency effect for the objects beyond the body size. Taken together,

the affordance boundary not only separated the objects into two categories based on their

relative size to human body, but also delineated the range of objects that evoked neural

representations associated with affordance processing.

Fig 3. Affordance representation in the visual streams. a, An example block with the

probe action "graspable". The participants indicated whether each of the subsequently

presented objects was graspable by pressing the corresponding button. The action probing

question was presented in Chinese during the experiment. **b**, The ROIs included in this

experiment. **c**, The activation of each condition in the pFs and SPL. The bars represent the

contrast estimates of each condition versus baseline. The stars indicate the significant

difference between congruent and incongruent conditions. *$p<.05$, **$p<.01$, ***$p<.001$,

otherwise non-significance. Error bars represent the standard error (SE).

In addition to the pFs and SPL, we also examined the congruency effect in the lateral

occipital cortex (LO), which is involved in object representation (e.g., Grill-Spector et al.,

2000; Konkle & Caramazza, 2013) and provides inputs to both the pFs and SPL (Hebart et

al., 2018). Meanwhile, the primary motor cortex (M1), which receives inputs from the dorsal

stream (Vainio & Ellis, 2020), is involved in affordance processing (e.g., McDannald et al.,

2018) and action executions (Binkofski et al., 2002). Although both the LO and M1 showed a

significantly higher response to objects than baseline, no congruency effect in affordance for

objects within the body size was observed (main effect of congruency: $F(1,11) = 1.74$, p

$=.214$, $\eta^2=.13$, Supplementary Fig. S3). Therefore, it is unlikely that the representation of

affordance is exclusively dictated by visual inputs or automatically engaged in motor

execution. This finding suggests that affordance perception likely requires perceptual

processing and is not necessarily reflected in motor execution, diverging from Gibsonian

concept of direct perception.

Discussion

One long-lasting debate on affordance centers on the distinction between representational

and direct perception of affordance. An outstanding theme shared by many embodied theories

of cognition is the replacement hypothesis (e.g., Van Gelder, 1998), which challenges the

necessity of representation as posited by computationalism's cognitive theories (e.g., Fodor,

1975). This hypothesis suggests that input is discretized/categorized and subjected to

abstraction or symbolization, creating discrete stand-ins for the input (e.g.,

representations/states). Such representationalization would lead to a categorization between

the affordable (the objects) and those beyond affordance (the environment), in contrast to the

perspective offered by embodied theories. The present study probed this

'representationalization' of affordance by examining whether affordance perception

introduces discontinuity and qualitative dissociation in response to continuous action-related

physical features (such as object size relative to the agents), which allows sensorimotor input

to be assigned into discrete states/kinds, in line with the representation-based view under the

constraints of body size. Alternatively, it assessed whether activity directly mirrors the input,

free from discretization/categorization/abstraction, in line with the representation-free view.

First, our study found evidence demonstrating discretization in affordance perception.

Then, through the body imagination experiment, we provided causal evidence suggesting that

this discretization originates from sensorimotor interactions with objects rather than amodal

sources, such as abstract object concepts independent of agent motor capability. Finally, we

demonstrated the supramodality of this embodied discontinuity by leveraging the recent

advances in AI. We showed that the discretization in affordance perception is supramodally

accessible to disembodied agents such as large language models (LLMs), which lack

sensorimotor input but can access linguistic materials built upon discretized representations.

These results collectively suggest that sensorimotor input undergoes discretization, as implied

in the computationalism's idea of representation. Note that, these results are not contradictory

to the claim of the embodied theories, as these representations do shape processes beyond the

sensorimotor domain but after discretization.

This observed boundary in affordance perception extends the understanding of the

discontinuity in perception in response to the continuity of physical inputs (Harnad, 1987;

Young et al., 1997). Perceptual boundary has been demonstrated in various domains, such as

color perception (Bornstein, & Korda, 1984), speech-sounds perception (Liberman et al.,

1957), and facial gender discrimination (Campanella et al., 2001). The boundaries reflect a

fundamental adaptation of perception to facilitate categorizations necessary for an organism

(Goldstone & Hendrickson, 2010). Our study, for the first time, unveiled a boundary in object

affordance, wherein affordance similarity across the boundary was significantly lower than

that within the boundary. Critically, the boundary separating object affordances along a size

axis coincided with human body size, suggesting that object affordances are characterized in

a dimension scaled by human body size.

What is the function of the affordance boundary? About four decades ago, Gibson

(1979) postulated that only objects of sizes comparable to an animal's body size are amenable

to interaction and capable of providing affordances to the animal, thereby possessing

ecological values that distinctly differ from those of larger objects. In this study, we expand

upon this notion by arguing that the affordance boundary serves to delineate (manipulable)

objects from their surrounding environment. In other words, objects within the range of an

animal's body size are indeed objects in the animal's eye and possess affordances as defined

by Gibson. In contrast, objects larger than that range typically surpass the animal's motor

capabilities, rendering them too cumbersome for effective manipulation. Consequently, these

larger objects are less likely to be considered as typical targets for manipulation by the

animal, as opposed to the smaller objects. That is, they are perceived not as *the* "objects" in

the animal's eye, but as part of the background environment, due to their impracticality for

direct interactions. Future studies should incorporate a broader range of objects and a more

comprehensive set of affordances for finer delineation of the representational discontinuity

between objects and the environment.

This speculation aligns with previous fMRI studies where large objects activated the

medial portion of the ventral temporal cortex (Huang et al., 2022; Magri et al., 2021),

overlapping with the parahippocampus gyrus involved in scene representation (Park et al.,

2011; Troiani et al., 2014), and smaller objects activated the lateral portion, such as the pFs,

where the congruency effect of affordance was identified in our study. Furthermore, we

found that the congruency effect was only evident for objects within the body size range, but

not for objects beyond, supporting the idea that affordance is typically represented only for

objects within the body size range. While it is acknowledged that the sample size of the fMRI

study was small (12 participants), necessitating cautious interpretation of its results, the

observed neural-level affordance discontinuity is notable. That is, qualitative differences in

neural activity between objects within the affordance boundary and those beyond replicated

our behavioral findings. This convergent evidence reinforced our claim that objects were

discretized into two broad categories along the continuous size axis, with affordance only

being manifested for objects within the boundary.

In this context, an animal's body size and sensorimotor capacity determine the

boundary of manipulation, and thus, the boundary between manipulable objects and the

environment. Therefore, our study provides a novel perspective on a long-standing question

in psychology, cognitive science, and philosophy: what constitutes an object? Existing

psychological studies, especially in the field of vision, define objects in a disembodied

manner, primarily relying on their physical properties such as shape (e.g., de Beeck et al.,

2008) and absolute size (e.g., Konkle & Oliva, 2011). Our identification of the affordance

boundary presents a new source of *object-ness*: the capability of being a source of affordance

under the constraints of an animal's sensorimotor capacity, which resonates the embodied

influence on the formation of abstract concepts (e.g., Barsalou, 1999; Lakoff & Johnson,

1980) of objects and environment. Consistently, our fMRI data did not show the congruency

effect for objects beyond the body size range, distinct from objects within this range,

suggesting a categorization influenced by objects' relative size to the human body. In this

respect, man is indeed the measure of all things.

The metric provided by the body size, however, was changeable when the body schema

was intentionally altered through participants' imagination of possessing either a cat- or

elephant-sized body, with which the participants had no prior sensorimotor experience.

Importantly, they perceived new affordances in a manner as if they had had embodied

experience with this new body schema. Therefore, this finding suggests that the affordance

boundary is cognitively penetrable, arguing against the directness of affordance perception

(e.g., Gibson, 1979; Greeno, 1994; Prindle et al., 1980) or the exclusive sensorimotor origin

of affordances (e.g., Gallagher, 2017; Thompson, 2010; Hutto & Myin, 2012; Chemero,

2013). Further, this finding that the boundary adapted to manipulation on body schema

suggests that the abstraction/representationalization may be dynamically updated in response

to the current motor capacity and body schema of the agent, suggesting that the affordance-

based process is probably determined dynamically by the nature of the agent-object dyads,

rather than being a fixed belief about objects. Future studies could explore the dynamics of

affordance representationalization, probably by investigating how affordance representations

evolve during active interactions with novel objects or under conditions of altered motor

capabilities. Finally, our findings also suggest that disembodied conceptual knowledge

pertinent to action likely modulates affordance perception. Indeed, it has been proposed that

conceptual knowledge is grounded in the same neural system that supports action (Barsalou,

1999; Glenberg et al., 2013; Wilson & Golonka, 2013), thereby suggesting that sensorimotor

information, along with other model inputs, may be embedded in language (e.g., Casasanto,

2011; Glenberg & Gallese, 2012; Stanfield & Zwaan, 2001), as the grounded theory proposed

(see Barsalou, 2008 for a review).

Direct evidence for this speculation comes from the disembodied ChatGPT models,

which showed an evident affordance boundary despite lacking direct interaction with the

environment. We speculated that ChatGPT models may have formed the affordance boundary

through a human prism ingrained within its linguistic training corpus. In fact, when inquired

about the size of a hypothetical body constructed for its use, ChatGPT (GPT-4) replied, "It

could be the size of an average adult human, around 5 feet 6 inches (167.6 cm) tall. This

would allow me to interact with the world and people in a *familiar* way." Critically, this size

corresponds to the location where the affordance boundary of ChatGPT models was found. In

essence, a virtual body schema may have automatically emerged in ChatGPT models,

possibly based on the body schema inherited from humans through language, enabling

ChatGPT models to display a preliminary ability to reason the relationship between bodily

action and objects. It should be noted that the affordance boundary was not present in all

LLMs tested. Specifically, LLMs with a smaller number of parameters, such as BERT and

GPT-2, did not exhibit any robust boundary, suggesting the emergence of the boundary may

depend on language processing ability determined by the scale of training datasets and the

complexity of the model (Hestness et al., 2017; Brown et al., 2020), as well as alignment

methods used in fine-tuning the model (Ouyang et al., 2022). Nevertheless, caution should

be taken when interpreting the capabilities of LLMs like ChatGPT, which are often

considered "black boxes." That is, our observation indicates that some degree of sensorimotor

information is embedded within human language materials presumably through linguistic

statistics, but it is not sufficient to assert that LLMs have developed a human-like ability to

represent affordances. Furthermore, such information alone may be insufficient for LLMs to

mimic the characteristics of the affordance perception in biological intelligence. Future

studies are needed to elucidate such limitation.

While the primary focus of our study concerns the nature of human perception of

affordance, our findings on ChatGPT models raise an intriguing question that extends beyond

psychology and neuroscience into the domain of artificial intelligence (AI). The AI field has

predominantly concentrated on disembodied cognition, such as vision and language. In

contrast, the utilization of sensorimotor information to interact with and adapt to the world,

including affordance perception in our study, represents a crucial human cognitive

achievement that remains elusive for AI systems. Traditional AI (i.e., task-specific AI) has

been confined with narrowly defined tasks, with substantial limitations in adaptability and

autonomy. Accordingly, these systems have served primarily as tools for humans to achieve

specific outcomes, rather than as autonomous agents capable of independently formulating

goals and translating them into actionable plans. In recent years, significant efforts have been

directed towards evolving traditional AI into more agent-like entities, especially in domains

like navigation, object manipulation, and other interactions with the physical world. Despite

these advancements, the capabilities of AI still fall behind human-level intelligence. On the

other hand, embodied cognition theories suggest that sensorimotor interactions with the

environment are foundational for various cognitive domains. From this point of view,

endowing AI with human-level abilities in physical agent-environment interactions might

provide an unreplaceable missing piece for achieving Artificial General Intelligence (AGI).

This development would significantly facilitate AI's role in robotics, particularly in actions

essential for survival and goal accomplishment, a promising direction for the next

breakthrough in AI (Gupta et al., 2021; Smith & Gasser, 2005).

However, equipping a disembodied AI with the ability for embodied interaction planning within a specific environment remains a complex challenge. By testing the potential representationalization of action possibilities (affordances) in both humans and LLMs, the present study suggests a new approach to enhancing AI's interaction ability with the environment. For instance, our finding of supramodal affordance representation may indicate a possible pathway for disembodied LLMs to engage in embodied physical interactions with their surroundings. From an optimistic view, these results suggest that LLM-based agents, if appropriately designed, may leverage affordance representations embedded in language to interact with the physical world. Indeed, by clarifying and aligning such representations with the physical constitutes of LLM-based agents, and even by explicitly constructing an agent-specific object space, we may foster the sensorimotor interaction abilities of LLM-based agents. This progression could lead to achieving animal-level interaction abilities with the world, potentially sparking new developments in the field of embodied cognition theories.

Although our study showed the supramodality of the representationalization of affordance, two questions remain. First, the magnitude of the boundary observed in ChatGPT models was smaller than that in humans. This discrepancy might be compensated by merely enhancing the language processing ability of LLMs. Alternatively, direct interaction with the environment may be necessary for LLMs to achieve human-level performance in affordance perception. Second, the size of virtual body schema of ChatGPT models, if present, coincided with human body size. Integrating LLMs with real robots (e.g., Driess et al., 2023) may pose a challenge because the to-be-supported robots or cars for autopilot might not fall within human body size range. Future studies may be needed to align the inherited body schema with the actual constitution of the robots. Addressing these questions is beyond the scope of the present study but may hold significant implications for the development of AI systems possessing human-level ingenuity and adaptability in interacting with the world.

In summary, our findings regarding the affordance boundary highlight the interdependence between an agent and the external world in shaping cognition. Furthermore, taking our finding with embodied humans and disembodied LLMs into account, we propose a

revision to the purely sensorimotor-based concept of affordance by emphasizing a

disembodied, perhaps conceptual, addition to it. That is, the embodied cognition and

symbolic processing of language may be more intricately and fundamentally connected than

previously thought: perception-action problems and language problems can be treated as the

same kind of process (Wilson & Golonka, 2013). In this context, man is the measure of both

the world and the words, for both humans and AIs. The presence of such a metric may shed

light on the development of AI systems that can fully capture essential human abilities

founded on sensorimotor interactions with the world.

Methods

Participants

A total of five hundred and thirty-four Chinese participants were recruited for the

original object-action relation judgment task online (https://www.wjx.cn/) in China. Research

advertisements were distributed through an online message board associated with Tsinghua

University. Most participants were undergraduate or graduate students of Tsinghua

University, and the rest were from the general public. Six participants were excluded from the

data analyses because their task completion time did not pass the predetermined minimum

completion time criteria, leaving us with a final sample of 528 participants (311 males, aged

from 16 to 73, mean age = 24.1 years). For the object-action relation judgment task with

manipulated body schema, another one hundred and thirty-nine participants from the same

population were recruited from the same platform. We chose a smaller sample size for the

imagination experiment compared to than for the object-action relation judgment task,

because inspection of the data of the first sample showed that the affordance pattern became

stable after the first 50 participants. To maximize the validity of the manipulation, data from

participants whose imagined height fell within the average human size range (100cm -

200cm) were excluded from further analysis. Consequently, 100 participants (49 males, aged

from 17 to 39 years, mean age = 23.2 years) remained in the analysis. This exclusion criterion

was broader than the standard adult human height range of 140cm to 180cm (NCD-RisC,

2016). This approach ensured that our analysis focused on participants who unambiguously

imagined a body schema different from humans, yet within the known height range of cats

and elephants. Each participant completed an online consent form before starting the

experiment. For the fMRI experiment, twelve undergraduate or graduate Chinese students (8

males, aged from 19 to 31 years, mean age = 23.7 years) from Tsinghua University

participated. The sample size of the fMRI study was decided according to the sample size of

existing studies reporting action-related effects with similar paradigms. All participants

reported normal or corrected-to-normal vision. Each participant completed a pre-scan MRI

safety questionnaire and a consent form before the experiment.

This study was approved by the Institutional Review Board at Beijing Normal

University. All participants were compensated financially for their time.

Stimuli

For all the behavioral tasks, the stimuli comprised 27 objects from the THINGS database

(Hebart et al., 2019). Each image was portrayed as a typical exemplar of a daily-life object

isolated against a white background, sized 400×400 pixels. The objects spanned real-world

size rank 2 to 8, as classified by Konkle and Oliva (2011), where the actual size of each

object was measured as the diagonal size of its bounding box. The size rank was calculated as

a logarithmic function of the diagonal size, with smaller ranks corresponding to smaller real-

world sizes (e.g., the airplane is in size rank 8 and the apple is in size rank 2). The full list of

objects, their diagonal size, and size rankings were provided in Supplementary Table S6. The

objects were selected from the dataset in Konkle and Oliva's study (2011) to cover typic

object sizes in the world (ranging from 14 cm to 7,618 cm), and actions related to these

objects were selected to span a spectrum of daily humans-objects/environments interactions,

from single-point movements (e.g., hand, foot) to whole-body movements (e.g., lying,

standing), based on the Kinetics Human Action Video Dataset (Kay et al., 2017).

For the fMRI experiment, the stimuli included images of 4 objects (bed, bottle, ball, and

piano), with 5 exemplars for each object. The resulting 20 images (4 objects × 5 exemplars,

from the THINGS database) each depicted an isolated object against a white background, all

sized 400 × 400 pixels.

Procedure

Object-action relation judgment task for human participants

To measure the perceived affordances of objects, we developed an object-action relation

judgement task, requiring participants to map 27 objects with 14 actions. The 27 object

images were pre-randomly divided into three groups (nine images each) to form nine-box

grids for display convenience. The 14 actions covered common interactions between human

and objects or environments identified in the kinetics human action video dataset (Kay et al.,

2017).

The task comprised 42 trials (14 actions × 3 object groups) in total. In each trial, one

group of object images (nine object images) and a question asking the appropriateness of

applying a specific action to each object were shown (e.g., "Which objects are sit-able?", see

Fig. 1b, top panel). Participants were asked to choose the objects that afforded the specific

action according to their own senses. They were informed that there were no right or wrong

answers. Each object-action combination would only be presented once during the task. From

this task, we would calculate the percentage that one object was judged affording each of the

14 actions across participants. Since previous research has demonstrated a fundamental

separation between the processing of animate and inanimate objects (e.g., Konkle &

Caramazza, 2013), and the affordances of inanimate objects differ from those of animate

objects (Gibson, 1979), we only include 24 inanimate objects in the following analysis by

excluding 3 animate objects (animals: bird, dog, and horse).

Manipulation of body schema

To manipulate participants' perceived body schema, we asked the participants to imagine themselves as small as a cat, or as large as an elephant. Each participant was randomly assigned to one body-schema condition. Before the experiment started, we presented an instruction screen with an illustration: "Please imagine that you have now grown smaller/larger than your real size, to roughly the same size as a cat/an elephant, as shown in the image below. Please answer the following questions based on this imagined situation." The illustration was also presented in each trial, above the action question and the object images. At the end of the task, as a manipulation check, participants were asked to indicate their imagined body size by responding to the question: "What is the approximate height (cm) you imagine yourself to be during the whole task?"

Object-action relation judgment task for large language models

To test the perceived affordance of the same set of objects by large language models (LLMs), BERT (Bidirectional Encoder Representations from Transformers), GPT-2, and ChatGPT models (based on GPT-3.5 and GPT-4, respectively) were tasked with the same object-action judgement task. Different from the human task, nouns were presented to the models instead of object images (Fig. 1b, bottom panel, for example).

For BERT, the task was formatted as a mask-filling task, in which the inputs were questions such as "Among airplanes, kettles, plates, umbrellas, laptops, beds, [MASK] can be sit-able." We recorded the likelihood score that BERT provided for each listed object at the masked position. For the example question, the possibility score for the word "airplane" was 0.00026.

For GPT-2, the input questions were like, "Among airplanes, kettles, plates, umbrellas, laptops, beds, the thing that can be sit-able is the [blank space]." The likelihood scores GPT-2 provided for each listed object in the position after the input sentence (blank space) were recorded.

To mimic sampling from human participants, we ran BERT and GPT-2 each 20 times

with different random seeds in the dropout layers, considering them as different subjects.

For ChatGPT models, the task was in a direct question-and-answer format. We asked,

for example, "Which objects are sit-able: 'airplane, kettle, plate, …brick'? " and the models

responded by naming a subset of the object list. To get the probability for each object-action

pair, ChatGPT models were run on the same task 20 times, with each new conversation on

the OpenAI website (https://chat.openai.com/chat) considered as one subject. The percentage

that an object was judged affording each of the 14 actions was calculated by averaging the

output across conversations.

Representational similarity matrix for perceived affordance

For each object, we calculated the probability that it was judged affording each of the 14

actions across participants to create a 14-dimension vector. Affordance similarity (*r*) between

each object pair was then calculated based on the Pearson's correlation between these

affordance vectors. A 24×24 symmetric matrix was then generated, with the affordance

similarity between object *i* and object *j* being denoted in cell (*i,j*). A hierarchical clustering

analysis was performed, employing the seaborn clustermap method with Euclidean distance

and Complete linkage(Waskom, 2021).

Affordance similarity between neighboring size ranks

To test the relationship between object affordance and object sizes, we first averaged the

affordance vector among objects within each size rank. Next, the Pearson's correlation

between the average vectors of neighboring size ranks was calculated as the similarity index

for each pair of neighboring size ranks, representing how similar the affordance was

collectively provided by objects in these two ranks. Pearson and Filon's (1898) Z,

implemented in the R package "cocor" (Diedenhofen & Musch, 2015) was used to evaluate

the significance of these similarities (alpha level = .05, one-tail test). For significance tests,

Bayesian statistical analyses were conducted using the web version of the "bayesplay" R

package (Colling, 2021). Specifically, the data (likelihood) model was specified as a normal

distribution, where the correlation coefficients were transformed to Fisher's z. The null

hypothesis was specified as a standard normal distribution centered at zero. Conversely, the

alternative hypothesis was specified as a normal distribution centered at 2. Bayes factors

(BF10) were calculated and interpreted using the classification scheme suggested by

Wagenmakers et al. (2011), wherein a Bayes factor greater than 10 is considered strong

evidence for accepting H1 over H0.

Size similarity between neighboring size ranks

The size of each object was indexed by its real-world size documented in Konkle and

Oliva (2011). Size similarity between size rank i to j was represented as the difference

between the averaged diagonal sizes of objects in size rank i and j relative to that of objects in

rank i:

613
$$Size\ similarity\ (i,j) = 1 - \frac{diagonal\ size_j - diagonal\ size_i}{diagonal\ size_i}$$

Object-level affordance similarity

This analysis focused on objects within size rank 3 to 6. Pearson's correlations between

affordance vectors were conducted for objects within the same size rank as well as for objects

from adjacent ranks. We traversed all possible object pairs and plotted the resulting

correlation values against the mean sizes of the two objects. We also plotted the average

similarity indexes across objects of the same rank composition.

Trough value

To quantify the magnitude of the trough (sharp decrease) observed in the affordance

similarity curve, we first measured the trough value by subtracting the similarity value at the

trough from the similarity values at its two banks (the sites neighboring the trough site):

624
$$Trough\ value = \frac{r_{i+1} + r_{i-1}}{2} - r_i$$

where r_i indicates the affordance similarity between size rank i and size rank $i+1$. The

higher the trough value is, the larger the decrease is.

A permutation test was conducted to evaluate if the trough value was significant above

zero for both LLMs and human data. The *p*-value for this test follows the formula adapted

from Unpingco's (2016):

$$p(T > T_{obs}) = \frac{1}{N} \sum_{i=1,N} I(T_i \geq T_{obs})$$

where T_{obs} is the observed trough value, and *I* is the indicator function. Under the alpha

level of 0.05, if $p < .05$, then the T_{obs} is considered a significant value above zero.

fMRI experiment

The fMRI scanning consisted of one high-resolution T1 anatomical run and four task

runs for each participant. In each task run, participants performed four action blocks (grasp,

kick, lift, and sit). The block order was counterbalanced across runs. Within each block (see

Fig. 3a), an introduction screen showing a question "Which objects are [grasp, kick, lift, sit]-

able" was presented for 2 s at the beginning to indicate the action type, followed by 20 object

images (4 objects × 5 exemplars). The object images were presented in a random order, for

2s each, with a jittered inter-stimulus interval (ISI) varying between 2-4s. Participants were

asked to judge whether the object shown was grasp/kick/lift/sit-able or not by pressing

corresponding buttons (e.g., yes: right index finger; no: left index finger). The response

buttons were also counterbalanced across participants. The task run lasted for 464s in total,

with the four blocks separated by 10s fixation periods.

With this design, we were able to measure the neural activation of objects within agent

size range and those beyond. Further, for each object, there would be congruent trials (e.g.,

grasp-able – bottle: affordance = 1) and incongruent trials (e.g., sit-able – bottle: affordance =

0). We were then able to locate the brain regions representing the objects' affordance by

comparing trials in which the presented objects afforded the presented action option with

those that did not, i.e., to locate the regions showing congruency effect (congruent -

incongruent).

fMRI Data Acquisition

Imaging data were collected using a 3T Siemens Prisma MRI scanner with a 64-channel

phase-arrayed head coil at the Centre for Biomedical Imaging Research at Tsinghua

University. High-resolution T1-weighted images were acquired with a magnetization-

prepared rapid acquisition gradient-echo (MPRAGE) sequence (TR/TE = 2530/2.27 ms, flip

angle = 7°, voxel resolution = 1×1×1 mm). Functional blood-oxygen-level-dependent

(BOLD) images were acquired with a T2*-weighted gradient echo-planar sequence (TR/TE =

2000/34.0 ms, flip angle = 90°, voxel resolution = 2×2×2 mm, FOV = 200×200 mm).

Earplugs were used to attenuate the scanner noise, and a foam pillow and extendable padded

head clamps were used to restrain head motion. All the stimuli were projected onto a screen

at the back of the scanner with a resolution of 1024 × 768, and were viewed from a distance

of approximately 110 cm via a mirror placed on the head coil.

fMRI Data Analyses

Structural T1 and functional images were preprocessed using FSL (FMRIB's Software

Library, https://fsl.fmrib.ox.ac.uk/fsl/fslwiki) v6.0.5 (Jenkinson et al., 2012). A standard

preprocessing pipeline was applied, including skull stripping using the BET (Brain Extraction

Tool; Smith, 2002), slice-timing correction, motion correction using the MCFLIRT method

(Jenkinson et al., 2002), temporal high-pass filtering (100s), and spatial smoothing using a

Gaussian kernel of full-width half magnitude (FWHM) 5mm. Each run's functional data were

registered to a T1-weighted standard image (MNI152) with FLIRT.

For functional data analysis, a first-level voxel-wise general linear model (GLM)

implemented in a FEAT analysis was performed on each run separately. To get neural

activation maps for objects within and beyond versus baseline, the GLM included 3

regressors: objects within body size (bottle and football), objects beyond body size (bed and

piano), and fixation period as baseline; ISI period, response key press and introduction image

were included as 3 nuisance factors. The resultant first-level contrasts of parameter estimates

(COPE) were entered into the next higher-level group analyses, and performed using a

random-effects model (FLAME stage 1, Beckmann et al., 2003). We focused on two critical

contrasts: objects within vs. fixation, and objects beyond vs. fixation, and the conjunction of

these two contrasts. The resulting Z-statistic images were thresholded at $Z > 2.3$, $p = .05$

(Worsley, 2001), and corrected for multiple comparisons using an adjusted cluster-wise

(FWE: family-wise error) significance threshold of $p = 0.05$.

Region of interest (ROI) definition

We chose the pFs, LO, SPL, and M1 as ROIs based on existing literature highlighting

their distinct contributions to affordance perception (Borghi, 2005; Sakreida et al., 2016).

Eight ROIs depicted in Fig. 3b were constructed based on the overlap between the whole-

brain map activated by both objects within and beyond and corresponding functional atlases

(the pFs and LO from Zhen et al., 2015; the SPL and M1 from Fan et al., 2016). To achieve

ROIs of similar sizes, we applied varying thresholds to each cortical area: for the pFs and LO,

the atlases were thresholded at 55% and 90%, resulting 266 voxels in the lpFs, 427 voxels in

the rpFs, 254 voxels in the lLO and 347 voxels in the rLO; for the SPL and M1, the atlases

were thresholded at 78% and 94%, resulting 661 voxels in the lSPL, 455 voxels in the rSPL,

378 voxels in the lM1, and 449 voxels in the rM1. In the subsequent analysis, homologous

areas spanning both cortical hemispheres were merged.

Affordance congruency effect

For the affordance congruency effect of each object type, we modelled another GLM

containing 5 regressors: congruent conditions for objects within/beyond, respectively,

incongruent conditions for objects within/beyond, respectively, and fixation period as

baseline; ISI period, response key press and introduction image were included as 3 nuisance

factors. The resultant first-level COPEs were subjected to the following ROI analysis. A

repeated-measures ANOVA with Object type (WITHIN and BEYOND) and Congruency

(Congruent, Incongruent) as within-subjects factors was run on the average beta values

(contrast estimate) extracted from their respective contrasts versus the fixation for each ROI.

To search all the possible brain regions that revealed congruency effect of objects

beyond, we also ran a whole-brain analysis on the contrast between congruent vs.

incongruent condition for objects beyond. The corresponding first-level COPE was entered

into the group-level analyses with a random-effects model (FLAME stage 1, Beckmann et al.,

2003). The resulting Z-statistic images were thresholded at $Z > 2.3$, $p = .05$ (Worsley, 2001),

and corrected for multiple comparisons using an adjusted cluster-wise (FWE: family-wise

error) significance threshold of $p = 0.05$.

For the whole-brain analyses on the congruency effect, the object size effect, and their

interaction, see Supplementary Fig. S4 and Table S2 to S5.

Acknowledgements

This study was funded by Natural Science Foundation of China (31600925, 32371099,

31861143039), the Shuimu Scholar Program of Tsinghua University, China Postdoctoral

International Exchange Program (YJ20220273), Beijing Municipal Science & Technology

Commission, Administrative Commission of Zhongguancun Science Park

(Z221100002722012), Tsinghua University Guoqiang Institute (2020GQG1016), Beijing

Academy of Artificial Intelligence (BAAI), and Double First-Class initiative Funds for

Discipline Construction.

Data availability

726 The data and the code that support the findings of this study are available from the

727 corresponding author upon reasonable request.

Declaration of conflicting interests

The author declared no potential conflicts of interest with respect to the research, authorship, and/or publication of this article.

References

Barsalou, L. W. (1999). Perceptual symbol systems. *Behavioral and Brain Sciences, 22*(4), 637-660.

Barsalou, L. W. (2008). Grounded cognition. *Annual Review of Psychology*, *59*, 617-645.

Beckmann, C. F., Jenkinson, M., & Smith, S. M. (2003). General multilevel linear modeling for group analysis in FMRI. *NeuroImage*, *20*(2), 1052-1063.

de Beeck, H. P. O., Torfs, K., & Wagemans, J. (2008). Perceived shape similarity among unfamiliar objects and the organization of the human object vision pathway. *Journal of Neuroscience*, *28*(40), 10111-10123.

Binkofski, F., Fink, G. R., Geyer, S., Buccino, G., Gruber, O., Shah, N. J., ... & Freund, H. J. (2002). Neural activity in human primary motor cortex areas 4a and 4p is modulated differentially by attention to action. *Journal of Neurophysiology*, *88*(1), 514-519.

Borghi, A. M. (2005). Object concepts and action. *Grounding cognition: The role of perception and action in memory, language, and thinking*, 8-34.

Bornstein, M. H., & Korda, N. O. (1984). Discrimination and matching within and between hues measured by reaction times: Some implications for categorical perception and levels of information processing. *Psychological Research*, *46*(3), 207-222.

Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., ... & Amodei, D. (2020). Language models are few-shot learners. arXiv 2020. *arXiv preprint arXiv:2005.14165*, *4*.

Campanella, S., Chrysochoos, A., & Bruyer, R. (2001). Categorical perception of facial

gender information: Behavioural evidence and the face-space metaphor. *Visual*

Cognition, *8*(2), 237-262.

Casasanto, D. (2011). Different bodies, different minds: the body specificity of language and

thought. *Current Directions in Psychological Science*, *20*(6), 378-383.

Castiello, U., Bennett, K. M. B., & Stelmach, G. E. (1993). Reach to grasp: the natural

response to perturbation of object size. *Experimental Brain Research*, *94*(1), 163-178.

Cesari, P., & Newell, K. M. (2000). Body-scaled transitions in human grip

configurations. *Journal of Experimental Psychology: Human Perception and*

Performance, *26*(5), 1657.

Chemero, A. (2013). Radical embodied cognitive science. *Review of General*

Psychology, *17*(2), 145-150.

Colling, L.J. (2021). ljcolling/go-bayesfactor: (Version v0.9.0).*Zenodo*. doi:

10.5281/zenodo.4642331

Devlin, J., Chang, M. W., Lee, K., & Toutanova, K. (2018). Bert: Pre-training of deep

bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.

Diedenhofen, B., & Musch, J. (2015). cocor: A comprehensive solution for the statistical

comparison of correlations. *PloS One*, *10*(4), e0121945.

Driess, D., Xia, F., Sajjadi, M. S., Lynch, C., Chowdhery, A., Ichter, B., ... & Florence, P.

(2023). PaLM-E: An Embodied Multimodal Language Model. *arXiv preprint*

arXiv:2303.03378.

Fan, L., Li, H., Zhuo, J., Zhang, Y., Wang, J., Chen, L., ... & Jiang, T. (2016). The human

brainnetome atlas: a new brain atlas based on connectional architecture. *Cerebral*

Cortex, *26*(8), 3508-3526.

Filimon, F., Nelson, J. D., Hagler, D. J., & Sereno, M. I. (2007). Human cortical

representations for reaching: mirror neurons for execution, observation, and

imagery. *NeuroImage*, *37*(4), 1315-1328.

Fodor, J. A. (1975). *The Language of Thought* (Vol. 5). Harvard University Press.

Gallagher, S. (2017). *Enactivist interventions: Rethinking the mind.* Oxford University Press.

Gibbs Jr, R. W. (2005). *Embodiment and cognitive science.* Cambridge University Press.

Gibson, J. J. (1979). *The ecological approach to visual perception: Classic edition.*

Glenberg, A. M., & Gallese, V. (2012). Action-based language: A theory of language

acquisition, comprehension, and production. *Cortex*, *48*(7), 905-922.

Glenberg, A. M., Witt, J. K., & Metcalfe, J. (2013). From the revolution to embodiment: 25

years of cognitive psychology. *Perspectives on Psychological Science*, *8*(5), 573-585.

Goldstone, R. L., & Hendrickson, A. T. (2010). Categorical perception. *Wiley*

Interdisciplinary Reviews: Cognitive Science, *1*(1), 69-78.

Greeno, J. G. (1994). Gibson's Affordances. *Psychological Review*, *101*(2), 336-342.

Grill-Spector, K., Kushnir, T., Hendler, T., & Malach, R. (2000). The dynamics of object-

selective activation correlate with recognition performance in humans. *Nature*

Neuroscience, *3*(8), 837-843.

Gupta, A., Savarese, S., Ganguli, S., & Fei-Fei, L. (2021). Embodied intelligence via learning

and evolution. *Nature Communications*, *12*(1), 5721.

Harnad, S. (1987). Psychophysical and cognitive aspects of categorical perception: A critical

overview.

Hebart, M. N., Dickter, A. H., Kidder, A., Kwok, W. Y., Corriveau, A., Van Wicklin, C., &

Baker, C. I. (2019). THINGS: A database of 1,854 object concepts and more than

26,000 naturalistic object images. *PloS One*, *14*(10), e0223792.

Hebart, M. N., Bankson, B. B., Harel, A., Baker, C. I., & Cichy, R. M. (2018). The

representational dynamics of task and object processing in humans. *eLife*, *7*, e32816.

Hertrich, I., Dietrich, S., & Ackermann, H. (2016). The role of the supplementary motor area

for speech and language processing. *Neuroscience & Biobehavioral Reviews*, *68*, 602-

610.

Hestness, J., Narang, S., Ardalani, N., Diamos, G., Jun, H., Kianinejad, H., ... & Zhou, Y.

(2017). Deep learning scaling is predictable, empirically. *arXiv preprint*

arXiv:1712.00409.

Huang, T., Song, Y., & Liu, J. (2022). Real-world size of objects serves as an axis of object

space. *Communications Biology*, *5*(1), 1-12.

Hutto, D. D., & Myin, E. (2012). *Radicalizing enactivism: Basic minds without content.* MIT

Press.

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved optimization for the

robust and accurate linear registration and motion correction of brain

images. *NeuroImage*, *17*(2), 825-841.

Jenkinson, M., Beckmann, C. F., Behrens, T. E., Woolrich, M. W., & Smith, S. M. (2012).

Fsl. *NeuroImage*, *62*(2), 782-790.

Kantak, S. S., Stinear, J. W., Buch, E. R., & Cohen, L. G. (2012). Rewiring the brain:

potential role of the premotor cortex in motor control, learning, and recovery of function

following brain injury. *Neurorehabilitation and Neural Repair*, *26*(3), 282-292.

Kay, W., Carreira, J., Simonyan, K., Zhang, B., Hillier, C., Vijayanarasimhan, S., ... &

Zisserman, A. (2017). The kinetics human action video dataset. *arXiv preprint*

arXiv:1705.06950.

Konkle, T., & Oliva, A. (2011). Canonical visual size for real-world objects. *Journal of*

Experimental Psychology: Human Perception and Performance, *37*(1), 23.

Konkle, T., & Oliva, A. (2012). A real-world size organization of object responses in

occipitotemporal cortex. *Neuron*, *74*(6), 1114-1124.

Konkle, T., & Caramazza, A. (2013). Tripartite organization of the ventral stream by animacy

and object size. *Journal of Neuroscience*, *33*(25), 10235-10242.

Kourtis, D., Vandemaele, P., & Vingerhoets, G. (2018). Concurrent cortical representations

of function-and size-related object affordances: an fMRI study. *Cognitive, Affective, &*

Behavioral Neuroscience, *18*, 1221-1232.

Lakoff, G., & Johnson, M. (1980). The metaphorical structure of the human conceptual

system. *Cognitive Science*, *4*(2), 195-208.

Liberman, A. M., Harris, K. S., Hoffman, H. S., & Griffith, B. C. (1957). The discrimination

of speech sounds within and across phoneme boundaries. *Journal of Experimental*

Psychology, *54*(5), 358.

Magri, C., Konkle, T., & Caramazza, A. (2021). The contribution of object size,

manipulability, and stability on neural responses to inanimate objects. *NeuroImage*, *237*,

118098.

Malach, R., Reppas, J. B., Benson, R. R., Kwong, K. K., Jiang, H., Kennedy, W. A., ... &

Tootell, R. B. (1995). Object-related activity revealed by functional magnetic resonance

imaging in human occipital cortex. *Proceedings of the National Academy of*

Sciences, *92*(18), 8135-8139.

Mark, L. S. (1987). Eyeheight-scaled information about affordances: a study of sitting and

stair climbing. *Journal of Experimental Psychology: Human Perception and*

Performance, *13*(3), 361.

Matić, K., de Beeck, H. O., & Bracci, S. (2020). It's not all about looks: The role of object

shape in parietal representations of manual tools. *Cortex*, *133*, 358-370.

Merleau-Ponty, M., & Smith, C. (1962). *Phenomenology of Perception* (Vol. 2012). London:

Routledge.

McDannald, D. W., Mansour, M., Rydalch, G., & Bolton, D. A. (2018). Motor affordance for

grasping a safety handle. *Neuroscience Letters*, *683*, 131-137.

NCD Risk Factor Collaboration (NCD-RisC). (2016). A century of trends in adult human

height. *Elife*, *5*, e13410.

Newell, K. M., Scully, D. M., McDonald, P. V., & Baillargeon, R. (1989). Task constraints

and infant grip configurations. *Developmental Psychobiology: The Journal of the*

International Society for Developmental Psychobiology, *22*(8), 817-831.

OpenAI. (2022). *ChatGPT*. https://openai.com/blog/chatgpt

OpenAI. (2023). *GPT-4 Technical Report*. https://cdn.openai.com/papers/gpt-4.pdf

Ouyang, L., Wu, J., Jiang, X., Almeida, D., Wainwright, C., Mishkin, P., ... & Lowe, R.

(2022). Training language models to follow instructions with human feedback. *Advances*

in Neural Information Processing Systems, *35*, 27730-27744.

Park, S., Brady, T. F., Greene, M. R., & Oliva, A. (2011). Disentangling scene content from

spatial boundary: complementary roles for the parahippocampal place area and lateral

occipital complex in representing real-world scenes. *Journal of Neuroscience*, *31*(4),

1333-1340.

Pearson, K., & Filon, L. N. G. (1898). VII. Mathematical contributions to the theory of

evolution.—IV. On the probable errors of frequency constants and on the influence of

random selection on variation and correlation. *Philosophical Transactions of the Royal*

Society of London. Series A, Containing Papers of a Mathematical or Physical

Character, (191), 229-311.

Prindle, S. S., Carello, C., & Turvey, M. T. (1980). Animal-environment mutuality and direct

perception. *Behavioral and Brain Sciences*, *3*(3), 395-397.

Pylyshyn, Z. (1999). Is vision continuous with cognition?: The case for cognitive

impenetrability of visual perception. *Behavioral and Brain Sciences*, *22*(3), 341-365.

Radford, A., Narasimhan, K., Salimans, T., & Sutskever, I. (2018). Improving language

understanding by generative pre-training.

Sakreida, K., Effnert, I., Thill, S., Menz, M. M., Jirak, D., Eickhoff, C. R., ... & Binkofski, F.

(2016). Affordance processing in segregated parieto-frontal dorsal stream sub-

pathways. *Neuroscience & Biobehavioral Reviews*, *69*, 89-112.

Smith, S. M. (2002). Fast robust automated brain extraction. *Human Brain Mapping*, *17*(3),

143-155.

Smith, L., & Gasser, M. (2005). The development of embodied cognition: Six lessons from

babies. *Artificial life*, *11*(1-2), 13-29.

Snow, J. C., Pettypiece, C. E., McAdam, T. D., McLean, A. D., Stroman, P. W., Goodale, M.

A., & Culham, J. C. (2011). Bringing the real world into the fMRI scanner: Repetition

effects for pictures versus real objects. *Scientific Reports*, *1*(1), 1-10.

Stanfield, R. A., & Zwaan, R. A. (2001). The effect of implied orientation derived from

verbal context on picture recognition. *Psychological Science*, *12*(2), 153-156.

Thompson, E. (2010). *Mind in life: Biology, phenomenology, and the sciences of mind*.

Harvard University Press.

Troiani, V., Stigliani, A., Smith, M. E., & Epstein, R. A. (2014). Multiple object properties

drive scene-selective regions. *Cerebral Cortex*, *24*(4), 883-897.

Tucker, M., & Ellis, R. (2004). Action priming by briefly presented objects. *Acta*

psychologica, *116*(2), 185-203.

Unpingco, J. (2016). *Python for probability, statistics, and machine learning* (Vol. 1).

Springer International Publishing.

Vainio, L., & Ellis, R. (2020). Action inhibition and affordances associated with a non-target
object: An integrative review. *Neuroscience & Biobehavioral Reviews*, *112*, 487-502.

Van Gelder, T. (1998). The dynamical hypothesis in cognitive science. *Behavioral and Brain*
Sciences, *21*(5), 615-628.

Varela, F. J., Thompson, E., & Rosch, E. (2017). *The embodied mind, revised edition:*
Cognitive science and human experience. MIT press.

Wagenmakers, E.-J., Wetzels, R., Borsboom, D. & van der Maas, H. L. J. Why psychologists
must change the way they analyze their data: the case of psi: Comment on Bem
(2011). *Journal of Personality and Social Psychology, 100*(3), 426–432.

Warren, W. H. (1984). Perceiving affordances: visual guidance of stair climbing. *Journal of*
Experimental Psychology: Human Perception and Performance, *10*(5), 683.

Warren Jr, W. H., & Whang, S. (1987). Visual guidance of walking through apertures: body-
scaled information for affordances. *Journal of Experimental Psychology: Human*
Perception and Performance, *13*(3), 371.

Waskom, M. L. (2021). Seaborn: statistical data visualization. Journal of Open Source
Software, 6(60), 3021.

Wilson, M. (2002). Six views of embodied cognition. *Psychonomic Bulletin & Review, 9*(4),
625-636.

Wilson, A. D., & Golonka, S. (2013). Embodied cognition is not what you think it
is. *Frontiers in Psychology*, *4*, 58.

Worsley, K. J. (2001). Statistical analysis of activation images. *Functional MRI: An*
Introduction to Methods, *14*(1), 251-270.

Young, A. W., Rowland, D., Calder, A. J., Etcoff, N. L., Seth, A., & Perrett, D. I. (1997).
Facial expression megamix: Tests of dimensional and category accounts of emotion
recognition. *Cognition*, *63*(3), 271-313.

Zhen, Z., Yang, Z., Huang, L., Kong, X. Z., Wang, X., Dang, X., ... & Liu, J. (2015).

Quantifying interindividual variability and asymmetry of face-selective regions: a

probabilistic functional atlas. *NeuroImage*, *113*, 13-25.