**Title:** Body size as a metric for the affordable world

**Running title**: body-scaled metric for affordance.

Xinran Feng[1†], Shan Xu[2†], Yuannan Li[1], & Jia Liu[1*]

[1]Department of Psychology & Tsinghua Laboratory of Brain and Intelligence, Tsinghua

University, Beijing, China.

[2]Faculty of Psychology, Beijing Normal University, Beijing, China

[†]Equal contribution

[*]Correspondence to: liujiathu@tsinghua.edu.cn (J. Liu)

## Abstract

The physical body of an organism serves as a vital interface for interactions with its

environment. Here we investigated the impact of human body size on the perception of action

possibilities (affordances) offered by the environment. We found that the body size

delineated a distinct boundary on affordances, dividing objects of continuous real-world sizes

into two discrete categories with each affording distinct action sets. Additionally, the

boundary shifted with imagined body sizes, suggesting a causal link between body size and

affordance perception. Intriguingly, ChatGPT, a large language model lacking physical

embodiment, exhibited a modest yet comparable affordance boundary at the scale of human

body size, suggesting the boundary is not exclusively derived from organism-environment

interactions. A subsequent fMRI experiment showed that only the affordances of objects

within the range of body size were represented in the brain, suggesting that objects capable of

being manipulated are the only objects capable of offering affordance in the eyes of an

organism. In summary, our study suggests a novel definition of object-ness in an affordance-

based context, advocating the concept of embodied cognition in understanding the emergence

of intelligence constrained by an organism's physical attributes.

Keywords: embodied cognition; affordance; body-scaled metric; affordance boundary;

ChatGPT;

## Introduction

*Man is the measure of all things. - Protagoras*

The assertion by the ancient Greek philosopher Protagoras highlights the notion that reality is defined by how the world is perceived by humans. A contemporary interpretation of this statement is the embodied theory of cognition (e.g., Chemero, 2013; Gallagher, 2017; Gibbs, 2005; Wilson, 2002; Varela et al., 2017), which posits that human body scale (e.g., size) constrains the perception of objects and the generation of motor responses. For instance, humans evaluate the climbability of steps based on their leg length (Mark, 1987; Warren,1984), and determine the navigability of apertures according to the critical aperture-to-shoulder-width ratio (Warren & Whang, 1987). Additionally, grasping strategies have been shown to be contingent upon object size relative to one's body (Cesari & Newell, 2000; Newell et al., 1989) or hand size (Castiello et al., 1993; Tucker & Ellis, 2004). However, whether body size simply serves as a reference for locomotion and object manipulation, or alternatively, plays a pivotal role in shaping the representation of objects as suggested by Protagoras, remains an open question.

To underscore the latter point, Gibson (1979), the pioneer of embodied cognition research, stated that "Detached objects must be comparable in size to the animal under consideration if they are to afford behavior (p.124)." This implies that an object's affordance, encompassing all action possibilities offered to an animal, is determined by the object's size relative to the animal's size rather than its real-world size. For instance, in a naturalistic environment, such as a picnic scene shown in Fig. 1a, there may exist a qualitative distinction between objects within (the objects with warm tints in Fig. 1a) and beyond (those with cold tints) the size range of humans. Only objects within the range, such as the apple, the umbrella and the bottles, may afford actions, while those beyond this range, such as the trees and the tent, are largely viewed as part of the environment. Consequently, visual perception may be ecologically constrained, and the body may serve as a metric that facilitates meaningful engagement with the environment by differentiating objects that are accessible for interactions from those not. Based on Gibson's statement, we proposed two hypotheses: first,

the affordance of objects will exhibit a qualitative difference between objects within and

beyond the size range of an organism's body; second, affordance-related neural activity will

emerge exclusively for objects within the organism's size range.

To test these hypotheses, we first measured the affordance of a diverse array of objects

varying in real-world sizes (e.g., Konkle, & Oliva, 2011). We found a dramatic decline in

affordance similarity between objects within and beyond human body size range, as these

objects afforded distinct sets of action possibilities. Notably, the affordance boundary shifted

in response to the imagined body sizes and could be attained solely from language, as

demonstrated by the large language model (LLM), ChatGPT (OpenAI, 2022). A subsequent

fMRI experiment corroborated the qualitative difference in affordances demarcated by the

body size, as affordances of objects within humans' size range, but not those beyond, were

represented in both dorsal and ventral visual streams of the brain. This study advances our

understanding of the role of body size in shaping object representation and underscores the

significance of body size as a metric for determining object affordances that facilitates

meaningful engagement with the environment.

## Results

To illustrate how human body size affects object affordances with different sizes, we first

characterized the affordances of a set of daily objects. In each trial, we presented a matrix

consisting of nine objects and asked participants to report which objects afforded a specific

action (e.g., sit-able: a chair, a bed, a skateboard, but not a phone, a laptop, an umbrella, a

kettle, a plate, or a hammer) (Fig. 1b). In this task, there were 14 actions commonly executed

in daily life and 24 object images from the THINGS database (Hebart et al., 2019), with sizes

ranging from size rank 2 to 8 according to Konkle and Oliva (2011)'s classification. These

objects covered real-world sizes from much smaller (17 cm on average, rank 2) to orders of

magnitude larger (5,317 cm on average, rank 8) than the human body size (see Methods for

details). Consequently, affordances for each object were indexed by a 14-dimensional action

vector, with the value for each dimension representing the percentage of participants who

agreed on a certain action being afforded by the object (e.g., 88% for the action of grasping

on a hammer indicating 88% of participants agreed that a hammer affords grasping).

Supplemental Fig. S1 showed the affordances of two example objects.

An affordance similarity matrix was then constructed where each cell corresponded to

the similarity in affordances between a pair of objects (Fig. 1c). A clustering analysis

revealed a two-cluster structure. Visual inspection suggested that the upper-left cluster

consisted of objects smaller than human body size (red labels), and the lower-right cluster

contained objects larger than human body size (green labels). Critically, the between-cluster

similarity in the affordance similarity matrix approached zero, suggesting a division in

affordances located near the body size. To quantify this observation, we calculated the

similarity in affordances between each neighboring size rank. Indeed, we identified a clear

trough in affordance similarity, dropping to around zero, between size rank 4 (77cm on

average) and 5 (146cm on average), which was significantly smaller than that between size

rank 3 and 4 ($Z = 3.91$, $p < .001$) and that between size rank 5 and 6 ($Z = 1.66$, $p = .048$). This

trough suggested an affordance boundary between size rank 4 and 5, while affordance

similarities between neighboring ranks remained high ($r$s $> 0.45$) and did not significantly

differ from each other ($p$s $> 0.05$) on either side of the boundary (Fig. 1d, left panel, green

lines). This pattern was evident for both genders, indicating no gender difference. Note that

the abrupt change in affordance similarity across the boundary cannot be explained by

changes in objects' real-world size, as the similarity in objects' real-world size was relatively

stable across ranks, without any trend of a trough-shape curve (Fig. 1d, left panel, yellow

line). Intriguingly, rank 4 and rank 5 corresponds to 80 cm to 150 cm, a boundary situated

between these two ranks is within the range of the body size of a typical human adult. This

finding suggested that objects were classified into two categories based on their affordances,

with the boundary aligning with human body size.

To better locate the boundary, we focused on the affordance similarity between

individual objects within size rank 3 to 6 (approximately ranging from 30cm to 220cm in

real-world size, the area with grey shade in Fig. 1d), where the trough-shape curve was

identified. Specifically, we traversed all pairs of objects with similar real-world diagonal

sizes (from either the same rank or from neighboring ranks), calculated their average real-

world size as an index of the approximate location of boundary between this pair of objects,

and plotted the affordance similarity against the average real-world size of each object pair.

As shown in the inset (grey box) of Fig. 1d, consistent with the rank-wise analysis, the abrupt

decrease in affordance similarity exclusively happened between objects from size rank 4 and

5 (light green dots). The averaged real-world size in these object pairs was 104 cm (95% CI,

105 to 130 cm) and the affordance similarity in such object pairs was around zero. This result

further narrowed the location estimation of the boundary, and demonstrated that the

affordance boundary persisted at the level of individual objects.

**Fig 1. An affordance boundary in the affordable world. a**, An illustration of a picnic

scene, featuring objects of various sizes relative to human body. Example objects within the

normal body size range are painted red, and those beyond green. We hypothesized qualitative

differences between perceived affordances of these two kinds of objects. **b**, A demonstration

of the object-action relation judgement task for human participants (top) and AI models

(bottom). The question in task for human participants was presented in Chinese. **c**, The

representational similarity matrix (RSM) for objects based on human rating of affordance

similarity. Object sizes are denoted with red to green. Two primary clusters emerged in

clustering analysis of the similarity pattern are outlined with black boxes. **d**, *Left panel*: The

overall affordance similarity and that of each gender (left y-axis) as well as real-world size

similarity (right y-axis) between neighboring size ranks. The error bars represent the standard

error (SE). *Right panel*: The point clouds of pairwise correlations between objects from the

same rank or neighboring ranks. Each colored dot represents the affordance similarity (y-

axis) and the average real-world size (x-axis) of a specific object pair. The grey dots indicate

the averaged size (x-axis) and pairwise similarity (y-axis) of object pairs in different rank

compositions. Left to right: both from size rank 3, from size rank 3 and 4, both from size rank

4, from size rank 4 and 5, both from size rank 5, from size rank 5 and 6, and both from size

rank 6. The horizontal error bars represent 95% confidence interval (CI) of the averaged

object size in each pair, and the vertical error bars denote the CI of pairwise affordance

similarity.

One may argue that the location of the affordance boundary coincidentally fell within the

range of human body size, rather than being influenced by human body size. To establish a

causal link between them, we directly manipulated the body schema, referring to an

experiential and dynamic functioning of the living body in its environment (Merleau-Ponty &

Smith, 1962), to examine whether the affordance boundary would shift accordingly. Utilizing

the same paradigm, we instructed a new group of participants to imagine themselves as small

as a cat (typical diagonal size: 77cm, size rank 4, referred to as the "cat condition"), and

another new group to envision themselves as large as an elephant (typical diagonal size: 577

cm, size rank 7, referred to as the "elephant condition") throughout the task (Fig. 2a). This

manipulation proved effective, as evidenced by the participants' reported imagined heights in

the cat condition being 42 cm (SD = 25.6) and 450 cm (SD = 426.8) in the elephant condition

on average, respectively, when debriefed at the end of the task.

With exactly the same set of objects, a distinct shift in the affordance boundary was

observed for each condition (Fig. 2b). In the cat condition, the affordance boundary was

identified between size rank 3 and 4, with affordance similarity between size rank 3 and 4

being significantly lower than that between size rank 2 and 3 ($Z = 1.76$, $p = .039$) and that

between size rank 4 and 5 ($Z = 1.68$, $p = .047$). In contrast, in the elephant condition, the

affordance boundary shifted to the right, as demonstrated by a decrease in affordance

similarity between size rank 6 and 7, and that between size rank 7 and 8 as compared to that

between size rank 5 and 6, with a trend towards significance (with size rank 6-7: $Z = 1.28$, $p$

$= .099$; with size rank 7-8: $Z = 1.48$, $p = .069$). The observation that the affordance boundary

shifted to the left under the cat condition and to the right under the elephant condition

suggests that affordance perception is influenced even by imagined body size. Furthermore,

the cognitive penetrability (Pylyshyn, 1999) of affordance perception implies potential

susceptibility of affordance perception to semantic or conceptual transformation or

modification.

To test the further speculation that the affordance boundary can be derived solely from

conceptual knowledge without direct sensorimotor experience, we employed a disembodied

agent, the large language model (LLM) ChatGPT (Chat Generative Pre-trained Transformer;

https://openai.com/blog/chatgpt/). This model was trained on a massive corpus of language

materials originated from humans, yet it can not receive any sensorimotor information from

the environment. Here we asked whether language alone would be sufficient to form an

affordance boundary in ChatGPT models as well as in smaller LLMs, BERT (Devlin et al.,

2018) and GPT-2 (Radford et al., 2018).

The experimental procedure was similar to that conducted with human participants,

except that images were replaced by the corresponding words (see Methods). Given

randomness embedded in response generation, each model was tested 20 times to simulate

the sampling of human participants. We found that the affordance similarity curves

demonstrated by the ChatGPT models were both trough-shaped between size rank 4 and 5,

the same location where the boundary emerged in human participants (Fig. 2c, green lines).

Further statistical analyses showed a significant difference in affordance similarity between

size rank 3 and 4, and that between size rank 4 and 5 (ChatGPT (GPT-3.5): Z = 1.98, $p$

= .024; ChatGPT (GPT-4): Z = 2.73, $p$ = .003). The affordance similarity between size rank 4

and 5 was also lower than that between size rank 5 and 6, yet the difference did not reach the

significance (ChatGPT (GPT-3.5): Z = 0.96, $p$ = .17; ChatGPT (GPT-4): Z = 1.27, $p$ = .10).

In contrast, no trough-shaped boundary was observed in either BERT or GPT-2 (Fig. 2c,

yellow lines), despite an apparent but non-significant decrease in affordance similarity in

GPT-2 between size rank 5 and 6 ($ps$ > .20). To further quantify the magnitude of the

decrease in affordance similarity between the size rank 4 and 5, we measured the decrease by

subtracting the similarity value at the trough from the neighboring similarity values and then

subjected it to a permutation test (see Methods). We found a significant decrease in

affordance similarity in humans (permutation N = 5000, $p(T > T_{obs})$ = 0.015) and ChatGPT

(GPT-4) (permutation N = 5000, $p(T > T_{obs})$ = 0.046), a marginal significant decrease in

ChatGPT (GPT-3.5) (permutation N = 5000, $p(T > T_{obs})$ = 0.061), and no significance in

either BERT or GPT-2 ($p$s > .46, Fig. 2d). Thus, the affordance boundary can be derived

from language solely without sensorimotor information from environment. Interesting, it

appears to spontaneously emerge when the language processing ability of the LLMs

surpasses a certain threshold (i.e., GPT-2/ BERT < ChatGPT models).

**Fig 2. A disembodied origin of the affordance boundary. a**, The schematic diagram of the
imagined size in the cat condition (top) and the elephant condition (bottom), with the mean
estimated height reported by participants for each condition. **b**, The affordance similarity
between neighboring size ranks for manipulated body sizes (Red line: cat-size body; Green
line: elephant-size body). The dashed line marks the boundary of the human-size body. The
red and green arrows indicate the corresponding boundary shift in each condition. **c**, The
affordance similarity between neighboring size ranks for different large language models, and
human data from Fig. 1d was re-drawn as a reference. The stars indicate significant contrasts
between affordance similarities between neighboring data points. **d**, The trough value of each
model at between size rank 4-5. The stars here indicate the significant trough value compared

to zero. The error bars represent the estimated standard error (SE). *p<.05, **p<.01,

***p<.001.

A further analysis on the affordances separated by the boundary revealed that objects

within human body size range were primarily subjected to hand-related actions such as

grasping, holding and throwing. These affordances typically involve object manipulation with

humans' effectors. In contrast, objects beyond the size range of human body predominantly

afforded actions such as sitting and standing, which typically require locomotion or posture

change of the whole body around or within the objects. The distinct categories of reported

affordances demarcated by the boundary imply that the objects on the two sides of the

boundary may be represented differently in the brain.

To test this speculation, we used fMRI to measure neural activity in the dorsal and

ventral visual streams when participants were instructed to evaluate whether an action was

affordable by an object (Fig. 3a). Four objects were chosen from the behavioral experiment:

two within the body size range (i.e., bottle and football, WITHIN condition) and the two

beyond (i.e., bed and piano, BEYOND condition). Accordingly, four representative actions

(to grasp, to kick, to sit and to lift) were selected in relation to the respective objects. During

the scan, the participants were asked to decide whether a probe action was affordable (e.g.,

grasp-able – bottle, Congruent condition) or not (e.g., sit-able – bottle, Incongruent condition)

by each subsequently-presented object. The congruence effect, derived from the contrast of

Congruent by Incongruent conditions, served as an index of affordance representation.

We examined the congruency effect in two object-selective regions defined by the

contrast of objects against baseline (see Methods), each representing a corresponding visual

stream: the posterior fusiform (pFs) in the ventral stream, which is involved in object

recognition (e.g., Grill-Spector et al., 2000; Malach et al., 1995) and objects' real-world size

processing (Konkle, & Oliva, 2012; Snow et al., 2011), and the superior parietal lobule (SPL)

in the dorsal stream, one of the core tool network regions (e.g., Filimon et al. 2007; Matić et

al., 2020). For the rest object-selective regions identified in this experiment, see

Supplemental Fig. S2 and Supplemental Table S1. A repeated-measures ANOVA with object

type (WITHIN versus BEYOND) and congruency (Congruent versus Incongruent) as within-

subject factors was performed for each ROI, respectively. A significant interaction between

object type and congruency was observed in both ROIs (SPL: $F(1,11) = 15.47$, $p = .002$,

$\eta^2 = .58$; pFs: $F(1,11) = 24.93$, $p < .001$, $\eta^2 = .69$), suggesting that these regions represented

affordances differentially based on object type (Fig. 3c). A *post hoc* simple effect analysis

revealed the congruency effect solely for objects within body size range (SPL: $p < .001$; pFs:

$p = .021$), not for objects beyond ($p$s $> .41$). In addition, the main effect of object type was not

significant in either ROI ($p$s $> .17$), suggesting that the absence of the congruency effect for

objects beyond the body size cannot be attributable to compromised engagement in viewing

these objects. In addition, a whole-brain analysis was performed, and no region showed the

congruency effect for the objects beyond the body size. Taken together, the affordance

boundary not only separated the objects into two categories based on their relative size to

human body, but also delineated the range of objects that receive proper affordance

representation in the brain.

**Fig 3. Affordance representation in the visual streams. a**, An example block with the

probe action "graspable". The participants indicated whether each of the subsequently

presented objects is graspable by pressing the corresponding button. The action probing

question was presented in Chinese during the experiment. **b**, The ROIs included in this

experiment. **c**, The activation of each condition in the pFs and SPL. The bars represent the

contrast estimates of each condition versus baseline. The stars indicate the significant

difference between congruent and incongruent condition. *$p<.05$, **$p<.01$, ***$p<.001$,

otherwise non-significance. Error bars represent the standard error (SE).

In addition to the pFs and SPL, we also examined the congruency effect in the lateral

occipital cortex (LO), which provides inputs to both the pFs and SPL (Hebart et al., 2018),

and the primary motor cortex (M1), which receives inputs from the dorsal stream (Vainio &

Ellis, 2020) and executes actions (Binkofski et al., 2002). Although both the LO and M1

showed a significantly higher response to objects than baseline, no congruency effect in

affordance for objects within the body size was observed (main effect of congruency: $F(1,11)$

$= 1.74$, $p =.214$, $\eta^2=.13$, Supplementary Fig. S3). Therefore, it is unlikely that the

representation of affordance is exclusively dictated by visual inputs or automatically engaged

in motor execution. This finding suggests that affordance perception likely requires

perceptual processing and is not necessarily reflected in motor execution, diverging from

Gibsonian concept of direct perception.

**Discussion**

Boundaries highlight the discontinuity in perception in response to the continuity of physical

inputs (Harnad, 1987; Young et al., 1997). Perceptual boundary has been demonstrated in

various domains, such as color perception (Bornstein, & Korda, 1984), speech-sounds

perception (Liberman et al., 1957), and facial gender discrimination (Campanella et al.,

2001). The boundaries reflect a fundamental adaptation of perception to facilitate

categorizations necessary for an organism (Goldstone & Hendrickson, 2010). Our study, for

the first time, unveiled a boundary in object affordance, wherein affordance similarity across

the boundary was significantly lower than that within the boundary. Critically, the boundary

separating object affordances along a size axis coincided with human body size, suggesting

that object affordances are characterized in a dimension scaled by human body size.

What is the function of the affordance boundary? About four decades ago, Gibson

(1979) postulated that only objects of sizes comparable to an animal's body size are amenable

to interaction and capable of providing affordances to the animal, thereby possessing

ecological values that distinctly differ from those of larger objects. In this study, we expand

upon this notion by arguing that the affordance boundary serves to delineate (manipulable)

objects from their surrounding environment. In other words, objects within the range of an

animal's body size are indeed objects in the animal's eye and possess affordances as defined

by Gibson. In contrast, objects larger than that range are not *the* "objects" with which the

animal is intrinsically inclined to interact, but probably considered less interesting component

of the environment.

This speculation aligns with previous fMRI studies where large objects activated the

medial portion of the ventral temporal cortex (Huang et al., 2022; Magri et al., 2021),

overlapping with the parahippocampus gyrus involved in scene representation (Park et al.,

2011; Troiani et al., 2014), and smaller objects activated the lateral portion, such as the pFs,

where the congruency effect of affordance was identified in our study. Furthermore, we

found that the congruency effect was only evident for objects within the body size range, but

not for objects beyond, supporting the idea that affordance is typically represented only for

objects within the body size range. In this context, an animal's body size and the

sensorimotor capacity determine the boundary of manipulation, and thus, the boundary

between manipulable objects and the environment. Therefore, our study provides a novel

perspective on a long-standing question in psychology, cognitive science, and philosophy:

what constitutes an object? Existing psychological studies, especially in the field of vision,

define objects in a disembodied manner, primarily relying on their physical properties such as

contour (not scrambled). Our identification of the affordance boundary presents a new source

of *object-ness*: the capability of being a source of affordance under constraints of an animal's

sensorimotor capacity, which resonates the embodied influence on the formation of abstract

concepts (e.g., Barsalou, 1999; Lakoff & Johnson, 1980) of objects and environment. In this

respect, man is indeed the measure of all things.

The metric provided by the body size, however, was changeable when the body schema

was intentionally altered through participants' imagination of possessing either a cat- or

elephant-sized body, with which the participants had no prior sensorimotor experience.

Importantly, they perceived new affordances in a manner as if they have had embodied

experience with this new body schema. Therefore, this finding suggests that the affordance

boundary is cognitively penetrable, arguing against the directness of affordance perception

(e.g., Gibson, 1979; Greeno, 1994; Prindle et al., 1980) or the exclusive sensorimotor origin

of affordances (e.g., Gallagher, 2017; Thompson, 2010; Hutto & Myin, 2012; Chemero,

2013). Alternatively, disembodied conceptual knowledge pertinent to action likely modulates

affordance perception. Indeed, it has been proposed that conceptual knowledge is grounded in

the same neural system as that involved in action (Barsalou, 1999; Glenberg et al., 2013;

Wilson & Golonka, 2013), thereby suggesting that sensorimotor information may be

embedded in language (e.g., Casasanto, 2011; Glenberg & Gallese, 2012; Stanfield & Zwaan,

2001), as the grounded theory proposed (see Barsalou, 2008 for a review).

Direct evidence for this speculation comes from the disembodied ChatGPT models,

which showed an evident affordance boundary despite lacking direct interaction with the

environment. We speculated that ChatGPT models may have formed the affordance boundary

through a human prism ingrained within its linguistic training corpus. In fact, when inquired

about the size of a hypothetical body constructed for its use, ChatGPT (GPT-4) replied, "It

could be the size of an average adult human, around 5 feet 6 inches (167.6 cm) tall. This

would allow me to interact with the world and people in a *familiar* way." Critically, this size

corresponds to the location where the affordance boundary of ChatGPT models was found. In

essence, a virtual body schema may have automatically emerged in ChatGPT models,

possibly based on the body schema inherited from humans through language, enabling

ChatGPT models to display a preliminary ability to reason the relationship between bodily

action and objects. It should be noted that the affordance boundary was not present in all

LLMs tested. Specifically, LLMs with a smaller number of parameters, such as BERT and

GPT-2, did not exhibit any robust boundary, suggesting the emergence of the boundary may

depend on language processing ability determined by the scale of training datasets and the

complexity of the model (Hestness et al., 2017; Brown et al., 2020), as well as alignment

methods used in fine-tuning the model (Ouyang et al., 2022).

While the primary focus of our study concerns the nature of human perception of affordance, our findings on ChatGPT models raise an intriguing question that extends beyond psychology and neuroscience into the domain of artificial intelligence (AI). The AI field has predominantly concentrated on disembodied cognition, such as vision and language. In contrast, the utilization of sensorimotor information to interact with and adapt to the world, including affordance perception in our study, represents a crucial human cognitive achievement that remains elusive for AI systems. Developing such abilities may facilitate AI-supported robotics in navigation, object manipulation, and other actions essential for survival and goal accomplishment, which is considered a promising direction of the next breakthrough in AI (Gupta et al., 2021; Smith & Gasser, 2005).

Although our study showed that the ability to perceive affordance can emerge solely from language, two questions remain. First, the magnitude of the boundary observed in ChatGPT models was smaller than that in humans. This discrepancy might be compensated by merely enhancing the language processing ability of LLMs. Alternatively, direct interaction with the environment may be necessary for LLMs to achieve human-level performance in affordance perception. Second, the size of virtual body schema of ChatGPT models, if present, coincided with human body size. When integrating LLMs with real robots (Driess et al., 2023), this may pose a challenge because the to-be-supported robots or cars for autopilot might not fall within human body size range. Future studies may be needed to align the inherited body schema with the actual constitution of the robots. Addressing these questions is beyond the scope of the present study but may hold significant implications for the development of AI systems possessing human-level ingenuity and adaptability in interacting with the world.

In summary, our findings regarding the affordance boundary highlight the interdependence between an agent and the external world in shaping cognition. Furthermore, taking our finding with embodied humans and disembodied LLMs into account, we propose a revision to the purely sensorimotor-based concept of affordance by emphasizing a disembodied, perhaps conceptual, addition to it. That is, the embodied cognition and

symbolic processing of language may be more intricately and fundamentally connected than previously thought: perception-action problems and language problems can be treated as the same kind of process (Wilson & Golonka, 2013). In this context, man is the measure of both the world and the words, for both humans and for AIs. The presence of such a metric may shed light on the development of AI systems that can fully capture essential human abilities founded on sensorimotor interactions with the world.

## Methods

### Participants

A total of five hundred and thirty-four participants were recruited for the original object-action relation judgement task online (https://www.wjx.cn/). Six participants were excluded from the data analyses because their task completion time did not pass the predetermined minimum completion time criteria, leaving us with a final sample of 528 participants (311 males, aged from 16 to 73, mean age = 24.1 years). For the object-action relation judgement task with manipulated body schema, another one hundred and thirty-nine participants were recruited from the same platform. Data from participants whose imagined height fell within the average human size range (100cm - 200cm) were excluded from further analysis, with 100 participants (49 males, aged from 17 to 39 years, mean age = 23.2 years) remained. Each participant completed an online consent form before starting the experiment.

For the fMRI experiment, twelve students (8 males, aged from 19 to 31 years, mean age = 23.7 years) from Tsinghua University participated. All participants reported normal or corrected-to-normal vision. Each participant completed a pre-scan MRI safety questionnaire and a consent form before the experiment.

This study was approved by the Institutional Review Board at Beijing Normal University. All participated were all compensated financially for their time.

**Stimuli**

For all the behavioural tasks, the stimuli comprised 27 objects from the THINGS database (Hebart et al., 2019). Each image was portraited a typical exemplar of daily-life object isolated against a white background, sized $400 \times 400$ pixels. The objects spanned real-world size rank 2 to 8, as classified in Konkle and Oliva (2011), where the actual size of each object was measured as the diagonal size of its bounding box. The size rank was calculated as a logarithmic function of the diagonal size, with smaller ranks corresponding to smaller real-world sizes (e.g., the airplane is in size rank 8 and the apple is in size rank 2). The full list of objects, along with their corresponding diagonal size and size rank, was provided in Supplementary Table S2.

For fMRI experiment, the stimuli included images of 4 objects (bed, bottle, ball, and piano), with 5 exemplars for each object. The resulting 20 images (4 objects × 5 exemplars, from the THINGS database) each depicted an isolated object against a white background, all sized $400 \times 400$ pixels.

**Procedure**

***Object-action relation judgement task for human participants***

To measure the perceived affordances of objects, we developed an object-action relation judgement task, requiring participants to map 27 objects with 14 actions. The 27 object images were pre-randomly divided into three groups (nine images each) to form nine-box grids for display convenience. The 14 actions covered common interactions between human and objects or environments identified in the kinetics human action video dataset (Kay et al., 2017).

The task comprised 42 trials (14 actions × 3 object groups) in total. In each trial, one group of object images (nine object images) and a question asking the appropriateness of applying a specific action to each object were shown (e.g., "Which objects are sit-able?", see Fig. 1b, top panel). Participants were asked to choose the objects that afforded the specific

action according to their own senses. They were informed that there were no right or wrong

answers. Each object-action combination would only be presented once during the task. From

this task, we would calculate the percentage that one object was judged affording each of the

14 actions across participants. Since previous research has demonstrated a fundamental

separation between the processing of animate and inanimate objects (e.g., Konkle &

Caramazza, 2013), and the affordances of inanimate objects differ from those of animate

objects (Gibson, 1979), we only include 24 inanimate objects in the following analysis by

excluding 3 animate objects (animals: bird, dog, and horse).

*Manipulation of body schema*

To manipulate participants' perceived body schema, we asked the participants to

imagine themselves as small as a cat, or as large as an elephant. Each participant was

randomly assigned to one body-schema condition. Before the experiment we would present

an instruction screen with an illustration before the experiment start: "Please imagine that you

have now grown smaller/larger than your real size, to roughly the same size as a cat/an

elephant, as shown in the image below. Please answer the following questions based on this

imagined situation." The illustration was also presented in each trial, above the action

question and the object images. At the end of the task, as a manipulation check, participants

were asked to indicate their imagined body size by responding to the question: "What is the

approximate height (cm) you imagine yourself to be during the whole task?"

*Object-action relation judgement task for large language models*

To test the perceived affordance of the same set of objects by large language models

(LLMs), BERT (Bidirectional Encoder Representations from Transformers), GPT-2, and

ChatGPT models (based on GPT-3.5 and GPT-4, respectively) were tasked with the same

object-action judgement task. Different from the human task, nouns were presented to the

models instead of object images (Fig. 1b, bottom panel, for an example).

457   For BERT, the task was formatted as a mask-filling task, in which the inputs were

458 questions such as "Among airplanes, kettles, plates, umbrellas, laptops, beds, [MASK] can be

459 sit-able.". We recorded the likelihood score that BERT provided for each listed object at the

460 masked position. For the example question, the possibility score for the word "airplane" was

461 0.00026.

462   For GPT-2, the input questions were like, "Among airplanes, kettles, plates, umbrellas,

463 laptops, beds, the thing that can be sit-able is the [blank space]." The likelihood scores GPT-2

464 provided for each listed object in the position after the input sentence (blank space) were

465 recorded.

466   To mimic sampling from human participants, we ran BERT and GPT-2 each for 20

467 times with different random seeds in the dropout layers, considering them as different

468 subjects.

469   For ChatGPT models, the task was in a direct question-and-answer format. We asked,

470 for example, "Which objects are sit-able: 'airplane, kettle, plate, …brick'? " and the models

471 responded by naming a subset of the object list. To get the probability for each object-action

472 pair, ChatGPT models were run on the same task 20 times, with each new conversation on

473 the OpenAI website (https://chat.openai.com/chat) considered as one subject. The percentage

474 that an object was judged affording each of the 14 actions was calculated by averaging the

475 output across conversations.

476   ***Representational similarity matrix for perceived affordance***

477   For each object, we calculated the probability that it was judged affording each of the 14

478 actions across participants to create a 14-dimension vector. Affordance similarity ($r$) between

479 each object pair was then calculated based on the Pearson's correlation between these

480 affordance vectors. A $24 \times 24$ symmetric matrix was then generated, with the affordance

481 similarity between object $i$ and object $j$ being denoted in cell ($i,j$). A hierarchical clustering

482 analysis was performed and visualized with seaborn clustermap (Waskom, 2021).

     *Affordance similarity between neighbouring size ranks*

To test the relationship between object affordance and object sizes, we first averaged the

affordance vector among objects within each size rank. Next, the Pearson's correlation

between the average vectors of neighboring size ranks was calculated as the similarity index

for each pair of neighboring size ranks, representing how similar the affordance collectively

provided by objects in these two ranks. Pearson and Filon's (1898) Z, implemented in R

package "cocor" (Diedenhofen & Musch, 2015) was used to evaluate the significance of

these similarities (alpha level = .05, one-tail test).

*Size similarity between neighbouring size ranks*

The size of each object was indexed by its real-world size documented in Konkle and

Oliva (2011). Size similarity between size rank $i$ to $j$ was represented as the difference

between the averaged diagonal sizes of objects in size rank $i$ and $j$ relative to that of objects in

rank $i$:

$$Size\ similarity\ (i,j) = 1 - \frac{diagonal\ size_j - diagonal\ size_i}{diagonal\ size_i}$$

*Object-level affordance similarity*

This analysis focused on objects within size rank 3 to 6. Pearson's correlation between

affordance vectors were conducted for objects within the same size rank as well as for objects

from adjacent ranks. We traversed all possible object pairs, and plotted the resulting

correlation values against the mean sizes of the two objects. We also plotted the average

similarity indexes across objects of the same rank composition.

*Trough value*

To quantify the magnitude of the trough (sharp decrease) observed in the affordance

similarity curve, we first measured the trough value by subtracting the similarity value at the

trough from the similarity values at its two banks (the sites neighboring the trough site):

$$Trough\ value = \frac{r_{i+1} + r_{i-1}}{2} - r_i$$

508  where $r_i$ indicates the affordance similarity between size rank $i$ and size rank $i+1$. The

509  higher the trough value is, the larger the decrease is.

510  A permutation test was conducted to evaluate if the trough value was significant above

511  zero for both LLMs and human data. The *p*-value for this test follows the formula adapted

512  from Unpingco's (2016):

$$p(T > T_{obs}) = \frac{1}{N} \sum_{i=1,N} I(T_i \geq T_{obs})$$

514  where $T_{obs}$ is the observed trough value, and *I* is the indicator function. Under the alpha

515  level of 0.05, if $p < .05$, then the $T_{obs}$ is considered a significant value above zero.

**fMRI experiment**

The fMRI scanning consisted of one high-resolution T1 anatomical run and four task

runs for each participant. In each task run, participants performed four action blocks (grasp,

kick, lift, and sit). The block order was counterbalanced across runs. Within each block (see

Fig. 3a), an introduction screen showing a question "Which objects are [grasp, kick, lift, sit]-

able" was presented for 2 s at the beginning to indicate the action type, followed by 20 object

images (4 objects × 5 exemplars). The object images were presented in a random order, for

2s each, with a jittered inter-stimulus interval (ISI) varying between 2-4s. Participants were

asked to judge whether the object shown was grasp/kick/lift/sit-able or not by pressing

corresponding buttons (e.g., yes: right index finger; no: left index finger). The response

buttons were also counterbalanced across participants. The task run lasted for 464s in total,

with the four blocks separated by 10s fixation periods.

With this design, we were able to measure the neural activation of objects within agent

size range and those beyond. Further, for each object, there would be congruent trials (e.g,

grasp-able – bottle: affordance = 1) and incongruent trials (e.g., sit-able – bottle: affordance =

0). We were then able to locate the brain regions representing the objects' affordance by

comparing trials in which the presented objects afford the presented action option with those

do not, i.e., to locate the regions showing congruency effect (congruent - incongruent).

**fMRI Data Acquisition**

Imaging data were collected using a 3T Siemens Prisma MRI scanner with a 64-channel

phase-arrayed head coil at the Centre for Biomedical Imaging Research in Tsinghua

University. High-resolution T1-weighted images were acquired with a magnetization-

prepared rapid acquisition gradient-echo (MPRAGE) sequence (TR/TE = 2530/2.27 ms, flip

angle = 7°, voxel resolution = 1×1×1 mm). Functional blood-oxygen-level-dependent

(BOLD) images were acquired with a T2*-weighted gradient echo-planar sequence (TR/TE =

2000/34.0 ms, flip angle = 90°, voxel resolution = 2×2×2 mm, FOV = 200×200 mm).

Earplugs were used to attenuate the scanner noise, and a foam pillow and extendable padded

head clamps were used to restrain head motion. All the stimuli were projected onto a screen

at the back of the scanner with a resolution of 1024 × 768, and were viewed from a distance

of approximately 110 cm via a mirror placed on the head coil.

**fMRI Data Analyses**

Structural T1 and functional images were preprocessed using FSL (FMRIB's Software

Library, https://fsl.fmrib.ox.ac.uk/fsl/fslwiki) v6.0.5 (Jenkinson et al., 2012). A standard

preprocessing pipeline was applied, including skull stripping using the BET (Brain Extraction

Tool; Smith, 2002), slice-timing correction, motion correction using the MCFLIRT method

(Jenkinson et al., 2002), temporal high-pass filtering (100s), and spatial smoothing using a

Gaussian kernel of full width half magnitude (FWHM) 5mm. Each run's functional data were

registered to a T1-weighted standard image (MNI152) with FLIRT.

For functional data analysis, a first-level voxel-wise general linear models (GLM)

implemented in a FEAT analysis was performed on each run separately. To get neural

activation maps for objects within and beyond versus baseline, the GLM included 3

regressors: objects within body size (bottle and football), objects beyond body size (bed and

piano), and fixation period as baseline; ISI period, response key press and introduction image

were included as 3 nuisance factors. The resultant first-level contrasts of parameter estimates

(COPE) were entered into the next higher-level group analyses, performed using a random-

effects model (FLAME stage 1, Beckmann et al., 2003). We focused on two critical contrasts:

objects within vs. fixation, and objects beyond vs. fixation, and the conjunction of these two

contrasts. The resulting Z-statistic images were thresholded at Z > 2.3, $p = .05$ (Worsley,

2000), and corrected for multiple comparisons using an adjusted cluster-wise (FWE: family-

wise error) significance threshold of $p = 0.05$.

### *Region of interest (ROI) definition*

Eight ROIs (Fig. 3b) of brain regions involved in affordance processing were selected

based on the overlap of the outcomes from the whole-brain conjunction map (areas activated

for both objects within and beyond) and corresponding functional atlases (pFs and LO from

Zhen et al., 2015; SPL and M1 from Fan et al., 2016). For pFs and LO's atlases, the

probabilistic activation maps (PAM) were thresholded at around 70%, in which map each

voxel contains a percentage of participants who showed activation for seeing objects versus

baseline in Zhen et al.'s study, resulting 266 voxels in lpFs, 427 voxels in rpFs, 254 voxels in

lLO and 347 voxels in rLO. For SPL and M1, the probabilistic activation maps were

thresholded at around 80%, resulting 661 voxels in lSPL, 455 voxels in rSPL, 378 voxels in

lM1, and 449 voxels in rM1. Homologous areas within the cortical hemispheres were merged

in the following ROI analysis.

### *Affordance congruency effect*

For the affordance congruency effect of each object type, we modelled another GLM

containing 5 regressors: congruent conditions for objects within/beyond, respectively,

incongruent conditions for objects within/beyond, respectively, and fixation period as

baseline; ISI period, response key press and introduction image were included as 3 nuisance

factors. The resultant first-level COPEs were subjected the following ROI analysis. A

repeated-measures ANOVA with Object type (WITHIN and BEYOND) and Congruency

(Congruent, Incongruent) as within-subjects factors was run on the average beta values

(contrast estimate) extracted from their respective contrasts versus the fixation for each ROI.

To search all the possible brain regions that revealed congruency effect of objects

beyond, we also ran a whole-brain analysis on the contrast between congruent vs.

incongruent condition for objects beyond. The corresponding first-level COPE was entered

into the group-level analyses with a random-effects model (FLAME stage 1, Beckmann et al.,

2003). The resulting Z-statistic images were thresholded at $Z > 2.3$, $p = .05$ (Worsley, 2000),

and corrected for multiple comparisons using an adjusted cluster-wise (FWE: family-wise

error) significance threshold of $p = 0.05$.

**Acknowledgements**

This study was funded by Natural Science Foundation of China (31600925, 31861143039),

Beijing Municipal Science & Technology Commission, Administrative Commission of

Zhongguancun Science Park (Z221100002722012), Tsinghua University Guoqiang Institute

(2020GQG1016), and Beijing Academy of Artificial Intelligence (BAAI).

**Data availability**

The data and the code that support the findings of this study are available from the

corresponding author upon reasonable request.

**Declaration of conflicting interests**

The author declared no potential conflicts of interest with respect to the research, authorship,

and/or publication of this article.

## References

Barsalou, L. W. (1999). Perceptual symbol systems. *Behavioral and Brain Sciences, 22*(4), 637-660.

Barsalou, L. W. (2008). Grounded cognition. *Annual Review of Psychology*, *59*, 617-645.

Beckmann, C. F., Jenkinson, M., & Smith, S. M. (2003). General multilevel linear modeling for group analysis in FMRI. *NeuroImage*, *20*(2), 1052-1063.

Binkofski, F., Fink, G. R., Geyer, S., Buccino, G., Gruber, O., Shah, N. J., ... & Freund, H. J. (2002). Neural activity in human primary motor cortex areas 4a and 4p is modulated differentially by attention to action. *Journal of Neurophysiology*, *88*(1), 514-519.

Bornstein, M. H., & Korda, N. O. (1984). Discrimination and matching within and between hues measured by reaction times: Some implications for categorical perception and levels of information processing. *Psychological Research*, *46*(3), 207-222.

Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., ... & Amodei, D. (2020). Language models are few-shot learners. arXiv 2020. *arXiv preprint arXiv:2005.14165*, *4*.

Campanella, S., Chrysochoos, A., & Bruyer, R. (2001). Categorical perception of facial gender information: Behavioural evidence and the face-space metaphor. *Visual Cognition*, *8*(2), 237-262.

Casasanto, D. (2011). Different bodies, different minds: the body specificity of language and thought. *Current Directions in Psychological Science*, *20*(6), 378-383.

Castiello, U., Bennett, K. M. B., & Stelmach, G. E. (1993). Reach to grasp: the natural response to perturbation of object size. *Experimental Brain Research*, *94*(1), 163-178.

Cesari, P., & Newell, K. M. (2000). Body-scaled transitions in human grip configurations. *Journal of Experimental Psychology: Human Perception and Performance*, *26*(5), 1657.

Chemero, A. (2013). Radical embodied cognitive science. *Review of General*
*Psychology*, *17*(2), 145-150.

Devlin, J., Chang, M. W., Lee, K., & Toutanova, K. (2018). Bert: Pre-training of deep
bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.

Diedenhofen, B., & Musch, J. (2015). cocor: A comprehensive solution for the statistical
comparison of correlations. *PloS One*, *10*(4), e0121945.

Driess, D., Xia, F., Sajjadi, M. S., Lynch, C., Chowdhery, A., Ichter, B., ... & Florence, P.
(2023). PaLM-E: An Embodied Multimodal Language Model. *arXiv preprint*
*arXiv:2303.03378*.

Fan, L., Li, H., Zhuo, J., Zhang, Y., Wang, J., Chen, L., ... & Jiang, T. (2016). The human
brainnetome atlas: a new brain atlas based on connectional architecture. *Cerebral*
*Cortex*, *26*(8), 3508-3526.

Filimon, F., Nelson, J. D., Hagler, D. J., & Sereno, M. I. (2007). Human cortical
representations for reaching: mirror neurons for execution, observation, and
imagery. *NeuroImage*, *37*(4), 1315-1328.

Gallagher, S. (2017). *Enactivist interventions: Rethinking the mind.* Oxford University Press.

Gibbs Jr, R. W. (2005). *Embodiment and cognitive science.* Cambridge University Press.

Gibson, J. J. (1979). The ecological approach to visual perception: classic edition.

Glenberg, A. M., & Gallese, V. (2012). Action-based language: A theory of language
acquisition, comprehension, and production. *Cortex*, *48*(7), 905-922.

Glenberg, A. M., Witt, J. K., & Metcalfe, J. (2013). From the revolution to embodiment: 25
years of cognitive psychology. *Perspectives on Psychological Science*, *8*(5), 573-585.

Goldstone, R. L., & Hendrickson, A. T. (2010). Categorical perception. *Wiley*
*Interdisciplinary Reviews: Cognitive Science*, *1*(1), 69-78.

Greeno, J. G. (1994). Gibson's Affordances. *Psychological Review*, *101*(2), 336-342.

Grill-Spector, K., Kushnir, T., Hendler, T., & Malach, R. (2000). The dynamics of object-
selective activation correlate with recognition performance in humans. *Nature*
*Neuroscience*, *3*(8), 837-843.

Gupta, A., Savarese, S., Ganguli, S., & Fei-Fei, L. (2021). Embodied intelligence via learning
and evolution. *Nature Communications*, *12*(1), 5721.

Harnad, S. (1987). Psychophysical and cognitive aspects of categorical perception: A critical
overview.

Hebart, M. N., Dickter, A. H., Kidder, A., Kwok, W. Y., Corriveau, A., Van Wicklin, C., &
Baker, C. I. (2019). THINGS: A database of 1,854 object concepts and more than
26,000 naturalistic object images. *PloS One*, *14*(10), e0223792.

Hebart, M. N., Bankson, B. B., Harel, A., Baker, C. I., & Cichy, R. M. (2018). The
representational dynamics of task and object processing in humans. *eLife*, *7*, e32816.

Hestness, J., Narang, S., Ardalani, N., Diamos, G., Jun, H., Kianinejad, H., ... & Zhou, Y.
(2017). Deep learning scaling is predictable, empirically. *arXiv preprint*
*arXiv:1712.00409*.

Huang, T., Song, Y., & Liu, J. (2022). Real-world size of objects serves as an axis of object
space. *Communications Biology*, *5*(1), 1-12.

Hutto, D. D., & Myin, E. (2012). *Radicalizing enactivism: Basic minds without content*. MIT
Press.

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved optimization for the
robust and accurate linear registration and motion correction of brain
images. *NeuroImage*, *17*(2), 825-841.

Jenkinson, M., Beckmann, C. F., Behrens, T. E., Woolrich, M. W., & Smith, S. M. (2012).
Fsl. *NeuroImage*, *62*(2), 782-790.

Kay, W., Carreira, J., Simonyan, K., Zhang, B., Hillier, C., Vijayanarasimhan, S., ... &

Zisserman, A. (2017). The kinetics human action video dataset. *arXiv preprint*

*arXiv:1705.06950*.

Konkle, T., & Oliva, A. (2011). Canonical visual size for real-world objects. *Journal of*

*Experimental Psychology: Human Perception and Performance*, *37*(1), 23.

Konkle, T., & Oliva, A. (2012). A real-world size organization of object responses in

occipitotemporal cortex. *Neuron*, *74*(6), 1114-1124.

Konkle, T., & Caramazza, A. (2013). Tripartite organization of the ventral stream by animacy

and object size. *Journal of Neuroscience*, *33*(25), 10235-10242.

Lakoff, G., & Johnson, M. (1980). The metaphorical structure of the human conceptual

system. *Cognitive Science*, *4*(2), 195-208.

Liberman, A. M., Harris, K. S., Hoffman, H. S., & Griffith, B. C. (1957). The discrimination

of speech sounds within and across phoneme boundaries. *Journal of Experimental*

*Psychology*, *54*(5), 358.

Magri, C., Konkle, T., & Caramazza, A. (2021). The contribution of object size,

manipulability, and stability on neural responses to inanimate objects. *NeuroImage*, *237*,

118098.

Malach, R., Reppas, J. B., Benson, R. R., Kwong, K. K., Jiang, H., Kennedy, W. A., ... &

Tootell, R. B. (1995). Object-related activity revealed by functional magnetic resonance

imaging in human occipital cortex. *Proceedings of the National Academy of*

*Sciences*, *92*(18), 8135-8139.

Mark, L. S. (1987). Eyeheight-scaled information about affordances: a study of sitting and

stair climbing. *Journal of Experimental Psychology: Human Perception and*

*Performance*, *13*(3), 361.

Matić, K., de Beeck, H. O., & Bracci, S. (2020). It's not all about looks: The role of object

shape in parietal representations of manual tools. *Cortex*, *133*, 358-370.

Merleau-Ponty, M., & Smith, C. (1962). *Phenomenology of Perception* (Vol. 2012). London:

Routledge.

Newell, K. M., Scully, D. M., McDonald, P. V., & Baillargeon, R. (1989). Task constraints

and infant grip configurations. *Developmental Psychobiology: The Journal of the*

*International Society for Developmental Psychobiology*, *22*(8), 817-831.

OpenAI. (2022). *ChatGPT*. https://openai.com/blog/chatgpt

OpenAI. (2023). *GPT-4 Technical Report*. https://cdn.openai.com/papers/gpt-4.pdf

Ouyang, L., Wu, J., Jiang, X., Almeida, D., Wainwright, C., Mishkin, P., ... & Lowe, R.

(2022). Training language models to follow instructions with human feedback. *Advances*

*in Neural Information Processing Systems*, *35*, 27730-27744.

Park, S., Brady, T. F., Greene, M. R., & Oliva, A. (2011). Disentangling scene content from

spatial boundary: complementary roles for the parahippocampal place area and lateral

occipital complex in representing real-world scenes. *Journal of Neuroscience*, *31*(4),

1333-1340.

Pearson, K., & Filon, L. N. G. (1898). VII. Mathematical contributions to the theory of

evolution.—IV. On the probable errors of frequency constants and on the influence of

random selection on variation and correlation. *Philosophical Transactions of the Royal*

*Society of London. Series A, Containing Papers of a Mathematical or Physical*

*Character*, (191), 229-311.

Prindle, S. S., Carello, C., & Turvey, M. T. (1980). Animal-environment mutuality and direct

perception. *Behavioral and Brain Sciences*, *3*(3), 395-397.

Pylyshyn, Z. (1999). Is vision continuous with cognition?: The case for cognitive

impenetrability of visual perception. *Behavioral and Brain Sciences*, *22*(3), 341-365.

Radford, A., Narasimhan, K., Salimans, T., & Sutskever, I. (2018). Improving language
understanding by generative pre-training.

Roux-Sibilon, A., Kalénine, S., Pichat, C., & Peyrin, C. (2018). Dorsal and ventral stream
contribution to the paired-object affordance effect. *Neuropsychologia*, *112*, 125-134.

Smith, S. M. (2002). Fast robust automated brain extraction. *Human Brain Mapping*, *17*(3),
143-155.

Smith, L., & Gasser, M. (2005). The development of embodied cognition: Six lessons from
babies. *Artificial life*, *11*(1-2), 13-29.

Snow, J. C., Pettypiece, C. E., McAdam, T. D., McLean, A. D., Stroman, P. W., Goodale, M.
A., & Culham, J. C. (2011). Bringing the real world into the fMRI scanner: Repetition
effects for pictures versus real objects. *Scientific Reports*, *1*(1), 1-10.

Stanfield, R. A., & Zwaan, R. A. (2001). The effect of implied orientation derived from
verbal context on picture recognition. *Psychological Science*, *12*(2), 153-156.

Thompson, E. (2010). *Mind in life: Biology, phenomenology, and the sciences of mind.*
Harvard University Press.

Troiani, V., Stigliani, A., Smith, M. E., & Epstein, R. A. (2014). Multiple object properties
drive scene-selective regions. *Cerebral Cortex*, *24*(4), 883-897.

Tucker, M., & Ellis, R. (2004). Action priming by briefly presented objects. *Acta*
*psychologica*, *116*(2), 185-203.

Unpingco, J. (2016). *Python for probability, statistics, and machine learning* (Vol. 1).
Springer International Publishing.

Vainio, L., & Ellis, R. (2020). Action inhibition and affordances associated with a non-target
object: An integrative review. *Neuroscience & Biobehavioral Reviews*, *112*, 487-502.

Varela, F. J., Thompson, E., & Rosch, E. (2017). *The embodied mind, revised edition:*
*Cognitive science and human experience*. MIT press.

Warren, W. H. (1984). Perceiving affordances: visual guidance of stair climbing. *Journal of*
*Experimental Psychology: Human Perception and Performance*, *10*(5), 683.

Warren Jr, W. H., & Whang, S. (1987). Visual guidance of walking through apertures: body-
scaled information for affordances. *Journal of Experimental Psychology: Human*
*Perception and Performance*, *13*(3), 371.

Waskom, M. L. (2021). Seaborn: statistical data visualization. Journal of Open Source
Software, 6(60), 3021.

Wilson, M. (2002). Six views of embodied cognition. *Psychonomic Bulletin & Review, 9*(4),
625-636.

Wilson, A. D., & Golonka, S. (2013). Embodied cognition is not what you think it
is. *Frontiers in Psychology*, *4*, 58.

Worsley, K. J. (2001). Statistical analysis of activation images. *Functional MRI: An*
*Introduction to Methods*, *14*(1), 251-270.

Young, A. W., Rowland, D., Calder, A. J., Etcoff, N. L., Seth, A., & Perrett, D. I. (1997).
Facial expression megamix: Tests of dimensional and category accounts of emotion
recognition. *Cognition*, *63*(3), 271-313.

Zhen, Z., Yang, Z., Huang, L., Kong, X. Z., Wang, X., Dang, X., ... & Liu, J. (2015).
Quantifying interindividual variability and asymmetry of face-selective regions: a
probabilistic functional atlas. *NeuroImage*, *113*, 13-25.