Humans switch between heuristics instead of combining cues when judging object properties from motion

Vivian C. Paulun[1,2,3*], Florian S. Bayer[2], Joshua B. Tenenbaum[3], and Roland W. Fleming[2,4]

[1]*Department of Psychology, University of Wisconsin-Madison, USA*

[2]*Department of Experimental Psychology, Justus Liebig University Giessen, Germany*

[3]*Department of Brain and Cognitive Sciences, Massachusetts Institute of Technology, USA*

[4]*Center for Mind, Brain and Behavior (CMBB), University of Marburg and Justus Liebig University Giessen, Germany*

[*]To whom correspondence should be addressed. Email: paulun@wisc.edu

Abstract

A key to interacting with the physical world is the ability to infer object properties, such as elasticity, from vision, allowing us to anticipate an object's behavior in advance. This kind of perceptual inference challenges current AI systems—highlighting the complexity of the underlying computations. How does the human brain solve this task? Here, we propose a resource-rational model based on learned statistics of object motion to explain how humans judge elasticity. We created 100,000 physics-based simulations of bouncing objects with different elasticities and found that even tiny changes in initial conditions (e.g., orientation) yield starkly different trajectories. Yet, across these simulations, we identified 23 motion features that capture natural variations in elasticity. Although a weighted combination of these features reliably predicts physical elasticity, surprisingly, humans do not seem to employ cue combination when judging elasticity. Instead, we found that observers flexibly switch between different cues, i.e., heuristics. A series of experiments designed to carefully tease apart several competing heuristics, suggests that observers switch between different computationally efficient yet highly informative heuristics depending on the information available in the stimulus.

Keywords: Visual Perception, Intuitive Physics, Computational Rationality

1 Introduction

To grasp, catch, stack, or avoid objects, we need to infer their physical properties such as elasticity, mass, compliance, or friction (Diaz et al., 2013; Fikes et al., 1994; Glowania et al., 2017; Klein et al., 2020; Paulun et al., 2016; Weir et al., 1991a, 1991b). In most cases, we see objects before we interact with them, making vision the primary source of information to perceive and predict the physical world. Still, researchers do not yet fully understand the cues and computations the brain relies on to estimate the internal properties of objects (Aliaga et al., 2015; Bates et al., 2019; Battaglia et al., 2013; Bi et al., 2021, 2019; Bi and Xiao, 2016; Hamrick et al., 2016; Kawabe et al., 2015; Paulun et al., 2017, 2015; Paulun and Fleming, 2020; Schmid and Doerschner, 2018; Schmidt et al., 2017; Van Assen et al., 2018; Yildirim et al., 2018). Unlike an object's shape, size or identity, physical properties like mass or elasticity can only be *inferred* from the observed behavior of the object or substance (Bi and Xiao, 2016; Kawabe et al., 2015; Paulun et al., 2017, 2015; Paulun and Fleming, 2020; Van Assen et al., 2018), e.g., how a fluid flows, jelly wobbles or a ball bounces. The challenging nature of such inferences is underlined by the fact that even though AI models have matched or surpassed human performance in tasks like object recognition (Krizhevsky et al., 2012; Szegedy et al., 2015) or segmentation (Kirillov et al., 2023), they still struggle with intuitive physical reasoning (Motamed et al., 2025; Tung et al., n.d.), especially for non-rigid objects. What makes visual inference of physical properties so difficult?

Consider a bouncing elastic object: How it bounces depends on many factors besides its elasticity, e.g., the initial direction and force with which it was thrown. An individual object can produce an infinite variety of trajectories, i.e., spatiotemporal paths, while objects with different elasticities can trace very similar paths depending on other factors, such as the object's initial speed, height or direction of motion (**Figure 1A**). In previous work(Paulun and Fleming, 2020), we have shown that observers estimate the elasticity of bouncing cubes based on their motion trajectory. But, if there is no unique mapping between an object's elasticity and its trajectory, how does the brain estimate the former from the latter?

Warren and colleagues (Warren et al., 1987) suggested that observers use the relative height of a simulated, two-dimensional ball around a bounce (i.e. the ratio of initial and final height) to visually judge elasticity, and the duration between two bounces when the ball's height is occluded. While their study elegantly isolated different cues and demonstrated that observers are sensitive to them, it remains unclear how people judge elasticity in more natural settings with more complex trajectories and when no single cue is a perfect determinant of elasticity (such as relative bounce height was in their study).

Our work addresses these two key questions: (1) How do people visually infer elasticity in naturalistic scenes, where no single cue alone perfectly predicts elasticity? (2) How does the brain learn to visually infer elasticity without ever having access to the ground

truth? Although individual trajectories vary, motion trajectories of the same elasticity will somewhat resemble each other in terms of their overall characteristic motion features, e.g., bounce height, speed of velocity decay and trajectory length. While no individual feature is perfectly diagnostic of elasticity, variations across different trajectories are also not random because they result from lawful physical constraints. By observing a number of examples, the brain could learn the dominant feature dimensions along which bouncing objects vary and represent elastic objects within the space of these features. A given heuristic (such as the bounce height ratio suggested by Warren and others) could be thought of as a special instance of this, in which the brain might identify just *one* feature along which trajectories are varying and thus elasticity judgments will rely on. However, another possibility is that the brain encodes elastic objects along multiple different features which would lead to a more robust representation in naturalistic settings. By considering different visual features, e.g., number of bounces and bounce height ratio, the brain could overcome the potential pitfalls of single heuristics.

This idea leads to several testable predictions, which we evaluate here. First, motion features can be used to disentangle physical elasticity from other confounding factors (such as initial speed). Second, the relation between physical elasticity and motion features can be learned through observation alone. Third, either a single motion feature (i.e., a heuristic) or a robust combination of several features can explain the pattern of successes and failures in human perception. To test these assumptions, we employed a data-driven approach. For this purpose, we simulated 100,000 short (4 sec) trajectories of a bouncing cube in a room (**Figure 1A**). The cube's elasticity (coefficient of restitution) varied from 0.0 (not elastic) to 0.9 (very elastic) in ten steps. Importantly, we also varied the initial position, orientation, and velocity of the cubes to gain 10,000 different trajectories for each level of elasticity. Although computer simulations are only approximations of the real world, we validated that they reproduce several crucial physical behaviors of bouncing objects (Paulun and Fleming, 2020). Only through simulation can we generate sufficient number and diversity of trajectories to identify and evaluate statistical regularities. We chose nonrigid, i.e., deformable, cubes as stimuli, because they result in chaotic and highly variable trajectories while being feasible in terms of the parameters to create and analyze them and are, thus, the ideal case example to study. Next, we identified 28 candidate 3D motion features (**Figure 2A-D, Table 1**) based on the physics of bouncing objects, and previously proposed cues (Nusseck et al., 2007; Warren et al., 1987). We then determined how they statistically relate to physical elasticity in our dataset und used PCA to determine the optimal feature combination to predict elasticity. Our analysis revealed several competing hypotheses of how humans visually judge elasticity using motion features, all of which could be learned in an unsupervised fashion from observation alone. In a series of carefully designed experiments, we selected stimuli that systematically decouple these highly correlated alternative hypotheses and find the one that best predicts human

83 perception on a stimulus-by-stimulus basis. To begin, we first established human
84 accuracy and consistency in elasticity perception in a random subset of our dataset as
85 a benchmark to test out models of perception against.
86

Results

Observers accurately infer elasticity, but make systematic errors

Fifteen observers rated the apparent elasticity of bouncing cubes in 150 simulated
animations—fifteen different trajectories for each of the ten elasticities (see **Methods**
and **Figure 1A** and **Video S1**). Although the initial speed, position, and orientation of the
cubes varied randomly, yielding widely variable trajectories, observers were very
accurate at estimating the cube's relative elasticity (**Figure 1B**). Average ratings
increased systematically with physical elasticity (linear regression: R^2 = .84, F(1, 148) =
748.73, p < .001). However, if observers had perfect elasticity constancy, they would
give videos showing the same elasticity the same ratings. This is not what we found:
Cubes with identical physical elasticity were perceived to have different elasticities
(average SD per elasticity level was 0.09 and significantly different from zero: t(9) =
16.40, p < .001). Importantly, the pattern of errors was not random but highly consistent
between different observers (r = .91 ± .04; M ± SD) as well as within repeated ratings of
the same individual (r = .90 ± .04). In fact, there was no significant difference between
intra- and inter-observer variability (t(14) = 2.08, p = 0.056). What causes this systematic
pattern of errors? If humans represent elastic objects in terms of their characteristic
motion features, perceptual errors should occur whenever a trajectory falls onto an
"atypical location" in that feature space. In the following, we test this prediction.

***Figure 1. Stimuli and results of Experiment 1**. A) Example stimuli of lowest (e = 0.0)*
and highest elasticity (e = 0.9), frames of the animations were overlaid for illustration
purposes (see also Video S1). Even though both images in each row show the same
cube (i.e., the same physical properties), the trajectories are different because we
*randomly varied the initial speed, position, and orientation. **B)** Average elasticity ratings*
of Experiment 1 together with a linear fit. Dots of the same color show simulations of the
same elasticity but varying initial parameters.

Motion features disentangle physical elasticity from other latent factors

We propose that the brain represents trajectories of bouncing objects using one or more spatiotemporal features and infers elasticity from their systematic variation. To test this hypothesis, we explored a set of motion features derived from the 3D trajectories of the object. We started with 28 potential features that between them capture many aspects of bounce trajectories (**Table 1**; see **Table S1** for additional details, **Figures S1-2**). The features were selected by: (a) consideration of the physics of ideal bouncing objects, (b) proposals from previous literature (Nusseck et al., 2007; Warren et al., 1987), and (c) subjective observations of the simulations. Some features describe characteristics of individual bounces (e.g., average bounce height, rebound velocity) or measure the coefficient of restitution in simplified, idealized settings (e.g., bounce height ratio). Others capture summary statistics that integrate over time and might be useful in realistic scenes that deviate from ideal conditions (e.g., number of bounces, movement duration; **Figure 2A-B**). Such statistics provide several different ways of measuring how quickly the object dissipates kinetic energy as it bounces around. All motion features are stimulus computable from observable quantities, i.e., positions and changes of positions over time, and derived from first principles. We computed the motion features from the trajectories of the cube's center of mass (CoM) and eight corners for all 100,000 simulations (see **Methods**). Although object rotation and deformation are important for a complete physical representation of the object's motion, we do not consider them here, as our previous findings show that they have a negligible effect on the perceived elasticity in these stimuli (Paulun and Fleming, 2020). With this exception we aimed to achieve a comprehensive characterization of the trajectories by defining a diverse set of features to follow a data-driven approach and constrain our hypothesis space based on the data rather than a priori assumptions.

Table 1. Motion features with % variance explained in physical elasticity, see Table S1.
Features< 5% were excluded from further analysis.

%	Feature (acronym; unit)
82.29	Movement duration until the cube stopped moving. (movDur; sec)
78.93	Number of bounces from the floor, the ceiling and the walls. (nBounce)
78.92	Duration until the cube landed after the last bounce from any wall. (bounceDur; sec)
77.87	Number of bounces from the floor. (nBounceFloor)
67.27	Cumulative length of the motion trajectory. (trajLen; m)
52.76	Mean ratio of energy before and after a bounce. (mEnerRatio)
51.91	Mean acceleration over time. (mAccel; m/s^2)
50.80	Conserved energy over time. (consEner)
45.85	Maximum ratio of energy before and after a bounce. (maxEnerRatio)
44.86	Maximum length of bounce arcs from floor (maxArcLenFloor; m)
41.80	Mean ratio of incident to rebound velocity of all bounces. (mVelRatio)

39.42	Maximal ratio of incident to rebound velocity of all bounces. (maxVelRatio)
36.51	Maximal ratio of durations of consecutive bounces from the floor. (maxBounceDurRatio)
35.46	Maximal duration of individual bounces from the floor. (maxBounceDur; sec)
35.21	Maximal rebound velocity of bounces from every wall. (maxReboundVel; m/s)
35.13	Maximal ratio of bounce heights of two consecutive bounces from the floor. (maxBounceHtRatio)
35.10	Maximal height of bounces from the floor. (maxBounceHt; m)
30.84	Mean ratio of bounce durations of consecutive bounces from the floor. (mBounceDurRatio)
23.42	Mean ratio of bounce heights of two consecutive bounces from the floor. (mBounceHtRatio)
16.25	Maximal length of bounce arcs, i.e., trajectory between consecutive bounces. (maxArcLen; m)
6.24	Mean height of bounces from the floor. (mBounceHt; m)
5.49	Mean velocity over time. (mVel; m/s)
5.25	Mean length of bounce arcs, i.e., trajectory, between consecutive bounces. (mArcLen; m)
4.06	Mean length of bounce arcs from floor. (mArcLenFloor; m)
1.86	Difference between movement and bounce duration. (otherMotionDur; sec)
0.77	Mean duration of individual bounces from the floor. (mBounceDur; sec)
0.15	Mean height of the object over time. (mHeight; m)
0.01	Mean rebound velocity of bounces from all walls. (mReboundVel; m/s)

First, we evaluated how well each of the individual features captured the variance
across different elasticities. We found that many features varied systematically with
physical elasticity (**Figure 2C-D & 3B, Table 1**). The most diagnostic features (which
share the most variation with physical elasticity) were those that integrate information
over time, such as movement duration or the number of bounces. Interestingly, we
found that heuristics that were previously identified for idealized settings, e.g., related
to the height and duration of bounces, were not among the best features in our complex
scenario. We narrowed our hypothesis space by excluding features that explained < 5 %
of the variance from further analysis. We found that the remaining 23 features were
significantly correlated with one another across the set of 100,000 trajectories (mean
absolute correlation, M = 0.48; see **Figure S3A-B**). To identify independent dimensions
of variation, we applied principal component analysis (PCA) to the normalized and
equalized motion features of all trajectories. Representing the trajectories in the space
of the first two PCs reveals that physical elasticity varies largely along the first
dimension (**Figure 2E**). Indeed, we found that ground truth elasticity and the first PC
share 82.83% of their variance. In other words, physical elasticity emerges as the latent
variable driving most variance in the feature representation of all trajectories. Although
adding further PCs necessarily increases the explained variance of the dataset (**Figure
S3C**), adding more PCs to a multiple linear regression model fitted to physical elasticity
does not increase the shared variance by much (with all PCs: 86.25%). Moreover, while
PC1 robustly predicts physical elasticity, it is mostly independent of the other latent
parameters we used to initialize our simulations (e.g., velocity; all < 1.0%, **Figure S3D**).
Thus, this linear combination of motion features (see **Figure S4** for feature loadings)

successfully disentangles physical elasticity from other scene factors that contribute to
the raw physical trajectory of bouncing objects. Notably, this feature weighting is not the
result of a fitting process but emerges naturally and without supervision from the
statistics across many examples. This underlines the potential of motion features to
form a statistical appearance model of bouncing objects in a completely data-driven
fashion. In the following, we test whether PC1 can explain the perceptual patterns found
in Experiment 1 ('multi-feature model'). Importantly, applying a PCA to the raw motion
trajectories (**Figure 2F**) does not yield comparable elasticity estimates—highlighting the
crucial role of appearance features.

Figure 2. Spatiotemporal motion features of bouncing objects. *A) Example trajectory*
of a low (e = 0.0) and high (e = 0.9) elastic cube, each dot represents one frame; color
*gradient represents movement duration. **B)** The same two trajectories, red dots*
*represent bounces off the floor. **C)** Distribution of movement durations in the set of*
*100,000 trajectories, true elasticity is color-coded. **D)** Distribution of "number of*
*bounces off the floor" in the set of 100,000 stimuli. **E)** All 100,000 simulations in the*
space of the first two PCs resulting from a PCA on the motion features ("feature space").
Physical elasticity (color-coded) seems to vary mainly along the first PC, which explains
*most of the variance, see **Figure S3C-D**. F) 100,000 trajectories in the space of the first*
two PCs resulting from a PCA on the raw trajectories. Rather than physical elasticity
(color-coded), the PCs seem to be related to the position of the cube in 3D space, see
***Figure S3E-F**. Note that although the initial position of the cube is uniformly sampled, its*

3D position over time is biased due to gravity. This results in a tilted square in the 2D
representation of the PCs.

Optimal motion features predict elasticity perception

Having established that motion features are highly diagnostic of physical elasticity and
that their relation to elasticity can be learned without supervision from observation
alone, our analysis revealed several strong hypotheses for how the brain could visually
infer elasticity. Next, we sought to answer the key question whether the human brain
relies on a single motion feature (i.e., a heuristic) when estimating elasticity or instead
combines different visual features to a potentially more robust estimate, similar to PC1.
Note that besides PC1, we also tested a more traditional precision-based maximum-
likelihood estimation (MLE) model of cue combination in which the features are
weighted according to their reliability, i.e., their weights are inversely proportional to
their variance. The MLE model was overall highly correlated with the PC1 model (r = .98
over the 100k simulations) but performed slightly worse in predicting elasticity (physical
and perceived, see **Figure S5**). We therefore considered PC1 as the stronger cue
combination model to test against individual heuristics.

Interestingly, we found that motion features that turned out to be good, i.e., diagnostic,
heuristics of *physical* elasticity, were also the best to predict perceived elasticity in
experiment 1 (**Figure 3B**). Strikingly, movement duration, the best feature for predicting
physical elasticity, was also the best to predict *perceived* elasticity (R^2 = .91, F(1, 148) =
1515.1, p < .001, **Figure 3A-B**). On a stimulus-by-stimulus basis, movement duration
was a better predictor of human ratings than physical elasticity (evidence ratio:
$w_{movDur}/w_{Physics}$ = 1.51e+20). Can a combination of features outperform this? We find that
a multi-feature model, i.e., PC1, is a very good predictor of perceived elasticity in
Experiment 1 (linear regression: R^2 = .89, F(1, 148) = 1210.5, p < .001, see **Figure 3B-C**).
This is impressive given that the feature weighting was derived from observing the
covariation of features in a large data set rather than a fitting procedure to the
perceptual (or any) data. PC1 predicts perception better than the ground truth does
(evidence ratio: $w_{FeatureModel}/w_{Physics}$ = 3.38e+13), but worse than movement duration
(evidence ratio: $w_{movDur}/w_{FeatureModel}$ = 4.46e+06; $w_{movDur} \approx$ 1). However, the predictions of
both models are strongly correlated (r = .95, p < .001, in the complete data set). In
Experiment 2 we therefore systematically decouple their predictions.

Figure 3. Prediction of perceived elasticity by different competing models. A)
Perceived elasticity (in Experiment 1) as a function of the prediction made by the
statistically optimal feature: movement duration. B) Explained variance in terms of
perceived elasticity (in Experiment 1) as a function of explained variance of physical
elasticity (in the data set of 100,000) for individual features (blue) and the multi-feature
model (PC1, red). The noise ceiling shows the average explained variance between
individual subjects and the average subject (± 95%-CI). C) Rated elasticity from
Experiment 1 as a function of the prediction made by the feature combination from PC1,
i.e., the multi-feature model.

When observing complete motion trajectories people use movement duration as a heuristic to elasticity

The aim of Experiment 2 was threefold: First, we systematically decoupled the predictions of the multi-feature model from those of the movement duration heuristic to bring both models into conflict. Second, in order to test whether any of the other features are—individually—a better predictor of perceived elasticity, we systematically decoupled all other features from the multi-feature model. Since it is impossible to isolate each of the 23 features from all other features one by one, we decoupled each feature from the weighted combination of all features to test its causal contribution to elasticity perception. In doing so, we are able to overcome the purely correlational analysis reported so far and experimentally tests 24 competing hypotheses at once, thereby going beyond previous studies (Bi et al., 2019; Kawabe et al., 2015; Paulun et al., 2017, 2015; Schmid and Doerschner, 2018; Schmidt et al., 2017; Van Assen et al., 2018). Third, because any good model of elasticity perception should be able to predict the pattern of errors on a stimulus-by-stimulus basis, all stimuli in this experiment had the same physical elasticity, i.e., all perceptual differences are illusory. This provides an even more stringent test of our 24 competing models.

For this purpose, we simulated another 90,000 motion trajectories of the cube with medium elasticity (e = 0.5). From the total of 100,000 simulations of medium elasticity, we selected 23 sets of stimuli (one for each of the candidate motion features) for which

individual feature and multi-feature model predictions were essentially uncorrelated ($|r|$
< .05; see **Methods** and **Figure S6** for more details). A new group of 30 participants
judged the elasticity of these stimuli. Note that this rigorous stimulus selection process
risks diminishing the very effects we seek to find: We first narrow the range of features
by keeping elasticity constant and then select stimuli that, by definition, include outliers
with a low correlation between a given feature and PC1.

Although these careful steps may have limited our statistical power, Experiment 2
provided clear results. For each feature, **Figure 4A** shows the correlation of perceived
elasticity in the specific stimulus set (chosen for that feature) with the feature prediction
(x-axis) and the multi-feature model prediction (y-axis). Seventeen features show a
significantly lower correlation with perception than the multi-feature model ($p < .0022$,
Bonferroni corrected). Only for one feature—movement duration—does the correlation
with perception ($r = .45$) significantly exceed the multi-feature model ($r = .07$, $p < .0022$).
In other words, when brought directly into conflict, movement duration can explain
perceived elasticity better than a weighted feature combination. Thus, the high
correlation between the multi-feature model and perception in Experiment 1 is
presumably mediated by the contribution of movement duration (which has the third
highest loading of all features to PC1). Is movement duration also driving the high
correlations between the multi-feature model and perception in the other stimulus sets
of Experiment 2? **Figure S6E** shows the partial correlations between perception and
single features vs. perception and multi-feature model prediction when controlling for
the effect of movement duration. The correlations between perception and multi-
feature model ($r = .56 \pm .14$ (M ± SD)) decrease significantly when controlling for
movement duration ($r = .12 \pm .11$; $t(21) = 12.97$, $p < .001$), indicating that movement
duration is indeed the driving factor. Across all stimuli, movement duration was—
again—the best predictor of perceived elasticity ($R^2 = .78$, F(1, 223) = 787.61, $p < .001$,
see also **Figure 4B and S5D**). Thus, the longer an object moved in the scene, the more
elastic it appeared. Experiment 2 showed that this relation holds true even if physical
elasticity is constant, leading to a powerful perceptual illusion. **Video S2** demonstrates
these large, systematic, and robust illusory differences in apparent elasticity.

Figure 4. **Results of the decorrelation experiment**. **A)** *Correlation of the pooled perceptual ratings with the multi-feature model (y-axis) and the individual features (x-axis). Each dot represents the correlations for one set of stimuli that were specifically selected to decouple the prediction of one feature from the model. Features that fall below the diagonal (light blue shaded area) exceed the model, i.e., their predictions correlate more strongly with perception than the model does. Filled dots indicate a significant difference between the two correlation coefficients. Error bars show 95% confidence intervals. Please note, that the correlation coefficients are lower than in Experiment 1 because the data is pooled across participants (instead of averaged) to get a more reliable estimate from the small number of stimuli in each set. For the noise ceiling, we calculated for each stimulus set how much the pooled responses correlate with the average response. The noise ceiling shows the mean (± 95 % - CI) across features.* **B)** *Average elasticity ratings for all stimuli of Experiment 2 as a function of movement duration together with a linear fit. Elasticity ratings clearly increase with an increase in movement duration. All stimuli had the same physical elasticity of 0.5 (grey line). Thus, all perceived differences in elasticity between stimuli are illusory. See* **Video S2** *and* **Figure S6**.

Observers flexibly switch to another heuristic when movement duration is unobservable

Our everyday experience suggests that we are able to judge an object's elasticity even without observing for how long the object moves, e.g., if someone catches it before it comes to rest. To study systematically whether and how well people can estimate elasticity when this one cue is not available, we truncated a subset of the videos from Experiment 1 to exactly 1 second and presented these to a new group of 15 observers in **Experiment 3**, see **Video S3**. In these videos it was not possible to observe movement duration. Yet, we found that the average elasticity ratings increased systematically with physical elasticity (linear regression: R^2 = .73, F(1, 78) = 215.41, *p* < .001, see **Figure S7A**) and showed a near-perfect correlation (*r* = .97, *p* < .001) with ratings for the full movies (Exp. 1; see **Figure 5A**), although the consistency between observers was moderately lower here (*r* = .80 ± .16, M ± SD) than in Experiment 1 (*r* = .91 ± .04; *t*(28) = -

2.63, p = .05). How do observers infer elasticity when movement duration cannot be
observed? Do they rely on a different heuristic?

Truncating the videos altered most feature values, not just movement duration. **Figure**
5B shows how well the multi-feature model and the individual features can predict
physical as well as perceived elasticity in 1-sec movies. The multi-feature model was
the best at explaining both physics and perception and again better explains perception
than ground truth physics (R^2 = .77, F(1, 78) = 260.27, p < .001; evidence ratio:
$w_{FeatureModel}/w_{Physics}$ = 296.05; see also **Figure S7B**). Several individual features, particularly
those measuring the presence of large bounces in the trajectory (such as
maxArcLenFloor or maxBounceHt), also capture a large proportion of the variance in
perceived elasticity. To disentangle these competing, but correlated hypotheses, we
conducted **Experiment 4** following the same logic as in Experiment 2: From the dataset
of 100,000 cubes of medium elasticity, we first identified the simulations that had a
movement duration of at least 1 sec. For this subset, we calculated the motion features
for the first second and then selected 22 sets of stimuli (one set for each feature except
movement duration) in which the prediction of that feature individually was
uncorrelated with the prediction of the multi-feature model. A new group of 30
observers estimated elasticity in these 1-sec stimuli.

Again, we found that one of the most diagnostic features—maximum bounce height—
showed a significantly higher correlation with perception than the multi-feature model (r
= .54 > r = .25, p < .0023, **see Figure 5C**) when brought directly into conflict, and that
was the best predictor of perceived elasticity across all stimuli in Experiment 4 (R^2 = .74,
F(1, 197) = 565.56, p < .001, see **Figure 5D** and **S6C**). Thus, the higher the largest bounce
was, the more elastic the cube appeared even if the true elasticity was equal (see **Video**
S4). There was only one other feature—bounce duration—for which the correlation
between feature and perception was larger than the correlation between multi-feature
model and perception (r = .36 > r = .10, p < .0023). However, bounce duration did not
vary much in the stimulus set, because in most simulations the cube would have
bounced for longer than 1 second had the movie not been truncated (see **Figure S7E**).
Therefore, bounce duration was only a diagnostic feature when it was notably shorter
than one second. For most (12/22) features, we found that the multi-feature model
predicted the data better than the individual features (p < .0023, Bonferroni corrected).
Akin to the results of Experiment 2, these high correlations seemed to be driven by the
best single feature, maximum bounce height (see **Figure S7D**). More precisely, the
correlations between perception and multi-feature model (r = .49 ± .16 (M ± SD))
decreased significantly when controlling for maximum bounce height (r = .23 ± .09; t(21)
= 6.65, p < .001).

In sum, Experiment 4 showed that observers reported robust perceptual differences
between truncated stimuli even though all had the same physical elasticity. Perceived
elasticity was best explained by one of the most predictive features, maximum bounce
height. Intuitively this makes sense, as the maximal bounce height is easy to compute

(i.e., requires only one position) and it occurs within the first second in most trajectories
(94.1%, see **Figure S7F**). Taken together, this suggests that if unable to fully observe an
object's movement until it comes to a standstill, we instead form an impression of its
elasticity based on the highest of the bounces that it makes.
357

Figure 5. **Results of Experiments 3 and 4 with truncated movies**. *A) Average*
perceived elasticity in 1-sec movie clips (Exp. 3) as a function of the movement duration
of the apparent elasticity in full movies of the same stimuli. Physical elasticity is color-
*coded. **B**) Explained variance in terms of perceived elasticity (in Experiment 3) as a*
function of explained variance of physical elasticity in 1-sec movies (in the data set of
100,000) for individual features (blue), the multi-feature model (red). For a legend of
individual features see Figure 2G. The noise ceiling shows the average explained
*variance between individual subjects and the average subject (± 95%-CI). **C**) Correlation*
of the pooled perceptual ratings with the multi-feature model (y-axis) and the individual
features (x-axis). Each dot represents the correlations for one set of stimuli that were
specifically selected to decouple the prediction of one feature from the model. Features
that fall below the diagonal (light blue shaded area) exceed the model, i.e., their
predictions correlate more strongly with perception than the model does. Filled dots
indicate a significant difference between the two correlation coefficients. Error bars
show 95% confidence intervals. For the noise ceiling, we calculated for each stimulus
set how much the pooled responses correlate with the average response. The noise
*ceiling shows the mean (± 95 % - CI) across features. **D**) Average elasticity ratings of*
Experiment 4 as a function of the maximum bounce height together with a linear fit.

Elasticity ratings clearly increase with an increase in maximum bounce height. All
*stimuli had the same physical elasticity of 0.5 (grey line). See **Videos S3** and **S4**, and*
***Figure S7**.*

Discussion

Here we propose that when visually judging the physical properties of objects and
materials, people often represent them in terms of their typical appearance—i.e., in
terms of their typical mid-level spatiotemporal features. Specifically, our results
suggest that when asked to judge the elasticity of a bouncing object, observers judge
how long the object moves. If the motion duration is cut short, i.e., it cannot be
observed, observers instead rely on the maximal bounce height to judge elasticity. This
implies a flexible and computationally efficient strategy.

While this study is not the first to suggest a role of mid-level features in the estimation of
physical properties (Bi et al., 2019; Bi and Xiao, 2016; Kawabe et al., 2015; Kawabe and
Nishida, 2016; Paulun et al., 2017, 2015; Schmid and Doerschner, 2018; Schmidt et al.,
2017; Van Assen et al., 2018), it overcomes three critical limitations of previous work.
First, we assess the statistical relations between a diverse set of potential visual
features and physical elasticity in a large dataset and thereby show how—in principle—
observing the variations of motion features in many examples spontaneously reveal
elasticity and establish which features (or their combination) are best at doing so.
Second, to the best of our knowledge, no study has yet *manipulated* the proposed visual
cues to physical properties in naturalistic stimuli. Here, we achieved such manipulation
by using a large dataset to identify stimuli that decouple the inherently correlated
predictions of different models. Third, we identified *illusory* stimuli that decouple
feature predictions from ground truth physics. Thus, we not only predict the good overall
performance of observers in elasticity estimation but, critically, also their specific
perceptual errors on a stimulus-by-stimulus basis. Our findings have implications on
both theoretical and methodological levels.

Learning. We have previously hypothesized that by observing the outside world and its
inherent statistical relations (Fleming, 2014; Fleming and Storrs, 2019), the brain can
learn—in an unsupervised manner—many dimensions along which objects in our
environment vary. The statistical appearance model proposed here is not intended as a
model of this learning process, but rather a proof of principle about the learnability of
the cues and the impact that such unsupervised statistical observation approaches
have on perception. We found that by observing various motion features of bouncing
cubes, elasticity emerges spontaneously as the main dimension of variation. The
motion features themselves were not the result of learning from the stimulus set but
instead were explicit operationalizations of our hypotheses. This approach allowed
testing the contribution of a large, yet testable number of interpretable motion features
and their combination. Would similar features emerge from applying unsupervised or
self-supervised learning algorithms? It would be interesting to investigate this question

within different frameworks, from deep learning to program learning or simulation-
based learning. For example, might the same heuristics be derived within a mental
physics simulation model? How would the latent feature space of an (unsupervised)
deep learning model compare to the motion features identified here? However, it would
be practically impossible to test the individual contribution of the thousands of features
in the trained network to perceived elasticity. Yet, here, it is precisely this decoupling of
competing hypotheses that ultimately enabled us to predict human perception on a
stimulus-by-stimulus basis.

Mid-level features. One of our key findings is that when asked to estimate the elasticity
of bouncing objects, observers judge the movement duration or the maximal bounce
height in case the duration is visibly cut short. Crucially, this implies that the brain does
represent *multiple* features of bouncing objects at a time but does not combine them in
the sense of classic cue combination (Ernst and Banks, 2002) to estimate the latent
parameter (elasticity). If the brain represents bouncing objects in terms of their visual
motion features, as our results suggest, 'estimating elasticity' means determining the
relative position of the observed object on the feature manifold. Across four
experiments, we found that observers base their elasticity estimates on only 2-3 visual
features. Why would the brain rely on these and not on other features? Presumably, the
most effective features are both salient and inexpensive to compute. Movement
duration and maximum bounce height both capture important events in the observed
motion, i.e., the largest bounce and the end of the motion. It is not trivial to determine
the computational costs of different features. Yet, at a minimal level, it seems plausible
to assume that single measures, e.g., height or duration, will be computationally
cheaper than their derivatives or ratios. In that sense, movement duration and
maximum bounce height, are among the computationally simplest features we tested.
Duration and spatial distance are quantities the visual system can estimate reliably and
accurately (Buhusi and Meck, 2005; Eagleman, 2008; Eagleman et al., 2005; Epstein and
Rogers, 1995).

Even though we found strong evidence that humans base their elasticity estimates
mainly on two motion features, some other features may play an important role in
identifying the stimulus as a bouncing object in the first place. A key assumption of our
model is that the observed motion is due to a semi-elastic object bouncing in an
environment, as opposed to some other cause (e.g., animate motion (Scholl and
Tremoulet, 2000), fluid flow (Kawabe et al., 2015; Morgenstern and Kersten, 2017; Van
Assen et al., 2018)). If applied to other trajectories the resulting 'elasticity estimate'
would be meaningless, e.g., for a feather gliding in the wind or a driving car. An
important line of future research is to investigate the cues underlying the recognition
process through which we identify the stimulus as a bouncing object in the first place.

The motion features we tested here are stimulus-computable, yet they assume a
perfect representation of the object's trajectory. As such, they oversimplify the input
available to elasticity-estimating processes in the biological brain. For example,

humans have a more accurate representation of image-plane motions than motion in depth (Murdison et al., 2019; Welchman et al., 2008), and may not be equally sensitive to all velocities in these displays. Thus, to transform the heuristic model into a truly image-computable one, future work will also need to incorporate aspects of low-level vision, including object segmentation. Yet, we reasoned that important insights into the estimation of material properties can still be gained even without fully modeling all preceding processing stages.

Generalization. Deformable cubical objects produce diverse and complex trajectories. We have shown that visual motion features generalize across large variations caused by several independent factors. Movement duration and maximum bounce height are likely to generalize to some extent across other scenes and objects. For example, if the object had a different shape or if it interacted with other objects in a different space, higher elasticity objects would still tend to move longer and bounce higher. Participants presumably had little experience with bouncing non-rigid cubes prior to our experiments. Yet, they were broadly able to judge elasticity reliably, suggesting they could generalize from previous experience with other scenes and objects. In an experimental setting, it would be possible to break the relation between motion features and elasticity. For example, if the floor was completely inelastic, like sand, no object would rebound. It is, however, unlikely that human observers would be able to estimate the objects' elasticity in these cases. Thus, although motion features would not capture physical elasticity, they might still be reliable predictors of perceived elasticity. Because our model is stimulus computable (based on the true or estimated 3D position), such hypotheses can be easily tested in future research.

Simulation vs. heuristics. A current topic of active discussion is the extent to which physical perception and reasoning proceed through sophisticated but computationally costly internal simulations (Bates et al., 2019; Battaglia et al., 2013; Hamrick et al., 2016; Wu et al., 2015; Yildirim et al., 2018) or cheaper but potentially less accurate heuristics (Kubricht et al., 2017; Ludwin-Peery et al., 2021; Paulun et al., 2017, 2015). How do our results fit into this theoretical spectrum? Representing objects and materials in terms of their appearance features entails an understanding of the observable consequences of natural variations between objects, e.g., the ways in which elastic objects bounce. Yet, the resulting estimation strategy appears like a classic heuristic, i.e., a simple but sufficient rule of thumb such as "the longer it moves, the more elastic it is". In fact, our results could provide an explanation of how the brain derives such heuristics from observation alone and of how it switches from using one feature to another (i.e. when there is no variation along the first feature dimension). This does not mean that observers *cannot* simulate possible future behaviors of objects, such as how the trajectory of a bouncing cube continues, just that they may not choose to do so when simpler yet near-optimal heuristics are available. This interpretation is consistent with previous work by Battaglia and colleagues (Battaglia et al., 2013), who found that when a simple heuristic is a more efficient and optimal way to make a

prediction (e.g., "How far will the blocks fall when the block tower falls over?",
observers tend to use such heuristics (e.g., height of the tower) rather than simulation.
Thus, we suggest that observers can draw on different forms of computation, but do so
taking into consideration the relative costs and demands of the specific task at hand—
an example of *bounded* or *computational rationality* (Gershman et al., 2015; Gigerenzer
and Todd, 2001). For example, when asked to infer a single parameter (e.g., elasticity)
from an observed trajectory, time- and energy-consuming simulations represent a poor
allocation of resources when a simple read-out from the feature estimation provides
high accuracy. However, visual features are likely too inaccurate when making time- or
location-critical predictions about an object's future trajectory (Diaz et al., 2013; Mann
et al., 2019; Mrowca et al., 2018). Under these conditions, the additional costs
associated with internal simulation may pay off. Similarly, when no standard heuristics
apply, observers may use simulation even for physical inference of material properties,
such as mass, as shown by Hamrick et al (Hamrick et al., 2016). Future studies should
further investigate the different cognitive strategies humans use under various
circumstances as well as the metacognitive process that switches between different
strategies.

Conclusion

Visually estimating physical object properties is a crucial, yet computationally
challenging task. The visual input is highly ambiguous because an object's behavior
depends on numerous entangled factors. Estimating the elasticity of a bouncing object
requires disentangling the different causal contributions of elasticity, initial speed,
position, and other factors. Using a 'big data' approach, we showed that representing
trajectories in terms of their characteristic spatiotemporal features—such as the
maximum bounce height or movement duration—yields elasticity estimates that are
inexpensive to compute and robust to external factors. Our experiments suggest that
the brain estimates elasticity by flexibly switching between a few single-feature
heuristics based the information available in the stimuli. Our model explains both the
broad successes and the systematic failures of human elasticity perception and
correctly predicts a novel illusion in which appearance features maximally diverge from
ground truth. Observers can draw on multiple cues and computations, and appear to
select strategies with lower computational costs, i.e., computationally rationally.
Similar principles might underlie the visual perception of other physical objects
properties, such as mass or softness.

METHODS

Experimental model and study participant detail

Ninety undergraduate students (68 females) from the University of Giessen participated in the experiments (15 in Exp. 1 and 3, 30 in Exp. 2 and 4). Their average age was 24 years (SD = 3.5 years). No person participated in more than one experiment. All participants were naïve with regard to the aims of the study and they gave written informed consent before the experiment. Participants were compensated with 8€/h. The experimental procedure was in accordance with the declaration of Helsinki and approved by the local ethics committee (LEK FB06) at Giessen University.

Physical simulations

The dataset was created with the Caronte physics engine of RealFlow 2014 (V.8.1.2.0192; Next Limit Technologies, Madrid Spain), a 3D dynamic simulation software. The dataset contains 100,000 simulations of a cubical object (0.1 m^3) bouncing in a cubical room (1.0 m^3). We chose a cube as the target object because it produces a greater variety of trajectories than, for example, a sphere because the rebound direction depends not only on the direction of the object but also its orientation. We have previously shown that human observers can judge the elasticity of a bouncing cube in such a scene (Paulun and Fleming, 2020). We varied the cube's elasticity in ten equal steps from 0.0 to 0.9. This value corresponds to the coefficient of restitution—the proportion of energy the cube retains upon collision. We created 10,000 simulations for each level of elasticity by randomly varying its initial velocity, orientation, and position, while keeping all other parameters constant. We simulated 121 frames at 30 fps of the cube moving through the room under gravity. In addition to the original dataset, we simulated another 90,000 trajectories of just one elasticity (0.5). As before, initial velocity, orientation, and position varied randomly. We used the 90,000 simulations + 10,000 simulations of the medium elasticity from the original dataset to search for stimuli in Experiments 2 and 4. For all 190,000 simulations, we provide 3D positions of the cube's center of mass (CoM) and its eight corners across all 121 frames [LINK WILL BE INCLUDED UPON ACCEPTANCE].

Motion features and multi-feature model

We calculated 28 motion features based on the CoM and the eight corners of the cube for all 100,000 simulations. The end of the cube's movement was defined as the point at which its velocity dropped below 0.003 m/s, since simulated velocity never reaches zero. All other features were computed only for the frames in which the cube was moving. The exact definition of all 28 motion features is described in **Table S1** and **Figures S1-2**. Next, we normalized every motion feature to a range between [0.0, 1.0] and equalized their histograms. We determined the R^2-score, the shared variance with physical elasticity, for each feature and excluded features from further analysis if they explained <5% of the variance. We performed a principal component analysis (PCA)

with the remaining 23 features. The resulting scores of the first principal component
(PC) were used to predict perceived elasticity, see **Figure S3**.

Stimuli
Experiment 1 contained 15 stimuli per level of elasticity, randomly selected from the
original dataset (i.e., 150 stimuli). For Experiment 2 we selected 225 stimuli that
systematically decoupled the predictions of each individual feature from both the multi-
feature model and physical elasticity. Specifically, for each of the 23 features we chose
ten stimuli from the medium elasticity dataset for which the predictions of the individual
feature and the multi-feature model were uncorrelated ($|r| < 0.05$), while spanning the
widest possible range on both dimensions (**Figure S6A**). In Experiments 1 and 2, each
stimulus was presented for the full duration of the cube's movement. In Experiments 3
and 4, only the first second of each stimulus was presented (and no stimulus had a
movement duration that was shorter than 1 sec). For Experiment 3, we used a random
subset of eight stimuli per elasticity level from the stimuli of Experiment 1 (i.e., 80
stimuli). For Experiment 4, we selected 213 stimuli that systematically decoupled the
predictions of each individual feature (except movement duration) from both the
prediction of the multi-feature model and physical elasticity. The selection procedure
was the same as in Experiment 2, but all stimuli were truncated to exactly one second.

The simulations selected as stimuli were rendered using RealFlow's built-in Maxwell
renderer. The room was rendered with a white matte material, and the target object was
rendered with a blue opaque material. The scene was illuminated brightly using an HDR
map through the transparent ceiling. Stimuli of all experiments are available for
download at [LINK WILL BE INCLUDED UPON ACCEPTANCE].

Set up
All experiments were conducted using the same setup. Stimuli were presented on an
Eizo LCD monitor (ColorEdge CG277; resolution: 2560 × 1440 pixels; refresh rate: 60 Hz).
Participants used a chin rest to maintain a constant viewing distance of 54 cm. At this
distance, the stimuli had a visual angle of 19.6 x 19.6 degrees.

Procedure
All experiments followed the same basic procedure. Participants were instructed to
watch a short movie of an object and rate its elasticity. Elasticity was defined to them as
the property that distinguishes for example a bouncy ball from a hacky sack. On each
trial, one stimulus was presented in a loop until a response was given. Below the movie,
a horizontal rating bar was displayed, ranging from 'not elastic' to 'very elastic'.
Participants adjusted a slider along the bar to indicate their rating. Each stimulus was
repeated three times over the course of the experiment, and all stimuli were presented
in random order. Before the main experiment, participants completed ten practice

trials, one for each level of elasticity (unknown to participants) to provide an impression of the stimulus range without biasing their response scale. The experimental code was written in Matlab 2018a using Psychtoolbox 3 (Brainard, 1997; Kleiner et al., 2007; Pelli, 1997) and is available here [LINK WILL BE INCLUDED UPON ACCEPTANCE].

Analysis

In all experiments, we averaged across repetitions to obtain one rating per stimulus from every participant. For Experiments 1 and 3, we calculated the average across participants, as well as inter- and intra-observer variability (standard deviation). We fitted linear regression models to the average elasticity ratings using either physical elasticity, the multi-feature model, or each of the individual feature as predictors. Models were compared using AIC values, specifically their Akaike weights and evidence ratios (Burnham and Anderson, 2004). Akaike weights represent the probability that a given model is the best among those tested, while evidence ratios indicate the relative likelihood of two competing models given the data. For Experiments 2 and 4, we pooled the data across participants. For each feature's stimulus set, we computed correlations between pooled ratings and both the corresponding feature prediction and the multi-feature model prediction. Pooling (rather than averaging) allowed more reliable estimation of the correlation coefficients based on full trial counts rather than just 10 averages. For each feature, the resulting correlation coefficients were compared using a two-tailed significance test for dependent groups with one overlapping variable (Olkin, 1967). Additionally, we computed the explained variance in perceived elasticity (averaged across participants) for each feature and the model across *all* stimuli, independent of the stimulus set.

Supplemental information

Document S1. Figures S1–S6 and Table S1.
Video S1. Example stimuli from Experiment 1 (elasticity increases from left to right, full length movies), related to Figure 1.
Video S2. Elasticity Illusion from Experiment 2 (movement duration increases form left to right, constant elasticity (e = 0.5)), related to Figure 4.
Video S3. Example stimuli from Experiment 3 (elasticity increases from left to right, movies truncated to 1 second), related to Figure 5.
Video S4. Elasticity Illusion from Experiment 4 (maximum bounce height increases from left to right, constant elasticity (e = 0.5)), related to Figure 5.

Acknowledgments

The authors thank Britta Fritz, Saskia Honnefeller, Judith Kanehl, and Jasmin Kleis for their help with data collection. This research was funded by the Deutsche

652 Forschungsgemeinschaft (DFG, German Research Foundation; Project 222641018–
653 SFB/TRR 135 TP C1 and Project PA 3723/1-1) and by the European Research Council
654 (ERC) Advanced Grant "STUFF" (Project 101098225).

Author Contributions

656 VCP, FSB, and RWF conceived and designed the study, developed the features and
657 computational model. VCP simulated the data set, rendered the stimuli, collected and
658 analyzed the data, made the figures, and wrote a first draft of the manuscript. All
659 authors discussed the results and wrote and approved the manuscript.

References

Aliaga C, O'Sullivan C, Gutierrez D, Tamstorf R. 2015. Sackcloth or silk?: the impact of appearance vs
dynamics on the perception of animated cloth. Proceedings of the ACM SIGGRAPH
Symposium on Applied Perception. Presented at the SAP '15: ACM Symposium on Applied
Perception 2015. Tübingen Germany: ACM. pp. 41–46. doi:10.1145/2804408.2804412
Bates CJ, Yildirim I, Tenenbaum JB, Battaglia P. 2019. Modeling human intuitions about liquid flow
with particle-based simulation. *PLoS Comput Biol* **15**:e1007210.
doi:10.1371/journal.pcbi.1007210
Battaglia PW, Hamrick JB, Tenenbaum JB. 2013. Simulation as an engine of physical scene
understanding. *Proc Natl Acad Sci USA* **110**:18327–18332. doi:10.1073/pnas.1306572110
Bi W, Jin P, Nienborg H, Xiao B. 2019. Manipulating patterns of dynamic deformation elicits the
impression of cloth with varying stiffness. *Journal of Vision* **19**:18. doi:10.1167/19.5.18
Bi W, Shah AD, Wong KW, Scholl B, Yildirim I. 2021. Perception of soft materials relies on physics-
based object representations: Behavioral and computational evidence. *bioRxiv* 2021–05.
Bi W, Xiao B. 2016. Perceptual constancy of mechanical properties of cloth under variation of
external forcesProceedings of the ACM Symposium on Applied Perception. Presented at the
SAP '16: ACM Symposium on Applied Perception 2016. Anaheim California: ACM. pp. 19–23.
doi:10.1145/2931002.2931016
Brainard DH. 1997. The Psychophysics Toolbox. *Spat Vis* **10**:433–436.
Buhusi CV, Meck WH. 2005. What makes us tick? Functional and neural mechanisms of interval
timing. *Nat Rev Neurosci* **6**:755–765. doi:10.1038/nrn1764
Burnham KP, Anderson DR. 2004. Multimodel Inference: Understanding AIC and BIC in Model
Selection. *Sociological Methods & Research* **33**:261–304. doi:10.1177/0049124104268644
Diaz G, Cooper J, Rothkopf C, Hayhoe M. 2013. Saccades to future ball location reveal memory-based
prediction in a virtual-reality interception task. *Journal of Vision* **13**:20. doi:10.1167/13.1.20
Eagleman DM. 2008. Human time perception and its illusions. *Curr Opin Neurobiol* **18**:131–136.
doi:10.1016/j.conb.2008.06.002
Eagleman DM, Tse PU, Buonomano D, Janssen P, Nobre AC, Holcombe AO. 2005. Time and the Brain:
How Subjective Time Relates to Neural Time. *J Neurosci* **25**:10369–10371.
doi:10.1523/JNEUROSCI.3487-05.2005
Epstein W, Rogers S, editors. 1995. Perception of Space and Motion. Elsevier. doi:10.1016/b978-0-
12-240530-3.x5000-7
Ernst MO, Banks MS. 2002. Humans integrate visual and haptic information in a statistically optimal
fashion. *Nature* **415**:429–433.

Fikes TG, Klatzky RL, Lederman SJ. 1994. Effects of Object Texture on Precontact Movement Time in
695   Human Prehension. *Journal of Motor Behavior* **26**:325–332.
696   doi:10.1080/00222895.1994.9941688

697   Fleming RW. 2014. Visual perception of materials and their properties. *Vision Research* **94**:62–75.
698   doi:10.1016/j.visres.2013.11.004

699   Fleming RW, Storrs KR. 2019. Learning to see stuff. *Curr Opin Behav Sci* **30**:100–108.
700   doi:10.1016/j.cobeha.2019.07.004

701   Gershman SJ, Horvitz EJ, Tenenbaum JB. 2015. Computational rationality: A converging paradigm for
702   intelligence in brains, minds, and machines. *Science* **349**:273–278.
703   doi:10.1126/science.aac6076

704   Gigerenzer G, Todd PM. 2001. Simple heuristics that make us smart, 1. issued as an Oxford Univ.
705   Press paperback. ed, Evolution and cognition. New York: Oxford University Press.

706   Glowania C, van Dam LCJ, Brenner E, Plaisier MA. 2017. Smooth at one end and rough at the other:
707   influence of object texture on grasping behaviour. *Exp Brain Res* **235**:2821–2827.
708   doi:10.1007/s00221-017-5016-2

709   Hamrick JB, Battaglia PW, Griffiths TL, Tenenbaum JB. 2016. Inferring mass in complex scenes by
710   mental simulation. *Cognition* **157**:61–76. doi:10.1016/j.cognition.2016.08.012

711   Kawabe T, Maruya K, Fleming RW, Nishida S. 2015. Seeing liquids from visual motion. *Vision Research*
712   **109**:125–138. doi:10.1016/j.visres.2014.07.003

713   Kawabe T, Nishida S. 2016. Seeing jelly: judging elasticity of a transparent objectProceedings of the
714   ACM Symposium on Applied Perception, SAP '16. New York, NY, USA: Association for
715   Computing Machinery. pp. 121–128. doi:10.1145/2931002.2931008

716   Kirillov A, Mintun E, Ravi N, Mao H, Rolland C, Gustafson L, Xiao T, Whitehead S, Berg AC, Lo W-Y,
717   Dollár P, Girshick R. 2023. Segment Anything. doi:10.48550/arXiv.2304.02643

718   Klein LK, Maiello G, Paulun VC, Fleming RW. 2020. Predicting precision grip grasp locations on three-
719   dimensional objects. *PLOS Computational Biology* **16**:e1008081.
720   doi:10.1371/journal.pcbi.1008081

721   Kleiner M, Brainard D, Pelli D, Ingling A, Murray R, Broussard C. 2007. What's new in psychtoolbox-3.
722   *Perception* **36**:1–16.

723   Krizhevsky A, Sutskever I, Hinton GE. 2012. ImageNet Classification with Deep Convolutional Neural
724   NetworksAdvances in Neural Information Processing Systems. Curran Associates, Inc.

725   Kubricht JR, Holyoak KJ, Lu H. 2017. Intuitive Physics: Current Research and Controversies. *Trends in*
726   *Cognitive Sciences* **21**:749–759. doi:10.1016/j.tics.2017.06.002

727   Ludwin-Peery E, Bramley NR, Davis E, Gureckis TM. 2021. Limits on simulation approaches in intuitive
728   physics. *Cognitive Psychology* **127**:101396. doi:10.1016/j.cogpsych.2021.101396

729   Mann DL, Nakamoto H, Logt N, Sikkink L, Brenner E. 2019. Predictive eye movements when hitting a
730   bouncing ball. *Journal of Vision* **19**:28. doi:10.1167/19.14.28

731   Morgenstern Y, Kersten DJ. 2017. The perceptual dimensions of natural dynamic flow. *Journal of*
732   *Vision* **17**:7. doi:10.1167/17.12.7

733   Motamed S, Culp L, Swersky K, Jaini P, Geirhos R. 2025. Do generative video models understand
734   physical principles? doi:10.48550/arXiv.2501.09038

735   Mrowca D, Zhuang C, Wang E, Haber N, Fei-Fei LF, Tenenbaum J, Yamins DL. 2018. Flexible neural
736   representation for physics predictionAdvances in Neural Information Processing Systems.
737   Curran Associates, Inc.

Murdison TS, Leclercq G, Lefèvre P, Blohm G. 2019. Misperception of motion in depth originates from
an incomplete transformation of retinal signals. *Journal of Vision* **19**:21.
doi:10.1167/19.12.21

Nusseck M, Lagarde J, Bardy B, Fleming R, Bülthoff HH. 2007. Perception and prediction of simple
object interactionsProceedings of the 4th Symposium on Applied Perception in Graphics and
Visualization. Presented at the APGV07: ACM Symposium on Applied Perception in Graphics
and Visualization 2007. Tubingen Germany: ACM. pp. 27–34. doi:10.1145/1272582.1272587

Olkin I. 1967. Correlations revisited In: Stanley JC, editor. Improving Experimental Design and
Statistical Analysis. Rand McNally. pp. 102–128.

Paulun VC, Fleming RW. 2020. Visually inferring elasticity from the motion trajectory of bouncing
cubes. *Journal of Vision* **20**:6. doi:10.1167/jov.20.6.6

Paulun VC, Gegenfurtner KR, Goodale MA, Fleming RW. 2016. Effects of material properties and
object orientation on precision grip kinematics. *Exp Brain Res* **234**:2253–2265.
doi:10.1007/s00221-016-4631-7

Paulun VC, Kawabe T, Nishida S, Fleming RW. 2015. Seeing liquids from static snapshots. *Vision
Research* **115**:163–174. doi:10.1016/j.visres.2015.01.023

Paulun VC, Schmidt F, van Assen JJR, Fleming RW. 2017. Shape, motion, and optical cues to stiffness
of elastic objects. *Journal of Vision* **17**:20. doi:10.1167/17.1.20

Pelli DG. 1997. The VideoToolbox software for visual psychophysics: transforming numbers into
movies. *Spat Vis* **10**:437–442.

Schmid AC, Doerschner K. 2018. Shatter and splatter: The contribution of mechanical and optical
properties to the perception of soft and hard breaking materials. *Journal of Vision* **18**:14.
doi:10.1167/18.1.14

Schmidt F, Paulun VC, Van Assen JJR, Fleming RW. 2017. Inferring the stiffness of unfamiliar objects
from optical, shape, and motion cues. *Journal of Vision* **17**:18. doi:10.1167/17.3.18

Scholl BJ, Tremoulet PD. 2000. Perceptual causality and animacy. *Trends Cogn Sci* **4**:299–309.
doi:10.1016/s1364-6613(00)01506-0

Szegedy C, Wei Liu, Yangqing Jia, Sermanet P, Reed S, Anguelov D, Erhan D, Vanhoucke V, Rabinovich
A. 2015. Going deeper with convolutions2015 IEEE Conference on Computer Vision and
Pattern Recognition (CVPR). Presented at the 2015 IEEE Conference on Computer Vision and
Pattern Recognition (CVPR). Boston, MA, USA: IEEE. pp. 1–9. doi:10.1109/cvpr.2015.7298594

Tung H-Y, Ding M, Chen Z, Bear DM, Gan C, Tenenbaum JB, Yamins DLK, Fan J, Smith KA. n.d.
Physion++: Evaluating Physical Scene Understanding that Requires Online Inference of
Different Physical Properties.

Van Assen JJR, Barla P, Fleming RW. 2018. Visual Features in the Perception of Liquids. *Current
Biology* **28**:452-458.e4. doi:10.1016/j.cub.2017.12.037

Warren WH, Kim EE, Husney R. 1987. The Way the Ball Bounces: Visual and Auditory Perception of
Elasticity and Control of the Bounce Pass. *Perception* **16**:309–336. doi:10.1068/p160309

Weir PL, MacKenzie ,Christine L., Marteniuk ,Ronald G., Cargoe ,Sherri L., and Frazer MB. 1991a. The
Effects of Object Weight on the Kinematics of Prehension. *Journal of Motor Behavior* **23**:192–
204. doi:10.1080/00222895.1991.10118362

Weir PL, MacKenzie CL, Marteniuk RG, Cargoe SL. 1991b. Is Object Texture a Constraint on Human
Prehension!: Kinematic Evidence. *Journal of Motor Behavior* **23**:205–210.
doi:10.1080/00222895.1991.10118363

Welchman AE, Lam JM, Bülthoff HH. 2008. Bayesian motion estimation accounts for a surprising bias
in 3D vision. *Proc Natl Acad Sci USA* **105**:12087–12092. doi:10.1073/pnas.0804378105

Wu J, Yildirim I, Lim JJ, Freeman B, Tenenbaum J. 2015. Galileo: Perceiving physical object properties
by integrating a physics engine with deep learning. *Advances in neural information*
processing systems **28**.
Yildirim I, Smith KA, Belledonne ME, Wu J, Tenenbaum JB. 2018. Neurocomputational modeling of
human physical scene understanding.
789