Flattening the curve - How to get better results with small deep-mutational-scanning datasets

Gregor Wirnsberger[1], Iva Pritišanac[2,4], Gustav Oberdorfer[3,4], Karl Gruber[1,4*]

1 Institute of Molecular Biosciences, University of Graz, Graz, Austria
2 Institute of Molecular Biology and Biochemistry, Medical University of Graz, Graz, Austria
3 Institute of Biochemistry, Graz University of Technology, Graz, Austria
4 BioTechMed-Graz, Austria

*karl.gruber@uni-graz.at

Abstract

Proteins are utilised in various biotechnological applications, often requiring the optimisation of protein properties by introducing specific amino acid exchanges. Deep mutational scanning (DMS) is an effective high-throughput method for evaluating the effects of these exchanges on protein function. DMS data can then inform the training of a neural network to predict the impact of mutations. Most approaches employ some representation of the protein sequence for training and prediction. As proteins are characterised by complex structures and intricate residue interaction networks, directly providing structural information as input reduces the need to learn these features from the data.

We introduce a method for encoding protein structures as stacked 2D contact maps, which capture residue interactions, their evolutionary conservation, and mutation-induced interaction changes. Furthermore, we explored techniques to augment neural network training performance on smaller DMS datasets.

To validate our approach, we trained three neural network architectures originally used for image analysis on three DMS datasets, and we compared their performances with networks trained solely on protein sequences. The results confirm the effectiveness of the protein structure encoding in machine learning efforts on DMS data. Using structural representations as direct input to the networks, along with data augmentation and pre-training, significantly reduced demands on training data size and improved prediction performance, especially on smaller datasets, while performance on large datasets was on par with state-of-the-art sequence convolutional neural networks. The methods highlighted here have the potential to expand the applicability of DMS by reducing experimental requirements and by making it accessible to cases where true high-throughput screening is not feasible. Additionally, we present an open-source, user-friendly software tool to make these data analysis techniques accessible, particularly to biotechnology and protein engineering researchers who wish to apply them to their mutagenesis data.

Author summary

We introduce a novel approach to improve predictions of protein properties based on deep mutational scanning (DMS) data. Our method utilizes a unique data representation for protein structures through stacked 2D contact maps, which capture

residue interactions and alterations in these interactions due to amino acid substitutions, as well as evolutionary conservation. We also tested several techniques to enhance the performance of neural networks when trained on small datasets. By training three neural network architectures on three public DMS datasets, we demonstrate the value of integrating protein structure information in training neural networks to predict the effects of amino acid substitutions. Utilizing structural information along with data augmentation and pre-training significantly improves performance on smaller datasets compared to state-of-the-art sequence convolutional neural networks while achieving similar performance on larger datasets. Thus, our approach could substantially reduce the experimental input needed and provide valuable predictions even for smaller DMS datasets when high-throughput screening is not feasible.

Introduction

Proteins are found in viruses, bacteria, plants, and humans and fulfil a huge number of different functions and tasks in living organisms. Given their enormous functional diversity, proteins also present an attractive platform for various applications in biotechnology and bioengineering. However, naturally occurring proteins often require optimization for such non-native uses. One common method of protein optimization involves the substitution of specific amino acids, which can significantly enhance or alter the protein's function as, for instance, observed in the increased brightness of fluorescent proteins [1], or in antibody binding target modifications [2].

Amino acid substitutions can profoundly affect the properties of proteins, with mutagenesis providing a potent tool for evaluating these effects. A powerful technique for gaining comprehensive insights into genotype-phenotype relationships is deep mutational scanning (DMS) [3]. This approach enables the creation of expansive datasets depicting the effects of mutations on a given protein. DMS combines some type of protein display, which provides a physical link between a protein and its encoding nucleic acid sequence, with high-throughput sequencing, allowing for the characterization of up to 10^5 protein variants. The methodology involves applying selective pressure based on the protein's function to a diverse library of protein variants, which are sequenced before and after selection. High-throughput sequencing then quantifies the abundance of each variant. Throughout selection, variants with beneficial mutations become enriched, while those with deleterious mutations become depleted, offering a means to quantify the fitness of a vast sequence diversity for a protein of interest [4]. The broad applicability of DMS is demonstrated in its diverse uses, such as investigating the sequence determinants of $A\beta$ aggregation in Alzheimer's disease [5], probing protein binding behaviour [6], forecasting the evolutionary trajectories of human H3N2 influenza variants [7], optimizing antimicrobial peptides [8], and elucidating the effects of mutations in SARS-CoV-2 proteins [9] [10].

DMS experiments have increasingly become the method of choice for a host of projects aiming to achieve specific engineering goals. As the number of these experiments grows, there is an increasing demand for user-friendly predictive methods tailored to this kind of data. Consequently, a variety of methods have been developed to predict the effects of mutations in proteins. Some of these methods rely solely on evolutionary data and omit experimentally determined data to predict the functional consequences of amino acid substitutions. These approaches include, for example, the use of hidden Markov models [11], Potts models (EVmutation [12]), and variational autocoders (DeepSequence [13]). Others are natural language processing models, which are strongly influenced by the training approaches used in their field of origin. They get pre-trained in an unsupervised manner on a large amount of data and then fine-tuned on the prediction task. Here, models like LSTM [14] and transformer [15] are used.

Additionally, there are models that employ decision tree ensembles (like Envision [16]) trained on deep mutational scanning data or use Gaussian processes [17] for predictions. Often, these models, particularly those grounded in natural language processing (NLP), take only the protein sequence as input. Other models, such as Envision, integrate structural features into their framework but tend to utilize more general features like secondary structures and solvent accessibility instead of harnessing the unique information that each amino acid can offer.

Another important aspect in training ML models is training efficient encoding of the underlying data. In the case of proteins, this can be the amino acid sequence alone without any 3D information [18], a graph representation of the protein structure [18], or voxel-based spatial structural encoding [19]. In recent years, models used in natural language processing have increasingly been applied to problems with proteins. Although these models are very powerful and can produce great results, they tend to need a massive number of parameters, leading to high memory and computation requirements [20].

Since protein structure is more conserved than sequence [21], we created a - to our knowledge - new encoding for protein structures to take advantage of the information contained in the 3D structure. The encoding consists of 2D contact maps representing different physico-chemical properties of amino acids and their accompanying interaction, as well as the evolutionary conservation of each interacting residue in the structure (Section 0.3). In addition, this encoding allows the use of standard architectures for image classification networks, thus giving access to a large number of different architectures that can be used to solve this problem. Furthermore, we create a helpful pre-training and data augmentation protocol that helps to improve results when only a small amount of data is available (Fig. 1).

In evaluating the applicability and performance of our approach under the constraints of limited training data, we trained various architectures on datasets ranging from 50 to 6000 samples. For this analysis, we utilized sub-datasets that mirror the fitness score distribution of the complete datasets. This approach provides insight into the number of lab-tested variants required as training data to reliably model the underlying fitness score distribution of a protein's fitness landscape.

We assessed the performance of the same architecture with both sequence input and our structure representation, as well as the impact of pre-training and data augmentation. For this purpose, we relied on a recently published study by Gelman *et al.* [18]. Their work offers a comprehensive analysis of DMS datasets and evaluates the applicability of networks trained with sequence input on large datasets. Since these authors employed a simpler convolutional neural network architecture (CNN), we were able to use the same network architecture for our approach, enabling comparisons that are not influenced by architecture complexity or the use of distinct neural network architectures. This also facilitated comparisons with more complex CNN architectures and their potential benefits.

We further examined the performance of architectures with fewer parameters, revealing that while our representation provides an advantage, data augmentation and pre-training are crucial for optimal performance. Our workflow also demonstrated robust performance with an architecture that significantly reduces the number of parameters.

To promote the utilization of these methods in biotechnology and protein engineering, we provide open-source software featuring a user-friendly command line interface designed to be accessible also to non-ML experts. Executing the program with new DMS data requires minimal input, but the software also provides numerous advanced settings if needed in specific cases.

Fig 1. Overview of the training and prediction workflow. Initially, models are pre-trained on predicting a pseudo score that arises from the data representation (consisting of stacked 2D contact maps representing different physico-chemical properties and evolutionary information). This helps the model adjust its weights to the kind of prediction it will later be used for while not requiring additional data acquisition. Data augmentation is applied to up-size the training data to improve the prediction quality further. This is then used to train the network on experimentally determined (fitness-) scores of the protein of interest. In the end, the trained model can be used to predict these scores and, therefore, the effects of amino acid exchanges in the protein that were not experimentally determined. It is also possible to omit pretraining and data augmentation and train the network solely on experimentally determined data. Three different network architectures were used in this study, but they can be easily changed to any architecture of choice that accepts the input in the form of the data representation.

Materials and methods

0.1 Data

In our study, we utilized DMS data previously prepared and used in the study by Gelman *et al.* [18]. We specifically chose data from avGFP, Pab1, and GB1, as these proteins demonstrated the best results in their study, making them ideal for comparison as the data set quality does not influence the results. As Gelman *et al.* [18] already explored the influence of data quality on learning performance, finding a strong correlation between predictive performance and data quality, we opted to use these three high-quality datasets and then tested the influence of dataset size, pretraining, data augmentation, encoding, and network architecture. A limited analysis, which included only the optimal settings and one of the three architectures used, was performed on two lower-quality datasets (Bgl3 and Ube4B) also used in [18], where they exhibited poorer performance. Regarding protein structures, we also relied on data used in [18] to ensure the sequence, and consequently, the structure matched the DMS data.

Therefore, we used the PDB files of these structures provided in the corresponding GitHub repository [22].

The DMS datasets also contain nonsense mutations. We chose not to use assay scores for proteins featuring one or more nonsense mutations since these scores would represent protein fragments and thus would not reflect the properties of the wild-type protein containing a particular mutation. We, therefore, modified the datasets to exclude all nonsense mutations during training, validation, and testing.

0.2 Dataset preparation

Data and dataset selection can have an impact on the performance of the neural network. In order to avoid any advantage or bias through the use of only specific subsections of the data, e.g. an example would be only low DMS scores, we selected the training, validation and test dataset in the following procedure: The whole dataset war randomly shuffled. The first n data points were used as training data, the next $n \times 0.2$ samples were used as validation data during the training, and the next 5000 data points were used as test dataset after the training, where n is the training data size. This ensures that the training-, validation- and test datasets are completely disjoint and do not feature overlapping data. Since the artificially created pretraining data has a Pearson correlation of around -0.5 to the DMS data, the pretraining datasets were created so that the data points in the pretraining dataset do not feature mutations that are in the test dataset to ensure no knowledge leak and an unbiased test result. This lead to training- and test datasets that feature a similar DMS score distribution as the whole dataset and therefore build a representative sample (Figure: S1 - S3).

0.3 Interactions and their encoding

To emulate the effect of different mutations in a protein, we create interaction matrices that use a set of different amino acid properties to describe the interactions between residues in a protein and their change due to mutations. Additionally, a matrix that encodes the evolutionary conservation of interacting residues and an index matrix are used. Visual representations of the individual matrices, using Pab1 as an example, can be found in Fig. S4. This encoding method relies on the availability of the complete structure of the protein. In real-world scenarios, experimental structural data might not always be available or complete. However, there are a variety of approaches to address this issue, such as filling missing loops or even using advanced protein structure prediction tools like AlphaFold [23] to model the entire protein structure. In a worst-case scenario, in which only incomplete structures are available, the encoding can still work but would require dataset modifications (*e.g.*, index adjustments based on the missing residues).

0.3.1 Distance Matrix

To know which residues interact with each other, the protein's crystal structure is used. The coordinates of all atoms of the protein structure are stored in the corresponding PDB file [24].

$$d_{\mathrm{ij}} = \sqrt{(x_i - x_j)^2 + (y_i - y_j)^2 + (z_i - z_j)^2} \tag{1}$$

These are used to calculate the distance (d_{ij}) between all atoms of the protein (Eq: 1). Interacting residues are identified by checking the closest distance between side chain atoms of two residues, i and j. Using this approach, the smallest distances between all residues are calculated, and a symmetric $n \times n$ distance matrix (D), where n denotes

the sequence length, is generated. Using equation 2, this matrix is then used to generate
a so-called factor matrix (F).

$$F_{ij} = 1 - \frac{d_{ij}}{max(D)} \tag{2}$$

where d_{ij} denotes the distance between two residues and $max(D)$ the biggest distance
seen in the structure.
This factor matrix is used to scale the "strength" of the interactions in all subsequent
matrices (apart from the position matrix (P)) by calculating the Hadamard product
(element-wise product) of F with each interaction matrix. Elements in F which
correspond to distances larger than 20 Å are set to zero. This leads to a higher value for
close interactions and a lower one for interactions of residues that are further apart and,
in addition, masks interactions that originate from residues that are further apart than
20 Å.

0.3.2 Index Matrix

Convolution neural networks (CNN) are translation invariant. This is one of the
features that make them powerful in image recognition tasks since they can find
patterns they have learned anywhere in an image and not rely on their position. In our
case, this translation invariance is an undesirable feature because the positions of the
interactions matter. To combat this issue, we introduce a simple position matrix (P). It
describes the position of each interaction in the matrices based on the index matrix I
(Fig. 2). To calculate P, the Hadamard product of D and I is formed where D is set to 1
for distances smaller than $dist_{th}$ and to 0 for bigger distances.

$$I = \begin{bmatrix} 0 & 1 & 2 & 3 \\ 1 & 0 & 6 & 7 \\ 2 & 6 & 0 & 11 \\ 3 & 7 & 11 & 0 \end{bmatrix}$$

Fig 2. Sample index matrix before normalising the values to be in the range $[0, 1]$

0.3.3 Hydrogen Bonding

The number of hydrogen bonds is one of the factors that determine the stability of a
protein. Therefore it is a crucial kind of interaction since mutations that introduce
hydrogen bonding capabilities or remove them will thus alter this property. Not all
amino acids have the same capability of forming hydrogen bonds with their side chain.
Some can only act as a donor(K, R, W), some as an acceptor (D, E), some as donors or
acceptors (H, N, Q, S, T, Y) and some are not able to form hydrogen bonds with their
side chain at all (A, C, F, G, I, L, M, P, V).
The hydrogen bonding matrix B features a value of 1 for interactions formed by a donor
and an acceptor, by a donor and an acceptor/donor, by an acceptor acceptor/donor or
by an acceptor/donor acceptor/donor pair or a value of 0 otherwise.

0.3.4 Hydrophobicity

Proteins often contain a hydrophobic core and a hydrophilic outside that interacts with
its surroundings. The hydrophobic core plays an important role in the folding process of
a protein. Therefore, mutations that change the hydrophobicity in certain areas of a
protein can have positive and negative effects.

The hydrophobicity values used are obtained from Parrot [25]. The hydrophobicity values range from -4.5 for arginine to 4.5 for isoleucine.

$$H_{ij} = 1 - \frac{|h_i - h_j|}{9} \tag{3}$$

where h denotes the hydrophobicity of a certain residue, and 9 is the maximum possible hydrophobicity difference.
The hydrophobicity matrix (H) (Eq: 3) describes how well-interacting residues match in terms of their hydrophobicity.

0.3.5 Charge

There are three main types of amino acids in terms of charge. They can be divided into neutral (A, C, F, G, I, L, M, N, P, Q, S, T, W, Y), positively (R, H, K) and negatively (D, E) charged. Salt bridges, which are interactions of residues of opposite charge, are, besides hydrogen bonds, another type of interaction that is important for the stability of a protein. On the other side, amino acids with the same charge may repel each other and thereby destabilise the structure of a protein. To obtain the charge matrix (C) (Eq: 4), interactions of positively charged amino acids get a value of 1 assigned, interactions of amino acids carrying the same charge get a value of -1 assigned, and all other interactions get a value of 0 assigned.

$$C_{ij} = c_i \times c_j \times -1 \tag{4}$$

where c denotes the charge "value" of a certain residue encoded.

0.3.6 Surface accessible side chain area

Amino acids feature a variety of different sizes of their side chain. This is reflected in the difference in their surface accessible side chain area (SASA). The bigger the SASA, the higher the possibility for a (strong) interaction. Therefore a mutation that changes the interaction area between two interacting residues can have an influence on their interaction strength. The SASA values are obtained from Parrot [25], ranging from 0 for glycine to 254 for tryptophan.

$$A_{ij} = \frac{a_i + a_j}{max_{\text{SASA}} \times 2} \tag{5}$$

a denotes the interaction area of a certain residue and max_{SASA} the maximum SASA value for an amino acid.
The interaction area matrix (A) (Eq: 5) describes the interaction area between residues.

0.3.7 Clashes

Amino acids also differ in the length of their side chains. That means certain mutations can lead to potential "holes" in a protein if the side chains get shorter or potential clashes because the side chains are too long for the space between them.

$$X_{ij} = \frac{\Delta l_i + \Delta l_j + d_{ij}}{2 \times max_l + dist_{\text{th}}} \tag{6}$$

Δl denotes the change in the side chain length at a certain residue position from wild-type to the variant, max_l the maximum side chain length and $dist_{\text{th}}$ the maximum allowed distance between two residues to count as interacting.

Side chain lengths range from 0 Å for glycine to 8.28 Å for arginine. The values of the side chain length are obtained by measuring the distance from the Cα to the side chain atom with the biggest distance using Pymol [26]. The clash matrix (X) (Eq: 6) represents the distances between interacting side chain residues. If a mutation leads to a distance between two residues that is closer than the distance between them in the wild-type, a negative length value is created. This makes this matrix, besides the charge matrix C, the only matrix where values are in the range of [-1, 1] instead of [0, 1].

0.3.8 Evolution

To make use of the evolutionary information that can be obtained through blastp [27], we create a matrix (E)(Eq: 7) based on the conservation of amino acids at each sequence position. Therefore we use the result of a blastp search against the wild-type protein sequence with its default settings against the experimental clustered non-redundant database and align the obtained sequences as well as the wild-type sequence using the multiple sequence alignment tool clustal omega [28]. From this, the duplicated sequences get removed. To calculate the conservation at each sequence position, all present amino acids get counted at each position in the aligned wild-type sequence, and their number gets divided by the total number of amino acids at the specific sequence position. Amino acids that are not present at this position get a value of zero assigned. To evaluate the conservation of an interaction, the conservation scores of the interacting residues get multiplied. The evolutionary information gained through this approach could also be integrated via e.g. a separate branch of the neural network but was chosen because this representation was easier incorporated into the existing network structure. Additionally, this representation encodes the change in the conservation of an interaction based on the exchanged amino acid(s).

$$E_{\mathrm{ij}} = e_{\mathrm{i}} \times e_{\mathrm{j}} \tag{7}$$

e denotes the conservation score of the current amino acid at its specific sequence position.
Figure S4 shows an example of all interaction matrices (B, H, C, A, X) for Pab1 containing the mutation "N127R, A178H, G177S, A178G, G188H, E195K, L133M, P125S" as well as the position matrix (P), the interaction matrix (M) which describes which residues interact with each other and the distance matrix (D).

0.4 Network architectures

0.4.1 Simple CNN

Since we wanted to compare our structure representation to the sequence convolution approach (Section: 0.4.4), a LeNet5 [29] - like convolutional neural network (Fig. S5) was used. It contains a feature extraction part containing three 2D convolution layers with 16, 32 and 64 filters and a kernel size of 3×3, each followed by a max pooling layer. After that comes a flatten layer and a classifier part consisting of 4 fully connected layers with 128, 256, 256 and 64 nodes and a single output node. We used the leaky rectified linear unit (leaky RELU) as the activation function for all layers in the model. Zero-padding is used throughout the whole network. This model is referred to as "simple CNN".

0.4.2 DenseNet

To compare the performance to a more recently described architecture, we chose to use a DenseNet [30] - like architecture (Fig. S6), which will be referred to as "DenseNet".

Here the core building block consists of a 2D convolution layer with 128 filters and a kernel size of 1×1, followed by a 2D convolution layer with 12 filters and a kernel size of 3×3. Zero-padding is used throughout the whole network to keep each layer's input and output dimensions the same. The input into the first 2D convolution layer and the output of the second get concatenated. This is repeated 4 (*block depth*) times and is then followed by a 2D average pooling layer with a kernel size of 2×2. All this combined is one block, and this is repeated 4 (*block number*) times. In the end, a 2D global average pooling layer is followed by a fully connected network with 128, 128, and 64 nodes per layer leading into one output node. Additionally, we used an "intro layer" for avGFP, which consists of a 2D convolution layer with 128 filters, a kernel size of 3×3 and a stride of 2 followed by a 2D max pooling layer with a kernel size of 3 and a stride of 2 at the beginning of the network. This reduces the size of the input and thereby reduces the number of computations needed in the rest of the network. In contrast to the original DenseNet we omitted batch normalisation because it led to worse performance and used the leaky RELU instead of RELU as activation function.

0.4.3 SepConvMixer

To test the performance of a network with as few parameters as possible, we implemented an architecture (Fig. S7) similar to ConvMixer [31]. Sequence convolution requires up to 82 times, simple CNN up 185 times, and DenseNet up to 21 times the number of parameters in our settings (Table 4). The two main contributors to the reduction of the number of parameters were the possibility of using a smaller fully connected network as classifier as well as the use of 2D separable convolution layers. The latter first performs a depth-wise spatial convolution, which acts separately on each input channel and is followed by a point-wise convolution to mix the resulting output channels. The network starts with one 2D separable convolution layer with 32 filters where we used a kernel size of 3×3 and a stride of 1 for smaller proteins (like Pab1 and GB1) and a kernel size of 9×9 and a stride of 9 for bigger proteins (avGFP). This is 9(*depth*) times followed by a block consisting of 2 2D separable convolution layers with 32 filters and a kernel size of 3×3. The input into the first, the output of the first, and the output of the second layer get added at the end of the block. This is followed by a 2D global max pooling layer and a fully connected network consisting of 128- and 64-node layers followed by a single-node output layer. We used the leaky RELU as well as zero-padding to keep the dimensions the same throughout the whole network. The used *depth* was 9. The "down-sampling" (a kernel size of 9×9 with a stride of 9 in the first layer) for bigger proteins slightly reduces the performance but is a worthy trade-off to reduce the computational cost.

0.4.4 Sequence convolution

For result comparison, we used the network architectures of [18] as specified in their main experiments (/pub/regression_args/PROTEIN_main_cnn.txt [22]). Apart from enabling early stopping and restricting the length of the training to 100 epochs, we chose the default parameters when using the /code/regression.py. This is referred to as "sequence convolution" throughout the paper.

0.4.5 Implementation

Our models are implemented using Python v3.10, TensorFlow v2.9.1, and Keras v2.9.0

0.5 Training

The training was done using the mean absolute error as the metric, Adam as optimiser with a learning rate of 0.001 and a maximum number of epochs of 100. Furthermore, we have used a limit to stop the training if the mean absolute error did not improve by at least 0.01 over 20 epochs. The batch size for the training was 32 and parallelised by using 12 central processing unit (CPU) cores of an AMD Ryzen Threadripper 3960X. The training was performed on an Nvidia RTX A5000 graphics processing unit (GPU). For pretraining, we limited the maximum number of epochs to 70.
The training of the sequence convolution neural network was done using Google Colaboratory with the GPU provided by default.

0.6 Experiment setup

For each training, we used three different data sets, which were all obtained from the original data sets of the proteins: a train, a tune and a test set. The test set always consists of 5000 randomly chosen unique entries each. The tune set has one-fifth of the size of the training data set for our architectures and always 5000 entries for sequence convolution. The train datasets contained 50, 100, 250, 500, 1000, 2000 or 6000 entries for all training runs. The train data set is the data set that the network uses to train. The tune set is used to calculate the validation statistics during training, and the test set is used to calculate the statistics of the performance of the network after training. For the training of simple CNN, SepConvMixer and DenseNet we used data augmentation (Section: 0.7) as described below, as well as pre-training (Section: 0.8). Training simple CNN, SepConvMixer, DenseNet and sequence convolution was done on three randomly chosen subsets of the whole protein data sets to construct the train, tune and test sets to avoid picking one that suites one architecture better by chance. For sequence convolution, we used the same train, tune and test sets as for the training of simple CNN, SepConvMixer and DenseNet; however, we have not used data augmentation and transfer learning during its training process.

0.7 Data augmentation

Since neural networks learn better with more data, we used a simple data augmentation method to obtain more training data from small data sets. This method uses the given experimental data, e.g. Table 1, shuffles it and adds it to the original not shuffled data to create new augmented variants like shown in Table 2. This is done four times, and the newly created data is stored. This data is then used as input data to perform the same action three times where, after each round, the newly created data is used as the new input data in the next round. From this newly created augmented data, as many samples are drawn as needed to get a maximum of 20000 training samples when the original data is added ($aug_{used} = 20000 - n_{original}$ where aug_{used} is the number of augmented samples used and $n_{original}$ the number of original data). If the augmentation does not produce enough data to reach a combined number of 20000 samples after the original data is added, the whole augmented data is used. It did not show good results when increasing the number of runs to produce +20000 samples when the original data set is not big enough to reach the number of samples with the number of runs described above. This kind of data augmentation produces pseudo labels for data and assumes an additive effect of mutations. Even though there are more intricate models to describe the relationship between different mutations in a protein, this method provides a simple and effective way to quickly generate more data that helps the model produce better results. In addition, the assumption of simple additivity does not rely on another model like e.g. DeepSequence [13] to be added to the training procedure. We also tried

training the networks only on augmented data and fine-tuning them on the original ³⁵⁵ small data sets. This showed worse performance than training them with the original ³⁵⁶ and augmented data combined.

Table 1. Sample data for augmentation

variant	number mutations	score
K1L,S3A	2	-0.3
R23H,W19F	2	0.1
C5G,A7L	2	-1.0

Shows data samples later used for an example of data augmentation.

³⁵⁷

Table 2. Sample augmentation

augmented variant	number mutations	augmented score
K1L,S3A,R23H,W19F	4	-0.2
R23H,W19F,C5G,A7L	4	-0.9
C5G,A7L,K1L,S3A	4	-1.3

Shows how data points of 1 are added during data augmentation.

0.8   Pre-training ³⁵⁸

To overcome the need for big data sets, we used pre-training to obtain better results ³⁵⁹ while training on small data sets. We used it only for simple CNN, SepConvMixer and ³⁶⁰ DenseNet. The transfer of weights of the feature extraction part of a network trained on ³⁶¹ a whole dataset of another protein yields better performance than starting from a ³⁶² completely untrained network. However, to pre-train a network on data that is more ³⁶³ closely correlated to the protein of interest, we created a pseudo-score that can be ³⁶⁴ calculated without the need for experimental data (section: 0.8.1). After training the ³⁶⁵ model on the pseudo data, the weights of the feature extractor got transferred to an ³⁶⁶ untrained network, frozen, and a new classifier was trained. The same was done with a ³⁶⁷ trainable feature extractor. During initial tests, the reduction of the learning rate did ³⁶⁸ not improve the performance. Therefore we omitted it in further studies. Transferring ³⁶⁹ the weights of the whole pre-trained model, including the classifier, showed worse ³⁷⁰ performance. We also tested networks pre-trained on other proteins, e.g. pre-trained on ³⁷¹ avGFP and trained on Pab1, but our pre-training method proved to be more effective. ³⁷²

0.8.1   Pseudo Score ³⁷³

In order to calculate the pseudo score for the pre-training, the wild-type of the protein ³⁷⁴ gets encoded in the same way as for training the network. The same is done for all ³⁷⁵ possible single and double mutants of the protein. To calculate the pseudo score of a ³⁷⁶ variant, the encoded wild type gets element-wise subtracted from the encoded variant ³⁷⁷ matrix. Of all these values, the absolute value is taken and summed up over all matrices. ³⁷⁸ This gets divided by 100 to shift the values into the range of the real fitness scores. ³⁷⁹ 40000 of these created data points are randomly chosen and used to pre-train the ³⁸⁰ models. These pseudo scores show a Pearson's R of around -0.5 to the original DMS ³⁸¹ data for the different datasets. ³⁸²

0.9   Recall Performance ³⁸³

To access the recall performance of simple CNN, SepConvMixer and DenseNet when ³⁸⁴ trained on different-sized training datasets (Section: 0.6), we used the pre-trained ³⁸⁵

models without data augmentation since this is one of the best-performing settings. The models were trained on different-sized training datasets (50 - 6000 data points) or 80% of the whole datasets. Then the test data set, which consists of only variants that the models have never seen before, was used to access the recall performance by letting the models predict the scores and checking how many of the predicted top-scoring variants were actually part of the actual top scoring 100 variants of the test dataset, given a certain budget (Fig. 4 & S8). The recall performance was computed as described in [18]. If one ranks all variants according to their predicted (fitness-) score, the budget refers to the number of best variants predicted by the network from all variants, which are examined to see whether they occur in the actual 100 best variants. The term "best case" refers to the theoretical optimal outcome. For instance, if we were to select 20 variants from a goal set of the top 100 variants, the best possible outcome would be that all 20 chosen variants are within the true top 100. Thus, the "best case" would reflect a recall score of 0.2. If the budget would be 150 variants, the best case would be that all top 100 variants are contained in the 150 predicted best variants and would therefore result in a recall score of 1.0. The best case is meant as a comparison for what could be the maximum achieved recall score.

0.10 Single Mutation Effect Prediction

To test how many training samples a network needs to get an idea of the effect of single mutations, all single mutations of the DMS dataset of GB1 were used as ground truth. Then pre-trained SepConvMixer models were trained on different numbers of training samples of the original datasets (50 -6000 data points). These models, as well as only the pre-trained model of SepConvMixer, were asked to predict the score of every single mutation present. This was done for GB1 because this dataset consists of all possible single mutations, whereas the Pab1 and avGFP datasets would not yield a comparable ground truth due to missing single-point mutations.

0.11 Generalization

To test the models' capabilities in predicting mutants with a higher number of mutations than they were trained on, the avGFP dataset was used. This dataset is the only one containing variants with up to 14 mutations. Therefore, the training and tune sets consisted of 10,221 and 2,556 data points, respectively, featuring only single and double mutants. The test set consisted of 38,937 variants containing three to 14 mutations. The models were trained under four different settings: from scratch, meaning no pre-training or data augmentation; only with pre-training on our pseudo-score, which contains only scores for single and double mutants; only with data augmentation; and lastly with pre-training and data augmentation combined. The training was done three times with different random seeds to check the prediction consistency. Pearson's R values between the true and the predicted scores of the test set mutants were computed to evaluate the performance.

0.12 Data Availability

The data used to train all networks and the code can be found on GitHub (`https://github.com/ugSUBMARINE/image-dms`) and is licensed under the MIT license. The code is set up so that it can easily be used to reproduce the results of this publication. It can also be easily adapted to pre-train and train our networks (or any other network of interest) on a new dataset.

Results

We tested new ways of encoding protein structure and improving the training on deep
mutational scanning (DMS) datasets. To this end, a simple convolutional neural
network with a LeNet5 [29] -like architecture (simple CNN, Section: 0.4.1), a
DenseNet [30] -like Network (DenseNet, Section: 0.4.2) and a network heavily inspired
by ConvMixer [31] (SepConvMixer, Section: 0.4.3) were used. Furthermore, two
methods, data augmentation and pre-training, were tested for their applicability to
DMS data. To assess their performance, a state-of-the-art sequence convolution
model [18] (sequence convolution) was trained with the same data sets, and the results
were compared. Furthermore, we tested the recall performance of the Top 100 variants
in a data set as well as the predictive performance of the effect of single mutations for
models trained on different amounts of data. To evaluate the "real world applicability",
we conducted a synthetic experiment to see how well the three different models
generalised to variants containing three or more mutations when they were only trained
on data containing single- and double mutants.

0.13   Neural network training

In order to evaluate the performance of the three different architectures as well as of the
original sequence convolution, each model was trained on three different data sets. In
addition, different-sized parts of the datasets were used to determine the influence of the
amount of training data. This showed improved performance of all three architectures
for smaller datasets and the positive impact of pre-training and data augmentation on
predictive performance. For larger datasets, all approaches perform almost equivalently.
For all tests, three data sets, avGFP, Pab1 and GB1 from [18], were used. These were
modified not to include nonsense mutations. From these modified data sets, three
subsets were created: the train, tune and test sets. The train data set varied in size
from 50 to 6000, whereas the tune and test data sets always consisted of 5000 entries
each for the sequence convolution. For simple CNN, DenseNet and SepConvMixer, a
smaller tune set size of one-fifth of the train data set size was used to test whether the
size of the tune data impacts the performance. The test set size of 5000 entries to assess
the models' performance was kept the same. The train set is used for training the
models. The tune set is used as validation data to check the loss and metrics of the
model after each epoch for data it has not seen during training. The test set is used
after training to calculate the statistics of the model's performance since this contains
data the model has never seen before. All tests were performed three times with
randomly chosen samples of the whole modified data sets, and the median of the results
was used to assess the performance. Three main performance metrics are used: mean
squared error (MSE), Pearson's correlation coefficient and Spearman's correlation
coefficient, with the main focus on Pearson's correlation coefficient. No dedicated
hyper-parameter tuning was done, but those that had proven to be the best after some
initial testing were used. To test the impact of an "intro layer" like in the original
DenseNet, which is a normal 2D convolution layer with a kernel size of 3×3 and a stride
of 2 followed by a 2D max pooling layer with a kernel size of 3×3 and a stride of 2, we
chose to include this in the training of avGFP but not for Pab1 and GB1. The same
was done for SepConvMixer, where the first separable convolution layer has either a
kernel size of 3 and a stride of 1 or, for avGFP, a kernel size of 9 and a stride of 9. The
use of an "intro layer" reduces the performance for smaller proteins like Pab1 and GB1
slightly but is needed and a good trade-off to be computationally efficient for proteins of
the size of avGFP and bigger. Here the decrease in performance is smaller.
In order to improve predictions on small data sets, two methods were applied: data
augmentation and pre-training. Data augmentation was already shown to be important

when the data set size is small [32]. Since the proposed data representation is not translation and rotation invariant, it was not possible to use the same data augmentation methods (e.g. rotation, crop, flip, transpose, etc.) as used in image processing. Hence, a simpler data augmentation method was used that sums up scores of existing data (Section: 0.7). Another method to improve a model's performance is pre-training. Here a model can be pre-trained unsupervised if a lot of unlabelled data is available [33] or supervised on a big labelled data set with similar content to the data one is interested in and then fine-tuned on the data set of interest [34]. Since the proposed data representation already captures some variation due to mutations in a protein, we created a simple pre-training procedure, where the models are pre-trained on a pseudo-score that arises from the representations itself (Section 0.8.1).

In the figures (3 and S9 - S13), the median of the three training runs for each data point is shown. The graphs in the top row show either the Pearson-, the Spearman correlation coefficient or the MSE for the predictions on the test set made by the models. The bottom row shows the relative performance compared to the sequence convolution. The data set size always refers to the amount of data from the original split and is not related to the data set size after data augmentation. For the MSE, the relative performance was calculated with $p_{\mathrm{MSE}} = 2 - (MSE_{\mathrm{i}}/MSE_{\mathrm{seqconv}})$ where p is the relative performance, the MSE_{i} the MSE of a model to compare to and MSE_{seqconv} the MSE of the sequence convolution. The relative performance of the correlation coefficients was calculated $p_{\mathrm{R}} = R_{\mathrm{i}}/R_{\mathrm{seqconv}}$ where p is the relative performance, R_i the correlation coefficient for the model to compare to and $R_{seqconv}$ the correlation coefficient of the sequence convolution model.

Fig 3. Pearson's R for predictions of the test data set of SepConvMixer for all three proteins in the upper row, as well as the relative performance compared to sequence convolution in the lower row. Here sequence convolution is indicated as a black dashed line at 1×of its own performance. Label descriptions can be found in Table 3
.

Table 3. Label description for result plots.

label	augmentation	transfer	train CL
sequence convolution	No	No	Yes
base	No	No	No
transfer no train conv	No	Yes	No
transfer train conv	No	Yes	Yes
aug	Yes	No	No
aug transfer no train conv	Yes	Yes	No
aug transfer train conv	Yes	Yes	Yes

Augmentation specifies whether data augmentation was used, transfer whether pre-training was used and train CL whether the convolution layers were trainable or not when pre-training was used.

In general, the more data the networks get to train, the better they perform, and the less important the approach becomes since they tend to perform almost equivalently ($>= 2000$ training samples). Another trend that can be observed is that the more original data the networks get, the less important augmentation and pre-training become to achieve the same training results.

The best performances were obtained when the networks were pre-trained, and the weights of the convolutional layer were not frozen in the subsequent training runs. Data augmentation had an additional positive effect. On smaller datasets ($<= 500$ training samples), the difference in the performance of a chosen method is more pronounced. For example, for Pab1 and avGFP, using data augmentation and freezing the convolutional layers show a better performance in simple CNN (Fig. S15) but show a worse performance when the training dataset gets bigger. In contrast, this method leads to an overall worse performance in DenseNet (Fig. S16) and SepConvMixer. This is especially true for SeqConvMixer, and can be caused by the low number of trainable parameters (13k) for the network under this setting (Fig. 3). Looking at the method that produces the best results, training a pre-trained network and using data augmentation, DenseNet has a similar performance overall to simple CNN and SepConvMixer. A performance improvement from DenseNet can be seen in small datasets (Fig. S17). When the number of training samples gets over 500, the performances of all architectures are almost identical. One fact that stands out about DenseNet is that it takes at least 6000 samples to show the same performance as sequence convolution when no pre-training and data augmentation is used. In contrast, simple CNN without pre-training and data augmentations needs 250 to 500 training samples to show the same performance as sequence convolution or even surpass it. SepConvMixer shows the same trend, starting to surpass sequence convolution at 100 training samples without pre-training and data augmentation on Pab1 and GB1 but needs pre-training in order to show improved performance on avGFP (Fig. 3).

In general, comparing the correlations of all three networks to sequence convolution, the best methods (using pre-training with and without data augmentation) perform at worst $0.95\times$ of sequence convolution but most of the time better, especially on small data sets. In general, the difference in performance for different methods is less pronounced in simple CNN than in DenseNet and SepConvMixer.

Data augmentation works well for data sets that feature only single and double mutants, such as Pab1 and GB1. When the dataset already consists of variants with more than two mutations (up to 14 in the case of avGFP), the approach does not work as well when the training data size surpasses 250 entries. This might be caused by the additive nature of the data augmentation used in our pipeline. Since adding two single mutants is more likely to be additive in real life compared to adding two variants, both carrying

12 mutations on their own, because a higher number of variants increases the likelihood that two mutations interfere with each other and, therefore, corrupt the additivity of their scores when they occur on their own.

When comparing the number of parameters (Table: 4) for sequence convolution and simple CNN, the protein sequence length is the determining factor. The bigger the protein, the more will the simple CNN exceed the sequence convolution in terms of the number of parameters. For DenseNet and SepConvMixer the number of parameters will stay constant and only change due to the use or absence of the first introduction layer. This difference is due to the use of a flatten layer in the sequence convolution and simple CNN after their feature extraction part, whereas DenseNet and SepConvMixer both use a global pooling layer instead that always has the same size, regardless of the input data. For the lower-quality datasets, we performed a limited analysis with only SepConvMixer. Additionally, we only used two settings for training, one without pretraining and without data augmentation and one with pretrained SepConvMixer. We can see an increase in performance when pretraining is used, but as already shown in [18], we can observe the same trend with a reduced performance compared to the other three datasets (Fig: S18).

Table 4. Number of parameters of each network.

architecture	protein	trainable parameter
sequence convolution	Pab1	990k
simple CNN	Pab1	803k
DenseNet	Pab1	714k
SepConvMixer	Pab1	37k
sequence convolution	avGFP	3.118k
simple CNN	avGFP	7.029k
DenseNet	avGFP	799k
SepConvMixer	avGFP	38k

Number of trainable parameters of the three different architectures for two different proteins: Pab1 (75 amino acids) and avGFP (237 amino acids).

0.13.1 Performance Comparison

Comparing sequence convolution to simple CNN shows the advantage of incorporating the structure in the model learning process because these two approaches use the same kind of network architecture. For training set sizes $>= 100$, simple CNN without pre-training and data augmentation shows a performance up to $1.35\times$ of the performance of sequence convolution or at least the same performance in terms of Pearson's R (Fig. S15). For training sets containing 50 data points, it shows a relative performance p_R between zero and 1. SepConvMixer performs similarly to simple CNN and does not rely on data augmentation and transfer learning to show improvements over sequence convolution despite its low number of parameters. The usage of pre-training and data augmentation improves the performance, especially on smaller datasets and can lead to $1.2\times$ and up a maximum performance of $1.75\times$ compared to the sequence convolution (Fig. 3). At worst, it performs comparably to sequence convolution over all dataset sizes. Using a more complex architecture (DenseNet) can improve the performance on smaller dataset sizes ($<= 250$) but needs at least pre-training to reach that level of performance (Fig. S17). Looking at the difference in performance between simple CNN, SepConvMixer and DenseNet, one can see that DenseNet can improve the performance for smaller datasets when pre-training and/or data augmentation is used. On the other hand, when none of these methods is used, DenseNet shows a strongly reduced performance and higher variability in its results (Figs. S19 - S21).

0.14 Predictive Performance

The recall performances of models trained on up to 6000 data points show a similar overall performance. When asked to predict all single mutation effects, a SepConvMixer trained on 250 data points will already be able to qualitatively predict advantageous and deleterious amino acid exchanges.

Comparing the recall performance of the top 100 variants of the test data set, one can see that the pre-trained models of simple CNN, DenseNet, and SepConvMix perform very similarly (Fig. S8). For SepConvMix trained on 6000 training samples, it takes a budget size between 70 to 1040 samples to recall 60 % of the top 100 variants. When trained on 500 training samples, it needs between 500 to 1270 samples to match this performance, and when trained on 50 training samples, 1390 up to 1700 samples are required to reach this performance (Fig. 4).

Fig 4. Recall of the top 100 test set mutations given a certain budget (number of predictions that may contain the true Top 100) for SepConvMixer. The models were trained on train data sets containing 50 - 6000 data points or on 80% of the whole data set, which is labelled "whole". The 60% recall performances when trained on 6000 data points are shown as ■, as ♦ when trained on 500 data points, and as ▲ when trained on 50 data points. The term "best case" refers to the theoretical optimal outcome. (For a detailed description, see Section 0.9)

Testing the performance on predicting the effects of single mutations of pre-trained SepConvMixer networks trained on reduced dataset sizes (Section: 0.6) shows under visual comparison that for GB1, a protein with a sequence length of 56 amino acids, models trained on 250 training samples start to have a good idea of which single mutations has a positive and which has a negative effect (Fig. 5). This comparison was only possible for GB1 since its data set contains all possible single mutants.

0.15 Generalization

Examining the performance of models trained on only single and double mutants in predicting mutants that have more than two amino acid exchanges again shows the advantage of pre-training and data augmentation.

In order to determine how well the different neural networks are applicable in "real lab applications", a synthetic experiment was conducted. The various networks (simple CNN, DenseNet, SepConvMixer) were trained on 10.221 single and double mutants of avGFP, with and without pre-training and/or data augmentation. Then they were asked to predict the test dataset that contains variants featuring a minimum of three and a maximum of 14 mutations. This led to a maximum performance in terms of Pearson's R of 0.835 (Fig. 6). Over all settings, simple CNN showed the best results, followed by SepConvMixer. DenseNet showed the worst performance. Looking at the consistency of the results, SepConvMixer outperforms the other two networks. In accordance with previous results, the models can improve their predictions when

Fig 5. Prediction of the mutational effect of each single mutation at each sequence position using SepConvMixer on the example of GB1. The pre-trained models were trained on training data sets consisting of 50 to 6000 or 80% of the whole GB1 dataset and asked to predict the score of every possible single mutation of GB1. For comparison, the actual measured data are shown as ground truth and the result of a model that was only pre-trained. Figure S22 shows the difference of all predictions to the ground truth. On the y-axis, the amino acids are alphabetically ordered.

pre-training and data augmentation are used. Also in line with previous experiments, the best setting combination is pre-training combined with data augmentation. Under these settings, all models perform the best and deliver the same performance.

Fig 6. Pearson's R of predictions for variants of avGFP containing three to 14 mutations when the networks were only trained on single and double mutants (B: no pre-training and no data augmentation, PT: with pre-training, DA: with data augmentation, PT+DA: with pre-training and data augmentation)

Discussion

It has previously been shown that incorporating the structure in the form of a graph and training a graph neural network to predict deep mutational scanning results achieves the same performance as sequence convolution [18]. By introducing our new protein structure representation, we could show that even without pre-training and data augmentation, a better correlation between experimentally determined and predicted scores can be achieved using the same architecture with a smaller number of filters. Furthermore, we can show that the predictive performance can be greatly improved by two straightforward but effective methods of pre-training and data augmentation. Even though the pre-training is very effective, it is not enough to freeze the convolution layers and only let the fully connected layers be trainable. This shows already worse performance after the train sample size exceeds 500 samples, even though simple CNN can compensate better because the major part of its architecture consists of fully connected layers. The current way our contact maps are generated is used as a fast and simple approximation of the changes happening in the structure of a protein due to amino acid substitutions. The matrix representing the charge interactions does not take into account the protonation state of the amino acids, and the hydrophobicity matrix is only a simple scale and does not take the side chain surroundings into account. These are just two examples where improvements in the protein structure representation can still be made. This might, in turn, help the network to predict mutational effects even

better due to a more realistic representation. Data augmentation can be advantageous when used with datasets containing only single and double mutants and network architectures with a smaller number of parameters. When the network architecture with the highest number of parameters is used (Simple CNN for avGFP), one can see that this network, when no pre-training is used, over-fits the augmented data. Since this data resembles synthetically generated fitness scores that are not always correct, it has to be used with architectures that use fewer parameters. In contrast, the smallest network (SepConvMixer) still manages to perform decently when only data augmentation is used (Fig. 6). Using different protein sequence alignment databases (non-redundant and experimental, which is a 90% clustered version of the non-redundant database) did not change the training results significantly. Interestingly, SepConvMixer performed almost the same as the other architectures despite its much smaller number of parameters. This is promising since fewer parameters reduce the risk of over-fitting. Therefore, the network should be better able to generalise to unseen data. Furthermore, this network will need fewer computational resources. We also showed that more modern network architectures compared to simple CNN could improve the performance when the training sample size is small. Since no dedicated hyper-parameter tuning was performed, an increase in the performance of the models is still possible. A word on protein structure: With the advancement of programs like AlphaFold [23], and RoseTTAFold [35], we can assume that there is a trustworthy structure for most proteins. Even homology modelling might be sufficient to supply a decent protein structure that can be used to create the structure representation. Another advantage of our encoding is the possibility to encode "average" structures derived from molecular dynamics simulations or structures with optimized rotamer positions which leads to an even more natural representation of the protein structure and could potentially create an even better encoding through the interaction matrices. Besides the advantage of being able to use a large number of different architectures derived from the computer vision field, our encoding has the additional advantage of being computationally efficient while representing the biophysical-, interaction- and structural change that occurs due to amino acid substitutions. This makes a more structure-related workflow feasible for researchers without access to high-performance (computing) clusters. Regarding experimental protein engineering in the lab, minimizing the data size required to achieve comparable or superior prediction results is crucial in reducing time, cost, and resources. Our analysis indicates that these models already perform reasonably well in that respect. The ultimate goal would be to transfer "learnings" from one DMS dataset to train a universal network capable of predicting the fitness of proteins for which no experimental data exists is very intriguing but currently most likely restricted to proteins with sufficiently similar structures.

Acknowledgement

The authors thank Prof. Thomas Pock and Prof. Robert Kourist for fruitful discussions. Funding was provided by the Austrian Science Fund (FWF) through project DOC-130 (doc.funds BioMolStruct - Biomolecular Structures and Interactions).

References

1. Heim R, Tsien RY. Engineering green fluorescent protein for improved brightness, longer wavelengths and fluorescence resonance energy transfer. Current Biology. 1996;6(2):178–182. doi:10.1016/S0960-9822(02)00450-5.

2. Binz HK, Amstutz P, Plückthun A. Engineering novel binding proteins from nonimmunoglobulin domains. Nature Biotechnology. 2005;23(10):1257–1268. doi:10.1038/nbt1127.

3. Fowler DM, Fields S. Deep mutational scanning: a new style of protein science. Nature Methods. 2014;11:801–807. doi:10.1038/nmeth.3027.

4. Araya CL, Fowler DM. Deep mutational scanning: assessing protein function on a massive scale. Trends in Biotechnology. 2011;29(9):435–442. doi:10.1016/j.tibtech.2011.04.003.

5. Gray VE, Sitko K, Kameni FZN, Williamson M, Stephany JJ, Hasle N, et al. Elucidating the Molecular Determinants of A beta Aggregation with Deep Mutational Scanning. G3 Genes—Genomes—Genetics. 2019;9(11):3683–3689. doi:10.1534/g3.119.400535.

6. Fowler DM, Araya CL, Fleischman SJ, Kellog EH, Stephany JJ, Baker D, et al. High-resolution mapping of protein sequence-function relationships. Nature Methods. 2010;7:741–746. doi:10.1038/nmeth.1492.

7. Lee JM, Huddleston J, Doud MB, Hooper KA, Wu NC, Bedford T, et al. Deep mutational scanning of hemagglutinin helps predict evolutionary fates of human H3N2 influenza variants. Proceedings of the National Academy of Sciences. 2018;115(35):E8276–E8285. doi:10.1073/pnas.1806133115.

8. Koch P, Schmitt S, Heynisch A, Gumpinger A, Wüthrich I, Gysin M, et al. Optimization of the antimicrobial peptide Bac7 by deep mutational scanning. BMC Biology. 2022;20:114. doi:10.1186/s12915-022-01304-4.

9. Starr TN, Greaney AJ, Hilton SK, Crawford KHD, Navarro MJ, Bowen JE, et al. Deep mutational scanning of SARS-CoV-2 receptor binding domain reveals constraints on folding and ACE2 binding. Cell. 2020;182(5):1295-1310.e20. doi:10.1016/j.cell.2020.08.012.

10. Frank F, Keen MM, Rao A, Bassit L, Liu X, Bowers HB, et al. Deep mutational scanning identifies SARS-CoV-2 Nucleocapsid escape mutations of currently available rapid antigen tests. Cell. 2022;185(19):3603–3616.e13. doi:10.1016/j.cell.2022.08.010.

11. Shihab HA, Gough J, Cooper DN, Stenson PD, Barker GLA, Edwards KJ, et al. Predicting the Functional, Molecular, and Phenotypic Consequences of Amino Acid Substitutions using Hidden Markov Models. Human Mutation. 2013;34(1):57–65. doi:10.1002/humu.22225.

12. Hopf TA, Ingraham JB, Poelwijk FJ, Schärfe CPI, Springer M, Sander C, et al. Mutation effects predicted from sequence co-variation. Nature Biotechnology. 2017;35(2):128–135. doi:10.1038/nbt.3769.

13. Riesselman AJ, Ingraham JB, Marks DS. Deep generative models of genetic variation capture the effects of mutations. Nature Methods. 2018;15(10):816–822. doi:10.1038/s41592-018-0138-4.

14. Biswas S, Khimulya G, Alley EC, Esvelt KM, Church GM. Low-N protein engineering with data-efficient deep learning. Nature Methods. 2021;18(4):389–396. doi:10.1038/s41592-021-01100-y.

15. Rives A, Meier J, Sercu T, Goyal S, Lin Z, Liu J, et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein

sequences. Proceedings of the National Academy of Sciences. 725
2021;118(15):e2016239118. doi:10.1073/pnas.2016239118. 726

16. Gray VE, Hause RJ, Luebeck J, Shendure J, Fowler DM. Quantitative Missense 727
Variant Effect Prediction Using Large-Scale Mutagenesis Data. Cell Systems. 728
2018;6(1):116–124.e3. doi:https://doi.org/10.1016/j.cels.2017.11.003. 729

17. Romero PA, Krause A, Arnold FH. Navigating the protein fitness landscape with 730
Gaussian processes. Proceedings of the National Academy of Sciences. 731
2013;110(3):E193–E201. doi:10.1073/pnas.1215251110. 732

18. Gelman S, Fahlberg SA, Heinzelman P, Romero PA, Gitter A. Neural networks 733
to learn protein sequence-function relationships from deep mutational scanning 734
data. Proceedings of the National Academy of Sciences. 735
2021;118(48):e2104878118. doi:10.1073/pnas.2104878118. 736

19. Amidi A, Amidi S, Vlachakis D, Megalooikonomou V, Paragios N, Zacharaki E. 737
EnzyNet: enzyme classification using 3D convolutional neural networks on spatial 738
representation. PeerJ. 2018;6:e4750. doi:10.7717/peerj.4750. 739

20. Ofer D, Brandes N, Linial M. The language of proteins: NLP, machine learning 740
& protein sequences. Computational and Structural Biotechnology Journal. 741
2021;19:1750–1758. doi:10.1016/j.csbj.2021.03.022. 742

21. Illergård K, Ardell DH, Elofsson A. Structure is three to ten times more 743
conserved than sequence—A study of structural response in protein cores. 744
Proteins: Structure, Function, and Bioinformatics. 2009;77(3):499–508. 745
doi:10.1002/prot.22458. 746

22. Gelman S, Fahlberg SA, Heinzelman P, Romero PA, Gitter A. Neural networks 747
for deep mutational scanning data; 2021. Available from: 748
https://github.com/gitter-lab/nn4dms. 749

23. Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, et al. 750
Highly accurate protein structure prediction with AlphaFold. Nature. 751
2021;589:583–589. doi:10.1038/s41586-021-03819-2. 752

24. Berman H, Henrick K, Nakamura H. Announcing the worldwide Protein Data 753
Bank. Nature Structural & Molecular Biology. 2003;10(12):980–980. 754
doi:10.1038/nsb1203-980. 755

25. Griffith D. PARROT: Protein Analysis using RecuRrent neural networks On 756
Training data; 2020. Available from: https: 757
//github.com/idptools/parrot/blob/master/parrot/encode_sequence.py. 758

26. Schrödinger, LLC. The PyMOL Molecular Graphics System, Version 2.5.5; 2023. 759

27. Johnson M, Zaretskaya I, Raytselis Y, Merezhuk Y, McGinnis S, Madden TL. 760
NCBI BLAST: a better web interface. Nucleic Acids Research. 2008;36(Web 761
Server issue):W5-9. doi:10.1093/nar/gkn201 762

28. McWilliam H, Li W, Uludag M, Squizzato S, Park YM, Buso N, et al. Analysis 763
Tool Web Services from the EMBL-EBI. Nucleic Acids Research. 2013;41(Web 764
Server issue):W597-600. doi:10.1093/nar/gkt376 765

29. Lecun Y, Bottou L, Bengio Y, Haffner P. Gradient-based learning applied to 766
document recognition. Proceedings of the IEEE. 1998;86(11):2278–2324. 767
doi:10.1109/5.726791. 768

30. Huang G, Liu Z, Van Der Maaten L, Weinberger KQ. Densely Connected Convolutional Networks. In: 2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR); 2017. p. 2261–2269.

31. Trockman A, Kolter JZ. Patches Are All You Need? arXiv. 2022;2201.09792 doi:10.48550/arXiv.2201.09792

32. Moreno-Barea FJ, Jerez JM, Franco L. Improving classification accuracy using data augmentation on small data sets. Expert Systems with Applications. 2020;161:113696. doi:10.1016/j.eswa.2020.113696.

33. Caron M, Bojanowski P, Mairal J, Joulin A. Unsupervised Pre-Training of Image Features on Non-Curated Data. In: Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV); 2019.

34. Iorga C, Neagoe VE. A Deep CNN Approach with Transfer Learning for Image Recognition. In: 2019 11th International Conference on Electronics, Computers and Artificial Intelligence (ECAI); 2019. p. 1–6.

35. Baek M, DiMaio F, Anishchenko I, Dauparas J, Ovchinnikov S, Lee GR, et al. Accurate prediction of protein structures and interactions using a three-track neural network. Science. 2021;373(6557):871–876. doi:10.1126/science.abj8754.