Unsupervised Learning of Perceptual Feature Combinations

Minija Tamosiunaite[1,2*]**, Christian Tetzlaff**[3,4]**, Florentin Wörgötter**[1]

*For correspondence:
minija.tamosiunaite@vdu.lt (MT)

[1]Department for Computational Neuroscience, Third Physics Institute, University of Göttingen, Germany; [2]Vytautas Magnus University, Faculty of Informatics, Kaunas, Lithuania; [3]Group of Computational Synaptic Physiology, Department for Neuro- and Sensory Physiology, University Medical Center Göttingen, Germany; [4]Campus Institute Data Science, Göttingen, Germany

---

Abstract In many situations, it is behaviorally relevant for an animal to respond to co-occurrences of perceptual, possibly polymodal features, while these features alone may have no importance. Thus, it is crucial for animals to learn such feature combinations in spite of the fact that they may occur with variable intensity and occurrence frequency. Here, we present a novel unsupervised learning mechanism that is largely independent of these contingencies and allows neurons in a network to achieve specificity for different feature combinations. Furthermore, we show that other existing advanced learning rules cannot satisfactorily form such multi-feature representations. Neurons with this property may, thus, serve as an initial stage for the processing of ecologically relevant real world situations for an animal.

Introduction

Coincident events or features can be highly relevant for animals and humans, and recognizing feature combinations may make all the difference between danger and safety. The red color of a mushroom paired with white surface dots as compared to a red one with a plain surface makes the difference between the poisonous Amanita muscaria (toadstool) and the eatable Amanita caesarea. While humans learn such feature combinations usually by supervision, animals often do so via trial and error. For example, rats and other animals perform scouting and probing of novel food sources until found to be safe. Repeated exposure to sensor-perceivable feature combinations in conjunction with no negative effects will then lead to the conclusion that it should be safe to eat this.

A central problem that arises here is that features will not only occur in combination but also on their own. This will happen with different individual- as well as coincidence-occurrence frequencies and, in addition, usually also with variable intensity. Thus, in order to learn the meaning of combined features, the nervous system must learn this without being distracted by this variability. In terms of a neural network, this means that the neurons therein need to learn this in a convergent manner. Hence, neural plasticity must come to a standstill as soon as a feature combination has been detected where ongoing plasticity may lead to unwanted responses to single features alone.

Such an ecologically driven stopping of learning is a non-trivial problem for unsupervised learning, though. For example, Hebbian learning leads to unbounded (divergent) weight growth. Many stabilization methods and/or augmentations of the original Hebbian learning rule have been suggested to prevent this, for example the covariance rule (*Sejnowski, 1977*), subtractive normalization methods (*Miller and MacKay, 1994*), the Bienenstock, Cooper Munroe rule (BCM, *Bienenstock et al., 1982*), Oja's rule (*Oja, 1982*), and several more. More recently, learning rules had been intro-

duced which combine Hebbian weight growth with a homeostatic, balancing term, called synaptic scaling (*Turrigiano et al., 1998*; *London and Segev, 2001*; *Turrigiano and Nelson, 2004*), for achieving convergence to a target activity (*Tetzlaff et al., 2011*). However, below we will show that these methods cannot solve the above problem.

As a consequence the issue of how to control weight development in an unsupervised way such that a neuron will reliably code for a feature combination remains unresolved. Here we suggest a rather simple solution to this. When growing weights in a network, combination-selective responses can be achieved by gradually dropping the learning rate to zero (simulated annealing) as soon as the neuron's activity is getting 'large enough', which happens earlier for combined than for individual stimuli. Simulated annealing has become a textbook method in reinforcement learning (RL), for example for step-size reduction (*Sutton and Barto, 1998*) or for reducing exploration rates (*Eberhart et al., 2001*) as well as in deep-RL (*Mnih et al., 2015*), but it is also widely used in supervised learning (*Nakamura et al., 2021*; *Huang et al., 2017*; *Liu et al., 2023*) as well as in different variants of Hebbian learning (*Xu et al., 1992*; *Hyvärinen and Oja, 1998*; *Nessler et al., 2008*; *Krotov and Hopfield, 2019*), the latter being most closely related to the investigations in this study. However, in the context of Hebbian learning, annealing is usually applied as an additional mechanism to ensure an efficient convergence of weights, but never as the main factor for activity stabilization on its own.

Central to our approach is that the principle of using the neuron's output as the determining variable for the annealing leads to the advantageous property that neurons in a network will indeed develop specificity for different input (or feature) combinations. This differs from mere spike-coincidence detection because — as discussed above — the learning of input combination specificity needs to be independent (within reason) of the intensity of the input, represented by its occurrence frequency and its amplitude (or input firing rate). Amplitude invariance can to some degree be achieved using network-intrinsic normalization (e.g. *Heeger, 1992*) by which differently strong activity, e.g. from external sensory features that converges onto a cell, will still lead to similar, albeit not identical, responses. These could then serve as the normalized inputs to the learning neuron. Below we will however show that conventional learning rules remain rather sensitive to even small amplitude variations that would remain after normalization such that input combination specificity cannot be learned in a robust manner. Another aspect that leads to problems is that learning needs repetitions. However, the brain has little or no influence on the occurrence frequency of any external stimulus or stimulus combination. Hence, to reliably learn input combination specificity the system must tolerate quite some variability in the occurrence frequencies of the different inputs as well as concerning their coincidences.

We start this investigation in the first part of the paper by analysing a simple case of a neuron with only two inputs and compare a set of the most common learning rules to show that — different from the other rules — the annealing-rule reliably allows detecting input coincidences in spite of amplitude and frequency variations of the input signals. This way the neuron acts as a (frequency and amplitude independent) AND operator. This will then be extended to a recurrent network and we demonstrate that all possible variants of multi-input ANDs are present in this network. We will finally discuss possible biological mechanisms that might support this function and also other issues concerning the learning of input coincidences.

Models

In this section we will first describe our neuron model, then the learning rule that we are proposing. Afterwards we briefly specify the traditional learning rules to which we are comparing the newly proposed method. Finally, we describe a setup, where we have embedded this rule in a recurrent neural network.

Neuron model

To obtain the neuronal response, first we calculate the weighted sum of the inputs:

$$y = \boldsymbol{\omega}^T \mathbf{u}, \tag{1}$$

where $\mathbf{u} = (u_1, ..., u_n)^T$ are inputs, $\boldsymbol{\omega} = (\omega_1, ..., \omega_n)^T$ are weights, and n is the number of inputs. In analogy to real neurons, we will call y the *membrane potential*. We will first analyze the simplest neuron that can detect co-incidences with $n = 2$, but will increase the number of inputs in the later-shown recurrent network example. To calculate the actual neuronal response v, called *spike rate or rate*, we apply a nonlinear function, where coefficients were set to obtain the response characteristic shown in Figure 1 A. This represents a sigmoidal function with a threshold $y_T \approx 0.281$, beneath which the firing rate will be zero:

$$v = f_s(y) = \begin{cases} \frac{1}{0.9}\left(\frac{1}{1+e^{-10(y-0.5)}} - 0.1\right) & , \text{if } \geq 0, \\ 0 & , \text{otherwise.} \end{cases} \tag{2}$$

The Hebb Rule

We investigate the effect of learning rate annealing on the Hebb rule given by:

$$\frac{d\boldsymbol{\omega}}{dt} = \mu(t)\mathbf{u}g(y), \tag{3}$$

with $\mathbf{u}$ the input vector of the neuron, $g(y)$ the influence of the neuron's output on the learning and $\mu(t)$ the learning rate, which will change over time due to annealing.

Learning Rate Annealing

Central to our method, however, is that the spike rate v guides the annealing of the learning rate $\mu(t)$, where we start annealing, as soon as the neuron has reached "high enough" outputs v. The annealing equation is as follows:

$$\frac{d\mu}{dt} = -v S_a(v - v_a)\mu, \tag{4}$$

where v_a is the annealing threshold and $S_a(x)$ is another sigmoidal function:

$$S_a(x) = \frac{1}{1 + e^{-\beta x}}, \tag{5}$$

Figure 1. Neural activation- (A) & annealing function (B).

where we used $\beta = 100$ to obtain a steep step-like transition (see Figure 1 B). However, the method will work in a similar way with several times bigger or smaller β. Learning starts at $t = 0$ with $\mu(0) = \mu_0$. The sigmoidal function leads to the following effect: at the time when v exceeds v_a, the annealing rate abruptly increases. The value for v_a is expected to be around or higher than the inflection point of v. We have investigated $v_a \geq 0.45$. Note that, if annealing happens too early, the neuron's differentiation capability remains low, as its activation function non-linearity will not play any role.

Hebbian Learning Rules with Annealing

We define for Equation 3 different characteristics for g. First, there is a rule, which we call *annealed membrane Hebb (AMH)* rule, defining $g(y) = y$, hence:

$$\frac{d\boldsymbol{\omega}}{dt} = \mu(t)\mathbf{u}y \tag{6}$$

¹²⁴ This rule leads to exponential weight growth (see Eq. 15) due to the fact that the neuronal output
¹²⁵ coupled with the learning-equation creates a positive feedback loop.

¹²⁶ To avoid this problem, we have replaced this rule with one that is largely output independent
¹²⁷ and leads to linear weight growth (see Eq. 13). This so-called *annealed Linear Learning (ALL)* rule
¹²⁸ uses $g(y) = H(y - \eta)$ with H being the Heaviside function:

$$H(y - \eta) = \begin{cases} 1 & \text{, if } y - \eta > 0, \\ 0 & \text{, otherwise.} \end{cases} \tag{7}$$

¹²⁹ Hence, the ALL-rule is given by:

$$\frac{d\boldsymbol{\omega}}{dt} = \mu(t)\boldsymbol{u}H(y - \eta) \tag{8}$$

¹³⁰ This learning rule augments traditional Hebbian learning by the assumption that weight change
¹³¹ will *not* depend on the actual activation of the neuron. Instead learning will start as soon as the
¹³² membrane potential y exceeds a threshold η and then only depends on the incoming input(s).
¹³³ Analysis of the experimental literature shows (see Discussion) that this type of learning may be
¹³⁴ biophysically more realistic than other variants of the Hebb rule.

¹³⁵ Below, we will also show that this rule works best for the here-investigated task of coincidence
¹³⁶ detection. For simplicity, we used $\eta = 0$ but results will not change much as long as one uses
¹³⁷ reasonably small values for η.

¹³⁸ Note that, in principle, one can also define a Hebb rule that relies on the actual rate v and, hence,
¹³⁹ considers the output transform (Eq. 2) by setting $g(y) = v$. However, this case, which is governed
¹⁴⁰ by the sigmoid output function of the neuron, can be tuned to either approximate the annealed
¹⁴¹ membrane Hebb (AMH) or the annealed linear learning (ALL) rule. Hence, we will not consider it
¹⁴² any further.

Reference Models
¹⁴³ **Reference Models**
¹⁴⁴ We compared our method to the classical BCM (*Bienenstock et al., 1982*) and Oja (*Oja, 1982*) rules
¹⁴⁵ as well as to a newer approach called synaptic scaling (*Tetzlaff et al., 2011*).

¹⁴⁶ Note that in the following we use x for annotating the neuron's output, where we use either
¹⁴⁷ $x = y$ (linear case) or $x = v$ (non-linear case).

¹⁴⁸ For the BCM rule we use the basic equations and parameterizations from (*Toyoizumi et al.,*
¹⁴⁹ *2014*), as given in equations 1 and 2 therein:

$$\tau_\omega \frac{d\boldsymbol{\omega}}{dt} = \boldsymbol{u}x(x - \theta), \tag{9}$$

¹⁵⁰ where $\boldsymbol{u}$ are inputs, τ_ω defines the learning rate, and θ is defined as follows:

$$\tau_\theta \frac{d\theta}{dt} = -\theta + x\frac{x}{x_0}. \tag{10}$$

¹⁵¹ Accordingly, x_0 provides the target value for output x. Furthermore, τ_θ is smaller than τ_ω. Values
¹⁵² used in experiments are given in the corresponding figure legends.

¹⁵³ For the Oja rule, we use the standard formulation from (*Oja, 1982*):

$$\frac{d\boldsymbol{\omega}}{dt} = \mu x(\boldsymbol{u} - x\boldsymbol{\omega}). \tag{11}$$

¹⁵⁴ For synaptic scaling, we use the following equation taken from (*Tetzlaff et al., 2011*):

$$\frac{d\boldsymbol{\omega}}{dt} = \mu x\boldsymbol{u} + \mu v(x_0 - x)\boldsymbol{\omega}^2, \tag{12}$$

¹⁵⁵ where $v < 1$ and parameter x_0 determines the value at which the output is stabilizing (for concrete
¹⁵⁶ values see figure legends).

Experimental Settings

In the first part of the results section, we are investigating the ALL-rule on a neuron with only two inputs with varying input amplitudes, frequencies and the standard deviation of the amplitudes as well as the coincidence rates between both inputs. This is extended by detailed statistics how our system behaves for different annealing-rates v and thresholds v_a. Finally, we compare the results from the ALL-rule to results obtained from a set of the most common learning rules under similar conditions.

In the second part of the results sections, we employed the ALL-rule for generation of *all possible* coincident combinations of N external inputs. For that we create a randomly connected network of M neurons with sparse connectivity of c connections per neuron on average. We use for connectivity a Gaussian distribution with standard deviation of $c/5$. However we are limiting this to a minimum of at least one connection onto each neuron. We also impose a limit on the maximally allowed connections, where for $c = 2$ this amounts to allowing connection numbers in the interval $[1, 3]$. We analyse the cases $M = 200$ and $M = 1000$, with $c = 2$ and $c = 10$ (allowed interval $[1, 19]$). In addition to those connections, 15% of randomly selected neurons are supplied with one connection each from randomly chosen external input neurons. We analyzed cases of $N = 3$ and $N = 5$ external inputs. Inputs can take two values: 0 or 0.5. For this part of the study we did not vary input amplitudes or frequencies. The goal of this part of the study is to show that such a system can self-organize into creating output neurons that respond to *different* possible combinations of active inputs. Hence, one such neuron will then respond if a certain subset of k inputs is active at the same time (AND operation) and not respond if any one of these k inputs is not present. In this case the remaining $n - k$ inputs will not be able to drive this output neuron whatsoever. We were considering that a neuron is signaling for a certain input combination in case its activity is above a "classification" threshold for this combination, but below threshold for any other combination. We analyzed a set of thresholds from $v = 0.4$ to 0.8 in steps of 0.1.

This way, we measured how many neurons, which are signaling a possible combination, appear within a network by calculating statistics from 100 trials to generate and train a network. For this, we varied the network connection matrix trial by trial. Also, neurons in the network were generated with an annealing threshold drawn from a uniform distribution in $[0.75, 0.95]$, which also was re-generated for each trial. Then, we present results as percentage of neurons in the network that represent a certain combination. Hence, 2% means that there were 4 neurons representing that combination in a neural network with $M = 200$ neurons and 20 neurons representing that combination in the $M = 1000$ network.

Example code for the different experiments will be made publicly available after journal-acceptance of this article.

Results

First we analyze the properties of the annealing learning rules as compared to the reference methods (BCM, Oja, Synaptic Scaling) for a neuron that has only two inputs. This analysis is started by an analytical calculation that compares annealed membrane Hebb (AMH) with annealed Linear Learning (ALL) after which we show simulation results for a wide variety of cases that cannot be captured by analytics. The central finding here is that only the ALL-rule allows for reliable separation between coincidence and no-coincidence cases without having to re-tune neuron parameters for different input situations.

This part is followed by a study of recurrently connected networks with more than two inputs, where we ask how reliably such a network could detect various types of coincidences.

Separation Properties

In the following we analyze how well does the ALL-rule, as compared to the AMH-rule, separate the resulting output spike rates (coincidence case) relative to the individual rates obtained from

Figure 2. A) Separation properties calculated analytically B) Histograms of numerical results for ALL- and AMH-rules in case of Gaussian distribution of input amplitudes. In all cases, input presentation frequencies are equal. In B) input coincidence is 10% everywhere; input amplitudes: mean for the blue distributions was normalized to 1.0 and for the orange ones to ϕ; standard deviations indicated above the plots. Annealing parameters are $v_a = 0.7$, $v = 0.2$. Initial weights are $\boldsymbol{\omega}(0) = [0.001, 0.001]^T$ and initial learning rate $\mu_0 = 0.0005$; Euler integration with step $dt = 1$. Disks in A mark the points with the corresponding plots in B. Tilted lines are truncation marks for the blue histograms.

---

only one input. We can here obtain analytical arguments under the assumption of independent
constant inputs in the limit of few coincidences only (where the latter constraint is needed for the
AMH-rule only). Then, we also complement these analytical considerations by some simulations
that allow relaxing the above constraints.

Hence, we assume two constant inputs, u_1 and ϕu_1 with $\phi > 1$. For the case of the ALL-rule one
can calculate weight growths over time as:

$$\begin{aligned}
\omega_1(t) &= \mu_0 u_1 t + \omega_0 \\
\omega_2(t) &= \mu_0 \phi u_1 t + \omega_0
\end{aligned} \tag{13}$$

211 where μ_0 is the learning rate before annealing and ω_0 the start weight. Accordingly, the membrane
212 potentials are:

$$\begin{aligned}
y_1(t) &= \mu_0 u_1^2 t + \omega_0 u_1 \\
y_2(t) &= \mu_0 \phi^2 u_1^2 t + \omega_0 \phi u_1.
\end{aligned} \tag{14}$$

213   For the AMH-rule we get for the weights:

$$\begin{aligned}
\omega_1(t) &= \omega_0 e^{\mu_0 u_1^2 t} \\
\omega_2(t) &= \omega_0 e^{\mu_0 \phi^2 u_1^2 t},
\end{aligned} \tag{15}$$

214 and the membrane potentials are given by:

$$\begin{aligned}
y_1(t) &= \omega_0 u_1 e^{\mu_0 u_1^2 t} \\
y_2(t) &= \omega_0 \phi u_1 e^{\mu_0 \phi^2 u_1^2 t}.
\end{aligned} \tag{16}$$

If we allow for (rare) coincidences between the two inputs then the membrane potential be-
comes $y_1 + y_2$ and the neuron's output will be $v_{1+2} = f_s(y_1 + y_2)$ (see Eq. 2). Due to the definitions
of y_1 and y_2 the following conjecture holds: $v_{1+2} > v_2 > v_1$. As a consequence v_{1+2} will eventually hit
the annealing threshold v_a at time t_a. If we now assume instantaneous annealing, then all weight
growth will stop and we can ask which values will the individual outputs v_1 and v_2 have reached?
This way we can assess the separation between the coincidence-driven output (which is then at v_a)
and the other two outputs. To be able to call such a neuron an AND-operator a clear separation is
needed and here we are only concerned with v_2, which is anyhow larger than v_1. Hence, we calcu-
late for different parameters u_1, μ_0, ϕ and v_a how big the separation $s(t_a)$ between $v_{1+2}(t_a) = v_a$ and
$v_2(t_a)$ is as $s(t_a) = v_a - v_2(t_a)$. This last step has to be calculated numerically as the resulting terms
cannot any longer by analytically solved. Figure 2 A shows the results. Note, that μ_0 has no influ-
ence on the separation, it only determines how early/late the annealing threshold will be reached.
The figure shows that only for identical amplitudes the separation between the coincidence case
and the individual input case will be the same for the annealed membrane Hebb- and the annealed
Linear Learning rule. For all other situations, the ALL-rule leads to a far better separation. Further-
more, note that separation is largely independent of the annealing threshold, which adds to the
robustness of the annealing approach.
In panel B we show how the ALL- versus AMH-rules behave when using inputs with a Gaussian
distribution in amplitudes and the same presentation frequencies for both inputs. Coincidence
rate was 10%. Responses to the individual inputs are shown in orange and blue and the coincident
case in green. The results are consistent with the analytical analysis in panels A except for a slight
increase in separation values due to more balanced weight growth in the simulation, because of
the 10% coincidences, where the analytics could only be calculated for the limit case of 0%. The
ALL-rule leads to a much stronger separation. Numbers at the bottom show the distance between
the mean values of the orange and green distributions, where separability entirely ceases towards
the right for AMH. Furthermore, note that the AMH-rule shows the expected exponential run-away
property for the stronger (orange) distributions and the blue ones do not develop any firing rate v
above zero for unequal amplitudes. Using a rate-based Hebb rule (hence $g(y) = v$), would mitigate
these effects as soon as the membrane potential to rate transformation approaches the Heaviside
property.

Annealed Linear Learning rule: Neuron output analysis

In the following we focus on the ALL-rule, which provides a better separation than the the AMH-
rule as shown above. In Figure 3 we present histograms of neuron outputs for different input
combinations. Input amplitudes are drawn from a Gaussian distribution and are characterized by
mean and standard deviation (see first column in Figure 3 A). We use mean amplitudes of 1, 1.2
and 1.5. Standard deviation std=0.1 for Figure 3. (Cases with std=0.2, i.e., higher input variance,
had been shown already in Figure 2 above).
In addition to the amplitude distribution, inputs are characterized by their presentation fre-
quency, which could be understood as how often stimuli are delivered to the neuron by the exter-
nal world. In part A of Figure 3, we show results in case both inputs are presented with the same
frequency, while in part B results are shown in which the first stimulus is twice more frequent.
Another important input parameter is how frequently two inputs coincide at the neuron. We
consider 50, 30 and 10% coincidence. When the presentation frequency of the two inputs differs,
we calculate the percentage of coincidence with respect to the input with smaller presentation
frequency.
In Figure 3 we show the input distributions of the neuron (left column) and the neuron output v
in case of coincidence in green, while the response to single inputs are blue and orange. All neuron
outputs are limited to the interval $[0, 1]$, due to the non-linear response curve (see Figure 1 A).
As expected, the output for coincident inputs (green) is always the highest. We can also ob-
serve that the gap between the blue or orange histograms and the green histogram is in almost

Figure 3. Histograms of neuron inputs (first column) and outputs v for the ALL-rule. A: Equal presentation frequency; B: Different presentation frequency. Parameters: $v_a = 0.7$, $v = 0.1$, std=0.1. Mean amplitudes of the inputs are indicated in the first column. Initial weights are $\boldsymbol{\omega}(0) = [0.001, 0.001]^T$ and initial learning rate is $\mu_0 = 0.0005$; Euler integration with step $dt = 1$. For other parameters: see plots. Response histograms (blue or yellow) in case of amplitude or presentation frequency difference are grouping very close to zero, where we truncate the zero bin to optimize for visibility (see truncation marks).

all cases quite big. Furthermore, this gap "sits at the same location" such that a unique discrimination threshold v_d could be defined to differentiate coincident from non-coincident responses (e.g. $v_d = 0.6$). These properties are, thus, largely independent of input amplitudes, frequencies, and percentages of coincidence. Thus, only due to these invariances such a neuron can indeed be called "input coincidence detector" (AND operation-like). Below we will show that other learning rules do not achieve this, but first we quantify the robustness of these properties.

In Figure 4 we show for the ALL-rule, how the separation of coincidence vs no coincidence varies with different annealing parameters, where we vary the annealing onset threshold and the annealing rate v_a and v (Eq. (4)). We show the classification error for coincidence vs no coincidence. Classification threshold is kept at $v = 0.5$. First, in Figure 4 A,B we present error plots in parameter space in case both inputs have the same presentation frequency and both amplitudes are equal: mean=1, std=0.1, with 30% (A) or 50% (B) coincidence. These are the most favorable cases from all cases shown here and one can see that the error is zero (or very small) in a very big region of the parameter space (white and light colored patch in the middle of the plots). This patch slightly decreases when amplitudes (E, F), or frequencies (C, D) of the two inputs differ, but differences

Figure 4. Classification error (coincidence vs. not coincidence) of the ALL-rule in respect to parameter variations. Parameters are annealing onset threshold and annealing rate. Decision threshold is 0.5. Panels (A-L) variable amplitude, coincidence and presentation frequency; panels (M-P) extreme cases: bigger variance, smaller coincidence, bigger amplitude difference, bigger frequency difference. Averages over 20 trials are shown. Initial weights are $\boldsymbol{\omega}(0) = [0.001, 0.001]^T$ and initial learning rate $\mu_0 = 0.0005$; Euler integration with step $dt = 1$.

between the plots remain small. Amplitude increase of the less frequent input can compensate for the frequency decrease (see G, H). The errors in the plots "above-left" the white patch are false positives, while for "bottom-right" they are false negatives.

In the third row (panels I-L) the same type of representation is shown, but for a set of amplitude differences, where the first input average amplitude is always at one, while the second input average amplitude is drawn from a set {0.8, 0.9, 1.0, 1.1 and 1.2} (uniform probability), std=0.1 everywhere. Also in this case the error is zero in a big patch of the parameter space.

In Figure 4 M-P we present various less favorable cases to investigate the limits of the ALL-rule: higher input variance (std=0.2, panel M), small coincidence (just 10%, panel N), wide amplitude range in the interval [0.5,1.5] (panel O), as well the case when one input is five times less frequent (30% coincidence, panel P). Except for the last, five times less frequent case, we always get a parameter region where errors are zero. In the case where one input is five times less frequent (P), however, we still get low classification errors for a large range of parameters. Note, that in this case the coincidence percentage is very small as we calculate the 30%-percentage from the less frequent input. Thus, this case is, indeed, very unfavorable.

Comparison to Reference Methods

In Figure 5 we show results obtained with the three reference methods where we use either the membrane potential y or the rate output v to drive learning. Results of this investigation are char-

Figure 5. Results for the reference methods: BCM, Oja and Synaptic Scaling using linear (*y*, marked *mem*) and non-linear (*v*, *rate*) output terms in the learning. Input coincidence is 30% everywhere. Amplitudes and standard deviation (std) are shown above each column. Presentation frequency is equal, except the last column where it is 2:1. For all linear versions $\boldsymbol{\omega}(0) = [0.001, 0.001]^T$, for non-linear: $\boldsymbol{\omega}(0) = [0.2, 0.2]^T$. Other parameters: BCM linear: $v_0 = 1$, $\tau_\omega = 100$, $\tau_\theta/\tau_\omega = 0.1$, $\theta(0) = 0.2$; BCM nonlinear, different from above: $v_0 = 0.3$; Oja & Synaptic Scaling (linear & non-linear): $\mu = 0.001$; Synaptic Scaling: linear: $v_0 = -200$, $v = 0.01$, non-linear: $v_0 = -1.35$, $v = 0.7$.

acteristic for the problems that these methods have with the task of input coincidence detection.
Also in some cases, quite some parameter tuning was needed to get any reasonable result. Note
also that all reference rules heavily depend on the output, which is assumed to be monotonically
increasing; thus they are not compatible with Heaviside regimes we used in our rule.
The most prominent property of the membrane-BCM method is that the coincidence output is
not the highest: outputs to single inputs reside on both sides of the green coincidence histogram.
Note, that the original membrane-BMC method results in negative weights. In the paper of ***Toy-***
oizumi et al. (***2014***) an augmented BCM equation is provided to avoid this, but using this will not
alter the above observation. When using the rate to drive learning with BCM, the situation im-
proves, but differences in presentation frequency lead to non-separatable distributions (see the
last column in row 2 in Figure 5). However, in general, the rate-BCM performs second best in our

₃₀₉ task, which may be due to the fact the BCM does indeed also implement some sort of "simulated
₃₁₀ annealing", where an increase of the neurons activity will shift the BCM threshold accordingly (see
₃₁₁ Discussion section for details).

₃₁₂ For membrane-Oja there is no unique separation threshold to be found for the difference cases
₃₁₃ and it depends on the stimulus situation. Furthermore, some distributions overlap and cannot be
₃₁₄ separated at all. For rate-Oja, we could not find any parameter setting that produces reasonable
₃₁₅ results and plots shown here were the best we could produce. Note, that Oja in existing literature
₃₁₆ is normally used in linear regimes (i.e., only as membrane-Oja).

₃₁₇ The same is true for rate-scaling (last row), where membrane scaling works better and nicely
₃₁₈ separates all distributions, albeit always with different separation thresholds.

₃₁₉ Hence, none of the reference methods can reliably assure that (1) there is a large gap between
₃₂₀ the single input distributions and the distributions of coincident inputs and (2) that this gap does
₃₂₁ not shift when using (within reason) different input situations allowing for a unique separation
₃₂₂ threshold. As mentioned above, only due these two properties a neuron can operate as an "input
₃₂₃ coincidence detector", which cannot reliably be achieved with these methods.

Recurrent networks with the ALL-rule

₃₂₅ First, in Figure 6 we provide a box plot for the number of different combinations obtained for
₃₂₆ $N = 3$ or $N = 5$ external inputs in case of $M = 200$ neurons in a recurrent network. Statistics
₃₂₇ are shown for 100 randomly generated networks. For this we count, after learning, how many
₃₂₈ neurons respond, for example, to an input combination of "x11xx". Such a neuron, shown with
₃₂₉ green index "12" (decimal for the binary code 01100) in the panel B, thus, requires inputs 2 and 3
₃₃₀ (encoded as "1") to be active, where the other inputs may or may not be present (encoded as "x"),
₃₃₁ but they will not be able to drive this neuron on their own. One can see that for $N = 3$ the number
₃₃₂ of cells representing different combinations is essentially uniformly distributed, while for $N = 5$
₃₃₃ the number of neurons representing single inputs is higher than the rest. As expected standard

Figure 6. Box plots for different combinations of inputs for the cases of $N = 3$ and $N = 5$ inputs for the ALL-rule. Combinations are aligned in ascending order of active inputs, with color code indicating the number of inputs, see legend at the bottom. Combinations are indicated by decimal numbers corresponding to binary set notation (e.g. "3" means the combination: 00011, where only the two last inputs are active). "o" means other, where this denotes occurrences of cells signaling several different combinations. The size of the neural network is $M = 200$, average connectivity $c = 2$, annealing parameters are: annealing rate $v = 0.3$, where the annealing threshold v_a for each neuron individually is drawn from a uniform distribution [0.75,0.95]. Decision threshold is 0.7. Initial weights are chosen from Gaussian distribution with mean=0.001 and std=0.0002. Initial learning rate $\mu(0) = 0.0005$. Euler integration with $dt = 1$. Median, mean and standard deviation are shown on the basis of 100 trials.

Figure 7. Different combination distribution based on decision threshold and neural network architecture. A and B: three input case; C and D: five input case. Numbers 1 to 5 indicate combinations responsive to corresponding number of inputs; "Other" represent cells signaling more than one combination (see text for explanation), "Sub." denotes sub-threshold cases, while "Sust." denotes sustained activity, which does not subside after switching off the inputs, which does not happen here (but in the baseline, see next Figure). Neural network (NN) architecture notation: "No of neurons"-"connectivity" (M-c). Numbers above column groups denote percentage of combination-selective neurons (vs. "Other" and "Sub." neurons). Initial settings and learning parameters as in Fig. 6.

---

deviations are high but, in spite of this, for any of the possible combinations there are always at
least a few cells that represent them.

It is here important to note that this network does not produce an excess of neurons that re-
spond to the condition "other" (about 7 aut of 200 cells do this in the 5-input case, panel B). "Other"
means that a neuron would code, for example, for "x1x1x" as well as for "11xxx" and possibly for
even more different combinations. If self-organization were driven by a pure random process a
very strong excess of such neurons would be expected, which is not the case here. In the next
figures this is analyzed in more detail. Hence, our networks, indeed, self-organize into a set of
input-combination selective neurons.

In Figure 7 we analyze how the proportion of different combinations change with varying de-
cision threshold (A,C) and for the same decision threshold but in different network architectures
(B,D). We quantify how many neurons are – on average – selective for *any* input combination. To
achieve this, we first sum the number of neurons that represent the same *type* of input combina-
tion: e.g. single input. Then we divide this sum by the number of possible type-identical combi-
nations. For example, for the $N = 5$-case there are 5 single, 10 double, 10 triple, 5 quadruple and
1 quintuple possible combinations existing. Hence, percentage plots in figure 7 do not sum up to
100. However, to also be able to show the strong difference between combination-selective versus
non-selective ("other" + "sub-threshold" + "sustained") neurons, we provide the total percentage
of the combination-selective neurons, too (numbers in italics at the top of each plot). Standard
deviations are of the same order of magnitude, as shown in the box-plot above and omitted here
to make the diagrams better readable.

Figure 8. Comparison to baseline. A: Three input case, B: Five input case. The column group "learned" shows performance of the ALL-rule, $M = 200$, $c = 2$; copied from Figure 7; "permuted" is for the case with learned weights randomly permuted; "permuted x 1.5" and "permuted x 2" for cases with permuted weights multiplied by 1.5 and 2, respectively. Decision threshold kept at 0.7 everywhere. Abbreviations: "Sub." = sub-threshold, "Sust." = sustained activity. Green numbers denote percentage of "Òther".

Decision threshold dependence is analyzed in parts A and C for $N = 3$ and $N = 5$, respectively. All combinations are represented with an increasing prevalence of more-complex combinations for higher threshold values. Single cases are over-represented, where this over-representation decreases with increasing decision threshold.

The green columns in the histograms show "Other" cases, which count all the cells in the network that are active with two or more combinations, where one is not the subset of the other. This number is not substantial when connectivity is low $c = 2$ and higher if we use connectivity $c = 10$ in five input case (see panel D). However, note that also in this case there are still around 80% of combination specific cells existing. If the decision threshold becomes too high (see for the threshold value 0.8 in A and C), sub-threshold cases emerge (black column). These are cases where the neuron may "fire" but never reaches decision threshold. None of the networks that we trained this way showed sustained activity, which is a type of activity that persists after the inputs have been switched off (but see next).

Results can be compared to baseline performance, where the weights obtained by the ALL-rule are randomly reshuffled (permuted) in between connections in the network, while the general network connectivity pattern (which neuron connects to which other neuron) remains the same. The percentage of different cases is shown in Figure 8, column group "permuted". Here we see that both, for $N = 3$ (A) and $N = 5$ (B), we only have a few percent of neurons responding to single inputs only, whereas essentially no more-complex combinations emerge (compare to columns "learned" plotted on the left). Instead, for baseline most of the cells remain sub-threshold. The question naturally arises whether this is just a scaling effect? Hence, to investigate if we can get more useful above-threshold combinations with bigger weights, we increased all weights in the baseline by 1.5 or by 2 (columns "permuted x 1.5" and "permuted x 2"). Here we get a few more single responses and, as discussed above, also more "Other" responses (numbers in green), but now also sustained activity emerges (brown column in the diagrams) and dominates for "permuted x 2". Hence, the network activity does not come to rest after stimuli have been removed. Thus, this baseline shows that the ALL-method, suggested in this study, allows generating in an unsupervised manner neurons selective for *specific* combinations of inputs (low number of random="other" combinations) without leading to sustained activation.

Discussion

In this study we have shown how it is possible for neurons to arrive, by unsupervised learning, at a well-defined target activity, when using multiple inputs, so that different neurons in a network become specific for different feature combinations. A comparison with a wide variety of other learning rules shows that these properties are not easily attainable in an input amplitude and frequency independent manner. The neurons in our system develop this way the property of a

³⁹⁰ (somewhat unconventional) "switched AND-OR operator" (Fig. 9), where certain input lines must
³⁹¹ be present (AND property) while others are irrelevant (switches remain open for those) such that
³⁹² only the AND-gated inputs drive the output. To achieve this we have introduced two modifications
³⁹³ of the traditional Hebb rule, which we will discuss in the following:

A) We reduced the influence of the neuronal output onto learning to an all-or-none behavior by using the Heaviside function with a threshold $\eta \geq 0$. This way learning will start as soon as the neuronal activity is larger than this threshold but will not depend on the actual magnitude of the neuronal activity.

Figure 9. Switched AND-OR operator.

B) We used annealing of the learning rate, as soon as the neuron has reached a certain output
⁴⁰⁶ level. While annealing is a well-known supplementary technique in many, also unsupervised, ap-
⁴⁰⁷ proaches (*Xu et al., 1992*; *Hyvärinen and Oja, 1998*; *Nessler et al., 2008*; *Krotov and Hopfield, 2019*)
⁴⁰⁸ we use it as the *main* mechanism to stabilize learning.

All-or-non learning

⁴¹¹ The use of the Heaviside function for Hebbian learning (Eq. 8) provides, from a theoretical perspec-
⁴¹² tive, several clear advantages because it leads only to linear weight growth. Different from this,
⁴¹³ the membrane Hebb rule, which uses the membrane potential to drive learning (Eq. 6), leads to
⁴¹⁴ exponential weight growth and a strong run-away effect of the weights that belong to the stronger
⁴¹⁵ inputs (see Fig. 2 B). Furthermore, (especially at dendritic spines) it appears that the post-synaptic
⁴¹⁶ depolarization effects, that influence Ca^{++} influx through NMDA channels, which determine LTP,
⁴¹⁷ have an all-or-none effect on plasticity. The absolute values for Ca^{++} within the dendrite required
⁴¹⁸ for the induction of synaptic plasticity have been estimated as 150–500 nM for LTD and > 500 nM
⁴¹⁹ for LTP (*Cormier et al., 2001*). Furthermore, it has been measured that a single EPSP can raise
⁴²⁰ the Ca^{++}-level to 700 nM, where a pairing of post-synaptic depolarization with synaptic stimulation
⁴²¹ would even drive it up to as much as 12 μM (*Sabatini et al., 2002*).

⁴²² Based on these findings *Rackham et al.* (*2010*) had designed a model of plasticity in spines that
⁴²³ predicts that an EPSP resulting from the activation of a single synapse is sufficient to cause a sig-
⁴²⁴ nificant Ca^{++} influx through NMDA receptors. This is in line with experimental data (*Bloodgood*
⁴²⁵ *and Sabatini, 2007*; *Canepari et al., 2007*; *Sobczyk and Svoboda, 2007*). As a consequence, it ap-
⁴²⁶ pears that every post-synaptic back-propagating spike or dendritic spike will be enough to lead to
⁴²⁷ substantial Ca^{++} influx to trigger plasticity (at a spine). This argues for a sharp transition of the
⁴²⁸ post-synaptic learning influence, where the use of the Heaviside function would represent a limit
⁴²⁹ case. Sigmoidal transition functions similar to Eq. 2 could be used instead, where results for this
⁴³⁰ study will be little affected if the sigmoid is steep enough (data not shown).

Learning Rate Annealing

⁴³³ In 1998, Bi and Poo (*Bi and Poo, 1998*) had shown that the change in EPSP amplitude is inversely
⁴³⁴ related to the size of the EPSP when employing a plasticity protocol. Hence, large synapses grow
⁴³⁵ less than small synapses. This is potentially a ceiling (saturation) effect of LTP and could, in theo-
⁴³⁶ retical terms, indeed be captured by a learning rate annealing mechanism. This, however, points
⁴³⁷ to a core problem: For theoreticians the learning rate is just a single variable and learning rate
⁴³⁸ annealing is essentially just an abstraction of meta-plasticity. Linking this to complex multi-faceted

biophysical processes, thus, remains difficult. There is a wealth of literature that suggests that the reduction of LTP, due to meta-plasticity, could rely on effects that influence NMDA receptors (*Huang et al., 1992*; *Coan et al., 1989*; *Youssef et al., 2006*; *Satoshi et al., 1996*; *Frey et al., 1995*). However, the time course of this might be too fast as these effects seem to decay within about one hour (*Huang et al., 1992*). Stimulus driven annealing ought to be able to act rather on longer time-scales because the animal may only now and then encounter the relevant stimuli. Longer lasting reduction of LTP could be obtained by mechanisms that operate on its later phases (late-LTP) (*Frey and Morris, 1997*; *Redondo and Morris, 2011*; *Luboeinski and Tetzlaff, 2021*; *Lehr et al., 2022*) suspected to be essential for establishing synaptic consolidation. However, any potential role of this mechanisms in meta-plasticity related to annealing effects remains unknown. Nevertheless, it seems conceivable that neurons reduce their 'learning-efforts' by reducing the synthesis of some relevant biochemical components using a saturation-driven kinetics, as soon as the neuron's activity has grown enough, which could be understood as learning rate annealing.

In the theoretical literature, learning rate annealing is a very widely used mechanism applied with different learning rules and for different purposes (*Sandholm and Crites, 1996*; *Smith, 2002*; *Nessler et al., 2008*; *Krotov and Hopfield, 2019*). Notably, the BCM rule also has a mechanism built in that could be understood as annealing. Its threshold θ relies on the time-averaged level of postsynaptic firing. Thus, if firing levels are maintained at a high level, this threshold shifts, making LTP harder to obtain. With quite some tuning, this rule was also able to solve the tasks investigated in this study at least to some degree. However, BCM relies on a squared output term, which – in spite of the threshold-induced damping – makes its behavior for multiple inputs in a network complex and often unstable. Note that, under the physiological condition of $1 > \theta > \mu$, it can be easily shown by equating Nullclines and using a Taylor expansion, that the characteristic second fix-point of BMC (the first is at the origin) will only be a stable node if u and/or x_0 are big. In network learning this cannot be unequivocally assured, leading to instabilities. Given this complexity, it is unclear how BMC could be modeled in biophysical terms, also in view that saturation-driven kinetic mechanisms that operate of one or more compounds needed for LTP, do not map well to this rule. Synaptic scaling has been suggested as a possible mechanism to achieve this, too, and scaling operates on rather long time scales, slower than learning.

Comparing to other learning principles

Hence, one aspect concerns the question to what degree the ALL-rule might relate to synaptic scaling (*Turrigiano et al., 1998*). Scaling assumes that neurons "want" to achieve a certain target activity (*Turrigiano and Nelson, 2004*) and that synaptic changes are driven by this target. Hence, this is indeed related to the operation of the ALL-rule. Alas, the existing mathematical formulations where (Hebbian) plasticity is combined with some scaling term (*Tetzlaff et al., 2011*), do not reliably lead to this property. Different from this, the ALL-rule does achieve this in a robust manner, where – for the purpose of this study – we have set the target activity to relatively high values, which allows getting the AND-operator property. However, due to the design of the annealing mechanism, other target values can also be obtained by using a different (lower) annealing threshold v_a.

Furthermore, note that currently the ALL-rule leads only to weight growth. It is however, straightforward to complement this with a decay term (forgetting) and/or with a mechanism for LTD. This can, for example, be done by using a sigmoidal function $G(y - \eta), \eta > 0$ with values between -1 and $+1$ (or the Sign function) instead of the Heaviside function, which will lead to weight reduction for $y - \eta < 0$. We are currently investigating this rule, but this goes beyond the scope of the current study.

The other rules investigated in this study can lead to LTD, but none of them could reliably solve our task. Clearly, reinforcement learning and supervised learning would be able to achieve this, though. Both, however, require evaluative feedback in the form of rewards or by use of an error function. Different from this, our method is non-evaluative and essentially performs a process of self-organized stimulus sorting. Any potential ecologically meaningful evaluation could then come

on top and, for example, reinforcement learning of a beneficial behavioral policy could make use of the responses of our feature-combination specific neurons.

Conclusions

With the mechanisms employed here we demonstrated that neurons can learn to respond to specific input combinations in an unsupervised manner. While such responses are reminiscent of an AND operation, this can only be achieved if the system reacts in a rather invariant way – and different from a classical AND – to stimuli of different amplitude and occurrence frequency, which is assured by annealing. We believe that this specificity for input combinations may be of ecological relevance for an animal, because it allows learning to respond to sets of inputs that might indicate situations with different – positive or negative – valance, where individual features might be irrelevant.

Acknowledgments

Supported by the German Science Foundation (DFG), grant WO 388/17-1 (F.W.) and grant TE 1172/7-1 (C.T.), as well as by the European Commission H2020, grantno.: 899265 "ADOPD" (F.W.) and the German Federal Ministry of Education and Research (BMBF) grantno. 01IS22093A "KISSKI" (C.T.).

References

Bi GQ, Poo MM. Synaptic modifications in cultured hippocampal neurons: dependence on spike timing, synaptic strength, and postsynaptic cell type. Journal of Neuroscience. 1998; 18(24):10464–10472.

Bienenstock EL, Cooper LN, Munro PW. Theory for the development of neuron selectivity: orientation specificity and binocular interaction in visual cortex. Journal of Neuroscience. 1982; 2(1):32–48.

Bloodgood BL, Sabatini BL. Nonlinear regulation of unitary synaptic signals by CaV2. 3 voltage-sensitive calcium channels located in dendritic spines. Neuron. 2007; 53(2):249–260. doi: 10.1016/j.neuron.2006.12.017.

Canepari M, Djurisic M, Zecevic D. Dendritic signals from rat hippocampal CA1 pyramidal neurons during coincident pre-and post-synaptic activity: a combined voltage-and calcium-imaging study. The Journal of Physiology. 2007; 580(2):463–484. doi: 10.1113/jphysiol.2006.125005.

Coan E, Irving A, Collingridge G. Low-frequency activation of the NMDA receptor system can prevent the induction of LTP. Neuroscience Letters. 1989; 105(1-2):205–210.

Cormier R, Greenwood A, Connor J. Bidirectional synaptic plasticity correlated with the magnitude of dendritic calcium transients above a threshold. Journal of Neurophysiology. 2001; 85(1):399–406. doi: 10.1152/jn.2001.85.1.399.

Eberhart RC, Shi Y, Kennedy J. Swarm intelligence. Elsevier; 2001.

Frey U, Schollmeier K, Reymann K, Seidenbecher T. Asymptotic hippocampal long-term potentiation in rats does not preclude additional potentiation at later phases. Neuroscience. 1995; 67(4):799–807.

Frey U, Morris RG. Synaptic tagging and long-term potentiation. Nature. 1997; 385(6616):533–536.

Heeger DJ. Normalization of cell responses in cat striate cortex. Visual Neuroscience. 1992; 9(2):181–197.

Huang G, Li Y, Pleiss G, Liu Z, Hopcroft JE, Weinberger KQ. Snapshot ensembles: Train 1, get m for free. arXiv preprint arXiv:170400109. 2017; doi: 10.48550/arXiv.1704.00109.

Huang YY, Colino A, Selig DK, Malenka RC. The influence of prior synaptic activity on the induction of long-term potentiation. Science. 1992; 255(5045):730–733.

Hyvärinen A, Oja E. Independent component analysis by general nonlinear Hebbian-like learning rules. Signal Processing. 1998; 64(3):301–313.

Krotov D, Hopfield JJ. Unsupervised learning by competing hidden units. Proceedings of the National Academy of Sciences. 2019; 116(16):7723–7731. doi: 10.1073/pnas.1820458116.

Lehr AB, Luboeinski J, Tetzlaff C. Neuromodulator-dependent synaptic tagging and capture retroactively controls neural coding in spiking neural networks. Scientific Reports. 2022; 12(1):17772. doi: 10.1038/s41598-022-22430-7.

Liu C, Huang W, Xu RYD. Implicit bias of deep learning in the large learning rate phase: A data separability perspective. Applied Sciences. 2023; 13(6):3961. doi: 10.3390/app13063961.

London M, Segev I. Synaptic scaling in vitro and in vivo. Nature Neuroscience. 2001; 4(9):853–854. doi: 10.1038/nn0901-853.

Luboeinski J, Tetzlaff C. Memory consolidation and improvement by synaptic tagging and capture in recurrent neural networks. Communications Biology. 2021; 4(1):275. doi: 10.1038/s42003-021-01778-y.

Miller KD, MacKay DJ. The role of constraints in Hebbian learning. Neural Computation. 1994; 6(1):100–126.

Mnih V, Kavukcuoglu K, Silver D, Rusu AA, Veness J, Bellemare MG, Graves A, Riedmiller M, Fidjeland AK, Ostrovski G, et al. Human-level control through deep reinforcement learning. Nature. 2015; 518(7540):529–533. doi: 10.1038/nature14236.

Nakamura K, Derbel B, Won KJ, Hong BW. Learning-Rate Annealing Methods for Deep Neural Networks. Electronics. 2021; 10(16):2029. doi: 10.3390/electronics10162029.

Nessler B, Pfeiffer M, Maass W. Hebbian learning of Bayes optimal decisions. Advances in Neural Information Processing Systems. 2008; 21. doi: 10.5555/2981780.2981926.

Oja E. Simplified neuron model as a principal component analyzer. Journal of mathematical biology. 1982; 15:267–273.

Rackham O, Tsaneva-Atanasova K, Ganesh A, Mellor J. A Ca2+-based computational model for NMDA receptor-dependent synaptic plasticity at individual post-synaptic spines in the hippocampus. Frontiers in Synaptic Neuroscience. 2010; p. 31. doi: 10.3389/fnsyn.2010.00031.

Redondo RL, Morris RG. Making memories last: the synaptic tagging and capture hypothesis. Nature Reviews Neuroscience. 2011; 12(1):17–30. doi: 10.1038/nrn2963.

Sabatini BL, Oertner TG, Svoboda K. The life cycle of Ca2+ ions in dendritic spines. Neuron. 2002; 33(3):439–452. doi: 10.1016/S0896-6273(02)00573-1.

Sandholm TW, Crites RH. Multiagent reinforcement learning in the iterated prisoner's dilemma. Biosystems. 1996; 37(1-2):147–166.

Satoshi F, Yoichiro K, Masami M, Hidekazu F, Hiroshi S, Kenya K, Kenichi I, Zhixiong C, Hiroshi K. The long-term suppressive effect of prior activation of synaptic inputs by low-frequency stimulation on induction of long-term potentiation in CA1 neurons of guinea pig hippocampal slices. Experimental Brain Research. 1996; 111:305–312.

Sejnowski TJ. Storing covariance with nonlinearly interacting neurons. Journal of Mathematical Biology. 1977; 4(4):303–321.

Smith AJ. Applications of the self-organising map to reinforcement learning. Neural networks. 2002; 15(8-9):1107–1124. doi: 10.1016/S0893-6080(02)00083-7.

Sobczyk A, Svoboda K. Activity-dependent plasticity of the NMDA-receptor fractional Ca2+ current. Neuron. 2007; 53(1):17–24. doi: 10.1016/j.neuron.2006.11.016.

Sutton RS, Barto AG. Reinforcement learning: An introduction. MIT press; 1998.

Tetzlaff C, Kolodziejski C, Timme M, Wörgötter F. Synaptic scaling in combination with many generic plasticity mechanisms stabilizes circuit connectivity. Frontiers in Computational Neuroscience. 2011; 5:47. doi: 10.3389/fncom.2011.000.

Toyoizumi T, Kaneko M, Stryker MP, Miller KD. Modeling the dynamic interaction of Hebbian and homeostatic plasticity. Neuron. 2014; 84(2):497–510. doi: 10.1016/j.neuron.2014.09.036.

Turrigiano GG, Leslie KR, Desai NS, Rutherford LC, Nelson SB. Activity-dependent scaling of quantal amplitude in neocortical neurons. Nature. 1998; 391(6670):892–896.

Turrigiano GG, Nelson SB. Homeostatic plasticity in the developing nervous system. Nature Reviews Neuro-
science. 2004; 5(2):97–107. doi: 10.1038/nrn1327.

Xu L, Oja E, Suen CY. Modified Hebbian learning for curve and surface fitting. Neural Networks. 1992; 5(3):441–
457.

Youssef FF, Addae JI, Stone TW. NMDA-induced preconditioning attenuates synaptic plasticity in the rat hip-
pocampus. Brain Research. 2006; 1073:183–189. doi: 10.1016/j.brainres.2005.12.008.