Robust analysis of allele-specific copy number variations from scRNA-seq data with XClone

Rongting Huang[1,*], Xianjie Huang[1,2,*], Oliver Stegle[3,4], and Yuanhua Huang[1,2,5,#]

[1] School of Biomedical Sciences, The University of Hong Kong, Hong Kong SAR, China
[2] Center for Translational Stem Cell Biology, Hong Kong Science and Technology Park, Hong Kong SAR, China
[3] Division of Computational Genomics and Systems Genetics, German Cancer Research Center (DKFZ), Heidelberg, Germany
[4] Genome Biology Unit, European Molecular Biology Laboratory, Heidelberg, Germany
[5] Department of Statistics and Actuarial Science, The University of Hong Kong, Pokfulam, Hong Kong SAR, China
[*]: Co-first authors; [#]: Correspondence: `yuanhua@hku.hk`

Abstract. Somatic copy number variations (CNVs) are major mutations that contribute to the development and progression of various cancers. Despite a few computational methods proposed to detect CNVs from single-cell transcriptomic data, the technical sparsity of such data makes it challenging to identify allele-specific CNVs, particularly in complex clonal structures. In this study, we present a statistical method, XClone, that strengthens the signals of read depth and allelic imbalance by effective smoothing on cell neighborhood and gene coordinate graphs to detect haplotype-aware CNVs from scRNA-seq data. By applying XClone to multiple datasets with challenging compositions, we demonstrated its ability to robustly detect different types of allele-specific CNVs, enabling the discovery of corresponding subclones and the dissection of their phenotypic impacts.

Keywords: Copy number variation · Allelic imbalance · Somatic clone · ScRNA-seq modelling.

1 Introduction

The copy number variations (CNVs), including copy loss, gain and copy-neutral loss-of-heterozygosity (CN-LOH or interchangeably LOH hereafter), have been widely shown associations in various cancers [1,2]. CNVs have also been found predictive to clinical outcomes in patients and can reoccur in certain tumour types [3]. Accurate detection of CNVs is therefore crucial for studying and understanding the genetic factors that contribute to the development and progression of cancers. High-throughput sequencing is one of the most widely used techniques for studying CNVs in cancers initially in a bulk manner, e.g., in the pan-cancer analysis [4]. Soon after, single-cell sequencing emerged, providing a better understanding of CNVs and their clonal evolution. Recent advances in single-cell DNA-seq at both technology and computational levels, e.g., ACT [5] and CHISEL [6], have further enhanced the analysis of CNV heterogeneity and its potential association with clonal fitness [7].

Single-cell RNA-seq (scRNA-seq) technologies have further fueled the CNV analysis thanks to its high popularity and dual readout of transcriptome and genetic makeups. However, its high technical sparsity makes it challenging to accurately call CNVs at a single-cell resolution. Several methods have recently been developed to tackle these challenges. InferCNV is one of the first methods proposed for this purpose [8] and remains widely used, achieving reasonable accuracy probably thanks to its effective smoothing by a moving-average method and multiple denoising treatments. CopyKAT is another recently proposed method that leverages a polynomial dynamic programming model to smooth the transformed data along genomic coordinates, with an emphasis on the detection of diploid cells [9]. However, both InferCNV and CopyKAT do not consider allelic information and hence cannot detect copy-neutral LOH. On the other hand, HoneyBADGER [10] and CaSpER [11] were proposed to account for the allelic shift signal for detecting a full spectrum of CNVs. However, given the coverage of a single variant is extremely low, their independent use of individual SNPs often suffers from high noise. Instead, Numbat was recently introduced to substantially

resolve such challenge by aggregating multiple variants via population haplotype-based phasing [12], a strategy that has been proven powerful in scDNA-seq [6]. However, this method may sacrifice the resolution of clonal CNVs from a single-cell level to a pseudo-bulk level and its performance and robustness remain to be further assessed, especially on samples with extreme compositions of clonal CNVs.

To overcome these challenges, we introduce *XClone*, a statistical model to detect allele-specific CNVs on individual cells by modelling the raw read/UMI counts from scRNA-seq data. Briefly, this method accounts for two modules: the B-allele frequency (BAF) of heterozygous variants and the sequencing read depth ratio (RDR) of individual genes, respectively detecting the variation states on allelic imbalance and absolute copy number, which are further combined to generate the final CNV states (Fig. **1**a, Supp. Fig. S1-2, Methods). Uniquely, our method introduced two major innovations to boost the signal-to-noise ratio in detecting CNV states. First, in the BAF module, we implemented a three-step of haplotyping, from individual SNPs to a gene by population-based phasing, from consecutive genes (100 by default) to a gene bin by an Expectation-Maximization algorithm, and from gene bins to a chromosome arm by a dynamic programming method. Importantly, we re-designed our original genotyping software cellsnp-lite [13] to a tailored package *xcltk* to address the issue of double counting UMIs that cover multiple nearby SNPs (see Methods). Second, we employed two orthogonal strategies to smooth the CNV-state assignments on both BAF and RDR modules: horizontally with hidden Markov models along the genome coordinates and vertically with a k-nearest-neighbours (KNN) cell-cell connectivity graph, which not only denoises the data but also preserves the single-cell resolution.

2 Results

2.1 Assessment of CNV detection on a glioma with clone-specific allele loss

To evaluate the effectiveness of CNV detection, we utilized our XClone on a public tumor sample (glioma, BCH869) with a complex clonal structure that had been probed with high coverage using the Smart-seq2 platform. Notably, this sample has histone H3 lysine27-to-methionine mutations (H3K27M-glioma) and the dataset contains 489 malignant cells and 3 non-tumour cells [14]. As reported in the original study, a distinct subclonal structure has been observed in this population of cells by combining scRNA-seq (by using InferCNV) and whole-genome sequencing (WGS) data, where two major clones have different allele loss on chr14 (Fig. **1**b). When applying XClone's RDR module, we indeed observed a copy loss on chr14 for almost all cells (Fig. **1**c and Supp. Fig. S3: smoothened log-transformed raw ratio visualisation), consistent with that of InferCNV (Supp. Fig. S4b). However, when leveraging the BAF module, XClone was able to identify the different allele loss on chromosome 14, matching the reported clones from WGS (Fig. **1**d-e, Supp. Fig. S3 BAF panel). Interestingly, XClone's BAF module detects medium but consistent allelic shifts on chr7 (clone 1), chr17q and chr19p, endorsing the probable copy gain, instead of copy loss or LOH. In addition to the detection of these CNVs, XClone's combined mode provided further insight into the sample, identifying consensus CNVs such as copy gain on chr1q, chr2p, and chr17q. Clone-specific CNVs were also detected, including copy gain on chr7 and LOH on chr10 in clone 1, and copy gain on chr2q in both clones 1 and 3 (as shown in Fig. **1**e). These results provide a more comprehensive understanding of the clonal structure of the sample and demonstrate the utility of XClone in detecting CNVs.

To compare the performance of XClone with other popular CNV detection methods, we applied InferCNV, CopyKAT, CaSpER, and Numbat to the same dataset. To evaluate the accuracy of these methods, we introduced a quantitative assessment metric using a receiver operating characteristic (ROC) curve at an entry-level for each CNV state. This involved using the assignment probability (or transformed value) of each gene in each cell against the ground truth annotation (Fig. **1**g-i; Methods). The results showed that InferCNV and CopyKAT were effective at identifying absolute CN change (Supp. Fig. S4) while Numbat showed potential in detecting allele-specific CNVs, including the major copy gains and LOH. However, Numbat had a notable flaw in copy loss detection, as it missed one of the two allele losses on chr14 (Fig. **1**f). In contrast, XClone was able to identify nearly all CNVs across clones, achieving remarkable improvement on AUROC for all types of CNVs compared to any single counterpart method. Specifically, for copy gain,

Figure 1: Overview of XClone, CNV identification of a glioma sample BCH869 by XClone and performance comparison between methods. (a) Overview of XClone workflow. The XClone workflow begins with scRNA-seq raw files to generate allele-specific read counts matrices and gene expression read counts matrix (features by their genomic positions and cells by assigned cell barcode order). XClone performs the BAF module and RDR module independently and combines them to call the final CNV states. (b) UMAP of BCH869 with different types of cell annotation: cell clustering by transcriptomes and CNV tumor clone ID identified by the original paper, CNV region identified for each clone and the inference clonal tree in the original paper. (c-e) Heatmap visualisation of CNVs generated by XClone RDR module, BAF module and the combination of the 2 modules, respectively for BCH869. (f) Heatmap visualisation of CNVs generated by Numbat. (g-i) Assessment of performance in identification of copy number gain, copy number loss and loss of heterozygosity on BCH869 glioma sample.

XClone achieved an AUROC of 0.925 compared to 0.853 by InferCNV and 0.845 by Numbat (as shown in Fig. **1**g). For copy loss, XClone achieved an AUROC of 0.986 compared to 0.947 by InferCNV and 0.724 by Numbat (as shown in Fig. **1**h). For LOH, XClone achieved an AUROC of 0.992 compared to 0.994 by Numbat, while InferCNV does not support this CNV type due to the lack of allelic information (Fig. **1**i). Similar improvements were also observed when using the chromosome arm as a unit in the ROC curve (Supp. Fig. S5) or performing a precision-recall curve (Supp. Fig. S6). Notably, although XClone's plotting included cell cluster information, this information was not used in CNV estimation, similar to InferCNV. Thus, XClone preserved the CNV detection at the cell level rather than the cluster level.

2.2 XClone identifies CNV states in an ATC sample with extremely low tumor purity

Next, to examine XClone's capability in analysing droplet-based scRNA-seq (10x Genomics), we applied XClone to an anaplastic thyroid cancer sample (ATC2), covering 6,224 cells. This sample was initially analyzed by CopyKAT [9], where the tumor purity was found extremely low in the original analysis and our replication (2%; Fig. **2**a the second and fifth panels, respectively). Despite that the number of tumor cells is relatively small (n=123), they are found to consist of two distinct sub-clones, which were initially observed by Numbat [12] and are readily captured by multiple other methods, including InferCNV, CopyKAT, and our XClone (Fig. **2**a, bottom panels, Supp. Fig. S8a). CaSpER failed to capture the same subclone signal in the ATC2 sample (Supp. Fig. S8a,f).

However, the clonal CNV states detected by each tool varied dramatically, which may be attributed to the low tumor cell proportion. Notably, Numbat identified all CNVs as copy loss, which contrasts with the results of other tools. Although there was no ground truth from DNA assays, the BAF signal from scRNA-seq suggested that such widespread copy loss was a systematic error (Fig. **2**e); for example, chr1p showed a strong signal of balanced B allele frequency, which indicated it should not be a copy loss. Additionally, lacking allelic information, InferCNV and CopyKAT cannot detect any CN-LoH, including chr1q, chr4q, and chr16. However, regarding absolute copy number, InferCNV and CopyKAT yielded patterns similar to those of XClone, including copy gains on chr5 (subclone 2 only), chr7, and 19, and copy loss on chr6p, concordant with commonly occurred CNVs in ATC patients [9,15]. These findings further validate the accuracy of our method in detecting CNVs with respect to both absolute copy numbers and allelic imbalance.

2.3 XClone detects wide existence of LOH in a TNBC sample

Last, we applied XClone to a triple-negative breast cancer (TNBC) sample that was also assayed by droplet-based scRNA-seq (10x Genomics). As reported by the original study using CopyKAT, three clusters of cells were identified from the transcriptome, consisting of 300 normal cells and 797 tumour cells from two distinct CNV clones [9]. By re-analysing this dataset, our RDR module confirms both consensus CNVs (chr1q, chr6p, chr8, chr12p, chr18) and subclonal CNVs including chr2q, chr4p, chr6q, chr7q, chr15p, chr16p in Clone 1 and chrX in Clone 2 (Fig. **3**b, Supp. Fig. S9). On the other hand, when applying XClone's BAF module, various regions were found with copy neutral in absolute number but imbalanced allele frequency (Fig. **3**c-d). This is further confirmed by XClone's combined mode, presenting a wide existence of copy-neutral LOH (Fig. **3**e), which cannot be detected by methods omitting the allelic information, e.g., CopyKAT and InferCNV (Supp. Fig. S10 b-c). One example is chr1p where strong allelic bias is observed by the smoothed BAF signal (Fig. **3**c), further detected as LOH by XClone (with a minor probability of copy loss), while it is largely missed by Numbat (Fig. **3**f). Specifically, consensus LOH includes chr1p and chr21 with high purity, and also chr11p, chr13, chr14, chr17, and chr19 with strong allele bias support, while clone 2 has specific LOH on chr3p and chr22. Taking one step further, we leveraged the CNV probability detected by XClone to explore potential subclones within this sample, e.g., by K-means clustering on the flattened probability matrix here (XClone_ID in Fig. **3**e; Methods). The results show that the clonal reconstruction by XClone is perfectly concordant with the original one (ARI metric: 0.965; Fig. **3**a).

Furthermore, for the computational efficiency of the above two scRNA-seq datasets BCH869 and TNBC1, covering smart-seq with high coverage and 10x Genomics with high cell counts, CopyKAT is the most efficient

Figure 2: CNVs identification of ATC2 sample by XClone and other methods (inferCNV, CopyKAT, Numbat). (a) UMAP of ATC2 sample with different types of cell annotation: cell clustering by transcriptomes and Tumor/Normal annotation provided by CopyKAT at the top panel, tumor subclones identified by XClone, inferCNV and CopyKAT at the bottom panel, separated by a black dashed line. (b-c) Heatmap visualisation of CNVs generated by XClone RDR module. Absolute copy number changes (copy gain/loss) identification (b) and smoothened log-transformed raw ratio visualisation (c). (d-e) Heatmap visualisation of CNVs generated by XClone BAF module. Allele bias identification (d) and smoothened B allele frequency (e). (f) Heatmap visualisation of CNVs generated by XClone Combine module, indicating the final CNV detection results from the combination of RDR and BAF. (g-i) CNV identification results generated by inferCNV (g), CopyKAT (h), and Numbat (i), respectively. Note, all heatmap figures (b-i; except InferCNV) only contain tumor cells. For all cells, see Supp. Fig. S8.

method among all, closely followed XClone. While for methods using allelic information, XClone substantially reduced the running time (over 60%) compared to Numbat and CaSpER (Supp. Table S4). Under default settings, XClone exhibits higher running efficiency in terms of user time and wall clock time, with acceptable memory usage. One additional advantage of utilizing XClone is its flexibility in selecting modules, namely the RDR module and BAF module, independently. This feature offers different options and choices to users

Figure 3: TNBC1 CNVs identification by XClone and subclonal detection comparison with CopyKAT. (a) UMAP of TNBC1 with different types of cell annotation. Transcriptomes cluster here is the annotation of cell clusters from expression and allele frequency combined analysis, which is used as annotation in analysis and visualisation. (b-e) Heatmap visualisation of CNVs generated by XClone RDR module, BAF smoothing, BAF module and combination of the 2 modules, respectively for TNBC1, here the combined result shows that XClone detects similar subclones. (f) Heatmap visualisation of CNVs generated by Numbat.

based on their specific needs and preferences. A comprehensive analysis of the utilities associated with these methods is summarized in Supp. Table S5.

3   Discussion

In summary, XClone is a statistical method that models CNV states with RDR and BAF modules, and effectively smooths both cell neighborhood and gene coordinate graphs. We applied XClone to three types of unique cancer samples (glioma, ATC, and TNBC), each with distinct features such as complex clonal structure, extremely low purity, and ubiquitous CNVs. XClone demonstrated its robust and powerful capability

in detecting allele-specific CNV states and capturing a broad spectrum of genetic variations, which can help reveal their phenotypic impact. Due to its high accuracy in detecting CNVs at the cell level, XClone has the potential to enable the discovery of fine-resolved subclonal structures, providing insights for therapeutic strategies. Admittedly, further validation of the potentially identified subclones will be beneficial, possibly using other techniques such as mitochondrial variations [16,17].

4   Methods

4.1   Overview of XClone suite

XClone offers a comprehensive end-to-end pipeline for CNV analysis using scRNA-seq data. This pipeline accepts bam file(s) as input, models raw UMI or read counts, and outputs both smoothed BAF and RDR matrices for visualization, as well as the detected cell-by-gene CNV states as final results. It also requires users to specify a diploid cell group as a reference. There are four major steps, including pre-processing, pre-analysis, modelling, and post-analysis, as described in detail below and illustrated in (Fig.**1**a).

4.2   Preprocessing: extract count matrices with xcltk

In order to pre-process single-cell data for XClone, we developed a toolkit xcltk (`https://pypi.org/project/xcltk/`) to extract cell-by-gene count matrices from BAM file(s) for both RDR and BAF modules. The input can be a single BAM file containing cell barcodes (e.g., by 10x Genomics) or multiple BAM files with one file per cell (e.g., by smart-seq2). By default, we used annotated genes from GENCODE (32,696 for hg19 and 33,472 for hg38) – the same as Cell Ranger; however, users can also employ any customized gene (or other feature) annotations.

For the generation of read depth counts, xcltk calculates the UMIs (if applicable) or reads counts for each gene in every cell and produces a sparse matrix. This processing is highly similar to CellRanger developed by 10x Genomics, including reads filtering (by default only those reads with MAPQ< 20, aligned_length<30nt or FLAG>255 are filtered).

To generate allele-specific counts, xcltk requires a VCF file that contains phased germline genotypes in addition to the default gene and cell lists. The software identifies all heterozygous variants and counts UMIs or reads that support each allele, resulting in two matrices that display the alternative allele (AD) or the depth (DP) in each cell for each SNP. By using genotype phasing information, xcltk can combine multiple SNPs from a single gene and compress both AD and DP into cell-by-gene matrices. It is worth noting that when a UMI or read covers multiple variants on one gene, xcltk ensures that they are only counted once to avoid double counting. The software accomplishes this by retaining the UMI or read IDs for each SNP and only counting them once when aggregating all SNPs.

4.3   Pre-analysis: three-level allele phasing for haplotype-specific BAF

In XClone, in order to enhance the signal-to-noise ratio when analysing the allele information in the BAF module, we utilized a three-level allele phasing approach. First, we implemented **reference-based phasing** by utilizing the human population haplotype reference to phase individual SNPs. This phasing was accomplished by EAGLE2 [18] with the Haplotype Reference Consortium panel [19], which was powered by the Sanger imputation server (`https://imputation.sanger.ac.uk`) as the default option. Once the individual SNPs were phased, xcltk was able to count the phased alleles for SNPs across a gene (as described in Section 4.2).

Second, to avoid the errors in the population-based phasing when it comes to a longer genome range covering many genes, we further performed a **gene-bin phasing** (local phasing) to link a group of proximate and consecutive genes (we call it a gene bin, by default 100 genes). Intuitively, in each cell, we force the allele frequency AF to be the same for all genes in a gene bin, allowing flipping the allele of each gene. Namely, it assumes the CNV states are the same within a gene bin in a cell, even though the CNV states can be

different from cell to cell (e.g., some are normal cells and some are tumour cells). Similar to CHISEL [6], we implemented an EM algorithm (Supp. Algorithm 1) to achieve this by flipping the allele of each gene within a gene bin.

Third, for synchronising the BAF for visualisation, we introduced a **chromosome-range phasing** (global phasing) to further link all gene bins on each chromosome arm. Similar to the gene-bin phasing, this step can also use the genomic auto-correlation on the CNV states, which could be addressed by a dynamic programming algorithm, a Hidden Markov model, or a Gaussian process model. As this step is relatively independent of CNV state identification, we adopted the dynamic programming algorithm proposed in CHISEL for simplicity and efficiency (see Supp. Algorithm 2). Note, both the gene-bin and chromosome-range phasing steps depend on the auto-correlation of BAF deviance from 0.5 (theoretical BAF value for allele balance). Otherwise, if there is no allelic imbalance, it will return arbitrary phasing, which is irrelevant to the CNV state inference. The three-level allele phasing illustration is shown in Supp. Fig. S1 and the remarkable performance of the phasing of the three datasets were visualised in Supp. Fig. S3, S7, and S9, for sample BCH869, ATC2 and TNBC1, respectively.

4.4 Pre-analysis: horizontal and vertical smoothing for visualisation

Before detecting the CNV states, it is beneficial to visualise the raw signal of both RDR and BAF modules. Due to the high technical sparsity in scRNA-seq data, it is necessary to perform smoothing for the visualisation. Here, we performed both a horizontal smoothing by a weighted moving average (WMA) along with each chromosome and a vertical smoothing across cells via a k-nearest neighbour (KNN) graph.

Taking the read depth ratio (RDR) module as an example, the raw count matrix was first normalized to its total library counts, then divided by reference cell expression profile, and finally transformed to the logarithm scale as log ratio. Then this raw RDR matrix X is smoothed horizontally by a WMA connectivity matrix W and vertically by a KNN connectivity matrix M, as follows,

$$\tilde{X} = M \times X \times W, \tag{1}$$

where M is a cell-by-cell connectivity matrix generated from the KNN graph (k=10 by default) of routine scRNA-seq analysis `scanpy.pp.neighbors()`, and W is a gene-by-gene connectivity matrix linking each gene to its proximate consecutive genes on each chromosome arm (window size t=40 by default), as follows

$$W_{j,g} = \frac{W_{j,g}^o}{\sum_h W_{h,g}^o}, W_{j,g}^o = \begin{cases} t - |d(j;g)|, & 0 < |d(j;g)| < t \\ t * 2, & d(j;g) = 0 \\ 0, & |d(j;g)| \geq t, \end{cases}$$

where $d(j;g)$ refers to the ordinal distance from any gene j to a query gene g on genome coordinate. Of note, W is column normalised and M is row normalised, namely with sum to one.

For the B allele frequency (BAF) module, we took the cell-by-gene_bin matrix as input and performed a similar smoothing both horizontally (with WMA, window size t=101 by default) and vertically (with KNN). As an example, the smoothing steps for BCH869 scRNA were shown in Supp. Fig. S3. Once the smoothed RDR and BAF matrices are generated, they can serve both visual representation and empirical extraction of CNV parameters (see below Section 4.5, 4.6).

4.5 Modelling: mixture model for expression data (RDR module)

The Read Depth Ratio (RDR) module aims to detect the states of absolute copy numbers, i.e., CN-neutral, loss, and gain, for each gene in each cell. To start, it requires specifying reference cells (i.e., diploid cells), which can be picked from pre-annotated cell types from transcriptome by examining markers of non-tumour cells. Given the reference cells, XClone will calculate the reference average gene expression (ref_avg) and filter the genes with low expression (default 0.5 for 10x genomics and 1.8 for smart-seq). Optionally, it will

 further remove top marker genes for each pre-annotation cell group (15 by default), e.g., as detected by the
`scanpy.pp.rank_genes_groups()`.

Then, we used a negative binomial distribution to model the observed UMI (or read) counts for each
CNV state in a generalized linear model framework, as follows

$$p(X_{c,g}|z_{c,g,k} = 1) = \mathtt{NB}(X_{c,g}|\mu_{c,g,k}, \phi_g)$$
$$\mu_{c,g,k} = l_c \times X_{ref,g} \times C_k, \tag{2}$$

where $X_{c,g}$ denotes the raw read/UMI count at gene g cell c; l_c denotes the cell-specific library size factor;
$X_{ref,g}$ denotes the average count value for gene g in given reference diploid cells; C_k denotes the copy number
ratio compared to reference diploid state for each CNV state. The latent variable $z_{c,g,k}$ indicates if gene g
in cell c belongs to CNV state k ($z_{c,g,k} = 1$) or not ($z_{c,g,k} = 0$). In this module, we defined three states with
index $k = 0$ for copy loss, $k = 1$ for copy neutral and $k = 2$ for copy gain.

Considering that the reference count values $X_{ref,g}$ can be obtained directly, it leaves only three sets of
parameters to be estimated: l_c, C_k and ϕ_g. Here, we estimated them separately by a maximum likelihood
estimation with the `statsmodels` package [20] or using a heuristic method. To estimate the library size factor
l_c for each cell c, by default, we used the ratio of its total sum count to the average of reference cells. To
estimate the gene-specific dispersions ϕ_g, we fit a negative binomial GLM per gene in the form of Eq. (2)
but only on the reference cells ($C_k = 1$) with the fitted library size l_c from the previous step.

For the CNV ratio C_k, one can directly use a theoretical value, namely {0.5, 1, 1.5} respectively for
loss, neutral and gain (Supp. Fig. S2). Here, we further employed a heuristic method from the empirical
distribution. Based on the smoothed RDR value, we selected 3 guided genomic regions (chromosomes or
arms) that are most likely to be copy loss, copy neutral and copy gain regions, as ranked by the mean. In
general, CNV regions only cover a small percentage of the whole cell-by-gene matrix and the extreme ratio
value at each CNV state can be used to guide CNV ratio initialization. Thus, the CNV ratio C_k will be
extracted from quantiles of each of the corresponding chromosomes (or arms), specifically default quantile
0.96 in copy neutral, quantile 0.0001 in copy loss and quantile 0.99 in copy gain regions.

Once all three sets of parameters are fitted via the above procedures, we can calculate the probability of
assigning each gene in each cell to a certain CNV state via Eq.(2). Namely, we can obtain a cell-gene-state
probability tensor, as follows

$$p(z_{c,g,k} = 1|X_{c,g}, l_c, X_{ref,g}, \boldsymbol{C}) = \frac{\mathtt{NB}(X_{c,g}|l_c \cdot X_{ref,g} \cdot C_k, \phi_g)}{\sum_k \mathtt{NB}(X_{c,g}|l_c \cdot X_{ref,g} \cdot C_k, \phi_g)}. \tag{3}$$

4.6 Modelling: mixture model for phased allele-specific data (BAF module)

For the B-Allele Frequency (BAF) module, we took both AD and DP sparse matrices from xcltk, removed
marker genes provided by the RDR module, and performed the three-level phasing to generate gene_bin
based matrices as inputs for XClone modelling. Here, we used a beta-binomial distribution to model the
observed UMI (or read) counts for each CNV state, as follows

$$p(a_{c,g}|d_{c,g}, z_{c,g,k} = 1) = \mathtt{BB}(a_{c,g}|d_{c,g}, \rho_{g,k}, \tau_{g,k}), \tag{4}$$

where $a_{c,g}$ and $d_{c,g}$ denote phased B allele count and total count at gene_bin g in cell c, respectively. The Beta-
binomial is parameterised by the mean success rate ρ and concentration τ (namely $\alpha = \rho\tau$ and $\beta = (1-\rho)\tau$
in conventional parameterization). Here, we treat the concentration as a technical factor and shared by all
gene_bins in droplet-based data ($\tau_{g,k} = 100$ by default) while it can vary in smart-seq data depending on
the coverage of each gene_bin.

Here, $z_{c,g,k}$ is a latent variable indicating the cell c in gene_bin g is CNV state k ($z_{c,g,k} = 1$) or not
($z_{c,g,k} = 0$). The parameter $\rho_{g,k}$ denotes the expected allele frequency of gene_bin g in CNV state k. The
state index $k = \{0, 1, 2, 3, 4\}$ is respectively for allele A strong bias, allele A minor bias, allele balance, allele B

minor bias, and allele B strong bias, with the corresponding theoretical allele frequencies $\{0, 1/3, 0.5, 2/3, 1\}$
(Supp. Fig. S2).

The dataset-specific allele frequency parameters $\rho_{g,k}$ can also be estimated from the horizontally smoothed
BAF matrix to capture more accurate CNV patterns. Specifically, we first estimated the allele frequency for
copy neutral state $\rho_{g,k=2}$ from reference cells by directly using its gene_bin specific mean allele frequency. If
there are too few reference cells to accurately estimate the allele frequency, it can be set to 0.5 by default.
Next, to estimate the allele frequency of other BAF states $k = \{0, 1, 3, 4\}$, we applied a Gaussian mixture
model to the smoothed BAF matrix to identify five components with mean values, in order, for allele A bias
(strong, minor), allele balance and allele B bias (minor, strong) as an empirical estimation of the CNV ratio
for the BAF model. XClone also provides another mode of 3 BAF states (allele A bias, allele balance and
allele B bias) with the corresponding theoretical allele frequencies $\{0, 0.5, 1\}$ visualisation for comparison.

When the parameters are optimized above, similar to the RDR module, we can also obtain a cell-by-
gene_bin-by-state likelihood tensor by normalising Eq. (4), as follows,

$$p(z_{c,g,k} = 1 | a_{c,g}, d_{c,g}, \boldsymbol{\rho}_{g,\cdot}, \boldsymbol{\tau}_{g,\cdot}) = \frac{\mathsf{BB}(a_{c,g}|d_{c,g}, \rho_{g,k}, \tau_{g,k})}{\sum_k \mathsf{BB}(a_{c,g}|d_{c,g}, \rho_{g,k}, \tau_{g,k})}. \tag{5}$$

4.7 Post-analysis: CNV states smoothing, combination and denoise

Instead of directly using Eq. 3 and Eq. 5 for CNV states assignment at each gene (or gene_bin) in each
cell respectively in RDR and BAF modules, we further introduced a smoothing strategy for the state's
assignment. Specifically, for each module separately, we first performed a vertical smoothing via a KNN
connectivity matrix, as used in Section 4.4, and then we treated it as the input emission probability matrix
for horizontal smoothing by a hidden Markov model (HMM). For HMM, the start probability and transition
probability can be customised to capture different resolutions of smoothing. Here, we set start probability
$\{0.1, 0.8, 0.1\}$ (10x Genomics), $\{0.3, 0.4, 0.3\}$ (smart-seq) for the RDR module and $\{0.2, 0.15, 0.3, 0.15, 0.2\}$ for
the BAF module, and transition probability ($\{t = 10^{-6}, 1 - (K-1)t\}$ respectively for cross-state transition
and state keeping) as default. Then, we employed a forward-backward algorithm in HMM to achieve a
maximum likelihood for CNV assignment probabilities along genomic coordinates.

To combine the CNV states of RDR and BAF modules, we first need to synchronise feature dimensions,
as XClone's RDR module outputs a cell-by-gene-by-state CNV posterior probability tensor, while BAF has
a shape of cell-by-gene_bin-by-state. The default way is to map BAF gene_bin scale back to the gene scale
according to the RDR module. Then, we can combine the same dimensional RDR and BAF CNV posterior
probability tensors following the combination strategy in Supp. Fig. S2 to get the final combined CNV
posterior probability tensor.

After XClone detects the CNV states for each gene in each cell, a post-denoise step can be optionally
applied to clean the regions with a low chance of carrying CNVs. Specifically, for each gene, we calculated
the proportion of aneuploid cells and then fit a two-component Gaussian mixture model over the aneuploid
cell proportion among all genes. Then the genes assigned to the bottom component (i.e., with the lowest
proportion of aneuploid cells) will be taken as neural CNV regions, hence will be masked for CNV analysis.
Alternatively, users can manually set a threshold as cell proportion to denoise the probability matrix if there
is other evidence. We apply the post-denoise strategy default on the BAF module and it also can be applied
on the RDR and combined module by manually setting it.

4.8 Data generation, download, preprocessing and analysis

The BCH869 data generated using smart-seq2 was downloaded in FASTQ files from GEO (GSE102130) by
request from the authors. Within the original BCH869 dataset, there are 489 cells, with four tumor subclones
composed of 227, 221, 34 and 7 cells, according to the original study[14], 3 normal cells (Oligodendrocytes
and immune cells) from the same sample were combined in the dataset as reference cells in our study.

ATC2 is an anaplastic thyroid cancer sample with 6224 cells where tumor purity was found extremely
low [9]. TNBC1 is a triple-negative breast cancer sample with 1097 cells (2 subclones in tumor cells)[9]. The

ATC2 and TNBC1 datasets were generated using 3' 10x Genomics platform by Gao et al [9] and the aligned reads in BAM format and the called cell list were directly downloaded from GEO (GSE148673). For more details on the 3 datasets, see Supp. Table S1.

Given the aligned BAM file(s) and cell lists, we performed the genotyping by using cellsnp-lite v1.2.0 [13] and genotype phasing by using the Haplotype Reference Consortium panel [19] with EAGLE2[18], powered by Sanger Imputation Server (`https://imputation.sanger.ac.uk`). Then, feature counting was achieved by using xcltk v0.1.15 (see above Section 4.2).

4.9 Benchmarking CNV detection performance

It is necessary to benchmark the CNV inference methods using gold standard annotation as ground truth. The CNV profile of the BCH869 sample was well characterised by WGS and scRNA-seq, which is used as ground truth to identify copy number loss, copy number gain, and loss of heterozygosity. The BCH869 dataset has a complex clonal annotation (4 subclones with different CNV events) where the clone-specific CNV annotation was determined from the combination of scRNA-seq data (by InferCNV) and bulk WGS with haplotype analysis (Supp. Table S2).

With ground truth of BCH869 sample, we benchmarked XClone with four other CNVs detection tools specifically designed for scRNA-seq data, InferCNV[21], CaSpER[11], CopyKAT[9] and Numbat[12] (XClone v.0.3.4, InferCNV v.1.8.0, CopyKAT v.1.0.4, CaSpER v.0.2.0 and Numbat v.1.2.1) using their default parameters (details in Supp. Methods and running efficiency in Supp. Table S4).

For CNV detection performance evaluation at the single-cell level, we built a consensus cell-by-gene signal matrix for each tool at each CNV state. For XClone and Numbat, CNV event posterior probability was used to build a cell-by-gene matrix, and for InferCNV, CaSpER and CopyKAT, the modified expression was used. For Numbat and CaSpER whose output is at genomic region resolution, we mapped them to the gene level. The ground truth matrix is a same-dimensional cell-by-gene binary matrix indicating the existence of CNV events in the consensus cells and genes obtained above. The ground truth matrices are prepared for each state (copy gain, copy loss, and LOH) independently. Ground truth matrix value 1 indicates the CNV exists and 0 means not. By flattening the matrix and varying the cutoff on signal scores, we calculated the true positive rate (TPR) and false positive rate (FPR) between the detected (cell-by-gene signal matrix) and real CNV regions (cell-by-gene binary ground truth matrix) for each tool, further generated a receiver operating characteristic (ROC) curve and calculated the area under the ROC curve (AUC) values for evaluation. It is worth mentioning that for fair benchmarking with different tools, XClone can output CNVs in two resolutions: 1) gene_scale, where the CNV probabilities are reported for each gene in each cell; 2) chromosome arm_scale, where the CNV probabilities are reported for each arm of chromosomes in each cell. We showed the gene scale benchmarking results in Fig. **1**g-i and the chromosome arm scale benchmarking results in Supp. Fig. S5 for BCH869. Additionally, we also showed the Precision-Recall curves of each methods at both the gene scale and arm scale for BCH869 in Supp. Fig. S6.

Further, we take the ATC2 sample with extremely low tumor purity to benchmark the subclone identification performance. We found that inferCNV and CopyKAT both detect 2 subclones obviously (Fig. **2**g-h). By Combining expression with BAF analysis, we annotated the non-normal cells clusters into subclone1, and subclone2, which we used as cell annotation for assessing the subclonal detection performance for XClone by calculating the Adjusted Rand Index (ARI) metric (0.998 compared with inferCNV; 0.961 compared with CopyKAT, and 0.963 for inferCNV with CopyKAT, Fig. **2**a, bottom panel).

For the TNBC1 sample, as a high-quality annotation is lacking and it implies complex CNV profiles, we only used it in a qualitative manner by examining the consistency between the smoothed BAF signal (without inference) and the inferred CNV states. In this sample, the original paper reports two major subclones that comprised 44% (subclone A) and 28% (subclone B) of the tumour mass within the identified tumour cells [9]. By Combining expression with BAF analysis, we annotated the cell clusters into Clone 1, Clone 2 and Normal cells, which we used as cell annotation for assessing the clonal reconstruction performance for XClone by calculating the Adjusted Rand Index (ARI) metric (0.9653; Fig. **3**e).

Data availability

The BCH869 scRNA-seq data (Smart-seq2) raw FASTQ files were downloaded from GEO (GSE102130). The ATC2 scRNA-seq data (3' 10x Genomics) BAM files were downloaded from GEO (GSM4476492). The TNBC1 scRNA-seq data (3' 10x Genomics) BAM files were downloaded from GEO (GSM4476486).

Codes availability

XClone is implemented as an open-source Python package, publicly available at `https://github.com/single-cell-genetics/XClone`. XClone documentation and tutorials are publicly available at `https://xclone-cnv.readthedocs.io/en/latest/`. The preprocessing toolkit xcltk is freely available at `https://pypi.org/project/xcltk/`. The scripts for benchmarking can be found at `https://github.com/Rongtingting/CNV_calling_Benchmark`.

Contributions

Y.H. and O.S. conceived the study. R.H. and Y.H. designed the statistical model. R.H. led the implementation of the XClone software. R.H. performed all data analysis with help from X.H. X.H. implemented the xcltk preprocessing pipeline. X.H. and R.H. performed the benchmarking part. R.H. and Y.H. wrote the manuscript. All authors provided feedback on and approved the paper.

Acknowledgements

We thank Slava Ivanov for model exploration at the early stage. This project is supported by NSFC (62222217) and the University of Hong Kong through a startup fund and a seed fund (Y.H.). R.H. is supported by the University of Hong Kong via a University Postgraduate Fellowship.

References

1. Zack, T. I. *et al.* Pan-cancer patterns of somatic copy number alteration. *Nature genetics* **45**, 1134–1140 (2013).
2. Steele, C. D. *et al.* Signatures of copy number alterations in human cancer. *Nature* **606**, 984–991 (2022).
3. Nowakowska, B. Clinical interpretation of copy number variants in the human genome. *Journal of applied genetics* **58**, 449–457 (2017).
4. Pan-cancer analysis of whole genomes. *Nature* **578**, 82–93 (2020).
5. Minussi, D. C. *et al.* Breast tumours maintain a reservoir of subclonal diversity during expansion. *Nature* **592**, 302–308 (2021).
6. Zaccaria, S. & Raphael, B. J. Characterizing allele-and haplotype-specific copy numbers in single cells with chisel. *Nature biotechnology* 1–8 (2020).
7. Salehi, S. *et al.* Clonal fitness inferred from time-series modelling of single-cell cancer genomes. *Nature* **595**, 585–590 (2021).
8. Patel, A. P. *et al.* Single-cell rna-seq highlights intratumoral heterogeneity in primary glioblastoma. *Science* **344**, 1396–1401 (2014).
9. Gao, R. *et al.* Delineating copy number and clonal substructure in human tumors from single-cell transcriptomes. *Nature biotechnology* **39**, 599–608 (2021).
10. Fan, J. *et al.* Linking transcriptional and genetic tumor heterogeneity through allele analysis of single-cell rna-seq data. *Genome research* **28**, 1217–1227 (2018).
11. Serin Harmanci, A., Harmanci, A. O. & Zhou, X. Casper identifies and visualizes cnv events by integrative analysis of single-cell or bulk rna-sequencing data. *Nature communications* **11**, 1–16 (2020).
12. Gao, T. *et al.* Haplotype-aware analysis of somatic copy number variations from single-cell transcriptomes. *Nature Biotechnology* 1–10 (2022).
13. Huang, X. & Huang, Y. Cellsnp-lite: an efficient tool for genotyping single cells. *Bioinformatics* **37**, 4569–4571 (2021).
14. Filbin, M. G. *et al.* Developmental and oncogenic programs in h3k27m gliomas dissected by single-cell rna-seq. *Science* **360**, 331–335 (2018).

15. Ravi, N. *et al.* Identification of targetable lesions in anaplastic thyroid cancer by genome profiling. *Cancers* **11**, 402 (2019).

16. Miller, T. E. *et al.* Mitochondrial variant enrichment from high-throughput single-cell RNA sequencing resolves clonal populations. *Nature Biotechnology* 1–5 (2022).

17. Kwok, A. W. C. *et al.* MQuad enables clonal substructure discovery using single cell mitochondrial variants. *Nature communications* **13**, 1–10 (2022).

18. Loh, P.-R. *et al.* Reference-based phasing using the haplotype reference consortium panel. *Nature genetics* **48**, 1443–1448 (2016).

19. McCarthy, S. *et al.* A reference panel of 64,976 haplotypes for genotype imputation. *Nature genetics* **48**, 1279–1283 (2016).

20. Seabold, S. & Perktold, J. statsmodels: Econometric and statistical modeling with python. In *Proceedings of the 9th Python in Science Conference* (2010).

21. Tirosh, I. *et al.* Dissecting the multicellular ecosystem of metastatic melanoma by single-cell rna-seq. *Science* **352**, 189–196 (2016).