Stimulus expectations do not modulate visual event-related potentials in probabilistic cueing designs

Carla den Ouden** [1], Andong Zhou ** [1], Vinay Mepani[1], Gyula Kovács [2], Rufin Vogels[3], Daniel Feuerriegel[1]

1. Melbourne School of Psychological Sciences, The University of Melbourne
2. Institute of Psychology, Friedrich Schiller University Jena, Jena, Germany
3. Laboratorium voor Neuro- en Psychofysiologie, Department of Neurosciences, KU Leuven, Leuven, Belgium

** Denotes shared first-authorship reflecting equal contributions

Corresponding Author:

Daniel Feuerriegel

dfeuerriegel@unimelb.edu.au

Melbourne School of Psychological Sciences. Redmond Barry Building, The University of Melbourne, 3010, Australia

Highlights

- We performed a probabilistic cueing experiment while recording EEG.
- We tested for effects of fulfilled expectations, surprise, and image repetition.
- No expectation-related effects were observed.
- Robust within- and across-trial repetition effects were found.
- We did not find support for predictive coding models of expectation effects.

Stimulus expectations do not modulate visual ERPs

Abstract

Humans and other animals can learn and exploit repeating patterns that occur within

their environments. These learned patterns can be used to form expectations about

future sensory events. Several influential predictive coding models have been

proposed to explain how learned expectations influence the activity of stimulus-

selective neurons in the visual system. These models specify reductions in neural

response measures when expectations are fulfilled (termed expectation suppression)

and increases following surprising sensory events. However, there is currently scant

evidence for expectation suppression in the visual system when confounding factors

are taken into account. Effects of surprise have been observed in blood oxygen level

dependent (BOLD) signals, but not when using electrophysiological measures. To

provide a strong test for expectation suppression and surprise effects we performed a

predictive cueing experiment while recording electroencephalographic (EEG) data.

Participants (n=48) learned cue-face associations during a training session and were

then exposed to these cue-face pairs in a subsequent experiment. Using univariate

analyses of face-evoked event-related potentials (ERPs) we did not observe any

differences across expected (90% probability), neutral (50%) and surprising (10%) face

conditions. Across these comparisons, Bayes factors consistently favoured the null

hypothesis throughout the time-course of the stimulus-evoked response. When using

multivariate pattern analysis we did not observe above-chance classification of

expected and surprising face-evoked ERPs. By contrast, we found robust within- and

across-trial stimulus repetition effects. Our findings do not support predictive coding-

based accounts that specify reduced prediction error signalling when perceptual

expectations are fulfilled. They instead highlight the utility of other types of predictive

processing models that describe expectation-related phenomena in the visual system

without recourse to prediction error signalling.

Keywords: EEG, ERP, expectation, surprise, prediction

	1. Introduction
29	
30	Humans and other animals can learn from recurring patterns of sensory input and
31	form predictions about upcoming events. For example, after hearing a loud bark one
32	might expect to see a dog and would be surprised upon seeing a cat instead. These so-
33	called predictive processes can help us to detect unusual or novel events (Ulanovsky et
34	al., 2003; Press et al., 2020), identify deviations from regular sequences of stimuli (Fiser
35	& Aslin, 2002; Sherman et al., 2020) and make faster perceptual decisions when our
36	expectations are fulfilled (Mulder et al., 2012; Gold & Stocker, 2017).
37	A plethora of theories and models have been proposed to explain how
38	predictive processes influence the activity of stimulus-selective neurons in the visual
39	system (e.g., Rao & Ballard, 1999; Friston, 2005, 2010; Summerfield & de Lange, 2014;
40	Spratling, 2017; Keller & Mrsic-Flogel, 2018; Hogendoorn & Burkitt, 2019; Press et al.,
41	2020). Among these, a set of widely-influential hierarchical predictive coding models
42	(Friston, 2005, 2010; Bastos et al., 2012; Clark, 2013; Summerfield & de Lange, 2014)
43	have been developed based on the premise that sensory systems are continuously
44	attempting to infer the underlying causes of incoming sensory signals. This is
45	proposed to occur via generation and continuous updating of internal models of an
46	organism's sensory environment. Discrepancies between the internal model and
47	sensory input are thought to be indexed by activity of prediction error neurons that
48	are prevalent throughout the cortical hierarchy of the visual system (e.g., Friston,
49	2010). According to these predictive coding models, an organism can use past
50	experience to update its internal model in anticipation of expected sensory input.
51	When an observed stimulus matches the organism's expectations the degree of
52	prediction error (and activity of prediction error neurons) should be less than when
53	the stimulus is not expected (Summerfield & de Lange, 2014). Here, we describe
54	prediction errors as indexing the *absolute* degree of discrepancy between expectations
55	and sensory input with respect to a given feature space (in contrast to signed reward
56	prediction errors as defined in Schultz, 2016). We define expectations as predictions to
57	see certain stimuli (or stimulus features) that are formed *prior* to the appearance of
58	the stimulus (in contrast to e.g., Rao & Ballard, 1999, see Andersen & Chemero, 2013).
59	The diversity of predictive coding implementations (e.g., Bastos et al., 2012;
60	Spratling, 2017; Keller & Mrsic-Flogel, 2018) makes it difficult to derive specific model

predictions that are both i.) shared across models and ii.) unique to predictive coding

accounts (see Cao, 2020; Milkowski & Litwin, 2022). However, there is one hypothesis

that is relatively consistent across the models described above: that neural response

measures should inversely scale with the subjective appearance probability of a

presented stimulus (Walsh et al., 2020; Feuerriegel et al., 2021a). In the visual system

this hypothesis has been tested by entraining expectations to see particular stimuli in

certain contexts. For example, this is achieved by consistently pairing a visual stimulus

with a preceding cue (in predictive cueing designs, e.g., Egner et al., 2010) or

manipulating the frequency with which different stimuli are presented (e.g., Kimura et

al., 2009; Bell et al., 2016). Stimuli that conform to learned expectations are termed

expected stimuli, and those that violate such expectations are termed surprising

stimuli. A subset of studies also presented conditions whereby two or more different

stimuli are each expected to appear with equal probability (termed neutral stimuli, for

further definition see Arnal & Giraud, 2012; Feuerriegel et al., 2021a). We note that the

terms 'expected', 'surprising' and 'neutral' are defined here in ways that are consistent

with how these terms have been used in closely related work (e.g., Egner et al., 2010;

Rahnev et al., 2011; Amado et al., 2016; Feuerriegel et al., 2018a; Dunovan & Wheeler,

2018, for further discussion see Feuerriegel et al., 2021a). These terms may not cleanly

map onto concepts with similar names in other predictive processing frameworks, for

example those that describe quantitative measures of surprise (e.g., Baldi & Itti, 2010;

Loued-Khenissi & Preuschoff, 2020). Researchers have reported smaller fMRI BOLD

signals (Summerfield et al., 2008; Egner et al., 2010; Grotheer & Kovács, 2015) and

firing rates (Meyer & Olson, 2011; Bell et al., 2016) for expected compared to surprising

stimuli.

These effects have been collectively called expectation suppression (ES;

Summerfield et al., 2008; Todorovic & de Lange, 2012). According to predictive coding

accounts, ES is assumed to reflect suppressed, silenced or dampened responses when

one's expectations are fulfilled compared to when there are no consistent expectations

to see a particular stimulus (i.e., an expected-neutral condition difference,

Summerfield et al., 2008; Egner et al., 2010). For example, ES would lead to smaller

neural response measures when a single stimulus is cued to appear with high

probability (an expected stimulus) compared to when two different stimuli could each

be expected to appear with 50% probability (a neutral stimulus). These effects are

thought to be analogous to effects of expectation violation whereby surprising stimuli

(e.g., low appearance probability) evoke larger prediction error responses than

expected or neutral conditions (Egner et al., 2010).

In our recent review (Feuerriegel et al., 2021a) we reported that, for fMRI BOLD

signals in the visual system, there is actually limited and inconsistent evidence for ES

defined as an expected-neutral difference. BOLD signal differences between expected

and surprising stimuli were apparently due to surprise-related increases rather than

any suppression associated with expectation fulfilment (e.g., Summerfield & Koechlin,

2008; Amado et al., 2016).

In addition, multiple confounding factors were identified in Feuerriegel et al.

(2021a) that may mimic expectation effects in commonly used experiment designs.

One prominent confound is effects of repetition suppression and adaptation, whereby

stimuli that are identical (or similar) to those that were recently encountered evoke

reduced neural response magnitudes (Grill-Spector et al., 2006; Solomon & Kohn,

2014; Vogels, 2016). These effects are dissociable from those of cued probabilistic

expectations (Kaliukhovich & Vogels, 2011, 2014; Larsson & Smith, 2012; Grotheer &

Kovács, 2015; Vinken et al., 2018; Tang et al., 2018; Feuerriegel et al., 2018a; Solomon et

al., 2021). Importantly, adaptation effects can extend across experimental trials and

intervening stimulus presentations (Bayliss & Rolls, 1987; Kaliukhovich & Vogels, 2014;

Henson, 2016; Fritsche et al., 2022). Differences in the novelty of a stimulus

(operationalised as the number of times a stimulus has been encountered in an

experiment) can also lead to larger responses for relatively novel stimuli (Xiang &

Brown, 1998; Mur et al., 2010; Manahova et al., 2018). Both adaptation and novelty

effects are particularly problematic in experiments that entrain expectations by

manipulating the presentation frequency of different stimuli (e.g., Bastos et al., 2020).

Here, we note that some confounding factors have been described as consequences of

biased expectations, such as repetition suppression (Summerfield et al., 2008;

Auksztulewicz & Friston, 2016). If these descriptions are accurate, then expectation-

related effects should still be observed even when controlling for these confounds.

When these confounding factors are taken into account, it appears that

surprise-related effects on BOLD signals in predictive cueing designs (e.g., Amado et

al., 2016) have not replicated when using electrophysiological measures, such as firing

rates and local field potential amplitudes in macaques (e.g., Kaliukhovich & Vogels,

2011; Vinken et al., 2018; Solomon et al., 2021) and event-related potentials/fields

(ERPs/ERFs) in humans (Kok et al., 2017; Rungratsameetaweemana et al., 2018;

Solomon et al., 2021; reviewed in Feuerriegel et al., 2021a). Studies that did report

expected-surprising differences found effects at frontal channels or topographies

consistent with effects on the parietal P3 ERP component rather than sources in visual

cortex (Summerfield et al., 2011; Hall et al., 2018; Feuerriegel et al., 2018a). Solomon et

al. (2021) only reported differential ERPs to surprising stimuli when they were

designated as targets in a go/no-go task. These effects resembled ERP components

associated with target detection in perceptual decision tasks (e.g., Loughnane et al.,

2016). ES and surprise effects have been observed in macaques during predictive

cueing and statistical learning experiments that involved weeks of sequence learning

prior to recording (Meyer & Olson, 2011; Meyer et al., 2014; Ramachandran et al., 2017;

Schwiedrzik & Freiwald, 2017; Kaposvari et al., 2018; Esmailpour et al., 2022), however

these effects have not been consistently replicated in human studies whereby

sequences were learned over 1-2 testing sessions (e.g., Manahova et al., 2018; Zhou et

al., 2020; reviewed in Feuerriegel et al., 2021a).

It is possible that expectation effects are more subtle than previously assumed

and may require larger samples than what is typical of existing work in humans (e.g.,

n=23 in Kok et al., 2017; discussed in Feuerriegel et al., 2021a). In addition, participants

could not form expectations for specific images in Rungratsameetaweemana et al.

(2018) and expectation-related effects may be most prominent (or detectable) when

there are specific expectations for a combination of low- and high-level features.

Providing strong tests for expectation effects on electrophysiological measures is

important because prediction error signalling mechanisms are proposed to be directly

related to changes in ERPs, firing rates and local field potentials (e.g., Friston, 2005;

Bastos et al., 2012). By contrast, effects on fMRI BOLD signals are more difficult to

interpret because they can arise from additional consequences of surprise, such as

increased pupil dilation (O'Reilly et al., 2013; Richter & de Lange, 2019, discussed in

Feuerriegel et al., 2021a).

Here, we tested for ES and surprise effects in humans using a larger (n=48)

sample than previous electrophysiological studies while accounting for relevant

confounding factors identified in Feuerriegel et al. (2021a). We used a predictive

cueing design whereby a cue signalled the appearance probability of a subsequent face

image, ranging between 10% (surprising), 50% (neutral) and 90% (expected). We

compared ERPs evoked by expected, neutral and surprising faces using mass-

univariate analyses to characterise expectation effects across the entire time-course of

the stimulus-evoked response. We also tested for expected-surprising differences that

are broadly distributed across the scalp using multivariate pattern analysis (MVPA). In

each cueing condition only two different face images could potentially appear,

meaning that participants could form expectations for specific low- and high-level

stimulus features. In our design, expected and surprising faces were task-relevant but

did not require an immediate decision or motor response. This allowed us to avoid

ERP effects related to target detection or perceptual decision processes (e.g.,

O'Connell et al., 2012) that produced apparent surprise responses in one experiment of

Solomon et al. (2021).

We additionally included another neutral expectation condition in which one

of four face images could each be expected to appear with 25% probability (here

termed the 25% neutral condition). This allowed us to test for a different expectation-

related effect associated with the number of different stimuli that could potentially be

expected to appear (predictability effects) identified in previous work (Pajani et al.,

2017; Feuerriegel et al., 2018a; Rostalski et al., 2020). We also tested for stimulus

repetition effects to compare their time-courses to effects of ES or surprise. If the time

courses are different (as in Feuerriegel et al., 2018a) then this would further support

the view that repetition suppression and ES are distinct phenomena (contrary to e.g.,

Summerfield et al., 2008; Auksztulewicz & Friston, 2016).

183   **2. Method**

2.1. Participants

Fifty participants were recruited for this experiment. Participants were fluent in

English and had normal or corrected-to-normal vision. One participant was excluded

because of inconsistent cue-face relationships used across the training session and

experiment due to experimenter error. One additional participant was excluded

because of a response keypad malfunction during the first two blocks of the training

session. This left 48 participants for both behavioural and EEG data analyses (32

women, 16 men, 44 right-handed) aged between 18 and 35 ($M = 22.0$, $SD = 2.9$). This

was a substantially larger sample than existing studies testing for electrophysiological

expectation effects using predictive cueing designs (e.g., n=23 in Kok et al., 2017; n=17

in Rungratasemeetaweemana et al., 2018; n=22 in Solomon et al., 2021). As these

studies did not report statistically significant expectation effects, we did not have an *a*

priori effect size target for statistical power analyses. Instead, we aimed to maximise

measurement precision for frequentist and Bayesian statistical tests. Here we note

that, if the activity of superficial pyramidal neurons in visual cortex reflects prediction

errors (Friston, 2005; Bastos et al., 2012), one might expect to observe moderate to

large effects of stimulus expectations on EEG signals. Participants were reimbursed 45

AUD for their time. This study was approved by the Human Research Ethics

Committee of the University of Melbourne.

2.2. Stimuli

Stimuli were presented at a distance of 80cm on a 27" Benq RL2755 LCD monitor

(60Hz refresh rate) in a darkened room. Stimuli were presented using MATLAB and

functions from PsychToolbox (Brainard, 1997; Kleiner et al., 2007). Code used for

stimulus presentation will be available at osf.io/ahuc4/ at the time of publication. Cue

stimuli included seven animal images from the Bank of Standardised Stimuli (Brodeur

et al., 2014). Four female faces of neutral expression (denoted here as faces A/B/C/D)

were also presented (as used in Rostalski et al., 2020). Faces were greyscale and

centred with the fixation cross between the eyes. Face images were cropped so that

only the face was shown on a black background, omitting any hair, clothing or

jewellery. Example stimuli are displayed in Figure 1. Face stimuli were used because

previous experiments presenting faces have reported surprise-related effects using

fMRI (e.g., Summerfield et al., 2008; Amado et al., 2016) and in visual oddball designs

using EEG (e.g., Feuerriegel et al., 2021b). The first face that appeared in each trial

subtended 5.87 * 5.30 degrees of visual angle. The second face image in each trial was

20% smaller to increase the difficulty of the face matching task (described below).

2.3. Procedure

Prior to the experiment the EEG cap was set up and participants completed a

training session to learn the probabilistic cue-face associations. Seven different cues

were presented, which each cued the appearance probabilities of subsequently

presented face images A/B/C/D. The first cue indicated that Face A would appear with

90% probability (an expected stimulus), and Face B with 10% probability (a surprising

stimulus). The second cue instead indicated Face B would appear with 90%

probability and Face A with 10% probability. For the third and fourth cues, the same

probabilities were indicated in relation to Faces C and D. The fifth cue indicated that

either Faces A or B could each appear with 50% probability (50% neutral stimuli), and

the sixth cue indicated that faces C or D could each appear with 50% probability. The

seventh cue indicated that Faces A, B, C, or D could each appear with 25% probability

(25% neutral stimuli). These neutral conditions were included as comparison

conditions to isolate and quantify ES and surprise effects. The 25% neutral condition

was also included to test for effects of face image predictability (Rostalski et al., 2020)

and to provide an additional comparison condition used to test for ES (discussed in

Feuerriegel et al., 2021a). Examples of cue-face associations for a participant are shown

in Figure 1A. Animal images allocated to each cue type were counterbalanced across

participants.

During training, each of the seven cue-face associations was introduced in separate

sections. At the beginning of each section participants were shown the animal cue

image. They were then shown the associated faces and explicitly told the appearance

probability of each face following the cue. Following this, participants passively viewed

a block of trials during which a cue was presented for 400ms, and after a 500ms

interval a face image was presented for 400ms. Following the offset of this face a

fixation cross was presented for 1,200ms before the start of the following trial (Figure

1B). Faces followed the cues according to the instructed appearance probabilities. For

example, for the cue that indicates 90% probability for Face A and 10% for Face B, Face

A was presented nine times within the block and Face B was presented once. These

blocks included ten trials each for cues 1-6 and 20 trials for the seventh cue.

After the presentation of the first two cues, participants then completed a face

identification task. In each trial of this task, one of the two cues was presented for

400ms followed by a face image for 400ms after a 500ms interval (Figure 1C).

Participants were required to press keys 1 or 3 on a TESORO Tizona numpad (1000Hz

polling rate) using their left or right index finger depending on the face identity shown

(A or B). In half of trials the first cue was presented, and in the other half the second

cue was presented (randomly interleaved). During the task the overall probabilities

(averaged across cues) of Faces A and B appearing were 50%. This task was repeated

following the introduction of the third and fourth cues (presenting faces C and D), the

fifth cue (Faces A/B) and the sixth cue (Faces C/D). After instructions relating to the

seventh cue, participants were instructed to respond to only two of the four faces (A

and C) using left/right index fingers and to not respond when the other faces

appeared. Following their response, participants were provided with feedback

regarding the accuracy of their choice ('correct' or 'error') if their response was made

within 1200ms following face onset. If a response was not made in this window the

feedback 'too slow' was presented. If responses were made prior to face onset the

feedback 'too fast' was presented. Each face identification task block included 60 trials.

This task served to further strengthen the learned cue-face associations and allowed us

to assess whether participants had learned these associations based on task

performance across conditions. The training session lasted approximately twenty

minutes.

Right after the training session participants began the experiment. We used a

probabilistic cueing design that minimises confounds related to stimulus repetition

and recency that are prominent in some other designs (Feuerriegel et al., 2021a). In

each trial (depicted in Figure 1D) an animal cue was first presented for 400ms. After a

500ms interstimulus interval a face image (termed the S1 face) was presented for

400ms. Following another 500ms interstimulus interval, the second face in the trial

(S2 face) was presented for 400ms. After S2 face offset there was a 1200ms inter-trial

interval during which a fixation cross was displayed. Participants completed a face

matching task in which they were required to judge whether the S1 and S2 face images

were the same (repetitions) or different (alternations) by pressing keys 1 and 3 on the

numpad with their left and right index fingers. Key assignments were counterbalanced

across participants. Participants were required to make a response within 1200ms after

S2 face onset. If a response was not made during this window, the feedback 'too slow'

was presented for 1,000ms. If responses were made prior to S2 face onset then 'too fast'

feedback was presented. This task ensured that the S1 faces predicted by each cue were

task-relevant, but did not require an immediate perceptual decision and keypress

response (see also Kok et al., 2017).

Prior to the experiment participants completed practice trials until they were

confident in their ability to perform the task. Practice trials were identical to those in

the experiment except that participants were provided with feedback ('correct', 'error',

'too fast', 'too slow') for 1,000ms after the response window following S2 face onset in

each trial. A fixation cross was displayed for 800ms between the offset of task feedback

and the presentation of the cue in the subsequent trial.

There were 70 trials per block, consisting of 36 expected faces, four surprising

faces, twenty 50% neutral faces, and ten 25% neutral faces. Each face image was

presented an equal number of times within each block. Participants completed 12

blocks including a total of 840 trials. At the end of each block participants were

notified of their accuracy and mean RT for correct responses in that block.

Participants had self-paced breaks between each block (minimum 10 seconds). The

experiment (excluding breaks) lasted approximately 48 minutes.

Figure 1. Cue-face associations and trial diagrams. A) An example of cue-face associations for a participant. Each animal image cue

predicted the subsequent appearance of one of two face images with 90% probability (expected faces), 10% probability (surprising

faces) or 50% probability (50% neutral faces). An additional cue predicted one of four faces to each appear with 25% probability (25%

neutral faces). B) An example trial in the training session whereby participants were passively exposed to cue-face pairs. C) An

example trial from the training session face identification task. Participants were required to press one of two keys depending on the

face identity presented in each trial. For the 25% neutral cue condition, participants were instructed to press keys in response to two

of the face identities, and not to respond if one of the other two faces were presented. D) An example trial from the experiment.

Participants were required to press one of two keys based on whether the second (S2) face presented in the trial was the same or a

different identity to the first (S1) face. Neither the animal cues or the S1 face identity were predictive of the S2 face being a repetition

or alternation. All face images shown here are subject to a Pixabay license (https://pixabay.com/hu/service/license/). These images

were not part of the actual stimulus set and we do not have permission to publish the original images. All images in this figure have

been processed in the same way as the original stimuli.

2.4. Task Performance Analyses

To assess whether participants had learned the cue-face associations in the

training session we derived measures of accuracy (proportion correct) and mean RTs

for trials with correct responses. Analyses were performed in JASP v0.16.4 (JASP Core

Team). We compared performance across expected (90%), 50% neutral and surprising

(10%) faces. Accuracy was near ceiling for some conditions and was not normally

distributed and so Wilcoxon signed-rank tests were used to test for differences in

accuracy across conditions. Paired-samples t tests were used to test for differences in

mean RTs. Bonferroni corrections were used to adjust the alpha level for multiple

comparisons. Bayesian versions of each test were also run to derive Bayes factors in

favour of the alternative hypothesis (Cauchy prior distribution, width 0.707, 1,000

samples drawn for signed-rank tests). Because the training task for 25% probability

faces included 50% of trials where no response was required (resulting in a hybrid face

identification and go/no-go task) we did not compare performance between this and

other conditions.

Performance on the face matching task during the experiment was measured

by calculating accuracy and mean RTs for trials with correct responses. We compared

accuracy across conditions using Wilcoxon signed-rank tests with Bonferroni

corrections as described above. We compared mean RTs across S1 face appearance

probability conditions using a one-way repeated measures ANOVA. A Greenhouse-

Geisser correction was used to account for sphericity violations. RTs were also

compared across repeated and alternating face conditions using a paired-samples t

test. Bayesian versions of each test were also run in JASP.

2.5. EEG Data Acquisition and Processing

We recorded EEG using a 64-channel Biosemi Active II system (Biosemi, The

Netherlands) with a sampling rate of 512 Hz. Recordings were grounded using

common mode sense and driven right leg electrodes

(http://www.biosemi.com/faq/cms&drl.htm). We added six additional electrodes: two

electrodes placed 1 cm from the outer canthi of each eye, and electrodes placed above

and below the center of each eye.

We processed EEG data using EEGLab v2022.0 (Delorme & Makeig, 2004) in

MATLAB (Mathworks). The EEG dataset and data processing and analysis code will be

available at osf.io/ahuc4/ at the time of publication. First, we identified excessively

noisy channels by visual inspection (mean number of bad channels = 0.5, range 0-3)

and excluded these from average reference calculations and Independent Components

Analysis (ICA). Sections with large amplitude artefacts were also manually identified

and removed. We then low-pass filtered the data at 40 Hz (EEGLab Basic Finite

Impulse Response Filter New, default settings), re-referenced the data to the average

of all channels and removed one extra channel (AFz) to compensate for the rank

deficiency caused by average referencing. We duplicated the dataset and additionally

applied a 0.1 Hz high-pass filter (EEGLab Basic FIR Filter New, default settings) to

improve stationarity for the ICA. The ICA was performed on the high-pass filtered

dataset using the RunICA extended algorithm (Jung et al., 2000). We then copied the

independent component information to the non high-pass filtered dataset (e.g., as

done by Feuerriegel et al., 2018a). Independent components associated with blinks and

saccades were identified and removed according to guidelines in Chaumon et al.

(2015). After ICA, we interpolated previously removed noisy channels and AFz using

the cleaned dataset (spherical spline interpolation). EEG data were then high-pass

filtered at 0.1 Hz.

The resulting data were segmented from -100ms to 800ms relative to cue onset,

S1 face onset and S2 face onset. Epochs were baseline-corrected using the prestimulus

interval. Epochs containing amplitudes exceeding ±100μV from baseline at any of the

64 scalp channels, as well as epochs from trials with 'too fast' or 'too slow' responses to

S2 faces, were rejected (cues: mean epochs retained = 786 out of 840, range 629-837, S1

faces: mean = 792, range 636-839, S2 faces: mean = 793, range 629-838). Statistics

relating to numbers of epochs retained per condition are displayed in Supplementary

Table S1.

2.6. Mass-Univariate Analyses of ERPs

As face-evoked ERP components are most prominent at bilateral parietal and

parieto-occipital channels (e.g., Quek & Rossion, 2017; Feuerriegel et al., 2021b) we

defined a parieto-occipital region of interest (ROI) covering electrodes P7, P8, P9, P10,

PO7 and PO8. Trial-averaged ERPs in each condition were averaged across channels

within this ROI prior to analyses. To provide a more comprehensive coverage of visual

cortex we defined an additional occipital ROI covering electrodes Oz, O1, O2, POz,

and Iz. Data from this ROI was used in follow-up analyses (results displayed in the

Supplementary Material).

384   To test for expectation effects across the time-course of the S1 face-evoked

response we used mass-univariate analyses of ERPs. Paired-samples t tests were

performed at each time point relative to stimulus onset. Cluster-based permutation

tests based on the cluster mass statistic were used to account for multiple

comparisons (Maris & Oostenveld, 2007; 461 comparisons per analysis, 10,000

permutation samples, cluster forming alpha = .01, family-wise alpha = .05) using

functions from the Decision Decoding Toolbox v1.0.5 (Bode et al., 2019). For each

permutation sample, condition labels were swapped for a random subset of

participants and paired-samples t tests were performed at each time point. All t values

corresponding to uncorrected p-values of < .01 were formed into clusters with any

neighbouring such t values. Adjacent time points were considered temporal

neighbours. The sum of the t values within each cluster is termed the 'mass' of that

cluster. The largest cluster masses from each of the 10,000 permutation samples were

used to estimate the null distribution. The masses of each cluster identified in the

original dataset were then compared to the null distribution. The percentile ranking of

each cluster mass value relative to the null distribution was used to derive the p-value

for each cluster. This method provides control over the weak family-wise error rate

while maintaining high sensitivity to detect effects (Maris and Oostenveld, 2007,

Groppe et al., 2011).

403   We performed separate sets of mass-univariate analyses to compare ERPs

across different pairs of conditions. This allowed us to separately test for each

hypothesised effect. To test for combined effects of ES and surprise (as done in

previous work, e.g., Feuerriegel et al., 2018a; Richter & de Lange, 2019), we compared

ERPs following S1 faces in expected (90%) and surprising (10%) conditions. To test for

ES effects we compared ERPs across expected and 50% neutral, as well as expected and

25% neutral conditions. To test for effects of surprise we compared ERPs across

surprising and 50% neutral conditions. To test for effects of image predictability

(Feuerriegel et al., 2018a; Rostalski et al., 2020) we compared ERPs across 50% and

25% neutral conditions, in which either two or four face images could be expected to

appear, respectively. To derive estimates of evidence for the null and alternative

hypotheses at each timepoint we calculated Bayes factors at each time point for each

comparison using Bayesian paired-samples t tests as implemented in the BayesFactor

toolbox v2.3.0 (Krekelberg, 2022, default settings).

To compare the time-courses of stimulus repetition and expectation effects (as

done in Feuerriegel et al., 2018a) we additionally tested for effects of within- and

across-trial image repetition using mass-univariate analyses as described above. To

test for within-trial face repetition effects we compared ERPs evoked by S2 faces when

preceded by the same face as compared to a different S1 face identity. To test for

across-trial repetition effects we compared ERPs evoked by cue images based on

whether the cue in the previous trial was the same or a different image. We also

compared ERPs evoked by S1 faces depending on whether the S2 face in the previous

trial was the same or a different face identity.

2.7. Multivariate Pattern Classification Analyses

The ROI-based mass-univariate analyses described above are sensitive to

between-condition amplitude differences that are consistent across participants but

are less sensitive to ERP pattern differences that vary across individuals or effects that

occur outside of the predefined ROIs. To better test for such effects we used MVPA

using support vector machine (SVM) classification as implemented in DDTBOX v1.0.5

(Bode et a., 2019) interfacing LIBSVM (Chang & Lin, 2011). To test for the combined

influence of ES and surprise effects we trained classifiers to discriminate between

expected and surprising S1 faces. These were preceded by the same cue images,

meaning that late ERP differences across cue images could not contribute to above-

chance classification performance (e.g., via effects on pre S1 face ERP baselines). Please

note that here we did not classify face identity, but rather the expected or surprising

status of the S1 faces. To compare the classification accuracy time-courses against

within-trial repetition effects we also trained classifiers to discriminate between S2

faces based on whether they were preceded by the same face (repetition trials) or a

different face image (alternation trials).

We used a sliding window approach whereby epochs were split into non-
overlapping analysis time windows of 10ms in duration. Within each time window
EEG amplitudes were averaged separately for each of the 64 scalp channels to create a
spatial vector of brain activity (64 features) corresponding to each trial. In cases where
one condition included more epochs than the other, a random subset of epochs was
drawn from the former condition to balance epoch numbers. Data from each
condition were then split into five subsets of epochs. SVM classifiers (cost parameter C
= 1) were trained on the first four subsets (80% of the data) from each condition and
subsequently tested using the remaining subset to derive a classification accuracy
measure. This was repeated until each subset had been used once for testing. This 5-
fold cross-validation procedure was then repeated another five times with different
epochs randomly allocated to each subset each time to minimise drawing biases. The
average classification accuracy across all cross-validation steps and analysis repetitions
was taken as the estimate of classification performance for each participant. This
procedure was repeated with randomly permuted condition labels assigned to each
trial to derive an empirical chance distribution.

Classification performance using the original data was compared against
permuted-labels classification performance at the group level using paired-samples t
tests on data from each analysis time window. As we aimed to detect above-chance
classification performance we used one-tailed tests. We used cluster-based
permutation tests (settings as described above) to correct for multiple tests across
analysis time windows.

3. Results

3.1. Training Session Task Performance

Accuracy and mean RTs for each cueing condition in the face identification
task are plotted in Figure 2A-B. Participants achieved higher accuracy for expected
compared to surprising faces, $Z = 4.79$, $p < .001$, $BF_{10} > 2,600$, and 50% neutral
compared to surprising faces, $Z = 5.28$, $p < .001$, $BF_{10} > 5,800$ (Figure 2A). Participants
were slightly more accurate for 50% neutral as compared to expected faces, $Z = 2.65$, p
$= .008$, $BF_{10} = 7.42$. This is likely due to a block order effect. 50% neutral face training
blocks were always presented after blocks of expected and surprising faces, meaning

that participants were better practiced at the task when identifying neutral faces. RTs

were faster for expected compared to both 50% neutral, $t(47) = -4.22$, $p < .001$, $BF_{10} =$

209.92, and surprising faces, $t(47) = -6.25$, $p < .001$, $BF_{10} > 128{,}900$ (Figure 2B).

However, we did not observe faster RTs for 50% neutral compared to surprising faces,

$t(47) = -1.56$, $p = .125$, $BF_{10} = 0.49$. Higher accuracy and faster RTs for expected faces

indicates that participants successfully learned the cue-face associations within the

training session.

Please note that accuracy and mean RTs are plotted in Figure 2A-B also for 25%

neutral faces requiring a keypress response. However due to the difference in task for

this condition (with 50% of trials requiring no response) these were not compared

with the other conditions.

3.2. Experiment Task Performance

During the experiment accuracy was generally high across all S1 face expectancy

conditions for the S1-S2 face matching task (Figure 2C). Accuracy was slightly lower in

trials with surprising as compared to expected S1 faces, $Z = 2.06$, $p = .040$, $BF_{10} = 2.67$,

congruent with previous reports of impaired decision-making for stimuli immediately

following surprising events (reviewed in Wessel, 2018). However this effect was not

statistically significant when adjusting for multiple tests. Differences in accuracy were

not observed when comparing other S1 face expectancy conditions, expected-50%

neutral: $Z = 0.55$, $p = .586$, $BF_{10} = 0.16$, 50% neutral-surprising: $Z = 1.89$, $p = .059$, $BF_{10} =$

1.93, 50% neutral – 25% neutral: $Z = -1.58$, $p = .115$, $BF_{10} = 0.67$. Differences in mean RTs

were not observed across expectancy conditions, $F(2.15, 101.20) = 2.21$, $p = .112$, $BF_{10} =$

0.37 (Figure 2D). RTs for repeated faces were faster than those for alternating faces,

$t(47) = -10.07$, $p < .001$, $BF_{10} = > 30^{10}$ (Figure 2E) consistent with Rostalski et al. (2020).

Figure 2. Task performance during the training session and experiment. A) Accuracy in the training session face identification task by

cued stimulus appearance probability. Dots represent values for individual participants. Horizontal black lines denote group means.

For the 25% probability condition accuracy refers to the proportion of target faces that were correctly identified. B) Mean RTs for

correct trials. C) Accuracy in the face matching task by S1 face appearance probability condition. D) Mean RTs for correct trials by S1

face probability. E) Mean RTs for correct trials by S1-S2 repetition (Rep) or alternation (Alt) status.

3.3. Expectation and Predictability Effects on S1 Face-Evoked ERPs

We did not observe statistically-significant ERP amplitude differences across any of the compared expectancy conditions. Group-averaged ERPs for each set of conditions, difference waves, standardised Cohen's d effect size estimates (Cohen, 1988) and Bayes factors in favour of the alternative hypothesis are displayed in Figure 3. We did not observe differences between ERPs evoked by expected and surprising faces (Figure 3A), expected and 50% neutral faces (Figure 3B), expected and 25% neutral faces (Figure 3C), or 50% neutral and surprising faces (Figure 3D). Amplitude differences and standardised effect size point estimates were very small. Bayes factors generally provided evidence in favour of the null (values smaller than 1/3) across the time-course of the S1 face-evoked response.

We also compared ERPs across 50% and 25% neutral conditions to test for predictability effects (reported in Pajani et al., 2017; Feuerriegel et al., 2018a; Rostalski et al., 2020). Statistically-significant differences were not observed after correction for multiple comparisons. Bayes factors were in favour of the null hypothesis across most of the peristimulus time window (Figure 3E).

Results of analyses of ERPs at the occipital ROI (displayed in the Supplementary Material) were consistent with those described here.

Stimulus expectations do not modulate visual ERPs

Figure 3. Group-averaged ERPs evoked by expected (90% appearance probability), surprising (10% probability), and neutral (50% and

25% probability) S1 faces. A) Expected - surprising ERP differences. B) Expected – 50% neutral differences. C) Expected – 25% neutral

differences. D) 50% neutral - surprising differences. E) 50% neutral – 25% neutral differences. ERPs are averaged across channels

within the parieto-occipital ROI including channels PO7/8, P7/8 and P9/10. ERPs for each pair of compared conditions are displayed

along with difference waves (with shading denoting standard errors), Cohen's d estimates and Bayes factors in favour of the

alternative hypothesis.

3.4. Effects of Within-Trial Repetition on S2 Face-Evoked ERPs

Multiple within-trial face repetition effects were observed between 170-800ms from S2 face onset. Group-averaged ERPs for repeated and alternating S2 faces are displayed in Figure 4A. Scalp maps showing effect topographies are plotted in Figure 4B. This included an effect between 170-215ms (cluster mass = 90.58, critical cluster mass = 57.49, p = .044), an effect spanning 238-348ms (cluster mass = 409.79, p < .001) an effect spanning 379-453ms (cluster mass = 158.66, p = .009) and an effect spanning 754-800ms from S2 face onset (cluster mass = 92.79, p = .042). The timing and spatial distributions of these effects were broadly consistent with previously reported face repetition effects (e.g., Schweinberger & Neumann, 2016; Feuerriegel et al., 2018a, 2019).

3.5. Effects of Across-Trial Repetition on Cue- and S1 Face-Evoked ERPs

A number of across-trial cue image repetition effects were observed spanning 125-547ms from cue onset. Group–averaged ERPs evoked by cues that were either the same or different to the cue in the preceding trial are presented in Figure 4C. Cue repetition effects were observed between 125-172ms (cluster mass = 121.74, critical cluster mass = 47.50, p = .014), between 195-234ms (cluster mass = 87.22, p = .032) and between 254-547ms from cue stimulus onset (cluster mass = 769.71, p < .001). Topographies of effects (displayed in Figure 4D) resembled those observed for within-trial face repetition effects.

We also compared S1 face-evoked ERPs across conditions whereby the S2 face in the preceding trial was the same or a different face identity. Group-averaged ERPs are displayed in Figure 4E and scalp maps of effects are shown in Figure 4F. Across-trial repetition effects were observed between 178-229ms (cluster mass = 102.57, critical cluster mass = 39.88, p = .019) and between 664-725ms from S1 face onset (cluster mass = 105.78, p = .018).

Figure 4. Within- and across-trial repetition effects for S2 faces, cues, and S1 faces. A) S2 face-evoked ERPs depending on whether the S2 face was the same as the S1 face identity (repetition/Rep) or a different face (alternation/Alt). B) Scalp maps of face repetition effects for S2 faces averaged over each statistically significant time window. C) Cue-evoked ERPs depending on whether the cue image was the same as the cue in the previous trial (Rep) or a different cue (Alt). D) Scalp maps of across-trial cue

repetition effects averaged over each statistically significant time window. E) S1 face-

evoked ERPs depending on whether the S2 face in the previous trial was the same

(Rep) or a different identity (Alt). E) Scalp maps of across-trial S1 face repetition

effects averaged over each statistically significant time window. ERPs are averaged

across channels within the parieto-occipital ROI including channels PO7/8, P7/8 and

P9/10. ERPs for each pair of compared conditions are displayed along with difference

waves (with shading denoting standard errors), Cohen's d estimates and Bayes factors

in favour of the alternative hypothesis. Please note that Bayes factors are plotted on

logarithmic scales due to the wide ranges of values across the time-course of the

stimulus-evoked response. Grey shaded areas denote time windows of statistically

significant differences.

3.6. Multivariate Pattern Classification Results

We used MVPA to test for patterns of single-trial ERPs that discriminate

between expected (90% probability) and surprising (10%) S1 faces. S1 face expectancy

could not be classified at above-chance levels at any time during the epoch (Figure

5A). We did not attempt to classify between other expectancy conditions as the

preceding cue images systematically differed across these conditions within each

participant dataset. In these cases, late cue image-specific ERPs can influence S1 face

pre-stimulus baselines to produce spurious above-chance classification performance.

The within-trial repetition or alternation status of S2 faces could be classified at

above-chance levels from 160 ms after S2 face onset until the end of the epoch (cluster

mass = 948.72, critical cluster mass = 4.73, cluster p < .001).

Figure 5. Multivariate pattern classification results. A) Classification accuracy for discriminating between expected (90% appearance

probability) and surprising (10% probability) S1 faces. Blue lines display classification performance for the original data and orange

lines show performance for the data with permuted condition labels (empirical chance distribution). Shaded regions denote standard

errors. B) Classification accuracy for discriminating between repeated and alternating S2 faces. The magenta shaded area denotes the

time window of statistically significant above-chance classification performance.

4. Discussion

A set of influential predictive coding models specify that the response magnitudes of

visual stimulus-selective neurons should inversely scale with the subjective

appearance probability of a stimulus (Friston, 2005, 2010; Summerfield & de Lange,

2014; Walsh et al., 2020). To test this hypothesis, we entrained participants'

expectations to see particular face identities after certain cue images. Task

performance results indicated that participants had learned these cue-face

associations during a training session. We then presented the same cue-face

associations in our experiment. Importantly, the cued faces were task-relevant but did

not require an immediate decision or motor action. Despite analysing a large (n=48)

sample we did not observe effects of either ES or surprise on face-evoked ERPs. Bayes

factors instead signalled substantial support for the null hypothesis throughout the

time-course of the face-evoked response (BF_{10} values of ~0.2 for the majority of time

points for each comparison). We also did not replicate image predictability effects

observed in Feuerriegel et al. (2018a). However, we observed within- and across-trial

image repetition effects for cue and face stimuli.

Our results, taken together with multiple null findings reported in earlier

studies, indicate that expectations in predictive cueing designs are not sufficient to

produce differences in stimulus-evoked electrophysiological responses within the

human visual system. This is incongruent with models that specify reduced prediction

error signalling when an observer's expectations are fulfilled (e.g., Friston, 2005, 2010;

Clark, 2013; Summerfield & de Lange, 2014) but is consistent with a growing body of

electrophysiological work using predictive cueing designs that did not report effects of

ES or surprise on responses of visual stimulus-selective neurons (Kaliukhovich &

Vogels, 2011, 2014; Kok et al., 2017; Vinken et al., 2018; Rungratsameetaweemana et al.,

2018; Solomon et al., 2021).

We additionally report that both within- and across-trial repetition effects can

be readily observed in the absence of expectation effects. This is in line with most

contemporary models of adaptation (e.g., Solomon & Kohn, 2014; Vogels, 2016) but is

incongruent with predictive coding-based models that describe repetition suppression

as a product of biased expectations toward previously-seen stimuli (e.g., Summerfield

et al., 2008; Auksztulewicz & Friston, 2016).

4.1. Consequences of Cued Expectations on ERPs

We did not observe evidence for either ES or surprise effects on face-evoked ERPs. Bayes factors instead indicated evidence in favour of the null hypothesis throughout the peristimulus time window. Even when using MVPA, which can exploit distributed patterns of EEG signals across the scalp and ERP differences that are idiosyncratic to participants, we did not see above-chance classification accuracy when comparing expected and surprising faces.

Our findings are consistent with previous work using predictive cueing designs and electrophysiological recordings that did not report expectation effects (Kok et al., 2017; Rungratsameetaweemana et al., 2018; Kaliukhovich & Vogels, 2011; Vinken et al., 2018; Solomon et al., 2021; reviewed in Feuerriegel et al., 2021a). Although ERP differences between expected and surprising stimuli have been reported (Summerfield et al., 2011; Hall et al., 2018; Feuerriegel et al., 2018a) the topographies of these effects more closely indicate frontal sources or effects on the centro-parietal positivity ERP component (O'Connell et al., 2012; Twomey et al., 2015) rather than sources in the visual system. Tang et al. (2018) reported smaller visual N1 component peak amplitudes for surprising gratings, however this was likely a result of peak amplitude measurement biases due to a smaller number of trials per participant in the surprising condition (Thomas et al., 2004). Additionally, Solomon et al. (2021) reported expected-surprising differences only when surprising stimuli were targets, but the timing and topography of these effects closely resembled target detection-related ERP components observed in similar perceptual decision-making tasks (Loughnane et al., 2016). By contrast, in our design a perceptual decision was not required immediately following the expected and surprising S1 faces. Other effects of stimulus appearance probability outside of the visual system, such as those on P3 component amplitudes in oddball designs (Duncan-Johnson & Donchin, 1977; Polich & Margala, 1997), also appear to be absent when the critical stimuli do not prompt an immediate decision (Kimura et al., 2009; Feuerriegel et al., 2018b, 2021b; Amado & Kovács, 2016; File & Czigler, 2019).

At least three distinct possibilities arise from these findings. The first is that, in our study and in previous work, participants did not learn the predictive associations

between cues and subsequently presented stimuli. We consider this unlikely because

participants were explicitly told the cue-face contingencies in our experiment and

demonstrated faster RTs for expected stimuli in the training session task (see also Kok

et al., 2017; Rungratsameetaweeana et al., 2018; Vinken et al., 2018). During our

experiment participants were further exposed to the expected cue-face pairs at least

100 times per cue. This would be expected to provide at least an equivalent

opportunity to learn cue-stimulus associations as compared to existing fMRI

predictive cueing designs (e.g., Egner et al., 2010).

The second possibility is that effects of fulfilled expectations and surprise are

not expressed in neural activity that contributes to EEG and other electrophysiological

measures, but are instead captured by changes in BOLD signals. Effects of surprise

(but not ES) in predictive cueing designs have been identified and replicated across

fMRI studies (e.g., Summerfield & Koechlin, 2008; Amado et al., 2016; reviewed in

Feuerriegel et al., 2021a). However, this would run counter to the idea that prediction

errors are signalled by cortical pyramidal neurons that typically contribute to invasive

recordings and EEG/MEG (e.g., Friston, 2005; Bastos et al., 2012).

Notably, the inferences drawn from fMRI studies are complicated by additional

effects of surprise (separate from prediction error signalling) that contribute to the

BOLD response. For example, Richter & de Lange (2019) reported expected-surprising

BOLD signal differences for object images only when participants completed an object

categorisation task, and not during a task in which the objects were task-irrelevant

(see also Larsson & Smith, 2012). In addition, they found that RT differences between

expected and surprising conditions in the categorisation task correlated with BOLD

signal differences across the same conditions in V1 and temporal occipital fusiform

cortex. RTs are typically faster for expected stimuli (e.g., den Ouden et al., 2010;

Mulder et al., 2012; Richter et al., 2018) and similar associations between RTs and

BOLD signals in visual areas have been documented across decision-making tasks

(Yarkoni et al., 2009; Mumford et al., 2023). Such associations are thought to reflect

variation in the duration of decision-making processes that involve attention and

visual working memory, termed a time-on-task effect (Yarkoni et al., 2009).

Importantly, the probabilistic cueing studies that reported surprise effects on BOLD

signals did not include RT as a regressor in their models. Such effects are also relevant

to designs whereby participants detect a rare target that is distinct from the critical

stimuli (e.g., inverted faces, Summerfield et al., 2008; Larsson & Smith, 2012;

Feuerriegel et al., 2018a). This is because each stimulus requires a decision to

determine that it is not a target, even if no motor response is required in target-absent

trials (akin to a go/no-go task, Murphy et al., 2015). Time-on-task effects could be

interpreted within predictive coding frameworks as reflecting the duration of

prediction error signalling, where model convergence is slower for surprising stimuli.

However, this would be incongruent with the finding that surprise effects were task-

dependent in Richter and de Lange (2019).

Richter and de Lange (2019) also identified increased pupil dilation for

surprising stimuli from ~600 ms post stimulus onset, which correlated with the degree

of expected-surprising BOLD signal differences in V1. Notably, this pupil dilation

effect was not present when object stimuli were task-irrelevant. This can be

understood as a secondary consequence of surprise, whereby increased pupil dilation

leads to changes in retinal input and corresponding effects on low temporal resolution

BOLD signals in visual cortex. In addition, BOLD signal increases for surprising

stimuli have also been attributed to attentional capture once a stimulus is identified as

unexpected (see Press et al., 2020; Alink & Blank, 2021). These examples demonstrate

that surprise-related BOLD signal increases may not be straightforwardly attributed to

prediction error signalling, and that further work is required to disentangle co-

occurring, confounding phenomena. It remains to be determined why fMRI BOLD

signals show different patterns to electrophysiological measures under equivalent

conditions.

The third possibility is that cued expectations simply do not influence

stimulus-evoked activity of visual stimulus-selective neurons in predictive cueing

designs. This would suggest that prior observations of ES and surprise effects are not

due to reduced prediction error signalling that occurs when expectations are fulfilled,

but are rather due to co-occurring phenomena (such as pupil dilation) or confounding

factors (such as adaptation, discussed in Feuerriegel et al., 2021a).

To be clear, we acknowledge that there are consequences of learned

expectations that, in certain circumstances, can influence activity in the visual system

as well as behaviour. There are documented effects of directed attention guided by

expectations (Corbetta et al., 1990; Reynolds & Heeger, 2009) and pre-activation of

expected stimulus representations (Kok et al., 2017; Blom et al., 2020; Feuerriegel et al.,

2021c). Beyond the visual system, biases in motor action preparation (de Lange et al.,

2013; Gold & Stocker, 2017; Kelly et al., 2021) can enable faster responses when

expectations to see a particular stimulus are paired with expectations to make a

certain motor action. There are also well-documented effects associated with reward

predictions errors and information gain in areas such as the insula and striatum (e.g.,

Loued-Khenissi & Preuschoff, 2020; Schultz, 2016). Rather, our findings suggest that

appeals to ES and cortical prediction error minimisation via top-down inhibition are

not necessary to adequately model expectation-related phenomena in the visual

system. This highlights the utility of alternative models that describe a range of cued

expectation effects without recourse to ES (e.g., Spratling, 2017; Heeger, 2017; Press et

al., 2020, 2022; Feuerriegel et al., 2021c; Hogendoorn, 2022). Notably, many of these

models describe top-down excitatory rather than inhibitory modulations of stimulus-

selective visual neurons. This is consistent with evidence that cortical feedback

projections within the visual system predominantly originate from, and target,

excitatory rather than inhibitory neurons (reviewed in Spratling, 2017).

Mechanisms described in these models are likely to interact with other

processes that exploit the spatiotemporal structure of sensory environments. These

processes include adaptation (Solomon & Kohn, 2014; Vogels, 2016; Whitmire &

Stanley, 2016), surround suppression (Carandini & Heeger, 2012), end-stopping (Rao &

Ballard, 1999), as well as retinal circuit mechanisms that rapidly adjust to local

luminance levels (Rieke & Rudd, 2009), environmental image structure (Hosoya et al.,

2005), periodic stimulation patterns (Schwartz et al., 2007; Schwartz & Berry, 2008)

and smooth motion (Berry et al., 1999; Johnson et al., 2023). Systematically

investigating these interactions will likely uncover a host of novel predictive

phenomena, including feedforward or inherited effects across the visual cortical

hierarchy (e.g., Dhruv et al., 2011; Larsson et al., 2016).

4.2. Stimulus Predictability Effects

We also tested for stimulus predictability effects, operationalised here as differences in

the number of different stimuli that an observer could expect to appear. In Feuerriegel

et al. (2018a) we observed predictability effects at electrodes over visual cortex.

However, the relatively unpredictable faces in Feuerriegel et al. (2018a) were also more

novel than predictable faces. When controlling for this novelty confound in our

experiment, we did not replicate these effects.

Notably, we have observed predictability effects on BOLD signals in the

Fusiform Face Area (Rostalski et al., 2020) while controlling for a similar novelty

confound in Pajani et al. (2017). This appears to be another example of BOLD signal

effects that are not replicated when using electrophysiological measures.

4.3. Image Repetition Effects

We observed within- and across-trial repetition effects with similar latencies

and topographies to those reported in prior work (e.g., Schweinberger & Neumann,

2016; Feuerriegel et al., 2018a, 2019). Our findings complement existing evidence that

repetition effects last over multiple intervening stimulus presentations (Bayliss &

Rolls, 1987; Kaliukhovich & Vogels, 2014; Henson, 2016; Fritsche et al., 2022) and

highlight the need to strictly control for stimulus repetition and recency when testing

for consequences of learned expectations.

Our findings are consistent with work demonstrating distinct and separable

repetition and expectation effects (Grotheer & Kovács, 2015; Feuerriegel et al., 2018a;

Tang et al., 2018) and cortical adaptation in the absence of ES (Kaliukhovich & Vogels,

2011, 2014; Vinken & Vogels, 2018; Solomon et al., 2021). This body of evidence is not

congruent with models that describe repetition suppression and adaptation as

reflecting biased expectations toward recently seen stimuli (Summerfield et al., 2008;

Auksztulewicz & Friston, 2016). These findings instead preferentially support

normalisation-based models of adaptation (e.g., Dhruv et al., 2014; Solomon & Kohn,

2014; Vogels, 2016), which can account for a wide range of adaptation-related

phenomena without recourse to expectations or prediction error minimisation (e.g.,

Dhruv et al., 2011; Patterson et al., 2013; Kaliukhovich & Vogels, 2016).

Here, we note that the S1/S2 face repetition effect spanning 379-453ms from S2

face onset resembles the topography of the centro-parietal positivity (CPP)

component (O'Connell et al., 2012) and is likely a consequence of faster RTs (and

earlier CPP onsets) for repeated as compared to unrepeated stimuli (discussed in

Feuerriegel et al., 2022).

4.4. Limitations

Our findings should be interpreted with the following caveats in mind. Firstly, the

models and empirical evidence discussed here pertain to the visual system and may

not be representative of other sensory systems. For example, expectation effects have

been reported in auditory predictive cueing designs (e.g., Todorovic & de Lange, 2012).

BOLD signals in other brain areas such as the insula have also been found to scale

with quantitative measures of uncertainty and surprise (Preuschoff et al., 2008; Mohr

et al., 2010; Loued-Khenissi et al., 2020), although these effects may depend on the

task-relevance of expected and surprising stimuli (Richter & de Lange, 2019). The EEG

signals measured in our experiment may not be sensitive to neuronal activity within

the insula and other deep brain structures such as the striatum. In addition, our

inferences specifically relate to consequences of expectations that are formed in

advance of stimulus appearance. The term expectation has been used to describe other

phenomena within predictive coding models (e.g., Rao & Ballard, 1999; see Andersen &

Chemero, 2013), which may indeed arise via prediction error minimisation

mechanisms (for approximations of predictive coding in the retina see Hosoya et al.,

2005; Rieke & Rudd, 2009; Spratling, 2017). Our findings are not directly relevant to

those phenomena.

We also have focused on evidence from predictive cueing designs in which

there is a clear logic regarding how participants' expectations are manipulated. Effects

attributed to expectation violations have been reported in visual oddball designs,

although they are not always consistent across experiments using different stimulus

categories (e.g., Kimura et al., 2009; Male et al., 2020; Amado & Kovács, 2016;

Feuerriegel et al., 2021b) or tasks (File & Czigler, 2019; Petro et al., 2023). In macaques,

ES and surprise effects on electrophysiological measures have been observed in

statistical learning designs that involve weeks of training and hundreds of image

pairings (e.g., Meyer & Olson, 2011; Ramachandran et al., 2017; Kaposvari et al., 2018).

However, such effects have not been consistently replicated across studies with

human participants and shorter training periods that more closely match

hypothesised timescales of internal model updating in predictive coding accounts

(e.g., Manahova et al., 2018; Zhou et al., 2020). The qualitatively different patterns of

effects across paradigms highlights the importance of building a coherent body of

evidence *within* each paradigm and warrant caution when comparing our findings to

those from other designs.

In addition, we manipulated expectations relating to face images, meaning that

we cannot rule out ES or surprise effects on neurons selective for other stimulus

features (but see Kok et al., 2017; Solomon et al., 2021). Future work could adapt our

design to manipulate expectations relating to a broader set of stimulus features.

We also note that our analyses of ERP amplitudes focus on phase-locked EEG

responses, rather than non phase-locked effects that may be uncovered using time-

frequency analyses (e.g., Zhou et al., 2020; but see Vinken & Vogels, 2018; Solomon et

al., 2021). Our experiment was not designed to cleanly isolate time-frequency

responses evoked by single stimuli within each trial.

4.5. Conclusion

Our findings add to the growing body of evidence showing that expectations in

predictive cueing designs do not modulate electrophysiological responses in visual

stimulus-selective neurons. This evidence does not support predictive coding-based

accounts of how expectations shape neural activity in the visual system. We further

show that stimulus repetition and expectation effects are distinct and separable,

contrary to predictive coding-based models of repetition suppression and adaptation.

Acknowledgements

This project was supported by an Australian Research Council Discovery Early Career

Researcher Award to D.F. (ARC DE220101508). Funding sources had no role in study

design, data collection, analysis or interpretation of results. We thank the research

groups led by Floris de Lange, Clare Press and Daniel Yon for their insightful

comments on our findings.

Declaration of Interest Statement

Declarations of interest: none.

References

Alink, A., & Blank, H. (2021). Can expectation suppression be explained by reduced attention to predictable stimuli? *NeuroImage, 231*, 117824.

Amado, C., Hermann, P., Kovács, P., Grotheer, M., Vidnyánszky, Z., & Kovács, G. (2016). The contribution of surprise to the prediction based modulation of fMRI responses. *Neuropsychologia, 84*, 105-112.

Amado, C., & Kovács, G. (2016). Does surprise enhancement or repetition suppression explain visual mismatch negativity?. *European Journal of Neuroscience, 43*(12), 1590-1600.

Anderson, M. L., & Chemero, T. (2013). The problem with brain GUTs: Conflation of different senses of" prediction" threatens metaphysical disaster. *Behavioral and Brain Sciences, 3*, 204.

Arnal, L. H., & Giraud, A. L. (2012). Cortical oscillations and sensory predictions. *Trends in Cognitive Sciences, 16*(7), 390-398.

Auksztulewicz, R., & Friston, K. (2016). Repetition suppression and its contextual determinants in predictive coding. *Cortex, 80*, 125-140.

Baldi, P., & Itti, L. (2010). Of bits and wows: A Bayesian theory of surprise with applications to attention. *Neural Networks, 23*(5), 649-666.

Bastos, A. M., Usrey, W. M., Adams, R. A., Mangun, G. R., Fries, P., & Friston, K. J. (2012). Canonical microcircuits for predictive coding. *Neuron, 76*(4), 695-711.

Bastos, A. M., Lundqvist, M., Waite, A. S., Kopell, N., & Miller, E. K. (2020). Layer and rhythm specificity for predictive routing. *Proceedings of the National Academy of Sciences, 117*(49), 31459-31469.

Baylis, G. C., & Rolls, E. T. (1987). Responses of neurons in the inferior temporal cortex in short term and serial recognition memory tasks. *Experimental Brain Research, 65*, 614-622.

Bell, A. H., Summerfield, C., Morin, E. L., Malecek, N. J., & Ungerleider, L. G. (2016). Encoding of stimulus probability in macaque inferior temporal cortex. *Current Biology, 26*(17), 2280-2290.

Berry, M. J., Brivanlou, I. H., Jordan, T. A., & Meister, M. (1999). Anticipation of moving stimuli by the retina. *Nature*, *398*(6725), 334-338.

Blom, T., Feuerriegel, D., Johnson, P., Bode, S., & Hogendoorn, H. (2020). Predictions drive neural representations of visual events ahead of incoming sensory information. *Proceedings of the National Academy of Sciences*, *117*(13), 7510-7515.

Bode, S., Feuerriegel, D., Bennett, D., & Alday, P. M. (2019). The Decision Decoding ToolBOX (DDTBOX)–A multivariate pattern analysis toolbox for event-related potentials. *Neuroinformatics*, *17*, 27-42.

Brainard, D. H., & Vision, S. (1997). The psychophysics toolbox. *Spatial Vision*, *10*(4), 433-436.

Brodeur, M. B., Guérard, K., & Bouras, M. (2014). Bank of standardized stimuli (BOSS) phase II: 930 new normative photos. *PLoS One*, 9(9), e106953.

Cao, R. (2020). New labels for old ideas: Predictive processing and the interpretation of neural signals. *Review of Philosophy and Psychology*, *11*(3), 517-546.

Carandini, M., & Heeger, D. J. (2012). Normalization as a canonical neural computation. *Nature Reviews Neuroscience*, *13*(1), 51-62.

Chang, C. C., & Lin, C. J. (2011). LIBSVM: a library for support vector machines. *ACM Transactions on Intelligent Systems and Technology (TIST)*, *2*(3), 1-27.

Chaumon, M., Bishop, D. V., & Busch, N. A. (2015). A practical guide to the selection of independent components of the electroencephalogram for artifact correction. *Journal of Neuroscience Methods*, *250*, 47-63.

Clark, A. (2013). Whatever next? Predictive brains, situated agents, and the future of cognitive science. *Behavioral and Brain Sciences*, *36*(3), 181-204.

Cohen, J. (1988). *Statistical power analysis for the behavioral sciences*. Academic press.

Corbetta, M., Miezin, F. M., Dobmeyer, S., Shulman, G. L., & Petersen, S. E. (1990). Attentional modulation of neural processing of shape, color, and velocity in humans. *Science*, *248*(4962), 1556-1559.

de Lange, F. P., Rahnev, D. A., Donner, T. H., & Lau, H. (2013). Prestimulus oscillatory activity over motor cortex reflects perceptual expectations. *Journal of Neuroscience, 33*(4), 1400-1410.

Delorme, A., & Makeig, S. (2004). EEGLAB: An open source toolbox for analysis of single-trial EEG dynamics including independent component analysis. *Journal of Neuroscience Methods, 134*(1), 9-21.

den Ouden, H. E., Daunizeau, J., Roiser, J., Friston, K. J., & Stephan, K. E. (2010). Striatal prediction error modulates cortical coupling. *Journal of Neuroscience, 30*(9), 3210-3219.

Dhruv, N. T., Tailby, C., Sokol, S. H., & Lennie, P. (2011). Multiple adaptable mechanisms early in the primate visual pathway. *Journal of Neuroscience, 31*(42), 15016-15025.

Duncan-Johnson, C.C., & Donchin, E. (1977). On quantifying surprise: The variation of event-related potentials with subjective probability. *Psychophysiology, 14*(5), 456-467.

Dunovan, K., & Wheeler, M. E. (2018). Computational and neural signatures of pre and post-sensory expectation bias in inferior temporal cortex. *Scientific Reports, 8*(1), 13256.

Egner, T., Monti, J. M., & Summerfield, C. (2010). Expectation and surprise determine neural population responses in the ventral visual stream. *Journal of Neuroscience, 30*(49), 16601-16608.

Esmailpour, H., Raman, R., & Vogels, R. (2023). Inferior temporal cortex leads prefrontal cortex in response to a violation of a learned sequence. *Cerebral Cortex, 33*(6), 3124-3141.

Feuerriegel, D., Churches, O., Coussens, S., & Keage, H. A. (2018a). Evidence for spatiotemporally distinct effects of image repetition and perceptual expectations as measured by event-related potentials. *NeuroImage, 169*, 94-105.

Feuerriegel, D., Keage, H. A., Rossion, B., & Quek, G. L. (2018b). Immediate stimulus repetition abolishes stimulus expectation and surprise effects in fast periodic visual oddball designs. *Biological Psychology*, *138*, 110-125.

Feuerriegel, D., Churches, O., Coussens, S., & Keage, H. A. (2019). Temporal expectations modulate face image repetition suppression of early stimulus evoked event-related potentials. *Neuropsychologia*, *122*, 76-87.

Feuerriegel, D., Vogels, R., & Kovács, G. (2021a). Evaluating the evidence for expectation suppression in the visual system. *Neuroscience & Biobehavioral Reviews*, *126*, 368-381.

Feuerriegel, D., Yook, J., Quek, G. L., Hogendoorn, H., & Bode, S. (2021b). Visual mismatch responses index surprise signalling but not expectation suppression. *Cortex*, *134*, 16-29.

Feuerriegel, D., Blom, T., & Hogendoorn, H. (2021c). Predictive activation of sensory representations as a source of evidence in perceptual decision-making. *Cortex*, *136*, 140-146.

Feuerriegel, D., Murphy, M., Konski, A., Mepani, V., Sun, J., Hester, R., & Bode, S. (2022). Electrophysiological correlates of confidence differ across correct and erroneous perceptual decisions. *NeuroImage*, *259*, 119447.

File, D., & Czigler, I. (2019). Automatic detection of violations of statistical regularities in the periphery is affected by the focus of spatial attention: A visual mismatch negativity study. *European Journal of Neuroscience*, *49*(10), 1348-1356.

Fiser, J., & Aslin, R. N. (2002). Statistical learning of higher-order temporal structure from visual shape sequences. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, *28*(3), 458.

Friston, K. (2005). A theory of cortical responses. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *360*(1456), 815-836.

Friston, K. (2010). The free-energy principle: a unified brain theory? *Nature Reviews Neuroscience*, *11*(2), 127-138.

Fritsche, M., Solomon, S. G., & de Lange, F. P. (2022). Brief stimuli cast a persistent long-term trace in visual cortex. *Journal of Neuroscience*, *42*(10), 1999-2010.

Gold, J. I., & Stocker, A. A. (2017). Visual decision-making in an uncertain and dynamic world. *Annual Review of Vision Science*, *3*, 227-250.

Grill-Spector, K., Henson, R., & Martin, A. (2006). Repetition and the brain: Neural models of stimulus-specific effects. *Trends in Cognitive Sciences*, *10*(1), 14-23.

Groppe, D. M., Urbach, T. P., & Kutas, M. (2011). Mass univariate analysis of event-related brain potentials/fields I: A critical tutorial review. *Psychophysiology*, *48*(12), 1711-1725.

Grotheer, M., & Kovács, G. (2015). The relationship between stimulus repetitions and fulfilled expectations. *Neuropsychologia*, *67*, 175-182.

Hall, M. G., Mattingley, J. B., & Dux, P. E. (2018). Electrophysiological correlates of incidentally learned expectations in human vision. *Journal of Neurophysiology*, *119*(4), 1461-1470.

Heeger, D. J. (2017). Theory of cortical function. *Proceedings of the National Academy of Sciences*, *114*(8), 1773-1782.

Henson, R. N. (2016). Repetition suppression to faces in the fusiform face area: A personal and dynamic journey. *Cortex*, *80*, 174-184.

Hogendoorn, H. (2022). Perception in real-time: Predicting the present, reconstructing the past. *Trends in Cognitive Sciences*, *26*(2), 128-141.

Hogendoorn, H., & Burkitt, A. N. (2019). Predictive coding with neural transmission delays: A real-time temporal alignment hypothesis. *Eneuro*, *6*(2).

Hosoya, T., Baccus, S. A., & Meister, M. (2005). Dynamic predictive coding by the retina. *Nature*, *436*(7047), 71-77.

Johnson, P. A., Blom, T., van Gaal, S., Feuerriegel, D., Bode, S., & Hogendoorn, H. (2023). Position representations of moving objects align with real-time position in the early visual response. *eLife*, *12*, e82424.

Jung, T. P., Makeig, S., Westerfield, M., Townsend, J., Courchesne, E., & Sejnowski, T. J. (2000). Removal of eye activity artifacts from visual event-related potentials in normal and clinical subjects. *Clinical Neurophysiology, 111*(10), 1745-1758.

Kaliukhovich, D. A., & Vogels, R. (2011). Stimulus repetition probability does not affect repetition suppression in macaque inferior temporal cortex. *Cerebral Cortex, 21*(7), 1547-1558.

Kaliukhovich, D. A., & Vogels, R. (2014). Neurons in macaque inferior temporal cortex show no surprise response to deviants in visual oddball sequences. *Journal of Neuroscience, 34*(38), 12801-12815.

Kaliukhovich, D. A., & Vogels, R. (2016). Divisive normalization predicts adaptation-induced response changes in macaque inferior temporal cortex. *Journal of Neuroscience, 36*(22), 6116-6128.

Kaposvari, P., Kumar, S., & Vogels, R. (2018). Statistical learning signals in macaque inferior temporal cortex. *Cerebral Cortex, 28*(1), 250-266.

Keller, G. B., & Mrsic-Flogel, T. D. (2018). Predictive processing: A canonical cortical computation. *Neuron, 100*(2), 424-435.

Kelly, S. P., Corbett, E. A., & O'Connell, R. G. (2021). Neurocomputational mechanisms of prior-informed perceptual decision-making in humans. *Nature Human Behaviour, 5*(4), 467-481.

Kimura, M., Katayama, J. I., Ohira, H., & Schröger, E. (2009). Visual mismatch negativity: New evidence from the equiprobable paradigm. *Psychophysiology, 46*(2), 402-409.

Kleiner, M., Brainard, D., & Pelli, D. (2007). What's new in Psychtoolbox-3?

Kok, P., Mostert, P., & De Lange, F. P. (2017). Prior expectations induce prestimulus sensory templates. *Proceedings of the National Academy of Sciences, 114*(39), 10473-10478.

Krekelberg, B. (2022). BayesFactor: Release 2022 (v2.3.0). Zenodo. doi.org/10.5281/zenodo.7006300

Larsson, J., & Smith, A. T. (2012). fMRI repetition suppression: Neuronal adaptation or stimulus expectation? *Cerebral Cortex, 22*(3), 567-576.

Larsson, J., Solomon, S. G., & Kohn, A. (2016). fMRI adaptation revisited. *Cortex, 80,* 154-160.

Loued-Khenissi, L., & Preuschoff, K. (2020). Information theoretic characterization of uncertainty distinguishes surprise from accuracy signals in the brain. *Frontiers in Artificial Intelligence, 3,* 5.

Loued-Khenissi, L., Pfeuffer, A., Einhäuser, W., & Preuschoff, K. (2020). Anterior insula reflects surprise in value-based decision-making and perception. *Neuroimage, 210,* 116549.

Loughnane, G. M., Newman, D. P., Bellgrove, M. A., Lalor, E. C., Kelly, S. P., & O'Connell, R. G. (2016). Target selection signals influence perceptual decisions by modulating the onset and rate of evidence accumulation. *Current Biology, 26*(4), 496-502.

Male, A. G., O'Shea, R. P., Schröger, E., Müller, D., Roeber, U., & Widmann, A. (2020). The quest for the genuine visual mismatch negativity (vMMN): Event-related potential indications of deviance detection for low-level visual features. *Psychophysiology, 57*(6), e13576.

Manahova, M. E., Mostert, P., Kok, P., Schoffelen, J. M., & De Lange, F. P. (2018). Stimulus familiarity and expectation jointly modulate neural activity in the visual ventral stream. *Journal of Cognitive Neuroscience, 30*(9), 1366-1377.

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG-and MEG-data. *Journal of Neuroscience Methods, 164*(1), 177-190.

Meyer, T., & Olson, C. R. (2011). Statistical learning of visual transitions in monkey inferotemporal cortex. *Proceedings of the National Academy of Sciences, 108*(48), 19401-19406.

Meyer, T., Ramachandran, S., & Olson, C. R. (2014). Statistical learning of serial visual transitions by neurons in monkey inferotemporal cortex. *Journal of Neuroscience, 34*(28), 9332-9337.

Miłkowski, M., & Litwin, P. (2022). Testable or bust: Theoretical lessons for predictive processing. *Synthese*, *200*(6), 462.

Mohr, P. N., Biele, G., & Heekeren, H. R. (2010). Neural processing of risk. *Journal of Neuroscience*, *30*(19), 6613-6619.

Mulder, M. J., Wagenmakers, E. J., Ratcliff, R., Boekel, W., & Forstmann, B. U. (2012). Bias in the brain: a diffusion model analysis of prior probability and potential payoff. *Journal of Neuroscience*, *32*(7), 2335-2343.

Mumford, J. A., Bissett, P. G., Jones, H. M., Shim, S., Rios, J. A. H., & Poldrack, R. A. (2023). The response time paradox in functional magnetic resonance imaging analyses. *BioRxiv*. doi 10.1101/2023.02.15.528677

Mur, M., Ruff, D. A., Bodurka, J., Bandettini, P. A., & Kriegeskorte, N. (2010). Face-identity change activation outside the face system: "Release from adaptation" may not always indicate neuronal selectivity. *Cerebral Cortex*, *20*(9), 2027-2042.

Murphy, P. R., Robertson, I. H., Harty, S., & O'Connell, R. G. (2015). Neural evidence accumulation persists after choice to inform metacognitive judgments. *Elife*, *4*, e11946.

O'Connell, R. G., Dockree, P. M., & Kelly, S. P. (2012). A supramodal accumulation-to-bound signal that determines perceptual decisions in humans. *Nature Neuroscience*, *15*(12), 1729-1735.

O'Reilly, J. X., Schüffelgen, U., Cuell, S. F., Behrens, T. E., Mars, R. B., & Rushworth, M. F. (2013). Dissociable effects of surprise and model update in parietal and anterior cingulate cortex. *Proceedings of the National Academy of Sciences*, *110*(38), E3660-E3669.

Pajani, A., Kouider, S., Roux, P., & De Gardelle, V. (2017). Unsuppressible repetition suppression and exemplar-specific expectation suppression in the fusiform face area. *Scientific Reports*, *7*(1), 160.

Patterson, C. A., Wissig, S. C., & Kohn, A. (2013). Distinct effects of brief and prolonged adaptation on orientation tuning in primary visual cortex. *Journal of Neuroscience*, *33*(2), 532-543.

Petro, B., Gaál, Z. A., Kojouharova, P., & Czigler, I. (2023). The role of attention control in visual mismatch negativity (vMMN) studies. *Experimental Brain Research*, 1-8.

Polich, J., & Margala, C. (1997). P300 and probability: Comparisons of oddball and single-stimulus paradigms. *International Journal of Psychophysiology, 25,* 169-176.

Preuschoff, K., Quartz, S. R., & Bossaerts, P. (2008). Human insula activation reflects risk prediction errors as well as risk. *Journal of Neuroscience, 28*(11), 2745-2752.

Press, C., Kok, P., & Yon, D. (2020). The perceptual prediction paradox. *Trends in Cognitive Sciences, 24*(1), 13-24.

Press, C., Thomas, E., & Yon, D. (2022). Cancelling cancellation? Sensorimotor control, agency, and prediction. *Neuroscience & Biobehavioral Reviews*, 105012.

Quek, G. L., & Rossion, B. (2017). Category-selective human brain processes elicited in fast periodic visual stimulation streams are immune to temporal predictability. *Neuropsychologia, 104,* 182-200.

Rahnev, D., Lau, H., & De Lange, F. P. (2011). Prior expectation modulates the interaction between sensory and prefrontal regions in the human brain. *Journal of Neuroscience, 31*(29), 10741-10748.

Ramachandran, S., Meyer, T., & Olson, C. R. (2017). Prediction suppression and surprise enhancement in monkey inferotemporal cortex. *Journal of Neurophysiology, 118*(1), 374-382.

Rao, R. P., & Ballard, D. H. (1999). Predictive coding in the visual cortex: A functional interpretation of some extra-classical receptive-field effects. *Nature Neuroscience, 2*(1), 79-87.

Reynolds, J. H., & Heeger, D. J. (2009). The normalization model of attention. *Neuron, 61*(2), 168-185.

Richter, D., Ekman, M., & de Lange, F. P. (2018). Suppressed sensory response to predictable object stimuli throughout the ventral visual stream. *Journal of Neuroscience, 38*(34), 7452-7461.

Richter, D., & de Lange, F. P. (2019). Statistical learning attenuates visual activity only for attended stimuli. *Elife*, *8*, e47869.

Rieke, F., & Rudd, M. E. (2009). The challenges natural images pose for visual adaptation. *Neuron*, *64*(5), 605-616.

Rostalski, S. M., Amado, C., Kovács, G., & Feuerriegel, D. (2020). Measures of repetition suppression in the Fusiform Face Area are inflated by co-occurring effects of statistically learned visual associations. *Cortex*, *131*, 123-136.

Rungratsameetaweemana, N., Itthipuripat, S., Salazar, A., & Serences, J. T. (2018). Expectations do not alter early sensory processing during perceptual decision-making. *Journal of Neuroscience*, *38*(24), 5632-5648.

Schultz, W. (2016). Dopamine reward prediction-error signalling: A two-component response. *Nature Reviews Neuroscience*, *17*(3), 183-195.

Schwartz, G., Harris, R., Shrom, D., & Berry, M. J. (2007). Detection and prediction of periodic patterns by the retina. *Nature Neuroscience*, *10*(5), 552-554.

Schwartz, G., & Berry 2nd, M. J. (2008). Sophisticated temporal pattern recognition in retinal ganglion cells. *Journal of Neurophysiology*, *99*(4), 1787-1798.

Schweinberger, S. R., & Neumann, M. F. (2016). Repetition effects in human ERPs to faces. *Cortex*, *80*, 141-153.

Schwiedrzik, C. M., & Freiwald, W. A. (2017). High-level prediction signals in a low-level area of the macaque face-processing hierarchy. *Neuron*, *96*(1), 89-97.

Sherman, B. E., Graves, K. N., & Turk-Browne, N. B. (2020). The prevalence and importance of statistical learning in human cognition and behavior. *Current Opinion in Behavioral Sciences*, *32*, 15-20.

Solomon, S. G., & Kohn, A. (2014). Moving sensory adaptation beyond suppressive effects in single neurons. *Current Biology*, *24*(20), R1012-R1022.

Solomon, S. S., Tang, H., Sussman, E., & Kohn, A. (2021). Limited evidence for sensory prediction error responses in visual cortex of macaques and humans. *Cerebral Cortex*, *31*(6), 3136-3152.

Spratling, M. W. (2017). A review of predictive coding algorithms. *Brain and Cognition*, *112*, 92-97.

Summerfield, C., Trittschuh, E. H., Monti, J. M., Mesulam, M. M., & Egner, T. (2008). Neural repetition suppression reflects fulfilled perceptual expectations. *Nature Neuroscience, 11*(9), 1004-1006.

Summerfield, C., & Koechlin, E. (2008). A neural representation of prior information during perceptual inference. *Neuron, 59*(2), 336-347.

Summerfield, C., Wyart, V., Johnen, V. M., & De Gardelle, V. (2011). Human scalp electroencephalography reveals that repetition suppression varies with expectation. *Frontiers in Human Neuroscience, 5*, 67.

Summerfield, C., & De Lange, F. P. (2014). Expectation in perceptual decision making: Neural and computational mechanisms. *Nature Reviews Neuroscience, 15*(11), 745-756.

Tang, M. F., Smout, C. A., Arabzadeh, E., & Mattingley, J. B. (2018). Prediction error and repetition suppression have distinct effects on neural representations of visual information. *Elife, 7*, e33123.

Thomas, D.G., Grice, J.W., Najm-Briscoe, R.G., Williams Miller, J. (2004). The influence of unequal numbers of trials on comparisons of average event-related potentials. *Developmental Neuropsychology, 26*(3), 753–774.

Todorovic, A., & de Lange, F. P. (2012). Repetition suppression and expectation suppression are dissociable in time in early auditory evoked fields. *Journal of Neuroscience, 32*(39), 13389-13395.

Twomey, D. M., Murphy, P. R., Kelly, S. P., & O'Connell, R. G. (2015). The classic P300 encodes a build-to-threshold decision variable. *European Journal of Neuroscience, 42*(1), 1636-1643.

Ulanovsky, N., Las, L., & Nelken, I. (2003). Processing of low-probability sounds by cortical neurons. *Nature Neuroscience, 6*(4), 391-398.

Vinken, K., de Beeck, H. P. O., & Vogels, R. (2018). Face repetition probability does not affect repetition suppression in macaque inferotemporal cortex. *Journal of Neuroscience, 38*(34), 7492-7504.

Vogels, R. (2016). Sources of adaptation of inferior temporal cortical responses. *Cortex, 80*, 185-195.

Walsh, K. S., McGovern, D. P., Clark, A., & O'Connell, R. G. (2020). Evaluating the neurophysiological evidence for predictive processing as a model of perception. *Annals of the new York Academy of Sciences, 1464*(1), 242-268.

Wessel, J. R. (2018). An adaptive orienting theory of error processing. *Psychophysiology, 55*(3), e13041.

Whitmire, C. J., & Stanley, G. B. (2016). Rapid sensory adaptation redux: A circuit perspective. *Neuron, 92*(2), 298-315.

Xiang, J. Z., & Brown, M. W. (1998). Differential neuronal encoding of novelty, familiarity and recency in regions of the anterior temporal lobe. *Neuropharmacology, 37*(4-5), 657-676.

Yarkoni, T., Barch, D. M., Gray, J. R., Conturo, T. E., & Braver, T. S. (2009). BOLD correlates of trial-by-trial reaction time variability in gray and white matter: A multi-study fMRI analysis. *PLoS One, 4*(1), e4257.

Zhou, Y. J., Pérez-Bellido, A., Haegens, S., & de Lange, F. P. (2020). Perceptual expectations modulate low-frequency activity: A statistical learning magnetoencephalography study. *Journal of Cognitive Neuroscience, 32*(4), 691-702.