Genomic language model predicts protein co-regulation and function

Yunha Hwang[1*], Andre L. Cornman[2], Elizabeth H. Kellogg[3], Sergey Ovchinnikov[4*], Peter R. Girguis[1*]

[1] Department of Organismic and Evolutionary Biology, Harvard University, Cambridge, MA, USA
[2] Independent contributor
[3] Department of Molecular Biology and Genetics, Cornell University, Ithaca, NY, USA
[4] John Harvard Distinguished Science Fellowship Program, Harvard University, Cambridge, MA, USA

* co-correspondence: yhwang@g.harvard.edu, so@fas.harvard.edu, pgirguis@oeb.harvard.edu

Abstract

Deciphering the relationship between a gene and its genomic context is fundamental to understanding and engineering biological systems. Machine learning has shown promise in learning latent relationships underlying the sequence-structure-function paradigm from massive protein sequence datasets. However, to date, limited attempts have been made in extending this continuum to include higher order genomic context information. Evolutionary processes dictate the specificity of genomic contexts in which a gene is found across phylogenetic distances, and these emergent genomic patterns can be leveraged to uncover functional relationships between gene products. Here, we trained a genomic language model (gLM) on millions of metagenomic scaffolds to learn the latent functional and regulatory relationships between genes. gLM learns contextualized protein embeddings that capture the genomic context as well as the protein sequence itself, and encode biologically meaningful and functionally relevant information (e.g. enzymatic function, taxonomy). Our analysis of the attention patterns demonstrates that gLM is learning co-regulated functional modules (i.e. operons). Our findings illustrate that gLM's unsupervised deep learning of the metagenomic corpus is an effective and promising approach to encode functional semantics and regulatory syntax of genes in their genomic contexts and uncover complex relationships between genes in a genomic region.

	Main
28	

Introduction
Evolutionary processes result in the linkage between protein sequences, structure and function. The
resulting sequence-structure-function paradigm[1] has long provided the basis for interpreting vast amounts
of genomic data. Recent advances in neural network (NN)-based protein structure prediction methods[2,3],
and more recently protein language models (pLMs)[4–7] suggest that data-centric approaches in unsupervised
learning can represent these complex relationships shaped by evolution. To date, these models largely
consider each protein as an independent and standalone entity. However, proteins are encoded in genomes
alongside other proteins, and the specific genomic context that a protein occurs in is determined by
evolutionary processes where each gene gain, loss, duplication and transposition event is subject to
selection and drift[8–10]. These processes are particularly pronounced in bacterial and archaeal genomes where
frequent horizontal gene transfers (HGT) shape genomic organization and diversity[11,12]. Thus, there exists
an inherent evolutionary linkage between genes, their genomic context, and gene function[13–15], which can
be explored by characterizing patterns that emerge from large metagenomic datasets.
42
Recent efforts to model genomic information have shown predictive power of genomic context in gene
function[16] and metabolic trait evolution[17] in bacterial and archaeal genomes. However, these methods
represent genes as categorical entities, despite these genes existing in continuous space where
multidimensional properties such as phylogeny, structure, and function are abstracted in their sequences.
On the other end of the spectrum of representations, there have been efforts to use unsupervised learning
on nucleotide sequences to predict gene expression level[18] and detect regulatory motifs[19–21]. These models
are largely trained and benchmarked on the human genome and focus on predicting gene regulation rather
than function. Most recent efforts to leverage diverse microbial sequences to model genome-scale
information include GenSLMs[22], which is pretrained on codon-level representations of diverse bacterial
and viral gene sequences and later fine-tuned on SARS-CoV-2 genomes. In order to learn generalizable
gene-to-gene-context interactions across biology, a model needs to be pretrained on 1) diverse lineages of
organisms, 2) rich and continuous representation of genes and 3) longer segments of genomes with multiple
genes. To our knowledge, there has been no method that combines all three aspects of pretraining to learn
genomic information across diverse lineages of biology (see summary of previous studies in **Extended**
Data 1).
58
In order to close the gap between genomic-context and gene sequence-structure-function, we developed the
first genomic language model (gLM) that, to our knowledge, represents proteins using pLM embeddings
that encode relational properties[4] and structure information[23]. Our model is based on the transformer[24]
architecture and is trained using millions of unlabelled metagenomic sequences via the masked language
modeling[25] objective, with the hypothesis that its ability to attend to different parts of a multi-gene sequence
will result in the learning of gene functional semantics and regulatory syntax (e.g. operons). Here, we report
evidence of the learned contextualized protein embeddings and attention patterns capturing biologically
relevant information. We demonstrate gLM's potential for predicting gene function and co-regulation, and
propose future applications and research directions, including transfer learning capabilities of gLM.
68
Masked language modeling of genomic sequences
Language models, such as Bidirectional Encoder Representations from Transformers (BERT[25]), learn the
semantics and syntax of natural languages using unsupervised training of a large corpus. In masked
language modeling, the model is tasked with reconstructing corrupted input text[25], where some fraction of
the words are masked. Significant advances in language modeling performance was achieved by adopting
the transformer[24] neural network architecture, where each token (i.e. word) is able to attend to other tokens.
This is in contrast to Long-Short-Term-Memory networks (LSTMs)[26] that sequentially processes tokens.
To model genomic sequences, we trained a 19-layer transformer model (**Figure 1A;** for a detailed figure
see **Extended Data 2**) on seven million metagenomic contig fragments consisting of 15 to 30 genes from
the MGnify[27] database. Each gene in a genomic sequence is represented by a 1280 feature vector (context-

free protein embeddings) generated by using ESM2 pLM[23], concatenated with an orientation feature
(forward or backward). For each sequence, 15% of genes are randomly masked, and the model learns to
predict the masked label using the genomic context. Based on the insight that more than one gene can
legitimately be found in a particular genomic context, we allow the model to make four different predictions
and also predict their associated probabilities (**Extended Data 2**). Thus, instead of predicting their mean
value, the model can approximate the underlying distribution of multiple genes that can occupy a genomic
niche. We assess the model's performance using a pseudo-accuracy metric, where a prediction is considered
correct if it is closest to the masked protein in euclidean distance compared to the other proteins encoded
in the sequence (see **Methods**). We validate our model's performance on the *Escherichia coli* K-12
genome[28] by excluding from training 5.1% of MGnify subcontigs in which more than half of the proteins
are similar (>70% sequence identity) to *E. coli* K-12 proteins. It is important to note that our goal was not
to remove all *E. coli* K-12 homologs from the training, which would have removed a vast majority of
training data as many essential genes are shared across organisms. Instead, our goal was to remove as many
E.coli K-12-like genomic contexts (subcontigs) from training, which is more appropriate for the training
objective. gLM achieves 71.9% in validation pseudo-accuracy and 59.2% in validation absolute accuracy
(**Extended Data 3**). Notably, 53.0% of the predictions made during validation are with high confidence
(with prediction likelihood > 0.75), and 75.8% of the high confidence predictions are correct, indicating
gLM's ability to learn a confidence metric that corresponds to increased accuracy. We baseline our
performance with a bidirectional LSTM model trained using the same language modeling task on the same
training dataset, where validation performance plateaus at 28% pseudo-accuracy and 15% absolute
accuracy (**Extended Data 3 and 4,** note that biLSTM is smaller because it failed to converge when scaling
the number of layers). We ablate the use of pLM representations as input to gLM by replacing them with
one-hot amino acid representations (**Extended Data 5**) and report performance equivalent to random
predictions (3% pseudo-accuracy and 0.02% absolute accuracy).

103
104
Figure 1. gLM training and inference schematics. A) For training, contigs (contiguous genomic
sequences) containing up to 30 genes are first translated into proteins, which are subsequently embedded
using a pLM encoder (ESM2). Masked inputs are generated by random masking at 15% probability and
gLM (a transformer encoder) is trained to make four predictions for each masked protein, with associated
likelihoods. Training loss is calculated on both the prediction and likelihoods. **B)** At inference time, inputs
are generated from a contig using ESM2 output. Contextualized protein embeddings (hidden layers of gLM)
and attention patterns are used for various downstream tasks. See **Extended Data 2** for detailed schematics.
112
113

Contextualized gene embeddings capture gene semantics

The mapping from gene to gene-function in organisms is not one-to-one. Similar to words in natural language, a gene can confer different functions[29] depending on its context[30], and many genes confer similar functions (i.e. convergent evolution[31], remote homology[32]). We used gLM to generate 1280-feature contextualized protein embeddings at inference time (**Figure 1B**), and we examined the "semantic" information captured in these embeddings. Analogous to how words are likely to have different meanings depending on the type of text in which they are found (**Figure 2A**), we find that contextualized protein embeddings of genes that appear across multiple environments (biomes) tend to cluster based on biome types. We identified 31 proteins in our training database (MGYPs) that occurred more than 100 times and distributed with at least 20 occurrences in each "Host-associated", "Environmental", and "Engineered" biomes according to MGnify's designation. We find that gLM's contextualized protein embeddings capture biome information for the majority (n=21) of these multi-biome MGYPs. For instance, a gene encoding a protein annotated "translation initiation factor IF-1" occurs multiple times across biomes. While the input to gLM (context-free protein embedding; ESM2 representation) is identical across all occurrences, gLM's output (contextualized protein embeddings) cluster with biome types (**Figure 2B**; silhouette score = 0.17, see the other 30 multi-biome MGYP visualizations in **Extended Data 6**). This suggests that the diverse genomic contexts that a gene occupies are specific for different biomes, implying biome-specific gene semantics.

We explored an ecologically important example of genomic "polysemy" (multiple meanings conferred by the same word; **Figure 2C**) of methyl-coenzyme M reductase (MCR) complex. The MCR complex is able to carry out a reversible reaction (Reaction 1 in **Figure 2D**), whereby the forward reaction results in the production of methane (methanogenesis) while the reverse results in methane oxidation (methanotrophy). We first examine the McrA (methyl-coenzyme M reductase subunit alpha) protein in diverse lineages of ANME (ANaerobic MEthane oxidizing) and methanogenic archaeal genomes. These archaea are polyphyletic and occupy specific ecological niches. Notably, similar to how a semantic meaning of a word exists on a spectrum and a word can have multiple semantically appropriate meanings in a context (**Figure 2C**), the MCR complex can confer different functions depending on the context. Previous reports demonstrate capacities of ANME (ANME-2 in particular) carrying out methanogenesis[33] and methanogens conducting methane oxidation in specific growth conditions[34]. The context-free ESM2 embedding of these proteins (**Figure 2E**) shows little organization, with little separation between ANME-1 and ANME-2 McrA proteins. However, contextualized gLM embeddings (**Figure 2F**) of the McrA proteins show distinct organization where ANME-1 McrA proteins form a tight cluster, while ANME-2 McrA proteins form a cluster with methanogens (silhouette score after contextualization: 0.24; before contextualization: 0.027). This organization reflects the phylogenetic relationships between the organisms that McrAs are found in, as well as the distinct operonic and structural divergence of MCR complexes in ANME-1 compared to those found in ANME-2 and methanogens[35]. As proposed by Shao et al.[35], the preferred directionality in Reaction 1 (**Figure 2D**) in ANME-2 and some methanogens may be more dependent on thermodynamics.

We also demonstrate that contextualized gLM embeddings are more suitable for determining the functional relationship between gene classes. Analogous to how the words "dog" and "cat" are closer in meaning relative to "dog" and "train" (**Figure 2G**), we see a pattern where Cas1 and Cas2 that appear diffuse in multiple subclusters in context-free protein embedding space (**Figure 2H**) cluster in contextualized embedding space (**Figure 2I**). This reflects their similarity in function (e.g. phage defense). This is also demonstrated in biosynthetic genes, lipopolysaccharide synthase (LPS) and polyketide synthase (PKS) genes clustering closer together in contextualized embedding space distinct from the Cas proteins (**Figure 2I**). We quantitate this pattern with a higher silhouette score measuring phage defense and biosynthetic gene separation (gLM representation: 0.105 ± 0.012, pLM representation: 0.078 ± 0.011; paired t-test, t-statistic: 4.6, p-value = 0.001, n=10). Contextualized protein embeddings are therefore able to capture relational properties akin to semantic information[36], where genes encoding proteins that are more similar in their function are found in similar genomic contexts.

165
In order to quantify the information gain as a result of training a transformer on genomic contexts, we
compare clustering results in 2B, F, and I with clustering conducted on (sub)contig-averaged pLM
embeddings (**Extended Data 7**). By mean-pooling pLM embeddings across a given subcontig, we can
summarize the context information as a naive baseline. We report a most consistent clustering (higher
silhouette scores) of gLM embeddings compared to contig-averaged pLM for all three analyses (see
Extended Data 7 figure captions for values). We demonstrate that the gLM transformer model learns
representations that correlate with biological function, which are not captured by the naive baseline.

Figure 2. Contextualized protein embedding analysis and comparison with concepts in natural language modeling. A) A word upon contextualization can be mapped to embedding space. For many words, the semantic meaning varies in different types of literature, and therefore their contextualized embeddings cluster with source text type. Figure was created for qualitative visualization. B) The input

protein embedding (output of ESM2 and context-free protein embedding) is the same across all occurrences
of the protein in the database. Upon contextualization with gLM, contextualized protein embeddings of the
same protein (last hidden layer of gLM at inference time) cluster with biome type, analogous to the source
text type in natural language (A). Contextualization of 30 other multi-biome MGYPs can be found in
Extended Data 6. **C)** A word's meaning upon contextualization varies across a continuous spectrum and
can be ambiguous even with contextualization (e.g. double entendre). **D)** Reaction 1, carried out by the
MCR complex, either backward (Methanotrophy) or forward (Methanogenesis). **E)** Principal Component
Analysis (PCA) of context-free protein embeddings of McrA sequences in genomes (total explained
variances = 0.56), colored by metabolic classification of the organism (ANME, methanogen) based on
previous studies and labeled by class-level taxonomy. **F)** PCA of contextualized McrA embeddings (total
explained variance = 0.68), where gLM embeddings cluster with the direction of Reaction 1 that the MCR
complex is likely to carry out. **G)** Geometric relationship between contextualized protein embeddings based
on the semantic closeness of words. **H)** Input (context-free) protein embeddings of Cas1, Cas2,
lipopolysaccharide synthases (LPS) and polyketide synthases (PKS) showing clustering based on structural
and sequence similarity. **I)** Clustering of contextualized protein embeddings where phage defense proteins
cluster (Cas1 and Cas2) and biosynthetic gene products cluster (LPS and PKS).
194

Characterizing the unknown

Metagenomic sequences feature many genes with unknown or generic functions, and some are so divergent that they do not contain sufficient sequence similarity to the annotated fraction of the database[37]. In our dataset, of the 30.8M protein sequences, 19.8% could not be associated with any known annotation (see **Methods**), and 27.5% could not be associated with any known Pfam domains using a recent deep learning approach (ProtENN[38]). Understanding the functional role of these proteins in their organismal and environmental contexts remains a major challenge because most of the organisms that house such proteins are difficult to culture and laboratory validation is often low-throughput. In microbial genomes, proteins conferring similar functions are found in similar genomic contexts due to selective pressures bestowed by functional relationships (e.g. protein-protein interactions, co-regulations) between genes. Based on this observation, we posited that contextualization would provide richer information that pushes the distribution of unannotated genes closer to the distribution of annotated genes. We compared the distributions of unannotated and annotated fractions of proteins in our dataset using context-free pLM embeddings and contextualized gLM embeddings. We found a statistically significant lower divergence between distributions of unannotated and annotated genes in gLM embeddings compared to pLM embeddings (paired t-test of Kullback-Leibler divergences, t-test statistic = 7.61, p-value < 1e-4, n = 10; see **Methods** for sampling and metric calculation). This suggests a greater potential for using gLM embeddings to transfer validated knowledge in cultivable and well-studied strains (e.g. *E. coli* K-12) to the vastly uncultivated metagenomic sequence space. Genomic context, along with molecular structure and phylogeny, appear to be important information to abstract in order to effectively represent sequences such that we can uncover hidden associations between the known and the unknown fractions of biology.

Contextualization improves enzyme function prediction

To test the hypothesis that the genomic context of proteins can be used to aid function prediction, we evaluated how contextualization can improve the expressiveness of protein representations for enzyme function prediction. First, we generated a custom MGYP-EC dataset where the train and test data were split at 30% sequence identity for each EC class (see **Methods**). Second, we apply a linear probe (LP) to compare the expressiveness of representations at each gLM layer, with and without masking the queried protein (**Extended Data 8**). By masking the queried protein, we can assess gLM's ability to learn functional information of a given protein, only from its genomic context, without the propagation of information from the protein's pLM embeddings. We observed that a large fraction of contextual information pertaining to enzymatic function is learned in the first six layers of gLM. We also demonstrate that context information alone can be predictive of protein function, reaching up to 24.4 ± 0.8% accuracy. In contrast, without masking, gLM can incorporate information present in the context with the original pLM information for each queried protein. We observed an increase in expressivity of gLM embeddings also in the shallower layers, with accuracy reaching up to 51.6 ± 0.5% in the first hidden layer. This marks a 4.6 ± 0.5% increase from context-free pLM prediction accuracy (**Figure 3A)** and 5.5 ± 1.0% increase in mean average precision (**Figure 3C**) Thus, we demonstrate that information that gLM learns from the context is orthogonal to information captured in pLM embedding. We also observed diminishing expressivity in enzyme function information with deeper layers of gLM; this is consistent with previous examinations of LLMs, where deeper layers are specialized to the pretraining task (masked token prediction), and is consistent with previous examinations of LLMs, where the best-performing layer depends on the specific downstream tasks[39]. Finally, to further examine the expressiveness of these representations, we compared per-class F1 score gains (**Figure 3B**). We observe statistically significant differences in F1 scores (t-test, Benjamini/Hochberg corrected p-value < 0.05) between the two models in 36 out of 73 EC classes with more than ten samples in the test set. Majority (27 out of 36) of the statistical differences resulted in improved F1 score in LP trained on gLM representations.

Horizontal transfer frequency corresponds to genomic context embedding variance

A key process that shapes microbial genome organization and evolution is horizontal gene transfer (HGT). The taxonomic range in which genes are distributed across the tree of life depends on their function and the

selective advantage they incur in different environments. Relatively little is known about the specificity in
the genomic region into which a gene gets transferred across phylogenetic distances. We examined the
variance of gLM embeddings for proteins that occur at least one hundred times in the database. Variance
of gLM-learned genomic contexts are calculated by taking a random sample of 100 occurrences and then
calculating the mean pairwise distances between the hundred gLM embeddings. We conduct such
independent random sampling and distance calculation ten times per gene and then calculate the mean
value. As a baseline, we calculate variance of subcontig-averaged pLM embeddings using the same
sampling method, to compare the information learned from training gLM. Our results show that gLM-
learned genomic context variances have a longer right-hand tail (kurtosis = 1.02, skew = 1.08) compared
to the contig-averaged pLM baseline that is more peaked (kurtosis = 2.2, skew = 1.05) **(Figure 3D)**.
Notably, the most context-variant genes in the right tail of gLM-learned context variance distribution
(orange) included phage genes and transposases, reflecting their ability to self-mobilize. Interestingly, we
did not find any phage genes in the right-most tail of contig-averaged pLM embedding variance distribution
(blue), although we did find genes involved in transposition (**Extended Data 9**). gLM-learned genomic
context variances can be used as a proxy for horizontal transfer frequencies and can be used to compare the
fitness effects of the genomic context on the evolutionary trajectory (e.g. gene flow) of genes, as well as to
identify novel and functional transposable elements.

Figure 3. Contextualization of gene function. A) Linear probe EC classification accuracy for pLM
(ESM2) representations and gLM (1st hidden layer) representations. **B)** F1-score comparisons of
statistically significant (Benjamini/Hochberg corrected p-value < 0.05) differences in performance of pLM-
and gLM-based EC number linear probes. EC classes are ordered with the largest gain with
contextualization on the left to the largest loss with contextualization on the right. **C)** Precision-Recall
curves of pLM- and gLM-based EC number linear probes. **D)** Histogram of variance (# bins = 100)
calculated using contextualized embeddings (gLM; orange) and contig-averaged pLM (blue) embeddings
of MGYPs that occur at least 100 times in the database. Histograms for unannotated and annotated fraction
of the MGYPs are plotted separately and bars are not stacked. Annotated examples in the long right tail
include phage proteins and transposases, reflecting their ability to self-mobilize (see annotations of top tens
most variant genes in **Extended Data 9**).

Transformer's attention captures operons

The transformer attention mechanism[24] models pairwise interaction between different tokens in the input sequence. Previous examinations of the attention patterns of transformer models in natural language processing (NLP)[39] have suggested that different heads appear to specialize in syntactic functions. Subsequently, different attention heads in pLMs[40] have been shown to correlate to specific structural elements and functional sites in a protein. For our gLM, we hypothesized that specific attention heads focus on learning operons, a "syntactic" feature pronounced in microbial genomes where multiple genes of related function are expressed as single polycistronic transcripts. Operons are prevalent in bacterial, archaeal and their viral genomes, while rare in eukaryotic genomes. We used the *E.coli* K-12 operon database[41] consisting of 817 operons for validation. gLM contains 190 attention heads across 19 layers. We found that heads in shallower layers correlated more with operons (**Figure 4A, Extended Data 10**), with raw attention scores in the 7th head of the 2th layer [L2-H7] linearly correlating with operons with 0.44 correlation coefficient (Pearson's rho, Bonferroni adjusted p-value < 1E-5) (**Figure 4B**). We further trained a logistic regression classifier (operon predictor) using all attention patterns across all heads. Our classifier predicts the presence of an operonic relationship between a pair of neighboring proteins in a sequence with high precision (mean average precision = 0.775±0.28, five-fold cross-validation) (**Figure 4C**). We baseline this performance by training an operon predictor on the one-hot amino acid representation-based gLM ablation (mean average precision = 0.426 ± 0.015, five-fold cross-validation; **Extended Data 5**), that learns from the orientation and co-occurrence information but cannot fully leverage rich representation of genes.

Context dependency of AAA+ regulator functions in complex genetic systems

Understanding the functional role of a regulatory protein in an organism remains a challenging task because the same protein fold may carry out different functions depending on the context. For instance, AAA+ proteins (ATPases associated with diverse cellular activities) utilize the chemical energy from ATP hydrolysis to confer diverse mechanical cellular functions[42]. However, AAA+ regulators can also play very different, broad functional roles depending on their cellular interacting partners from protein degradation and DNA replication to DNA transposition. One particularly interesting example is the TnsC protein, which regulates DNA insertion activity[43] in Tn7-like transposon systems. Multiple bioinformatic efforts focused on discovery of novel transposons through metagenome search[44] and sequence searches of assembled genomes[45] aimed at identifying suitable homologs for genome-editing applications[46]. In order to test whether the methods developed here could identify novel Tn7-like transposition systems as well as distinguish these from other functional contexts, we explored the contextualized semantics of TnsC's structural homologs in the MGnify database. Without contextualization, there appears no clustering with associated transposase activity (KL divergence ratio = 1.03; see **Methods** for calculation of this metric, **Figure 4E**). However, with added contextualization, previously identified TnsC (orange) and manually inspected TnsC-like structural homolog (red, labeled "TnsC-like") cluster together (KL divergence ratio = 0.38; **Figure 4F**; see **Extended Data 11BC** for comparison with gLM-only and contig-averaged pLM baselines). We further validate this visualization using embedding distance-based clustering (**Extended Data 12**). Many structural homologs of TnsC were not involved in transposition and this is reflected in distinct clusters of gray data points away from known TnsC (oranges) and TnsC-like structural homologs (red) in **Figure 4F**. These clusters represent diverse and context-dependent AAA+ regulation activity that cannot be predicted from neither structure nor raw sequence alone. We predicted an operonic relationship between these AAA+ regulators and their neighboring genes and found many to be in operonic relationships with gene modules of diverse function including pilus assembly and viral host-nuclease inhibition (**Figure 4D, Extended Data 11A**). In some cases, queried AAA+ proteins did not appear to be in an operonic association with the neighboring proteins, suggesting some AAA+ proteins are less likely to be functionally associated with their neighbors than others (**Extended Data 11A, example 6**). Using this example of AAA+ regulators, we illustrate that combining the contextualized protein embeddings and attention-based operon interaction may provide an important avenue for exploring and characterizing the functional diversity of regulatory proteins.

Figure 4. Attention analysis. A) Correlation coefficients (Pearson's rho) between attention heads across layers and operons. Darker color corresponds to stronger correlation with previously identified operons. Attention patterns of the second layer-seventh head [L2-H7] is most strongly correlated with the operons. B) Three random examples of contigs and predicted operonic relationship between neighboring proteins. Proteins are listed in the order they are encoded in the contig. Ground truth E.coli K-12 operons (top row), raw attention scores in the attention head [L2-H7] most correlated with operons (middle row) and logistic regression prediction using all attention heads (last row) where false positive predictions (or possibly misannotated ground truths in the case of flagellar proteins in the first example) are marked in red. C) Five-fold cross-validation precision-recall curves of logistic regression trained using all operons and attention heads. D) AAA+ regulator associations characterized using attention-based prediction of operons (Extended Figure 11A) corresponding to labeled examples in panels E and F. E) ESM2 generated input protein embeddings of AAA+ regulator proteins that are structural homologs to TnsC (grey and red; using Foldseek[47]). Structural homologs of TnsC with confirmed involvement in Tn7-like transposons upon manual inspection were designated "TnsC-like AAA+ (manually inspected)" and are colored red. Other MGYP proteins annotated as "TnsC" against the UniRef90 database (orange) were added as positive controls for TnsC function. NuoA (NADH-quinone oxidoreductase subunit A; purple) were added as structural and functional negative controls. DnaB helicases (blues) were added as functional negative controls, as these proteins have similar folds to TnsC but are not associated with transposition. F) Combined input protein and context embeddings of genes in panel E. These embeddings are generated through

348　concatenation of pLM (ESM2) embeddings and context (last layer of gLM) embeddings. Negative controls
349　(NuoA and DnaB helicases) form distinct clusters in both E and F. Numbered labels in grey boxes indicate
350　the AAA+ proteins with various functional association predictions listed in panel D and **Extended Data**
351　**11A.** Raw distance based clustering of the embeddings are shown in **Extended Data 12**.
352
353

gLM predicts paralogy in protein-protein interactions

Proteins in an organism are found in complexes and interact physically with each other. Recent advances in protein-protein interaction (PPI) prediction and structural complex research has largely been guided by identifying interologs (conserved PPI across organisms) and co-evolutionary signals between residues[48]. However, distinguishing paralogs from orthologs (otherwise known as the "Paralog matching" problem) in the expanding sequence dataset remains a computational challenge requiring queries across the entire database and/or phylogenetic profiling. In cases where multiple interacting pairs are found within an organism (e.g. histidine kinases (HK) and response regulators (RR)), prediction of interacting pairs is particularly difficult[49]. We reasoned that gLM, although not directly trained for this task, may have learned the relationships between paralogs versus orthologs. In order to test this capability, we used a well studied example of interacting paralogs (ModC and ModA, **Figure 5A**) which form an ABC transporter complex. We queried gLM to predict the embedding of an interacting pair given no context except the protein sequence of either ModA or ModC. We find that without any fine-tuning gLM performs at least an order of magnitude better than what is expected by random chance (see **Methods**). Specifically, for 398 out of 2700 interacting pairs, gLM makes predictions that belong to the same cluster (50% sequence identity, n=2100 clusters) as the true label, and in 73 pairs, the gLM predicts a label that is closest to the exact interacting pair (simulated random chance expected match=1.6 ± 1.01, n=10) (**Figure 5B**). Importantly, when considering only very high confidence predictions (prediction likelihood > 0.9, n=466), gLM is able to match paralogs with an increased accuracy of 25.1%. When paralogs are correctly paired, gLM is more confident about the prediction (average confidence for correct prediction = 0.79, average confidence across all predictions = 0.53), while less certain predictions are either out of distribution, or closer to the mean of labels (**Figure 5C**). We attribute part of the inaccuracies in prediction due to the fact that gLM was not trained on the task of predicting a masked gene given only a single gene as genomic context, though we expect the performance to improve with expanding the training sequence length range and fine-tuning the model specifically for the "paralog matching" problem.

Contextualized contig embeddings and potential for transfer learning

Contextualized protein embeddings encode the relationship between a specific protein and its genomic context, retaining the sequential information within a contig. We hypothesized that this contextualization adds biologically meaningful information that can be utilized for further characterization of the multi-gene genomic contigs. Here, we define a contextualized contig embedding as a mean-pooled hidden layer across all proteins in the subcontig, and a context-free contig embedding as mean-pooled ESM2 protein embeddings across the sequence (see methods). Both embeddings consist of 1280 features. We test our hypothesis by examining each of these embeddings' ability to linearly distinguish viral sequences from bacterial and archaeal subcontigs. In metagenomic datasets, the taxonomic identity of assembled sequences must be inferred post-hoc, therefore the identification of viral sequences is conducted based on the presence of viral genes and viral genomic signatures[50]. However, such classification task remains a challenge particularly for smaller contig fragments and less characterized viral sequences. Here, we sampled random 30-protein subcontigs from the representative bacterial and archaeal genome database and reference viral genomes in the NCBI and visualized their context-free contig embeddings (**Figure 5D**) and contextualized contig embeddings (**Figure 5E**). We observed more separation and taxonomic clusters at both domain- and class-levels (**Extended Data 10**), suggesting that taxonomic signature is enhanced by encoding the latent relationships between proteins. This is further validated by training a logistic regression classifier on context-free and contextualized contig embeddings for class-level taxonomy (**Extended Data 13AB**), where we see a statistically significant improvement in average precision (**Figures 5F,** see **Extended Data 13CD** for confusion matrices). This emphasizes the biological importance of a protein's relative position in the genome and its relationship with the genomic context, and further indicates that this information can be effectively encoded using gLM. Contextualized contig embeddings present opportunities for transfer learning beyond viral sequence prediction, such as improved metagenomically-assembled genome (MAG) binning and assembly correction.

Figure 5. Potential for transfer learning. A) ModA and ModC interaction (adapted with permission from Ovchinnikov et al.[48]) B) UMAP projection of predictions (orange) and labels (blues) of paralogs (ModAC shown in A), where correct predictions are colored in green. C) Predicted embeddings are colored based on the predicted confidence. Out of distribution predictions and predictions closer to the mean are generally of lower confidence, while correct predictions are of higher confidence. D&E) Random 30-gene contigs from representative bacterial ("bac") and archaeal ("arch") genomes and reference viral ("vir") genomes were embedded by mean-pooling ESM2 protein embeddings (context-free contig embeddings, D) and by mean-pooling the last hidden layer of gLM (contextualized contig embeddings, E). F) Micro-averaged precision-recall curves and average precisions for logistic regression classifiers trained using context-free contig embeddings (grey lines) and contextualized contig embeddings (colored lines) for class-level taxonomy classification task. Each line represents a fold in stratified k-fold cross-validation (k=5). Class-level taxonomy for each contig is shown in **Extended Data 13AB** and the confusion matrices for logistic regression classifiers are shown in **Extended Data 13CD.**

Discussion

The unprecedented amount and diversity of metagenomic data, coupled with advances in deep learning presents exciting opportunities for building models that can learn hidden patterns and structures of biological systems. Such models build upon the conceptual and statistical frameworks that evolutionary biologists have developed for the past century. With capabilities of abstracting much larger amounts of data, these models can disentangle the extraordinary complexity of organismal genomes and their encoded functions; this is a key step in furthering our understanding of biological processes. The work presented here demonstrates and validates the concept of genomic language modeling. Our implementation of the masked genomic language modeling illustrates the feasibility of training such a model, and provides evidence that biological information is being captured in learned contextualized embeddings and yielding meaningful interpretations of the attention patterns. We show that gLM can be used for diverse downstream tasks including enzyme function prediction, operon prediction, paralog matching and contig taxonomy prediction. Furthermore, we demonstrate gLM's ability to illuminate context dependency in functions across structural and sequence homology through the example of AAA+ regulators. Taken together, gLM presents a highly promising direction for interpreting biology and we propose key areas for further development: First, the transformer architecture has shown to be successful in efficient scaling; in both natural language[51] and protein language processing[23], increasing the number of parameters in the model along with the training dataset size have been shown to lead to vastly improved performance and generalizability. Our model consists of ~1B parameters which is at least a magnitude smaller compared to state-of-the-art pLMs. With further hyperparameter tuning and scaling, we expect better performance of the model. Second, our model currently uses pLM embeddings to represent proteins in the input. These embeddings are generated by mean-pooling the amino acid residue-level hidden states across the protein sequence, and therefore the residue specific information and synonymous mutation effects are likely obscured. Future iterations of the model could use raw residue-level or codon-level embeddings as input to allow modeling of residue-to-residue co-evolutionary interactions between proteins and synonymous mutation effects on gene function. Third, the task of reconstructing masked protein embeddings requires modeling a distribution over possible embeddings; our method approximates this distribution using a fixed number of predictions. Future work could improve upon this by using a generative approach, such as a diffusion or GAN model. This may allow for better prediction accuracy and greater generalizability for unseen datasets. Fourth, adding non-protein modalities (e.g. non-coding regulatory elements) as input to gLM may also greatly improve gLM's representation of biological sequence data, and can learn protein function and regulation conditioned upon other modalities[52]. Finally, our model was trained largely on bacterial, archaeal and viral genomes, therefore, how this method can be adapted for eukaryotic genomes, especially those with extensive intergenic regions, remains to be further explored.

One of the most powerful aspects of the transformer-based language models is their potential for transfer learning and fine-tuning. We tested some of the capabilities of gLM and successfully showed that higher order biological information including gene function and regulation can be learned using genomic sequences. Our results highlight the importance of contextualization of biological data, particularly as we scale our modeling efforts from biomolecules to whole organisms. We propose the following promising future directions for applying gLM for advancing biological research. 1) Feature-based transfer learning for predicting protein function (e.g. Gene Ontology [GO] term), particularly those with limited sequence and structural homology. 2) Fine-tuning gLM for the protein-protein-interactome prediction task. 3) Using gLM features to encode genomic contexts as additional input for improved and contextualized protein structure predictions. In conclusion, genomic language modeling is a powerful tool to unbiasedly condense important biological information from full metagenomic sequences. Coupled with the advances in long-read sequencing, we expect a drastic increase in the input data quality, quantity and diversity. Genomic language modeling presents an avenue to bridge the gap between atomic structure and organismal function, and thereby brings us closer to modeling biological systems, discovering novel biology, and ultimately, manipulating biology with precision (e.g. genome editing, synthetic biology).

Methods

Sequence database

470
471
The genomic corpus was generated using the MGnify[27] dataset (released 2022-05-06 and downloaded 2022-
06-07). First, genomic contigs with greater than 30 genes were divided into 30 gene non-overlapping
subcontigs resulting in a total of 7,324,684 subcontigs with lengths between 15 and 30 genes (subcontigs <
15 genes in length were removed from the dataset). We chose 30 as maximum context length because 67%
of the raw MGnify contigs with > 15 genes were of =< 30 genes in length (**Extended Data 14**), and
therefore increasing the context length beyond 30 would have resulted in many examples with padding
(reduced computational efficiency). Each gene in the subcontig was mapped to a representative protein
sequence (representative MGYP) using mmseqs/linclust[53], with coverage and sequence identity thresholds
set at 90% (pre-computed in the MGnify database), resulting in a total of 30,800,563 representative
MGYPs. Each representative MGYP was represented by a 1280-feature protein embedding, generated by
mean-pooling the last hidden layer of the ESM2[54] "esm2_t33_650M_UR50D" model. Due to the memory
limitation in computing embeddings for very long sequences, 116 of the MGYP sequences longer than
12290 amino acids were truncated to 12290 amino acids. ESM2 embeddings were normalized (by
subtracting the mean of each feature and dividing by its standard deviation) and clipped such that all features
range from -10 to 10, to improve training stability. A small fraction (0.4%) of the genes could not be
mapped to a representative MGYP and therefore the corresponding sequence information could not be
retrieved from the MGnify server; these sequences were assigned a 1280 feature vector of ones. For each
gene in the sub-sequence, we added a gene orientation feature to the standardized MGYP protein
embedding, where 0.5 denotes "forward" orientation relative to the direction of sequencing, and -0.5
denotes "reverse" orientation. Thus, each gene was represented by a 1281 feature vector in our corpus.

492
gLM architecture and training
gLM was built on the huggingface implementation of the RoBERTa[55] transformer architecture. gLM
consisted of 19 layers with hidden size 1280 and ten attention heads per layer, with relative position
embedding ("relative_key_query")[56]. For training, 15% of the tokens (genes) in the sequence (subcontig)
were randomly masked to a value of -1. We then tasked the model with the objective of predicting the label
of the masked token, where the label consists of a 100-feature vector that consists of the PCA whitened 99
principal components (explained variance = 89.7%. **Extended Data 15**) of the corresponding ESM2
protein embedding concatenated with its orientation feature. Reduced dimensionality of labels using PCA
increased the stability of training. Specifically, gLM projects the last hidden state of the model into four
100-feature vectors and four corresponding likelihood values using a linear layer. Total loss is calculated
using the following equation:
$MSE(closest\ prediction, label) + \alpha * CrossEntropyLoss(likelihoods, closest\ prediction\ index)$

505
506 The closest prediction is defined as the prediction that is closest to the label, computed by L2 distance. We
507 set α = 1e-4. gLM was trained in half precision with batch size 3000 with distributed data parallelization
508 on four NVIDIA A100 GPUs over 1,296,960 steps (560 epochs) including 5000 warm-up steps to reach a
509 learning rate of 1e-4 with AdamW[57] optimizer.

510
Performance metric and validation
In order to evaluate the model quality and its generalizability beyond the training dataset, we use a pseudo-
accuracy metric, where we deem a prediction to be "correct" if it is closest in Euclidean distance to the
label of the masked gene relative to the other genes in the subcontig. Thus, $pseudo\ accuracy =$
$\frac{\#count(argmin(dist(prediction, labels\ in\ subcontig)) == index(masked\ gene))}{\#masked\ genes}$. We chose to validate our metric
and subsequent analyses on the best annotated genome to date: *E.coli* K12[58]. In order to remove as many
E.coli K12 like subcontigs from the training dataset, we removed 5.2% of the subcontigs in which more
than half of the genes were > 70% similar (calculated using mmseqs2 search[53]) in amino acid sequence to
E.coli K12 genes. We validate our pseudo accuracy metric by calculating the absolute accuracy on the

E.coli K12 genome for which each gene was masked sequentially: $absolute\ accuracy =$

$$\frac{\#count(argmin(dist(prediction, all\ genes\ in\ E.coli\ K12)) == index(masked\ gene))}{\#genes\ in\ E.coli\ K12}$$

Contextualized embedding calculation and visualization
Contextualized protein embedding of a gene is calculated by first inputting a 15-30 gene subcontig
containing the gene of interest, and then running inference on the subcontig using the trained gLM without
masking. We then use the last hidden layer of the model corresponding to the gene as the embedding
consisting of 1280 features.

Gene annotation
Genes were annotated using Diamond v2.0.7.145[59] against the UniRef90 database[60] with an e-value cut-off
1E-5. Genes were labeled as "unannotated" if either 1) no match was found in the UniRef90 database, or
2) the match was annotated with following keywords: "unannotated", "uncharacterized", "hypothetical",
"DUF"(domain of unknown function).

McrA protein analysis
McrA protein encoding Methanogens and ANME genomes were selected from the accession ID list found
in the supplement of Shao et al[35]. subcontigs containing *mcrA* were extracted with at most 15 genes before
and after *mcrA*. The context-free and contextualized embeddings of McrA were calculated using the ESM2
and gLM respectively.

Distributions of unannotated and annotated embeddings
Distributions of unannotated and annotated embeddings in the database were compared using Kullback-
Leibler (KL) divergence analysis. First, ten random samples of 10,000 subcontigs from the MGnify corpus.
pLM and gLM embeddings of the genes were calculated using mean-pooled last hidden layer of ESM2
embeddings and mean-pooled last hidden layer of gLM respectively. Outliers were removed using
Mahalanobis distance and a chi-squared threshold of 0.975. pLM and gLM embedding dimensions were
reduced to 256 principal components (91.9 ± 1.72% and 80.1 ± 6.89% total variances explained
respectively). KL divergence was calculated using the following equation:

$$D_{KL}(P||Q) = \frac{1}{2}(tr(\Sigma_1^{-1}\Sigma_0) - k + (\mu_1 - \mu_0)^T\Sigma_1^{-1}(\mu_1 - \mu_0) + ln(\frac{det\ \Sigma_1}{det\ 0}))$$

where P corresponds to the distribution of unannotated genes and Q corresponds to the distribution of
unannotated genes, with μ_0, μ_1 respectively as means and Σ_0, Σ_1 respectively as covariance matrices. The
significance of the KL divergence differences between pLM and gLM embeddings is calculated using a
paired t-test across the ten samples.

Enzyme Commission number prediction
Custom MGYP-Enzyme Commission (MGYP-EC) dataset was created by first searching (mmseqs2[53] with
default setting) MGYPs against the "split30.csv" dataset previously used to train CLEAN[61]. "split30.csv"
dataset consists of EC numbers assigned to UniProt sequences clustered at 30% identity. Only MGYP hits
with >70% sequences to "split30.csv" were considered and MGYPs with multiple hits with >70% similarity
were removed. Test split was selected by randomly selecting 10% of "split30.csv" UniProt IDs in each EC
category that map to MGYPs. EC categories with less than four distinct UniProt IDs with MGYP mapping
were removed from the dataset, resulting in 253 EC categories. The train set consisted of MGnify subcontigs
in the corpus that contained at least one the 27936 MGYPs mapping to 1878 UniProt IDs. The test set
consisted of randomly selected MGnify subcontig containing each of 4441 MGYPs mapping to 344 UniProt
IDs. pLM (context-free) embeddings were calculated for each of MGYP with EC number assignment by
mean-pooling the last hidden layer of its ESM2 embedding. Masked (context-only) gLM embeddings were
calculated for each of the 19 layers by running inference on subcontigs with masks at the positions of
MGYPs with EC number assignment and subsequently extracting per-layer hidden representations for

masked positions. gLM (contextualized) embeddings were calculated also for each layer by running
inference without masking and subsequently extracting per-layer hidden representations for MGYPs with
EC number assignments. Linear probing was conducted for these embeddings with a single linear layer.
Linear probes were trained with early stopping (patience = 10, github.com/Bjarten/early-stopping-
pytorch/blob/master/pytorchtools.py) and batch size = 5000, and training results were replicated five times
with random seeds to calculate error ranges.
575
Variance of contextualized protein embedding analysis
Contextualized protein embeddings are generated at inference time. Variances of contextualized protein
embeddings were calculated for MGYPs that occur at least 100 times in the dataset, excluding the
occurrences at the edges of the subcontig (first or last token). For each such MGYP, we take 10 random
independent samples consisting of 100 occurrences and calculate the mean pairwise euclidean distances
between the contextualized embeddings. To assess the role gLM plays in contextualization, we used the
above sampling method to calculate the variance of contig-averaged pLM embeddings (pLM embeddings
mean-pooled across the contig) for each MGYP that occurs at least 100 times in the dataset.
584
Attention analysis
Attention heads (n = 190) were extracted by running inference on unmasked subcontigs, and the raw
attention weights were subsequently symmetrized. *E.coli* K12 RegulonDB[58] was used to probe heads with
attention patterns that correspond the most with operons. Pearson's correlation between symmetrized raw
attentions and operons were calculated for each head. We trained a logistic regression classifier that predicts
whether two neighboring genes belong to the same operon based on the attention weights across all attention
heads corresponding to the gene pair.
592
TnsC structural homolog analysis
TnsC structural homologs were identified by searching ShCAST TnsC (PDB 7M99 chain H) against the
MGYP database using Foldseek on ESM Atlas (https://esmatlas.com/). The contigs containing these
homologs in the MGnify database were used to calculate the contextualized protein embeddings of the
identified structural homologs. Contigs with less than 15 genes were excluded from the analysis. Contigs
encoding proteins that were previously identified as "TnsC" using the UniRef90 database (see **Gene**
annotation methods section above) were included in the database. "TnsC-like" contigs were manually
annotated based on the presence of transposase genes (TnsB) and TniQ. Fifty random examples of MGnify
contigs containing MGYPs annotated as NuoA and DnaB were added as negative controls for the UMAP
visualization. We calculated KL divergence ratios using the following formula $\frac{D_{KL}(B||A)}{D_{KL}(C||A)}$ where A is the
distribution of representations of known TnsC, B is the distribution of representations of manually curated
TnsC-like AAA+ regulators, C is the distribution of representations of other AAA+ regulators that are
functionally unrelated structural homologs of known TnsC. Therefore, this metric ranges from 0 to 1, where
a lower ratio represents increased ability to functionally discriminate distribution of B from C relative to A.
KL divergence was calculated using the same formula as in the methods section **Distributions of**
unannotated and annotated embeddings, except with 20 principal components that explained >85% of
variances across all embeddings.
610
Paralogy and orthology analysis
UniProt IDs from ABC transporter ModA and ModC protein interacting paralog pairs (n = 4823) were
previously   identified   by   Ovchinnikov   et   al[48]   and   were   downloaded   from
https://gremlin.bakerlab.org/cplx.php?uni_a=2ONK_A&uni_b=2ONK_C   and   subsequently   used   to
download raw protein sequences from the UniProt server. Only pairs (n = 2700) where both raw sequences
were available for download, and where the UniProt ID differed by one (indicating adjacent positioning in
the reference genome) were selected for subsequent analyses. We constructed test contigs consisting of
three genes, where first and third genes are masked, and the second gene encodes one of the pair in forward

direction. We then queried gLM to predict the two neighboring masked genes, and considered the prediction to be correct if either of the proteins closest to masked genes's highest confidence prediction in embedding space belongs to the same sequence cluster as the interacting protein (50% amino acid sequence identity, calculated using CD-HIT v4.6[62]). Random chance correct prediction rate (1.6±1.0 was simulated using 1000 iterations of random predictions generated within the standard normal distribution and performing the same operation as above to compute the rate of correct predictions.

Taxonomic analysis and visualization
4551 bacterial and archeal representative genomes and 11660 reference viral genomes were downloaded from the RefSeq database (ftp://ftp.ncbi.nlm.nih.gov/genomes/refseq) on 12 Feb 2023. A random 30-gene subcontig is chosen and encoded using ESM2, which then were subsequently concatenated with an orientation vector and then used as input for the trained gLM. The last hidden layer was mean-pooled across the sequence to retrieve 1280-feature contextualized contig embeddings. The ESM2 protein embeddings were also mean-pooled across the sequence to retrieve 1280-feature context-free contig embeddings. We trained a logistic regression classifier to predict the class-level taxonomy of subcontigs and evaluated the performance using stratified k-fold cross-validation (k=5).

UMAP visualization and statistical tests
All UMAP dimensionality reductions calculated with following parameters: n_neighbors = 15, min_dist = 0.1. Silhouette scores were calculated using the *sklearn* package using the default setting with euclidean distance metric.

Data and code availability

Data availability
Dataset used for training is available for download from the MGnify server (http://ftp.ebi.ac.uk/pub/databases/metagenomics/peptide_database/2022_05/). The model is available at zenodo under accession number 10.5281/zenodo.7855545.

Code availability
Training and inference code and analysis scripts are available at https://github.com/y-hwang/gLM.

Declarations

Acknowledgements. We would like to thank the EBI MGnify team for generating and maintaining the metagenome database. We would also like to thank Meta AI's ESM developers who made both the folded MGnify proteins structures and source-code openly available. We also thank Simon Roux and Landen Goszashti for insightful discussions.

Author contributions. YH prepared the datasets and trained the model with support from ALC and SO; ALC, SO and PRG provided input in analysis and data interpretation; YH wrote the manuscript with input from all authors; All authors read and approved the final manuscript.

Funding information. This work was supported by the Gordon and Betty Moore Foundation grant #9208 to P.R.G., NSF OCE-1635365 to P.R.G, and by the National Aeronautics and Space Administration under grant no. 80NSSC18K1140 and 80NSSC19K1427 issued through the NASA Network for Life Detection program to P.R.G. The computations in this paper were run on the FASRC Cannon cluster supported by the FAS Division of Science Research Computing Group at Harvard University.

Conflicting interests. The authors declare that they have no conflict of interest.

Extended data

Extended Data 1. Comparison of gLM to previous efforts in modeling various aspects of biological sequences.

	Multi-gene input	Continuous representation of genes	Generalizable across organisms (Organism-agnostic pretraining)	Self-supervised language model
gLM (this study)	✓	✓	✓ (Metagenomic sequences with bias towards bacteria, archaea and viruses)	✓
pLMs[4–7] (e.g. ESM2, ProtBert, ProtT5, ProGen, CaLM)	✗	✓	✓	✓
Miller et al[16]	✓	✗	✓	✗
Enformer[18]	✓	✓	✗ (Pretrained on human and mouse genomes only)	✗
DNABERT[19]	✗ (Max context length of DNABERT-6 is 3072 bp, which is not sufficient to include a median length (26,288 bp) human protein coding gene[63])	✓	✗ (Pretrained on human genome)	✓
Nucleotide Transformer[20]	✗ (Max context length is 6000 bp, which is not sufficient to include a median length (26,288 bp) human protein coding gene)	✓	✗ (Heavily biased towards human genome)	✓
HyenaDNA[21]	✓	✓	✗ (Pretrained on Human genome)	✓
GenSLM-foundation model[22]	✗ (Single genes used for pretraining)	✓	✓	✓
GenSLM-SARS-CoV2 genome model[22]	✓	✓	✗ (fine-tuned on SARS-CoV2 genomes only)	✓

674
Extended Data 2. Detailed gLM training and inference schematics. A) Training begins with converting
15-30 gene metagenomic subcontigs to protein embeddings using ESM2. Orientation feature is
concatenated for each protein and 15% of the proteins are masked randomly to generate training inputs.
Labels are generated by applying PCA dimensionality reduction on the ESM2 protein embeddings, and
concatenating the orientation feature. gLM is trained to make four possible predictions for the masked
tokens, and their associated likelihoods. Training loss is calculated on both the prediction and likelihoods.
The training stage takes several weeks on four NVIDIA A100 GPUs. **B)** At inference time, inputs are
generated from a metagenomic subcontig using ESM2 output concatenated with an orientation feature.
Hidden states and attention patterns of the trained gLM can be used for various downstream tasks.

684
685

686
687 **Extended data 3. Validation accuracy curves for gLM (A) and biLSTM baseline (B).**

688
689
690 **Extended data 4. Comparison of biLSTM baseline model with transformer-based gLM architecture**
691 **and validation performances.** Note that the biLSTM baseline is smaller in model size than gLM. While
692 we attempted to scale this model by increasing the number of layers, the model failed to converge.
693

	biLSTM	gLM
Number of layers	5	19
Attention heads	N/A	10
Input embedding dimension	1281	1281
Hidden size	1280	1280
Batch size	4000	3000
Learning rate	1e-4	1e-4
Warm up steps	5000	5000
Training steps	467,253	1,296,960
Number of predictions	1	4
Number of parameters	27,811,840	954,736,916
% Pseudo-accuracy (validation)	27.9	71.9
% Absolute accuracy (validation)	14.78	59.2

Extended Data 5. Ablation of pLM representations. Ablated gLM was trained on one-hot representations
until convergence (<0.1% decrease in loss over 40k iterations).

	gLM	**gLM one-hot**
Representations	ESM2 embedding	One-hot amino acid encoding
Pooling	mean	mean
Number of layers	19	19
Attention heads	10	10
Input embedding dimension	1281	34
Hidden size	1280	1280
Batch size	3000	3000
Learning rate	1e-4	1e-4
Warm up steps	5000	5000
Training steps	1296960	132050
Number of predictions	4	4
Number of parameters	954736916	945338764
% Pseudo-accuracy (validation)	71.9	3.29
% Absolute accuracy (validation)	59.2	0.002
Operon prediction mAP	0.775 ± 0.29	0.426 ± 0.015

699 **Extended Data 6. Contextualized protein embeddings for all 30 other multi-biome MGYPs. Biome**
700 color legend is identical to **Figure 2B**. Blue: Host-associated, Green: Engineered, Orange: Environmental,
701 Grey: Mixed.

702
703

704
705 **Extended Data 7. Contig-averaged pLM embeddings for figures 2B, F, and I respectively.** Contig-
706 averaged pLM embeddings were calculated by mean-pooling pLM embeddings across a given subcontig.
707 Silhouette scores for clustering based on biomes (A), preferred direction of enzymatic reaction (B) and
708 functional category (C) are 0.08, 0.067, and 0.05±0.17 (n = 10 independent samples) respectively.
709
710

711
Extended Data 8. Linear probing of context-free, context-only and contextualized gene embeddings.

A) Schematics of how context-free, context-only, and contextualized gene embeddings are extracted for
linear probing. Context-only gene embeddings are extracted by masking the queried gene, therefore the
original pLM signal cannot propagate through to gLM representation. This can be used to quantify how
gLM-learned context informs EC number prediction independent of pLM signal. B) Schematics of how LP
is used for EC number classification. C) Per-layer linear probing accuracy of gLM contextualized
embeddings, where no-masking was performed at the time of inference. The 0th layer of gLM is equivalent
to context-free pLM embedding. D) Per-layer linear probing accuracies of gLM context-only embeddings,
where the queried genes are masked at the time of inference.

Extended Data 9. Context-variant gene annotations.

A. List of top ten most context variant genes where variance is calculated using gLM contextualized embeddings.

MGYP ID	Mean embedding variance	UniRef annotation
815530568	18.87014775	Uncharacterized protein n=1
3385096772	17.70851124	Tail fiber protein n=20
2546832411	17.70269541	Capsular exopolysaccharide family n=1
767058056	17.08193362	Type I restriction enzyme endonuclease subunit
3381572716	16.44215407	Ferrous iron transport protein B n=11
2534762610	16.38703203	None
2733868861	16.21466745	30S ribosomal protein S18 n=4
551790786	16.06301055	30S ribosomal protein S18 n=285
3383952544	15.74879686	CRISPR-associated endoribonuclease Cas2 n=88
832772145	15.62986097	Ferrous iron transport protein A n=6

B. List of top most context variant genes where variance is calculated using contig-Averaged .

MGYP ID	Mean embedding variance	UniRef annotation
3384243084	18.43362238	DDE_Tnp_1 domain-containing protein n=137
943740416	17.77505976	Phosphoribosylamine--glycine ligase n=7
120256991	16.91703339	Asparaginase n=7
209907419	16.75686986	DNA mismatch repair protein MutS n=2
3380534673	16.67205026	IS66-like element ISBf10 family transposase
3384295730	16.44076785	IS66-like element ISBf10 family transposase
3381576767	16.23692972	VOC domain-containing protein n=96
3385319961	16.10454523	Peptidase E n=538
87924424	15.97918443	3-oxoacyl-[acyl-carrier-protein] synthase 3
997418675	15.91416004	HNH homing endonuclease n=2

Heads

Layers

731
732 **Extended data 10. Visualization of attention heads for a randomly chosen sequence.** Increasing layer
733 depth down the figure. Darker color represents larger attention scores.

Extended Data 11. Attention-based operon prediction of AAA+ regulators. A) Annotations were made by searching against the UniRef90 database. Protein annotation in Red indicates the location of the AAA+ regulator identified based on a structural search of TsnC. Raw attention in the most correlated head (2nd layer, 7nd head, "L2-H7") is shown in the first row of the heatmap, and the second row is the predicted operon using the logistic regression predictor trained on *E.coli* K-12 operon dataset. **B)** gLM representations (last hidden layer of gLM) for **Figure 4EF** (KL divergence ratio = 0.53). **C)** Contig-averaged pLM baseline for **Figure 4EF**, where pLM embeddings across the subcontig were averaged to represent the queried protein (KL divergence ratio = 0.57)

744   **Extended Data 12. Distance based clustering of raw embeddings of AAA+ regulators and controls**
745   **shown in Figure 4EF.** Row colors and labels correspond to the point colors and designation used in
746   **Figure 4EF** and **Extended Data 12**.

Extended Data 13. Contextualization of contig embeddings and taxonomic classification. Comparison of context-free (A) and contextualized (B) class-level taxonomy of 30-gene contigs as shown in **Figure 5G**. Confusion matrices for context-free (C) and contextualized (D) logistic regression classifier as shown in **Figure 5F**.

754
755 **Extended Data 14**. Cumulative distribution of raw MGnify contig lengths (count of encoded genes),
756 MGnify contigs < 15 genes were excluded from the corpus in this study. Red line is drawn at the contig
757 length of 30 genes.

759
760
761 **Extended Data 15**. Cumulative explained variance of principal components of ESM2 embeddings
762 calculated on 2.5 million randomly selected MGYPs.

References

1.   Redfern, O. C., Dessailly, B. & Orengo, C. A. Exploring the structure and function paradigm. *Curr.*
Opin. Struct. Biol. **18**, 394–402 (2008).

2.   Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**, 583–589
(2021).

3.   Baek, M. *et al.* Accurate prediction of protein structures and interactions using a three-track neural
network. *Science* **373**, 871–876 (2021).

4.   Rives, A. *et al.* Biological structure and function emerge from scaling unsupervised learning to 250
million protein sequences. *Proc. Natl. Acad. Sci. U. S. A.* **118**, (2021).

5.   Elnaggar, A. *et al.* ProtTrans: Towards Cracking the Language of Life's Code Through Self-
Supervised Deep Learning and High Performance Computing. *arXiv [cs.LG]* (2020).

6.   Madani, A. *et al.* Large language models generate functional protein sequences across diverse
families. *Nat. Biotechnol.* 1–8 (2023).

7.   Outeiral, C. & Deane, C. Codon language embeddings provide strong signals for protein
engineering. *BioRxiv* (12/2022) doi:10.1101/2022.12.15.519894.

8.   Wright, S. On the roles of directed and random changes in gene frequency in the genetics of
populations. *Evolution* **2**, 279–294 (1948).

9.   Lynch, M. & Conery, J. S. The Origins of Genome Complexity. *Science* **302**, 1401–1404 (2003).

10. Cordero, O. X. & Polz, M. F. Explaining microbial genomic diversity in light of evolutionary
ecology. *Nat. Rev. Microbiol.* **12**, 263–273 (2014).

11. Treangen, T. J. & Rocha, E. P. C. Horizontal transfer, not duplication, drives the expansion of
protein families in prokaryotes. *PLoS Genet.* **7**, e1001284 (2011).

12. Shapiro, B. J. *et al.* Population genomics of early events in the ecological differentiation of bacteria.
Science **336**, 48–51 (2012).

13. Kountz, D. J. & Balskus, E. P. Leveraging Microbial Genomes and Genomic Context for Chemical

Discovery. *Acc. Chem. Res.* **54**, 2788–2797 (2021).

14. Shmakov, S. A. *et al.* Systematic prediction of functionally linked genes in bacterial and archaeal

genomes. *Nat. Protoc.* **14**, 3013–3031 (2019).

15. Yelton, A. P. *et al.* A semi-quantitative, synteny-based method to improve functional predictions for

hypothetical and poorly annotated bacterial and archaeal genes. *PLoS Comput. Biol.* **7**, e1002230

(2011).

16. Miller, D., Stern, A. & Burstein, D. Deciphering microbial gene function using natural language

processing. *Nat. Commun.* **13**, 5731 (2022).

17. Konno, N. & Iwasaki, W. Machine learning enables prediction of metabolic system evolution in

bacteria. *Sci Adv* **9**, eadc9130 (2023).

18. Avsec, Ž. *et al.* Effective gene expression prediction from sequence by integrating long-range

interactions. *Nat. Methods* **18**, 1196–1203 (2021).

19. Ji, Y., Zhou, Z., Liu, H. & Davuluri, R. V. DNABERT: pre-trained Bidirectional Encoder

Representations from Transformers model for DNA-language in genome. *Bioinformatics* **37**, 2112–

2120 (2021).

20. Dalla-Torre, H. *et al.* The Nucleotide Transformer: Building and Evaluating Robust Foundation

Models for Human Genomics. *bioRxiv* 2023.01.11.523679 (2023) doi:10.1101/2023.01.11.523679.

21. Nguyen, E. *et al.* HyenaDNA: Long-Range Genomic Sequence Modeling at Single Nucleotide

Resolution. (2023).

22. Zvyagin, M. *et al.* GenSLMs: Genome-scale language models reveal SARS-CoV-2 evolutionary

dynamics. *bioRxiv* (2022) doi:10.1101/2022.10.10.511571.

23. Lin, Z. *et al.* Evolutionary-scale prediction of atomic-level protein structure with a language model.

Science **379**, 1123–1130 (2023).

24. Vaswani, Shazeer & Parmar. Attention is all you need. *Adv. Neural Inf. Process. Syst.*

25. Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep Bidirectional

Transformers for Language Understanding. *arXiv [cs.CL]* (2018).

26. Hochreiter, S. & Schmidhuber, J. Long short-term memory. *Neural Comput.* **9**, 1735–1780 (1997).

27. Richardson, L. *et al.* MGnify: the microbiome sequence data analysis resource in 2023. *Nucleic*

Acids Res. **51**, D753–D759 (2023).

28. Blattner, F. R. *et al.* The complete genome sequence of Escherichia coli K-12. *Science* **277**, 1453–

1462 (1997).

29. Jeffery, C. J. Protein moonlighting: what is it, and why is it important? *Philos. Trans. R. Soc. Lond.*

B Biol. Sci. **373**, (2018).

30. Miskei, M. *et al.* Fuzziness enables context dependence of protein interactions. *FEBS Lett.* **591**,

2682–2695 (2017).

31. Gherardini, P. F., Wass, M. N., Helmer-Citterich, M. & Sternberg, M. J. E. Convergent evolution of

enzyme active sites is not a rare phenomenon. *J. Mol. Biol.* **372**, 817–845 (2007).

32. Ben-Hur, A. & Brutlag, D. Remote homology detection: a motif based approach. *Bioinformatics* **19**

Suppl 1, i26–33 (2003).

33. Bertram, S. *et al.* Methanogenic capabilities of ANME-archaea deduced from[13]C-labelling

approaches. *Environmental Microbiology* vol. 15 2384–2393 Preprint at

https://doi.org/10.1111/1462-2920.12112 (2013).

34. Moran, J. J., House, C. H., Thomas, B. & Freeman, K. H. Products of trace methane oxidation

during nonmethyltrophic growth by*Methanosarcina*. *Journal of Geophysical Research* vol. 112

Preprint at https://doi.org/10.1029/2006jg000268 (2007).

35. Shao, N. *et al.* Expression of divergent methyl/alkyl coenzyme M reductases from uncultured

archaea. *Commun Biol* **5**, 1113 (2022).

36. Reif, E. *et al.* Visualizing and measuring the geometry of BERT. *Adv. Neural Inf. Process. Syst.* **32**,

(2019).

37. Vanni, C. *et al.* Unifying the known and unknown microbial coding sequence space. *Elife* **11**,

(2022).

38. Bileschi, M. L. *et al.* Using deep learning to annotate the protein universe. *Nat. Biotechnol.* **40**, 932–

937 (2022).

39. Rogers, A., Kovaleva, O. & Rumshisky, A. A primer in BERTology: What we know about how

BERT works. *Trans. Assoc. Comput. Linguist.* doi:10.1162/tacl_a_00349/96482.

40. Vig, J. *et al.* BERTology Meets Biology: Interpreting Attention in Protein Language Models. *arXiv*

[cs.CL] (2020).

41. Salgado, H. *et al.* Using RegulonDB, the Escherichia coli K-12 Gene Regulatory Transcriptional

Network Database. *Curr. Protoc. Bioinformatics* **61**, 1.32.1–1.32.30 (2018).

42. White, S. R. & Lauring, B. AAA+ ATPases: achieving diversity of function with conserved

machinery. *Traffic* **8**, 1657–1667 (2007).

43. Park, J.-U. *et al.* Structures of the holo CRISPR RNA-guided transposon integration complex.

Nature **613**, 775–782 (2023).

44. Rybarski, J. R., Hu, K., Hill, A. M., Wilke, C. O. & Finkelstein, I. J. Metagenomic discovery of

CRISPR-associated transposons. *Proc. Natl. Acad. Sci. U. S. A.* **118**, (2021).

45. Benler, S. *et al.* Cargo Genes of Tn7-Like Transposons Comprise an Enormous Diversity of Defense

Systems, Mobile Genetic Elements, and Antibiotic Resistance Genes. *MBio* **12**, e0293821 (2021).

46. Klompe, S. E., Vo, P. L. H., Halpin-Healy, T. S. & Sternberg, S. H. Transposon-encoded CRISPR–

Cas systems direct RNA-guided DNA integration. *Nature* **571**, 219–225 (2019).

47. van Kempen, M. *et al.* Foldseek: fast and accurate protein structure search. *bioRxiv*

2022.02.07.479398 (2022) doi:10.1101/2022.02.07.479398.

48. Ovchinnikov, S., Kamisetty, H. & Baker, D. Robust and accurate prediction of residue-residue

interactions across protein interfaces using evolutionary information. *Elife* **3**, e02030 (2014).

49. Lupo, U., Sgarbossa, D. & Bitbol, A.-F. Pairing interacting protein sequences using masked

language modeling. *arXiv* (2023) doi:2308.07136.

50. Guo, J. *et al.* VirSorter2: a multi-classifier, expert-guided approach to detect diverse DNA and RNA

viruses. *Microbiome* **9**, 37 (2021).

51. Kaplan, J. *et al.* Scaling Laws for Neural Language Models. *arXiv [cs.LG]* (2020).

52. Kiros, R., Salakhutdinov, R. & Zemel, R. Multimodal Neural Language Models. in *Proceedings of*

the 31st International Conference on Machine Learning (eds. Xing, E. P. & Jebara, T.) vol. 32 595–

603 (PMLR, 22--24 Jun 2014).

53. Steinegger, M. & Söding, J. MMseqs2 enables sensitive protein sequence searching for the analysis

of massive data sets. *Nat. Biotechnol.* **35**, 1026–1028 (2017).

54. Lin, Z. *et al.* Evolutionary-scale prediction of atomic level protein structure with a language model.

bioRxiv 2022.07.20.500902 (2022) doi:10.1101/2022.07.20.500902.

55. Liu, Y. *et al.* RoBERTa: A Robustly Optimized BERT Pretraining Approach. *arXiv [cs.CL]* (2019).

56. Huang, Z., Liang, D., Xu, P. & Xiang, B. Improve Transformer Models with Better Relative Position

Embeddings. *arXiv [cs.CL]* (2020).

57. Loshchilov, I. & Hutter, F. Decoupled Weight Decay Regularization. *arXiv [cs.LG]* (2017).

58. Tierrafría, V. H. *et al.* RegulonDB 11.0: Comprehensive high-throughput datasets on transcriptional

regulation in Escherichia coli K-12. *Microb Genom* **8**, (2022).

59. Buchfink, B., Xie, C. & Huson, D. H. Fast and sensitive protein alignment using DIAMOND. *Nat.*

Methods **12**, 59–60 (2015).

60. Suzek, B. E., Huang, H., McGarvey, P., Mazumder, R. & Wu, C. H. UniRef: comprehensive and

non-redundant UniProt reference clusters. *Bioinformatics* **23**, 1282–1288 (2007).

61. Yu, T. *et al.* Enzyme function prediction using contrastive learning. *Science* **379**, 1358–1363 (2023).

62. Li, W., Jaroszewski, L. & Godzik, A. Clustering of highly homologous sequences to reduce the size

of large protein databases. *Bioinformatics* **17**, 282–283 (2001).

63. Piovesan, A., Caracausi, M., Antonaros, F., Pelleri, M. C. & Vitale, L. GeneBase 1.1: a tool to

summarize data from NCBI gene datasets and its application to an update of human gene statistics.

Database **2016**, (2016).