Context-Aware Amino Acid Embedding Advances Analysis of TCR-Epitope Interactions

Pengfei Zhang [1,2], Seojin Bang [2]*, Michael Cai [1,2] and Heewook Lee [1,2] †

[1] School of Computing and Augmented Intelligence, Arizona State University, Tempe, AZ, USA

[2] Biodesign Institute, Arizona State University, Tempe, AZ, USA

Abstract

Accurate prediction of binding interaction between T cell receptors (TCRs) and host cells is fundamental to understanding the regulation of the adaptive immune system as well as to developing data-driven approaches for personalized immunotherapy. While several machine learning models have been developed for this prediction task, the question of how to specifically embed TCR sequences into numeric representations remains largely unexplored compared to protein sequences in general. Here, we investigate whether the embedding models designed for protein sequences, and the most widely used BLOSUM-based embedding techniques are suitable for TCR analysis. Additionally, we present our context-aware amino acid embedding models (`catELMo`) designed explicitly for TCR analysis and trained on 4M unlabeled TCR sequences with no supervision. We validate the effectiveness of `catELMo` in both supervised and unsupervised scenarios by stacking the simplest models on top of our learned embeddings. For the supervised task, we choose the binding affinity prediction problem of TCR and epitope sequences and demonstrate notably significant performance gains (up by at least 14% AUC) compared to existing embedding models as well as the state-of-the-art methods. Additionally, we also show that our learned embeddings reduce more than 93% annotation cost while achieving comparable results to the state-of-the-art methods. In TCR clustering task (unsupervised), `catELMo` identifies TCR clusters that are more homogeneous and complete about their binding epitopes. Altogether, our `catELMo` trained without any explicit supervision interprets TCR sequences better and negates the need for complex deep neural network architectures.

---

*Now at Google.

†Correspondence: heewook.lee@asu.edu

1   Introduction

T cell receptors (TCRs) play critical roles in adaptive immune systems as they enable T cells to distinguish abnormal cells from healthy cells. TCRs carry this important function by binding to antigens presented by major histocompatibility complex (MHC) and recognizing whether the antigens are self or foreign [1]. It is widely accepted that the third complementarity-determining region (CDR3) of the TCRβ chain is the most important in determining its binding specificity to epitope—a part of an antigen [2, 3]. The advent of publicly available databases of TCR-epitope cognate pairs opened the door to computational methods to predict the binding affinity of a given pair of TCR and epitope sequences. Computational prediction of binding affinity is important as it can drastically reduce the cost and the time needed to narrow down a set of candidate TCR targets, thereby accelerating the development of personalized immunotherapy leading to vaccine development and cancer treatment [4, 5]. Computational prediction is challenging primarily due to 1) many-to-many binding characteristics [6] and 2) the limited amount of currently available data.

Despite the challenges, many deep neural networks have been leveraged to predict binding affinity between TCRs and epitopes [7, 8, 9, 10, 11, 12]. While each model has its own strengths and weaknesses, they all suffer from poor generalizability when applied to unseen epitopes, not present in the training data [7, 13]. In order to alleviate this, we focus mainly on embedding, as embedding an amino acid sequence into a numeric representation is the very first step needed to train and run a deep neural network. Furthermore, a 'good' embedding has been shown to boost downstream performance even with a few numbers of downstream samples [14, 15].

BLOSUM matrices [16] are widely used for representing amino acids into biological-related numeric vectors in TCR analysis [7, 9, 11, 17]. However, BLOSUM matrices are static embedding methods as they always map an amino acid to the same vector regardless of its context. For example, in static word embedding, the word "mouse" in phrases "a mouse in desperate search of cheese" and "to click, press and release the left mouse button" will be embedded as the same numeric representation even though it is used in different contexts. Similarly, the amino acid residue G appearing five times in a TCRβ CDR3 sequence CASGGTGGANTGQLYF may play different roles in binding to antigens as each occurrence has a different position and neighboring residues. The loss of such contextual information from static embedding may inevitably compromise model performances [18, 19].

Recent successes of large language models [14, 15] have been prompting new research applying text embedding techniques to amino acid embedding. Large language models are generally trained on a large text corpus in a self-supervised manner where no labels are required [18, 20, 21]. A large number of (unlabeled) protein sequences has been available via high quality and manually curated databases such as UniProt [22]. With the latest development of targeted sequencing assays of TCR repertoire, a large number (unlabeled) of TCR sequences has also been accessible to the public via online databases such as ImmunoSEQ [23]. These databases have allowed researchers to develop large-scale amino acid embedding models that can be used for various downstream tasks. Asgari et al. [24] first utilized Word2vec [20] model with 3-mers of amino acids to learn embeddings of protein sequences. By considering a 3-mer amino acids as a word and a protein sequence as a sentence, they learn amino acid representations by predicting the context of a given target 3-mer in a large corpus of surrounding ones. Yang et al. [25] applied Doc2vec [21] models to protein sequences with different sizes of k-mers in a similar manner to Asgari et al. and showed better performance over sparse one-hot encoding. One-hot encoding produces static embeddings, like BLOSUM, which leads to the loss of positional and contextual information.

Later, SeqVec [26] and ProtTrans [27] experimented with dynamic protein sequence embeddings via multiple context-aware language models [18, 19, 28], showing advantages across multiple tasks. Note that the aforementioned amino acid embedding models were designed for protein sequence analysis. Although these models may have learned general representations of protein sequences, it does not necessarily signify their generalization performance on TCR-related downstream tasks.

Here, we explore strategies to develop amino acid embedding models and emphasize the importance of using 'good' amino acid embeddings for a significant performance gain in TCR-related downstream tasks. It includes neural network depth, architecture, types and numbers of training samples, and parameter initialization. Based on our experimental observation, we propose catELMo, whose architecture is adapted from ELMo (Embeddings from Language Models [18]), a bi-directional context-aware language model. catELMo is trained on more than four million TCR sequences collected from ImmunoSEQ [23] in an unsupervised manner, by contextualizing amino acid inputs and predicting the next amino acid token. We compare its performance with state-of-the-art amino acid embedding methods on two TCR-related downstream tasks. In TCR-epitope binding affinity prediction application, catELMo significantly outperforms the state-of-the-art method by at least 14% (absolute improvement) of AUCs. We also show catELMo achieves an equivalent performance to

the state-of-the-art method while dramatically reducing downstream training sample annotation cost (more than 93% absolute reduction). In the epitope-specific TCR clustering application, `catELMo` also achieves comparable to or better cluster results than state-of-the-art methods.

2   Results

`catELMo` is a bi-directional amino acid embedding model that learns contextualized amino acid representations (Fig. 1a), treating an amino acid as a word and a sequence as a sentence. It learns patterns of amino acid sequences with its self-supervision signal, by predicting each the next amino acid token given its previous tokens. It has been trained on 4,173,895 TCRβ CDR3 sequences (52 million of amino acid tokens) from ImmunoSEQ [23] (Table 1). `catELMo` yields a real-valued representation vector for a sequence of amino acids, which can be used as input features of various downstream tasks. We evaluated `catELMo` on two different TCR-related downstream tasks, and compared its performance with existing amino acid embedding methods, namely BLOSUM62 [16], Yang et al. [25], ProtBert [27], SeqVec [26], and TCRBert [29]. We also investigated various components of `catELMo` in order to account for its high performance, including the neural network architecture, layer depth and size, types of training data, and the size of downstream training data.

We briefly summarize the two downstream tasks here and refer further details to Section 4.4. The first downstream task is TCR-epitope binding affinity prediction (Fig. 1b). All embedding models compared were to embed input sequences into the identical prediction model. Each prediction model was trained on 300,016 TCR-epitope binding and non-binding pairs (1:1 ratio), embedded by each embedding model. We used a neural network with three linear layers for the prediction model, which takes a pair of TCR and epitope as input and returns a binding affinity (0–1) of the pair. The prediction performance was evaluated on testing sets each defined by two types of splitting methods [10], called TCR and epitope splits. The testing set of TCR split has no TCRs overlapped with training and validation sets, allowing us to measure out-of-sample TCR performance. Similarly, the testing set of epitope split has no epitopes overlapped with training and validation sets, allowing us to measure out-of-sample epitope performance. For a fair comparison, a consistent embedding method was applied to both TCR and epitope sequences within a single prediction model. The second task is epitope-specific TCR clustering that aims at grouping TCRs that bind to the same epitope (Fig. 1c). We tested with TCR sequences of human and mouse species sampled from McPAS [30] database.

Figure 1. **Methods overview.** **a**) `catELMo` is an ELMo-based bi-directional amino acid sequence representation model trained on TCR sequences. It takes a sequence of amino acid strings as input and predicts the right (or left) next amino acid tokens. `catELMo` consists of a charCNN layer and four bidirectional LSTM layers followed by a softmax activation. For a given TCR sequence of length L, each layer returns L vectors of length 1,024. The size of an embedded TCR sequence, therefore, is $[5, L, 1024]$. Global average pooling with respect to the length of TCR, L, is applied to get a representation vector with a size of $1,024$. **b**) TCR-epitope binding affinity prediction task. An embedding method (e.g., `catELMo`) is applied to both TCR and epitope sequences. The embedding vectors are then fed into a neural network of three linear layers for training a binding affinity prediction model. The model predicts whether a given TCR and epitope sequence bind or not. **c**) Epitope-specific TCR sequences clustering. The hierarchical clustering algorithm is applied to TCR embedding vectors to group TCR sequences based on their epitope-specificity.

Table 1. **Data Summary.** The number of unique epitopes, TCRs, and TCR-epitope pairs used for `catELMo` and downstream tasks analysis.

Usage	Source	Unique Epitopes	Unique TCRs	Unique TCR-epitope Pairs	Amino Acid Tokens
`catELMo` Training	ImmuneSEQ [23]	✗	4,173,895	✗	52,546,029
Binding Affinity Prediction	VDJdb* [33]	187	3,915	4,047	✗
	McPAS [30]	301	9,822	10,156	✗
	IEDB [34]	1189	136,492	145,678	✗
	Total (after removing duplicates)	982	140,675	150,008	✗
Epitope-specific TCR Clustering	McPAS [30] Human, Mice	8	5,607	5,607	✗
	McPAS [30] Human	8	5,528	5,528	✗
	McPAS [30] Mice	8	1,322	1,322	✗

*VDJdb pairs with a score larger than 0 were used. ✗ represents not applicable. For binding affinity prediction task, we additionally generated 150,008 unique non-binding TCR-epitope sequences as negative samples.

We applied the hierarchical clustering [31] and reported normalized mutual information (NMI) [32] to qualify the goodness of the clustering partition of TCR sequences.

2.1 `catELMo` outperforms the existing embedding methods at discriminating binding and non-binding TCR-epitope pairs

We investigated the downstream performance of TCR-epitope binding affinity prediction models trained using `catELMo` embeddings. In order to compare performance across different embedding methods, we used the identical downstream model architecture for each method. The competing embedding methods compared are BLOSUM62 [16], Yang et al. [25], ProBert [27], SeqVec [26] and TCRBert [29]. We observed that the prediction model using `catELMo` embeddings significantly outperformed those using existing amino acid embedding methods in both TCR (Figure 2a, b) and epitope (Figure 2d, e) split. In TCR split, where no TCRs in the testing set exist in the training and validation set, `catELMo`'s prediction performance was significantly greater than the second best method (p-value $< 6.28 \times 10^{-23}$, Table 2). It achieved AUC 96.04 which was 14 points higher than that of the second-highest performing method, while the rest of the methods performed worse than or similar to BLOSUM62. In epitope split, where no epitopes in the testing set exist in the training and validation set, the prediction model using `catELMo` also outperformed others with even larger performance gaps. `catELMo` significantly boosted 17 points of AUCs than the second-highest performing method (p-value $< 1.18 \times 10^{-7}$, Table 3). Similar performance gains from `catELMo` were also observed in other metrics such as Precision, Recall, and F1 scores (Supplementary Fig. 1).

We also visually observed that `catELMo` aided the model to better discriminate binding and non-binding

Figure 2. **Comparison of the amino acid embedding methods for TCR-epitope binding affinity prediction task.** We obtained TCR and epitope embeddings and used them as input features of binding affinity prediction model. A binding affinity prediction model is trained on each embedding method's embedding dataset. The prediction performance comparison on **a), b), c)** TCR split and **d), e), f)** epitope split. **a), d)** Receiver Operating Characteristic (ROC) curve and **b), e)** AUC of the prediction model trained on different embedding methods. Error bars represent standard deviations over 10 trials. **c), f)** AUCs of the prediction model trained on different portions of downstream datasets. Error bands represent 95% confidence intervals over 10 trials.

Table 2. **TCR-epitope binding affinity prediction performance of TCR split.** Average and standard deviation of 10 trials are reported. P-values are from two-sample t-tests between catELMo and the second best method (underlined).

	AUC (%)	Precision (%)	Recall (%)	F1 (%)
BLOSUM62	82.03 ± 0.25	67.16 ± 1.01	82.04 ± 1.01	70.57 ± 0.73
Yang et al.	75.03 ± 0.20	62.54 ± 0.78	79.71 ± 1.45	65.22 ± 0.69
ProtBert	77.86 ± 0.29	70.01 ± 1.47	69.90 ± 2.65	69.85 ± 0.41
SeqVec	81.61 ± 0.21	69.30 ± 1.33	79.02 ± 2.02	71.75 ± 0.66
TCRBert	80.79 ± 0.17	74.19 ± 1.17	70.48 ± 1.60	72.89 ± 0.23
catELMo (ours)	$\mathbf{96.04 \pm 0.12}$	$\mathbf{86.88 \pm 0.92}$	$\mathbf{91.83 \pm 0.98}$	$\mathbf{88.94 \pm 0.21}$
p-value	6.28×10^{-23}	1.94×10^{-15}	1.82×10^{-14}	1.29×10^{-29}

TCRs for the five most frequent epitopes that appeared in our collected TCR-epitope pairs (Fig. 3). These five epitopes account for a substantial portion of our dataset, comprising 14.73% (44,292 pairs) of the total TCR-epitope pairs collected. For visualization, we performed t-SNE [35] on the top fifty principal components of the last latent vectors of each prediction model. Each point represents a pair of TCR-epitope, colored by epitope (lighter shade for positive binding and darker shade for negative binding). Different degrees of overlapping between positive pairs and negative ones in regard to the same epitope can be seen in the t-SNE plots. For example, most of the binding and non-binding data points from SeqVec embeddings are barely separated within each epitope group. On the other hand, the t-SNE plot of catELMo exhibits noticeable contrast between binding and non-binding pairs, indicating that catELMo aids the prediction model to distinguish labels. We also observed catELMo outperformed the other embedding methods in discriminating binding and non-binding TCRs for almost all individual epitopes. As shown in Supplementary Fig. 2, the prediction model using catELMo embeddings achieved the highest AUCs in 39 out of 40 epitopes,

Table 3. **TCR-epitope binding affinity prediction performance of epitope split.** Average and standard deviation of 10 trials are reported. P-values are from two-sample t-tests between catELMo and the second best method (underlined).

	AUC (%)	Precision (%)	Recall (%)	F1 (%)
BLOSUM62	75.54 ± 4.74	64.87 ± 2.17	73.12 ± 5.72	66.65 ± 2.94
Yang et al.	66.83 ± 2.46	58.68 ± 1.19	73.00 ± 3.65	60.16 ± 1.52
ProtBert	72.55 ± 4.18	67.66 ± 3.12	62.21 ± 6.93	66.04 ± 3.23
SeqVec	76.71 ± 4.02	66.35 ± 2.31	73.49 ± 6.26	67.92 ± 2.74
TCRBert	74.43 ± 3.98	73.34 ± 2.07	57.02 ± 7.70	67.64 ± 3.45
catELMo (ours)	$\mathbf{94.10 \pm 0.90}$	$\mathbf{84.64 \pm 1.39}$	$\mathbf{88.85 \pm 2.04}$	$\mathbf{86.33 \pm 1.04}$
p-value	1.18×10^{-7}	1.89×10^{-10}	1.47×10^{-5}	2.71×10^{-10}

Figure 3. **tSNE visualization for top five frequent epitopes.** We visually compared the embedding models on TCR-epitope binding affinity prediction task. We conduct tSNE analysis on the top 50 principle components of the last hidden layer features of the TCR-epitope binding affinity prediction models for out-of-sample epitopes. The clearer the boundary between positive pairs (lighter shade) and negative pairs (darker shade) associated with the same epitope sequence, the better the model is at discriminating binding and non-binding pairs.

and the second highest AUC on an epitope (GTSGSPIVNR) with only 1.09% lower than the highest score.

2.2 `catELMo` reduces a significant amount of annotation cost for achieving comparable prediction power

Language models trained on large corpus are known to improve downstream task performance with a smaller number of downstream training data [14, 19]. Similarly in TCR-epitope binding, we show that catELMo trained entirely on unlabeled TCR sequences facilitates its downstream prediction model to achieve the same performance with a significantly smaller amount of TCR-epitope training pairs (i.e., epitope-labeled TCR sequence). We trained a binding affinity prediction model for each $k\%$ of downstream data (i.e., catELMo embeddings of TCR-epitope pairs) where $k = 1, 2, \cdots, 10, 20, 30, \cdots, 100$. The widely used

BLOSUM62 embedding matrix was used as a comparison baseline under the same ks as it performs better than or is comparable to the other embedding methods.

A positive log-linear relationship between the number of (downstream) training data and AUCs was observed for both TCR and epitope split (Fig. 2c, f). The steeper slope in `catELMo` suggests that prediction models utilizing `catELMo` embeddings exhibit higher performance gain per number of training pairs compared to the BLOSUM62-based models. In TCR split, we observed that `catELMo`'s binding affinity prediction models with just 7% of the training data significantly outperform ones that use a full size of BLOSUM62 embeddings (p-value = 0.0032, Fig. 2c). `catELMo` with just 3%, 4%, and 6% of the downstream training data achieved similar performances to when using a full size of Yang et al., ProtBert, and SeqVec embeddings, respectively. Similarly, in epitope split, we showed `catELMo`'s prediction models with just 3% of training data achieved equivalent performance as ones built on a full size of BLOSUM62 embeddings (p-value = 0.8531, Fig. 2f). Compare to the other embedding methods, `catELMo` with just 1%, 2%, and 5% of the downstream training data achieved similar or better performance than when using a full size of Yang et al., ProtBert, and SeqVec embeddings, separately. Similar performance gains from `catELMo` were also observed in other metrics such as Precision, Recall, and F1 scores (Supplementary Fig. 3). Achieving accurate prediction with a small amount of training data is important for TCR analysis as obtaining the binding affinity of TCR-epitope pairs is costly.

2.3 `catELMo` allows clustering of TCR sequences with high performance

Clustering TCRs of similar binding profiles is important in TCR repertoire analysis as it facilitates discoveries of TCR clonotypes that are condition-specific [36, 37]. In order to demonstrate that `catELMo` embeddings can be used for other TCR-related downstream tasks, we performed hierarchical clustering [31] using each method's embedding (`catELMo`, BLOSUM62 [16], Yang et al. [25], ProBert [27], SeqVec [26] and TCRBert [29]) and evaluated the identified clusters against the ground-truth TCR groups labeled by their binding epitopes. We additionally compared our results with state-of-the-art TCR clustering methods, TCRdist [37] and GIANA [38], both of which were developed from BLOSUM62 matrix (see Section 4.4.2). Normalized mutual information (*NMI*) [32] is used to measure the clustering quality. Fig. 4a demonstrates NMI clustering comparison results of all TCR sequences bound to the top eight epitopes, covering both human and mouse species. We find that the cluster model built on `catELMo` embeddings maintains either the best or

Figure 4. **Comparison of the amino acid embedding methods for epitope-specific TCR clustering.** Hierarchical clustering is applied on the McPAS [30] database. We cluster TCRs binding to the top eight epitopes of **a**) both human and mouse species, **b**) only human epitopes, and **c**) only mouse epitopes. Larger NMI scores indicate TCR sequences that bind to the same epitope are grouped together in the same cluster and TCR sequences that do not bind to the same epitope are separated apart in different clusters.

second best NMI scores compared with ones that are computed on other embeddings. To investigate whether this observation remains true on individual species, we conducted the same clustering analysis on human and mouse species, separately. We showcase NMI comparison for the top eight epitopes in human (Fig. 4b) and mouse (Fig. 4c) species and observe a similar pattern that clustering results with `catELMo` achieve the highest or second-highest NMI scores. Altogether, `catELMo` embedding can assist TCR clustering with no supervision while achieving similar or better performance than other state-of-the-art methods in both human and mouse species.

2.4 ELMo-based architecture is preferable to BERT-based architecture in TCR embedding models

We observed `catELMo` using ELMo-based architecture outperformed the model using embeddings of TCRBert which uses BERT (Table 4). The performance differences were approximately 15 AUCs in TCR split (p-value $< 3.86 \times 10^{-30}$) and 19 AUCs in epitope split (p-value $< 3.29 \times 10^{-8}$). Because TCRBert was trained on a smaller amount of TCR sequences (around 0.5 million sequences) than `catELMo` , we further compared `catELMo` with various sizes of BERT-like models trained on the same dataset as `catELMo`: BERT-Tiny-TCR, BERT-Base-TCR, and BERT-Large-TCR having a stack of 2, 12, and 30 Transformer layers respectively (see Section 4.6.2). Note that BERT-Base-TCR uses the same number of Transformer layers as TCRBert. Additionally, we compared different versions of `catELMo` by varying the number of BiLSTM layers (2,

Table 4. **AUCs of TCR-epitope binding affinity prediction models built on BERT-based embedding models.** Average and standard deviation of 10 trials are reported.

	Nums of Transformer Layers	Embedding Size	TCR Split (%)	Epitope Split (%)
BERT-Tiny-TCR	2	768	81.23 ± 0.18	74.20 ± 4.01
BERT-Base-TCR	12	768	81.91 ± 0.21	74.94 ± 4.49
BERT-Large-TCR	30	1,024	81.29 ± 0.17	74.65 ± 3.79
TCRBert	12	768	80.79 ± 0.17	74.43 ± 3.98

4–default, and 8, see Section 4.6.1). As summarized in Table 4, TCR-epitope binding affinity prediction models trained on `catELMo` embeddings (AUC 96.04 and 94.70 on TCR and epitope split) consistently outperformed models trained on these Transformer-based embeddings (AUC 81.23–81.91 and 74.20–74.94 on TCR and epitope split). The performance gaps between `catELMo` and Transformer-based models (14 AUCs in TCR split and 19 AUCs in epitope split) were statistically significant (p-values $< 6.72 \times 10^{-26}$ and $< 1.55 \times 10^{-7}$ for TCR and epitope split respectively). We observed that TCR-epitope binding affinity prediction models trained on `catELMo`-based embeddings consistently outperformed the ones using Transformer-based embeddings (Table 4, 5). Even the worst-performed BiLSTM-based embedding model achieved higher AUCs than the best-performed Transformer-based embeddings at discriminating binding and non-binding TCR-epitope pairs in both TCR (p-value $< 2.84 \times 10^{-28}$) and epitope split (p-value $< 5.86 \times 10^{-6}$).

2.5 Within-domain transfer learning is preferable to cross-domain transfer learning in TCR analysis

We showed that `catELMo`, trained on TCR sequences, significantly outperformed amino acid embedding methods trained on generic protein sequences. `catELMo`-Shallow and SeqVec shared the same architecture consisting of character-level convolutional layers and a stack of two bi-directional LSTM layers but were trained on different types of training data. `catELMo`-Shallow was trained on TCR sequences (about 4

Table 5. **AUCs of TCR-epitope binding affinity prediction models trained on different sizes of `catELMo` embeddings.** Average and standard deviation of 10 trials are reported.

	Nums of BiLSTM Layers	Embedding Size	TCR Split (%)	Epitope Split (%)
`catELMo`-Shallow	2	1,024	95.67 ± 0.32	86.32 ± 2.68
`catELMo`	4	1,024	$\mathbf{96.04 \pm 0.12}$	$\mathbf{94.10 \pm 0.90}$
`catELMo`-Deep	8	1,024	93.94 ± 0.19	91.57 ± 1.59

million) while SeqVec was trained on generic protein sequences (about 33 million). Although `catELMo`-Shallow was trained on a relatively smaller amount of sequences compared to SeqVec, the binding affinity prediction model built on `catELMo`-Shallow embeddings (AUC 95.67 in TCR split and 86.32 in epitope split) significantly outperformed the one built on SeqVec embeddings (AUC 81.61 in TCR split and 76.71 in epitope split) by 14.06 and 9.61 on TCR and epitope split respectively. This suggests that knowledge transfer within the same domain is preferred whenever possible in TCR analysis.

3 Discussion

`catELMo` is an effective embedding model that brings substantial performance improvement in TCR-related downstream tasks. Our study emphasizes the importance of choosing the right embedding models. The embedding of amino acids into numeric vectors is the very first and crucial step that enables the training of a deep neural network. It has been previously demonstrated that a well-designed embedding can lead to significantly improved results on downstream analysis [25, 26, 27]. The reported performance of `catELMo` embedding on TCR-epitope binding affinity prediction and TCR clustering tasks indicates that `catELMo` is able to learn patterns of amino acid sequences more effectively than state-of-the-art embedding methods. While all other methods compared (except BLOSUM62) leverage a large number of unlabeled amino acid sequences, only our prediction model using `catELMo` significantly outperforms widely used BLOSUM62 and other models such as netTCR [9, 17] and ATM-TCR [10] trained on paired (TCR-epitope) samples only (Table 6). Our work suggests the need for developing sophisticated strategies to train amino acid embedding models that can enhance the performance of TCR-related downstream tasks even while requiring less amount of data and simpler prediction model structures.

Two important observations made from our experiments are 1) the type of data used for training amino acid embedding models is far more important than the amount of data and 2) ELMo-based embedding models consistently perform much better than BERT-based embedding models. While previously developed amino acid embedding models such as SeqVec and ProtBert were trained on 184- and 1,690-times more amino acid tokens compared to the training data used for `catELMo`, the prediction models using SeqVec and ProtBert performed poorly compared to the model using `catELMo` (see Sections 2.1 and 2.3). SeqVec and ProtBert were trained based on generic protein sequences, whereas `catELMo` was trained on a collection of TCR sequences from pooled TCR repertoires across many samples, indicating that the use of TCR data to train

Table 6. **AUCs of TCR-epitope binding affinity prediction models comparison with state-of-the-art prediction models.** All models are trained on the same dataset. Average and standard deviation of 10 trials are reported.

	TCR Split (%)	Epitope Split (%)
Ours	**96.04 ± 0.12**	**94.10 ± 0.90**
ATM-TCR	80.92 ± 0.26	74.87 ± 0.64
netTCR	81.07 ± 0.31	73.70 ± 0.44

embedding models is more critical than much larger amount of generic protein sequences.

In the field of natural language processing, Transformer-based models have been bolstered as the superior embedding model [14, 15, 19]. However, for TCR-related downstream tasks, `catELMo` using biLSTM layer-based design outperforms BERT using Transformer layers (see Section 2.4). While it is difficult to pinpoint the reasons, the bi-directional architecture to predict the next token based on its previous tokens in ELMo may mimic the interaction process of TCR and epitope sequences either from left to right or from right to left. In contrast, BERT uses Transformer encoder layers that attend tokens both on the left and right to predict a masked token, refer to as masked language modeling. As the Transformer layer can be along with the next token prediction objectives, it remains as a future work to investigate Transformer with causal language models, such as GPT-3 [14], for amino acid embedding. Additionally, the clear differences of TCR sequences compared to natural languages are 1) the compact vocabulary size (20 standard amino acids vs. over 170k English words) and 2) the length of peptides in TCRs being smaller than the number of words in sentences or paragraphs in natural languages. These differences may allow `catELMo` to learn sequential dependence without losing long-term memory from the left end.

Often in classification problems in life sciences, the difference in the number of available positive and negative data can be very large and TCR-epitope binding affinity prediction problem is no exception. In fact, the number of experimentally generated non-binding pairs are practically non-existent and obtaining experimental negative data is costly [17]. This requires researchers to come up with a strategy to generate negative samples and it can be non-trivial. A common practice is to sample new TCRs from repertoires and pair them with existing epitopes [9, 39], a strategy we also used. Another approach is to randomly shuffle TCR-epitope pairs within positive binding dataset, resulting in TCRs and epitopes that are not known to bind paired together [10, 11]. The prediction model consistently outperformed the other embedding

methods by large margins in both TCR and epitope splits as shown in Supplementary Fig 4. The model using `catELMo` achieves 24% and 36% higher AUCs over the second best embedding method for TCR (p-value $< 1.04 \times 10^{-18}$, Supplementary Table 1) and epitope (p-value $< 6.26 \times 10^{-14}$, Supplementary Table 2) split, respectively. Moreover, we observe that using `catELMo` embeddings, prediction models that are trained with only 2% downstream samples still statistically outperform ones that are built on a full size of BLOSUM62 embeddings in TCR split (p-value = 0.0005). Similarly, with only 1% training samples, `catELMo` reaches comparable results as BLOSUM62 with a full size of downstream samples in epitope split (p-value = 0.1438). In other words, `catELMo` dramatically reduces about 98% annotation cost (Supplementary Table 3). This confirms that the embeddings from `catELMo` maintain high performance regardless of the methodology used to generate negative samples.

Parameter fine-tuning in neural networks is a training scheme where initial weights of the network are set to the weights of a pre-trained network. Fine-tuning has been shown to bring performance gain to the model over using random initial weights [40]. We investigated the possibility of performance boost of our prediction model using fine-tuned `catELMo`. Since SeqVec shares the same architecture with `catELMo`-Shallow and is trained on generic protein sequences, we used the weights of SeqVec as initial weights when fine-turning `catELMo`-Shallow. We compared the performance of binding affinity prediction models using the fine-tuned `catELMo`-Shallow and vanilla `catELMo`-Shallow (trained from scratch with random initial weights from a standard normal distribution). We observed that the performance when using fine-tuned `catELMo`-Shallow embeddings was significantly improved by approximately 2 points AUCs in TCR split (p-value $< 4.17 \times 10^{-9}$) and 9 points AUCs in epitope split (p-value $< 5.46 \times 10^{-7}$).

For fair comparison purposes, when predicting the binding affinity of TCR-epitope pairs, we ensured that the same embedding model is applied to both TCR and epitope sequences in one single prediction model. However, we have observed improved performance when using `catELMo` to embed TCRs only and using the widely-used BLOSUM62 matrix to embed epitope sequences. This suggests that an embedding model specifically designed for epitope may further enhance the prediction performance (Supplementary Table 4). However, training a robust language model for amino acid sequences typically requires a large amount of data, as noted in previous studies [26, 27]. Less than 13k unique linear epitope records were found under the following filtering conditions [34]: T cell assay performed with restricted to human host MHC Class I. This amount of publicly available linear epitope sequences, however, is very limited compared to TCR repertoires,

 which presents a challenge in training a large embedding model for epitope sequences.

4 Methods

We first present data used for training the amino acid embedding models and the downstream tasks. We then review existing amino acid embedding methods and their usage on TCR-related tasks. We introduce our approach, `catELMo`, a bi-directional amino acid embedding method that computes contextual representation vectors of amino acids of a TCR (or epitope) sequence. We describe in detail how to apply `catELMo` to two different TCR-related downstream tasks. Lastly, we provide details on the experimental design, including the methods and parameters used in comparison and ablation studies.

4.1 Data

TCRs for training `catELMo`: We collected 5,893,249 TCR sequences from repertoires of seven projects in the ImmunoSEQ database: HIV [41], SARS-CoV2 [23], Epstein Barr Virus [42], Human Cytomegalovirus [43], Influenza A [44], Mycobacterium Tuberculosis [45], and Cancer Neoantigens [46]. CDR3 sequences of TCRβ chains were used to train the amino acid embedding models as those are the major segment interacting with epitopes [2] and exist in large numbers. We excluded duplicated copies and sequences containing wildcards such as '*' or 'X'. Altogether, we obtained 4,173,895 TCR sequences (52,546,029 amino acid tokens) of which 85% were used for training and 15% were used for testing.

TCR-epitope pairs for binding affinity prediction: We collected TCR-epitope pairs known to bind each other from three publicly available databases: IEDB [34], VDJdb [33], and McPAS [30]. Unlike the (unlabeled) TCR dataset for `catELMo` training, each TCR is annotated with an epitope known to bind each other, which we referred to as a TCR-epitope pair. We only used pairs with human MHC class I epitopes and CDR3 sequences of the TCRβ chain. We further filtered out sequences containing wildcards such as '*' or 'X'. For VDJdb, we excluded pairs with a confidence score of 0 as it means a critical aspect of sequencing or specificity validation is missing. We removed duplicated copies and merged datasets collected from the three databases. Altogether, we obtained 150,008 unique TCR-epitope pairs known to bind to each other having 140,675 unique TCRs and 982 unique epitopes. We then generated the same number of non-binding TCR-epitope pairs as negative samples by randomly pairing each epitope of the positive pairs

with a TCR sampled from the healthy TCR repertoires of ImmunoSEQ. We note that it includes no identical TCR sequences with the TCRs used for training the embedding models. Altogether, we obtained 300,016 TCR-epitope pairs where 150,008 pairs are positive and 150,008 pairs are negative.

TCRs for antigen-specific TCR clustering: We collected 9,822 unique TCR sequences of humans and mice hosts from McPAS [30]. Each TCR is annotated with an epitope known to bind, which is used as a ground-truth label for TCR clustering. We excluded TCR sequences that bind to neoantigen pathogens or multiple epitopes and only used CDR3 sequences of TCRβ chain. We composed three subsets for different experimental purposes. The first dataset contains both human and mice TCRs. We used TCRs associated with the top eight frequent epitopes, resulting in 5,607 unique TCRs. The second dataset consists of only human TCRs, and the third dataset consists of only mouse TCRs. In a similar manner, we selected TCRs that bind to the top eight frequent epitopes. As a result, we obtained 5,528 unique TCR sequences for the second dataset and 1,322 unique TCR sequences for the third dataset.

4.2 Amino acid embedding methods

In this section, we review amino acid embedding methods previously proposed. There are two categories of the existing approaches: static and context-aware embedding methods. Static embedding method represents an amino acid as a static representation vector remaining the same regardless of its context. Context-aware embedding method, however, represents an amino acid differently in accordance with its context. Context-aware embedding is also called dynamic embedding in contrast to static embedding. We explain the key ideas of various embedding methods, and introduce their usage in previous works.

4.2.1 Static embeddings

BLOSUM BLOSUM [16] is a scoring matrix where each element represents how likely an amino acid residue is to be substituted by another over evolutionary time. It has been commonly used to measure alignment scores between two protein sequences. There are various BLOSUM matrices such as BLOSUM45, BLOSUM62, and BLOSUM80 where a matrix with a higher number is used for the alignment of less divergent sequences. BLOSUM have also served as the de facto standard embedding method for various TCR analyses. For example, BLOSUM62 was used to embed TCR and epitope sequences for training deep neural network models predicting their binding affinity [7, 9, 17]. BLOSUM62 was also used to embed

TCR sequences for antigen-specific TCR clustering and TCR repertoire clustering. GIANA [38] clustered TCRs based on the Euclidean distance between TCR embeddings. TCRdist [37] used BLOSUM62 matrix to compute the dissimilarity matrix between TCR sequences for clustering.

Word2vec and Doc2vec   Word2vec [20] and Doc2vec [21] are a family of embedding models to learn a single linear mapping of words, which takes a one-hot word indicator vector as input and returns a real-valued word representation vector as output. There are two types of Word2vec architectures: continuous bag-of-words (CBOW) and skip-gram. CBOW predicts a word from its surrounding words in a sentence. It embeds each input word via a linear map, sums all input words' representations, and applies a softmax layer to predict an output word. Once training is completed, the linear mapping is used to obtain a representation vector of a word. On the contrary, skip-gram predicts the surrounding words given a word while it also uses a linear mapping to obtain a representation vector. Doc2vec is a model further generalized from Word2vec, which introduces a paragraph vector representing paragraph identity as an additional input. Doc2vec also has two types of architectures: distributed memory (DM) and distributed bag-of-words (DBOW). DM predicts a word from its surrounding words and the paragraph vector, while DBOW uses the paragraph vector to predict randomly sampled context words. In a similar way, linear mapping is used to obtain a continuous representation vector of a word.

Several studies adapted Word2vec and Doc2vec to embed amino acid sequences [24, 47, 25]. ProtVec [24] is the first Word2vec representation model trained on a large number of amino acid sequences. Its embeddings were used for several downstream tasks such as protein family classification, disordered protein visualization, and classification. Kimothi et al. [47] adapted Doc2vec to embed amino acid sequences for protein sequence classification and retrieval. Yang et al. [25] trained Doc2vec models on 524,529 protein sequences of UniProt [22] database. They considered a k-mer amino acids as a word, and a protein sequence as a paragraph. They trained DM models to predict a word from w surrounding words and a paragraph with various sizes of k and w.

4.2.2   Context-aware embeddings

ELMo   ELMo [18] is a deep context-aware word embedding model trained on a large corpus. It learns each token's (e.g., a word) contextual representation in forward and backward directions using a stack of two bi-directional LSTM layers. Each word of a text string is first mapped into a numerical representation

vector via the character-level convolutional layers. The forward (left-to-right) pass learns a token's contextual representation depending on itself and the previous context in which it is used. The backward (left-to-right) pass learns a token's representation depending on itself and its subsequent context.

ELMo is less commonly implemented for amino acid embedding than Transformer-based deep neural networks. One example is SeqVec [26]. It is an amino acid embedding model using ELMo's architecture. It feeds each amino acid as a training token of size 1, and learns its contextual representation both forward and backward within a protein sequence. The data was collected from UniRef50 [48], which consists of 9 billion amino acid tokens and 33 million protein sequences. SeqVec was applied to several protein-related downstream tasks such as secondary structure and long intrinsic disorder prediction, and subcellular localization.

BERT   BERT [19] is a large language model leveraging Transformer [49] layers to learn context-aware word embeddings jointly conditioned on both directions. BERT is learned for two objectives. One is the masked language model to learn contextual relationships between words in a sentence. It aims to predict the original value of masked words. The other is the next sentence prediction which aims to learn the dependency between consecutive sentences. It feeds a pair of sentences as input and predicts whether the first sentence in the pair is contextually followed by the second sentence.

BERT's architecture has been used in several amino acid embedding methods [27, 50, 29]. They treated an amino acid residue as a word and a protein sequence as a sentence. ProtBert [27] was trained on 216 million protein sequences (88 billion amino acid tokens) of UniRef100 [48]. It was applied for several protein sequence applications such as secondary structure prediction and sub-cellular localization. ProteinBert [50] combined language modeling and gene ontology annotation prediction together during training. It was applied to protein secondary structure, remote homology, fluorescence and stability prediction. TCRBert [29] was trained on 47,040 TCRβ and 4,607 TCRα sequences of PIRD [51] dataset and evaluated on TCR-antigen binding prediction and TCR engineering tasks.

4.3   Our approach: `catELMo`

We propose `catELMo`, a bi-directional amino acid embedding model designed for TCR analysis. `catELMo` adapts ELMo's architecture to learn context-aware representations of amino acids. It is trained on TCR sequences,

which is different from the existing amino acid embedding models such as SeqVec trained on generic protein sequences. As illustrated in Fig. 1a, catELMo is composed of a character CNN (CharCNN) [52] layer converting each one-hot encoded amino acid token to a continuous representation vector, a stack of four bi-directional LSTM [53] layers learning contextual relationship between amino acid residues, and a softmax layer predicting the next (or previous) amino acid residue.

Given a sequence of N amino acid tokens, $(t_1, t_2, ..., t_N)$, CharCNN maps each one-hot encoded amino acid token t_k to a latent vector c_k through seven convolutional layers with kernel sizes ranging from 1 to 7, and the numbers of filters of 32, 32, 64, 128, 256, 512, and 1,024, each of which is followed by a max-pooling layer, resulting in a 1,024-dimensional vector. The output of the CharCNN, $(c_1, c_2, ..., c_N)$, is then fed into a stack of four bidirectional LSTM layers consisting of forward and backward passes. For the forward pass, the sequence of the CharCNN output is fed into the first forward LSTM layer followed by the second forward LSTM layer, and so on. Each LSTM cell in every forward layer has 4,096 hidden states and returns a 512-dimensional representation vector. Each output vector of the last LSTM layer is then fed into a softmax layer to predict the right next amino acid token. Residual connection is applied between the first and second layers and between the third and fourth layers to prevent gradient vanishing. Similarly, the sequence of the CharCNN output is fed into the backward pass, in which each cell returns a 512-dimensional representation vector. Unlike the forward layer, each output vector of the backward layer followed by a softmax layer aims to predict the left next amino acid token.

Through the forward and backward passes, catELMo models the joint probability of a sequence of amino acid tokens. The forward pass aims to predict the next right amino acid token given its left previous tokens, which is $P(t_k|t_1, t_2, ..., t_{k-1}; \theta_c, \theta_{fw}, \theta_s)$ for each k-th cell where θ_c indicates parameters of CharCNN, θ_{fw} indicates parameters of the forward layers, and θ_s indicates parameters of the softmax layer. The joint probability of all amino acid tokens for the forward pass is defined as:

$$P(t_1, t_2, ..., t_N; \theta_c, \theta_{fw}, \theta_s) = \prod_{k=1}^{N} P(t_k|t_1, t_2, ..., t_{k-1}; \theta_c, \theta_{fw}, \theta_s)$$

The backward pass aims to predict the next left amino acid token given its right previous tokens. Similarly,

the joint probability of all amino acid tokens for the backward pass is defined as:

$$P(t_1, t_2, ..., t_N; \theta_c, \theta_{bw}, \theta_s) = \prod_{k=1}^{N} P(t_k | t_{k+1}, t_{k+2}, ..., t_N; \theta_c, \theta_{bw}, \theta_s)$$

where θ_{bw} indicates parameters of the backward layers. During `catELMo` training, the combined log-likelihood of the forward and backward passes is jointly optimized, which is defined as:

$$\sum_{k=1}^{N} [logP(t_k | t_1, t_2, ..., t_{k-1}; \theta_c, \theta_{fw}, \theta_s) + logP(t_k | t_{k+1}, t_{k+2}, ..., t_N; \theta_c, \theta_{bw}, \theta_s)]$$

Note that the forward and backward layers have their own weights (θ_{fw} and θ_{bw}). This helps to avoid information leakage that a token used to predict its right tokens in forward layers is undesirably used again to predict its own status in backward layers.

For each amino acid residue, `catELMo` computes five representation vectors of length 1,024: one from CharCNN and four from BiLSTM layers. Those vectors are averaged over and yield an amino acid representation vector of length 1,024. A sequence of amino acids is then represented by an element-wise average of all amino acids' representation vectors, resulting in a representation vector of length 1,024. For example, `catELMo` computes a representation for each amino acid in a TCR sequence $CASSPTSGGQETQYF$ as a vector of length 1,024. The sequence is then represented by averaging over 15 amino acid representation vectors, which is a vector with a length of 1,024. `catELMo` is trained up to 10 epochs with a batch size of 128 on two NVIDIA RTX 2080 GPUs. We follow the default experimental settings of ELMo unless otherwise specified.

4.4 Downstream tasks

We evaluate the amino acid embedding models' generalization performance on two downstream tasks: TCR-epitope binding affinity prediction and epitope-specific TCR clustering.

4.4.1 TCR-epitope binding affinity prediction

Computational approaches that predict TCR-epitope binding affinity benefit rapid TCR screening for a target antigen and improve personalized immunotherapy. Recent computational studies [7, 9, 10, 17] formulated it as a binary classification problem that predicts a binding affinity score (0–1) given a pair of TCR and epitope

sequences.

We evaluate `catELMo` based on the prediction performance of a binding affinity prediction model trained on its embedding, and compare it with the state-of-the-art amino acid embeddings (further demonstrated in Section 4.5). We first obtain different types of TCR and epitope embeddings from `catELMo` and the comparison methods. To measure the generalized prediction performance of binding affinity prediction models, we split each method's dataset into training (64%), validation (16%), and testing (20%) sets. We use two splitting strategies established in the previous work [10]: TCR split and epitope split. TCR split was designed to measure the models' prediction performance on out-of-sample TCRs where no TCRs in the testing set exist in the training and validation set. Epitope split was designed to measure the models' prediction performance on out-of-sample epitopes where no epitopes in the testing set exist in the training and validation set.

The downstream model architecture is the same across all embedding methods, having three linear layers where the last layer returns a binding affinity score (Fig. 1b). Taking `catELMo` as an example, we first obtain a `catELMo` representation of length 1,024 for each sequence. We then feed the TCR representation to a linear layer with 2,048 neurons, followed by a Sigmoid Linear Units (SiLU) activation function [54], batch normalization [55], and 0.3 rate dropout [56]. Similarly, we feed the epitope representation to another linear layer with 2,048 neurons, followed by the same layers. The outputs of TCR and epitope layers are then concatenated (4,096 neurons) and passed into a linear layer with 1,024 neurons, followed by a SiLU activation function, batch normalization, and 0.3 rate dropout. Finally, we append the last linear layer with a neuron followed by a sigmoid activation function to obtain the binding affinity score ranging from 0 to 1. The models are trained to minimize a binary cross-entropy loss via Adam optimizer [57]. We set the batch size as 32 and the learning rate as 0.001. We stop the training if either the validation loss does not decrease for 30 consecutive epochs or it iterates over 200 epochs. Finally, we compare and report AUC scores of binding affinity prediction models of the different embedding methods.

4.4.2 Epitope-specific TCR clustering

Clustering TCRs is the first and fundamental step in TCR repertoire analysis as it can potentially identify TCR clonotypes that are condition-specific [36, 37]. We perform hierarchical clustering [31] to `catELMo` and the state-of-the-art amino acid embeddings (further demonstrated in Section 4.5). We also obtain clusters

from the existing TCR clustering approaches (TCRdist and GIANA). Both methods are developed on the BLOSUM62 matrix and apply nearest neighbor search to cluster TCR sequences. GIANA used the CDR3 of TCRβ chain and V gene, while TCRdist predominantly experimented with CDR1, CDR2, and CDR3 from both TCRα and TCRβ chains. We evaluate the identified clusters of each method against the ground-truth TCR groups labeled by their binding epitopes.

We first obtain different types of TCR embeddings from `catELMo` and the comparison methods. All embedding methods except BLOSUM62 yield the same size representation vectors regardless of TCR length. For BLOSUM62 embedding, we pad the sequences so that all sequences are mapped to the same size vectors (further demonstrated in Section 4.5). We then perform hierarchical clustering on TCR embeddings of each method. In detail, the clustering algorithm starts with each TCR as a cluster with size 1. It repeatedly merges the closest two clusters based on the Euclidean distance between TCR embeddings until it reaches the target number of clusters.

We compare the normalized mutual information (NMI) between the identified cluster and the ground-truth. NMI is a harmonic mean between homogeneity and completeness. Homogeneity measures how many TCRs in a cluster bind to the same epitope, while completeness measures how many TCRs binding to the same epitope are clustered together. A higher value indicates a better clustering result. It ranges from zero to one where zero indicates no mutual information found between the identified clusters and the ground-truth clusters and one indicates a perfect correlation.

4.5 Comparison studies

We demonstrate how we implement existing amino acid embedding methods to compare with `catELMo` for the two TCR-related downstream tasks.

BLOSUM62. Among various typs of BLOSUM matrices, we use BLOSUM62 as it has been widely used in many TCR-related models [7, 9, 11, 17, 37, 38]. We obtain embeddings by mapping each amino acid to a vector of length 24 via BLOSUM62 matrix. Since TCRs (or epitopes) have varied lengths of the sequences, we pad each sequence using IMGT [58] method. If a TCR sequence is shorter than the predefined length 20 (or 22 for epitopes) [10], we add zero-padding to the middle of the sequence. Otherwise, we remove amino acids from the middle of the sequence until it reaches the target length. For each TCR, we flatten 20 amino

acid embedding vectors of length 24 into a vector of length 480. For each epitope, we flatten 22 amino acid embedding vectors of length 24 into a vector of length 528.

Yang et al. We select the 3-mer model with a window size of 5 to embed TCR and epitope sequences, which is the best combination obtained from a grid search. Each 3-mer is embedded as a numeric vector of length 64. The vectors are averaged to represent a whole sequence, resulting in a vector of length 64.

SeqVec and ProtBert. We embed each amino acid as a numeric vector of length 1,024. The vectors are element-wisely averaged to represent a whole sequence, resulting in a vector of length 1,024.

TCRBert. We embed each amino acid as a numeric vector of length 768. The vectors are element-wisely averaged to represent a whole sequence with a vector of length 768.

4.6   Ablation studies

We provide details of our experimental design and ablation studies.

4.6.1   Depth of `catELMo`

We investigate the effect of various depths of `catELMo` on TCR-epitope binding affinity prediction performance. We compare `catELMo` with different numbers of BiLSTM layers, specifically `catELMo`-Shallow, `catELMo`, and `catELMo`-Deep with 2, 4 and 8 layers respectively. Other hyperparameters and the training strategy remained the same as described in Section 4.3. For each amino acid residue, we average the output vectors of CharCNN and four (or two, eight) BiLSTM, resulting in a numerical vector of length 1,024. We then element-wisely average over all amino acids' representations to represent a whole sequence, resulting in a numerical vector of length 1,024. Embeddings from various depths are used to train binding affinity prediction models, resulting in three sets of downstream models. All settings of the downstream models remain the same as described in Section 4.4.1. The downstream models' prediction performance is compared to investigate the optimal depth of `catELMo`.

4.6.2 Neural architecture of `catELMo`

We compare `catELMo` with BERT-based amino acid embedding models using another context-aware architecture, Transformer, which has shown outstanding performance in natural language processing tasks. We train different sizes of BERT, a widely used Transformer-based model, for amino acid embedding, named BERT-Base-TCR, BERT-Tiny-TCR, and BERT-Large-TCR. Each model has 2, 12, and 30 Transformer layers and returns 768, 768, and 1024 sizes of embeddings for each amino acid token. Their objectives, however, only consist of the masked language prediction and do not include the next sentence prediction. For each TCR sequence, 15% of amino acid tokens are masked out and the model is trained to recover the masked tokens based on the remaining ones. The models are trained on the same training set as `catELMo` for 10 epochs. Other parameter settings are the same as TCRBert, which is included as one of the comparison models. All other settings remain the same as described in Section 4.4.1. TCRBert and BERT-Base-TCR share the same architecture, whereas TCRBert is trained on fewer training samples (PIRD). The embedding of a whole TCR sequence is obtained by average pooling over all amino acid representations. Embeddings from each model are used to train binding affinity prediction models, resulting in three sets of downstream models. The prediction performance of the downstream prediction models is compared to evaluate the architecture of `catELMo`.

4.6.3 Size of downstream data

We investigate how much downstream data `catELMo` can save in training a binding affinity prediction model while achieving the same performance with a model trained on a full size of data. We train the same model on different portion of `catELMo` embedding dataset. In detail, we randomly select $k\%$ of binding and $k\%$ of non-binding TCR-epitope pairs from training (and validation) data ($k = 1, 2, \cdots, 10, 20, \cdots, 100$), obtain `catELMo` embeddings for those, and feed them to train TCR-epitope binding affinity prediction models. Note that the TCR-epitope binding affinity prediction models in this experiment differ only in the number of training and validation pairs, meaning that the same testing set is used for different ks. We run ten times of experiments for each k and report their average and standard deviation of AUC, recall, precision, and F1 scores. We compare their performance to those trained on a full size of the other embedding datasets. For a more detailed investigation, we also perform the same experiment on BLOSUM62 embeddings and compare it with ours.

Data availability

Datasets used in downstream tasks and embedding models are described in detail in Section 4.1. Those datasets have been combined and summarized by us and are accessible at https://github.com/Lee-CBG/catELMo/tree/main/datasets.

Code availability

The implementation of `catELMo` as well as all of our trained embedding models are publicly available at https://github.com/Lee-CBG/catELMo.

Authors' contributions

HL conceived the idea for the overall project. PZ, SB and HL designed the method and wrote the manuscript. PZ carried out the experiments. MC collected data and participated in project discussions.

Ethics declarations

The authors declare no competing interests.

References

[1] Attaf M, Legut M, Cole DK, Sewell AK. The T cell antigen receptor: the Swiss army knife of the immune system. Clinical & Experimental Immunology. 2015;181(1):1-18.

[2] Davis MM, Bjorkman PJ. T-cell antigen receptor genes and T-cell recognition. Nature. 1988;334(6181):395-402.

[3] Krogsgaard M, Davis MM. How T cells 'see' antigen. Nature Immunology. 2005;6(3):239-45.

[4] Sbai H, Mehta A, DeGroot A. Use of T cell epitopes for vaccine development. Current drug targets-Infectious disorders. 2001;1(3):303-13.

[5] Schumacher TN. T-cell-receptor gene therapy. Nature Reviews Immunology. 2002;2(7):512-9.

[6] Sewell AK. Why must T cells be cross-reactive? Nature Reviews Immunology. 2012;12(9):669-77.

[7] Springer I, Besser H, Tickotsky-Moskovitz N, Dvorkin S, Louzoun Y. Prediction of specific TCR-peptide binding from large dictionaries of TCR-peptide pairs. Frontiers in immunology. 2020:1803.

[8] Jokinen E, Huuhtanen J, Mustjoki S, Heinonen M, Lähdesmäki H. Predicting recognition between T cell receptors and epitopes with TCRGP. PLoS computational biology. 2021;17(3):e1008814.

[9] Jurtz VI, Jessen LE, Bentzen AK, Jespersen MC, Mahajan S, Vita R, et al. NetTCR: sequence-based prediction of TCR binding to peptide-MHC complexes using convolutional neural networks. BioRxiv. 2018:433706.

[10] Cai M, Bang S, Zhang P, Lee H. ATM-TCR: TCR-epitope binding affinity prediction using a multi-head self-attention model. Frontiers in immunology. 2022;13.

[11] Weber A, Born J, Rodriguez Martínez M. TITAN: T-cell receptor specificity prediction with bimodal attention networks. Bioinformatics. 2021;37:i237-44.

[12] Lu T, Zhang Z, Zhu J, Wang Y, Jiang P, Xiao X, et al. Deep learning-based prediction of the T cell receptor–antigen binding specificity. Nature Machine Intelligence. 2021;3(10):864-75.

[13] Moris P, De Pauw J, Postovskaya A, Gielis S, De Neuter N, Bittremieux W, et al. Current challenges for unseen-epitope TCR interaction prediction and a new perspective derived from image classification. Briefings in Bioinformatics. 2021;22(4):bbaa318.

[14] Brown T, Mann B, Ryder N, Subbiah M, Kaplan JD, Dhariwal P, et al. Language models are few-shot learners. Advances in Neural Information Processing Systems. 2020;33:1877-901.

[15] Raffel C, Shazeer N, Roberts A, Lee K, Narang S, Matena M, et al. Exploring the limits of transfer learning with a unified text-to-text transformer. Journal of Machine Learning Research. 2020;21(140):1-67.

[16] Henikoff S, Henikoff JG. Amino acid substitution matrices from protein blocks. Proceedings of the National Academy of Sciences. 1992;89(22):10915-9.

[17] Montemurro A, Schuster V, Povlsen HR, Bentzen AK, Jurtz V, Chronister WD, et al. NetTCR-2.0 enables accurate prediction of TCR-peptide binding by using paired TCRα and β sequence data. Communications biology. 2021;4(1):1-13.

[18] Peters ME, Neumann M, Iyyer M, Gardner M, Clark C, Lee K, et al. Deep Contextualized Word Representations. Association for Computational Linguistics; 2018. p. 2227-37.

[19] Devlin J, Chang MW, Lee K, Toutanova K. Bert: Pre-training of deep bidirectional transformers for language understanding. Association for Computational Linguistics; 2019. p. 4171-86.

[20] Mikolov T, Chen K, Corrado G, Dean J. Efficient Estimation of Word Representations in Vector Space. International Conference on Learning Representations, Workshop Track Proceedings; 2013. .

[21] Le Q, Mikolov T. Distributed representations of sentences and documents. PMLR. International conference on machine learning; 2014. p. 1188-96.

[22] Apweiler R, Bairoch A, Wu CH, Barker WC, Boeckmann B, Ferro S, et al. UniProt: the universal protein knowledgebase. Nucleic acids research. 2004;32:D115-9.

[23] Nolan S, Vignali M, Klinger M, Dines JN, Kaplan IM, Svejnoha E, et al. A large-scale database of T-cell receptor beta (TCRβ) sequences and binding associations from natural and synthetic exposure to SARS-CoV-2. Research square. 2020.

[24] Asgari E, Mofrad MR. Continuous distributed representation of biological sequences for deep proteomics and genomics. PloS one. 2015;10(11):e0141287.

[25] Yang KK, Wu Z, Bedbrook CN, Arnold FH. Learned protein embeddings for machine learning. Bioinformatics. 2018;34(15):2642-8.

[26] Heinzinger M, Elnaggar A, Wang Y, Dallago C, Nechaev D, Matthes F, et al. Modeling aspects of the language of life through transfer-learning protein sequences. BMC bioinformatics. 2019;20(1):1-17.

[27] Elnaggar A, Heinzinger M, Dallago C, Rehawi G, Wang Y, Jones L, et al. ProtTrans: Towards cracking the language of lifes code through self-supervised deep learning and high performance computing. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2021:1-1.

[28] Lan Z, Chen M, Goodman S, Gimpel K, Sharma P, Soricut R. ALBERT: A lite BERT for self-supervised learning of language representations. 8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020; 2020. .

[29] Wu K, Yost KE, Daniel B, Belk JA, Xia Y, Egawa T, et al. TCR-BERT: learning the grammar of T-cell receptors for flexible antigen-xbinding analyses. bioRxiv. 2021.

[30] Tickotsky N, Sagiv T, Prilusky J, Shifrut E, Friedman N. McPAS-TCR: a manually curated catalogue of pathology-associated T cell receptor sequences. Bioinformatics. 2017;33(18):2924-9.

[31] Ward Jr JH. Hierarchical grouping to optimize an objective function. Journal of the American statistical association. 1963;58(301):236-44.

[32] Strehl A, Ghosh J. Cluster Ensembles—A knowledge reuse framework for combining multiple partitions. J Mach Learn Res. 2002;3(Dec):583-617.

[33] Shugay M, Bagaev DV, Zvyagin IV, Vroomans RM, Crawford JC, Dolton G, et al. VDJdb: a curated database of T-cell receptor sequences with known antigen specificity. Nucleic acids research. 2018;46(D1):D419-27.

[34] Vita R, Mahajan S, Overton JA, Dhanda SK, Martini S, Cantrell JR, et al. The immune epitope database (IEDB): 2018 update. Nucleic acids research. 2019;47(D1):D339-43.

[35] Van der Maaten L, Hinton G. Visualizing data using t-SNE. Journal of machine learning research. 2008;9(11).

[36] Purtic B, Pitcher LA, Van Oers NS, Wülfing C. T cell receptor (TCR) clustering in the immunological

synapse integrates TCR and costimulatory signaling in selected T cells. Proceedings of the National Academy of Sciences. 2005;102(8):2904-9.

[37] Dash P, Fiore-Gartland AJ, Hertz T, Wang GC, Sharma S, Souquette A, et al. Quantifiable predictive features define epitope-specific T cell receptor repertoires. Nature. 2017;547(7661):89-93.

[38] Zhang H, Zhan X, Li B. GIANA allows computationally-efficient TCR clustering and multi-disease repertoire classification by isometric transformation. Nature communications. 2021;12(1):1-11.

[39] Gielis S, Moris P, Bittremieux W, De Neuter N, Ogunjimi B, Laukens K, et al. Detection of enriched T cell epitope specificity in full T cell receptor sequence repertoires. Frontiers in immunology. 2019;10:2820.

[40] Yosinski J, Clune J, Bengio Y, Lipson H. How transferable are features in deep neural networks? Advances in Neural Information Processing Systems. 2014;27.

[41] Chan HY, Zhang J, Garliss CC, Kwaa AK, Blankson JN, Smith KN. T cell receptor sequencing-based assay identifies cross-reactive recall CD8+ T cell clonotypes against autologous HIV-1 epitope variants. Frontiers in immunology. 2020;11:591.

[42] Gil A, Kamga L, Chirravuri-Venkata R, Aslan N, Clark F, Ghersi D, et al. Epstein-barr virus epitope–major histocompatibility complex interaction combined with convergent recombination drives selection of diverse t cell receptor α and β repertoires. MBio. 2020;11(2):e00250-20.

[43] De Neuter N, Bartholomeus E, Elias G, Keersmaekers N, Suls A, Jansens H, et al. Memory CD4+ T cell receptor repertoire data mining as a tool for identifying cytomegalovirus serostatus. Genes & Immunity. 2019;20(3):255-60.

[44] Herati RS, Muselman A, Vella L, Bengsch B, Parkhouse K, Del Alcazar D, et al. Successive annual influenza vaccination induces a recurrent oligoclonotypic memory response in circulating T follicular helper cells. Science immunology. 2017;2(8):eaag2152.

[45] DeWitt WS, Yu KK, Wilburn DB, Sherwood A, Vignali M, Day CL, et al. A diverse lipid antigen-specific TCR repertoire is clonally expanded during active tuberculosis. The Journal of Immunology. 2018;201(3):888-96.

[46] Rajamanickam V, Ballesteros-Merino C, Samson K, Ross D, Bernard B, Fox BA, et al.. Treatment-induced immune cell priming as a potential explanation for an outstanding anti-tumor response in a patient with metastatic colorectal cancer; 2021. Available from: https://clients.adaptivebiotech.com/pub/cd09abd3-5c8b-465f-ae98-bf3f810b3229.

[47] Kimothi D, Soni A, Biyani P, Hogan JM. Distributed Representations for Biological Sequence Analysis. CoRR. 2016;abs/1608.05949.

[48] Suzek BE, Huang H, McGarvey P, Mazumder R, Wu CH. UniRef: comprehensive and non-redundant UniProt reference clusters. Bioinformatics. 2007;23(10):1282-8.

[49] Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al. Attention is all you need. Advances in neural information processing systems. 2017;30.

[50] Brandes N, Ofer D, Peleg Y, Rappoport N, Linial M. ProteinBERT: A universal deep-learning model of protein sequence and function. Bioinformatics. 2022;38(8):2102-10.

[51] Zhang W, Wang L, Liu K, Wei X, Yang K, Du W, et al. PIRD: pan immune repertoire database. Bioinformatics. 2020;36(3):897-903.

[52] Kim Y, Jernite Y, Sontag D, Rush AM. Character-aware neural language models. In: Thirtieth AAAI conference on artificial intelligence; 2016. .

[53] Hochreiter S, Schmidhuber J. Long short-term memory. Neural computation. 1997;9(8):1735-80.

[54] Elfwing S, Uchibe E, Doya K. Sigmoid-weighted linear units for neural network function approximation in reinforcement learning. Neural Networks. 2018;107:3-11.

[55] Ioffe S, Szegedy C. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In: International conference on machine learning. PMLR; 2015. p. 448-56.

[56] Srivastava N, Hinton G, Krizhevsky A, Sutskever I, Salakhutdinov R. Dropout: a simple way to prevent neural networks from overfitting. The journal of machine learning research. 2014;15(1):1929-58.

[57] Kingma DP, Ba J. Adam: A method for stochastic optimization. CoRR. 2014;abs/1412.6980.

[58] Lefranc MP, Pommié C, Kaas Q, Duprat E, Bosc N, Guiraudou D, et al. IMGT unique numbering for im-

680   munoglobulin and T cell receptor constant domains and Ig superfamily C-like domains. Developmental

681   & Comparative Immunology. 2005;29(3):185-203.

Supplementary Materials for Context-Aware Amino Acid Embedding Advances Analysis of TCR-Epitope Interactions

Pengfei Zhang, Seojin Bang, Michael Cai, and Heewook Lee

April 12, 2023

Figure 1. **Prediction performance of TCR-epitope binding affinity prediction models trained on different embedding methods**. The average and standard deviation (error bar) of 10 trials are reported. **a**) AUC, precision, recall, and F1 of TCR split, and **b**) epitope split.

Table 1. **TCR-epitope binding affinity prediction performance of TCR split where negative samples are generated by random shuffling.** Average and standard deviation of 10 trials are reported. P-values are from two-sample t-tests between `catELMo` and the second best method (underlined).

	AUC (%)	Precision (%)	Recall (%)	F1 (%)
BLOSUM62	73.95 ± 0.28	66.18 ± 0.96	66.97 ± 2.86	66.34 ± 0.24
Yang et al.	69.89 ± 0.19	62.54 ± 0.65	66.00 ± 2.08	63.24 ± 0.20
ProtBert	71.16 ± 0.20	63.69 ± 0.72	65.03 ± 2.68	63.90 ± 0.21
SeqVec	$\underline{86.66 \pm 0.22}$	$\underline{76.50 \pm 0.55}$	$\underline{79.48 \pm 1.27}$	$\underline{77.52 \pm 0.21}$
TCRBert	73.67 ± 0.24	64.29 ± 0.56	70.92 ± 1.26	65.65 ± 0.31
`catELMo` (ours)	$\mathbf{97.80 \pm 0.13}$	$\mathbf{91.98 \pm 0.65}$	$\mathbf{93.97 \pm 1.53}$	$\mathbf{92.88 \pm 0.49}$
p-value	1.04×10^{-18}	8.00×10^{-14}	1.77×10^{-11}	1.82×10^{-22}

Figure 2. **AUCs of the top 40 frequent out of sample epitopes in the binding affinity prediction task**.

Figure 3. **AUCs of TCR-epitope binding affinity prediction models trained on different portions of downstream datasets.**. The average and interval of 95% confidence (error band) of 10 trials are reported. **a**) AUC, precision, recall, and F1 of TCR split, and **b**) epitope split.

Figure 4. **Prediction performance of TCR-epitope binding affinity prediction models trained on different embeddings where negative samples are generated by random shuffling.** The average and standard deviation (error bar) of 10 trials are reported. **a**) AUC, precision, recall, and F1 of TCR split and **b**) epitope split.

Table 2. **TCR-epitope binding affinity prediction performance of epitope split where negative samples are generated by random shuffling.** Average and standard deviation of 10 trials are reported. P-values are from two-sample t-tests between `catELMo` and the second best method (underlined).

	AUC (%)	Precision (%)	Recall (%)	F1 (%)
BLOSUM62	50.76 ± 3.79	50.01 ± 2.54	47.47 ± 7.70	50.02 ± 2.49
Yang et al.	45.54 ± 3.13	46.11 ± 2.46	41.12 ± 6.25	46.38 ± 2.15
ProtBert	51.24 ± 2.85	50.39 ± 1.94	45.32 ± 4.31	50.18 ± 1.76
SeqVec	$\underline{57.89 \pm 2.42}$	$\underline{56.79 \pm 2.26}$	33.77 ± 9.09	$\underline{51.69 \pm 3.00}$
TCRBert	50.41 ± 2.59	49.71 ± 1.91	$\underline{48.00 \pm 5.08}$	49.69 ± 1.83
catELMo (ours)	$\mathbf{86.95 \pm 3.58}$	$\mathbf{83.16 \pm 2.82}$	$\mathbf{73.24 \pm 9.31}$	$\mathbf{79.03 \pm 4.36}$
p-value	6.26×10^{-14}	1.17×10^{-13}	2.85×10^{-6}	8.65×10^{-12}

Table 3. **AUCs of TCR-epitope binding affinity prediction model trained on different portions of downstream `catELMo` embeddings where negative samples are generated by random shuffling.** The average and standard deviation of 10 trials are reported.

Percentile of Training Samples Used	TCR Split (%)	Epitope Split (%)
1%	68.17 ± 0.60	51.14 ± 5.76
2%	75.11 ± 0.69	55.21 ± 6.09
3%	78.92 ± 0.63	58.06 ± 6.82
4%	81.99 ± 0.52	61.55 ± 6.18
5%	83.51 ± 0.73	63.34 ± 4.72
6%	85.19 ± 0.65	65.57 ± 5.91
7%	86.34 ± 0.55	67.38 ± 4.31
8%	87.38 ± 0.55	69.03 ± 5.57
9%	88.16 ± 0.46	70.14 ± 4.99
10%	88.56 ± 0.48	71.64 ± 4.09

Table 4. **AUCs of TCR-epitope binding affinity prediction models trained on `catELMo` and BLOSUM62 embeddings**. The average and standard deviation of 10 trials are reported.

TCR Embedding	Epitope Embedding	TCR Split (%)	Epitope Split (%)
catELMo	catELMo	96.04 ± 0.12	94.10 ± 0.90
catELMo	BLOSUM62	$\mathbf{96.30 \pm 0.15}$	$\mathbf{94.46 \pm 1.08}$