NEURAL BASIS OF SOUND-SYMBOLIC PSEUDOWORD-SHAPE CORRESPONDENCES

Deborah A. Barany[1], Simon Lacey[2,3,4], Kaitlyn L. Matthews[5], Lynne C. Nygaard[5] and K. Sathian[2,3,4]

[1]Department of Kinesiology, University of Georgia and Augusta University/University of Georgia Medical Partnership, Athens, GA, 30602, USA; Department of [2]Neurology, [3]Neural & Behavioral Sciences and [4]Psychology, Penn State Health Milton S. Hershey Medical Center and Penn State University, Hershey, PA 17033-0859, USA; [5]Department of Psychology, Emory University, Atlanta, GA 30322, USA

Corresponding author:
K. Sathian
Department of Neurology
Milton S. Hershey Medical Center
Penn State College of Medicine
Hershey, PA 17033-0859, USA
Tel: 717-531-1801
Fax: 717-531-0384
Email: ksathian@pennstatehealth.psu.edu

Highlights

- fMRI investigation of sound-symbolic correspondences between auditory pseudowords and visual shapes
- Faster reaction times for congruent than incongruent audiovisual stimuli
- Greater activation in premotor areas and anterior insula for incongruent stimuli
- Greater activation in primary auditory and somatosensory cortices for congruent stimuli
- Higher multivariate classification accuracy for congruent stimuli in language-related areas

ABSTRACT

Non-arbitrary mapping between the sound of a word and its meaning, termed sound symbolism, is commonly studied through correspondences between sounds and visual shapes, e.g., auditory pseudowords, like 'mohloh' and 'kehteh', are matched to rounded and pointed visual shapes, respectively. Here, we used functional magnetic resonance imaging (fMRI) to investigate the neural basis of the pseudoword-shape correspondence. During scanning, right-handed participants (n = 22) encountered audiovisual stimuli consisting of a simultaneously presented visual shape (rounded or pointed) and an auditory pseudoword ('mohloh' or 'kehteh') and indicated via a right-handed keypress whether the stimuli matched or not. Reaction times were faster for congruent than incongruent stimuli. On a univariate contrast between congruent and incongruent stimuli, activity was greater in the left primary auditory and somatosensory cortices, left anterior fusiform/parahippocampal and right mid-cingulate gyri, and caudate nuclei bilaterally for the congruent condition; and at left precentral, left supplementary motor and bilateral anterior insular cortical foci in the incongruent condition. Multivoxel pattern analysis revealed higher classification accuracy in the pars opercularis of the left inferior frontal gyrus (Broca's area), the left supramarginal gyrus, and the right mid-occipital gyrus for the audiovisual stimuli when bimodally congruent than when incongruent. Visual and auditory cortices robustly differentiated between the two visual/auditory stimuli, respectively, regardless of audiovisual congruency. Frontoparietal cortical regions distinguished congruent from incongruent stimulus pairs, independent of the visual or auditory features. Taken together, these findings indicate that sound-symbolic correspondences engage neural processes in sensory, motor, and language systems.

KEYWORDS: multisensory, sound symbolism, language, fMRI, multivoxel pattern analysis

INTRODUCTION

Sound symbolism refers to the idea that the sounds of a word resemble its meaning (Nuckolls, 1999). This idea dates back to Plato's Cratylus dialog (Ademollo, 2011), but has receded in modern times in favor of the mainstream view that sound-meaning associations are essentially arbitrary (e.g. Pinker, 1999). Recently, however, there has been a resurgence of interest in the phenomenon, fueled by the discovery of crossmodal correspondences between the sounds of words and (non-auditory) perceptual dimensions. For instance, auditory pseudowords such as 'takete' or 'kiki' are reliably matched with pointed visual shapes, whereas 'maluma' or 'bouba' are matched with rounded shapes (Köhler, 1929, 1947; Ramachandran & Hubbard, 2001). Further, the perceptual ratings of auditory pseudowords as rounded or pointed relate not only to phonological features (e.g., McCormick et al., 2015; Fort et al., 2015; Cuskley et al., 2017), but also to their acoustic properties, including spectrotemporal parameters of the pseudoword sounds and parameters of vocal roughness associated with sound production (Lacey et al., 2020).

Prior functional magnetic resonance imaging (fMRI) studies investigated the neural basis of sound symbolism using a variety of tasks across a few different semantic domains, without much consistency of findings. Revill et al. (2014) asked native English speakers to listen to words drawn from multiple foreign languages and match their meaning with one of a pair of antonyms spanning domains of motion, size and shape: activity was greater in the left intraparietal sulcus for words rated as sound-symbolic compared to those rated as non-sound-symbolic. Visually presented Japanese mimetic words for motion and shape, when they matched visual images of actions or shapes, evoked activity in the right posterior superior temporal sulcus (Kanero et al., 2014). Judging the size of visual objects during presentation of sound symbolically incongruent, relative to congruent, pseudowords led to greater activity in bilateral anterior cingulate cortex, the right anterior superior temporal gyrus, the left posterior middle temporal gyrus and the right lingual gyrus (Itagaki et al., 2019). Congruent tactile hard/soft stimuli and visually presented Japanese words that were sound-symbolic for hardness/softness, relative to incongruent stimulus pairs, led to activity in a number of areas including the anterior insula and medial superior frontal gyrus bilaterally; these regions also distinguished between congruent and incongruent stimuli on multivoxel pattern analyses (MVPA) (Kitada et al., 2021), however, the reported analyses did not explore whether individual stimuli could be distinguished.

Returning to the sound-symbolic shape domain, two previous studies measured fMRI activity while participants viewed concurrently presented auditory pseudowords and visual shapes. Peiffer-Smadja & Cohen (2019) reported greater BOLD activity for incongruent than congruent audiovisual pairs in the dorsolateral prefrontal cortex bilaterally in a task where participants were asked to detect occasional target stimuli unrelated to the pseudoword-shape correspondence of interest, possibly reflecting greater effort during processing of the incongruent stimuli. McCormick et al. (2022) found that sound symbolically incongruent stimulus pairs elicited a stronger BOLD response than congruent stimuli in the intraparietal sulcus and supramarginal gyrus bilaterally, and in the left middle frontal gyrus, when participants attended to the auditory input to distinguish between a rounded and a pointed pseudoword; these findings were thought

to be consistent with changes in phonological processing and/or multisensory attention as a function of sound-symbolic congruency (McCormick et al., 2022). In both these fMRI studies, audiovisual sound-symbolic congruency was processed implicitly, with the participants' attention directed either to a specific modality (McCormick et al., 2022) or to unrelated stimuli (Peiffer-Smadja & Cohen, 2019).

In the present fMRI study, we investigated the neural correlates of sound symbolism for shape when participants were asked to explicitly assess the sound-symbolic audiovisual pseudoword-shape correspondence. We reasoned that an explicit judgment task would lead to stronger congruency effects and potentially unmask effects favoring the congruent condition. As cited above, effects for congruent stimuli were not observed in two studies using implicit matching of auditory pseudowords and visual shape (Peiffer-Smadja & Cohen, 2019; McCormick et al., 2022), but did occur during explicit matching of visually presented words to visual or tactile stimuli (Kanero et al., 2014; Kitada et al., 2021). In addition to examining univariate BOLD effects under explicit task conditions, we also performed MVPA to identify regions sensitive to congruency. We hypothesized that classification accuracy for specific pseudoword-shape combinations would be higher in congruent than incongruent trials and that regions distinguishing between congruent and incongruent stimuli would be distinct from those differentiating between specific stimulus pairs. One obvious set of loci for congruency effects comprises areas involved in multisensory processing, including classical visual and auditory cortex. In view of the widespread nature of multisensory processing in the neocortex (Ghazanfar & Schroeder, 2006), these areas could mediate multisensory integration. In addition, findings implicating a role of sound symbolism in language structure and function, including the ubiquity of sound-symbolic associations across multiple languages (Blasi et al., 2016), the higher frequency of rounded (pointed) phonemes in words signifying rounded (pointed) objects (Sidhu et al., 2021), the facilitation of word learning by sound symbolism (Nygaard et al., 2009), and the relative advantage for onomatopoeic words in aphasia (Meteyard et al., 2015), lead to the prediction that congruency effects would be found in classical language areas. Finally, brain regions mediating motor control and related somatosensory processing are also candidate loci for congruency effects, given findings suggesting close relationships between articulatory and manual movements (Vainio & Vainio, 2021, 2022), and acoustic similarities between speech and action sounds (Margiotoudi & Pulvermüller, 2020).

METHODS
Participants
Twenty-four people took part in this study (14 female, 10 male; mean age = 22.6 years, SD = 3.8 years). All participants were right-handed based on the validated subset of the Edinburgh handedness inventory (Raczkowski et al., 1974) and reported normal hearing and normal, or corrected-to-normal, vision. All participants gave written informed consent and were compensated for their time. All procedures were approved by the Emory University Institutional Review Board and complied with the Declaration of Helsinki. Participants performed three scanning sessions; in the first two, auditory pseudowords and visual shapes were presented in separate sessions (which are the subject of a separate report), and the third comprised the

audiovisual task reported here. Two participants with poor behavioral performance (see *Multisensory fMRI task*) were excluded from further analyses.

Stimuli
We created sound-symbolic audiovisual stimuli, each consisting of an auditory pseudoword and a two-dimensional visual shape. Two auditory pseudowords ('mohloh' and 'kehteh') and two shapes (pointed and rounded) were chosen from large stimulus sets (McCormick et al., 2015, see below; McCormick, unpublished data, see below: Figure 1A). The pseudowords and shapes chosen were at the ends of independent rounded and pointed dimensions based on empirical ratings for 537 pseudowords (McCormick et al., 2015) and 90 visual shapes (McCormick, 2015, unpublished data). These independent rating scales were converted to a single scale on which 'most rounded' = 1 and 'most pointed' = 7; ratings for the pseudowords ranged from 2.3 – 5.8 (median 4.2) and for the shapes from 1.6 – 6.7 (median 4.4). 'Mohloh' was the 12[th] most rounded pseudoword, rated 2.8, but we used the 20th most pointed pseudoword, 'kehteh' (rated 5.4), in order to get the closest match in duration. We used the 10[th] most rounded visual shape, rated 2.3, and the 10[th] most pointed visual shape, rated 6.4, to match the number of protuberances (five) between the shapes. A more detailed analysis of the pseudowords and shapes can be found in Lacey et al. (2020) and the stimuli themselves are available at https://osf.io/ekpgh/.

The pseudowords were digitally recorded in a female voice using Audacity v2.0.1 (Audacity Team, 2012), with a SHURE 5115D microphone and an EMU 0202 USB external sound card, at a 44.1 kHz sampling rate. The recordings were then processed in Sound Studio (Felt Tip Inc., NY), using standard tools and default settings, edited into separate files, amplitude-normalized, and down-sampled to a 22.05 kHz sampling rate (standard for speech). Stimulus duration was 563 ms for 'mohloh' and 546 ms for 'kehteh', resulting in a difference in duration of 17ms or approximately 3%. Because sound segments in language naturally differ in duration, these differences were retained. The visual shapes were solid gray shapes on a black background, each subtending approximately 1° of visual angle and presented at the center of the screen for 500ms. Duration of visual shape presentation was not varied to match the accompanying pseudowords, to avoid having the shape duration vary as a function of congruency and thus introduce a confound.

Stimuli were presented concurrently in audiovisual pairs (Figure 1A) that were either congruent ('mohloh'/rounded shape or 'kehteh'/pointed shape) or incongruent ('kehteh'/rounded shape or 'mohloh'/pointed shape) with respect to the crossmodal pseudoword-shape (sound-symbolic) correspondence. Stimuli were delivered via MATLAB 2014b (The MathWorks Inc., Natick, MA) to synchronize delivery with fMRI acquisition and also record responses and reaction times (RTs). A mirror angled over the head coil enabled participants to see the visual stimuli projected onto a screen placed in the rear magnet aperture. Auditory stimuli were presented via scanner-compatible Sensimetrics S14 headphones (Sensimetrics Corporation, Gloucester MA).

Multisensory fMRI task
We used a jittered event-related design in which participants performed 12 runs of the audiovisual task. Each run consisted of 22 congruent trials and 22 incongruent trials, each

contained within the TR of 2 s (see Image acquisition, below: Figure 1B). Inter-trial intervals (ITIs), or null periods, ranged from 2 s to 30 s. We used optseq2 (https://surfer.nmr.mgh.harvard.edu/optseq/; Dale, 1999; Dale et al., 1999) to schedule trials and ITIs, in order to optimize the estimation of the hemodynamic response. Each run began and ended with a rest period of 10 s for a total run duration of 326 s. Pseudoword-shape pairs were presented in a fixed pseudorandom order within each run; the 12 run orders were counterbalanced across participants. Participants attended to each audiovisual stimulus pair and judged whether the pair was a match or a mismatch, pressing one of two buttons on a hand-held response box to indicate their response. Participants were free to make their own judgments of match/mismatch; they were not informed of our interest in studying sound symbolism. The right index and middle fingers were used to indicate match/mismatch responses, counterbalanced across subjects.

All participants, except two, judged the 'match' condition to be congruent pairs of stimuli and the 'mismatch' condition to be incongruent pairs of stimuli. These two participants responded with the opposite than expected mapping for at least one of the pseudoword-shape pairs, and their data were excluded from analysis.

Image acquisition

MR scans were performed on a 3 Tesla Siemens Trio TIM whole body scanner (Siemens Medical Solutions, Malvern, PA), using a 32-channel head coil. T2*-weighted functional images were acquired using a single-shot, gradient-recalled, echoplanar imaging (EPI) sequence for BOLD contrast. For functional scans, 34 axial slices of 3.1 mm thickness were acquired using the following parameters: repetition time (TR) 2000 ms, echo time (TE) 30 ms, field of view (FOV) 200 mm, flip angle (FA) 90°, in-plane resolution 3.125×3.125 mm, and in-plane matrix 64×64. High-resolution 3D T1-weighted (T1w) anatomic images were acquired using an MPRAGE sequence (TR 2300 ms, TE 3.9ms, inversion time 1100 ms, FA 8°) comprising 176 sagittal slices of 1 mm thickness (FOV 256 mm, in-plane resolution 1×1 mm, in-plane matrix 256×256). Once magnetic stabilization was achieved in each run, the scanner triggered the computer running MATLAB and the Psychophysics Toolbox extensions (Brainard, 1997; Pelli, 1997; Kleiner et al, 2007) so that the experiment was synchronized with scan acquisition.

Image preprocessing

Results included in this manuscript come from preprocessing performed using *fMRIPrep* version 20.0.6, (Esteban et al., 2019; Esteban et al., 2020; RRID:SCR_016216), which is based on *Nipype* 1.4.2 (Gorgolewski et al., 2011; RRID:SCR_002502). Many internal operations of *fMRIPrep* use *Nilearn* 0.6.2 (Abraham et al., 2014, RRID:SCR_001362], mostly within the functional processing workflow. For more details of the pipeline, see the section corresponding to workflows in *fMRIPrep*'s documentation (https://fmriprep.readthedocs.io/en/latest/workflows.html). The T1w image was corrected for intensity non-uniformity (INU) with N4BiasFieldCorrection (Tustison et al., 2010), distributed with ANTs 2.2.0 (Avants et al., 2008; RRID:SCR_004757), and used as the T1w-reference throughout the workflow. The T1w-reference was then skull-stripped with a *Nipype* implementation of the antsBrainExtraction.sh workflow (from ANTs), using OASIS30ANTs as the target template. Brain tissue segmentation of cerebrospinal fluid (CSF), white matter (WM)

and gray matter (GM) was performed on the brain-extracted T1w using `fast` (Zhang et al., 2001; FSL 6.0.3:b862cdd5, RRID:SCR_002823).

For each of the 12 BOLD runs per subject, the following preprocessing was performed. First, a reference volume and its skull-stripped version were generated using a customized implementation of *fMRIPrep*. Susceptibility distortion correction (SDC) was omitted. The BOLD reference was then co-registered to the T1w reference using `flirt` (FSL 6.0.3:b862cdd5, Jenkinson & Smith, 2001) with the boundary-based registration (Greve & Fischl, 2009) cost function. Co-registration was configured with nine degrees of freedom to account for distortions remaining in the BOLD reference. Head-motion parameters with respect to the BOLD reference (transformation matrices, and six corresponding rotation and translation parameters) were estimated before spatiotemporal filtering using mcflirt (FSL 6.0.3:b862cdd5, Jenkinson et al., 2002). BOLD runs were slice-time corrected using 3dTshift from AFNI 20190316 (Cox, 1996, RRID:SCR_005927). The BOLD time-series (including slice-timing correction when applied) were resampled onto their original, native space by applying the transforms to correct for head motion. These resampled BOLD time-series will be referred to as preprocessed BOLD in original space, or just preprocessed BOLD.

Several confounding time-series were calculated based on the preprocessed BOLD: framewise displacement (FD), the derivative of the root mean squared variance over voxels (DVARS), and three region-wise global signals. FD and DVARS were calculated for each functional run, using their implementations in *Nipype* (following the definitions by Power et al., 2014). The three global signals were extracted within the CSF, the WM, and the whole-brain masks. Additionally, a set of physiological regressors was extracted to allow for component-based noise correction (*CompCor*, Behzadi et al., 2007). Principal components were estimated after high-pass filtering the preprocessed BOLD time-series (using a discrete cosine filter with 128 s cut-off) for the two *CompCor* variants: temporal (tCompCor) and anatomical (aCompCor). tCompCor components were then calculated from the top 5% variable voxels within a mask covering the subcortical regions. This subcortical mask was obtained by heavily eroding the brain mask, which ensures it does not include cortical GM regions. For aCompCor, components were calculated within the intersection of the aforementioned mask and the union of CSF and WM masks calculated in T1w space, after their projection to the native space of each functional run (using the inverse BOLD-to-T1w transformation). Components were also calculated separately within the WM and CSF masks. For each CompCor decomposition, the *k* components with the largest singular values were retained, such that the retained components' time series were sufficient to explain 50 percent of variance across the nuisance mask (CSF, WM, combined, or temporal). The remaining components were dropped from consideration.

The head-motion estimates calculated in the correction step were also placed within the corresponding confounds file. The confound time series derived from head motion estimates and global signals were expanded with the inclusion of temporal derivatives and quadratic terms for each (Satterthwaite et al., 2013). Frames that exceeded a threshold of 0.5 mm FD or 1.5 standardised DVARS were annotated as motion outliers. All resamplings were performed with a single interpolation step by composing all the pertinent transformations (i.e. head-motion transform matrices, susceptibility distortion correction when available, and co-registrations to anatomical and output spaces). Gridded (volumetric) resamplings were performed using antsApplyTransforms (ANTs), configured with Lanczos interpolation to minimize the smoothing

effects of other kernels (Lanczos, 1964). Non-gridded (surface) resamplings were performed using `mri_vol2surf` (FreeSurfer).

fMRI data analysis
Statistical analyses of fMRI data were conducted using SPM12 (Wellcome Trust Center for Neuroimaging, London, UK) as implemented in *Nipype*. We used a standard General Linear Model (GLM) to estimate separate regressors (betas) for each of the four conditions in each run. Stimulus onsets were modeled as a boxcar function with duration equal to that trial's reaction time (Grinband et al., 2008) and convolved with the canonical hemodynamic response function. The six translation and rotation head-motion parameter estimates were included as additional regressors of no interest.

A univariate analysis was conducted by first smoothing the preprocessed BOLD signal in native space with an 8 mm full-width half-maximum (FWHM) isotropic Gaussian kernel prior to the first-level analysis. We then performed a linear contrast to evaluate the difference in BOLD activity between the congruent ('mohloh'/rounded shape or 'kehteh'/pointed shape) and incongruent ('kehteh'/rounded shape or 'mohloh'/pointed shape) conditions. The resulting individual contrast maps were normalized to MNI space and then submitted to a second-level analysis of group data with subject treated as a random factor (so that the degrees of freedom equal n-1, i.e., 21), followed by pairwise contrasts. An explicit mask based on a combined gray matter and white matter mask from segmentation of the T1w images was applied at the group level to isolate within-brain activations. Correction for multiple comparisons ($p < 0.05$) was achieved using the topological FDR correction method, using whole brain, activation clusters with cluster-forming threshold of $p < 0.001$ and FDR cluster-level correction of $p < 0.05$ (Chumbley et al., 2010).

Searchlight multivariate pattern analyses (MVPA) were performed using The Decoding Toolbox (TDT) in SPM (Hebart et al., 2015). The unsmoothed (Misaki et al., 2013) GLM run-wise beta estimates for each of the four conditions were first z-scored voxelwise and within each run to factor out univariate effects, avoid spurious correlations between mean estimates across runs, and improve classification accuracy (Lee & Kable, 2018). We implemented two types of cross-validated, leave-one-run-out searchlight decoding analyses using spherical searchlights with a 4-voxel radius and an L2-norm regularized support vector machine classifier with $C = 1$ from the LIBSVM package (Chang & Lin, 2011). For the *within-congruency classification*, the classifier was trained to discriminate between either the two congruent stimulus pairs (i.e., 'kehteh'/pointed shape vs. 'mohloh'/rounded shape) or the two incongruent ones (i.e., 'mohloh'/pointed shape vs. 'kehteh'/rounded shape) separately (Figure 1C). To directly test whether any region showed better decoding when the stimuli were congruent relative to when they were incongruent (or vice versa), we contrasted the individual classification accuracy maps for the congruent conditions with those for the incongruent conditions.

To test for specific patterns of brain activity related to congruency independent of sensory characteristics, we performed a *between-congruency classification* (Kaplan et al., 2015; Man et al., 2015). To decode the visual shapes, classifiers were trained to distinguish between two of the four conditions in which the visual shapes were different but the auditory pseudoword was the same (e.g., 'kehteh'/pointed shape vs. 'kehteh'/rounded shape: Figure 1D-Shape). The classifier was then tested on the two remaining conditions containing the other pseudoword

(e.g., 'mohloh'/pointed shape vs. 'mohloh'/rounded shape: Figure 1D-Shape). Regions that represent visual properties should show decoding of visual shape independent of the accompanying auditory pseudoword (e.g., similar patterns of activity for 'kehteh'/rounded shape and 'mohloh'/rounded shape). In contrast, in regions where responses are driven by the congruency of crossmodal correspondences (or the associated motor responses), we should be able to decode the congruency/incongruency of the stimuli (e.g., similar patterns of activity for 'kehteh'/pointed shape and 'mohloh'/rounded shape). Similarly, to decode congruency/incongruency across auditory features, we trained classifiers to distinguish between auditory pseudowords when the accompanying visual shape was held constant (e.g., 'kehteh'/pointed shape vs. 'mohloh'/pointed shape) and then tested on the two remaining conditions containing the other shape (e.g., 'kehteh'/rounded shape vs. 'mohloh'/rounded shape: Figure 1D-Pseudoword). As before, we should be able to differentiate regions where auditory features drive responses from regions that represent crossmodal congruency independent of the pseudoword presented.

For both the *within-* and *between-congruency* analyses, the individual classification accuracy searchlight maps were smoothed with a 4 mm full-width half-maximum (FWHM) isotropic Gaussian kernel and normalized to MNI space before second-level analysis of group data with subject as a random factor. All analyses included a combined GM/WM explicit mask to exclude non-brain voxels. For the *within-congruency* analysis comparing differences in classification accuracy for congruent > incongruent (incongruent > congruent), only voxels exhibiting above-chance classification of the congruent (incongruent) conditions at the group level were included. The group-level maps were corrected for multiple comparisons using the topological FDR correction method with cluster-forming threshold of $p < 0.001$ and FDR cluster-level correction of $p < 0.05$ (Chumbley et al., 2010).

All activations were localized with respect to 3D cortical anatomy with the AAL (Tzourio-Mazoyer et al., 2002; Rolls et al., 2015) and AICHA (Joliot et al., 2015) atlases; differences between the two were resolved by reference to an MRI atlas (Cho et al., 2010). Activation maps are overlaid on a group-averaged structural image normalized to MNI space.

RESULTS

Behavioral data

Table 1 shows the mean accuracy and RTs for each of the four conditions. Accuracy was not significantly different for congruent vs. incongruent trials ($t_{21} = 0.261$; $p = 0.797$; $d = 0.056$). RTs were faster when the pseudoword and shape were sound-symbolically congruent compared to when they were incongruent ($t_{21} = -5.374$; $p < 0.001$; $d = -1.15$).

fMRI univariate analyses

The contrast of congruent > incongruent conditions showed higher activation in the right, and near the left, caudate nucleus, as well as in the left anterior fusiform/parahippocampal, right mid-cingulate, left mid-superior temporal, and left postcentral gyri. The reverse contrast (incongruent > congruent) showed greater activation in the left precentral sulcus, left supplementary motor area (SMA), bilateral anterior insula, and right pons (Figure 2 and Table 2).

fMRI searchlight MVPA

Within-congruency classification

In separate decoding analyses of the congruent and incongruent conditions, a whole-brain searchlight analysis showed robust above-chance classification accuracy in visual and auditory cortices, reflecting distinct patterns for unique visual shapes and auditory pseudowords, respectively (Figure 3A; Table 3). The congruent conditions showed additional above-chance classification in the pars opercularis of the left inferior frontal gyrus (IFG), corresponding to Broca's area, and the left supplementary motor area. To test the hypothesis that decoding of shape and pseudowords would be better for congruent than incongruent trials, we contrasted the individual classification accuracy maps for the congruent condition with those for the incongruent condition. This contrast was restricted to those voxels that exhibited above-chance classification in the congruent condition. The resulting difference map revealed significantly higher above-chance classification in the congruent, compared to the incongruent, conditions in right mid-occipital cortex, Broca's area (left IFG, pars opercularis) and the left supramarginal gyrus (SMG) (Figure 3B; Table 4). Classification accuracies at the peak coordinate in the right mid-occipital cluster were above chance for both congruent and incongruent conditions, but significantly higher for the congruent condition, as revealed by the difference map, Figure 3C. (Note that the right mid-occipital cluster was part of a large swath of occipital (early visual) cortex with significant classifier accuracy in the congruent condition.) Classifier performance differences between congruent and incongruent conditions in Broca's area and the left SMG resulted from above-chance classification for the congruent, but not the incongruent, conditions (Figure 3C). No region showed significantly higher above-chance classification of the incongruent conditions after FDR-correction for multiple comparisons.

Between-congruency classification

A whole-brain searchlight analysis revealed distinct regions for processing of the visual shapes and auditory pseudowords, and for processing their crossmodal correspondences (Figure 4, Tables 5 and 6). When classifiers were trained to distinguish the two visual shapes, significant above-chance decoding of visual shape was restricted to visual cortical regions with peak local maxima in the lingual gyrus and calcarine sulcus, whereas decoding of crossmodal congruency (i.e. congruent vs. incongruent) was significantly above chance in multiple regions, including left precentral gyrus, bilateral superior frontal gyrus, right pallidum, right postcentral gyrus, left hippocampus, right superior parietal lobule, right middle frontal gyrus, left posterior cingulate gyrus, and right inferior frontal gyrus (Figure 4A, Table 5). A similar pattern of results was observed for classifiers trained to distinguish between the auditory pseudowords: only bilateral auditory cortex (with peak local maxima in the superior temporal sulcus/gyrus) displayed significant above-chance pseudoword decoding, whereas there was significant above-chance decoding of crossmodal congruency/incongruency in multiple bilateral parietofrontal and temporal regions, and on the right in the parahippocampal gyrus, cerebellum, thalamus, and anterior insula (Figure 4B, Table 6). Notably, congruency decoding in parietofrontal regions was more prominent in the left hemisphere (contralateral to the index and middle fingers used to pressing the buttons indicating match or mismatch responses).

DISCUSSION

Previous fMRI studies of the sound-symbolic correspondence between auditory pseudowords and visual shapes (McCormick et al., 2022; Peiffer-Smadja & Cohen, 2019) have been limited to univariate analyses of task conditions involving implicit registration of the correspondence. The present study is the first fMRI investigation of this psychophysically well-studied sound-symbolic correspondence using an explicit audiovisual matching task and incorporating MVPA to supplement conventional univariate analyses. These features of experimental design and analysis enable novel insights into the neural basis of sound symbolism.

Activations on univariate contrasts

In the present study using an explicit audiovisual matching task based on the sound-symbolic correspondence between auditory pseudowords and visual shapes, greater activity for incongruent, compared to congruent, bimodal stimuli was found in cortex of the left precentral sulcus (premotor cortex) and the left SMA, which are both regions involved in motor planning. Activation in these regions cannot be attributed solely to RT differences in the motor response since RT duration for each trial was explicitly modeled in the GLM (Grinband et al., 2008). Instead, these activations might reflect embodiment of the roundedness/pointedness of auditory pseudowords in manual actions via associations of the neural representations of such actions with those of the articulations involved in speech (Vainio & Vainio, 2021, 2022), and/or the resemblances between the sounds generated by speech and manual actions (Margiotoudi & Pulvermüller, 2020). Alternatively, greater activation in motor areas for incongruent trials could be due to the reprogramming of a preplanned response to congruent stimuli (Hartwigsen et al., 2012; Pellegrino et al., 2018). We also found higher activity for incongruent relative to congruent stimuli in the anterior insula bilaterally, which may reflect surprise associated with perception and decision-making, as noted in other contexts (Loued-Khenissi et al., 2020). These activations differ from those reported in earlier studies using implicit sound-symbolic matching, where bimodally incongruent stimuli elicited stronger activation than congruent stimuli in prefrontal cortical areas and the intraparietal sulcus, thought to indicate neural processes related to attention or effort (McCormick et al., 2022; Peiffer-Smadja & Cohen, 2019); and in the supramarginal gyrus which is involved in phonological processing (Hartwigsen et al., 2010; Oberhuber et al., 2016; see McCormick et al., 2022).

These earlier studies (McCormick et al., 2022; Peiffer-Smadja & Cohen, 2019) did not find regions that were preferentially active for congruent relative to incongruent stimuli, perhaps owing to reliance on implicit matching tasks. Here, our explicit matching task revealed activations for congruent compared to incongruent stimuli. Interestingly, some of these activated foci were in sensory cortical areas: One such focus was in auditory cortex in the superior temporal gyrus, including primary auditory cortex (Moerel et al., 2014) and neighboring auditory association cortex (Malinowska et al., 2017). Another was in a higher-order region of visual cortex, in the anterior fusiform gyrus (see Kliger & Yovel, 2020), extending into the parahippocampal gyrus, which has been implicated in evaluating audiovisual congruency (Diaconescu et al., 2011). Some of these activations may reflect multisensory convergence in sensory cortices (e.g., Schroeder et al., 2003), with audiovisual congruency leading to stronger activity in auditory as well as visual cortical areas, as hypothesized. Interestingly, a left somatosensory cortical focus in the postcentral gyrus also displayed higher activity for

congruent relative to incongruent stimuli. The anatomical location of this focus indicated that it was located in the hand representation (Martuzzi et al., 2014, see Table 2), medial to both the face representation (Moulton et al., 2009) and the part of somatosensory cortex activated during listening to and repeating speech (Darainy et al., 2019). Therefore, as with the incongruent activations mentioned above, activity at this focus could be due to postulated embodiment of the roundedness/pointedness of auditory pseudowords in manual actions through associations of the neural representations of manual actions and speech articulations (Vainio & Vainio, 2021, 2022), and/or similarities between the sounds of speech and manual actions (Margiotoudi & Pulvermüller, 2020). However, if this explanation were true, it is curious that corresponding activation was not found in primary motor cortex or areas mediating motor planning; thus, further work is needed to address the reason(s) for somatosensory cortical activation in our task.

Finally, we observed preferential bilateral activation near the caudate nucleus for congruent relative to incongruent audiovisual stimuli. Although the mechanism underlying this caudate nucleus activation is unclear, a similar preference for audiovisual congruency in the caudate nuclei has been found previously (Stevenson et al., 2009; McNorgan et al, 2015).

Multivoxel pattern analyses
MVPA offers insights into much finer-grained information processing than is possible with conventional univariate analyses, and has not previously been applied to the sound-symbolic pseudoword-shape correspondence, or to decode particular stimulus combinations in neuroimaging studies of sound symbolism. Interestingly, MVPA revealed superior classification performance of the bisensory stimulus pairs when congruent, compared to when they were incongruent, in the pars opercularis of the left IFG, i.e., Broca's area, and in the left SMG, both regions of the classical language network.

Although Broca's area is considered to be involved in syntactic processing (Fedorenko & Blank, 2020; Kemmerer, 2022; Maran et al., 2022), a number of studies implicate it in audiovisual associations relevant to language: For instance, high-gamma power in Broca's area was reported to be enhanced by congruent audiovisual speech, along with a progressive increase in coherence between auditory cortex and Broca's area over the duration of the stimulus, whereas coherence between these regions decreased over time for incongruent audiovisual speech (Lange et al., 2013). Another study found that anodal transcranial direct current stimulation (tDCS, which increases cortical excitability) over Broca's area facilitated acquisition of novel associations between pseudowords and unfamiliar visual objects (Perikova et al., 2022). An fMRI study using MVPA found that viewing of congruent lip movements facilitated classification of phonemes in Broca's area, with a larger effect for phonemes distinguished by manner of articulation (voiced vs. unvoiced consonants) than those distinguished by place of articulation (Zhang and Du, 2022). Our finding of higher classification performance of congruent, compared to incongruent, pseudoword-shape pairs in Broca's area resonates with these earlier studies and provides further evidence that processing of audiovisual congruency related to sound symbolism is indeed associated with language (Blasi et al., 2016; Sidhu et al., 2021; Nygaard et al., 2009; Meteyard et al., 2015).

Similar reasoning may apply to the left SMG, where again classification of the bisensory stimulus pairs was better when they were congruent rather than incongruent. The SMG has

been implicated in language processing and phonological processing in particular (Hartwigsen et al., 2010; Oberhuber et al., 2016). Reinforcing this line of thought, Zhang and Du (2022) found that viewing of congruent lip movements facilitated classification of phonemes in the left SMG in addition to Broca's area; however, in the SMG, classifier performance was significant for place of articulation but not voicing. The left SMG also demonstrates beta power suppression for incongruent audiovisual speech (Lange et al., 2013). Curiously, a number of studies have demonstrated stronger univariate activation for incongruent than congruent stimuli in both Broca's area (Ojanen et al., 2005; Pekkola et al., 2006; Szycik et al., 2009) and the left SMG (Bernstein et al., 2009; Xie et al., 2019; McCormick et al, 2022), which may reflect greater effort associated with processing of incongruent audiovisual stimuli related to speech. Though we did not observe increased univariate activation in Broca's area or left SMG in the present study, our MVPA findings of superior classifier performance for congruent compared to incongruent stimuli suggest that the neuronal populations recruited in these areas are more distinct for congruent than incongruent stimuli, independent of overall activation.

Note that in both Broca's area and the left SMG, the classifier in the present study yielded above-chance performance for congruent, but not incongruent stimuli. In contrast, in the right mid-occipital focus in early visual cortex, the classifier performed above chance for both congruent and incongruent stimulus pairs, with better performance for congruent pairings. This is consistent with multisensory convergence with a preference for congruency; see, for example, Kitada et al. (2021), who found congruency effects in touch-related regions when participants judged whether tactile stimuli were matched or mismatched with Japanese mimetic words related to tactile hardness and softness.

Separate between-congruency MVPA allowed us to directly test whether activity patterns were related to low-level sensory features or to processing congruency. We observed above-chance classification of the two visual stimuli in visual cortical areas, regardless of which auditory stimulus was paired with them. Similar above-chance classification of the two pseudoword stimuli was observed in auditory cortical areas, regardless of the accompanying visual stimulus. These findings are not surprising, but provide sanity checks on classifier performance. In contrast, classification of stimulus pairs as congruent or incongruent, regardless of the particular stimuli, was above chance in multiple brain regions. Among these regions, frontoparietal areas in the left hemisphere were prominent, perhaps attributable to decoding of finger movements (Shen et al., 2014), since each participant always used one finger to indicate that the audiovisual stimuli matched (congruent), and another finger to indicate the stimuli were mismatched (incongruent). However, other loci extend beyond this motor network and may relate to variations in attentional demand or decision processes for distinguishing congruent from incongruent stimuli. Future work is needed to isolate regions sensitive to processing congruency independent of the motor response.

Conclusions
This fMRI study provided evidence for multiple neural processes underlying sound symbolism. These operations include auditory and visual cortical processing of the stimuli, with some of the processing reflecting multisensory convergence; somatic sensorimotor processing, which may be due to manual embodiment of the audiovisual stimuli or response preparation and execution; and more general cognitive operations mediating attention or decisions. Most interestingly, the

present study offers robust support for a relationship of sound symbolism to the neural processes mediating language. Additional work is needed to disentangle the contributions of these various processes to sound symbolism and to more fully understand the role of sound symbolism in language.

ACKNOWLEDGMENTS
This work was supported by grants to KS and LCN from the National Eye Institute at the NIH (R01 EY025978) and the Emory University Research Council. Support to KS from the Veterans Administration is also acknowledged. Neuroimaging data were collected at the Facility for Education and Research in Neuroscience (FERN) at Emory University. We thank Kate Pirog Revill for assistance with scanning and Sara List for data collection.

DATA AND CODE AVAILABILITY
Data are available on request to the corresponding author and on submission of a completed data sharing agreement, project outline, and agreement on any co-authorship requirements etc. .

REFERENCES

Abraham, A., Pedregosa, F., Eickenberg, M., Gervais, P., Mueller, A., Kossaifi, J. et al. (2014). Machine learning for neuroimaging with scikit-learn. *Frontiers in Neuroinformatics*, 14.

Ademollo, F. (2011). *The Cratylus of Plato: A commentary.* Cambridge, UK: Cambridge University Press.

Audacity Team (2012) Audacity v2.0.1 [Computer program]. Retrieved from http://audacity.sourceforge.net/ Audacity ® software is copyright © 1999-2014 Audacity Team.

Avants, B. B., Epstein, C. L., Grossman, M., & Gee, J. C. (2008). Symmetric diffeomorphic image registration with cross-correlation: evaluating automated labeling of elderly and neurodegenerative brain. *Medical Image Analysis*, 12(1), 26-41.

Behzadi, Y., Restom, K., Liau, J., & Liu, T. T. (2007). A component based noise correction method (CompCor) for BOLD and perfusion based fMRI. *Neuroimage*, 37(1), 90-101.

Bernstein, L.E., Lu, Z.-L. & Jiang, J. (2008). Quantified acoustic-optical speech signal incongruity identifies cortical sites of audiovisual speech processing*. Brain Research*, 1242:172-184.

Blasi, D. E., Wichmann, S., Hammarström, H., Stadler, P. F., & Christiansen, M. H. (2016). Sound–meaning association biases evidenced across thousands of languages. *Proceedings of the National Academy of Sciences USA,* 113: 10818–10823.

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, 10: 433-436.

Chang, C. C., & Lin, C. J. (2011). LIBSVM: a library for support vector machines. *ACM transactions on intelligent systems and technology (TIST)*, 2(3), 1-27.

Cho, Z.-H. (Editor). (2010). *7.0 Tesla MRI Brain Atlas*. New York: Springer Science+Business Media LLC.

Chumbley, J., Worsley, K., Flandin, G., & Friston, K. (2010). Topological FDR for neuroimaging. *Neuroimage*, 49(4), 3057-3064.

Cox, R. W. (1996). AFNI: software for analysis and visualization of functional magnetic resonance neuroimages. *Computers and Biomedical Research*, 29(3), 162-173.

Cuskley, C., Simner, J., & Kirby, S. (2017). Phonological and orthographic influences in the bouba–kiki effect. *Psychological Research*, 81: 119–130

Dale, A.M. (1999). Optimal experimental design for event-related fMRI. *Human Brain Mapping*, 8:109-114.

Dale, A.M., Greve, D.N. & Burock, M.A. (1999) Optimal Stimulus Sequences for Event-Related fMRI. *5th International Conference on Functional Mapping of the Human Brain*. Düsseldorf, Germany, June 11-16, 1999.

Darainy, M., Vahdat, S. & Ostry, D.J. (2019). Neural basis of sensorimotor plasticity in speech motor adaptation. *Cerebral Cortex*, 29: 2876-2889.

Diaconescu, A.O., Alain, C. & McIntosh, A.R. (2011). The co-occurrence of multisensory facilitation and cross-modal conflict in the human brain. *Journal of Neurophysiology*, 106: 2896-2909.

Esteban, O., Markiewicz, C.J., Blair, R.W., Moodie, C.A., Ilkay Isik, A., Erramuzpe, A. et al. (2019). fMRIPrep: a robust preprocessing pipeline for functional MRI. *Nature Methods*, 16: 111-116.

Esteban, O., Ciric, R., Finc, K., Blair, R. W., Markiewicz, C. J., Moodie, C. A. et al. (2020). Analysis of task-based functional MRI data preprocessed with fMRIPrep. *Nature protocols,* 15(7), 2186-2202.

Fedorenko, E. & Blank, I.A. (2020). Broca's area is not a natural kind. *Trends in Cognitive Sciences*, 24:270-284.

Fort, M., Martin, A., & Peperkamp, S. (2015). Consonants are more important than vowels in the bouba-kiki effect. *Language & Speech*, 58: 247–266.

Ghazanfar, A.A. & Schroeder, C.E. (2006). Is neocortex essentially multisensory? *Trends in Cognitive Sciences*, 10: 278-285.

Gorgolewski, K., Burns, C. D., Madison, C., Clark, D., Halchenko, Y. O., Waskom, M. L., & Ghosh, S. S. (2011). Nipype: a flexible, lightweight and extensible neuroimaging data processing framework in python. *Frontiers in Neuroinformatics*, 13.

Greve, D. N., & Fischl, B. (2009). Accurate and robust brain image alignment using boundary-based registration. *Neuroimage*, 48(1), 63-72.

Grinband, J., Wager, T. D., Lindquist, M., Ferrera, V. P., & Hirsch, J. (2008). Detection of time-varying signals in event-related fMRI designs. *Neuroimage*, 43(3), 509-520.

Hartwigsen, G., Baumgaertner, A., Price, C. J., Koehnke, M., Ulmer, S. & Siebner, H. R. (2010). Phonological decisions require both left and right supramarginal gyri*, Proceedings of the National Academy of Sciences USA*, 107: 16494–16499.

Hartwigsen, G., Bestmann, S., Ward, N. S., Woerbel, S., Mastroeni, C., Granert, O., & Siebner, H. R. (2012). Left dorsal premotor cortex and supramarginal gyrus complement each other during rapid action reprogramming. *Journal of Neuroscience*, 32(46), 16162-16171.

Hebart, M.N., Görgen, K. & Haynes, J.-D. (2015). The Decoding Toolbox (TDT): a versatile software package for multivariate analyses of functional imaging data. *Frontiers in Neuroinformatics*, 8: 88, doi: 10.3389/fninf.2014.00088

Itagaki, S., Murai, S., & Kobayasi, K. I. (2019). Brain activity related to sound symbolism: cross-modal effect of an aurally presented phoneme on judgment of size. *Scientific Reports*, 9(1), 1-7.

Jenkinson, M., & Smith, S. (2001). A global optimisation method for robust affine registration of brain images. *Medical Image Analysis*, 5(2), 143-156.

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved optimization for the robust and accurate linear registration and motion correction of brain images. *Neuroimage*, 17(2), 825-841.

Joliot, M., Jobard, G., Naveau, M., Delcroix, N., Petit, L., Zago, L. et al. (2015). AICHA: an atlas of intrinsic connectivity of homotopic areas. *Journal of Neuroscience Methods*, 254:46-59.

Kanero, J., Imai, M., Okuda, J., Okada, H., & Matsuda, T. (2014). How sound symbolism is processed in the brain: a study on Japanese mimetic words. *PLoS one*, 9(5), e97905.

Kaplan, J.T., Man, K. & Greening, S.G. (2015). Multivariate cross-classification: applying machine learning techniques to characterize abstraction in neural representations. *Frontiers in Human Neuroscience*, 9:151, doi: 10.3389/fnhum.2015.00151

Kemmerer, D. (2022). Revisiting the relation between syntax, action, and left BA44. *Frontiers in Human Neuroscience*, 16:923022, doi:10.3389/fnhum.2022.923022

Kitada, R., Kwon, J., Doizaki, R., Nakagawa, E., Tanigawa, T., Kajimoto, H., et al. (2021). Brain networks underlying the processing of sound symbolism related to softness perception, *Scientific Reports,* 11: 7399. doi:10.1038/s41598-021-86328-6.

Kleiner M., Brainard D. & Pelli D. (2007) "What's new in Psychtoolbox-3?" *Perception*, 36: ECVP Abstract Supplement.

Kliger, L. & Yovel, G. (2020). The functional organization of high-level visual cortex determines the representation of complex visual stimuli. *Journal of Neuroscience*, 40: 7545-7558.

Köhler, W. (1929). *Gestalt psychology.* New York: Liveright.

Köhler, W. (1947). *Gestalt psychology: An introduction to new concepts in modern psychology.* New York: Liveright.

Lacey, S., Jamal, Y., List, S.M., McCormick, K., Sathian, K. & Nygaard, L.C. (2020). Stimulus parameters underlying sound-symbolic mapping of auditory pseudowords to visual shapes. *Cognitive Science*, 44: e12883.

Lanczos, C. (1964). Evaluation of noisy data. *Journal of the Society for Industrial and Applied Mathematics, Series B: Numerical Analysis*, 1(1), 76-85.

Lange, J., Christian, N. & Schnitzler, A. (2013). Audio-visual congruency alters power and coherence of oscillatory activity within and between cortical areas. *NeuroImage*, 79:111-120.

Lee, S., & Kable, J. W. (2018). Simple but robust improvement in multivoxel pattern classification. *PLoS One*, 13(11), e0207083.

Loued-Khenissi, L., Pfeuffer, A., Einhäuser, W. & Preuschoff, K. (2020). Anterior insula reflects surprise in value-based decision-making. *NeuroImage*, 210: 116549.

Malinowska, U., Crone, N.E., Lenz, F.A., Cervenka, M. & Boatman-Reich, D. (2017). Multi-regional adaptation in human auditory association cortex. *Frontiers in Human Neuroscience*, 11:247, doi: 10.3389/fnhum.2017.00247

Man, K., Damasio, A., Meyer, K. & Kaplan, J.T. (2015). Convergent and invariant object representations for sight, sound, and touch. *Human Brain Mapping*, 36:3629-3640.

Maran, M., Friederici, A.D. & Zaccarella, E. (2022). Syntax through the looking glass: A review on two-word linguistic processing across behavioral, neuroimaging and neurostimulation studies. *Neuroscience & Biobehavioral Reviews*, 142:104881.

Margiotoudi, K. & Pulvermüller, F. (2020). Action sound-shape congruencies explain sound symbolism. *Scientific Reports*, 10: 12706, doi: 10.1038/s41598-020-69528-4

Martuzzi, R., van der Zwaag, W., Farthouat, J., Gruetter, R. & Blanks, O. (2014). Human finger somatotopy in Areas 3b, 1, and 2: a 7T fMRI study using a natural stimulus. *Human Brain Mapping*, 35:213-226.

McCormick, K., Kim, J.Y., List, S. & Nygaard, L.C. (2015). Sound to meaning mappings in the bouba-kiki effect. *Proceedings 37th Annual Meeting Cognitive Science Society*, pp1565-1570.

McCormick, K., Lacey, S., Stilla, R., Nygaard, L.C. & Sathian, K. (2022). Neural basis of the sound-symbolic crossmodal correspondence between auditory pseudowords and visual shapes. *Multisensory Research,* 35: 29-78.

McNorgan, C. & Booth, J.R. (2015). Skill dependent audiovisual integration in the fusiform induces repetition suppression. *Brain & Language*, 141: 110-123.

Meteyard, L., Stoppard, E., Snudden, D., Cappa, S. F., & Vigliocco, G. (2015). When semantics aids phonology: A processing advantage for iconic word forms in aphasia. *Neuropsychologia*, 76: 264–275.

Misaki, M., Luh, W. M., & Bandettini, P. A. (2013). The effect of spatial smoothing on fMRI decoding of columnar-level organization with linear support vector machine. *Journal of Neuroscience Methods*, 212: 355-361.

Moerel, M., De Martino, F. & Formisano, E. (2014). An anatomical and functional topography of human auditory cortical areas. *Frontiers in Neuroscience*, 8: 225, doi: 10.3389/fnins.2014.00225

Moulton, E.A, Pense, G., Morris, S., Aiello-Lammens, M., Becerra, L. & Borsook, D. (2009). Segmentally arranged somatotopy within the face representation of human primary somatosensory cortex. *Human Brain Mapping*, 30: 757-765

Nuckolls, J.B. (1999). The case for sound symbolism. *Annual Review of Anthropology*, 28:225-252.

Nygaard, L. C., Cook, A. E., & Namy, L. L. (2009). Sound to meaning correspondences facilitate word learning. *Cognition*, 112: 181–186.

Oberhuber, M., Hope, T. M. H., Seghier, M. L., Parker Jones, O., Prejawa, S., Green, D.W. & Price, C. J. (2016). Four functionally distinct regions in the left supramarginal gyrus support word processing, *Cerebral Cortex*, 26: 4212–4226.

Ojanen, V., Möttönen, R., Pekkola, J., Jääskeläinen, I.P., Joensuu, R., Autti, T. & Sams, M. (2005). Processing of audiovisual speech in Broca's area. *NeuroImage*, 25:333-338.

Peiffer-Smadja, N., & Cohen, L. (2019). The cerebral bases of the bouba-kiki-effect. *NeuroImage*, 186: 679-689.

Pekkola, J., Laasonen, M., Ojanen, V., Autti, T., Jääskeläinen, I.P., Kujala, T. & Sams, M. (2006). Perception of matching and conflicting audiovisual speech in dyslexic and fluent readers: An fMRI study at 3T. *NeuroImage*, 29:797-807.

Pellegrino, G., Tomasevic, L., Herz, D. M., Larsen, K. M., & Siebner, H. R. (2018). Theta activity in the left dorsal premotor cortex during action re-evaluation and motor reprogramming. *Frontiers in Human Neuroscience*, 12, 364.

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: Transforming numbers into movies. *Spatial Vision*, 10: 437-442.

Perikova, E., Blagovechtchenski, E., Filippova, M., Shcherbakova, O., Kirsanov, A. & Shtyrov, Y. (2022). Anodal tDCS over Broca's area improves fast mapping and explicit encoding of novel vocabulary. *Neuropsychologia*, 168:108156

Pinker, S. (1999). *Words and Rules: The Ingredients of Language*. Harper Collins, New York, NY, USA.

Power, J. D., Mitra, A., Laumann, T. O., Snyder, A. Z., Schlaggar, B. L., & Petersen, S. E. (2014). Methods to detect, characterize, and remove motion artifact in resting state fMRI. *Neuroimage*, 84, 320-341.

Raczkowski, D., Kalat, J. W. & Nebes, R. (1974). Reliability and validity of some handedness questionnaire items. *Neuropsychologia*, 12: 43-47.

Ramachandran, V. S. & Hubbard, E. M. (2001). Synaesthesia – a window into perception, thought and language, *Journal of Consciousness Studies*, 8: 3–34.

Revill, K. P., Namy, L. L., DeFife, L. C. & Nygaard, L. C. (2014). Cross-linguistic sound symbolism and crossmodal correspondence: evidence from fMRI and DTI. *Brain & Language,* 128:18–24.

Rolls, E. T., Joliot, M. & Tzourio-Mazoyer, N. (2015). Implementation of a new parcellation of the orbitofrontal cortex in the automated anatomical labeling atlas. *NeuroImage*, 122: 1-5.

Satterthwaite, T. D., Elliott, M. A., Gerraty, R. T., Ruparel, K., Loughead, J., Calkins, M. E. et al. (2013). An improved framework for confound regression and filtering for control of motion artifact in the preprocessing of resting-state functional connectivity data. *Neuroimage*, 64, 240-256.

Schroeder, C.E., Smiley, J., Fu, K.G., McGinnis, T., O'Connell, M.N. & Hackett, T. (2003). Anatomical mechanisms and functional implications of multisensory convergence in early cortical processing. *International Journal of Psychophysiology*, 50: 5-17.

Shen, G., Zhang, J., Wang, M., Lei, D., Yang, G., Zhang, S., & Du, X. (2014). Decoding the individual finger movements from single-trial functional magnetic resonance imaging recordings of human brain activity. *European Journal of Neuroscience*, 39(12), 2071-2082.

Sidhu, D.M., Westbury, C., Hollis, G. & Pexman, P.M. (2021). Sound symbolism shapes the English language: the maluma/takete effect in English nouns. *Psychonomic Bulletin & Review*, 28: 1390-1398.

Stevenson, R.A., Kim, S. & James, T.W. (2009). An additive-factors design to disambiguate neuronal and areal convergence: measuring multisensory interactions between audio, visual, and haptic sensory streams using fMRI. *Experimental Brain Research*, 198: 183-194.

Szycik, G.R., Jansma, H. & Münte, T.F. (2009). Audiovisual integration during speech comprehension: An fMRI study comparing ROI-based and whole brain analyses. *Human Brain Mapping*, 30:1990-1999.

Tustison, N. J., Avants, B. B., Cook, P. A., Zheng, Y., Egan, A., Yushkevich, P. A., & Gee, J. C. (2010). N4ITK: improved N3 bias correction. *IEEE Transactions on Medical Imaging*, 29(6), 1310-1320.

Tzourio-Mazoyer, N., Landeau, B., Papathanassiou, D., Crivello, F., Etard, O., Delcroix, N. et al. (2002). Automated anatomical labeling of activations in SPM using a macroscopic anatomical parcellation of the MNI MRI single-subject Brain. *NeuroImage*, 15: 273-289.

Vainio, L. & Vainio, M. (2021). Sound-action symbolism. *Frontiers in Psychology*, 12: 718700, doi: 10.3389/fpsyg.2021.718700

Vainio, L. & Vainio, M. (2022). Interaction between grasping and articulation: how vowel and consonant pronunciation influences precision and power grip responses. *PLoS ONE*, 17: e0265651, doi: 10.1371/journal.pone.0265651

Xie, Y.J., Li, Y.Y., Xie, B., Xu, Y.Y. & Peng, L. (2019). The neural basis of complex audiovisual objects maintenances in working memory. *Neuropsychologia*, 133:107189.

Zhang, Y., Brady, M., & Smith, S. (2001). Segmentation of brain MR images through a hidden Markov random field model and the expectation-maximization algorithm. *IEEE Transactions on Medical Imaging*, 20(1), 45-57.

Zhang, L. & Du, Y. (2022). Lip movements enhance speech representations and effective connectivity in auditory dorsal stream. *NeuroImage*, 257:119311.

Table 1. Mean (standard error) accuracy and reaction times.

Stimulus pairs	Accuracy (%)	Reaction Time (ms)
Congruent		
'mohloh'/rounded shape	95.21 (0.75)	898 (33)
'kehteh'/pointed shape	95.73 (0.79)	832 (31)
Incongruent		
'mohloh'/pointed shape	96.35 (0.99)	958 (31)
'kehteh'/rounded shape	94.11 (1.76)	938 (33)

Table 2. Brain regions showing univariate activation differences for congruent vs. incongruent stimuli (whole-brain topological FDR-corrected; activation clusters with cluster-forming threshold of $p < 0.001$ and FDR cluster-level correction of $p < 0.05$). Coordinates of peak local maxima are shown for each cluster.

Anatomical Location	Peak MNI coordinates			Cluster Level	
	x	y	z	# voxels	$P_{FDR\text{-}corr}$
Congruent > incongruent					
L anterior fusiform/parahippocampal gyrus	-21	-34	-19	929	< 0.001
R caudate nucleus	9	16	12	153	< 0.001
L caudate nucleus	-8	14	17	71	0.013
R mid-cingulate gyrus	10	3	31	54	0.013
L mid-superior temporal gyrus	-46	-13	2	49	0.016
L postcentral gyrus	-45	-19	49	163	< 0.001
Incongruent > congruent					
L precentral sulcus	-31	-3	52	1456	< 0.001
L supplementary motor area	-6	13	49	984	< 0.001
L anterior insula	-41	15	8	434	< 0.001
R anterior insula	38	21	7	576	< 0.001
R pons	11	-39	-32	136	< 0.001

Table 3. Brain regions showing above-chance classification of visual and auditory stimuli in congruent and incongruent conditions (whole-brain topological FDR-corrected; activation clusters with cluster-forming threshold of $p < 0.001$ and FDR cluster-level correction of $p < 0.05$). Coordinates of peak local maxima are shown for each cluster.

Anatomical Location	Peak MNI coordinates			Cluster Level	
	x	y	z	# voxels	$P_{FDR\text{-}corr}$
Congruent decoding					
R calcarine sulcus	19	-87	7	1080150	< 0.001
R superior temporal gyrus	57	-12	-5	10332	< 0.001
L supramarginal gyrus	-62	-30	26	13328	< 0.001
R superior frontal gyrus	20	46	25	3704	< 0.001
L inferior frontal gyrus, pars opercularis	-45	6	28	3263	< 0.001
L supplementary motor area	-2	0	56	4171	< 0.001
R intraparietal sulcus	38	-49	48	2096	< 0.001
R inferior temporal gyrus	53	-47	-10	162	0.020
R precuneus	6	-47	6	583	0.006
L intraparietal sulcus	-41	-50	49	228	0.006
R middle temporal gyrus	64	-48	-9	122	0.042
R inferior temporal gyrus	41	-38	-9	152	0.023
Incongruent decoding					
R calcarine sulcus	16	-98	-1	26326	< 0.001
L middle occipital gyrus	-17	-100	4	21732	< 0.001
R superior temporal gyrus	59	-26	11	15147	< 0.001
L superior temporal gyrus	-42	-27	18	7938	< 0.001
R cerebellum	26	-40	-35	150	0.026
R middle occipital gyrus	40	-63	15	259	0.004
L precuneus	-13	-65	66	251	0.004
R fusiform gyrus	38	-42	-24	450	< 0.001

Table 4. Brain regions showing higher above-chance classification of visual and auditory stimuli in the congruent conditions vs. the incongruent conditions (whole-brain topological FDR-corrected; activation clusters with cluster-forming threshold of $p < 0.001$ and FDR cluster-level correction of $p < 0.05$). Coordinates of peak local maxima are shown for each cluster. Note: no region showed greater incongruent > congruent decoding.

Anatomical Location	Peak MNI coordinates			Cluster Level	
	x	y	z	# voxels	$P_{FDR\text{-}corr}$
L inferior frontal gyrus, pars opercularis	-44	10	15	291	0.008
L supramarginal gyrus	-60	-23	26	485	0.008
R mid-occipital gyrus	19	-88	6	239	0.008

Table 5. Brain regions showing above-chance decoding of visual shape and congruency (whole-brain topological FDR-corrected; activation clusters with cluster-forming threshold of *p* < 0.001 and FDR cluster-level correction of *p* < 0.05). Coordinates of peak local maxima are shown for each cluster.

Anatomical Location	Peak MNI coordinates			Cluster Level	
	x	y	z	# voxels	$P_{FDR\text{-}corr}$
Shape decoding					
R lingual gyrus	16	-93	-6	19354	< 0.001
L calcarine sulcus	-11	-99	-4	20279	< 0.001
Congruency decoding					
L precentral gyrus	-35	-25	60	42895	< 0.001
L superior frontal gyrus	-17	17	41	752	< 0.001
R superior frontal gyrus	19	20	44	1476	< 0.001
R pallidum	23	-7	6	928	< 0.001
R postcentral gyrus	49	-13	35	1813	< 0.001
L hippocampus	-29	-6	-23	706	< 0.001
R superior parietal lobule	20	-67	58	627	< 0.001
R middle frontal gyrus	38	41	23	832	< 0.001
R superior frontal gyrus	5	45	50	151	0.023
L posterior cingulate gyrus	-19	-46	28	1050	< 0.001
R inferior frontal gyrus, pars triangularis	49	22	15	280	0.007
R inferior frontal gyrus, pars orbitalis	41	32	-2	121	0.043

Table 6. Brain regions showing above-chance decoding of auditory pseudowords and congruency (whole-brain topological FDR-corrected; activation clusters with cluster-forming threshold of $p < 0.001$ and FDR cluster-level correction of $p < 0.05$). Coordinates of peak local maxima are shown for each cluster.

Anatomical Location	Peak MNI coordinates			Cluster Level	
	x	y	z	# voxels	$P_{FWE\text{-}corr}$
Pseudoword decoding					
R superior temporal sulcus/gyrus	63	-17	-2	5929	< 0.001
L superior temporal sulcus/gyrus	-54	-19	-1	720	< 0.001
Congruency decoding					
L postcentral gyrus	-12	-36	39	80140	< 0.001
R parahippocampal gyrus	28	-1	-29	2208	< 0.001
R postcentral gyrus	35	-29	61	17413	< 0.001
R thalamus	15	-10	6	15048	< 0.001
R posterior superior cerebellum	29	-72	-22	542	< 0.001
L orbito-frontal gyrus	-19	33	-19	253	0.003
L posterior inferior temporal gyrus	-35	-65	-18	1392	< 0.001
L middle/inferior temporal gyrus	-48	-48	-5	958	< 0.001
R anterior insula	33	30	6	354	0.001
R lateral cerebellum	36	-53	-28	309	0.001
L anterior inferior temporal gyrus	-35	-19	-23	374	0.001
L anterior middle temporal gyrus	-57	-15	-20	300	0.002
R inferior temporal gyrus	52	-50	-4	298	0.002
L posterior inferior temporal gyrus	-34	-86	-14	129	0.036
L inferior frontal sulcus	-46	30	23	153	0.022

Figure 1. Task design and classification analysis scheme. (A) There were four possible stimuli, reflecting unique combinations of two visual shapes, pointed or rounded, and two auditory pseudowords, 'kehteh' or 'mohloh'. (B) Pseudoword-shape pairs were presented simultaneously and participants pressed a response button indicating whether the pair were a 'match' (i.e., congruent) or a 'mismatch' (i.e., incongruent). (C) In the within-congruency classification analysis, leave-one-run-out cross-validation was used to test for patterns of brain activity discriminating the two congruent conditions or the two incongruent conditions. (D) in the between-congruency classification analyses, classifiers were trained to distinguish between the two conditions in which the visual shapes differed but the auditory pseudoword was the same (e.g., 'kehteh'/pointed shape vs. 'kehteh'/rounded shape). The classifier was then tested on the two remaining conditions containing the other pseudoword (e.g., 'mohloh'/pointed shape vs. 'mohloh'/rounded shape). Similarly, we trained classifiers to distinguish between auditory pseudowords holding the shape constant (e.g., 'kehteh'/pointed shape vs. 'mohloh'/pointed shape) and then tested them on the other shape (e.g., 'kehteh'/rounded shape vs. 'mohloh'/rounded shape). This approach differentiates whether patterns of brain activity were specific to features of the visual/auditory stimulus, or to the congruency/incongruency of the condition.

Figure 2. Univariate results. Whole-brain map showing significant effects ($p < 0.05$, FDR-corrected) from the incongruent vs. congruent contrasts.

Figure 3. Within-congruency classification. (A) Whole-brain searchlight maps showing significant above-chance classification of the two congruent conditions (congruent decoding) and the two incongruent conditions (incongruent decoding). (B) Whole-brain searchlight map showing significantly higher classification of the congruent conditions relative to the incongruent conditions. No region showed significantly higher above-chance classification of the incongruent conditions. (C) Mean decoding accuracy extracted from the peak voxel coordinates for each of the significant clusters in (B). All maps p < 0.05, FDR-corrected; error bars show ± standard error of the mean.

Figure 4. Between-congruency classification. (A) Whole-brain searchlight maps showing significant above-chance decoding of either the visual shape or the congruency of the stimuli. (B) Whole-brain searchlight maps showing significant above-chance decoding of either the auditory pseudoword or the congruency of the stimuli. All maps p < 0.05, FDR-corrected.