Assisting and Accelerating NMR Assignment with Restrainted Structure Prediction

Sirui Liu[1†], Haotian Chu[2], Yuhao Xie[1], Fangming Wu[3], Ningxi Ni[2], Chenghao Wang[2], Fangjing Mu[1], Jiachen Wei[1], Jun Zhang[1], Mengyun Chen[2], Junbin Li[2], Fan Yu[2], Hui Fu[4], Shenlin Wang[5], Changlin Tian[3,6], Zidong Wang[2†], Yi Qin Gao[1,4,7†]

1. Changping Laboratory, Beijing 102200, China.
2. Huawei Technologies Co., Ltd., Hangzhou, China.
3. High Magnetic Field Laboratory, Chinese Academy of Sciences, Hefei 230031, China.
4. Beijing National Laboratory for Molecular Sciences, College of Chemistry and Molecular Engineering, Peking University, Beijing 100871, China.
5. State Key Laboratory of Bioreactor Engineering, East China University of Science and Technology (ECUST), Shanghai 200237, China
6. Hefei National Laboratory of Physical Sciences at Microscale, School of Life Sciences, University of Science and Technology of China, Hefei 230027, China.
7. Biomedical Pioneering Innovation Center (BIOPIC), Peking University, Beijing 100871, China.

†To whom correspondence should be addressed.

Abstract

NMR experiments can detect in situ structures and dynamic interactions, but the NMR assignment process requires expertise and is time-consuming, thereby limiting its applicability. Deep learning algorithms have been employed to aid in experimental data analysis. In this work, we developed a RASP model which can enhance structure prediction with restraints. Based on the evoformer and structure module architecture of AlphaFold, this model can predict structure based on sequence and a flexible number of input restraints. Moreover, it can evaluate the consistency between the predicted structure and the imposed restraints. Based on this model, we constructed an iterative NMR NOESY peak assignment pipeline named FAAST, to accelerate assignment process of NOESY restraints and obtaining high quality structure ensemble. The RASP model and FAAST pipeline not only allow for the leveraging of experimental restraints to improve model prediction, but can also facilitate and expedite experimental data analysis with their integrated capabilities.

Introduction

NMR is an experimental technique used to determine structures and detect weak interactions in situ[1,2]. However, NMR assignment requires both expertise and time. It might take months even years for NMR assignment. Leveraging machine learning and deep learning

technologies, researchers have endeavored to automate the NMR assignment protocol. For example, ARTINA[3] provides an integrated pipeline which accepts raw NMR spectra, assigns chemical shifts and NOE peaks, and provides structures simultaneously. It utilizes molecular simulations to construct structures, with a focus on achieving automated and accurate chemical shift assignments. Specifically, the NOESY peak assignment process provides hydrogen restraints and is an essential technique in NMR structure analysis. Automated algorithms such as CYANA[4], ARIA[5,6], CANDID[7] have been developed to assist this process, yet they mostly apply strategies such as simulated annealing or molecular dynamics simulation for structure construction, thus is relatively time consuming.

Recent progress in deep learning provides more efficient and accurate tools to generate protein structure given its sequence. Employing deep learning protein structure prediction models for experimental data analysis has been a problem of interest. Researchers may encounter situations where the input data form and distribution of general structure prediction models, such as AlphaFold[8], do not necessarily align with the needs of experimental methods. While AlphaFold and AlphaFold-multimer[9] have greatly improved the accuracy of predicting static protein structures, unresolved issues remain, such as generating dynamic structures and predicting restrained structures. The questions of how experimental information can facilitate rapid structure prediction and how structure prediction methods can aid in the resolution or acceleration of experimental data analysis are still open. Attempts have been made to provide AlphaFold structures as templates for X-ray replacement[10] or Cryo-EM density map[11] templates. However, these approaches rely on iterative template use, which includes dense but not necessarily accurate restraints and cannot utilize structural differences to improve predictions. Recently, AlphaLink[12] fine-tuned AlphaFold to accept sparse restraints, improving AlphaFold's performance in cross-linking experiments.

In this work we propose a model named Restraints Assisted Structure Predictor (RASP) and an iterative NMR NOESY peak assignment pipeline called FAAST(iterative Folding Assisted peak ASsignmenT). The architecture of RASP is derived from AlphaFold evoformer and structure module, and it accepts abstract or experimental restraints, sparse or dense, to generate structures. This enables RASP to be used in diverse applications, including improving structure predictions for multi-domain proteins and those with few MSAs. The pLDDT score of RASP can evaluate restraint quality in terms of information efficiency and accuracy. Consequently, by leveraging the model's ability to accept a flexible number of restraints and evaluate them, together with an NMR assignment protocol adapted from ARIA[6], we developed the FAAST pipeline. Using chemical shift and NOE peak lists as input, FAAST assigns NOE peaks iteratively and generates a structure ensemble based on the subsampled restraints, thus accelerating NMR analysis.

Methods

Structure of RASP

To incorporate restraint information, we developed the RASP model derived from the AlphaFold2 evoformer and structure module. Four additional biases were added, which draw on restraint information: pair bias, MSA bias, IPA bias, and structure bias. To handle

inter-residue restraints as edge information, the first 3 biases adopt edge biases to the Evoformer and IPA modules. This inter-residue information can be naturally converted into features of shape ($N_{res}, N_{res}, C_{channels}$), similar to the pair activation in the Evoformer module of the original model. Following the strategy of merging pair activation and MSA activation in the Evoformer module, an extra contact bias is added to the row-wise attention and the outer-product mean module by pair bias. The merging of inter-residue information and per-residue information also occurs in the Invariant Point Attention. The contact information is added to the IPA attention weight matrix as IPA bias in the same way as the MSA bias. In addition to the biases in the attention, an additional bias is introduced in the structure generation process. When generating the 3D structure, near-residue pairs identified by restraint information are moved into close distances, whereas the rest of the residue pairs connected to the pairs are then pulled by optimizing the inter-residue distance in the violation loss of AlphaFold2.

Restraint loss and tasks

All AlphaFold losses are retained, including the auxiliary loss from the Structure Module (a combination of averaged FAPE and torsion losses on the intermediate structures), averaged cross-entropy losses for distogram and masked MSA predictions, model confidence loss, experimentally resolved loss, and violation loss.

We introduce restraint loss into the model training to reinforce the input restraints information in the final prediction. This loss comprises three components, each corresponding to a restraint-related task. The first task is a 0/1 classification task with a loss called contact classification loss. In this task, residue-wise distogram prediction of input restraints is computed, and reorganized into 2 classes (whether or not the contact exists) with cross entropy calculated using the ground truth label. The second task is to minimize the distance RMSD difference of input restraints using a loss called dRMSD contact loss. The last task is to make local structures similar to the ground truth structures, and takes a reduced version of backbone FAPE loss called contact FAPE loss, in which the errors of all atom positions are calculated in the local backbone frames of all residues in the restraints. The contact FAPE loss and dRMSD contact loss are weighted equally at 0.5 so that the three losses are of the same order of magnitude at the beginning of training. We clip the sum of the last two losses by 1.5 to avoid training clashes in abnormal training examples.

Sampling strategy

The model has been trained using the PSP dataset[13], which was previously constructed by us. The PSP dataset is a compilation of true and distilled protein structures, and it includes sequence, structure, template, and MSA data for each protein sequence. Training data for RASP are sampled with replacement from both the true structure and distillation datasets and mixed in a ratio of 1:3.

To simulate the restraints observed in real experiments, the residue-wise distance map of the protein structure is computed using the pseudo-Cβ atom position of the residue, where the pseudo-Cβ atom is the Cα atom position for glycine and Cβ for other amino acids. The restraints are sampled based on a probability distribution that decreases with residue-wise distance. When the distance is <7 Angstrom(A), the probability is equal, and it decays

exponentially from 7A to 10A. With this distribution, 90% of the sampled restraints are at a distance less than or equal to 8A, and 10% of the restraints are at a distance greater than or equal to 8A. This setting provides the model with a tolerance to restraints of poor quality. The number of restraints is also randomly sampled from a distribution with equal probability for 16-128A and an exponential decay from 128A to 2048A. The expected value of this distribution is 115 Angstrom.

NMR NOE assignment pipeline

The assignment pipeline used in this study was based on ARIA 2.3 (Ambiguous Restraints for Iterative Assignment), which was developed with Python 2 by Institut Pasteur. The FAAST assignment pipeline employed the Calibration - CalculateBounds - ViolationAnalysis - Partially assignment(CCVP) algorithm in ARIA, which was adapted from the original Python 2 code to Python 3. As the protein structure predicted by RASP does not distinguish equivariant hydrogens in amino acids, we modified the algorithm to fit into our pipeline and calculate the distances between equivalent atomic groups.

The initial assignment is performed by comparing the chemical shift and NOE lists. Most of the output are ambiguous restraints (ARs) while some peaks are naturally unambiguous (URs). The quality of the initial URs could be very low, with more than half exceeding a distance of 6.0 Angstroms. Thus, for the initial assignment, we filtered out initial URs with distances larger than 12 Angstroms in the reference prediction without restraints. For each iteration, the URs are fed into RASP to generate 20 structures with the UR subsampling rate of 5%, 10%, or 20%, depending on the iteration step, and the structures are relaxed by OpenMM[14]. The structure bundle is then used to assign NOE peaks by CCPV.

In the standard pipeline, the hyper-parameters used for restraint subsampling and CCVP are iteratively tightened, with a subsampling rate of 10% and partial assignment cumulative acceptance of 0.9 for the first iteration and 20% and 0.8 for the second iteration. ARs are transformed into URs iteratively. If after the second iteration, the median pLDDT score is lower than 80, a second round of iteration is initiated with subsampling and CCVP parameters of (5%, 0.9), (5%, 0.8), and (10%, 0.8). The entire process takes 2-5 structure generation iterations, and the number of iterations, as well as the iterating parameters, can be flexibly adjusted.

Benchmarking data

The benchmarking data for our method consist of three parts:

PSP validation dataset: This dataset is used to evaluate the performance of the RASP model. The restraints in this dataset are sampled in the same way as during training.

MR dataset: For most NMR structure in RCSB PDB database[15], restraint .mr files are also deposited. We selected all the NMR .mr files from the RCSB PDB database in which a) the restraint numbering followed the PDB numbering, and b) the restraint recall for long-term restraints of the structure predicted by AlphaFold2 was less than 90%. This resulted in 187 samples.

NMR dataset: The NMR dataset was obtained to evaluate the NMR FAAST protocol. We obtained the .star file (including the chemical shift and NOE list), .mr file (submitted restraints), and .pdb file (structure) for 100 sequences in the ARTINA dataset by crawling the

BMRB[16] and RCSB PDB databases. After filtering out the .star files with missing chemical shift or NOE lists, 57 sequences were available for testing our protocol.

Additionally, as the experimenter could filter the NOE list in .star files from the BMRB dataset before submission, we used the raw NOE peak list for pdb id 2MRM, provided by the experimental lab, to evaluate the peak quality.

Evaluation methods

We evaluated the structures and their consistency with restraints mainly with TM-score, root mean square deviation(RMSD), and restraint recall.

For structural comparison, TM-score[17,18] is the most frequently used in this work. It is a metric for assessing the topological similarity of protein structures. This score falls between 0 and 1, and higher TM-score indicates higher similarity between the two compared proteins. We used the TM-align[19] package downloaded from Zhang lab for calculation of TM-scores.

In FAAST evaluation, two types of RMSD are used. For measurement of mutual similarity within a structure ensemble, we calculate the pairwise Cα RMSD between all pairs of different structures within the bundle, and average them to obtain the pairwise mutual RMSD. For measurement of structure similarity between the deposited PDBs and processed structure ensemble, we follow the ARTINA[3] evaluation and calculated the backbone atom RMSD for structured regions defined by ARTINA.

Restraint recall is used to measure the consistency between a structure and a set of restraints. It is defined as the ratio between the number of rightly followed restraints by the structure and the number of ground truth restraints, similar to the definition of recall in the machine learning field. In RASP evaluation, since the restraints are at residue level, we define a pairwise restraint to be followed by the structure as the distance between pseudo-Cβ atoms (see sampling strategy in method) in the residue pair is closer than 8 Angstroms. In FAAST pipeline evaluation, since the NMR restraints are at atomic level, we define a pairwise restraint to be followed only when the closest hydrogen atomic distance in the two equivalent groups from the structure is lower than 6 Angstroms.

Results

RASP takes in restraints directly and helps in structure prediction

To facilitate general experimental information as restraints, we developed the RASP model based on the AlphaFold architecture. The model takes in sequence and a flexible number of distance restraints and returns a structure that largely complies with the restraints. Additionally, it measures the consistency between the restraints and sequences. We consider restraints as a form of edge information and thus use the edge bias in the evoformer MSA attention block (defined as MSA bias) and IPA (defined as IPA bias) (Figure 1A, 1B). Moreover, we experimented with the pair representation update in evoformer (defined as pair bias) and adopted the structure module (defined as structure bias) to ensure that the structure follows the restraints in one update. We evaluated the impact of the four types of bias information and found that MSA and IPA biases work the best (SI and Figure S1). Therefore, we use only the first two bias forms in the following experiments.

We implemented RASP using MindSpore[20] and trained it on 32 * Ascend910 NPUs. We initialized the model with MEGA-Fold[13] weights and fine-tuned it on the PSP dataset with a true structure: distillated structure ratio of 1:3. We sampled pairwise restraints to tolerate distance noise (refer to Methods). The training converged after 15k steps (480k samples in total, Figure S2) and demonstrated stable improvement over initial MEGA-Fold.

Although the model supports templates in prediction and could improve performance with template used, for fairness and to avoid data leakage, we chose not to utilize templates in this research. We tested the model's performance on the new validation set, which contains 490 samples of CAMEO[21,22,23,24] targets and unique proteins between October 2021 and March 2022. This validation set is strictly after the PDB and sequence deposition time of training set. When restricting the number of restraints to 100, the TM-score improved significantly for the structure prediction in the new validation set (Figure 1C). Furthermore, the model followed the randomly sampled restraints much better than those predicted by AlphaFold or MEGA-fold, as expected (Figure 1D and Figure S3). Moreover, the violation loss which measures bond and angle violation for RASP predictions remained low with a median of 0.0012 (Figure S4), indicating its capability to predict structures following basic physiochemical principles.

RASP helps structure prediction and evaluation in a broad range of restraints numbers

We discovered that the structure accuracy improves steadily as the number of restraints increases, starting from zero (Figure 2A). However, restraints recall remains relatively constant, implying that the current model can tolerate different numbers of prior information or restraints without adversely affecting the baseline model performance (Figure 2B). Additionally, the pLDDT score of the model serves as an indicator of the model's confidence in the restraints. For proteins with varying numbers of restraints, the pLDDT score rises stably though not significantly with an increase in the number of restraints applied. The pLDDT confidence correlates well with the corresponding structure TM-score with an overall correlation of 0.68 (Figure 2C).

Despite the difference in restraint numbers, due to sampling randomness, some restraints might provide repeating information with MSAs (and potentially templates, although templates is not used here for fairness), and in reality the restraints information provided by experiment may not necessarily be right. The restraint quality therefore could be considered in two aspects: one is how much additional information it provides aside from that provided by MSA and templates, another is how accurate the restraint information is. To examine the ability of the confidence score to distinguish good and bad predictions for the same protein with different additional restraints information, we first examined the confidence-TM-score correlation for proteins with at least one prediction not very good (defined as TM-score lower than 0.80). The average correlation score is 0.62 (Figure 2D). Since the same MSA is used for predictions of the same protein, and better structures can be attributed to more effective restraint information, this indicates that the pLDDT score can largely be used to distinguish better structures and better corresponding restraints. Furthermore, when incorrect restraints are intentionally used (restraints with a Cβ distance greater than 12 Angstroms, as defined), the TM-score decreases significantly along with the increasing incorrect ratio and fixed

number of 20 restraints (Figure 2E), suggesting that the model can tell inconsistent predictions and tend not to give bad structures. The TM-scores correlate well with the pLDDT scores with an overall correlation of 0.72 (Figure 2F and S5). These findings indicate that the pLDDT score can gauge how well the restraints may assist in structure prediction and the restraint's quality or self-consistency, both with restraints that may not be helpful and with bad restraints present. With this evaluation, the model may find applications in areas such as NMR determination (see section below).

RASP improve structure prediction assisted by pseudo and NMR restraints

By incorporating restraints, the model demonstrates improved capacity to predict the structures of multidomain and few-MSA proteins. Two cases representative of this improvement in the new validation set are 6XMV and 7NBV(Figure 3A and 3B). 6XMV is a multi-domain protein that exhibits wrongly predicted relative domain positions by both AlphaFold and Mega-Fold. However, utilizing randomly sampled restraints corrects the inter-domain positions. For 7NBV, which is a virus protein and only has three sequences in its multiple sequence alignment, an increase in the number of randomly sampled restraints leads to a stable improvement in structure quality, with 50 restraints being enough to generate a prediction with a TM-score higher than 0.7. These outcomes demonstrate the potential for using restraints to aid in the prediction of few-MSA and multi-domain proteins.

NMR is a commonly used experimental structure determination method that generates restraints of different magnitudes. Despite that in many cases AlphaFold predictions follow the restraints similar or even better than deposited NMR PDB structures[25,26], AlphaFold does not naturally foresee structures compatible with NMR restraints and may produce alternative structures as opposed to those deposited in the PDB. Given the continued evolution of NMR data deposit requirements and the length of time during which samples may be deposited, some entries in the PDB and BMRB database may not include restraint files. Following filtration of NMR samples deposited in the RCSB PDB bank with restraint files (.mr) available and bad AlphaFold predictions (long-term restraint recall lower than 90%), 187 samples remain. The samples exhibit a wide variation in the overall number of NMR restraints, from tens to thousands, with a median restraint quantity of 11.9 per residue. When leveraging NMR restraints to aid in structure prediction, the predicted structures better adhere to the restraints than AlphaFold predictions, both for overall restraints and especially for long-term restraints (defined as sequence separation ≥ 4 in this work), with restraint recall increasing from 95.1% to 98.9% and 78.4% to 95.5%, correspondingly(Figure 3C). The structures generated by RASP are interestingly more consistent with the deposited structures (Figure 3D).

NMR NOESY assignment pipeline FAAST

With the ability of the RASP model to take restraints from a wide range of sources and evaluate their quality with pLDDT scores, it has the potential to accelerate NMR NOESY peak assignments. These assignments accumulate over assigning iterations - starting with only a few correctly identified restraints - and lead to refined structure predictions. By

combining the RASP model with the ARIA assignment protocol, we were able to build an iterative NMR analysis pipeline called FAAST (Figure 4A). FAAST takes chemical shift and NOE peak lists as input and outputs peak assignment and structure ensembles. Each iteration involves subsampling the assigned restraints with an increasing ratio from the previous iteration as RASP input and generating an ensemble of 20 structures, which is then used for the subsequent NOE peak assignment. As pLDDT scores reflect the restraint quality, if the median pLDDT of the ensemble is lower than 80, we restart the second round of iteration with a lower restraint subsampling ratio to reduce restraints conflict (Figure 4B). The protocol allows for a maximum of one restart, resulting in a total ensemble iteration number of 2 or 5.

We benchmarked the FAAST pipeline on samples from ARTINA. Out of the 100 ARTINA samples, only 57 had both chemical shift and at least one 3D NOESY peak list deposited on BMRB and can be identified from the nmrstar files. We validated the NMR pipeline on all of the 57 samples. With a median time of 32 minutes (minimum and maximum time of 14 and 103 minutes), we were able to assign an median of 1569 peaks per sample, with a median peak number of 14.75 per residue(Figure 4C). Furthermore, the median pairwise mutual C-alpha RMSD for the structure ensemble is 0.86 (Figure 4D), indicating consistency between subsampled restraints and resulting structure ensemble. We wish to note that pairwise RMSDs from the structure bundle in the initial iteration have a median 2.01, higher than that from the final structures, indicating that the subsampling strategy is able to generate diversified structures, and that iterative refinement leads to convergence in structure ensemble.

Moreover, the predicted structure is consistent with simultaneously assigned restraints. On median, 99.6% of the identified restraints match the highest confidence structure and 99.0% for identified long-term restraints. In comparison, the model 1 structure and restraints from the PDB database conform on a median of 98.6% and 98.2% for all restraints and long-term restraints, respectively (Figures 4E and S4).

The predicted structures not only agree with the assigned peaks but are also consistent with the deposited PDB data. For the prediction with highest confidence, the median backbone RMSD against the deposited PDB model 1 is 0.785 Angstrom for structured regions defined by ARTINA. For the median scored structure in the structure ensemble, the backbone RMSD is 0.791 Angstrom against the PDB structure. Both are lower than that reported by ARTINA, in which the median RMSD is 1.44A for all samples and 1.47A for the 57 samples with BMRB peak lists (Figure 4F). Moreover, 96.9% of the deposited restraints from PDB database align with the predicted structure ensemble.

With only processed NOESY peak lists available and raw peak lists absent for samples downloaded directly from BMRB, we validated the pipeline's performance on the 2MRM case with raw NOESY peak lists provided by the experimental laboratory. For this YgaP protein, much more restraints can be assigned from the raw peak lists than from the deposited NOE peak lists (14.19 per residue for raw lists compared to 4.93 for deposited ones). The number of assigned long-term restraints is also higher (366 for raw lists and 285 for deposited lists). Despite similar small mutual RMSDs, the two predicted structures have similar TM-scores to the deposited structure (0.862 and 0.857), even though the restraints assigned from the raw peak list are in better consistency with those assigned from deposited lists, with the former recall of 98.2% and the latter of 94.9%. These results indicate that the pipeline

doesn't require strict peak assignment, and we expect the raw peak lists from NOE spectra will provide better assignment in the FAAST pipeline compared to the deposited peaks.

In summary, we have presented a fast NMR pipeline that provides accurate structure ensemble and highly consistent NOE peak assignments. Compared to previous methods, this pipeline is fast, and through restraints iteration and subsampling, can provide a structure ensemble plus a full set of NOE peak assignments compared to deep learning tools like AlphaFold. We expect this FAAST pipeline to perform better with raw peak lists.

Discussion

The question of how experimental results and AI methods could mutually benefit each other has been a topic of discussion, particularly with the emergence of advanced biochemical deep learning models. Here, we present the RASP model and the FAAST pipeline, wherein the former utilizes prior knowledge or restraints to improve in silico structure predictions, while the latter employs the former's flexible number restraint-taking capability and evaluation of restraint-structure quality to accelerate NOESY peak assignment. This model and pipeline underscore the self-consistency of the two questions as an AI method capable of being assisted by external knowledge has the potential to facilitate the acquisition of that external knowledge in return.

Despite the application of the RASP model on NMR restraints, due to its improvement of structure prediction with abstract randomly sampled restraints, flexibility in restraint number and ability to evaluate restraints, we expect it to be used for broad knowledge types, such as cross-linking or covalent labeling data as in AlphaLink, even abstract prior knowledge such as closeness of two residues regardless of the knowledge source, and in this way may help the generation of dynamic structures or states guided by restraints.

While we have currently applied our standard pipeline in FAAST for benchmark, parameters for RASP and CCVP steps can be flexibly adjusted by users to accommodate their particular peak quality and expectations on peak-structure convergence. When benchmarking the pipeline, we did not employ parallel computation considering the possibly limited computational resources for users. However, both the RASP prediction and relaxation can be executed parallelly, which is expected to accelerate the process up to 20 times depending on the hardware available. Since the chemical shift and NOE peak assignment could be iteratively improved, merging the chemical shift and peak assignment pipelines is also expected to produce more comprehensive and accurate NMR protein assignment pipelines.

Moreover, for now we only applied 3D NOESY spectra for source of restraints, we expect the current pipeline could be expanded to more NMR data types such as 4D NOESY spectra, as long as the restraints could be formatted as pairwise restraints. Diverse experimental data types that may provide differing information for various molecule types, such as NMR for protein-small molecule interactions exist. In addition to the conventional paired restraints, we expect to incorporate additional information forms(e.g. torsion angle and PRE in NMR) into our structure prediction and to develop multimer and interface prediction models. These restrained structure prediction models hold the potential to introduce an alternative approach to restrained design.

Data Availability

The RASP and FAAST code will be available at
https://gitee.com/mindspore/mindscience/tree/master/MindSPONGE/applications/FAAST/.

References

1. Kay L E. NMR studies of protein structure and dynamics[J]. Journal of magnetic resonance, 2011, 213(2): 477-491.
2. Wüthrich K. Protein structure determination in solution by NMR spectroscopy[J]. Journal of Biological Chemistry, 1990, 265(36): 22059-22062.
3. Klukowski P, Riek R, Güntert P. Rapid protein assignments and structures from raw NMR spectra with the deep learning technique ARTINA[J]. Nature Communications, 2022, 13(1): 6151.
4. Güntert P, Buchner L. Combined automated NOE assignment and structure calculation with CYANA[J]. J Biomol NMR, 2015, 62:453–471.
5. Nilges M, Macias MJ, O'Donoghue SI, Oschkinat H. Automated NOESY interpretation with ambiguous distance restraints: the refined NMR solution structure of the pleckstrin homology domain from beta-spectrin[J]. J Mol Biol, 1997, 269:408–422.
6. Rieping W, Habeck M, Bardiaux B, et al. ARIA2: automated NOE assignment and data integration in NMR structure calculation[J]. Bioinformatics, 2007, 23:381–382.
7. Herrmann T, Güntert P, Wüthrich K. Protein NMR structure determination with automated NOE assignment using the new software CANDID and the torsion angle dynamics algorithm DYANA[J]. J Mol Biol, 2002, 319:209–227.
8. Jumper J, Evans R, Pritzel A, et al. Highly accurate protein structure prediction with AlphaFold[J]. Nature, 2021, 596(7873): 583-589.
9. Evans R, O'Neill M, Pritzel A, et al. Protein complex prediction with AlphaFold-Multimer[J]. BioRxiv, 2021, biorxiv: 2021.10.04.463034.
10. Terwilliger T C, Poon B K, Afonine P V, et al. Improved AlphaFold modeling with implicit experimental information[J]. Nat Methods, 2022, 19:1376–1382.
11. Terwilliger T C, Afonine P V, Liebschner D, et al. Accelerating crystal structure determination with iterative AlphaFold prediction[J]. Acta Crystallographica Section D: Structural Biology, 2023, 79(3).
12. Stahl K, Graziadei A, Dau T, et al. Protein structure prediction with in-cell photo-crosslinking mass spectrometry and deep learning[J]. Nature Biotechnology, 2023: 1-10.
13. Liu S, Zhang J, Chu H, et al. PSP: million-level protein sequence dataset for protein structure prediction[J]. arXiv preprint arXiv:2206.12240, 2022.
14. Eastman P, Swails J, Chodera JD, et al. Openmm 7: Rapid development of high performance algorithms for molecular dynamics[J]. PLOS Computational Biology, 2017, 13(7):1–17.

15. Berman H M, Westbrook J, Feng Z, et al. The protein data bank[J]. Nucleic acids research, 2000, 28(1): 235-242.

16. Hoch J C, Baskaran K, Burr H, et al. Biological Magnetic Resonance Data Bank[J]. Nucleic Acids Research, 2023, 51(D1): D368-D376.

17. Zhang Y, Skolnick J. Scoring function for automated assessment of protein structure template quality[J]. Proteins, 2004, 57: 702-710.

18. Xu J, Zhang Z. How significant is a protein structure similarity with TM-score=0.5?[J]. Bioinformatics, 2010, 26: 889-895.

19. Zhang Y, Skolnick J. TM-align: A protein structure alignment algorithm based on TM-score[J]. Nucleic Acids Research, 2005, 33: 2302-2309.

20. https://www.mindspore.cn/

21. Robin X, Haas J, Gumienny R, et al. Continuous Automated Model EvaluatiOn (CAMEO)—Perspectives on the future of fully automated evaluation of structure prediction methods[J]. Proteins: Structure, Function, and Bioinformatics, 2021, 89(12): 1977-1986.

22. Haas J, Gumienny R, Barbato A, et al. Introducing "best single template" models as reference baseline for the Continuous Automated Model Evaluation (CAMEO)[J]. Proteins: Structure, Function, and Bioinformatics, 2019, 87(12): 1378-1387.

23. Haas J, Barbato A, Behringer D, et al. Continuous Automated Model EvaluatiOn (CAMEO) complementing the critical assessment of structure prediction in CASP12[J]. Proteins: Structure, Function, and Bioinformatics, 2018, 86: 387-398.

24. Haas J, Roth S, Arnold K, et al. The Protein Model Portal—a comprehensive resource for protein structure and model information[J]. Database, 2013, 2013:bat031.

25. Tejero R, Huang Y J, Ramelot T A., Montelione G T. AlphaFold Models of Small Proteins Rival the Accuracy of Solution NMR Structures[J]. Frontiers in Molecular Biosciences, 2022, 9:877000.

26. Li E H, Spaman L, Tejero R, et al. Blind Assessment of Monomeric AlphaFold2 Protein Structure Models with Experimental NMR Data[J]. BioRxiv preprint, 2023, biorxiv: 2023.01.22.525096.

Figure 1. RASP model takes in restraints in different forms and outperforms AlphaFold with restraint assistance. **A**. is a scheme of how the pairwise restraints can be taken into the model in the form of MSA, pair, IPA, and structure biases, adopted from the evoformer and structure module in AlphaFold. **B**. is the more detailed illustration of the model structure with restraints treated as biases in the evoformer block (left) and structure block (right). **C**. For the new validation set, RASP with a fixed number of randomly sampled input restraints outperforms AlphaFold on the TM-score between the PDB structure and predicted structure and **D**. on restraint recall.

Figure 2. RASP is robust against restraint number and the confidence score can be used to evaluate restraint quality. **A**.The TM-score of predicted structure by RASP steadily increases over both AlphaFold and MEGA-Fold, with increasing number of input restraints, and meanwhile **B**. regardless of the restraint number, the restraint recall is steady above that with no restraints applied for AlphaFold, MEGA-Fold, and RASP with zero restraints. The restraint recall for those without input restraints is calculated with a fixed number of randomly sampled contacts by the same sampling strategy as input restraints. **C**. The pLDDT with different restraints number and information quality correlates well with the real TM-score of the predicted structure and deposited PDB structure, with an overall correlation coefficient of 0.68. **D**. is the distribution of correlation coefficient between the predicted pLDDT confidence and TM-score with different number of restraints in use. The distribution is drawn for validation samples with at least one bad prediction

with TM-score<0.8, since we are more interested in the model ability to distinguish bad or inefficient restraints information from the good ones than to tell the best from a bunch of very good structures with efficient restraints. The pLDDT confidence and TM-score are largely positively correlated with a median of 0.62, suggesting that pLDDT score can be regarded as an indicator how much additional information input restraints provide. **E**. The TM-score decreases with decreasing percentage of good restraints, when total input restraints number is fixed at 20. **F**. The pLDDT confidence still correlates well with the TM-scores when bad restraints are present, with an overall correlation coefficient of 0.72, demonstrating the RASP model ability in telling bad restraint information and reporting this at the same time.

Figure 3. Input restraints can assist RASP prediction for multi-domain proteins, few-MSA proteins, and NMR structure prediction. **A**. For multi-domain structure 6XMV, both AlphaFold and MEGA-fold provide inaccurate relative domain positions, however with restraints RASP is able to fix the inter-domain structure. **B**. For 7NBV with few MSAs, restraint assisted prediction by RASP helps to improve the structure prediction with more accurate secondary structure and relative position between the helices and beta-sheets. **C**. With varied number of deposited .mr restraints provided by the PDB databank, NMR structures that fail for AlphaFold prediction can be fixed in terms of overall and long-term (sequence separation ≥ 4) restraint recall and **D**. TM-score that measures the similarity between the predicted structure and the deposited ones.

Figure 4. The FAAST NOESY assignment pipeline provides fast and accurate structure ensemble and NOE peak assignment at the same time. **A.** is the schematic figure of the FAAST workflow. **B.** shows the current assignment pipeline and parameters applied. In each iteration block, the first parameter is the percentage of input restraints subsampled for RASP structure prediction in order

to construct a structure bundle, the second parameter is the cumulative probability to rule out ambiguous restraints in assignment, which is also adjustable in ARIA. **C**. is the distribution for number of NOE assignments per residue for the 57 ARTINA samples. The median number is around 15 with peak lists from the BMRB database. **D**. is the distribution for pairwise mutual RMSD for C-alpha atoms of the structure bundle. The median pairwise RMSD is 0.86, indicating the predicted structures within each bundle are close to each other. **E**. is the restraint recall comparison between the FAAST structure and the deposited PDB for the deposited NMR restraints. The solved FAAST structures better follow the NMR restraints than the PDBs. **F**. The FAAST structures also exhibit lower backbone RMSD than those reported by ARTINA.