Title:

Using artificial intelligence to document the hidden RNA virosphere

Author list and affiliations:

Xin Hou[1,18], Yong He[2,18], Pan Fang[2], Shi-Qiang Mei[1], Zan Xu[2], Wei-Chen Wu[1], Jun-Hua Tian[3], Shun Zhang[2], Zhen-Yu Zeng[2], Qin-Yu Gou[1], Gen-Yang Xin[1], Shi-Jia Le[1], Yin-Yue Xia[4], Yu-Lan Zhou[5], Feng-Ming Hui[6,7], Yuan-Fei Pan[8], John-Sebastian Eden[9], Zhao-Hui Yang[10], Chong Han[11], Yue-Long Shu[12], Deyin Guo[13], Jun Li[14], Edward C. Holmes[9,15,19*], Zhao-Rong Li[2,19*] & Mang Shi[1,16,17,19,20*]

[1]National Key Laboratory of Intelligent Tracking and Forecasting for Infectious Diseases, State Key Laboratory for Biocontrol, School of Medicine, Shenzhen Campus of Sun Yat-sen University, Sun Yat-sen University, Shenzhen, China.

[2]Apsara Lab, Alibaba Cloud Intelligence, Alibaba Group, Hangzhou, China.

[3]Wuhan Centers for Disease Control and Prevention, Wuhan, China.

[4]Polar Research Institute of China, Shanghai, China.

[5]Department of Nursing, The Fifth Affiliated Hospital, Sun Yat-sen University, Zhuhai, China.

[6]School of Geospatial Engineering and Science, Southern Marine Science and Engineering Guangdong Laboratory (Zhuhai), Sun Yat-sen University, Zhuhai, China.

[7]Key Laboratory of Comprehensive Observation of Polar Environment, Ministry of Education, Sun Yat-sen University, Zhuhai, China.

[8]Ministry of Education Key Laboratory of Biodiversity Science and Ecological Engineering, National Observations and Research Station for Wetland Ecosystems of the Yangtze Estuary, Institute of Biodiversity Science and Institute of Eco-Chongming, School of Life Sciences, Fudan University, Shanghai, China.

[9]School of Medical Sciences, The University of Sydney, Sydney, NSW 2006, Australia.

[10]College of Life Sciences, Zhejiang University, Hangzhou, China.

[11]School of life science, Guangzhou University, Guangzhou, China.

[12]School of Public Health (Shenzhen), Shenzhen campus of Sun Yat-sen University, Sun Yat-

sen University, Shenzhen, China.

[13]Guangzhou National Laboratory, Guangzhou International Bio-Island, Guangzhou, China.

[14]Department of Infectious Diseases and Public Health, Jockey Club College of Veterinary

Medicine and Life Sciences, City University of Hong Kong, Hong Kong, China.

[15]Laboratory of Data Discovery for Health Limited, Hong Kong SAR, China.

[16]Shenzhen Key Laboratory for Systems Medicine in Inflammatory Diseases, Shenzhen

Campus of Sun Yat-sen University, Sun Yat-sen University, Shenzhen, China.

[17]Guangdong Provincial Center for Disease Control and Prevention, Guangzhou, China.

Author list footnotes:

41 [18]These authors contributed equally

42 [19]Senior authors

43 [20]Lead contact

Contact information:

46 *Correspondence: Mang Shi (shim23@mail.sysu.edu.cn); Zhao-Rong Li

47 (zhaorong.lzr@alibaba-inc.com); and Edward C. Holmes (edward.holmes@sydney.edu.au)

In brief

50 A deep learning algorithm (LucaProt) that integrates both sequence and predicted structural

51 information was employed to identify highly divergent RNA viral "dark matter" in 10,487

52 metatranscriptomes from diverse global ecosystems. A total of 161,979 potential RNA virus

53 species and 180 RNA virus supergroups was unveiled using this AI approach, including many

54 understudied groups.

Summary

Current metagenomic tools can fail to identify highly divergent RNA viruses. We developed a

deep learning algorithm, termed LucaProt, to discover highly divergent RNA-dependent RNA

polymerase (RdRP) sequences in 10,487 metatranscriptomes generated from diverse global

ecosystems. LucaProt integrates both sequence and predicted structural information, enabling

the accurate detection of RdRP sequences. Using this approach we identified 161,979

potential RNA virus species and 180 RNA virus supergroups, including many previously

poorly studied groups, as well as RNA virus genomes of exceptional length (up to 47,250

nucleotides) and genomic complexity. A subset of these novel RNA viruses were confirmed

by RT-PCR and RNA/DNA sequencing. Newly discovered RNA viruses were present in

diverse environments, including air, hot springs and hydrothermal vents, and both virus

diversity and abundance varied substantially among ecosystems. This study advances virus

discovery, highlights the scale of the virosphere, and provides computational tools to better

document the global RNA virome.

Introduction

RNA viruses infect a diverse array of host species. Despite their omnipresence, the pivotal role of RNA viruses as major constituents of global ecosystems has only recently garnered recognition due to large-scale virus discovery initiatives in animals,[1,2] plants,[3] fungi,[4] aquatic environments,[5] marine,[6] soil environments,[7] and planetary metatranscriptomes.[8] A common characteristic of these studies is their reliance on the analysis of RNA-dependent RNA polymerase (RdRP) sequences, a canonical component of RNA virus genomes. Collectively, these studies have led to the identification of tens of thousands of novel virus species, resulting in at least a 10-fold expansion of the virosphere and the proposal of new phylum-level virus groups such as the "*Taraviricota*" (i.e., "quenyaviruses").[6,9] Similarly, the data mining of metatranscriptomes from diverse ecosystems has revealed several divergent clades of RNA bacteriophage,[10,11] while recent metatranscriptomic studies have led to a remarkable 5-fold expansion in the diversity of viroid-like circular RNAs.[12-14] Despite such progress in uncovering RNA virus diversity through ecological sampling and sequencing, it is probable that more divergent groups of RNA viruses remain to be discovered.[9,15] This is in part because the current tools for metagenomic identification of RNA viruses can miss some highly divergent RdRPs.[16] It is therefore imperative to develop innovative strategies for the efficient identification of the full spectrum of RNA virus diversity.

Over the past decade, artificial intelligence (AI) related approaches, especially deep learning algorithms, have had a major impact on various research fields in the life sciences, such as molecular docking, compound screening and interaction, protein structure prediction and functional annotation, and infectious disease modelling.[17-22] This progress can be attributed to the advantages of deep learning algorithms over classic bioinformatic approaches, including enhanced accuracy, superior performance, reduced reliance on feature engineering, flexible model architectures, and self-learning capabilities.[23,24] Recently, deep learning approaches, such as CHEER, VirHunter, Virtifier and RNN-VirSeeker have been developed and applied to the identification of viruses from genomic and metagenomic data.[25-28]

These tools employ convolutional neural networks (CNNs) and recurrent neural networks (RNNs). CNNs are specifically designed for processing spatial data such as images

and leverage convolutions to exploit local correlations,[29] whereas RNNs are adept at handling

sequential data by capturing temporal dependencies and serial order memory.[30] Despite their

versatility, both face limitations in processing biological sequences: CNNs may encounter

challenges with inputs of varying lengths and capturing global correlations, while RNNs

struggle with longer sequences due to vanishing or exploding gradients and difficulties in

capturing long-term dependencies. It is imperative to consider these shortcomings when

assessing their appropriateness for specific tasks. In addition, many of these methodologies

exclusively focus on nucleotide sequences, disregarding protein sequences or structural

information, thereby constraining their capacity to identify highly divergent RNA viruses.

Recently, the transformer architecture has emerged as a powerful alternative for protein

function predictions based on sequence data, effectively accommodating sequences of

varying lengths and efficiently capturing both local and long-range relationships across

sequence positions, surpassing the capabilities of CNNs and RNNs.[31-34] Consequently, the

transformer architecture can be leveraged to design better tools for identifying highly

divergent RNA viruses.

Herein, we present a transformer-based tool for RNA virus discovery that utilizes protein

sequences and the structural characteristics of viral RdRP sequences. This tool was applied to

a data set comprising 10,487 metatranscriptomes from diverse ecological systems. To validate

and perform comparative analysis, the same data set was processed using other available

bioinformatics tools, and 50 samples were analyzed using both DNA and RNA sequencing.

By employing this tool in conjunction with extensive sequence data, we demonstrate how

artificial intelligence can accurately and efficiently detect RNA viruses exhibiting genetic

divergence beyond the capabilities of traditional similarity-based methods, revealing

previously unrecognized viral diversity.

Results

Deep learning reveals the dark matter of the RNA virosphere

We performed systematic searches to expand the diversity of RNA viruses in a variety of

ecological systems sampled on a global scale (Figures 1 and 2; Tables S1 and S2).

Accordingly, a total of 10,487 metatranscriptomes (51 Tb of total sequencing data) were

assembled, which resulted in more than 1,368 million contigs and 872 million predicted

proteins. Based on this data set, potential viral RdRPs were revealed and cross-validated

using two different strategies (Figures 1A, S1-S2). The major AI algorithm used here,

denoted "LucaProt", is a deep learning, transformer-based model based on sequence and

structural features of 5,979 well-characterized viral RdRPs (positive samples) and 229,434

protein sequences that were not viral RdRPs (negative samples), including non-RdRP viral

proteins, reverse transcriptases, and cellular proteins. LucaProt demonstrated exceptional

accuracy (0.014% false positives) and specificity (1.72% false negatives) when evaluated on

the test data set (Figure 1B). Furthermore, the generalizability and robustness of LucaProt

were further confirmed through a 10-fold cross-validation analysis (Figure S2).

Independently to LucaProt, we applied a more conventional approach (i.e., "ClstrSearch")

that clustered all proteins based on their sequence similarity and then used BLAST or HMM

models to identify resemblance to viral RdRPs or non-viral RdRP proteins.

146  By merging the results of the two search strategies we discovered 513,134 RNA viral

contigs, representing 161,979 putative viral species (i.e., >90% RdRP identity), and 180 RNA

viral supergroups that are comparable to existing viral classes and phyla as defined by the

International Committee on Taxonomy of Viruses (ICTV) (Figure 1; Table S3; see Methods).

Subsequently, we performed an automatic comparison of RdRP protein sequences with a

uniform definition (identity≥0.9, aligned fraction≥0.3) among this and other studies to reveal

a total of 70,458 putative unique viral species newly identified by LucaProt (Figures 1C and

S3). Notably, we unveiled 60 previously unidentified and underexplored groups that have

received only limited attention to date[5-8,10,35] (Figures 1C and S3). Among these, 512,690

viral contigs (99.9% of total contigs) and 157 supergroups (87.2%) were identified by both

LucaProt and ClstrSearch, while an additional 444 contigs and 23 supergroups were only

identified by LucaProt (Figure 1D).

Benchmarking of LucaProt with other tools for virus discovery

To assess the sensitivity and specificity of LucaProt, we benchmarked it against four other

virus discovery tools, utilizing the same data set and RdRP database. Notably, LucaProt

exhibited the highest recall rate (i.e., proportion of correctly predicted true positives), while

maintaining a relatively low false positive rate (i.e., proportion of incorrectly predicted true

negatives as positives; Figure 3A), along with reasonable computational efficiency (Figure

3E). Specifically, in comparisons, HMMscan and PalmScan showed the highest precision

rates (99.80%, 99.46%) but the lowest recall rates (65.00%, 65.03%), while Diamond blast

and HH-suite both exhibited the highest false positive rate (0.195%, 0.573%; Figures 3A).

When considering all RdRPs identified in this study, LucaProt exhibited the most

comprehensive virus discovery (98.22%), whereas the other four virus discovery tools could

only identify a portion of the entire collection (76.82%-87.81%, Figure 3B). Importantly, our

benchmarking results demonstrated that the other virus discovery tools only identified a

minority (<42%) of the new viruses identified by LucaProt only (i.e., but not by ClstrSearch)

(Figure 3C).

Of note, LucaProt successfully recalled over 98% of the virus RdRPs identified by six

other published studies,[5-8,10,35] even though none were used in either training or testing of the

models (Figure 3D). The exception was the study of Olendraite *et al.*,[35] for which LucaProt

had a slightly lower recall rate (Figure 3D). Manual inspection and sequence alignment

revealed that the sequences from Olendraite *et al.*,[35] not detected by LucaProt lacked the core

RdRP domain region. LucaProt also outperformed CHEER, VirHunter, Virtifier and RNN-

VirSeeker RNA virus discovery tools[25-28] in terms of recall, precision and long sequence

processing (Figures 3F-3H). The advanced transformer architecture incorporated into

LucaProt allowed the parallel processing of longer amino acid sequences,[31,36] which can

better capture the relationships between residues from distant parts of sequence space than

the CNN and/or RNN encoders implemented in the other bioinformatic tools compared.

Verification and confirmation of newly identified viral supergroups

That the 180 viral supergroups identified here represented RNA rather than DNA sequences

was substantiated through multiple lines of evidence. At the sequence level, two criteria were

employed to establish a viral supergroup: the absence of similarity to cellular proteins and the

presence of key RdRP motifs (Figures 4A and S4). Moreover, the majority (60/180) of the

newly identified supergroups, including those from LucaProt, shared varying degrees of

sequence similarity with existing reference RdRPs (i.e., BLAST *e*-value≤1*E*-3 and/or had

HMM model score≥10) (Figures 4A and S4; Table S4). To validate computational predictions,

simultaneous DNA and RNA extraction and sequencing were performed on the 50

environmental samples collected in this study to examine the presence of the 115 viral

supergroups identified in these samples (Table S5). This revealed that only RNA sequencing

reads mapped to contigs associated with viral RdRPs, whereas both RNA and DNA

sequencing reads mapped to contigs linked with DNA viruses, reverse-transcriptase (RT), and

cellular organisms (Figures 4B and S5). Seventeen of 115 viral supergroups were further

confirmed by a more sensitive RT-PCR approach: this revealed an absence of sequences

encoding viral RdRP in the DNA extractions, suggesting that these viral supergroups are *bona*

fide RNA organisms (Figures 4C and S5B). Finally, a 3D alignment was used to compare the

newly identified viral RdRPs with known viral RdRPs, eukaryotic RdRPs, eukaryotic DdRPs

and RTs to determine their degree of structural similarity (Figure 4D). The new RdRP

supergroups from LucaProt contained at least three signature components of viral RdRP

structures that resulted in significantly higher structural similarity to known RNA virus

proteins (average structure similarity=3.0) than their cellular counterparts (average structure

similarity=5.8).

210   Genomic structures reveal modularity and flexibility within the RNA virosphere

We next analyzed the composition and structure of the putative RNA virus genomes

identified in this study. The length of the RdRP-encoding genomes or genome segments

differed markedly within and between viral supergroups, although most were centered around

2,131 nt (Figure 5). Notably, however, our data set also contained exceptionally long RNA

virus genomes identified from soil that belonged to the Nido-like supergroup. One of these

genomes was 47.3 kb, making it one of the longest RNA viruses identified to date[37] (Figures

5C and S6; Table S6). Interestingly, an additional ORF was identified between the 5' end of

the genome of this virus and the ORF encoding RdRP, although the function of the encoded

protein is unclear due to a lack of sequence similarity to known proteins. In addition to the

RdRP, we characterized the other predicted proteins encoded by the newly identified virus

genomes. While most had no homologs in existing databases, we identified some that were

related to structural (e.g., coat, capsid, glycoprotein and envelope proteins) and non-structural

(e.g., helicase, protease, methyltransferase, movement protein, immune or host-related

regulatory proteins) proteins from known viruses (Figure 5D). Importantly, the presence of

these additional virus proteins in newly identified supergroups provided further evidence that

they were from *bona fide* RNA viruses. Furthermore, the presence of phage-related proteins

(i.e., phage coat, phage mat-A and phage integrase) indicates that some of the viruses likely

infect prokaryotic hosts, although further validation is required. In addition, the occurrence of

these proteins was incongruent with virus phylogenetic history as inferred from RdRP

sequences (Figure 5E), indicative of a modular-like configuration of RNA virus genomes.

Expanded phylogenetic diversity of RNA viruses

The expansion of the RNA virosphere at the level of virus species – a 55.9-fold increase

(251,846/4,502) from those defined by ICTV and a 1.4-fold increase (251,846/181,388) from

all previously described RdRP sequences – is also evident in both the enlargement of known

virus groups (e.g., phyla, orders, families) and the identification of entirely novel groups

(Figure 6). Many of viruses discovered here formed clades that were distinct from the

lineages observed in previously described virus supergroups (Figure 6). Interestingly, several

groups previously represented by only a limited number of genomes – namely the Astro-Poty,

Hypo, Yan and Cysto clades – experienced a major expansion to encompass larger viral

clusters with greater phylogenetic diversity (Figure 6). Several newly identified supergroups

also had high levels of phylogenetic diversity, including SG023 (1,232 virus species), SG025

(466 virus species), and SG027 (475 virus species), suggesting that more highly divergent

RNA viruses will be discovered in environmental samples. Following our analysis, the

supergroups with the greatest number of virus species here were the Narna-Levi (58,063 virus

species), Picorna-Calici (19,970 virus species), and Tombus-Noda (15,520 virus species).

Ecological structure of the global RNA virome

Our analysis revealed the ubiquitous presence of RNA viruses across diverse ecosystem

subtypes (32 categories) and in 1,612 locations globally. Despite repeated efforts to uncover

the diversity of RNA viruses from such ecological samples,[5-8,10,35] 33.3% of viral groups

detected by LucaProt were not described previously (Figure 7A). Indeed, despite an overall

deceleration, the rate of RNA virus discovery has not reached a plateau (Figure 7B),

highlighting the vast untapped diversity of the global RNA virosphere. This is especially

evident in soil environments, where there has been a notable increase in virus discovery.[10]

To help identify any ecological patterns we compared alpha diversity (measured by the

Shannon index) and abundance levels (measured by the number of reads per million total

non-rRNA reads, i.e., RPM) of the RNA virome among diverse ecosystem subtypes (Figures

7C and 7D; Table S7). In general, average alpha diversity was highest in leaf litter, wetland,

freshwater and wastewater environments, while virus abundance reached its peak in Antarctic

sediment, marine sediment, and freshwater ecosystem subtypes, with average RPMs ranging

from 18,424.6 to 46,685.5 (Figure 7C). In contrast, the lowest average diversity and

abundance were in halite and subsurface environments (Figure 7C), which as expected due to

their low biomass (i.e., host cells). For extreme ecological subtypes such as hot springs and

hydrothermal vents, the associated RNA viruses were characterized by low diversity but

moderate abundance (1,528.9 ~ 3,726.9 average RPM) (Figure 7C). It is also noteworthy that

the new viral supergroups established in this study were predominantly found in aquatic and

sediment samples, with only a few occurrences in vertebrate and invertebrate animal samples

(Figure 7C).

Our results further revealed the prevalence and abundance levels of particular viral

groups across ecosystem subtypes (Figure 7D). Of note, the majority (85.9%) of the viruses

discovered here only occurred in a single ecosystem subtype. Others, however, may be

ecological generalists. For example, members of the Narna-Levi, Partiti-Picobirna and

Picorna supergroups as well as Tombus-Noda supergroup were found in more than 32

ecosystem subtypes (Figure S7). Finally, we identified "marker" virus species, that exhibited

high prevalence and abundance exclusively within specific ecosystem subtypes (Figure 7D),

consistent with previous reports.[6,10] Among these, *Partiti-Picobirna sp.*1991 and *Partiti-*

Picobirna sp. 5447 were associated with hot springs, while *Tombus-Noda sp.* 2765 and

Supergroup 026 sp. 2205 were associated with hydrothermal vents, suggesting a likely

relationship with specialized hosts adapted to these environments.[38,39] However, since the

data sets analyzed here were generated by different laboratories employing distinct sample

processing, library preparation and sequencing procedures, the comparisons of viral diversity

and abundance among different ecosystem subtypes were necessarily subject to systemic

biases.

Discussion

The accurate identification of highly divergent RNA viruses remains a major challenge,

impeding a comprehensive understanding of the genetic diversity in the RNA virosphere and

hindering advancements in RNA virus evolution and ecology.[16,40] Indeed, the conventional

approach for RNA virus discovery has heavily relied on sequence similarity comparisons and

the completeness of sequence databases.[40,41] To address these issues, we developed a data-

driven deep learning model (i.e., LucaProt) that outperforms conventional methods in

accuracy, efficiency, and most importantly, the breadth of virus diversity detected.

Importantly, LucaProt not only incorporated sequence data but also integrated structural

information, which is crucial for accurate prediction of protein function, especially in the case

of the RdRP.[42] Without implementing the structural model, LucaProt had only 41.8% and

94.9% specificity and accuracy, respectively, on the test data set, and could only detect 44.5%

of the predicted RdRP proteins. Hence, conservation of RdRP structure outweighs the

significance of RdRP sequences in the identification of highly divergent RNA viruses.

Collectively, we have established an AI framework paradigm for large-scale RNA virus

discovery that can be readily extended to the accurate description of any biological "dark

matter" once the training data set is prepared.

All the RNA viral sequences identified in this study were classified into clusters and

supergroups, with the latter subsequently compared to viral classes and phyla as defined by

the ICTV.[43,44] Among the supergroups identified in this study, only 21 contained those from

viral phyla/classes currently classified by ICTV, such that there was a 8.6-fold expansion of

RNA virus diversity at the supergroup level compared to the latest ICTV report,[43] and a 1.5-

fold expansion of all RNA viruses described so far[5-8,10,35] (Figure 1C). This expansion

encompasses both existing viral supergroups as well as the discovery of 60 highly divergent

supergroups that have largely been overlooked in previous RNA virus discovery projects

(Figure 1D). The virus supergroups identified here were largely comparable to the existing

classification system at the phylum (e.g., phylum *Lenarviricota* in the case of the Narna-Levi

supergroup) or class (e.g., the *Stelpaviricetes, Alsuviricetes, Flasuviricetes* classes for the

Astro-Poty, Hepe-Virga, Flavi supergroups) levels, highlighting the extent of the phylogenetic

diversity identified here.

Despite the large expansion in RNA virus diversity documented here, major gaps remain

in our understanding of the evolution and ecology of the newly discovered viruses. In

particular, the hosts for most of the viruses identified remain unknown. As the majority of

current known RNA viruses infect eukaryotes,[45,46] and microbial eukaryotes exist in great

abundance and diversity in natural environments,[47,48] it is possible that the viral clades and

supergroups identified here were largely associated with diverse microbial eukaryotic hosts.

However, it is also likely that a substantial proportion of the novel viruses discovered are

associated with bacterial (and perhaps archaeal) hosts.[49-51] Indeed, mounting evidence[10,52]

strongly supports the notion that more groups of RNA viruses than currently documented are

associated with bacteria. Indeed, the presence of RNA bacteriophage in multiple RNA viral

supergroups underlines the evolutionary connection between RNA viruses from bacterial and

eukaryotic hosts. If viewed through the lens of virus-host co-divergence,[1,2,53] such a link

suggests that the evolutionary history of RNA viruses is at least as long, if not longer, than

that of the cellular organisms.

Limitations of the study

Our study has several limitations. First, classifying viruses on a deep evolutionary scale

remains a complex and challenging task due to the very high levels of genetic divergence

exhibited by these viruses. This divergence is so pronounced that neither sequence nor

structural homology can adequately uncover their true evolutionary histories. Second, while

we successfully confirmed the RNA nature of some virus supergroups through RNA and

DNA sequencing of the same sample, we could not apply this method to other viral

supergroups. This limitation arose because these supergroups were identified using data from

the SRA database that lack matching DNA sequencing data. Finally, the viral genomes we

identified only contain segments associated with the RdRP. For segmented viruses, this

means we only uncovered partial genomes, with the greater sequence divergence in non-RdRP segments hindering their identification. Future efforts using more generalized models could potentially identify all viral segments. AI models could be expanded to detect viral functional proteins beyond RdRP, enabling the identification of segments encoding highly divergent viral proteins. Alternatively, as all viral genome segments must have broadly matching levels of abundance (i.e. co-occur) as the RdRP, the detection of sequences at similar abundance to the RdRP could be used to identify additional segments, particularly if this pattern of co-occurrence is found in multiple libraries.

ACKNOWLEDGMENTS

This work was supported by the National Natural Science Foundation of China (82341118, 32270160), the Shenzhen Science and Technology Program (KQTD20200820145822023 and JCYJ20210324124414040), the Natural Science Foundation of Guangdong Province (2022A1515011854), the Guangdong Province "Pearl River Talent Plan" Innovation and Entrepreneurship Team Project (2019ZT08Y464), the Hong Kong Innovation and Technology Fund (ITF) (MRP/071/20X), and the Health and Medical Research Fund (COVID190206). E.C.H. is funded by a National Health and Medical Research Council (Australia) Investigator grant (GNT2017197) and by AIR@InnoHK administered by the Innovation and Technology Commission, Hong Kong Special Administrative Region, China. We thank the Computing and Storage teams of Alibaba Cloud Computing Co., Ltd. and Zhejiang laboratory for their contribution of 15 machines with 128 CPUs and 1T RAM of Elastic High-Performance Computing (EHPC), 64 Nvidia A100 Graphics Processing Units (GPUs), and 500TB of Network Attached Storage (NAS) resources.

AUTHOR CONTRIBUTIONS

Conceptualization, X.H., Y.H., E.C.H., Z.-R.L. and M.S.; Methodology, X.H., Y.H., J.-S.E., J.L., Z.-R.L. and M.S.; Investigation, X.H., Y.H., P.F., S.-Q.M., Z.X. and Q.-Y.G.; Writing – Original Draft, X.H., Y.H., E.-C.H. and M.S.; Writing – Review and Editing, All authors. Funding Acquisition, F.-M.H., Y.-L.S., D.-Y.G., Z.-R.L. and M.S.; Resources (sampling),

370 X.H., S.-Q.M., W.-W.C., J.-H.T., G.-Y.X., S.-J.L., Y.-Y.X., Y.-L.Z., F.-M.H., Y.-F.P., Z.-H.Y.

371 and C.H.; Resources (computational), S.Z., Z.-Y.Z. and Z.-R.L.; Supervision, Z.R.L. and M.S.

DECLARATION OF INTERESTS

374 The authors declare no competing interests.

Main figure titles and legends

Figure 1. The global RNA virosphere.

(A) RNA virus discovery pipeline. The pathway for sequence homolog-based virus discovery

is highlighted in blue on the left, including the clustering, expand and merge steps. The RdRP

AI modeling pathway is highlighted in orange on the right, including the modeling, clustering

and merge steps.

(B) Number of viral supergroups discovered using two methods (left), and the detection

accuracy of LucaProt (right).

(C) Venn diagram shows the shared putative virus species between available data from Wolf

et al., Edgar *et al.*, Zayed *et al.*, Neri *et al.*, Chen *et al.*, Olendraite *et al.*, and this study. The

bar graph shows the shared viral supergroups between the seven studies and the unique viral

supergroups identified in this study.

(D) Diverse RNA virus clusters (dark colored small circle) and RNA virus supergroups (light

colored large circle). The known viral clusters and supergroups defined by ICTV are shown

in dark grey and light grey, respectively. The viral clusters and supergroups discovered by

both ClstrSearch and LucaProt are shown in dark blue and light blue, respectively. The viral

clusters and supergroups additionally discovered by LucaProt only are in shown dark orange

and light orange, respectively.

See also Figures S1-S3 and Tables S1-S3.

Figure 2. Geographic coverage of the metatranscriptomic data analyzed in this study.

(A) Geographical distribution of the samples analyzed at an ecosystem level. Pie size is

positively correlated to the number of samples (log10). The DBSCAN clustering algorithm

was applied to group 1,837 latitude and longitude points from all metatranscriptomes into 70

clustered points.

(B) Total number of samples at different ecosystems. The embedded bar chart represents the

samples used for dual RNA and DNA sequencing in this study.

Figure 3. Benchmarking of LucaProt with other virus discovery tools.

(A) The recall, precision and false positive rate of LucaProt, Diamond, HMMscan, HH-suite,

and PalmScan was compared using the 50 metatranscriptomes sequenced in this study.

(B) The recall of LucaProt, Diamond, HMMscan, HH-suite, and PalmScan in identifying all

the RdRPs identified in this study.

(C) The recall of LucaProt, Diamond, HMMscan, HH-suite, and PalmScan compared for the

RdRPs additionally identified by LucaProt only.

(D) Recall of LucaProt in identifying RdRPs (length≥300aa) from six previous studies.

(E) The average time used by each bioinformatic tool was calculated based on six data sets of

varying lengths, each comprising 50 positive sequences and 50 negative sequences.

(F) Recall rate of prediction results for CHEER, VirHunter, Virtifier, RNN-VirSeeker and

LucaProt based on all the RdRPs identified this study.

(G) Precision rate and false positive rate of prediction results for CHEER, VirHunter, Virtifier,

RNN-VirSeeker and LucaProt based on the test data set.

(H) Number of viral sequences of different groups by contig length identified by CHEER,

VirHunter, Virtifier, RNN-VirSeeker and LucaProt. The training machines, training data sets,

training strategies, and final model selection of all methods compared are consistent with

LucaProt. All comparisons utilized multiple sets of hyperparameters with the best results

selected in each case.

Figure 4. Evaluation of authenticity of RNA viral supergroups.

(A) Distribution of BLAST median *e*-value, HMM score and mean AI modeling probabilities

of RNA virus supergroups, with the conserved RdRP motif C of each supergroup shown on

the left. For each group selected, the top 20 to 30 supergroups are shown by size for clarity.

The known viral supergroups defined by the ICTV show high sensitivity for all three methods

and are shaded in grey. The unclassified supergroups and new viruses discovered in this study

show declining homology but a relatively stable AI probability.

(B) The proportion of positive libraries and mean RPM (i.e., the number of mapped reads per

million non-rRNA reads) of representative viral supergroups, DNA viruses, RT, and cell

organisms in 50 samples collected in this study. DNA libraries are shown in purple and RNA

libraries in yellow, while the different groups of RNA viruses and DNA organisms are shown

in different colors, and red asterisks refer to those subsequently validated by RT-PCR.

(C) RT-PCR results of the first pairs of validation primers for representative RdRP sequences

from 17 RNA viral supergroups, capsid sequences from two DNA viral families (*Podoviridae*

and *Siphoviridae*), and RT sequences.

(D) Three-dimensional (3D) structure similarity analysis of representative RdRPs from 180

viral supergroups with Eu DdRPs, Eu RdRPs, and RT. Each point denotes a representative

structure. The distance between different points represents structural similarity: the greater

the distance, the lower the structural similarity. Four RdRP domain structures of the AI-

specific supergroups are displayed with the A, B and C motifs highlighted. Representative

RdRP domain structures from all supergroups are available at

https://doi.org/10.6084/m9.figshare.26298802.v14.

See also Figures S4 and S5.

Figure 5. Genomic features of viral supergroups.

(A) Size (i.e., the number of putative viral species) of all viral supergroups. The number of

supergroups included in each group is displayed above the violin chart. Centre lines in the

box plots represent the median bounds.

(B) Genome length of viral species in all viral supergroups. The number of viral species

included in each group is displayed above the violin chart. Centre lines in the box plots

represent the median bounds.

(C) Histogram of the genome size distribution of viral species from known, unclassified and

new supergroups.

(D) Distribution of annotated functional proteins in each viral supergroup. The supergroups

with no annotated genes other than RdRP are not shown.

(E) Genome structure of representatives from six known supergroups, 17 unclassified

supergroups and eight new supergroups. Grey stars represent reference virus genomes of

known supergroups. Domains not commonly found in RNA viruses are shown in yellow and

are labeled above their corresponding positions. At the bottom, scale length in nucleotides.

Abbreviations: GOLGA2L5: golgin subfamily A member 2-like protein 5; Pentaxin: pentaxin

family; Tme5 EGF: thrombomodulin like fifth domain, EGF-like; Mg trans NIPA:

magnesium transporter NIPA; NUDIX, nucleoside diphosphate-X hydrolase; RecX: RecX

family; TssO: type VI secretion system, TssO; Securin: securin sister-chromatid separation

inhibitor; Rax2: cortical protein marker for cell polarity; Abhydrolase: alpha/beta-hydrolase

family; OmdA: bacteriocin-protection, YdeI or OmpD-Associated; Blt1 C: Get5 carboxyl

domain; DnaJ: DnaJ domain; Trypan PARP: procyclic acidic repetitive protein (PARP); SAM

KSR: kinase suppressor RAS 1; CBD PlyG: PlyG cell wall binding domain; LydB: LydA-

holin antagonist; RelB: RelB antitoxin; T2SSE: type II/IV secretion system protein; PARP

regulatory: poly A polymerase regulatory subunit; Pheromone: fungal mating-type

pheromone; Y phosphatase2: tyrosine phosphatase family; PseudoU synth: RNA

pseudouridylate synthase; Glyco hydro 35: glycosyl hydrolases family 35; TIP: tuftelin

interacting protein.

See also Figure S6.

Figure 6. Phylogenetic diversity of 31 RNA viral supergroups.

Each phylogenetic tree was estimated using a maximum likelihood method based on an

amino acid alignment of the RdRP domain. Newly identified viruses are marked in yellow,

those listed as 'Viruses' in the NCBI GenBank are marked in light blue, and viral RdRP

sequences from six metagenomic studies[5-8,10,35] are marked in green. The name of each

supergroup is shown at the top of each phylogeny and the names of the families within each

supergroup are shown to the right of the tree. All trees are midpoint-rooted for clarity only,

and the scale bar indicates 0.5 amino acid substitutions per site. The tree files of all 180

supergroups are available at https://doi.org/10.6084/m9.figshare.26298802.v14.

Figure 7. Ecological structure of the global RNA virome.

(A) Global distribution of RNA viral species identified in this study. The Density-Based

Spatial Clustering of Applications with Noise (NBSCAN) clustering algorithm[68] was used to

cluster the 1,612 different latitude and longitude points from positive samples. Points with a

distance <800 km were aggregated, and the resulting 70 aggregated points were used to draw

the map. Viral species from known RNA virus supergroups are shown in gray, from

unclassified supergroups in blue, and from new supergroups in orange. Pie size reflects the

number of viral species (log10).

(B) Rarefaction curve of all RNA viral species. Inset, Rarefaction curve of RNA virus species

at the ecosystem level with colors indicating different ecosystems.

(C) Distribution of sample size (numbers in the bar chart), alpha diversity, RPM, virus

species from known supergroups, virus species from unclassified supergroups and virus

species from new supergroups at different ecosystem subtypes and colored by their

ecosystem. "Extreme ecosystem" here refers to high salinity, high temperature, or low

temperature environmental types. Only ecosystem subtypes with more than nine libraries

(excluded poly-A sequencing) were retained for ecological comparison. The ecosystem

subtypes on the y-axis are ordered from the highest to the lowest alpha diversity for each

ecosystem.

(D) Viral distributions in environmental and animal samples. The relative abundance of

viruses in each library was calculated and normalized by the number of mapped reads per

million no-rRNA reads (RPM). RNA virus species from 11 ecosystem subtypes are shown

and placed into three groups, indicated by the colors on the heatmap.

See also Figure S7.

Supplemental figure titles and legends

Figure S1. Detailed RNA virus discovery pipeline, related to Figure 1.

(A) Schematic diagram of the similarity-based discovery (i.e., ClstrSearch) and RdRP AI

modeling (i.e., LucaProt) approaches.

(B) Protein clustering process. Only clusters with more than ten members are retained for

viral cluster discovery.

(C) Ten iterations of RdRP expansion by recruiting newly detected RdRPs.

(D) RdRP clusters are merged into RdRP supergroups using BLAST median e-values.

(E) RdRP identification by LucaProt that includes five modules: Input, Tokenizer, Encoder,

Pooling, and Output.

Figure S2. Benchmarking of LucaProt for the RdRP modeling and threshold used in

ClstrSearch, related to Figure 1.

(A) The Sigmoid function of the LucaProt. The Sigmoid function (i.e., the Logistic function)

is used for the output layer of a binary classification model and for mapping a real number to

the probability of 0 ~ 1.

(B) Statistics of the data set used for LucaProt building, including the entire data set, training

set, validation set, and testing set.

(C) The confusion matrix on the validation data set.

(D) The confusion matrix on the testing data set.

(E) The metrics for the validation and testing data sets.

(F) and (G) The metrics on the validation and testing sets of 10-fold cross-validation for

LucaProt. The positive and negative samples were randomly shuffled and divided into ten

parts, with each part containing 540 positive and 21,744 negative samples. In the 10-fold

cross-validation, two parts were selected rotationally to serve as the validation and testing

sets, respectively, while the remaining samples were combined to form the training set.

(H) Number of hits with Diamond blastp v0.9.25.126 using different e-values at the test stage.

A total of 15,000 sequences were randomly sampled for the test, and host hits were

recognized by comparison against the NCBI non-redundant (nr) protein database (version

2023.01.09) with an e-value threshold of $1E$-3.

(I) Benchmarking of HMMscan bitscore and aligned fraction using the RdRP and non-RdRP

data sets (including RT, Eu DdRP and Ed RdRP derived from the NCBI GenBank database).

(J) BLAST Median e-value within the same known RdRP cluster. (K) BLAST Median e-

value between pairwise comparisons of known RdRP clusters, with a $1E$-3 cut-off used for

cluster merging.

Figure S3. Comparison of RNA virus discovery results between six previous studies and

the current study, related to Figure 1.

(A) The distribution of putative viral species of seven studies at the supergroup level and the

study-specific level.

(B) Upset plot showing the number of viral species found in each study and those that are

shared/unique between and among seven studies. The red bar in the top histogram represents

unique viral species identified in each study, while the green bar indicates viral species that

are shared between two or more studies. Rightmost histogram shows the number of

metatranscriptomes analyzed in each study. Of note, Olendraite *et al*. sourced viral RdRPs

from the NCBI Transcriptome Shotgun Assembly (TSA) database, such that the exact number

of metatranscriptomes analyzed is unclear.

Figure S4. The three highly conserved RdRP sequence motifs (A, B and C) and the

distribution of BLAST median e-value, HMM score and mean AI modeling probabilities

of the RNA virus supergroups, related to Figure 4.

RNA viral supergroups were divided into three groups by similarity to reference and other

published data sets, with the conserved RdRP A, B and C motifs of each supergroup shown

on the left.

Figure S5. Expression difference of RNA viruses and DNA organisms in our newly

sequenced data, related to Figure 4.

(A) Abundance comparisons for 58 RNA viral supergroups, four DNA virus families, RT and

cell organisms at DNA and RNA libraries.

(B) RT-PCR results of second pairs of validation primers for representative RdRP sequences

from 17 RNA viral supergroups, capsid sequences from two DNA virus families

(*Podoviridae* and *Siphoviridae*), and RT sequences.

Figure S6. Phylogenetic tree of the Nido-like supergroup and the genome structure of

representative viruses, related to Figure 5.

The tree was estimated using a maximum likelihood method based on the conserved RdRP

domain. The reference sequences reported previously are shaded grey, while the viruses

newly identified here are shaded by different colors according to ecotype. The names of viral

families are shown on right of the tree. The tree was midpoint-rooted for clarity only, and the

scale bar of tree indicates 0.2 amino acid substitutions per site. The genome structures of

representative viruses are shown on right of the tree. The scale bat at the bottom indicates the

length in nucleotides.

Figure S7. Specificity and shareability of RNA viruses, related to Figure 7.

(A) Number of specific putative viral species (i.e., putative "marker" viral species) in each

ecosystem subtype.

(B) Association between RNA viruses and different environmental ecosystems. The size of

the colored circles indicates the number of putative viral species identified by each ecosystem

type, while the thickness of the line indicates the number of viral species shared by each

ecosystem.

STAR★METHODS

Detailed methods are provided in the online version of this paper and include the following:

● KEY RESOURCES TABLE

● RESOURCE AVAILABILITY

○ Lead Contact

○ Materials availability

○ Data and code availability

● METHOD DETAILS

○ Samples and data sets

○ Identification of RNA viruses based on deep learning

○ Identification of RNA viruses based on homologous clustered proteins

○ Benchmarking LucaProt and comparisons to Diamond, HMMscan, HH-suite and

PalmScan

○ Virus verification

○ Structural prediction and comparisons between viral RdRPs and homologous

proteins

○ Annotation and characterization of virus genomes

○ Analyses of virome diversity, evolution and ecology

● QUANTIFICATION AND STATISTICAL ANALYSIS

SUPPLEMENTAL INFORMATION

Supplemental information can be found online at XXXXXXXXXX

STAR★METHODS

KEY RESOURCES TABLE

REAGENT or RESOURCE	SOURCE	IDENTIFIER
RNeasy®PowerSoil® Total RNA Kit	QIAGEN	Cat. #12866-25
RNeasy® PowerSoil® DNA Elution Kit	QIAGEN	Cat. #12867-25
NEB Next Ultra RNA Library Prep Kit	New England Biolabs	Cat. #E7770

NEB Next Ultra DNA Library Prep Kit	New England Biolabs	Cat. #E7370L
Biological samples		
Samples are described in Table S2	This paper	N/A
Deposited data		
Raw sequencing reads generated in this study	This paper	NCBI-SRA BioProject: PRJNA956286 (RNA-seq) and PRJNA956287 (DNA-seq)
All assembled contigs used in this study	This paper	https://ftp.cngb.org/pub/CNSA/data4/CNP0005901/CNS1149693/CNA0141908/
Representative viral genome sequences	This paper	https://db.cngb.org/search/project/CNP0005901/
All original data and code produced in this work	This paper	https://doi.org/10.6084/m9.figshare.26298802.v14
Original code produced in this study	This paper	https://github.com/alibaba/LucaProt
Software and algorithms		
MEGAHIT v1.2.8	Li et al.[54]	https://github.com/voutcn/megahit
ORFfinder v0.4.3	NCBI Team	https://ftp.ncbi.nlm.nih.gov/genomes/TOOLS/ORFfinder/linux-i64/
ESMFold	Lin et al.[56]	https://github.com/facebookresearch/esm
Subword-NMT v0.3.8		https://github.com/rsennrich/subword-nmt
Diamond v0.9.25.26	Buchfink et al.[58]	https://github.com/bbuchfink/diamond
CD-HIT v4.8.1		https://github.com/weizhongli/cdhit
HMMER	Potter et al.[59]	http://hmmer.org/
Mafft v7.475	Katoh et al.[60]	https://mafft.cbrc.jp/alignment/software/
Girvan-Newman algorithm	Girvan et al.[62]	https://memgraph.github.io/networkx-guide/algorithms/community-detection/girvan-newman/
iGraph package v1.3.5	Csárdi et al.[63]	https://igraph.org
HH-suite v3.3.0	Steinegger et al.[64]	https://github.com/soedinglab/hh-suite
PalmScan	Babaian et al.[61]	https://github.com/rcedgar/palmscan
Bowtie2 v2.4.2	Langmead et al.[65]	https://bowtie-bio.sourceforge.net/bowtie2/index.shtml
AlphaFold2 v2.3 PyMol v2.5.4	Jumper et al.[20]	https://alphafold.com/ http://www.pymol.org/pymol
NetworkX		https://networkx.org/
PhyML v3.1	Guindon et al.[67]	http://www.atgc-montpellier.fr/phyml/

RESOURCE AVAILABILITY

Lead Contact

Further information and requests for resources and additional data should be directed to and

will be fulfilled by the Lead Contact, Mang Shi (shim23@mail.sysu.edu.cn).

Materials availability

This study did not generate new unique reagents or specific biological material. The materials

used and generated in this study are available from the Lead Contact. As a computational

project, the input, results, output, and code of this study is publicly available and are

described below in the ''data and code availability'' section.

Data and code availability

The raw sequence reads newly generated in this study are available at the NCBI Sequence

Read Archive (SRA) database under BioProject accessions PRJNA956286 and

PRJNA956287 (Table S2). All assembled contigs from this study are available in the China

National GeneBank DataBase (CNGBdb) under the accession CNP0005901. The

representative viral genome sequences generated are available in the CNGBdb under the

accession CNP0005901 (https://db.cngb.org/search/project/CNP0005901/). Additionally, the

related result data sets and LucaProt-related resources are publicly available at

https://doi.org/10.6084/m9.figshare.26298802.v14, including: (i) the result data sets from this

study, including viral contigs, viral RdRP sequences, viral RdRP HMM profiles and

phylogenetic tree files; (ii) the LucaProt code, the data sets for model building, and the

trained model of LucaProt; (iii) the inference and prediction code using the trained model for

unknown sequences, benchmarks with other methods, and (iv) additional resources.

The original source code for ClstrSearch and LucaProt are stored at the GitHub

repository (ClstrSearch: https://github.com/alibaba/LucaProt/tree/master/ClstrSearch,

LucaProt: https://github.com/alibaba/LucaProt). We also provide the Python dependency

environment installation file, installation commands, and the running command of the trained

LucaProt model for inference or prediction, which can be found in the same GitHub

repository. These models are compatible with Linux, Mac OS, and Windows systems,

supporting both CPU and GPU configurations for inference tasks.

METHOD DETAILS

Samples and data sets

This study comprised RNA virus discovery through the metatranscriptomic analysis of

10,487 samples. The majority of these samples (n=10,437) were mined from the NCBI

Sequence Read Archive (SRA) database (https://www.ncbi.nlm.nih.gov/sra) between January

16 - August 14, 2020. We targeted samples collected from a wide range of environmental

types globally (Figure 2), including: aquatic (such as marine, riverine and lake water), soil

(such as sediment, sludge and wetland), host-related (such as biofilm, wood decay, and

rhizosphere), and extreme environmental samples (such as hydrothermal vent, hypersaline

lake and salt marsh), that were subject to high quality metatranscriptomic sequencing to

ensure the generation of ≥50 Mb total RNA Q20 sequencing data. In addition, 50 data sets

were generated in this study (see below), all of which were subject to high-quality short-read

sequencing utilizing Illumina sequencing platforms. The raw sequencing data output ranged

from 35.1 to 204.1 Gbp, and no enrichment for microbial organisms was performed during

sample processing or library preparations. For highly abundant environmental types, such as

"soil" and "marine", representative samples were selected to include as many projects (i.e.,

independent studies), geographic locations and ecological niches as possible.

In addition to data mined from the SRA database, we generated 50 metatranscriptomic

data sets from Antarctica and China. The sample types included marine (n=5), freshwater

(n=12), soil (n=19), and sediment (n=14), of which nine sediment samples were collected at

the Ross Sea station in Antarctica between January and February 2022, with the others from

Zhejiang, Guangdong, Hubei and Heilongjiang provinces of China collected between August

and October 2022. For each of these samples, DNA and RNA were simultaneously extracted:

the soil and sediment samples were extracted using the RNeasy® PowerSoil® Total RNA Kit

and RNeasy® PowerSoil® DNA Elution Kit (QIAGEN, Germany), while the marine and

freshwater samples were extracted using the DNeasy® PowerWater® Kit and RNeasy®

PowerWater® Kit (QIAGEN, Germany). The extracted nucleic acid was then subject to

library construction using the NEB Next Ultra RNA Library Prep Kit and NEB Next Ultra

DNA Library Prep Kit (New England Biolabs, China) for RNA and DNA samples,

respectively. Paired-end (150 bp) sequencing of these libraries was performed using the

Illumina NovaSeq 6000 platform (Illumina, USA).

For all 10,487 data sets used this study, sequence reads were *de novo* assembled into

contigs using MEGAHIT v1.2.8[54] with default parameters, without implementing any quality

control procedures to optimize time efficiency. Potential encoded proteins were predicted

from contigs using ORFfinder v0.4.3

(https://ftp.ncbi.nlm.nih.gov/genomes/TOOLS/ORFfinder/linux-i64/; parameters, -g 1, -s 2).

Identification of RNA viruses based on deep learning

We developed a new deep learning, transformer-based model, termed "Deep Sequential and

Structural Information Fusion Network for Protein Function Prediction" (i.e., LucaProt), that

effectively integrated protein sequence composition and structure information to identify viral

RdRPs. The model contains two channels. The first channel employs a Transformer-Encoder

for feature extraction from the raw sequence data. We used the Byte-Pair Encoding (BPE)

algorithm[55] for tokenization, enabling the model to handle longer sequences and identify

meaningful units (such as words, rather than individual residues) within sequences associated

with RdRPs. The BPE algorithm creates a word-level vocabulary from a sequence corpus and

tokenizes the input sequence accordingly, prior to feature extraction via the Transformer-

Encoder. The second channel leverages the protein language model ESM2-3B[56] to capture

residue-level features, utilizing the model's self-supervised learning capabilities to decode

contextual structural information. The model concludes with two Value-Level Attention

Pooling layers that down-sample each feature matrix into a vector. These two vectors are then

concatenated for the final classification task. The model includes five modules: Input,

Tokenizer, Encoder, Pooling, and Output (Figure S1E).

Input Layer: This layer accepts amino acid sequences as the model's input.

Tokenizer Layer: This layer processes raw sequence data into a digestible format for

feature extraction. This module comprises two components. First, a corpus comprising 5,979

positive sequences (i.e., viral RdRPs) and 150,000 sequences sampling from negative

samples (i.e., protein sequences that are not viral RdRPs) was constructed. The BPE

algorithm[55] from the Subword-NMT tool (https://github.com/rsennrich/subword-nmt) was

utilized to create a vocabulary of about 20,000 frequent subsequences or "words". These

words were derived by treating co-occurring amino acids in the sequences as single entities.

Additionally, each protein sequence was broken down into individual amino acids for

subsequent extraction of protein structural information using a large protein language model.

Encoder Layer: This layer transforms the data into two representations by different

tokenization strategies (as illustrated in the former layer): a sequence representation matrix

with word-level tokenization and a structural representation matrix with character-level

tokenization. For sequence processing, an advanced Transformer-Encoder model was utilized

to generate the sequence representation matrix. In terms of structural processing, the

intermediate matrices produced by the structural prediction model ESMFold (ESM2-3B)[56]

were used as the structural representation matrix. This methodology addresses the limitation

posed by the scarcity of experimentally observed 3D structures and obviates the need for

additional encoding steps, thereby guaranteeing computational efficiency.

Pooling Layer: This layer reduces dimension and selects features for efficient

classification. It employs a Value-Level Attention Pooling (VLAP) approach[57] to convert the

sequence and structural matrices into two vectors.

Output Layer: This layer transforms the pooled vectors into the probability value

indicative of a positive sample. The vectors from the pooling layer are concatenated and

passed through a fully connected layer. A sigmoid function outputs probability values

ranging from 0.0 to 1.0, with a threshold of 0.5 to classify sequences as viral RdRP or not

(Figure S2).

Model Building: We constructed a data set of 235,413 samples for model building. This

included 5,979 positive samples of known viral RdRPs (i.e., the well-curated RdRP database

described below) and 229,434 randomly selected negative samples of confirmed protein

sequences that were not viral RdRPs (as the positive samples account for a very small portion

of the total data, we constructed the training data set using the conventional 1:40 ratio of

positive to negative data). The representative negative samples contained proteins from

eukaryotic RNA-dependent RNA polymerase (Eu RdRP, n=2,233), eukaryotic DNA-

dependent RNA polymerase (Eu DdRP, n=1,184), reverse transcriptase (RT, n=48,490),

proteins obtained from DNA viruses (n=1,533), non-RdRP proteins obtained from RNA

viruses (n=1,574), as well as an array of cellular proteins from different functional categories

(n=174,420). We randomly divided the data set into training, validation, and testing sets with

a ratio of 8.5:1:1, which were used for model fitting, model finalization (based on the best

F1-score training iteration), and performance reporting (including accuracy, precision, recall,

F1-score, and Area under the ROC Curve (AUC)), respectively (Figure S2).

We further validated the performance and robustness of LucaProt model by

implementing a 10-fold cross-validation (Figure S2). During this process, both positive and

negative samples were randomly shuffled and divided into ten equal parts, with each part

comprising 540 positive and 21,744 negative samples. For the cross-validation, two parts

were sequentially selected as the validation and testing sets, respectively, while the remaining

samples were merged to form the training set.

LucaProt successfully identified 792,436 putative RdRP signatures from a data set of

144.6 million proteins derived from the 10,487 metatranscriptomes. These results were first

compared with the RdRPs identified based on ClstrSearch (see below). RdRPs that were

identified by deep learning algorithms (i.e., LucaProt) were either incorporated into RNA

virus supergroups using the Diamond blastp program v0.9.25.126[58] with an *e*-value threshold

of 1*E*-3, or, if they remained unclassified, were subjected to clustering, merging, and manual

alignment inspection. The presence of key viral RdRP motifs – motif A [DxxxxD], motif B

[(S/T)Gxxx(T/G)xxxN], and motif C [(S/G/N/A)D(D/N)] – were examined for all

supergroups through multiple sequence alignments.

Identification of RNA viruses based on homologous clustered proteins

Another strategy for the identification of RNA viruses at the cluster level involved the

utilization of homologous clustered proteins (Figure S1A). Accordingly, a total of 871.8

million amino acid sequences predicted by ORFfinder (see Samples and data sets) were

compared against a well-curated RdRP database (n=5,979) that contained only those derived

from reference RNA virus genomes downloaded from the NCBI GenBank database and their

close relatives in vertebrate and invertebrate hosts.[1,2] The comparisons were performed using

the Diamond blastp program v0.9.25.126,[58] with the *e*-value threshold set at 1*E*+5 to identify

more divergent RdRP sequences (Figures S1A and S2H). This process resulted in 75.3

million hits that were further subjected to similarity-based and multi-step clustering (three

iterations with 90%, 60%, and 20% amino acid identity, respectively) using CD-HIT v4.8.1

(https://github.com/weizhongli/cdhit); this process resulted in 3,805,584 clusters. False

positives and hits to known RdRP sequences were removed by comparison against the NCBI

non-redundant (nr) protein database (version 2023.01.09), the NCBI RefSeq protein database

(version 2023.03.26) and the virus RdRP database using the Diamond blastp program

v0.9.25.126[58] with an e-value threshold of 1E-3 (Figure S1B). The remaining unknown

protein clusters were subject to viral RdRP domain search using hidden Markov models

(HMMs) built from a manually reviewed profile of known RdRP clusters using HMMscan

v3.3.2 (e=10, hits≥1).[59] The RdRP sequences of each known viral group were aligned using

Mafft v7.475,[60] employing the L-INS-I algorithm. HMM profiles were then built from each

MSA using HMMbuild v3.3.2 with standard parameters.[59] Clusters that contained more than

one HMMscan hit were subsequently aligned and inspected for the presence of well-

conserved RdRP core sequences referred to as the "palmprint", delineated by the presence of

the three motifs (A, B and C) that collectively constitute the catalytic core within the RdRP

structure.[61] As a result of our rigorous screening and checking steps, a total of 713 potential

RdRP clusters were retained.

To further expand the RdRP collection based on the viruses newly discovered here, we

updated the RdRP protein database with the 713 RdRP clusters newly identified here and

used it to detect additional RdRP sequences from the original 144.6 million amino acid

sequences using Diamond blastp v0.9.25.126[58] with an e-value threshold of 1E-3. The newly

detected RdRPs were again incorporated into the RdRP database for another round of virus

detection. This procedure was repeated ten times. The resulting hits (21,747,015 in total)

were compared to the similarity-based clusters for the removal of false positives and virus

classification. The false positives and non-RdRP viral proteins that did not contain a RdRP

domain were removed by a HMMs-based search using an updated HMMs profile derived

from each RdRP cluster and built as described above. The cut-off was set to score≥40 and the

aligned fraction to ≥0.4 to remove false positives and partial virus RdRPs (Figures S1C and

S2I).

Finally, the expanded clusters were merged into virus supergroups using a hierarchical

method employing the Girvan-Newman algorithm,[62] with the edge betweenness determined

based on median *e*-value threshold of 1*E*-3 for each pair of clusters (Figures S1D, S2J-S2K).

Briefly, the merging of clusters employed the following steps: (i) the betweenness of all edges

(median *e*-value between clusters) in the network was calculated; (ii) the edge(s) with the

highest betweenness were removed; (iii) the betweenness of all edges affected by the removal

was recalculated; (iv) steps ii and iii were repeated until no edges remained. All processes

related to merging were performed using igraph package v1.3.5[63] implemented in *R*.

Benchmarking LucaProt and comparisons to Diamond, HMMscan, HH-suite and

PalmScan

We assessed the performance of LucaProt (prob≥0.5) relative to other four virus discovery

tools: Diamond v0.9.25.126[58] (with *e*-value threshold of 1*E*-3), HMMscan v3.3.2[59] (with

score≥30 and aligned fraction≥0.7 as referenced from Zayed *et al.*,[6]), HH-suite v3.3.0[64] (with

default parameters), and PalmScan[61] (with default parameters). This comparison included

recall, precision, false positive and false discovery based on the 2.05 million amino acid

sequences (length≥300aa) from contigs assembled from the 50 samples collected in this study,

employing a unified criterion and utilizing the same well-curated RdRP database (n=5,979).

True positive (TP) virus hits were determined by simultaneously identifying the true viral

RdRPs using both aforementioned tools (i.e., LucaProt, Diamond, HMMscan, HH-suite and

PalmScan), and subsequently confirming through comparison against the nr protein database

(version 2023.01.09) using the Diamond blastp program v0.9.25.126[58] with an *e*-value

threshold of 1*E*-3. True negative (TN) hits were defined as the subset of sequences

recognized as cellular proteins and/or with reads from DNA sequencing results mapping

against the corresponding contigs, among a data set comprising 2.05 million sequences. A

data set of 1,029,342 true negative sequences was obtained through both approaches. Recall

was calculated as the ratio of correctly predicted true positives to the total number of true

positives (recall rate=TP*100%/total TP). Precision was calculated as the proportion of all

predictions that were correctly predicted as true positives (precision rate=TP*100%/total

predictions). The false positive (FP) rate was calculated as the proportion of all true negatives

that were incorrectly predicted as positives (false positive rate=FP*100%/total TN). False

discovery (FD) was calculated as the proportion of all predictions that were incorrectly

predicted as positives (false discovery rate=FP*100%/total predictions).

To compare the computational time required by LucaProt to that of HH-suit, Diamond,

HMMscan, and PalmScan, we categorized the test data sets into six groups based on amino

acid sequence length: (300, 500), (500, 800), (800, 1,000), (1,000, 3,000), (3,000, 5,000),

and >5,000. Each group comprised 50 randomly sampled viral RdRPs and 50 non-viral

sequences. A single sequence was used as input to calculate the average time on the same

machine of the Alibaba Cloud Elastic Compute Service (ECS). The CPU execution

environment comprised 96 cores (vCPU) and 192 GiB memory (instance type:

ecs.c8i.24xlarge). For LucaProt, we also recorded the time spent on a single NVIDIA A100

80G GPU (instance type: ecs.gn7e-c16g1.16xlarge).

All scripts of the tools used, containing exact parameters and the database utilized in the

benchmarking, are available at https://doi.org/10.6084/m9.figshare.26298802.v14.

Virus verification

To determine whether the newly discovered viral RdRPs belonged to RNA viruses rather than

organisms with DNA genomes we performed three verification experiments. First, the RdRPs

were compared against the NCBI nr protein database (version 2023.01.09) using Diamond

blastp v0.9.25.126,[58] with the *e*-value threshold set to 1*E*-3. Proteins with similarity to

cellular proteins were removed. In addition, we confirmed the presence of the key RdRP

motifs (i.e., the A, B and C motifs) through alignment to all RNA supergroups that possessed

these motifs (i.e. motif A [DxxxxD], motif B [(S/T)Gxxx(T/G)xxxN], motif C [(S/G/N)DD]).

Sequences that failed to cover these motifs were removed.

Second, to ensure the accuracy of DNA read mapping, an initial quality control step was

performed on viral contigs using bbduk.sh (https://sourceforge.net/projects/bbmap/). As well

as the simultaneous RNA and DNA extraction and sequencing of the 50 environmental

samples collected in this study, we searched for published RNA studies that performed both

RNA and DNA sequencing on the samples. To confirm that the detected contigs represented

bona fide RNA viral genomes, reads from the DNA sequencing data were mapped against the

viral contigs using Bowtie2 v2.4.2[65] with the "end-to-end" setting.

Finally, RT-PCR assays were conducted to validate the presence of RNA organisms

within the viral supergroups identified. Two pairs of validation primers were designed for

each of the representative RdRP sequences from 17 of the 115 RNA viral supergroups

involved in 50 samples collected in this study. These comprised: (i) two known supergroups

defined by the ICTV: Astro-Poty, Bunya-Arena; (ii) ten unclassified supergroups derived

from this study and other studies: Supergroup022, Supergroup034, Supergroup038,

Supergroup053, Supergroup055, Supergroup063, Supergroup086, Supergroup104,

Supergroup124, Supergroup180; and (iii) five new supergroups identified here:

Supergroup102, Supergroup167, Supergroup175, Supergroup184, Supergroup187. We also

included gene sequences from two DNA virus families (the *Podoviridae* and *Siphoviridae*),

and RT sequences identified in this study, with a product length of 300-550 bp. For each of

these samples, both the reverse-transcribed RNA and the matching DNA underwent

simultaneous PCR amplification, and the amplification products were subject to

electrophoresis using a 1% agarose gel with GelRed dye, which was subsequently visualized

under UV.

Structural prediction and comparisons between viral RdRPs and homologous proteins

Three-dimensional structures of newly identified viral RdRPs from diverse RNA viral

supergroups were predicted from primary sequences using AlphaFold2 v2.3[20] and visualized

using the PyMol software v2.5.4 (http://www.pymol.org/pymol). The pLDDT (predicted local

distance difference test) score was measured for each structure prediction as its per-residue

estimate of the prediction confidence on a scale from 0-100. Considering the computational

resource limitations with such a large data set, ten representative RdRPs from each

supergroup were predicted: more than 52.03% of the structures predicted had >70% accuracy,

showing that AlphaFold2 was a relatively reliable source of structural information. The

previously resolved or predicted structures of viral RdRPs, eukaryotic RdRPs, eukaryotic

DdRPs and RTs were compared using the Super algorithm.[66] Considering that the protein

structures have similar molecular weights but substantial conformational variation, the

"number of aligned atoms after refinement" option was employed to evaluate the similarity

between each pair of proteins. Subsequently, NetworkX (https://networkx.org/) was

employed to construct a three-dimensional structure diagram using the "edge-weighted spring

embedded" approach, with results then mapped as a scatter plot (depicted in the Figure 4D).

Simultaneously, we visualized four viral RdRP domain proteins using PyMol.

Annotation and characterization of virus genomes

Potential open reading frames (ORFs) of every virus genome were predicted based on two

criteria: (i) the predicted amino acid sequences were longer than 200 amino acids in length,

and (ii) they were not completely nested within larger ORFs. The annotation of non-RdRP

ORFs was mainly based on comparisons of predicted proteins to hidden Markov models

(HMMs) collected from the Pfam database (version 2022.03.23, https://pfam-

legacy.xfam.org/) using HMMscan v3.3.2 implemented in HMMER (e=10, score≥10).[59] For

the remaining ORFs, the annotation was performed by blastp comparisons against the nr

protein database with an e-value threshold of 1E-3.

Analyses of virome diversity, evolution and ecology

To unveil the diversity of the RNA viruses identified and establish putative novel viral

species, we employed a protein sequence identity threshold of 90% and a minimum aligned

fraction of 30% for all viral RdRP domains identified in this study as implemented by CD-

HIT v4.8.1 (https://github.com/weizhongli/cdhit). Abundance levels were subsequently

estimated for every putative virus species based on the number of non-rRNA reads per

million (RPM) in each sample (i.e., sequencing run) mapped to the RdRP sequences of all

viral species using Bowtie2 v2.4.2[65] with the "end-to-end" setting. The abundance of each

putative virus species was estimated as the number of mapped reads per million total non-

rRNA reads (RPM) in each library.

Virus alpha diversity (measured using the Shannon index) and overall abundance were

subsequently estimated and compared across different geographic locations and ecosystem

subtypes, namely; soil, marine, freshwater, wetland, hot spring, salt marsh, and other

subtypes. "Marker virus species", that were greatly enriched in certain ecosystem subtypes,

were also identified based on the virus mapping results. The marker virus species were

defined as those present only in one ecosystem subtype with RPM≥1 and coverage

(percentage of horizontal covered bases with depth≥1) set at ≥20%.

To reveal the diversity and evolutionary relationships of RNA viruses within individual

virus supergroups, all previously documented RNA viruses were incorporated into

phylogenetic analyses, including RefSeq RdRPs sequences as well as those from previous

studies. For supergroups containing more than 500 RdRPs, similarity-based clustering using

CD-HIT v4.8.1 (https://github.com/weizhongli/cdhit) with a threshold of identity=0.6 was

employed to select representative RdRPs to ensure phylogenetic diversity, while for those

containing fewer than 500 RdRPs, all sequences were used in the phylogenetic analysis. The

RdRPs of each supergroup were aligned using the L-INS-I algorithm implemented in Mafft

v7.475.[60] Phylogenetic analyses were performed based on the sequence alignment using a

maximum likelihood algorithm, employing the LG model of amino acid substitution, a

Subtree Pruning and Regrafting (SPR) branch swapping algorithm, and a Shimodaira–

Hasegawa-like procedure as implemented in the PhyML program v3.1.[67]

QUANTIFICATION AND STATISTICAL ANALYSIS

All computational and statistical analyses were performed with the open-source software

tools referenced in the STAR Methods along with the described procedures.

Supplemental video and Excel table titles and legends

Table S1. Detailed information on the 10,437 metatranscriptomics retrieved from the SRA

database, related to Figure 1 and 2.

Table S2. Detailed information on the 50 environmental samples collected in this study,

related to Figure 1 and 2.

Table S3. Information on the RdRP sequences identified in this study, related to Figure 1.

Table S4. Predicted results of RdRPs identified in this study using three methods (Threshold:

BLAST: $e \leq$1E-3; HMM: score$\geq$10; AI: prob$\geq$0.5), related to Figure 4.

Table S5. Viral supergroups identified in 50 collected samples were confirmed through DNA

read mapping and RT-PCR, related to Figure 4.

Table S6. Size information (the number of dedup-contigs) of all viral supergroups, related to

Figure 5.

Table S7. Normalized abundance levels (measured by RPM) of each viral species in

environmental samples (RPM$\geq$1, coverage$\geq$20%), related to Figure 7.

REFERENCES

1.   Shi, M., Lin, X.D., Tian, J.H., Chen, L.J., Chen, X., Li, C.X., Qin, X.C., Li, J., Cao, J.P., Eden, J.S., et
al. (2016). Redefining the invertebrate RNA virosphere. Nature *540*, 539-543. 10.1038/nature20167.

2.   Shi, M., Lin, X.D., Chen, X., Tian, J.H., Chen, L.J., Li, K., Wang, W., Eden, J.S., Shen, J.J., Liu, L., et
al. (2018). The evolutionary history of vertebrate RNA viruses. Nature *556*, 197-202. 10.1038/s41586-
018-0012-7.

3.   Rivarez, M.P.S., Pecman, A., Bačnik, K., Maksimović, O., Vučurović, A., Seljak, G., Mehle, N.,
Gutiérrez-Aguirre, I., Ravnikar, M., and Kutnjak, D. (2023). In-depth study of tomato and weed
viromes reveals undiscovered plant virus diversity in an agroecosystem. Microbiome *11*, 60.
10.1186/s40168-023-01500-6.

4.   Sutela, S., Forgia, M., Vainio, E.J., Chiapello, M., Daghino, S., Vallino, M., Martino, E., Girlanda, M.,
Perotto, S., and Turina, M. (2020). The virome from a collection of endomycorrhizal fungi reveals new
viral taxa with unprecedented genome organization. Virus Evolution *6*, veaa076. 10.1093/ve/veaa076.

5.   Wolf, Y.I., Silas, S., Wang, Y., Wu, S., Bocek, M., Kazlauskas, D., Krupovic, M., Fire, A., Dolja, V.V.,
and Koonin, E.V. (2020). Doubling of the known set of RNA viruses by metagenomic analysis of an
aquatic virome. Nat Microbiol *5*, 1262-1270. 10.1038/s41564-020-0755-4.

6.   Zayed, A.A., Wainaina, J.M., Dominguez-Huerta, G., Pelletier, E., Guo, J., Mohssen, M., Tian, F.,
Pratama, A.A., Bolduc, B., Zablocki, O., et al. (2022). Cryptic and abundant marine viruses at the
evolutionary origins of Earth's RNA virome. Science *376*, 156-162. 10.1126/science.abm5847.

7.   Chen, Y.M., Sadiq, S., Tian, J.H., Chen, X., Lin, X.D., Shen, J.J., Chen, H., Hao, Z.Y., Wille, M., Zhou,
Z.C., et al. (2022). RNA viromes from terrestrial sites across China expand environmental viral
diversity. Nat Microbiol *7*, 1312-1323. 10.1038/s41564-022-01180-2.

8.   Edgar, R.C., Taylor, J., Lin, V., Altman, T., Barbera, P., Meleshko, D., Lohr, D., Novakovsky, G.,
Buchfink, B., Al-Shayeb, B., et al. (2022). Petabase-scale sequence alignment catalyses viral discovery.
Nature *602*, 142-147. 10.1038/s41586-021-04332-2.

9.   Obbard, D.J., Shi, M., Roberts, K.E., Longdon, B., and Dennis, A.B. (2020). A new lineage of
segmented RNA viruses infecting animals. Virus Evol *6*, vez061. 10.1093/ve/vez061.

10. Neri, U., Wolf, Y.I., Roux, S., Camargo, A.P., Lee, B., Kazlauskas, D., Chen, I.M., Ivanova, N., Zeigler
Allen, L., Paez-Espino, D., et al. (2022). Expansion of the global RNA virome reveals diverse clades of
bacteriophages. Cell *185*, 4023-4037 e4018. 10.1016/j.cell.2022.08.023.

11. Urayama, S.I., Fukudome, A., Hirai, M., Okumura, T., Nishimura, Y., Takaki, Y., Kurosawa, N.,
Koonin, E.V., Krupovic, M., and Nunoura, T. (2024). Double-stranded RNA sequencing reveals distinct
riboviruses associated with thermoacidophilic bacteria from hot springs in Japan. Nat Microbiol *9*, 514-
523. 10.1038/s41564-023-01579-5.

12. Lee, B.D., Neri, U., Roux, S., Wolf, Y.I., Camargo, A.P., Krupovic, M., Consortium, R.N.A.V.D.,
Simmonds, P., Kyrpides, N., Gophna, U., et al. (2023). Mining metatranscriptomes reveals a vast world
of viroid-like circular RNAs. Cell *186*, 646-661 e644. 10.1016/j.cell.2022.12.039.

13. Forgia, M., Navarro, B., Daghino, S., Cervera, A., Gisel, A., Perotto, S., Aghayeva, D.N., Akinyuwa,
M.F., Gobbi, E., Zheludev, I.N., et al. (2023). Hybrids of RNA viruses and viroid-like elements
replicate in fungi. Nat Commun *14*, 2591. 10.1038/s41467-023-38301-2.

14. Zheludev, I.N., Edgar, R.C., Lopez-Galiano, M.J., de la Pena, M., Babaian, A., Bhatt, A.S., and Fire,
A.Z. (2024). Viroid-like colonists of human microbiomes. bioRxiv. 10.1101/2024.01.20.576352.

15. Dominguez-Huerta, G., Wainaina, J.M., Zayed, A.A., Culley, A.I., Kuhn, J.H., and Sullivan, M.B.
(2023). The RNA virosphere: How big and diverse is it? Environ Microbiol *25*, 209-215.

1001     10.1111/1462-2920.16312.

1002 16. Cobbin, J.C., Charon, J., Harvey, E., Holmes, E.C., and Mahar, J.E. (2021). Current challenges to virus
1003     discovery by meta-transcriptomics. Curr Opin Virol *51*, 48-55. 10.1016/j.coviro.2021.09.007.

1004 17. McNutt, A.T., Francoeur, P., Aggarwal, R., Masuda, T., Meli, R., Ragoza, M., Sunseri, J., and Koes,
1005     D.R. (2021). GNINA 1.0: molecular docking with deep learning. J Cheminform *13*, 43.
1006     10.1186/s13321-021-00522-2.

1007 18. Pham, T.H., Qiu, Y., Zeng, J., Xie, L., and Zhang, P. (2021). A deep learning framework for high-
1008     throughput mechanism-driven phenotype compound screening and its application to COVID-19 drug
1009     repurposing. Nat Mach Intell *3*, 247-257. 10.1038/s42256-020-00285-9.

1010 19. Du, B.-X., Qin, Y., Jiang, Y.-F., Xu, Y., Yiu, S.-M., Yu, H., and Shi, J.-Y. (2022). Compound-protein
1011     interaction prediction by deep learning: Databases, descriptors and models. Drug Discov Today *27*,
1012     1350-1366. 10.1016/j.drudis.2022.02.023.

1013 20. Jumper, J., Evans, R., Pritzel, A., Green, T., Figurnov, M., Ronneberger, O., Tunyasuvunakool, K.,
1014     Bates, R., Zidek, A., Potapenko, A., et al. (2021). Highly accurate protein structure prediction with
1015     AlphaFold. Nature *596*, 583-589. 10.1038/s41586-021-03819-2.

1016 21. Gligorijevic, V., Renfrew, P.D., Kosciolek, T., Leman, J.K., Berenberg, D., Vatanen, T., Chandler, C.,
1017     Taylor, B.C., Fisk, I.M., Vlamakis, H., et al. (2021). Structure-based protein function prediction using
1018     graph convolutional networks. Nat Commun *12*, 3168. 10.1038/s41467-021-23303-9.

1019 22. Xu, L., Magar, R., and Barati Farimani, A. (2022). Forecasting COVID-19 new cases using deep
1020     learning methods. Comput Biol Med *144*, 105342. 10.1016/j.compbiomed.2022.105342.

1021 23. Deng, L. (2014). Deep Learning: Methods and Applications. Foundations and Trends® in Signal
1022     Processing *7*, 197-387. 10.1561/2000000039.

1023 24. Sarker, I.H. (2021). Deep Learning: A Comprehensive Overview on Techniques, Taxonomy,
1024     Applications and Research Directions. SN Comput Sci *2*, 420. 10.1007/s42979-021-00815-1.

1025 25. Shang, J., and Sun, Y. (2021). CHEER: HierarCHical taxonomic classification for viral mEtagEnomic
1026     data via deep leaRning. Methods *189*, 95-103. 10.1016/j.ymeth.2020.05.018.

1027 26. Sukhorukov, G., Khalili, M., Gascuel, O., Candresse, T., Marais-Colombel, A., and Nikolski, M. (2022).
1028     VirHunter: A Deep Learning-Based Method for Detection of Novel RNA Viruses in Plant Sequencing
1029     Data. Front Bioinform *2*, 867111. 10.3389/fbinf.2022.867111.

1030 27. Miao, Y., Liu, F., Hou, T., and Liu, Y. (2022). Virtifier: a deep learning-based identifier for viral
1031     sequences from metagenomes. Bioinformatics *38*, 1216-1222. 10.1093/bioinformatics/btab845.

1032 28. Liu, F., Miao, Y., Liu, Y., and Hou, T. (2022). RNN-VirSeeker: A Deep Learning Method for
1033     Identification of Short Viral Sequences From Metagenomes. IEEE/ACM Trans Comput Biol Bioinform
1034     *19*, 1840-1849. 10.1109/TCBB.2020.3044575.

1035 29. Lecun, Y., Bottou, L., Bengio, Y., and Haffner, P. (1998). Gradient-based learning applied to document
1036     recognition. Proceedings of the IEEE *86*, 2278-2324. 10.1109/5.726791.

1037 30. Jordan, M.I. (1997). Serial Order: A Parallel Distributed Processing Approach. *121*, 471-495.

1038 31. Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, L., and Polosukhin,
1039     I. (2017). Attention Is All You Need. arXiv.

1040 32. Kabir, A., and Shehu, A. (2022). GOProFormer: A Multi-Modal Transformer Method for Gene
1041     Ontology Protein Function Prediction. Biomolecules *12*. 10.3390/biom12111709.

1042 33. Cao, Y., and Shen, Y. (2021). TALE: Transformer-based protein function Annotation with joint
1043     sequence–Label Embedding. Bioinformatics *37*, 2825-2833. 10.1093/bioinformatics/btab198.

1044 34. Nambiar, A., Liu, S., Hopkins, M., Heflin, M., Maslov, S., and Ritz, A. (2020). Transforming the

1045   Language of Life: Transformer Neural Networks for Protein Prediction Tasks. bioRxiv.

1046 35. Olendraite, I., Brown, K., and Firth, A.E. (2023). Identification of RNA Virus-Derived RdRp

1047   Sequences in Publicly Available Transcriptomic Data Sets. Mol Biol Evol *40*.

1048   10.1093/molbev/msad060.

1049 36. Avsec, Ž., Agarwal, V., Visentin, D., Ledsam, J.R., Grabska-Barwinska, A., Taylor, K.R., Assael, Y.,

1050   Jumper, J., Kohli, P., and Kelley, D.R. (2021). Effective gene expression prediction from sequence by

1051   integrating long-range interactions. Nature Methods *18*, 1196-1203. 10.1038/s41592-021-01252-x.

1052 37. Neuman, B.W., Smart, A., Vaas, J., Bartenschlager, R., Seitz, S., Gorbalenya, A.E., Caliskan, N., and

1053   Lauber, C (2024). RNA genome expansion up to 64 kb in nidoviruses is host constrained and

1054   associated with new modes of replicase expression. bioRxiv 2024.07.07.602380; doi:

1055   https://doi.org/10.1101/2024.07.07.602380.

1056 38. Felipe Benites, L., Stephens, T.G., Van Etten, J., James, T., Christian, W.C., Barry, K., Grigoriev, I.V.,

1057   McDermott, T.R., and Bhattacharya, D. (2024). Hot springs viruses at Yellowstone National Park have

1058   ancient origins and are adapted to thermophilic hosts. Communications Biology *7*, 312.

1059   10.1038/s42003-024-05931-1.

1060 39. Thomas, E., Anderson, R.E., Li, V., Rogan, L.J., and Huber, J.A. (2021). Diverse Viruses in Deep-Sea

1061   Hydrothermal Vent Fluids Have Restricted Dispersal across Ocean Basins. mSystems *6*, e0006821.

1062   10.1128/mSystems.00068-21.

1063 40. Krishnamurthy, S.R., and Wang, D. (2017). Origins and challenges of viral dark matter. Virus Res *239*,

1064   136-142. 10.1016/j.virusres.2017.02.002.

1065 41. Chen, J., Guo, M., Wang, X., and Liu, B. (2016). A comprehensive review and comparison of different

1066   computational methods for protein remote homology detection. Brief Bioinform *19*, 231-244.

1067   10.1093/bib/bbw108.

1068 42. Monttinen, H.A.M., Ravantti, J.J., and Poranen, M.M. (2021). Structure Unveils Relationships between

1069   RNA Virus Polymerases. Viruses *13*. 10.3390/v13020313.

1070 43. Wolf, Y.I., Kazlauskas, D., Iranzo, J., Lucia-Sanz, A., Kuhn, J.H., Krupovic, M., Dolja, V.V., and

1071   Koonin, E.V. (2018). Origins and Evolution of the Global RNA Virome. mBio *9*. 10.1128/mBio.02329-

1072   18.

1073 44. Koonin, E.V., Dolja, V.V., Krupovic, M., Varsani, A., Wolf, Y.I., Yutin, N., Zerbini, F.M., and Kuhn, J.H.

1074   (2020). Global Organization and Proposed Megataxonomy of the Virus World. Microbiol Mol Biol Rev

1075   *84*. 10.1128/MMBR.00061-19.

1076 45. Wu, R., Bottos, E.M., Danna, V.G., Stegen, J.C., Jansson, J.K., and Davison, M.R. (2022). RNA

1077   Viruses Linked to Eukaryotic Hosts in Thawed Permafrost. mSystems *7*, e0058222.

1078   10.1128/msystems.00582-22.

1079 46. Charon, J., Murray, S., and Holmes, E.C. (2021). Revealing RNA virus diversity and evolution in

1080   unicellular algae transcriptomes. Virus Evolution *7*, veab070. 10.1093/ve/veab070.

1081 47. Ibarbalz, F.M., Henry, N., Brandao, M.C., Martini, S., Busseni, G., Byrne, H., Coelho, L.P., Endo, H.,

1082   Gasol, J.M., Gregory, A.C., et al. (2019). Global Trends in Marine Plankton Diversity across Kingdoms

1083   of Life. Cell *179*, 1084-1097 e1021. 10.1016/j.cell.2019.10.008.

1084 48. Kalu, E.I., Reyes-Prieto, A., and Barbeau, M.A. (2023). Community dynamics of microbial eukaryotes

1085   in intertidal mudflats in the hypertidal Bay of Fundy. ISME Communications *3*, 21. 10.1038/s43705-

1086   023-00226-8.

1087 49. Bollback, J.P., and Huelsenbeck, J.P. (2001). Phylogeny, genome evolution, and host specificity of

1088   single-stranded RNA bacteriophage (family Leviviridae). J Mol Evol *52*, 117-128.

1089   50.   Poranen, M.M., Mäntynen, S., and Ictv Report, C. (2017). ICTV Virus Taxonomy Profile: Cystoviridae.
1090   J Gen Virol *98*, 2423-2424. 10.1099/jgv.0.000928.
1091   51.   Callanan, J., Stockdale, S.R., Shkoporov, A., Draper, L.A., Ross, R.P., and Hill, C. (2018). RNA Phage
1092   Biology in a Metagenomic Era. Viruses *10*. 10.3390/v10070386.
1093   52.   Gan, T., and Wang, D. (2023). Picobirnaviruses encode proteins that are functional bacterial lysins.
1094   Proc Natl Acad Sci U S A *120*, e2309647120. 10.1073/pnas.2309647120.
1095   53.   Sharp, P.M., and Simmonds, P. (2011). Evaluating the evidence for virus/host co-evolution. Curr Opin
1096   Virol *1*, 436-441. 10.1016/j.coviro.2011.10.018.
1097   54.   Li, D., Liu, C.-M., Luo, R., Sadakane, K., and Lam, T.-W. (2015). MEGAHIT: an ultra-fast single-node
1098   solution for large and complex metagenomics assembly via succinct de Bruijn graph. Bioinformatics *31*,
1099   1674-1676. 10.1093/bioinformatics/btv033.
1100   55.   Gage, P. (1994). A New Algorithm for Data Compression. C Users J *12*, 23–38.
1101   10.5555/177910.177914.
1102   56.   Lin, Z., Akin, H., Rao, R., Hie, B., Zhu, Z., Lu, W., Smetanin, N., Verkuil, R., Kabeli, O., Shmueli, Y.,
1103   et al. (2023). Evolutionary-scale prediction of atomic-level protein structure with a language model.
1104   Science *379*, 1123-1130. 10.1126/science.ade2574.
1105   57.   He, Y., Wang, C., Zhang, S., Li, N., Li, Z.R., and Zeng, Z.Y. (2022). KG-MTT-BERT: Knowledge
1106   Graph Enhanced BERT for Multi-Type Medical Text Classification. arXiv.
1107   58.   Buchfink, B., Reuter, K., and Drost, H.-G. (2021). Sensitive protein alignments at tree-of-life scale
1108   using DIAMOND. Nat Methods *18*, 366-368. 10.1038/s41592-021-01101-x.
1109   59.   Potter, S.C., Luciani, A., Eddy, S.R., Park, Y., Lopez, R., and Finn, R.D. (2018). HMMER web server:
1110   2018 update. Nucleic Acids Research *46*, W200-W204. 10.1093/nar/gky448.
1111   60.   Katoh, K., and Standley, D.M. (2013). MAFFT multiple sequence alignment software version 7:
1112   improvements in performance and usability. Mol Biol Evol *30*, 772-780. 10.1093/molbev/mst010.
1113   61.   Babaian, A., and Edgar, R. (2022). Ribovirus classification by a polymerase barcode sequence. PeerJ
1114   *10*, e14055. 10.7717/peerj.14055.
1115   62.   Girvan, M., and Newman, M.E.J. (2002). Community structure in social and biological networks. Proc
1116   Natl Acad Sci U S A *99*, 7821-7826.
1117   63.   Csárdi, G., and Nepusz, T. (2006). The igraph software package for complex network research.
1118   64.   Steinegger, M., Meier, M., Mirdita, M., Vohringer, H., Haunsberger, S.J., and Soding, J. (2019). HH-
1119   suite3 for fast remote homology detection and deep protein annotation. BMC Bioinformatics *20*, 473.
1120   10.1186/s12859-019-3019-7.
1121   65.   Langmead, B., and Salzberg, S.L. (2012). Fast gapped-read alignment with Bowtie 2. Nat Methods *9*,
1122   357-359. 10.1038/nmeth.1923.
1123   66.   Hasegawa, H., and Holm, L. (2009). Advances and pitfalls of protein structural alignment. Curr Opin
1124   Struct Biol *19*, 341-348. 10.1016/j.sbi.2009.04.003.
1125   67.   Guindon, S., and Gascuel, O. (2003). A simple, fast, and accurate algorithm to estimate large
1126   phylogenies by maximum likelihood. Syst Biol *52*, 696-704.
1127   68.   Liu, J.F., H.Q., Liu, Z.Y, Wang, S., Zhang, Q., and He, Z.M. (2022). A Density-Based Spatial
1128   Clustering of Application with Noise Algorithm and its Empirical Research. Highlights in Science,
1129   Engineering and Technology *7*, 174-179.
1130

A

Known (defined by ICTV) Unclassified by ICTV Discovered in this study

● [0, 10) ⬤ [10, 100) ⬤ [100, 1,000) ⬤ [1,000, 10,000) ⬤ [10,000,)

B

Overall

No. of putative vial species

Ecosystem level

No. of samples

Ecosystem

Aquatic Terrestrial Extreme
Host (microbe) Host (plant) Food
Air Invertebrate Vertebrate

C

	No. of samples	Alpha diversity	RPM (log10)	No. of viral species in known-	No. of viral species in unclassied-	No. of viral species in new-
Marine	3,503					
Aquatic (other)	249					
Freshwater	1,031					
Wastewater	155					
Halite	57					
Subsurface	38					
Aquifer	83					
Surface	18					
Stromatolite	24					
Compost	52					
Freshwater sediment	132					
Sediment (other)	160					
Sludge	258					
Marine sediment	182					
Soil	1,567					
Wetland	124					
Hot springs	57					
Hydrothermal vent	172					
Non-marine saline	32					
Antarctic sediment	9					
Salt marsh	91					
Bioreactor	136					
Biofilm	317					
Anaerobic digester	90					
Wood decay	13					
Biogas fermenter	12					
Rhizosphere	394					
Leaf litter	209					
Food	229					
Air	283					
Invertebrate	125					
Vertebrate	441					

D

Ecosystem (subtype)

RNA virus

Ecosystem (subtype)

Marine Freshwater Marine sediment
Freshwater sediment Hydrothermal vent Salt marsh
Rhizosphere Leaf litter Air
Invertebrate Vertebrate

RNA virus

Environment-specific Animal-specifc Shared

RPM (log10)

0 1 2 3 4 5

Figure S1. Detailed RNA virus discovery pipeline, related to Figure 1.

(A) Schematic diagram of similarity-based discovery (i.e., ClstrSearch) and RdRP AI modeling (i.e., LucaProt).

(B) Protein clustering process; only clusters with more than ten members are retained for viral cluster discovery.

(C) Ten iterations of RdRP expansion by recruiting newly detected RdRPs in this process.

(D) RdRP clusters are merged into RdRP supergroups using BLAST median *e*-values.

(E) RdRP identification by a new deep learning model (i.e., LucaProt), that includes five modules: Input, Tokenizer, Encoder, Pooling, and Output.

A Sigmoid

B Data set Statistics

	Sequences	Positive Sequences	Negative Sequences	Max Seq Len	Min Seq Len
Entire Dataset	235,413	5,979	229,434	36,507	20
Training	190,845	4,899	185,946	36,507	23
Validation	22,284	540	21,744	17,258	54
Testing	22,284	540	21,744	7,182	20

C Confusion Matrix on Validation Set

	Actual Positives	Actual Negatives
Predicted Positives	540	1
Predicted Negatives	0	21,743

D Confusion Matrix on Testing Set

	Actual Positives	Actual Negatives
Predicted Positives	539	0
Predicted Negatives	1	21,744

E Metrics on Validation and Testing Set

	Accuracy	Precision (macro)	Recall (macro)	F1-score (macro)	AUC
Validation	0.999955	0.999076	0.999977	0.999526	0.99998923
Testing	0.999955	0.999977	0.999074	0.999525	0.99999991

F Metrics on 10-Fold Validation Set

	Accuracy	Precision (macro)	Recall (macro)	F1-score (macro)	AUC
Fold-01	0.999955	1.0	0.998148	0.999073	1.0
Fold-02	0.999910	0.998148	0.998148	0.998148	0.999976
Fold-03	1.0	1.0	1.0	1.0	1.0
Fold-04	0.999955	1.0	0.998148	0.999073	0.999998
Fold-05	1.0	1.0	1.0	1.0	1.0
Fold-06	1.0	1.0	1.0	1.0	1.0
Fold-07	1.0	1.0	1.0	1.0	1.0
Fold-08	0.999910	1.0	0.996296	0.998145	0.999995
Fold-09	1.0	1.0	1.0	1.0	1.0
Fold-10	1.0	1.0	1.0	1.0	1.0
Mean	0.999973	0.9998148	0.999074	0.9994439	0.9999969

G Metrics on 10-Fold Testing Set

	Accuracy	Precision (macro)	Recall (macro)	F1-score (macro)	AUC
Fold-01	0.999910	0.998148	0.998148	0.998148	0.999986
Fold-02	1.0	1.0	1.0	1.0	1.0
Fold-03	0.999910	0.998148	0.998148	0.998148	0.999994
Fold-04	1.0	1.0	1.0	1.0	1.0
Fold-05	1.0	1.0	1.0	1.0	1.0
Fold-06	1.0	1.0	1.0	1.0	1.0
Fold-07	0.999910	1.0	0.996296	0.998145	0.999991
Fold-08	1.0	1.0	1.0	1.0	1.0
Fold-09	1.0	1.0	1.0	1.0	1.0
Fold-10	0.999955	1.0	0.998148	0.999073	0.999997
Mean	0.9999685	0.9996296	0.999074	0.9993514	0.9999968

H Number of sequences vs Evalue — Total hits, Host hits

I RdRP vs Non-RdRP — Score; Covlen

J -Log10 (median evalue) by group

K -Log10 (Median evalue) panels: Astro-Poty, Birna-Permutotetra, Bunya-Arena, Cysto, Flavi, Hepe-Virga, Hypo, Luteo-Sobemo, Mono-Chu, Narna-Levi, Nido, Orthomyxo, Partiti-Picobirna, Picorna, Qinvirus, Reo, Quenyavirus, Tombus-Noda, Toti, Weivirus, Yanvirus, Yuevirus, Zhaovirus

Figure S2. Benchmarking of the LucaProt for the RdRP modeling and threshold used in ClstrSearch, related to Figure 1.
(A) The Sigmoid function of the LucaProt. The Sigmoid function, also called the Logistic function, is used for the output layer of a binary classification model, and mapping a real number to the probability of 0 ~ 1.
(B) Statistics of the data set used for LucaProt building, including the entire data set, training set, validation set, and testing set.
(C) The confusion matrix on the validation data set.
(D) The confusion matrix on the testing data set.
(E) The metrics for the validation and testing data sets.
(F) and (G) The metrics on the validation and testing sets of 10-fold cross-validation for LucaProt. The positive and negative samples were randomly shuffled and divided into ten parts, with each part containing 540 positive and 21,744 negative samples. In the 10-fold, two parts were selected rotationally to serve as the validation and testing sets, respectively, while the remaining samples were combined to form the training set.
(H) Number of hits with Diamond blastp v0.9.25.126 using different e-values at the test stage. A total of 15,000 sequences were randomly sampled for the test, and host hits were recognized by comparison against the NCBI non-redundant (nr) protein database (version 2023.01.09) with an e-value threshold of $1E$-3.
(I) Benchmarking of HMMscan bitscore and aligned fraction using the RdRP and non-RdRP data sets (including RT, Eu DdRP and Eu RdRP derived from the NCBI GenBank database).
(J) BLAST Median e-value within the same known RdRP cluster.
(K) BLAST Median e-value between pairwise comparisons of known RdRP clusters, with a $1E$-3 cut-off used for cluster merging.

Figure S3. Comparison of RNA virus discovery results between six previous studies and the current study, related to Figure 1.

(A) The distribution of putative viral species of seven studies at the supergroup level and the study-specific level.

(B) Upset plot shows the number of viral species found in each study and those are shared/unique between and among seven studies. The red bar in the top histogram represents unique viral species identified in each study, while the green bar indicates viral species that are shared between two or more studies. Rightmost histogram shows the number of metatranscriptomes analyzed in each study. Of note, Olendraite *et al.* sourced viral RdRPs from the NCBI Transcriptome Shotgun Assembly (TSA) database, such that the exact number of metatranscriptomes analyzed is unclear.

Figure S4. The three highly conserved RdRP sequence motifs (A, B and C) and the distribution of BLAST median e-value, HMM score and mean AI modeling probabilities of the RNA virus supergroups, related to Figure 4.
RNA viral supergroups were divided into three groups by similarity to reference and other published data sets, with the conserved RdRP A, B and C motifs of each supergroup shown on the left.

Figure S5. Expression difference of RNA viruses and DNA organisms in our newly sequenced data, related to Figure 4.

(A) Abundance comparisons for 58 RNA viral supergroups, four DNA virus families, RT and cell organisms at DNA and RNA libraries.

(B) RT-PCR results of second pairs of validation primers for representative RdRP sequences from 17 RNA viral supergroups, capsid sequences from two DNA virus families (Podoviridae and Siphoviridae), and RT sequences.

Nido

Figure S6. Phylogenetic tree of the Nido-like supergroup and the genome structure of representative viruses, related to Figure 5.
The tree was estimated using a maximum likelihood method based on the conserved RdRP domain. The reference sequences reported previously are shaded grey, while the viruses newly identified here are shaded by different colors according to different ecotypes. The names of viral families are shown on right of the tree. The tree was midpoint-rooted for clarity only, and the scale bar of tree indicates 0.2 amino acid substitutions per site. The genome structures of representative viruses are shown on right of the tree. At the bottom, scale indicates the length in nucleotides.

Figure S7. Specificity and shareability of RNA viruses, related to Figure 7.
(A) Number of specific putative viral species (i.e., putative "marker" viral species) in each ecosystem subtype.
(B) Association between RNA viruses and different environmental ecosystems. The size of the colored circles indicates the number of putative viral species identified by each ecosystem type, while the thickness of the line indicates the number of viral species shared by each ecosystem.