Human Attention during Goal-directed Reading Comprehension Relies on Task Optimization

Jiajie Zou[1], Yuran Zhang[1], Jialu Li[3], Xing Tian[3], Nai Ding[1,2*],

[1] Key Laboratory for Biomedical Engineering of Ministry of Education,

College of Biomedical Engineering and Instrument Sciences,

Zhejiang University, Hangzhou 310027, China

[2] Research Center for Applied Mathematics and Machine Intelligence,

Research Institute of Basic Theories, Zhejiang lab, Hangzhou 311121, China

[3] Division of Arts and Sciences, New York University Shanghai

Short title: Optimal Distribution of Reading Attention

*Corresponding author:

Nai Ding,

Email: ding_nai@zju.edu.cn

College of Biomedical Engineering and Instrument Sciences,

Zhejiang University, Hangzhou 310027, China

Abstract

The computational principles underlying attention allocation in complex goal-directed tasks remain elusive. Goal-directed reading, i.e., reading a passage to answer a question in mind, is a common real-world task that strongly engages attention. Here, we investigate what computational models can explain attention distribution in this complex task. We show that the reading time on each word is predicted by the attention weights in transformer-based deep neural networks (DNNs) optimized to perform the same reading task. Eye-tracking further reveals that readers separately attend to basic text features and question-relevant information during first-pass reading and rereading, respectively. Similarly, text features and question relevance separately modulate attention weights in shallow and deep DNN layers. Furthermore, when readers scan a passage without a question in mind, their reading time is predicted by DNNs optimized for a word prediction task. Therefore, we offer a computational account of how task optimization modulates attention distribution during real-world reading.

Keywords: computational neuroscience; reading comprehension; eye movements; deep neural network; attention

Introduction

Attention profoundly influences information processing in the brain [1-3], and a large number of studies have been devoted to studying the neural mechanisms of attention. From the perspective of David Marr, the attention mechanism can be studied from three levels, i.e., the computational, algorithmic, and implementational levels [4]. At the computational level, attention is traditionally viewed as a mechanism to allocate limited central processing resources [5-9]. More recent studies, however, propose that attention is a mechanism to optimize task performance, even in conditions where the processing resource is not clearly constrained [10-14]. The optimization hypothesis can explain the attention distribution in a range of well controlled learning and decision-making tasks [14, 15], but is rarely tested in complex processing tasks for which the optimal strategy is not obvious. Therefore, the computational principles that underlie the allocation of human attention during complex tasks remain elusive. Nevertheless, complex tasks are critical conditions to test whether the attention mechanisms abstracted from simpler tasks can truly explain real-world attention behaviors.

Reading is one of the most common and most sophisticated human behaviors [16, 17], and it is strongly regulated by attention: Since readers can only recognize a couple of words within one fixation, they have to overtly shift their fixation to read a line of text [3]. Thus, eye movements serve as an overt expression of attention allocation during reading [3, 18]. Computational modeling of the eye movements has mostly focused on

normal reading of single sentences. At the computational level, it has been proposed

that the eye movements are programed to, e.g., minimize the number of eye

movements [12]. At the algorithmic and implementational level, models such as the

E-Z reader [19] can accurately predict the eye movement trajectory with high

temporal and spatial resolution. Everyday reading behavior, however, often engages

reading of a multi-line passage and generally has a clear goal, e.g., information

retrieval or inference generation [20]. Few models, however, have considered how the

reading goal modulates reading behaviors. Here, we address this question by

analyzing how readers allocate attention when reading a passage to answer a specific

question in mind. The question may require, e.g., information retrieval, inference

generation, or text summarization (Fig. 1). We investigate whether the task

optimization hypothesis can explain the attention distribution in such goal-directed

reading tasks.

Finding an optimal solution for the goal-directed reading task, however, is

computationally challenging since the information related to question answering is

sparsely located in a passage and their orthographic forms may not be predictable.

Recent advances in DNN models, however, provide a potential tool to solve this

computational problem, since DNN models equipped with attention mechanisms

have approached and even surpassed mean human performance on goal-directed

reading tasks [21, 22]. Attention in DNN also functions as a mechanism to selectively

extract useful information, and therefore attention may potentially serve a

conceptually similar role in DNN. Furthermore, recent studies have provided strong

evidence that task-optimized DNN can indeed explain the neural response properties

in a range of visual and language processing tasks [23-30]. Therefore, although the

DNN attention mechanism certainly deviates from the human attention mechanism in

terms of its algorithms and implementation, we employ it to probe the computational-

level principle underlying human attention distribution during real-world goal-

directed reading.

Here, we investigated what computational principles could generate human-like

attention distribution during a goal-directed reading task. We employed DNNs to

derive a set of attention weights that are optimized for the goal-directed reading task,

and tested whether such optimal weights could explain human attention measured by

eye tracking. Furthermore, since both human and DNN processing is hierarchical, we

also investigated whether the human attention distribution during different processing

stages, which are characterized through different eye tracking measures, and the DNN

attention weights in different layers may be differentially influenced by visual

features, text properties, and the top-down task. Additionally, we recruited both native

and non-native readers to probe how language proficiency contributed to the

computational optimality of attention distribution.

Results

Experiment 1: Task and Performance

In Experiment 1, the participants ($N = 25$ for each question) first read a question and

then read a passage based on which the question should be answered (Fig. 1A). After

reading the passage, the participants chose from 4 options which option was the most

suitable answer to the question. In total, 800 question/passage pairs were adapted

from the RACE dataset [31], a collection of reading comprehension questions

designed for Chinese high school students who learn English as a second language.

The questions fell into 6 types (Fig. 1BC): Three types of questions required attention

to details, e.g., retrieving a fact or generate inference based on a fact, which were

referred to as local questions. The other 3 types of questions concerned the general

understanding of a passage, e.g., summarizing the main idea or identifying the

purpose of writing, which were referred to as global questions. None of the question

directly appeared in the passage, and the longest string that overlapped in the passage

and question was 1.8 ± 1.5 words on average.

Participants in Experiment 1 were Chinese college or graduate students who had

relatively high English proficiency. The participants correctly answered 77.94%

questions on average and the accuracy was comparable across the 6 types of questions

(Fig. 1B). We employed computational models to analyze what kinds of computations

were required to answer the questions. The simplest heuristic model chose the option

that best matched the passage orthographically (Fig. S1A). This orthographic model

achieved 25.6% accuracy (Fig. 1B). Another simple heuristic model only considered

word-level semantic matching between the passage and option, and achieved 27.3%

accuracy (Fig. 1B). The low accuracy of the two models indicated that the reading

comprehension questions could not be answered by word-level orthographic or

semantic matching.

Next, we evaluated the performance of 4 context-dependent DNN models, i.e.,

Stanford Attentive Reader (SAR) [32], BERT [33], ALBERT [21], and RoBERTa

[22], which could integrate information across words to build passage-level semantic

representations. The SAR used the bi-directional recurrent neural network (RNN) to

integrate contextual information (Fig. S1B) and achieved 47.6% accuracy. The other 3

models, i.e., BERT, ALBERT, and RoBERTa, were transformer-based models that

were trained in 2 steps, i.e., pre-training and fine-tuning (Fig. 1D). Since the 3 models

had similar structures, we averaged the performance over the 3 models (see Fig. S2

for the results of individual models). The model performance on the reading task was

37.08% and 73%, respectively, after pre-training and fine-tuning (Fig. 1B).

Computational Models of Human Attention Distribution

In Experiment 1, participants were allowed to read each passage for 2 minutes.

Nevertheless, to encourage the participants to develop an effective reading strategy,

the monetary reward the participant received decreased as they spent more time

reading the passage (see *Materials and Methods* for details). The results showed that

the participants spent, on average, 0.7 ± 0.2 minutes reading each passage (Fig. 1C),

corresponding to a reading speed of 457 ± 142 words/minute when divided by the

number of words per passage. The speed was almost twice the normal reading speed

for native readers [3], indicating a specialized reading strategy for the task.

Next, we employed eye tracking to quantify how the readers allocated their attention

to achieve effective reading and analyze which computational models could explain

the reading time on each word, i.e., the total fixation duration on each word during

passage reading. In other words, we probed into what kind of computational

principles could generate human-like attention distribution during goal-directed

reading. A simple heuristic strategy was to attend to words that were orthographically

or semantically similar to the words in the question (Fig. S1A). The predictions of the

heuristic models were not highly correlated with the human word reading time, and

the predictive power, i.e., the Pearson correlation coefficient between the predicted

and real word reading time, was around 0.2 (Fig. S3A).

The DNN models analyzed here, i.e., SAR, BERT, ALBERT, and RoBERTa, all

employed the attention mechanism to integrate over context to find optimal question

answering strategies. Roughly speaking, the attention mechanism applied a weighted

integration across all input words to generate a passage-level representation and

decide whether an option was correct or not, and the weight on each word was

referred to as the attention weight (see Fig. S1B and Fig. 2B for illustrations about the

attention mechanisms in the SAR and transformer-based models, respectively). When

the attention weights of the SAR were used to predict the human word reading time,

the predictive power was about 0.1 (Fig. 3A, Table S1).

In contrast to assigning a single weight on a word, the transformer-based model

employed a multi-head attention mechanism: Each of the 12 layers had 12 parallel

attention modules, i.e., heads. Consequently, each word had 144 attention weights (12

layers $\times$ 12 heads), which were used to model the word reading time of humans based

on linear regression. Since the attention weights of 3 transformer-based models

showed comparable power to predict human word reading time, we reported the

predictive power averaged over models (see Fig. S3A for the results of individual

models). The attention weights of randomly initialized transformer-based models

could predict the human word reading time and the predictive power, which was

around 0.3, was significantly higher than the chance level and the SAR (Fig. 3A,

Table S1). The attention weights of pre-trained transformer-based models could also

predict the human word reading time, the predictive power was around 0.5,

significantly higher than the predictive power of heuristic models, the SAR, and

randomly initialized transformer-based models (Fig. 3A, Table S1). The predictive

power was further boosted for local but not global questions when the models were

fine-tuned to perform the goal-directed reading task (Fig. 3A, Table S1). The weights

assigned to attention heads in the linear regression were shown in Fig. S4. For the

fine-tuned models, we also predict the human word reading time using an unweighted

averaged of the 144 attention heads and the predictive power was 0.3, significantly

higher than that achieved by the attention weights of SAR ($P = 4 \times 10^{-5}$, bootstrap).

These results suggested that the human attention distribution was consistent with the

attention weights in transformer-based models that were optimized to perform the

same goal-directed reading task.

Factors Influencing Human Word Reading Time

The attention weights in transformer-based DNN models could predict the human

word reading time. Nevertheless, it remained unclear whether such predictions were

purely driven by basic text features that were known to modulate word reading time.

Therefore, in the following, we first analyzed how basic text features modulated the

word reading time during the goal-directed reading task, and then checked whether

transformer-based DNNs could capture additional properties of the word reading time

that could not be explained by basic text features.

Here, we further decomposed text features into visual layout features, i.e., position of

a word on the screen, and word features, e.g., word length, frequency, and surprisal.

Layout features were features that were mostly induced by line changes, which could

be extracted without recognizing the words, while word features were finer-grained

features that could only be extracted when the word or neighboring words were

fixated. Linear regression analyses revealed layout features could significantly predict

the word reading time (Fig. 3B, Table S2). Furthermore, the predictive power was

higher for global than local questions (P = 4 × 10^{-5}, bootstrap, FDR corrected for

comparisons across 3 features, i.e., layout features, word features, and question

relevance), suggesting a question-type-specific reading strategy. Word features could

also significantly predict human reading time, even when the influence of layout

features was regressed out. The predictive power of the layout and word features,

however, was lower than the predictive power of attention weights of transformer-

based models (P = 4 × 10^{-5}, bootstrap, FDR corrected for comparisons across 2

features, i.e., layout and word features).

When the layout and word features were regressed out, the residual word reading time

was still significantly predicted by the attention weights in transformer-based models

(Fig. S3B, predictive power about 0.3). This result indicated that what the

transformer-based models extracted were more than basic text features. Next, we

analyzed whether the transformer-based models, as well as the human word reading

time, were sensitive to task-related features. To characterize the relevance of each

word to the question answering task, we asked another group of participants to

annotate which words contributed most to question answering. The annotated

question relevance could significantly predict word reading time, even when the

influences of layout and word features were regressed out (Fig. 3B, Table S2). When

the question relevance was also regressed out, the residual word reading time was still

significantly predicted by the attention weights in transformer-based models (Fig.

S3C, P = 0.003, bootstrap, FDR corrected for comparisons across 12 models × 6

question types), but the predictive power dropped to about 0.2. Furthermore, a linear

mixed effect model also revealed that more than 85% of the DNN attention heads

contribute to the prediction of human reading time when considering text features and

question relevance as covariates (*Supplementary Results*). These results demonstrated

that the DNN attention weights provided additional information about the human

word reading time than the text-related and task-related features analyzed here.

Further analyses revealed two properties of the distribution of question-relevant

words. First, for local questions, the question-relevant words were roughly uniformly

distributed in the passage, while for global questions, the question-relevant words

tended to be near the passage beginning (Fig. S5A). The eye tracking data showed

that readers also spent more time reading the passage beginning for global than local

questions (Fig. 3C), explaining why layout features more strongly influenced the

answering of global than local questions. Second, few lines in the passage were

question relevant (Fig. S5B), and the eye tracking data showed that readers spent

more time reading the line with the highest question relevance (Fig. 3D), confirming

the influence of question relevance on word reading time.

Attention in Different Processing Stages for Humans and DNNs

Next, we investigated whether humans and DNNs attended to different features in

different processing stages. The early stage of human reading was indexed by the gaze

duration, i.e., duration of first-pass reading of a word, and the later stage was indexed

by the counts of rereading. Results showed the influence of layout features increased

from early to late reading stages for global but not local questions (Fig. 4A, Table S3).

Consequently, the passage-beginning-effect differed between global and local

questions only for the late reading stage (Fig. S6A). The influence of word features

did not strongly change between reading stages, while the influence of question

relevance significantly increased from early to late reading stages (Fig. 4A, Fig. S6B).

These results suggested that attention to basic text features developed early, while the

influence of task mainly influenced late reading processes.

In the following, we further investigated whether transformer-based DNN attended to

different features in different layers, which represented different processing stages.

This analysis did not include layout features that were not available to the models.

The attention weights in shallow layers were sensitive to word features in

randomized, pre-trained, and fine-tuned models (Fig. 4BC). Only in the fine-tuned

models, however, the attention weights in deep layers were sensitive to question

relevance (see Figs. S7 & S8 for results of individual models). Therefore, the shallow

and deep layers separately evolved text-based and goal-directed attention, and goal-

directed attention was induced by fine-tuning on the task.

Experiment 2: Question-Type-Specificity of the Reading Strategy

In Experiment 1, different types of questions were presented in blocks which

encouraged the participants to develop question-type-specific reading strategies. Next,

we ran Experiment 2, in which questions from different types were mixed and

presented in a randomized order, to test whether the participants developed question-

type-specific strategies in Experiment 1. Since it was time consuming to measure the

response to all 800 questions, we randomly selected 96 questions for Experiment 2

(16 questions per type). In Experiment 2, the reading speed was on average 298 ± 123

words/minute, lower than the speed in Experiment 1 ($P = 6 \times 10^{-4}$, bootstrap, FDR

corrected for the comparisons across 4 experiments), but still much faster than normal

reading speed [3].

The word reading time was better predicted by fine-tuned than pre-trained

transformer-based models (Fig. 5A, Table S4). For the influence of text and task-

related features, compared to Experiment 1, the predictive power in Experiment 2 was

higher for layout and word features, but lower for question relevance (Fig. 5B, Table

S5). For local questions, consistent with Experiment 1, the effects of question

relevance significantly increased from early to late processing stages that are

separately indexed by gaze duration and counts of rereading (Fig. S9A, Table S3). The

passage beginning effect was higher for global than local questions (Fig. 5C, 2^{nd}

column, $P = 2 \times 10^{-4}$, bootstrap, FDR corrected for the comparisons across 4

experiments), but the difference was smaller than in Experiment 1 (Fig. 5C & Fig.

S10A, $P = 2 \times 10^{-4}$, bootstrap, FDR corrected for the comparisons across 4

experiments). The question relevance effect was also smaller in Experiment 2 than

Experiment 1 (Fig. 5D & Fig. S10B, $P = 2 \times 10^{-4}$, bootstrap, FDR corrected for the

comparisons across 4 experiments). All these results indicated that the readers

developed question-type-specific strategies in Experiment 1, which led to faster

reading speed and stronger task modulation of word reading time.

Experiment 3: Effect of Language Proficiency

Experiments 1 and 2 recruited L2 readers. To investigate how language proficiency

influenced task modulation of attention and the optimality of attention distribution, we

ran Experiment 3, which was the same as Experiment 2 except that the participants

were native English readers. In Experiment 3, the reading speed was on average $506 \pm$

155 words/minute, higher than that in Experiment 2 ($P = 6 \times 10^{-4}$, bootstrap, FDR

corrected for the comparisons across 4 experiments). The question answering

accuracy was comparable to L2 readers (Fig. 1B).

The word reading time for native readers was slightly better predicted by fine-tuned

than pre-trained transformer-based models (Fig. 5A, Table S4). For the influence of

text and task-related features, compared to Experiment 2, the predictive power in

Experiment 3 was higher for word features, but lower for layout features and question

relevance (Table S5). For local questions, the layout effect was more salient for gaze

duration than for counts of rereading. In contrast, the effect of word-related features

and task relevance was more salient for counts of rereading than gaze duration (Fig.

S9B, Table S3). The passage beginning effect was higher for global than local

questions, but the difference was smaller than in Experiment 2 (Fig. 5C & Fig. S10A,

$P = 2 \times 10^{-4}$, bootstrap, FDR corrected for the comparisons across 4 experiments). The

question relevance effect was also smaller for Experiment 3 than Experiment 2 (Fig.

5D & Fig. S10B, $P = 2 \times 10^{-4}$, bootstrap, FDR corrected for the comparisons across 4

experiments). These results showed that the word reading time of native readers was

significantly modulated by the task, but the effect was weaker than that on L2 readers.

Experiment 4: General-Purpose Reading

In the goal-directed reading task, participants read a passage to answer a question that

they knew in advance, and the eye tracking results revealed that participants spent

more time reading question-relevant words. Question-relevant words, however, were

generally longer content words (Fig. S5CD) that were often associated with longer

reading time even without a task [3]. Therefore, to validate the question relevance

effect, we ran Experiment 4 in which the participants read the passages without

knowing the question to answer. The experiment used the same 96 questions as in

Experiments 2 and 3, but adopted a different experimental procedure: Participants

previewed a passage before reading the question, and were allowed to read the

passage again to answer the question. We analyzed the reading pattern during passage

preview, which was referred to as general-purpose reading.

The participants were given 1.5 minutes to preview the passage, and the reading speed

was on average 225 ± 40 words/minute, lower than that in Experiments 1-3 ($P = 6 \times$

10^{-4}, bootstrap, FDR corrected for comparisons across 4 experiments). Before

question answering, they were given another 0.5 minutes to reread the passage, but on

average they spent only 0.04 minute on rereading it. During passage preview, the

word reading time was similarly predicted by the pre-trained and fine-tuned

transformer-based models (Fig. 5A, Table S4). Furthermore, the word reading time

was significantly predicted by layout and word features, but not question relevance

(Fig. 5B, Table S4). Both the early and late processing stages of human reading were

significantly affected by layout and word features, and the effects were larger for the

late processing stage indexed by counts of rereading (Fig. S9C, Table S3). The

passage beginning effect was not significantly different between local and global

questions (Fig. 5C, 4th column, P = 0.994, bootstrap, FDR corrected for comparisons

across 4 experiments), and the question relevance effect was significantly smaller than

the question relevance effect in Experiments 1-3 (Fig. 5D & Fig. S10B, P = 2×10^{-4},

bootstrap, FDR corrected for comparisons across 4 experiments). These results

confirmed that the question relevance effects observed during goal-directed reading

were indeed task dependent.

Discussion

Attention is a crucial mechanism to regulate information processing in the brain and it

has been hypothesized that a common computational role of attention is to optimize

task performance. Previous support for the hypothesis mostly comes from tasks for

which the optimal strategy can be easily derived. The current study, however,

considers a real-world reading task in which the participants have to actively sample a

passage to answer a question that cannot be answered by simple word-level

orthographic or semantic matching. In this challenging task, it is demonstrated that

human attention distribution can be explained by the attention weights in transformer-

based DNN models that are optimized to perform the same reading task but blind to

the human eye tracking data. Furthermore, when participants scan a passage without

knowing the question to answer, their attention distribution can also be explained by

transformer-based DNN models that are optimized to predict a word based on the

context.

Furthermore, we demonstrate that both humans and transformer-based DNN models

achieve task-optimal attention distribution in multiple steps: For humans, basic text

features strongly modulate the duration of the first reading of a word, while the

question relevance of a word only modulates how many times the word is reread,

especially for high-proficiency L2 readers compared to native readers. Similarly, the

DNN models do not yield a single attention distribution, and instead it generates

multiple attention distributions, i.e., heads, for each layer. Here, we demonstrate that

basic text features mainly modulate the attention weights in shallow layers, while the

question relevance of a word modulates the attention weights in deep layers,

reflecting hierarchical control of attention to optimize task performance. The attention

weights in both the shallow and deep layers of DNN contribute to the explanation of

human word reading time (Fig. S4).

Computational models of attention

A large number of computational models of attention have been proposed. According to Marr's 3 levels of analysis [4], some models investigate the computational goal of attention [10, 12] and some models provide an algorithmic implementation of how different factors modulate attention [19, 34]. Computationally, it has been hypothesized that attention can be interpreted as a mechanism to optimize learning and decision making, and empirical evidence has been provided that the brain allocates attention among different information sources to optimally reduce the uncertainty of a decision [10-12]. The current study provides critical support to this hypothesis in a real-world task that engages multiple forms of attention, e.g., attention to visual layout features, attention to word features, and attention to question-relevant information. These different forms of attention, which separately modulate different eye tracking measures (Fig. 4A), jointly achieve an attention distribution that is optimal for question answering.

The transformer-based DNN models analyzed here are optimized in two steps, i.e., pre-training and fine-tuning. The results show that pre-training leads to text-based attention that can well explain general-purpose reading in Experiment 4, while the fine-tuning process leads to goal-directed attention in Experiments 1-3 (Fig. 4B & Fig. 5A). Pre-training is also achieved through task optimization, and the pre-training task used in all the three models analyzed here is to predict a word based on the context. The purpose of the word prediction task is to let models learn the general

statistical regularity in a language based on large corpora, which is crucial for model

performance on downstream tasks [21, 22, 33], and this process can naturally

introduce the sensitivity to word surprisal, i.e., how unpredictable a word is given the

context. Previous eye-tracking studies have suggested that the predictability of words,

i.e., surprisal, can modulate reading time [35], and neuroscientific studies have also

indicated that the cortical responses to language converge with the representations in

pre-trained DNN models [25, 26]. The results here further demonstrate that the DNN

optimized for the word prediction task can evolve attention properties consistent with

the human reading process. Additionally, the tokenization process in DNN can also

contribute to the similarity between human and DNN attention distributions: DNN

first separates words into tokens (e.g., "tokenization" is separated into "token" and

"ization"). Tokens are units that are learned based on co-occurrence of letters, and is

not strictly linked to any linguistically defined units. Since longer words tend to be

separated into more tokens, i.e., fragments of frequently co-occurred letters, longer

words receive more attention even if the model pay uniform attention to each of its

input, i.e., a token.

A separate class of models investigates which factors shape human attention

distribution. A large number of models are proposed to predict bottom-up visual

saliency [36, 37], and recently DNN models are also employed to model top-down

visual attention. It is shown that, through either implicit [38, 39] or explicit training

[40], DNNs can predict which parts of a picture relate to a verbal phrase, a task

similar to goal-directed visual search [41]. The current study distinguishes from these studies in that the DNN model is not trained to predict human attention. Instead, the DNN models naturally generate human-like attention distribution when trained to perform the same task that humans perform, suggesting that task optimization is a potential cause for human attention distribution during reading.

Models for human reading and human attention to question-relevant information

How human readers allocate attention during reading is an extensively studied topic, mostly based on studies that instruct readers to read a sentence in a normal manner, not aimed to extract a specific kind of information [18]. Previous eye tracking studies have shown that the readers fixate longer upon, e.g., longer words, words of lower-frequency, words that are less predictable based on the context, and words at the beginning of a line [3]. A number of models, e.g., the E-Z reader [19] and SWIFT [42], have been proposed to predict the eye movements during reading based on basic oculomotor properties or lexical processing [19]. Some models also view reading as an optimization process that minimizes the time or the number of saccades required to read a sentence [12, 13]. These models can generate fine-grained predictions, e.g., which letter in a word will be fixated first, for the reading of simple sentences, but have only been occasionally tested for complex sentences or multi-line texts [43] or to characterize different reading tasks, e.g., z-string reading and visual searching [44].

When readers read a passage to answer a question that can be answered using a word-

matching strategy [45], a recent study has demonstrated that the specific reading goal

modulates the word reading time and the effect can be modeled using a RNN model

[46]. Here, we focus on questions that cannot be answered using a word-matching

strategy (Fig. 1B) and demonstrate that, for these challenging questions, attention is

still modulated by the reading goal but the attention modulation cannot be explained

by a word-matching model (Fig. S3). Instead, the attention effect is better captured by

transformer models than an advanced RNN model, i.e., the SAR (Fig. 3A).

Combining the current study and the study by Hahn et al. [46], it is possible that the

word reading time during a general-purpose reading task can be explained by a word

prediction task, the word reading time during a simple goal-directed reading task that

can be solved by word matching can be modeled by a RNN model, while the word

reading time during a more complex goal-directed reading task involving inference is

better modeled using a transformer model. The current study also further

demonstrates that elongated reading time on task-relevant words is caused by counts

of rereading and further studies are required to establish whether earlier eye

movement measures can be modulated by, e.g., a word matching task. In addition,

future studies can potentially integrate classic eye movement models with DNNs to

explain the dynamic eye movement trajectory, possibly with a letter-based spatial

resolution.

When human readers read a passage with a particular goal or perspective, previous

studies have revealed inconsistent results about whether the readers spent more time

reading task-relevant sentences [47-49]. To explain the inconsistent results, it has been

proposed that the question relevance effect weakens for readers with a higher working

memory and when readers read a familiar topic [50]. Similarly, here, we demonstrate

that non-native readers indeed spend more time reading question-relevant information

than native readers do (Fig. 5D & Fig. S10B). Therefore, it is possible that when

readers are more skilled and when the passage is relatively easy to read, their

processing is so efficient so that they do not need extra time to encode task-relevant

information and may rely on covert attention to prioritize the processing of task-

relevant information.

DNN attention to question-relevant information

A number of studies have investigated whether the DNN attention weights are

interpretable, but the conclusions are mixed: Some studies find that the DNN attention

weights are positively correlated with the importance of each word [51, 52], while

other studies fail to find such correlation [53, 54]. The inconsistent results are

potentially caused by the lack of gold standard to evaluate the contribution of each

word to a task. A few recent studies have used the human word reading time as the

criterion to quantify word importance, but these studies do not reach consistent

conclusions either. Some studies find that the attention weights in the last layer of

transformer-based DNN models better correlates with human word reading time than

basic word frequency measures [55], and integrating human word reading time into

DNN can slightly improve task performance [56]. Other studies, however, find no

meaningful correlation between the attention weights in transformer-based DNNs and

human word reading time [57].

The current results provide a potential explanation for the discrepancy in the

literature: The last layer of transformer-based DNNs is tuned to task relevant

information (Fig. 4B), but the influence of task relevance on word reading time is

rather weak for native readers (Fig. 5B). Consequently, the correlation between the

last-layer DNN attention weights and human reading time may not be robust. The

current results demonstrate that the reading time of both native and non-native readers

are reliably modulated by basic text features, which can be modeled by the attention

weights in shallower DNN layers.

Finally, the current study demonstrates that transformer-based DNN models can

automatically generate human-like attention, in the absence of any prior knowledge

about the properties of the human reading process. Simpler models that fail to explain

human performance also fail to predict human attention distribution. It remains

possible, however, different models can solve the same computational problem using

distinct algorithms, and only some algorithms generate human-like attention

distribution. In other words, human-like attention distribution may not be a unique

solution to optimize the goal-directed reading task. Sharing similar attention

distribution with humans, however, provides a way to interpret the attention weights

in computational models. From this perspective, the dataset and methods developed

here provides an effective probe to test the biological plausibility of NLP models that

can be easily applied to test whether a model evolves human-like attention

distribution.

Materials and Methods

Participants

Totally, 162 participants took part in this study (19-30 years old, mean age, 22.5

years; 84 female). All participants had normal or corrected-to-normal vision.

Experiment 1 had 102 participants. Experiments 2-4 had 20 participants. No

participant took part in more than one experiment. Additional 17 participants were

recruited but failed to pass the calibration process for eye tracking and therefore did

not participant in the reading experiments.

In Experiments 1, 2 and 4, participants were native Chinese readers. They were

college students or graduate students from Zhejiang University, and were thus above

the level required to answer high-school-level reading comprehension questions.

English proficiency levels were further guaranteed by the following criterion for

screening participants: a minimum score of 6 on IELTS, 80 on TOEFL, or 425 on

CET6[1]. In Experiment 3, participants were native English readers. The experimental

---

[1] The National College English Test (CET) is a national English test system developed to examine the English proficiency of college students in China. The CET includes tests of two levels: a lower level test CET4 and a higher level test CET6.

procedures were approved by the Research Ethics Committee of the College of

Medicine, Zhejiang University (2019–047). The participants provided written consent

and were paid.

Experimental materials

The reading materials were selected and adapted from the large-scale RACE dataset, a

collection of reading comprehension questions in English exams for middle and high

schools in China [31]. We selected 800 high-school level questions from the test set of

RACE and each question was associated with a distinct passage (117 to 456 words per

passage). All questions were multiple-choice questions with 4 alternatives including

only one correct option among them. The questions fell into 6 types, i.e., Cause ($N =$

200), Fact ($N = 200$), Inference ($N = 120$), Theme ($N = 100$), Title ($N = 100$), and

Purpose ($N = 80$). The Cause, Fact, and Inference questions concerned the location,

extraction, and comprehension of specific information from a passage, and were

referred to as local questions. Questions of Theme, Title, and Purpose tested the

understanding of a passage as a whole, and were referred to as global questions.

In a separate online experiment, we acquired annotations about the relevance of each

word to the question answering task. For each passage, a participant was allowed to

annotate up to 5 key words that were considered relevant to answering the

corresponding question. Each passage was annotated by N participants ($N \geq 26$),

producing N versions of annotated key words. Each version of annotation was then

validated by a separate participant. In the validation procedure, the participant was

required to answer the question solely based on the key words of a specific annotation

version; if the person could not derive the correct answer, this version of annotation

was discarded. The percentage of questions correctly answered in the validation

procedure was 75.9% and 67.6%, for local and global questions respectively. If M

versions of annotation passed the validation procedure and a word was annotated in K

versions, the question relevance of the word was K/M. More details about the question

types and the annotation procedures could be found in the reference [58].

Experimental procedures

Experiment 1: Experiment 1 included all 800 passages, and different question types

were separately tested in different sessions, hence 6 sessions in total. Each session

included 25 participants and one participant could participate in multiple sessions.

Before each session, participants were familiarized with 5 questions that were not

used in the formal session. During the formal session, questions were presented in a

randomized order. Considering the quantities of questions, for Cause and Fact

questions, the session was carried out in 3 separate days (one third questions on each

day), and for other question types, the session was carried out in 2 separate days (fifty

percent of questions on each day).

The experiment procedure in Experiment 1 was illustrated in Fig. 1A. In each trial,

participants first read a question, pressed the space bar to read the corresponding

passage, pressed the space bar again to read the question coupled with 4 options, and

chose the correct answer. The time limit for passage reading was 120 s. To encourage

the participants to read as quickly as possible, the bonus they received for a specific

question would decrease linearly from 1.5 to 0.5 RMB over time. They did not

receive any bonus for the question, however, if they gave a wrong answer.

Furthermore, before answering the comprehension question, the participants reported

whether they were confident about that they could correctly answer the question (yes

or no). Participants selected yes for 90.47% of questions (89.62% and 92.04% for

local and global questions, respectively). After answering the question, they also rated

their confidence about their answer on the scale of 1-4 (low to high). The mean

confidence rating was 3.25 (3.28 and 3.18 for local and global question, respectively),

suggesting that the participants were confident about their answers.

Experiments 2 and 3: Experiments 2 and 3 included 96 reading passages and

questions that were randomly selected from the questions used in Experiment 1 and

included 16 questions for each question type. The 6 types of questions were mixed

and presented in a randomized order. The trial structure, as well as the familiarization

procedure, in Experiments 2 and 3 was identical to that in Experiment 1. Experiments

2 and 3 were identical except that Experiment 2 recruited high-proficiency L2 readers

while Experiment 3 recruited native English readers.

Experiment 4: Experiment 4 included the 96 questions presented in Experiments 2

and 3, which were presented in a randomized order. The trial structure in Experiment

4 is similar to that in Experiments 1-3, except that a 90-s passage preview stage was

introduced at the beginning of each trial. During passage preview, participants had no

prior information of the relevant question. The participants could press the space bar

to terminate the preview and to read a question. Then, participants read the passage

again with a time limit of 30 s, before proceeding to answer the question. The

payment method was similar to Experiment 2, and the bonus was calculated based on

the duration of second-pass passage reading.

Stimulus presentation and eye tracking

The text was presented using the bold Courier New font, and each letter occupied 14

$\times$ 27 pixels. We set the maximum number of letters on each line to 120 and used

double space. We separated paragraphs by indenting the first line of each new

paragraph. Participants sat about 880 mm from a monitor, at which each letter

horizontally subtended approximately 0.25 degrees of visual angle.

Eye tracking data were recorded from the left eye with 500-Hz sampling rate (Eyelink

Portable Duo, SR Research). The experiment stimuli were presented on a 24-inch

monitor (1920 $\times$ 1080 resolution; 60 Hz refresh rate) and administered using

MATLAB Psychtoolbox [59]. Each experiment started with a 13-point calibration and

validation of eye tracker, and the validation error was required to be below 0.5

degrees of visual angle. Furthermore, before each trial, a 1-point validation was

applied, and if the calibration error was higher than 0.5 degrees of visual angle, a

recalibration was carried out. Head movements were minimized using a chin and

forehead rest.

Word-level reading comprehension models

The orthographic and semantic models probed whether the reading comprehension

questions could be answered based on word-level orthographic or semantic

information. Both models calculated the similarity between each content word in the

passage and each content word in an option, and averaged the word-by-word

similarity across all words in the passage and all words in the option (Fig. S1A). The

option with the highest mean similarity value was chosen as the answer. For the

orthographic model, similarity was quantified using the edit distance [60]. For the

semantic model, similarity was quantified by the correlation between vectorial

representations of word meaning, i.e., the glove model [61]. Performance of the

models remained similar if the answer was chosen based on the maximal word-by-

word similarity, instead of the mean similarity.

RNN-based reading comprehension models

The SAR was a classical RNN-based model for the reading comprehension task [32].

In contrast to the word-level models, the SAR was context sensitive and employed bi-

directional RNNs to integrate information across words (Fig. S1B). Independent bi-

directional RNNs were employed to build a vectorial representation for the question

and each option. An additional bi-directional RNN was applied to construct a

vectorial representation for each word in the passage, and a passage representation

was built by a weighted sum of the representations of individual words in the passage.

The weight on each word, i.e., the attention weight, captured the similarity between

the representation of the word and the question representation using a bilinear

function. Finally, based on the passage representation and each option representation,

a bilinear dot layer calculated the possibility that the option was the correct answer.

Transformer-based reading comprehension models

We tested 3 popular transformer-based DNN models, i.e., BERT [33], ALBERT [21],

and RoBERTa [22], which were all reported to reach high performance on the reading

comprehension task. ALBERT and RoBERTa were both adapted from BERT, and had

the same basic structure. RoBERTa differed from BERT in its pre-training procedure

[22] while ALBERT applied factorized embedding parameterization and cross-layer

parameter sharing to reduce memory consumption [21]. Following previous studies

[21, 22], each option was independently processed. For the i^{th} option ($i = 1, 2, 3,$ or 4),

the question and the option were concatenated to form an integrated option. As shown

in the left panel of Fig. 2B, for the i^{th} option, the input to models was the following

sequence:

$$CLS_i, P_1, P_2, ..., P_N, S_{i,1}, O_{i,1}, O_{i,2}, ..., O_{i,M}, S_{i,2},$$

where CLS_i, $S_{i,1}$, and $S_{i,2}$ denoted special tokens separating different components of

the input. P_1, P_2, …, P_N denoted all the N words of a passage, and $O_{i,1}$, $O_{i,2}$, …, $O_{i,M}$

denoted all the M words in the ith integrated option. Each of the token was represented

by a vector. The vectorial representation was updated in each layer, and in the

following the output of the lth layer was denoted as a superscript, e.g., CLS_i^l.

Following previous studies [21, 22], we calculated a score for each option, which

indicated the possibility that the option was the correct answer. The score was

calculated by first applying a linear transform to the final representation of the CLS

token, i.e.,

690
$$s_i = \Phi CLS_i^{12},$$

692　where CLS_i^{12} was the final output representation of CLS and Φ was a vector learned

693　from data. The score was independently calculated for each option and then

694　normalized using the following equation:

696
$$score_i = \frac{exp(s_i)}{\sum_{i=1}^{4} exp(s_i)}.$$

The answer to a question was determined as the option with the highest score, and all

the models were trained to maximize the logarithmic score of the correct option. The

transformer-based models were trained in two steps (Fig. 1D). The pre-training

process aimed to learn general statistical regularities in a language based on large

corpora, i.e., BooksCorpus [62] and English Wikipedia, while the fine-tuning process

trained models to perform the reading comprehension task based on RACE dataset.

All models were implemented based on HuggingFace [63] and all hyperparameters

for fine-tuning were adopted from previous studies [21, 22, 64, 65] (see Table S6).

Attention in transformer-based models

The transformer-based models we applied had 12 layers, and each layer had 12

parallel attention heads. Each attention head calculated an attention weight between

any pair of inputs, including words and special tokens. The vectorial representation of

each input was then updated by the weighted sum of the vectorial representations of

all inputs [66]. Since only the CLS token was directly related to question answering,

here we restrained the analysis to the attention weights that were used to calculate the

vectorial representation of CLS (Fig. 2B, right panel). In the h^{th} head, the vectorial

representation of CLS was computed using the following equations. For the sake of

clarity, we did not distinguish the input words and special tokens and simply denoted

them as X_i.

719
$$CLS^h = \sum_{i=1}^{N+M+3} \alpha_i V_i = \alpha_{CLS} V_{CLS} + \sum_{n=1}^{N} \alpha_{Pn} V_{Pn} + \alpha_{S1} V_{S1} + \sum_{m=1}^{M} \alpha_{Om} V_{Om} + \alpha_{S2} V_{S2},$$

720
$$\alpha_i = \frac{exp(Q_{CLS} K_i^{\text{T}})}{\sum_{i=1}^{N+M+3} exp(Q_{CLS} K_i^{\text{T}})},$$

721
$$V_i = X_i W^V + b^V, \quad K_i = X_i W^K + b^K, \quad Q_{CLS} = X_{CLS} W^Q + b^Q,$$

where W^V, W^Q, W^K, b^V, b^Q, and b^K were parameters to learn from the data, and α_i was

the attention weight between CLS and X_i. The attention weight between CLS and the

n^{th} word in the passage, i.e., α_{Pn}, was compared to human attention. Here, we only

considered the attention weights associated with the correct option. Additionally,

DNNs used byte-pair tokenization which split some words into multiple tokens. We

converted the token-level attention weights to word-level attention weights by

summing the attention weights over tokens within a word [55, 67].

Eye tracking measures

We analyzed eye movements during passage reading in Experiments 1-3, and the

passage preview in Experiment 4. For each word, the total fixation time, gaze

duration, and run counts was extracted using the SR Research Data Viewer software.

The total fixation time of a word was referred to as the word reading time. The gaze

duration was the how long a word was fixated before the gaze moved to other words,

reflected first-pass processing of a word. To characterize late processing of a word, we

further calculated the counts of rereading, which were defined as the run counts minus

1. Words that were not reread were excluded from the analysis of counts of rereading.

Each of the eye tracking measure was averaged across all participants who correctly

answered the question.

Regression models

We employed linear regression to analyze how well each model, as well as each set of

text/task-related features, could explain human attention measured by eye tracking. In

all regression analyses, each regressor and the eye-tracking measure were normalized

within each passage by taking the z-score. The predictive power, i.e., the Pearson

correlation coefficient between the predicted eye-tracking measure and the actual eye-

tracking measure, was calculated based on five-fold cross-validation.

Regressors: For the SAR, each word had one attention weight, which was used as the

regressor. For transformer-based models, since each model contained 12 layers and

each layer contained 12 attention heads, all together there were 144 regressors. Text

features included layout features and word features. The layout features concerned the

visual position of text, including the coordinate of the left most pixel of a word,

ordinal paragraph number of a word in a passage, ordinal line number of a word in a

paragraph, and ordinal line number of a word in a passage. The word features

included word length, logarithmic word frequency estimated based on the

BookCorpus [62] and English Wikipedia using SRILM [68], and word surprisal

estimated from GPT-2 Medium [69]. The task-related feature referred to the question

relevance annotated by another group of participants (see *Experimental materials* for

details).

Additionally, we also applied linear regression to probe how DNN attention was

affected by text features and question relevance. Since information of lines and

paragraphs were not available to DNNs, the layout features only included the ordinal

position of a word in a sentence, ordinal position of a word in a passage, and ordinal

sentence number of a word in this analysis.

Statistical tests

In the regression analysis, we employed a one-sided permutation test to test whether a

set of features could statistically significantly predict an eye tracking measure. Five

hundred chance-level predictive power was calculated by predicting the eye tracking

measure shuffled across all words within a passage: The eye tracking measure to

predict was shuffled but the features were not. The procedure was repeated 500 times,

creating 500 chance-level predictive power. If the actual correlation was smaller than

N out of the 500 chance-level correlation, the significance level was $(N + 1)/501$.

When comparing the responses to local and global questions, the 3 types of local/global

questions were pooled. The comparison between local and global questions, as well as

the comparison between experiments, was based on bias-corrected and accelerated

bootstrap [70]. For example, to test whether the predictive power differed between the

2 types of questions, all global questions were resampled with replacement 50000 times

and each time the predictive power was calculated based on the resampled questions,

resulting in 50000 resampled predictive power. If the predictive power for local

questions was greater (or smaller) than N out of the 50000 resampled predictive power

for global questions, the significance level of their difference was $2(N + 1)/50001$.

When multiple comparisons were performed, the p-value was further adjusted using the

false discovery rate (FDR) correction.

Acknowledgements

We thank David Poeppel, Yunyi Pan, and Erik D. Reichle for valuable comments on earlier versions of this manuscript; Jonathan Simon, Bingjiang Lyu, and members of the Ding lab for thoughtful discussions and feedback; Qian Chu, Yuhan Lu, Anqi Dai, Zhonghua Tang, and Yan Chen for assistance with experiments. Work supported by STI2030-Major Project 2021ZD0204105, National Natural Science Foundation of China 32222035, Major Scientific Research Project of Zhejiang Lab 2019KB0AC02, and Fundamental Research Funds for the Central Universities 226-2023-00091.

Author Contributions

Jiajie Zou implemented the experiments and models, analyzed data, and wrote the manuscript. Nai Ding acquired the funding, conceived and coordinated the project, analyzed data, and wrote the manuscript. Xing Tian coordinated the project and revised the manuscript. Yuran Zhang and Jialu Li implemented the experiments.

Competing Interest Statement

The authors declare no competing interests.

Data Availability

All eye tracking data is available at https://github.com/jiajiezou/TOA.

Code availability

The code is available at https://github.com/jiajiezou/TOA.

References

1. Posner MI, Petersen SE. The attention system of the human brain. Annu Rev Neurosci. 1990;13(1):25-42.

2. Treisman AM, Gelade G. A feature-integration theory of attention. Cogn Psychol. 1980;12(1):97-136.

3. Rayner K. Eye movements in reading and information processing: 20 years of research. Psychol Bull. 1998;124(3):372-422.

4. Marr D. Vision: A computational investigation into the human representation and processing of visual information, henry holt and co. Inc, New York, NY. 1982;2(4.2).

5. Kahneman D. Attention and effort: Citeseer; 1973.

6. Franconeri SL, Alvarez GA, Cavanagh P. Flexible cognitive resources: competitive content maps for attention and memory. Trends in Cognitive Sciences. 2013;17(3):134-41. doi: https://doi.org/10.1016/j.tics.2013.01.010.

7. Lennie P. The Cost of Cortical Computation. Current Biology. 2003;13(6):493-7. doi: https://doi.org/10.1016/S0960-9822(03)00135-0.

8. Carrasco M. Visual attention: The past 25 years. Vision research. 2011;51(13):1484-525. doi: https://doi.org/10.1016/j.visres.2011.04.012.

9. Borji A, Itti L. State-of-the-art in visual attention modeling. IEEE transactions on pattern analysis and machine intelligence. 2012;35(1):185-207.

10. Dayan P, Kakade S, Montague PR. Learning and selective attention. Nat Neurosci. 2000;3(11):1218-23.

11. Gottlieb J, Hayhoe M, Hikosaka O, Rangel A. Attention, reward, and information seeking. J Neurosci. 2014;34(46):15497-504. Epub 2014/11/14. PubMed PMID: 25392517; PubMed Central PMCID: PMCPMC4228145.

12. Legge GE, Hooven TA, Klitz TS, Mansfield JS, Tjan BS. Mr. Chips 2002: New insights from an ideal-observer model of reading. Vision Res. 2002;42(18):2219-34.

13. Liu Y, Reichle E. The emergence of adaptive eye movements in reading. Cogsci. 2010;32(32).

846   14.   Najemnik J, Geisler WS. Optimal eye movement strategies in visual search.

847   Nature. 2005;434(7031):387-91.

848   15.   Navalpakkam V, Koch C, Rangel A, Perona P. Optimal reward harvesting in

849   complex perceptual environments. Proc Natl Acad Sci USA.

850   2010;107(11):5232-7.

851   16.   Li X, Huang L, Yao P, Hyönä J. Universal and specific reading mechanisms

852   across different writing systems. Nat Rev Psychol. 2022;1:133-44.

853   17.   Gagl B, Gregorova K, Golch J, Hawelka S, Sassenhagen J, Tavano A, et al.

854   Eye movements during text reading align with the rate of speech production.

855   Nat Hum Behav. 2021;6:429-42. doi: 10.1038/s41562-021-01215-4.

856   18.   Clifton C, Ferreira F, Henderson JM, Inhoff AW, Liversedge SP, Reichle ED,

857   et al. Eye movements in reading and information processing: Keith Rayner's

858   40 year legacy. J Mem Lang. 2016;86:1-19. doi: 10.1016/j.jml.2015.07.004.

859   19.   Reichle ED, Rayner K, Pollatsek A. The EZ Reader model of eye-movement

860   control in reading: Comparisons to other models. Behav Brain Sci.

861   2003;26(4):445-76.

862   20.   White S, Chen J, Forsyth B. Reading-related literacy activities of American

863   adults: Time spent, task types, and cognitive skills used. J Lit Res.

864   2010;42(3):276-307.

865   21.   Lan Z, Chen M, Goodman S, Gimpel K, Sharma P, Soricut R. Albert: A lite

866   bert for self-supervised learning of language representations. International

867   Conference on Learning Representations; 2019: ICLR; 2020.

868   22.   Liu Y, Ott M, Goyal N, Du J, Joshi M, Chen D, et al. Roberta: A robustly

869   optimized bert pretraining approach. arXiv. 2019. doi: arXiv:1907.11692.

870   23.   Yamins DL, Hong H, Cadieu CF, Solomon EA, Seibert D, DiCarlo JJ.

871   Performance-optimized hierarchical models predict neural responses in higher

872   visual cortex. Proc Natl Acad Sci USA. 2014;111(23):8619-24.

873   24.   Kell AJ, Yamins DL, Shook EN, Norman-Haignere SV, McDermott JH. A

874   task-optimized neural network replicates human auditory behavior, predicts

875   brain responses, and reveals a cortical processing hierarchy. Neuron.

2018;98(3):630-44. e16.

25.   Goldstein A, Zada Z, Buchnik E, Schain M, Price A, Aubrey B, et al. Shared

computational principles for language processing in humans and deep

language models. Nat Neurosci. 2022;25(3):369-80.

26.   Schrimpf M, Blank IA, Tuckute G, Kauf C, Hosseini EA, Kanwisher N, et al.

The neural architecture of language: Integrative modeling converges on

predictive processing. Proc Natl Acad Sci USA. 2021;118(45):e2105646118.

doi: 10.1073/pnas.2105646118.

27.   Hasson U, Nastase SA, Goldstein A. Direct Fit to Nature: An Evolutionary

Perspective on Biological and Artificial Neural Networks. Neuron.

2020;105(3):416-34. doi: 10.1016/j.neuron.2019.12.002. PubMed PMID:

32027833; PubMed Central PMCID: PMC7096172.

28.   Donhauser PW, Baillet S. Two distinct neural timescales for predictive speech

processing. Neuron. 2020;105(2):385-93. e9.

29.   Rabovsky M, Hansen SS, McClelland JL. Modelling the N400 brain potential

as change in a probabilistic representation of meaning. Nature Human

Behaviour. 2018;2(9):693-705.

30.   Heilbron M, Armeni K, Schoffelen J-M, Hagoort P, de Lange FP. A hierarchy

of linguistic predictions during natural language comprehension. Proc Natl

Acad Sci USA. 2022;119(32):e2201968119. doi:

doi:10.1073/pnas.2201968119.

31.   Lai G, Xie Q, Liu H, Yang Y, Hovy E. Race: Large-scale reading

comprehension dataset from examinations. 2017 Conference on Empirical

Methods in Natural Language Processing; 2017: ACL; 2017.

32.   Chen D, Bolton J, Manning CD. A thorough examination of the cnn/daily mail

reading comprehension task. 54th annual meeting of the association for

computational linguistics; 2016: ACL; 2016.

33.   Devlin J, Chang M-W, Lee K, Toutanova K. Bert: Pre-training of deep

bidirectional transformers for language understanding. 2019 Conference of the

North American Chapter of the Association for Computational Linguistics;

2019: ACL; 2019.

34.   Itti L, Koch C, Niebur E. A model of saliency-based visual attention for rapid

scene analysis. IEEE Trans Pattern Anal Mach Intell. 1998;20(11):1254-9.

35.   Hale J. Information‐theoretical complexity metrics. Lang Linguist Compass.

2016;10(9):397-412.

36.   Tatler BW, Hayhoe MM, Land MF, Ballard DH. Eye guidance in natural

vision: reinterpreting salience. J Vis. 2011;11(5):5-25. Epub 2011/05/31. doi:

10.1167/11.5.5. PubMed PMID: 21622729; PubMed Central PMCID:

PMCPMC3134223.

37.   Borji A, Sihite DN, Itti L. Quantitative analysis of human-model agreement in

visual saliency modeling: a comparative study. IEEE Trans Image Process.

2013;22(1):55-69. Epub 2012/08/08. PubMed PMID: 22868572.

38.   Anderson P, He X, Buehler C, Teney D, Johnson M, Gould S, et al. Bottom-up

and top-down attention for image captioning and visual question answering.

The IEEE Conference on Computer Vision and Pattern Recognition; 2018:

CVPR; 2018.

39.   Xu K, Ba J, Kiros R, Cho K, Courville A, Salakhudinov R, et al. Show, attend

and tell: Neural image caption generation with visual attention. 32nd

International Conference on Machine Learning; 2015: PMLR; 2015.

40.   Das A, Agrawal H, Zitnick L, Parikh D, Batra D. Human attention in visual

question answering: Do humans and deep networks look at the same regions?

Comput Vis Image Underst. 2017;163:90-100.

41.   Wolfe JM, Horowitz TS. Five factors that guide attention in visual search. Nat

Hum Behav. 2017;1(3):1-8.

42.   Engbert R, Nuthmann A, Richter EM, Kliegl R. SWIFT: A dynamical model

of saccade generation during reading. Psychol Rev. 2005;112(4):777-813.

43.   Mancheva L, Reichle ED, Lemaire B, Valdois S, Ecalle J, Guérin-Dugué A.

An analysis of reading skill development using EZ Reader. J Cogn Psychol.

2015;27(5):657-76.

44.   Reichle ED, Pollatsek A, Rayner K. Using EZ Reader to simulate eye

movements in nonreading tasks: A unified framework for understanding the

eye–mind link. Psychol Rev. 2012;119(1):155.

45.   Hermann KM, Kocisky T, Grefenstette E, Espeholt L, Kay W, Suleyman M, et

al. Teaching machines to read and comprehend. Advances in Neural

Information Processing Systems; 2015.

46.   Hahn M, Keller F. Modeling task effects in human reading with neural

network-based attention. Cognition. 2023;230:105289. doi:

https://doi.org/10.1016/j.cognition.2022.105289.

47.   Yeari M, van den Broek P, Oudega M. Processing and memory of central

versus peripheral information as a function of reading goals: Evidence from

eye-movements. Read Writ. 2015;28(8):1071-97.

48.   Grabe M. Reader imposed structure and prose retention. Contemporary

Educational Psychology. 1979;4(2):162-71.

49.   Kaakinen JK, Hyönä J, Keenan JM. Perspective effects on online text

processing. Discourse processes. 2002;33(2):159-73.

50.   Kaakinen JK, Hyönä J, Keenan JM. How prior knowledge, WMC, and

relevance of information affect eye fixations in expository text. J Exp Psychol.

2003;29(3):447-57.

51.   Yang Z, Yang D, Dyer C, He X, Smola A, Hovy E. Hierarchical attention

networks for document classification. 2016 Conference of the North American

Chapter of the Association for Computational Linguistics: Human Language

Technologies; 2016: ACL; 2016.

52.   Lin Z, Feng M, Santos CNd, Yu M, Xiang B, Zhou B, et al. A structured self-

attentive sentence embedding. International Conference on Learning

Representations; 2017: ICLR; 2017.

53.   Serrano S, Smith NA. Is Attention Interpretable? 57th Annual Meeting of the

Association for Computational Linguistics; 2019: Association for

Computational Linguistics; 2019.

54.   Jain S, Wallace BC. Attention is not Explanation. 2019 Conference of the

North American Chapter of the Association for Computational Linguistics;

2019 jun; Minneapolis, Minnesota: Association for Computational Linguistics.

55. Bolotova V, Blinov V, Zheng Y, Croft WB, Scholer F, Sanderson M. Do People and Neural Nets Pay Attention to the Same Words: Studying Eye-tracking Data for Non-factoid QA Evaluation. 29th ACM International Conference on Information & Knowledge Management; 2020: ACM; 2020.

56. Malmaud J, Levy R, Berzak Y. Bridging Information-Seeking Human Gaze and Machine Reading Comprehension. arXiv. 2020.

57. Sood E, Tannert S, Frassinelli D, Bulling A, Vu NT. Interpreting attention models with human visual attention in machine reading comprehension. 24th Conference on Computational Natural Language Learning; 2020: Association for Computational Linguistics.

58. Zou J, Zhang Y, Jin P, Luo C, Pan X, Ding N. PALRACE: Reading Comprehension Dataset with Human Data and Labeled Rationales2021. Available from: https://arxiv.org/abs/2106.12373.

59. Brainard DH. The psychophysics toolbox. Spat Vis. 1997;10(4):433-6.

60. Levenshtein VI. Binary codes capable of correcting deletions, insertions, and reversals. Soviet physics doklady; 1966: Soviet Union.

61. Pennington J, Socher R, Manning C. Glove: Global vectors for word representation. 2014 Conference on Empirical Methods in Natural Language Processing; 2014.

62. Zhu Y, Kiros R, Zemel R, Salakhutdinov R, Urtasun R, Torralba A, et al. Aligning books and movies: Towards story-like visual explanations by watching movies and reading books. Proceedings of the IEEE international conference on computer vision; 2015.

63. Wolf T, Debut L, Sanh V, Chaumond J, Delangue C, Moi A, et al. HuggingFace's Transformers: State-of-the-art natural language processing. 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations; 2019: Association for Computational Linguistics; 2020.

64. Zhang S, Zhao H, Wu Y, Zhang Z, Zhou X, Zhou X. DCMN+: Dual co-

matching network for multi-choice reading comprehension. AAAI conference

on artificial intelligence; 2019: AAAI 2020.

65.   Ran Q, Li P, Hu W, Zhou J. Option comparison network for multiple-choice

reading comprehension. arXiv. 2019. doi: arXiv:1903.03033.

66.   Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al.

Attention is all you need. Advances in Neural Information Processing

Systems; 2017: Curran Associates; 2017.

67.   Clark K, Khandelwal U, Levy O, Manning CD. What does BERT look at? An

analysis of BERT's attention. 2019 ACL workshop blackboxNLP: Analyzing

and interpreting neural networks for NLP; 2019: ACL; 2019.

68.   Stolcke A. SRILM-an extensible language modeling toolkit. Seventh

International Conference on Spoken Language Processing; 2002.

69.   Radford A, Narasimhan K, Salimans T, Sutskever I. Improving language

understanding by generative pre-training. arXiv. 2018.

70.   Efron B, Tibshirani RJ. An introduction to the bootstrap: CRC press; 1994.

1011

Figures

 Fig. 1. Experiment and performance. (**A**) Experimental procedure for Experiments

 1-3. In each trial, participants saw a question before reading a passage. After reading

 the passage, they chose the answer to the question from 4 options. (**B**) Accuracy of

 question answering for humans and computational models. The question type is color

coded and an example question is shown for each type. trans_pre: pre-trained

transformer-based models; trans_fine: transformer-based models fine-tuned on the

goal-directed reading task. (**C**) Time spent on reading each passage. The box plot

shows the mean (horizontal lines inside the box), 25^{th} and 75^{th} percentiles (box

boundaries), and $25^{th}/75^{th}$ percentiles $\pm\, 1.5 \times$ interquartile range (whiskers). (**D**)

Illustration of the training process for transformer-based models. The pre-training

process aims to learn general statistical regularities in a language based on large

corpora, while the fine-tuning process trains models to perform the reading

comprehension task.

1029

A   *Examples of Human Attention Distribution and Model Predictions*

local question ("In Scotland, you will probably see ___ .")

word reading time

min   max

heuristic   DNN   features

global question ("What is the passage mainly about?")

heuristic   DNN   features

B   *Transformer-based DNN Models*

model architecture   attention mechanism

Fig. 2. Human attention distribution and computational models. (A) Examples of

human attention distribution, quantified by the word reading time. The histograms on

the right showed the mean reading time on each line, for both human data and model

predictions. trans_pre: pre-trained transformer-based models; trans_fine: transformer-

based models fine-tuned on the goal-directed reading task. (B) The general

architecture of the 12-layer transformer-based models. The model input consists of all

words in the passage and an integrated option. Output of the model relies on the node

CLS^{12}, which is used to calculate a score reflecting how likely an option is the correct

answer. The CLS node is a weighted sum of the vectorial representations of all words

and tokens, and the attention weight for each word in the passage, i.e., α, is the DNN

attention analyzed in this study.

Fig. 3. Model word reading time in Experiment 1. (**AB**) Predict the word reading time based on the attention weights of DNN models, text features, or question relevance. The predictive power is the correlation coefficient between the predicted word reading time and the actual word reading time. Predictive power significantly higher than chance is denoted by stars on the top of each bar. **P < 0.01. trans_rand: transformer-base models with randomized parameters; trans_pre: pre-trained transformer-based models; trans_fine: transformer-based models fine-tuned on the goal-directed reading task. (**C**) Relationship between the word reading time and line index. The word reading time is longer near the beginning of a passage and the effect is stronger for global questions than local questions. (**D**) Relationship between the word reading time and question relevance. Line 0 refers to the line with the highest question relevance. The word reading time is higher for the question-relevant line. Color indicates the question type. The shade area indicates one standard error of the mean (SEM) across participants.

Fig. 4. Factors influencing attention distribution in different processing stages for humans and DNNs. (**A**) Human attention in early and late reading stages is differentially modulated by text features and question relevance. The early and late stages are separately characterized by gaze duration, i.e., duration for the first reading of a word, and counts of rereading, respectively. **P < 0.01; ***P < 0.001. (**B**) DNN attention weights in different layers are also differentially modulated by text features and question relevance. Each attention head is separately modeled and averaged within each layer, and the results are further averaged across the 3 transformer-based models. Shallow layers of both fine-tuned and pre-trained models are more sensitive to text features. Deep layers of fine-tuned models are sensitive to question relevance. trans_rand: transformer-base models with randomized parameters; trans_pre: pre-trained transformer-based models; trans_fine: transformer-based models fine-tuned on the goal-directed reading task.

Fig. 5. Influence of task and language proficiency on word reading time. (**AB**) Predict the word reading time using attention weights of DNN models, text features, and question relevance for all 4 experiments. Predictive powersignificantly higher than chance is marked by stars of the same color as the bar. Significant differences

between experiments are denoted by black stars. trans_pre: pre-trained transformer-based models; trans_fine: transformer-based models fine-tuned on the goal-directed reading task. *P < 0.05; **P < 0.01; ***P < 0.001. (**CD**) Passage beginning and question relevance effects for all 4 experiments. The shade area indicates one SEM across participants.

Supplementary Material

Human Attention during Goal-directed Reading Comprehension Relies on Task Optimization

Jiajie Zou, Yuran Zhang, Jialu Li, Xing Tian, Nai Ding[*]

*Corresponding author: Nai Ding

Email: ding_nai@zju.edu.cn

This PDF file includes:

Figures S1 to S10

Tables S1 to S7

Supplementary Methods

Supplementary Results

A

Heuristic Models

B

Stanford Attentive Reader (SAR)

Fig. S1. Illustration of the word-level heuristic models and the RNN-based SAR model. (**A**) The orthographic and semantic models calculate the word-wise similarities between all words in the integrated option and all words in the passage, forming a similarity matrix. The similarity measures used in the orthographic and semantic models are the edit distance and correlation between word embeddings, respectively. For each option, the similarity matrix is averaged across all rows and all columns to form a scalar decision score. The option with the largest decision score is chosen as the answer. (**B**) The SAR model uses bi-directional RNNs to encode contextual information. A vectorial representation for the passage is created using the weighted sum of the vectorial representation of each word, and the weight on each word, i.e., the attention weight, is calculated based on its similarity to the vectorial representation of the question. The summarized passage representation and the option representation is used to form the decision score with a bilinear dot layer.

Fig. S2. Question answering accuracy for individual transformer-based models. Human results and other computational models are also plotted for comparison. *_pre: pre-trained transformer-based models; *_fine: transformer-based models fine-tuned on the goal-directed reading task.

Predicting Word Reading Time based on Computational Models

A **Raw Word Reading Time**

B **Regress Out Text Features**

C **Regress Out Text Features and Question Relevance**

Fig. S3. Transformer-based models can explain word reading time even when the influences of text features and question relevance are regressed out. (**A**) Predict the raw word reading time using the attention weights of individual transformer-based models. Results from other computational models are also plotted for comparison. (**B**) Predict the residual word reading time when basic text features, i.e., layout and word features, are regressed out. (C) Predict the residual word reading time when both basic text features and question relevance are regressed out. Prediction accuracy significantly higher than chance is denoted by stars of the same color as the bar. *_rand: transformer-base models with randomized parameters; *_pre: pre-trained transformer-based models; *_fine: transformer-based models fine-tuned on the goal-directed reading task. *P < 0.05; **P < 0.01.

Fig. S4. Weights on individual attention heads in the linear regression when predicting human word reading time. The weights of the linear regression are normalized by their maximum value. The light-colored dots denote the weights on each head, and the dark-colored dots represent the mean weight within a layer. trans_rand: transformer-base models with randomized parameters; trans_pre: pre-trained transformer-based models; trans_fine: transformer-based models fine-tuned on the goal-directed reading task.

Factors Influencing the Question Relevance

Fig. S5. Properties of the question relevance of words. (**A**) Question relevance as a function of the word position within a passage. For global but not local questions, question-relevant words concentrate near the beginning of a passage. (**B**) Decay of mean question relevance across lines. The question relevance is averaged within each line, and all lines in a passage are sorted based on the mean question relevance in descending order. Therefore, line 1 is the line with the highest question relevance, and line 2 is the line with the 2nd highest question relevance. For both global and local questions, the mean question relevance sharply decreases over lines. (**C**) The mean word length, in terms of the number of letters, for words with the question relevance greater or smaller than 0.1. Words of higher relevance are generally longer. (**D**) Percentage of content words for words with higher or lower question relevance. Question-relevant words are more often content words.

Fig. S6. Passage beginning effects (A) and question relevance effects (B) in early and late reading stages. The passage beginning effect differ between global and local questions mainly in the late reading stage reflected by the counts of rereading. The question-relevance effect is also only reliably observed in the late reading stage.

Fig. S7. Factors influencing attention weights in each layer of DNNs for local questions. Similar results are observed for all 3 models: The sensitivity to text features decreases from shallow to deep layers, while the sensitivity to question relevance increases across layers. trans_rand: transformer-base models with randomized parameters; trans_pre: pre-trained transformer-based models; trans_fine: transformer-based models fine-tuned on the goal-directed reading task.

Fig. S8. Factors influencing attention weights in each layer of DNNs for global questions. Similar results are observed for all 3 models: The sensitivity to text features decreases from shallow to deep layers, while the sensitivity to question relevance increases across layers. trans_rand: transformer-base models with randomized parameters; trans_pre: pre-trained transformer-based models; trans_fine: transformer-based models fine-tuned on the goal-directed reading task.

Early and Late Reading Stages in Exps 2-4

A   *Exp 2: L2, goal-directed (96 passage, mixed)*

B   *Exp 3: L1, goal-directed (96 passage, mixed)*

C   *Exp 4: L2, general-purpose (96 passage, mixed)*

Fig. S9. Factors influencing human reading in different processing stages in Experiments 2-4. The early and late stages are separately characterized by gaze duration, i.e., duration for the first reading of a word, and counts of rereading, respectively. $*P < 0.05$; $**P < 0.01$; $***P < 0.001$.

Experiments 1-4: Evaluation of Attention Effect

Fig. S10. Passage-beginning and question-relevance effects in 4 experiments. The passage beginning effect was quantified by the ratio between the mean word reading time on the first 3 lines of a passage and the mean word reading time on other lines. The question relevance effect was quantified by the ratio between mean word reading time on the line that was most relevant to the question and lines that were more than 5 lines away. See Fig. 1 for the explanation for the box plots. **$P < 0.01$; ***$P < 0.001$.

Table S1. P-values for the model prediction of word reading time.

	Cause	Fact	Inference	Theme	Title	Purpose
SAR	0.002	0.002	0.002	0.002	0.002	0.002
trans_rand	0.002	0.002	0.002	0.002	0.002	0.002
trans_pre	0.002	0.002	0.002	0.002	0.002	0.002
trans_fine	0.002	0.002	0.002	0.002	0.002	0.002
SAR vs. trans_rand	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}
SAR vs. trans_pre	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}
SAR vs. trans_fine	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}
trans_rand vs. trans_pre	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}
trans_rand vs. trans_fine	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}	7×10^{-5}
trans_pre vs. trans_fine	7×10^{-5}	7×10^{-5}	9×10^{-4}	0.351	0.468	0.278

Note: trans_rand: transformer-base models with randomized parameters; trans_pre: pre-trained transformer-based models; trans_fine: transformer-based models fine-tuned on the goal-directed reading task.

Table S2. P-values for the prediction of word reading time using text or task-related features.

	Cause	Fact	Inference	Theme	Title	Purpose
layout	0.002	0.002	0.002	0.002	0.002	0.002
word	0.002	0.002	0.002	0.002	0.002	0.002
relevance	0.002	0.002	0.002	0.002	0.002	0.002

Table S3. P-values for the prediction of early and late eye tracking measures using text or task-related features.

		local questions			Global questions		
		layout	word	relevance	layout	word	relevance
Exp 1	GD	0.002	0.002	0.002	0.002	0.002	0.002
	CR	0.002	0.002	0.002	0.002	0.002	0.002
	GD vs. CR	4×10^{-5}	4×10^{-5}	4×10^{-5}	6×10^{-5}	8×10^{-5}	6×10^{-5}
Exp 2	GD	0.002	0.002	0.01	0.002	0.002	0.006
	CR	0.002	0.002	0.002	0.002	0.002	0.002
	GD vs. CR	0.704	1×10^{-4}	1×10^{-4}	1×10^{-4}	0.333	0.333
Exp 3	GD	0.002	0.002	0.265	0.003	0.003	0.302
	CR	0.002	0.002	0.002	0.003	0.003	0.315
	GD vs. CR	6×10^{-5}	6×10^{-5}	8×10^{-5}	0.656	1×10^{-4}	0.724
Exp 4	GD	0.003	0.003	0.685	0.003	0.003	0.162
	CR	0.003	0.003	0.405	0.003	0.003	0.096
	GD vs. CR	6×10^{-5}	6×10^{-5}	0.280	1×10^{-4}	7×10^{-4}	0.552

Note: GD: gaze duration; CR: counts of rereading.

Table S4. P-values for the prediction of word reading time for all 4 experiments.

	local questions				global questions			
	Ex 1	Ex 2	Ex 3	Ex 4	Ex 1	Ex 2	Ex 3	Ex 4
trans_pre	0.003	0.003	0.003	0.003	0.004	0.004	0.004	0.004
trans_fine	0.003	0.003	0.003	0.003	0.004	0.004	0.004	0.004
trans_fine - trans_pre	0.003	0.003	0.041	0.814	0.9	0.9	0.829	0.714
layout	0.002	0.002	0.002	0.002	0.003	0.003	0.003	0.003
word	0.002	0.002	0.002	0.002	0.003	0.003	0.003	0.003
relevance	0.002	0.002	0.002	0.228	0.003	0.003	0.003	0.003

Note: trans_pre: pre-trained transformer-based models; trans_fine: transformer-based models fine-tuned on the goal-directed reading task.

Table S5. P-values for the comparisons between experiments.

	local questions				global questions			
	Ex 1 vs Ex 2	Ex 2 vs Ex 3	Ex 2 vs Ex 4	Ex 3 vs Ex 4	Ex 1 vs Ex 2	Ex 2 vs Ex 3	Ex 2 vs Ex 4	Ex 3 vs Ex 4
trans_pre	0.001	0.460	1×10^{-4}	1×10^{-4}	0.155	0.055	1×10^{-4}	1×10^{-4}
trans_fine	0.2	0.953	1×10^{-4}	1×10^{-4}	0.02	0.114	1×10^{-4}	1×10^{-4}
trans_fine - trans_pre	1×10^{-4}	0.032	1×10^{-4}	1×10^{-4}	0.04	0.305	0.12	0.622
layout	1×10^{-4}	0.014	1×10^{-4}	1×10^{-4}	0.021	1×10^{-4}	0.307	1×10^{-4}
word	0.001	0.001	1×10^{-4}	0.001	0.003	1×10^{-4}	1×10^{-4}	0.003
relevance	1×10^{-4}	0.002	1×10^{-4}	1×10^{-4}	1×10^{-4}	1×10^{-4}	1×10^{-4}	0.496

Note: trans_pre: pre-trained transformer-based models; trans_fine: transformer-based models fine-tuned on the goal-directed reading task.

Table S6. Hyperparameters for DNN fine-tuning. We adapted these hyperparamemers from references [1-4].

models	learning rate	fine-tuning steps	fine-tuning batch size	warmup steps	weight decay
BERT	1×10^{-5}	27455	16	0	0
ALBERT	2×10^{-5}	12000	32	1000	0
RoBERTa	1×10^{-5}	21964	16	1200	0.1

Supplementary Methods

To characterize the influences of different factors on human word reading time, we employed linear mixed effects models [5] implemented in the lmerTest package [6] of R. For the baseline model, we treated the type of questions (local vs. global; local = baseline) and all text/task-related features as fixed factors, and considered the interaction between the type of questions and these text/task-related features. We included participants and items (i.e., questions) as random factors, each with associated random intercepts. The formulation of the baseline model was: *reading-time ~ ParagraphNumber * QuestionType + LineNumberInPassage * QuestionType + LeftMostPixel * QuestionType + LineNumberInParagraph * QuestionType + LogWordFreq * QuestionType + WordLength * QuestionType + Surprisal * QuestionType + QuestionRelevance * QuestionType + (1 | Participant) + (1 | question)*. Additionally, starting from the baseline model, we augmented the baseline model by adding DNN attention as additional fixed factors. This augmentation facilitated an examination of whether DNN attention demonstrated a statistically significant contribution to the prediction of human word reading time. Notably, the DNN attention was derived from diverse sources, including SAR, randomized BERT, pre-trained BERT, and fine-tuned BERT.

Supplementary Results

The baseline mixed model revealed significant fixed effects for question type and all text/task-related features, as well as significant interactions between question type and

these text/task-related features (Table S7). Upon involving SAR attention, we

observed a statistically significant fixed effect associated with SAR attention. When

involving attention weights of randomly initialized BERT, the mixed model revealed

that most attention heads exhibited significant fixed effects, suggesting their

contributions to the prediction of human word reading time. A broader range of

attention heads showed significant fixed effects for both pre-trained and fine-tuned

BERT.

Table S7. Linear mixed effects modeling of human word reading time. The
question type is coded as 0 (local question) or 1 (global question), and other factors
are continuous regressors. Given the substantial number of attention weights in BERT
(i.e., 144), we present the 1st quartile and 3rd quartile values for b, SE, and t and report
the ratio of attention weights that reach significant level.

	b	SE	t	p
Baseline				
(Intercept)	67.60	2.91	23.26	< 0.001
QuestionType	61.68	2.50	24.67	< 0.001
LeftMostPixel	-66.94	0.53	-126.15	< 0.001
ParagraphNumber	5.39	0.18	30.44	< 0.001
LineNumberInParagraph	-1.89	0.12	-15.95	< 0.001
LineNumberInPassage	-5.96	0.07	-89.35	< 0.001
WordLength	16.55	0.08	211.84	< 0.001
LogWordFreq	-4.39	0.16	-27.43	< 0.001
Surprisal	2.19	0.08	26.72	< 0.001
QuestionRelevance	336.87	1.52	221.54	< 0.001
QuestionType:LeftMostPixel	-38.59	0.88	-44.05	< 0.001
QuestionType:ParagraphNumber	-12.05	0.32	-38.04	< 0.001
QuestionType:LineNumberInParagraph	-15.12	0.20	-76.80	< 0.001
QuestionType:LineNumberInPassage	2.65	0.11	23.14	< 0.001
QuestionType:WordLength	-0.57	0.13	-4.36	< 0.001
QuestionType:LogWordFreq	0.52	0.27	1.96	0.05

QuestionType:Surprisal	0.46	0.14	3.34	< 0.001
QuestionType:QuestionRelevance	-93.03	2.72	-34.258	< 0.001
With attention of SAR				
SAR Attention	2.12	0.11	19.41	< 0.001
With attention of randomized BERT				
Randomized BERT attention	-0.57	0.2~	-2.7~	64%<0.05
	~0.61	0.22	2.75	44%<0.001
With attention of pre-trained BERT				
Pre-trained BERT attention	-0.77	0.14~	-4.6~	80%<0.05
	~0.89	0.16	5.71	67%<0.001
With attention of fine-tuned BERT				
Fine-tuned BERT attention	-0.72	0.14~	-4.9~	86%<0.05
	~1.01	0.16	6.81	70%<0.001

Note: b: regression coefficient; *SE*: standard error of regression coefficient.

References

1. Lan Z, Chen M, Goodman S, Gimpel K, Sharma P, Soricut R. Albert: A lite bert for self-supervised learning of language representations. International Conference on Learning Representations; 2019: ICLR; 2020.

2. Liu Y, Ott M, Goyal N, Du J, Joshi M, Chen D, et al. Roberta: A robustly optimized bert pretraining approach. arXiv. 2019. doi: arXiv:1907.11692.

3. Zhang S, Zhao H, Wu Y, Zhang Z, Zhou X, Zhou X. DCMN+: Dual co-matching network for multi-choice reading comprehension. AAAI conference on artificial intelligence; 2019: AAAI 2020.

4. Ran Q, Li P, Hu W, Zhou J. Option comparison network for multiple-choice reading comprehension. arXiv. 2019. doi: arXiv:1903.03033.

5. Pinheiro J, Bates D. Mixed-effects models in S and S-PLUS: Springer science & business media; 2006.

6. Kuznetsova A, Brockhoff PB, Christensen RHB. lmerTest Package: Tests in Linear Mixed Effects Models. Journal of Statistical Software. 2017;82(13):1 - 26. doi: 10.18637/jss.v082.i13.