Exploring Correlation-Based Brain Networks with Adaptive Signed Random Walks

Roberto C. Sotero[1], Jose M. Sanchez-Bornot[2]

[1] Department of Radiology, and Hotchkiss Brain Institute. University of Calgary, Calgary, AB, Canada.
[2] Intelligent Systems Research Centre, Ulster University, Derry Londonderry, United Kingdom

Corresponding Author:
Roberto C. Sotero[1]
HSC 2923 - 3330 Hospital Drive NW, Calgary, AB, T2N 4N1, Canada
Email address: roberto.soterodiaz@ucalgary.ca

Abstract

The human brain is a highly connected network with complex patterns of correlated and anticorrelated activity. Analyzing functional connectivity matrices derived from neuroimaging data can provide insights into the organization of brain networks and their association with cognitive processes or disorders. Common approaches, such as thresholding or binarization, often disregard negative connections, which may result in the loss of critical information. This study introduces an adaptive random walk model for analyzing correlation-based brain networks that incorporates both positive and negative connections. The model calculates transition probabilities between brain regions as a function of their activities and connection strengths, dynamically updating probabilities based on the differences in node activity and connection strengths at each time step. Results show that the classical random walk approach, which considers the absolute value of connections, overestimates network integration and segregation while underestimating the mean first passage time (MFPT) compared to the proposed adaptive random walk model. The adaptive model captures a wide range of interactions and dynamics within the network, providing a more comprehensive understanding of its structure and function. The study suggests that considering both positive and negative connections, has the potential to offer valuable insights into the interregional coordination underlying various cognitive processes and behaviors.

Introduction

The human brain is an intricate and highly connected network, with numerous regions displaying complex patterns of correlated and anticorrelated activity (Bressler and Menon 2010). Functional connectivity matrices (Friston 1994) represent the statistical relationships between these activity signals from different brain regions, often derived from neuroimaging data such as functional Magnetic Resonance Imaging (fMRI), Electroencephalography (EEG), or Magnetoencephalography (MEG). These matrices can be used to investigate the organization of brain networks and to identify patterns of connectivity associated with different cognitive processes or brain disorders by means of various analytical techniques, such as graph theory and complex network analysis (Bassett and Sporns 2017; Bullmore and Sporns 2009).

When performing complex network analysis on correlation-based functional connectivity matrices, one of the following approaches is typically used: 1) Thresholding: where we apply a threshold to the functional connectivity matrix, preserving only the connections with correlations above a certain value (often positive correlations) (van den Heuvel and Hulshoff Pol 2010; Kazeminejad and Sotero 2019). This way, we create a binary or weighted network, discarding the negative correlations. This approach can lead to a loss of information about the negative interactions between brain regions (Rubinov and Sporns 2011). 2. Binarization: this involves binarizing the functional connectivity matrix by assigning "1" to connections with correlations above a specified threshold and "0" to connections below the threshold (Bassett and Sporns 2017; Kazeminejad and Sotero 2019). This approach also discards the negative correlations and can be used for further network analysis on a binary network. 3. Separate analysis of positive and negative connections. Two networks are created – one for positive correlations and another for negative correlations – and then perform network analysis on each network independently. This approach preserves the information about negative interactions between brain regions but treats them as separate entities (Sotero et al. 2020). 4. Disregard information about the connection sign by taking the absolute value of the connections (Meszlényi et al. 2017; Mahadevan et al. 2021). By disregarding the sign of the connections, we may inadvertently overlook critical aspects of the brain's organization, such as the balance between correlated and anticorrelated activity, which can provide insight into the interregional coordination underlying various cognitive processes and behaviors.

One approach that has shown promise in exploring the structure of complex networks, is the use of random walks (Noh and Rieger 2004). Random walks represent a type of stochastic process that characterizes the random motion of an object or particle in either discrete or continuous spaces (Pearson 1905). Within graph theory and network analysis, random walks are frequently employed to model the movement of a "walker" on a graph, with the walker traversing from one node to another along the edges of the graph (Riascos and Mateos 2021). Random walks have been adapted for use with signed social networks by adjusting the transition probabilities to preferentially favor positive edges over negative edges, or vice versa (Wan et al. 2019; Zhou et al. 2018; Yang, Cheung, and Liu 2007). However, the interpretation of signed connections in social networks, in terms of "trust" and "distrust", as well as the associated

79   transition probability models, are not directly transferable to correlation-based brain networks.
80   As such, a signed random walk model that aligns with the physiological interpretation of
81   correlated and anticorrelated activity in the brain is necessary.
82    In this study, we introduce a novel adaptive random walk approach to analyze correlation-
based brain networks, investigating the transition probabilities between nodes (brain regions) as
a function of their activities and connection strengths. The distinguishing feature of this model is
the inclusion of both positive and negative connections when calculating transition probabilities.
Positive connections signify an increased probability of transition between nodes exhibiting
similar activities, while negative connections denote a higher likelihood of transition between
nodes with dissimilar activities. By dynamically updating the transition probabilities in response
to node activity differences at each time step and considering connection strengths, the adaptive
random walk model offers a more comprehensive insight into the network's efficiency.
91    Our findings indicate that the classical random walk approach, which considers the absolute
92   value of connections, overestimates network integration (measured by global efficiency) and
93   segregation (measured by the average of local efficiencies) while underestimating the mean first
94   passage time (MFPT) compared to our adaptive random walk, which considers both positive and
95   negative connections. This proposed method captures a wide range of interactions and dynamics
96   within the network, providing a more comprehensive understanding of its structure and function.
97
98   ## Materials & Methods
99   **Computing the functional connectivity matrices**
100    In this study, resting-state (rs)-fMRI data from 491 neurotypical subjects were obtained from
the ABIDE Preprocessed Initiative (Cameron, Yassine, et al. 2013). To ensure that our results
were not influenced by any custom preprocessing pipeline, we utilized the preprocessed data
provided by ABIDE in the C-PAC pipeline (Cameron, Sharad, et al. 2013). The preprocessing
involved several steps. First, the skull was removed from images using the Analysis of
Functional Neuro Images (AFNI) software (Cox 1996). The brain was then segmented into three
tissues using FMRIB Software Library (FSL) (Smith et al. 2004) and the images were
normalized to the MNI 152 stereotactic space (Grabner et al. 2006; Mazziotta et al. 2001) using
Advanced Normalization Tools (ANTs) (Avants et al. 2011). Functional preprocessing included
motion and slice-timing correction, as well as voxel intensity normalization. Nuisance signal
regression was also performed, which encompassed 24 parameters for head motion, CompCor
(Behzadi et al. 2007) with five principal components for tissue signal in cerebrospinal fluid and
white matter, and linear and quadratic trends for low-frequency drifts. Global signal regression
(GSR) was applied to remove the global mean from signals, and images were co-registered with
their anatomical counterparts using FSL. Subsequently, the images were normalized to the MNI
152 space using ANTs.
116    The average voxel activity in each Region of Interest (ROI) of the anatomical automatic
labelling (AAL) atlas (Tzourio-Mazoyer et al. 2002) was extracted as the time series for that
region. As rs-fMRI primarily focuses on low-frequency fluctuations (< 0.1 Hz), a bandpass filter

was applied to frequencies between 0.01 Hz and 0.1 Hz. To construct the brain network, the time
series for each atlas ROI were correlated with the other regions using Pearson correlation. The
strengths of these correlations were used as the connection strengths between different ROIs. In
graph terms, this represents a graph where each node is at the center of the corresponding ROI,
and each edge weight corresponds to the correlation between the two nodes at opposite ends of
the edge.

Walk rule on the correlation network

First, let us consider an unweighted network consisting of N nodes. We place a large number
(K) of random walkers onto this network, where K is significantly larger than N. At each time
step, the walkers move randomly between the nodes that are directly linked to each other, with
equal probability. We allow the walkers to perform T time steps, and as a walker visits a node,
we record the number of walkers in the node. After T time steps, we expect that nodes with high
degree (hubs) will have a higher number of walkers than nodes with low degree.

For weighted networks, such as the functional connectivity matrix representing the brain
network, we propose a routing strategy that takes into account the sign of the connection. In the
proposed random walk model for correlation networks, the transition probabilities are computed
based on the weights in the functional connectivity matrix (C) and a similarity measure between
the activities of the source and destination nodes. The main idea is to favor transitions between
nodes with similar activities while also considering the positive or negative weights in the
network. Specifically, the transition probabilities are computed as follows:

1. At each time step t, we compute the activity $A(i, t)$ (number of walkers) at each node i.

2. For each node i, we calculate the adjusted weights for all its neighboring nodes j as follows:

a. We introduce the similarity measure $S_{ij}(t)$ between the activity of node i and node j at time
t using the formula:

143
$$S_{ij}(t) = 1 - \left| \frac{A_i(t) - A_j(t)}{\max (A_i(t), A_j(t))} \right| \tag{1}$$

144 To normalize the difference between the activities of the nodes, we divide by the maximum
145 of the activities $\max (A_i(t), A_j(t))$. The similarity $S_{ij}(t)$ ranges between 0 and 1. A value closer
146 to 1 indicates that the activities of nodes i and node j more similar, while a value closer to 0
147 indicates that the activities are more dissimilar.

148 b. If the weight C_{ij} is positive, the adjusted weight is:

149
$$\tilde{C}_{ij}(t) = C_{ij} S_{ij}(t) \tag{2}$$

150 If the weight C_{ij} is negative, the adjusted weight is:

151
$$\tilde{C}_{ij}(t) = |C_{ij}| \left(1 - S_{ij}(t) \right) \tag{3}$$

3. We then calculate the sum of the adjusted weights for all neighbors of node i. The transition
probability $P_{ij}(t)$ from node i to each neighboring node j is computed as:

$P_{ij}(t) = \tilde{C}_{ij}(t) / \sum_{j=1}^{N} \tilde{C}_{ij}(t)$ $\tag{4}$

Thus, a walker is more likely to travel through a positive connection C_{ij} if the activities in

nodes i and j are similar, while it is more likely to take a negative connection if the activities are

dissimilar.

Topological measures for correlation-based brain networks based on random walks

Efficiency is a measure used to describe the effectiveness of information transfer between

nodes within a network. It is a valuable tool for characterizing the overall organization and

function of brain networks based on random walks. Two types of efficiencies are commonly

computed: global efficiency and local efficiency.

Global efficiency is a measure of the network's overall ability to transfer information between

any pair of nodes (Latora and Marchiori 2001). To calculate global efficiency, we the MFPT

between all pairs of nodes in the network. MFPT is the average number of steps a random walker

takes to reach a target node from a starting node for the first time (Hughes 1995)r. For a network

with N nodes, the MFPT is calculated using the transition probabilities between nodes, which are

dependent on the connection strengths and the differences in node activities at each time step

(equations (1)-(4)). Once the MFPT matrix is computed, the inverse of the MFPT between each

pair of nodes is taken (excluding the diagonal elements). The global efficiency is then calculated

as the average of these inverse MFPT values, normalized by the total number of possible node

pairs $(N(N-1))$. Higher global efficiency values indicate better overall integration of the

network, reflecting a more efficient information transfer between nodes.

Local efficiency, on the other hand, is a measure of the network's fault tolerance or resilience

to the removal of a node. It represents the efficiency of the information transfer between the

neighbors of a given node when that node is removed from the network. To compute local

efficiency, first, we identify the neighbors of each node (i.e., the nodes directly connected to it).

Then, extract the subgraph MFPT matrix of these neighbors, and calculate the inverse of the

MFPT between each pair of neighbors. The local efficiency of the node is the average of these

inverse MFPT values, normalized by the total number of possible neighbor pairs. The average of

local efficiencies across all nodes in the network is often reported as an overall measure of

segregation in the network (Latora and Marchiori 2001).

Results

A large number of random walkers (10^4) were randomly placed on each of the 491

correlation-based functional connectivity matrices and allowed to move for $T = 1000$. At each

time step, the walkers moved randomly between directly connected nodes, with the probability

depending on the number of walkers at each node and the strength and sign of the connections

(see equations (1)-(4)). We recorded the number of walkers in each node (i.e., $A(i, t)$) and the

number of walkers that transited through each connection at each time step. This allowed us to

compute the Walkers' connectivity matrix(W), where each connection represents the total

number of walkers that transited through that connection during the entire simulation. Note that

(W) is a non-symmetric matrix. For comparison, we also ran a simulation with a classical

random walk where the transition probability only depended on the absolute value of the

connections: $P_{ij}(t) = |C_{ij}| / \sum_{j=1}^{N} |C_{ij}|$.

Figure 1 shows the correlation-based functional connectivity matrix for one subject (Figure

1A), and the corresponding walkers' activity on each node ($A(i,t)$) in the network when using

the absolute value of the connections (Figure 1B), and for the signed case (Figure 1C). We can

see from the figure that for the signed case, the activities in the nodes exhibit more variability

than for the 'Abs' case. This suggests that considering signed connections may provide a more

nuanced understanding of the network dynamics.

Figure 2 displays the walkers' connectivity matrix W, averaged across subjects for both the

'abs' case (Figure 2A) and the signed case (Figure 2B). We also plotted histograms of the

connections in W for the 'Abs' (Figure 2C) and signed cases (Figure 2D). In the 'Abs' case, we

observed 11,523 connections with fewer than 1,000 walkers, more than the 10,972 connections

in the signed network. For highly transited connections, the 'Abs' case had only four connections

with over 3,000 walkers and none with more than 5,000 walkers. In contrast, the signed case

featured 270 connections with over 3,000 walkers and eight connections with more than 5,000

walkers. The signed case revealed a greater number of highly transited connections and

demonstrated the presence of highly transited connections between homologous regions in the

left and right hemispheres. Specifically, the eight highly transited connections, in descending

order, were: 1) 'Calcarine L' to 'Calcarine R', 2) 'Calcarine R' to 'Calcarine L', 3) 'Cerebellum 8 L'

to 'Cerebellum 7b L', 4) 'Cerebellum 7b L' to 'Cerebellum 8 L', 5) 'Cuneus R' to 'Cuneus L', 6)

'Cuneus L' to 'Cuneus R', 7) 'Temporal Sup R' to 'Temporal Sup L', and 8) 'Temporal Sup L' to

'Temporal Sup R'. Here, 'L' denotes the left brain hemisphere, and 'R' indicates the right

Figure 3 shows the total number of walkers that transited each brain area, averaged across all

subjects. In the 'Abs' case (Figure 3A), the most transited brain areas were 'Temp Inf L', 'Lingual

R', and 'Temporal pole Mid L'. Interestingly, for the signed network (Figure 3B), the most

transited area was also 'Temp Inf L', followed by 'Temporal pole Mid L'. 'Lingual L', which

ranked as the second most transited area in the 'Abs' network, dropped to the 17th position in the

signed case. This result highlights the differences in the most transited brain areas between the

'Abs' and signed cases, demonstrating the impact of considering both positive and negative

connections on the analysis.

Figure 4 compares the global efficiency (Figure 4A), local efficiency (Figure 4B), and MFPT

(Figure 4C) averaged across subjects between the 'Abs' and signed cases. Figure 4C

demonstrates that taking the absolute value of the connections leads to an underestimation of the

MFPT. As we calculated the efficiencies using MFPT, this resulted in an overestimation of their

values. An interesting question in the signed case concerns the impact of the number of walkers

in the negative connections on the calculated topological measures. Figures 4D, 4E, and 4F plot

the three topological measures against the fraction of walkers that transited negative connections

compared to positive connections (Neg/Pos fraction). We found significant correlations between

global efficiency $(r = 0.59,\ p = 10^{-47})$, local efficiency ($r = 0.86, p = 10^{-142}$), and MFPT

($r = 0.85\,, p = 10^{-136}$) with the Neg/Pos fraction.

235
236
237   Insert Figure 1 around here
238
239   Insert Figure 2 around here
240
241   Insert Figure 3 around here
242
243   Insert Figure 4 around here
244

Discussion

In this study, we introduced an adaptive random walk approach for analyzing correlation-
based brain networks, taking into account both positive and negative connections. The proposed
method captures a broader range of network interactions and dynamics, revealing patterns that
might be missed when employing traditional methods. Our results indicate that the classical
random walk approach, which relies on the absolute value of connections, overestimates network
integration and segregation while underestimating the mean first passage time (MFPT) compared
to the proposed adaptive random walk model. This has important implications for understanding
the interregional coordination underlying various cognitive processes and behaviors (Bassett and
Sporns 2017).

Despite the advantages of the adaptive random walk model, there are some limitations that
should be addressed in future research. One limitation is the reliance on static functional
connectivity matrices, which may not fully capture the dynamic nature of brain activity. Future
studies could extend the model to account for dynamic functional connectivity, allowing for the
investigation of time-varying network organization (Preti, Bolton, and Van De Ville 2017).
Another limitation is the potential sensitivity of the model to the choice of parameters, such as
the initial number of walkers and the number of time steps. A systematic exploration of these
parameters should be performed to determine their impact on the results and to identify optimal
settings for different applications.

An additional aspect to consider in our study is the use of GSR in preprocessing the
neuroimaging data. GSR is a common preprocessing step that aims to remove global confounds,
such as physiological noise, from the data (Murphy and Fox 2017). However, it has been shown
that GSR can introduce more negative correlations into the functional connectivity matrices
(Murphy et al. 2009). This has led to some debate regarding the validity of negative correlations
as they may, at least partially, be an artifact of the preprocessing technique (Saad et al. 2012).
The potential impact of GSR on our adaptive random walk model is an important consideration,
as it could affect the observed transition probabilities and the subsequent network measures. In
our analysis, we treated both positive and negative correlations as meaningful connections,
reflecting the underlying physiological mechanisms. However, if GSR artificially inflates the
number of negative correlations, it could bias our results, potentially leading to an overestimation

of the impact of negative connections on the network organization. To address this issue, future
research could explore alternative preprocessing techniques that do not introduce additional
negative correlations or investigate the sensitivity of the adaptive random walk model to the
presence of artificially induced negative correlations. Comparing the results obtained using
different preprocessing methods or incorporating additional steps to correct for the possible
effects of GSR could help to disentangle the true physiological significance of the negative
correlations from the potential artifacts introduced by GSR. This would contribute to a more
robust understanding of the brain network organization and its underlying functional interactions.
Finally, future research could also further refine the adaptive random walk model by
incorporating additional factors that may influence the transition probabilities, such as the spatial
distance between brain regions or the directionality of connections.
286

Conclusions

In conclusion, the adaptive random walk model presented in this study offers a promising
approach for the analysis of correlation-based brain networks, accounting for both positive and
negative connections. While there are limitations to the current model, addressing these in future
research will help to further enhance its applicability and utility. This method provides a more
comprehensive understanding of brain network organization and has the potential to advance our
knowledge of the complex interplay between brain regions in various cognitive processes and
behaviors.
295
296
297

References

Avants, Brian B., Nicholas J. Tustison, Gang Song, Philip A. Cook, Arno Klein, and James C.
Gee. 2011. "A Reproducible Evaluation of ANTs Similarity Metric Performance in Brain
Image Registration." *NeuroImage* 54 (3): 2033–44.
https://doi.org/10.1016/j.neuroimage.2010.09.025.
Bassett, Danielle S., and Olaf Sporns. 2017. "Network Neuroscience." *Nature Neuroscience* 20
(3): 353–64. https://doi.org/10.1038/nn.4502.
Behzadi, Yashar, Khaled Restom, Joy Liau, and Thomas T. Liu. 2007. "A Component Based
Noise Correction Method (CompCor) for BOLD and Perfusion Based FMRI."
NeuroImage 37 (1): 90–101. https://doi.org/10.1016/j.neuroimage.2007.04.042.
Bressler, Steven L., and Vinod Menon. 2010. "Large-Scale Brain Networks in Cognition:
Emerging Methods and Principles." *Trends in Cognitive Sciences* 14 (6): 277–90.
https://doi.org/10.1016/j.tics.2010.04.004.
Bullmore, Ed, and Olaf Sporns. 2009. "Complex Brain Networks: Graph Theoretical Analysis of
Structural and Functional Systems." *Nature Reviews Neuroscience* 10 (3): 186–98.
https://doi.org/10.1038/nrn2575.
Cameron, Craddock, Sikka Sharad, Cheung Brian, Khanuja Ranjeet, Ghosh Satrajit, Yan
Chaogan, Li Qingyang, et al. 2013. "Towards Automated Analysis of Connectomes: The

Configurable Pipeline for the Analysis of Connectomes (C-PAC).” *Frontiers in Neuroinformatics* 7. https://doi.org/10.3389/conf.fninf.2013.09.00042.

Cameron, Craddock, Benhajali Yassine, Chu Carlton, Chouinard Francois, Evans Alan, Jakab András, Khundrakpam Budhachandra, et al. 2013. “The Neuro Bureau Preprocessing Initiative: Open Sharing of Preprocessed Neuroimaging Data and Derivatives.” *Frontiers in Neuroinformatics* 7. https://doi.org/10.3389/conf.fninf.2013.09.00041.

Cox, Robert W. 1996. “AFNI: Software for Analysis and Visualization of Functional Magnetic Resonance Neuroimages.” *Computers and Biomedical Research* 29 (3): 162–73. https://doi.org/10.1006/cbmr.1996.0014.

Friston, Karl J. 1994. “Functional and Effective Connectivity in Neuroimaging: A Synthesis.” *Human Brain Mapping* 2 (1–2): 56–78. https://doi.org/10.1002/hbm.460020107.

Grabner, Günther, Andrew L. Janke, Marc M. Budge, David Smith, Jens Pruessner, and D. Louis Collins. 2006. “Symmetric Atlasing and Model Based Segmentation: An Application to the Hippocampus in Older Adults.” *Medical Image Computing and Computer-Assisted Intervention: MICCAI ... International Conference on Medical Image Computing and Computer-Assisted Intervention* 9 (Pt 2): 58–66. https://doi.org/10.1007/11866763_8.

Heuvel, Martijn P. van den, and Hilleke E. Hulshoff Pol. 2010. “Exploring the Brain Network: A Review on Resting-State FMRI Functional Connectivity.” *European Neuropsychopharmacology* 20 (8): 519–34. https://doi.org/10.1016/j.euroneuro.2010.03.008.

Hughes, Barry D. 1995. *Random Walks and Random Environments*. Oxford, New York: Oxford University Press.

Kazeminejad, Amirali, and Roberto C. Sotero. 2019. “Topological Properties of Resting-State FMRI Functional Networks Improve Machine Learning-Based Autism Classification.” *Frontiers in Neuroscience* 12. https://www.frontiersin.org/articles/10.3389/fnins.2018.01018.

Latora, Vito, and Massimo Marchiori. 2001. “Efficient Behavior of Small-World Networks.” *Physical Review Letters* 87 (19): 198701. https://doi.org/10.1103/PhysRevLett.87.198701.

Mahadevan, Arun S., Ursula A. Tooley, Maxwell A. Bertolero, Allyson P. Mackey, and Danielle S. Bassett. 2021. “Evaluating the Sensitivity of Functional Connectivity Measures to Motion Artifact in Resting-State FMRI Data.” *NeuroImage* 241 (November): 118408. https://doi.org/10.1016/j.neuroimage.2021.118408.

Mazziotta, John, Arthur Toga, Alan Evans, Peter Fox, Jack Lancaster, Karl Zilles, Roger Woods, et al. 2001. “A Four-Dimensional Probabilistic Atlas of the Human Brain.” *Journal of the American Medical Informatics Association* 8 (5): 401–30. https://doi.org/10.1136/jamia.2001.0080401.

Meszlényi, Regina J., Petra Hermann, Krisztian Buza, Viktor Gál, and Zoltán Vidnyánszky. 2017. “Resting State FMRI Functional Connectivity Analysis Using Dynamic Time Warping.” *Frontiers in Neuroscience* 11. https://www.frontiersin.org/articles/10.3389/fnins.2017.00075.

Murphy, Kevin, Rasmus M. Birn, Daniel A. Handwerker, Tyler B. Jones, and Peter A. Bandettini. 2009. “The Impact of Global Signal Regression on Resting State Correlations: Are Anti-Correlated Networks Introduced?” *NeuroImage* 44 (3): 893–905. https://doi.org/10.1016/j.neuroimage.2008.09.036.

Murphy, Kevin, and Michael D. Fox. 2017. "Towards a Consensus Regarding Global Signal
Regression for Resting State Functional Connectivity MRI." *NeuroImage* 154 (July):
169–73. https://doi.org/10.1016/j.neuroimage.2016.11.052.
Noh, Jae Dong, and Heiko Rieger. 2004. "Random Walks on Complex Networks." *Physical*
Review Letters 92 (11): 118701. https://doi.org/10.1103/PhysRevLett.92.118701.
Pearson, Karl. 1905. "The Problem of the Random Walk." *Nature* 72 (1867): 342–342.
https://doi.org/10.1038/072342a0.
Preti, Maria Giulia, Thomas AW Bolton, and Dimitri Van De Ville. 2017. "The Dynamic
Functional Connectome: State-of-the-Art and Perspectives." *NeuroImage*, Functional
Architecture of the Brain, 160 (October): 41–54.
https://doi.org/10.1016/j.neuroimage.2016.12.061.
Riascos, A P, and José L Mateos. 2021. "Random Walks on Weighted Networks: A Survey of
Local and Non-Local Dynamics." *Journal of Complex Networks* 9 (5): cnab032.
https://doi.org/10.1093/comnet/cnab032.
Rubinov, Mikail, and Olaf Sporns. 2011. "Weight-Conserving Characterization of Complex
Functional Brain Networks." *NeuroImage* 56 (4): 2068–79.
https://doi.org/10.1016/j.neuroimage.2011.03.069.
Saad, Ziad S., Stephen J. Gotts, Kevin Murphy, Gang Chen, Hang Joon Jo, Alex Martin, and
Robert W. Cox. 2012. "Trouble at Rest: How Correlation Patterns and Group Differences
Become Distorted After Global Signal Regression." *Brain Connectivity* 2 (1): 25–32.
https://doi.org/10.1089/brain.2012.0080.
Smith, Stephen M., Mark Jenkinson, Mark W. Woolrich, Christian F. Beckmann, Timothy E. J.
Behrens, Heidi Johansen-Berg, Peter R. Bannister, et al. 2004. "Advances in Functional
and Structural MR Image Analysis and Implementation as FSL." *NeuroImage* 23 Suppl
1: S208-219. https://doi.org/10.1016/j.neuroimage.2004.07.051.
Sotero, Roberto C., Lazaro M. Sanchez-Rodriguez, Narges Moradi, and Mehdy Dousty. 2020.
"Estimation of Global and Local Complexities of Brain Networks: A Random Walks
Approach." *Network Neuroscience* 4 (3): 575–94. https://doi.org/10.1162/netn_a_00138.
Tzourio-Mazoyer, N., B. Landeau, D. Papathanassiou, F. Crivello, O. Etard, N. Delcroix, B.
Mazoyer, and M. Joliot. 2002. "Automated Anatomical Labeling of Activations in SPM
Using a Macroscopic Anatomical Parcellation of the MNI MRI Single-Subject Brain."
NeuroImage 15 (1): 273–89. https://doi.org/10.1006/nimg.2001.0978.
Wan, Cong, Yanhui Fang, Cong Wang, Yanxia Lv, Zejie Tian, and Yun Wang. 2019.
"SignRank: A Novel Random Walking Based Ranking Algorithm in Signed Networks."
Wireless Communications and Mobile Computing 2019 (April): e4813717.
https://doi.org/10.1155/2019/4813717.
Yang, Bo, William Cheung, and Jiming Liu. 2007. "Community Mining from Signed Social
Networks." *IEEE Transactions on Knowledge and Data Engineering* 19 (10): 1333–48.
https://doi.org/10.1109/TKDE.2007.1061.
Zhou, Jianlin, Lingbo Li, An Zeng, Ying Fan, and Zengru Di. 2018. "Random Walk on Signed
Networks." *Physica A: Statistical Mechanics and Its Applications* 508 (October): 558–66.
https://doi.org/10.1016/j.physa.2018.05.139.
403
404
405
406

Figures

Figure 1. Correlation-based functional connectivity matrix and walkers' activity on each node in the
network for one subject. (A) Functional connectivity matrix illustrating the strength of correlations
between different brain regions for a single subject. (B) Walker activity (A(i,t)) on each node in the
network when using the absolute value of the connections, demonstrating relatively uniform activity
across nodes. (C) Walker activity (A(i,t)) on each node in the network for the signed case, displaying
increased variability in node activity compared to the absolute case.

419
Figure 2: Comparison of walkers' connectivity matrices and connection histograms for the 'Abs' and
signed cases. (A) Walkers' connectivity matrix W, averaged across subjects for the 'Abs' case, illustrating
the number of walkers transiting between different brain regions using the absolute value of the
connections. (B) Walkers' connectivity matrix W, averaged across subjects for the signed case. (C)
Histogram of connections in W for the 'Abs' case, showing the distribution of connections with different
numbers of walkers. (D) Histogram of connections in W for the signed case, with a greater number of
highly transited connections than the 'Abs' case.
427
428
429
430

431
432   Figure 3: Total number of walkers transiting each brain area, averaged across all subjects for the 'Abs' and
433   signed cases. (A) Bar plot showing the mean and standard deviation of walkers transiting each brain area

434 in the 'Abs' case. (B) Bar plot illustrating the mean and standard deviation of walkers transiting each brain
435 area in the signed case.

438
Figure 4: Computing topological measures with random walks. Comparison of global efficiency, local
efficiency, and MFPT between the 'Abs' and signed cases, and their correlation with the fraction of
walkers transiting negative connections vs positive connections (Neg/Pos fraction). (A) Global efficiency
comparison, (B) local efficiency comparison, and (C) MFPT comparison between, (D) Scatter plot of the
relationship between global efficiency and Neg/Pos fraction, with a significant correlation
$(r = 0.59, \ p = 10^{-47})$,. (E) Scatter plot illustrating the correlation between local efficiency and the
Neg/Pos fraction ($r = 0.86, p = 10^{-142}$). (F) Scatter plot depicting the correlation between MFPT and
the Neg/Pos fraction ($r = 0.85, p = 10^{-136}$).