Exploring Correlation-Based Brain Networks with Adaptive Signed Random Walks

Roberto C. Sotero[1], Jose M. Sanchez-Bornot[2]

[1] Department of Radiology, and Hotchkiss Brain Institute. University of Calgary, Calgary, AB, Canada.
[2] Intelligent Systems Research Centre, Ulster University, Derry Londonderry, United Kingdom

Corresponding Author:
Roberto C. Sotero[1]
HSC 2923 - 3330 Hospital Drive NW, Calgary, AB, T2N 4N1, Canada
Email address: roberto.soterodiaz@ucalgary.ca

Abstract

The human brain is a highly connected network with complex patterns of correlated and anticorrelated activity. Analyzing functional connectivity matrices derived from neuroimaging data can provide insights into the organization of brain networks and their association with cognitive processes or disorders. Common approaches, such as thresholding or binarization, often disregard negative connections, which may result in the loss of critical information. This study introduces an adaptive signed random walk (ASRW) model for analyzing correlation-based brain networks that incorporates both positive and negative connections. The model calculates transition probabilities between brain regions as a function of their activities and connection strengths, dynamically updating probabilities based on the differences in node activity and connection strengths at each time step. Results show that the classical random walk approach, which only considers the absolute value of connections, underestimates the mean first passage time (MFPT) compared to the proposed ASRW model. Our model captures a wide range of interactions and dynamics within the network, providing a more comprehensive understanding of its structure and function. This study suggests that considering both positive and negative connections, has the potential to offer valuable insights into the interregional coordination underlying various cognitive processes and behaviors.

Introduction

The human brain is an intricate and highly connected network, with numerous regions displaying complex patterns of correlated and anticorrelated activity (Bressler and Menon 2010). Functional connectivity matrices (Friston 1994) represent the statistical relationships between these activity signals from different brain regions, often derived from neuroimaging data such as functional Magnetic Resonance Imaging (fMRI), Electroencephalography (EEG), or Magnetoencephalography (MEG). These matrices can be used to investigate the organization of brain networks and to identify patterns of connectivity associated with different cognitive processes or brain disorders by means of various analytical techniques, such as graph theory and complex network analysis (Bassett and Sporns 2017; Bullmore and Sporns 2009).

When performing complex network analysis on correlation-based functional connectivity matrices, one of the following approaches is typically used: 1) Binarization: this involves binarizing the functional connectivity matrix by assigning "1" to connections with correlations above a specified threshold and "0" to connections below the threshold (Bassett and Sporns 2017; Kazeminejad and Sotero 2019). This approach also discards the negative correlations and can be used for further network analysis on a binary network. 2) Thresholding: a more general approach than where we apply a threshold to the functional connectivity matrix, preserving only the connections with correlations above a certain value (often positive correlations) (van den Heuvel and Hulshoff Pol 2010; Kazeminejad and Sotero 2019). This way, we create a binary or weighted network, discarding the negative correlations. This approach can lead to a loss of information about the negative interactions between brain regions (Rubinov and Sporns 2011). 3) Separate analysis of positive and negative connections. Two networks are created – one for positive correlations and another for negative correlations – and then perform network analysis on each network independently. This approach preserves the information about negative interactions between brain regions but treats them as separate entities (Sotero et al. 2020). 4) Disregard information about the connection sign by taking the absolute value of the connections (Meszlényi et al. 2017; Mahadevan et al. 2021). By disregarding the sign of the connections, we may inadvertently overlook critical aspects of the brain's organization, such as the balance between correlated and anticorrelated activity, which can provide insight into the interregional coordination underlying various cognitive processes and behaviors.

One approach that has shown promise in exploring the structure of complex networks, is the use of random walks (Noh and Rieger 2004). Random walks represent a type of stochastic process that characterizes the random motion of an object or particle in either discrete or continuous spaces (Pearson 1905). Within graph theory and network analysis, random walks are frequently employed to model the movement of a "walker" on a graph, with the walker traversing from one node to another along the edges of the graph (Riascos and Mateos 2021). Random walks have been adapted for use with signed social networks by adjusting the transition probabilities to preferentially favor positive edges over negative edges, or vice versa (Wan et al. 2019; Zhou et al. 2018; Yang, Cheung, and Liu 2007). However, the interpretation of signed connections in social networks, in terms of "trust" and "distrust", as well as the associated transition probability models, are not directly transferable to correlation-based brain networks.

As such, a signed random walk model that aligns with the physiological interpretation of
correlated and anticorrelated activity in the brain is necessary.
In this study, we introduce a novel adaptive signed random walk (ASRW) approach to
analyze correlation-based brain networks, investigating the transition probabilities between
nodes (brain regions) as a function of their activities and connection strengths. The
distinguishing feature of this model is the inclusion of both positive and negative connections
when calculating transition probabilities. Positive connections represent a higher probability of
transitions between nodes exhibiting similar activities, while negative connections correspond to
a higher probability of transitions between nodes with dissimilar activities. By dynamically
updating the transition probabilities in response to node activity differences at each time step and
considering connection strengths, the ASRW model offers a more comprehensive insight into the
network's characteristics. To quantify this, we compute the mean first passage time (MFPT).
MFPT measures the average number of steps it takes for a random walker to travel from one
node to another in a network. It helps in understanding the accessibility and navigability of the
network. Our findings indicate that the classical random walk approach, which considers the
absolute value of connections produces lower MFPT than our ASRW model, which considers
both positive and negative connections. The proposed method captures a wide range of
interactions and dynamics within the network, providing a more comprehensive understanding of
its structure and function.
98
Materials & Methods
Computing the functional connectivity matrices
In this study, resting-state (rs)-fMRI data from 491 neurotypical subjects were obtained from the
ABIDE Preprocessed Initiative (Cameron, Yassine, et al. 2013). To ensure that our results were
not influenced by any custom preprocessing pipeline, we utilized the preprocessed data provided
by ABIDE in the C-PAC pipeline (Cameron, Sharad, et al. 2013). The preprocessing involved
several steps. First, the skull was removed from images using the Analysis of Functional Neuro
Images (AFNI) software (Cox 1996). The brain was then segmented into three tissues using
FMRIB Software Library (FSL) (Smith et al. 2004) and the images were normalized to the MNI
152 stereotactic space (Grabner et al. 2006; Mazziotta et al. 2001) using Advanced
Normalization Tools (ANTs) (Avants et al. 2011). Functional preprocessing included motion and
slice-timing correction, as well as voxel intensity normalization. Nuisance signal regression was
also performed, which encompassed 24 parameters for head motion, CompCor (Behzadi et al.
2007) with five principal components for tissue signal in cerebrospinal fluid and white matter,
and linear and quadratic trends for low-frequency drifts. Global signal regression (GSR) was
applied to remove the global mean from signals, and images were co-registered with their
anatomical counterparts using FSL. Subsequently, the images were normalized to the MNI 152
space using ANTs.
The average voxel activity in each Region of Interest (ROI) of the anatomical automatic
labelling (AAL) atlas (Tzourio-Mazoyer et al. 2002) was extracted as the time series for that

region. As rs-fMRI primarily focuses on low-frequency fluctuations (< 0.1 Hz), a bandpass filter
was applied to frequencies between 0.01 Hz and 0.1 Hz. To construct the brain network, the time
series for each atlas ROI were correlated with the other regions using Pearson correlation. The
strengths of these correlations were used as the connection strengths between different ROIs. In
graph terms, this represents a graph where each node is at the center of the corresponding ROI,
and each edge weight corresponds to the correlation between the two nodes at opposite ends of
the edge.

Walk rule on the correlation network: the ASRW model

First, let us consider a weighted network consisting of N nodes. We place a large number (K)
of random walkers onto this network, where K is significantly larger than N. At each time step,
the walkers move randomly between the nodes that are directly linked to each other, with
transition probability only depending on the absolute value of the connections:

131
$$P_{ij}(t) = \frac{|c_{ij}|}{\sum_{j=1}^{N}|c_{ij}|} \qquad (1)$$

We allow the walkers to perform T time steps, and as a walker visits a node, we record the
number of walkers in the node. After T time steps, we expect that nodes with high degree (hubs)
will have a higher number of walkers than nodes with low degree.

For correlation networks, such as the functional connectivity matrix representing the brain
network, we propose a routing strategy that takes into account the sign of the connection. In the
proposed ASRW model for correlation networks, the transition probabilities are computed based
on the weights in the functional connectivity matrix (C) and a similarity measure between the
activities of the source and destination nodes. The main idea is to favor transitions between
nodes with similar activities while also considering the positive or negative weights in the
network.

We define the activity in each node $A_i(t)$ as the number of walkers visiting the node, and the
walkers' connectivity matrix $W(t)$, where $W_{ij}(t)$ is the total number of walkers that traveled
from node i to node j until time step t.

At the beginning ($t = 0$), we use a uniform random distribution to assign each of the K
walkers to one of the 116 brain areas, resulting in an initial activity $A_i(0)$ for each node i. Given
the activities $A_i(0)$ the transition probabilities $P_{ij}(t + 1)$ and the next activities $A_i(t + 1)$ are
computed as follows:

1. For each node i, we calculate the adjusted weights for all its neighboring nodes j as
follows:

a. We introduce the similarity measure $S_{ij}(t)$ between the activity of node i and node j at time
t using the formula:

153
$$S_{ij}(t) = 1 - \left| \frac{A_i(t) - A_j(t)}{\max\left(A_i(t), A_j(t)\right)} \right| \qquad (2)$$

To normalize the difference between the activities of the nodes, we divide by the maximum
of the activities $\max\left(A_i(t), A_j(t)\right)$. The similarity $S_{ij}(t)$ ranges between 0 and 1. A value closer

to 1 indicates that the activities of nodes i and node j more similar, while a value closer to 0
indicates that the activities are more dissimilar.
b. If the weight C_{ij} is positive, the adjusted weight is $\left(\tilde{C}_{ij}(t) \geq 0\right)$:

$$\tilde{C}_{ij}(t) = C_{ij}S_{ij}(t) \tag{3}$$

If the weight C_{ij} is negative, the adjusted weight is:

$$\tilde{C}_{ij}(t) = |C_{ij}|\left(1 - S_{ij}(t)\right) \tag{4}$$

3. We then calculate the sum of the adjusted weights for all neighbors of node i. The transition
probability $P_{ij}(t + 1)$ of a walker moving from node i to each neighboring node j in the next
time step $t + 1$ is computed as:

$$P_{ij}(t + 1) = \frac{\tilde{C}_{ij}(t)}{\sum_{j=1}^{N}\tilde{C}_{ij}(t)} \tag{5}$$

Thus, a walker is more likely to travel through a positive connection C_{ij} if the activities in
nodes i and j are similar, while it is more likely to take a negative connection if the activities are
dissimilar.
4. The random walkers move based on the probabilities $P_{ij}(t + 1)$, and the next activites
$A_i(t + 1)$ are the new number of walkers at each node.
5. The walkers' connectivity matrix $W_{ij}(t + 1)$ is updated by adding the number of walkers that
travelled from node i to node j at time step $t + 1$ to $W_{ij}(t)$, for all pairs of nodes i and j. Note
that although the correlation matrix is symmetric, the resulting walkers' matrix W is usually not
symmetric due to the random movement of the walkers.
175
Mean First Passage Time Computation
MFPT measures the average number of steps a random walker needs to reach a target node from
a starting node for the first time (Hughes 1995). For a network with N nodes, the MFPT is the
average value of first passage times (FPT_{ij}) over all distinct node pairs, computed as:

$$MFPT = \frac{1}{N(N-1)}\sum_{i \neq j}^{N}\sum_{j=1}^{N} FPT_{ij} \tag{6}$$

where FPT_{ij} is the number of time steps walker takes to travel from node i to node j. To
evaluate this, we employ a Monte Carlo approach. Walkers are initially positioned at random
nodes and are moved according to a probability distribution defined by the network's connection
weights - this is determined by equations (1)-(4) for an adaptive signed random walk and
equation (5) for a classic random walk. Each time a walker reaches a new node for the first time,
we record this event's time. After a defined number of time steps, the recorded first-passage
times are used to compute the average, excluding any pairs where a first passage did not occur,
giving us the MFPT. This Monte Carlo simulation is repeated multiple times to provide an
average estimate of the time necessary for information to spread through the network.
190
Results

For each of the 491 correlation-based functional connectivity matrices, we utilize $K = 5 * 10^4$
random walkers and allocate them throughout the matrix. We employ a uniform random
distribution to assign each random walker to one of the 116 brain regions. Subsequently, the
random walkers are allowed to move for a duration of $T = 1000$ steps. At each time step, the
walkers moved randomly between directly connected nodes, with the transition probability
depending on the number of walkers at each node and the strength and sign of the connections
(see equations (1)-(4)). We recorded the number of walkers in each node (i.e., $A(i, t)$) and the
number of walkers that transited through each connection at each time step. This allowed us to
compute the walkers' connectivity matrix W, where each connection represents the total number
of walkers that transited through that connection during the entire simulation. For comparison,
we also ran a simulation with a classical random walk where the transition probability only
depended on the absolute value of the connections (see equation 1).
Figure 1 shows the rs-fMRI signals from the 116 brain areas (Figure 1A) and the
corresponding correlation-based functional connectivity matrix (Figure 1B) calculated from them
for one subject, the corresponding walkers' activity on each node ($A_i(t)$) in the network when
using the absolute value of the connections (Figure 1C, equation (1)), and for the signed case
(Figure 1D equations (2)-(5)). We can see from the figure that for the signed case, the activities
exhibit more variability than for the 'Abs' case. This suggests that considering signed
connections may provide a more nuanced understanding of the network dynamics.
Figure 2 displays the walkers' connectivity matrix W, averaged across subjects for both the
'Abs' case (Figure 2A) and the signed case (Figure 2B). We also plotted histograms of the
connections in W for the 'Abs' (Figure 2C) and signed cases (Figure 2D). In the 'Abs' case, we
observed 13,334 connections with fewer than 15000 walkers, and only 6 connections with more
than 15000 walkers. On the other hand, the signed case presented 272 connections transited by
more than 15000 walkers. The signed case revealed a greater number of highly transited
connections and demonstrated the presence of highly transited connections between homologous
regions in the left and right hemispheres. Specifically, the ten highly transited connections, in
descending order, were: 1) 'Calcarine R' to 'Calcarine L', 2) 'Calcarine L' to 'Calcarine R', 3)
'Cuneus R' to 'Cuneus L', 4) 'Cuneus L' to 'Cuneus R', 5) 'Cerebellum 7b L' to 'Cerebellum 8 L',
6) 'Cerebellum 8 L' to 'Cerebellum 7b L', 7) 'Temporal Sup L' to 'Temporal Sup R', and 8)
'Temporal Sup R' to 'Temporal Sup L', 9) 'Temporal Pole Mid L' to 'Temporal Pole Mid R', 10)
'Temporal Pole Mid R' to 'Temporal Pole Mid L'. Here, 'L' denotes the left brain hemisphere, and
'R' indicates the right hemisphere.
Figure 3 shows the total number of walkers that transited each brain area, averaged across all
subjects and its standard deviation. In the 'Abs' case (Figure 3A), the most transited brain areas
were 'Temp Inf L', 'Lingual R', and 'Temporal pole Mid L'. Interestingly, for the signed network
(Figure 3B), the most transited area was also 'Temp Inf L', followed by 'Temporal pole Mid L'.
'Lingual R', which ranked as the second most transited area in the 'Abs' network, dropped to the
18th position in the signed case. This result highlights the differences in the most transited brain

areas between the 'Abs' and signed cases, demonstrating the impact of considering both positive
and negative connections on the analysis.
Figure 4A compares the MFPT between the 'Abs' and signed cases averaged across subjects.
It demonstrates that using the absolute value of the connections results in lower values of the
MFPT than the signed case. An important aspect of the signed case is the influence of negative
connections in the FC matrix on the MFPT. Figure 4B depicts the MFPT plotted against the
percentage of negative connections in the FC matrix for all subjects. It can be observed from the
x-axis that the range of negative connections varied from 19% to 40%. We found a significant
negative correlation for the 'Abs' case ($r = -0.2728, pvalue = 7.87 * 10^{-10}$), and nearly
identical results were observed for the signed case ($r = -0.2787, pvalue = 3.27 * 10^{-10}$).
To interpret these findings, we conducted multiple simulations to calculate the MFPT in a
network under different scenarios. We generated a symmetric random network of 100 nodes by
creating a symmetric binary adjacency matrix with a designated connection probability ($p = 0.2$)
and randomly allocating weights to these connections, while ensuring network symmetry was
maintained. We then modulated a variable 'q' that determines the fraction of negative
connections, ranging from 0 (representing 'Abs' or absolute case with no negative connections) to
100%, with increments of 5%. For each 'q' value, a signed variant of the random matrix was
constructed by selecting and reversing the sign of a fraction 'q' of the connections (preserving
symmetry to simulate a functional connectivity matrix). Following this, we calculated the MFPT
for the resulting signed matrix. This calculation was repeated 200 times for each 'q' value, with
results averaged. We repeated this entire process for six different numbers of random walkers,
denoted as K: $K = 5 * 10^3$, $K = 10^4$, $K = 5 * 10^4$, $K = 7.5 * 10^4$, $K = 10^5$, and $K = $
$1.5 * 10^5$. Figure 5A depicts the outcomes. Our simulations reinforced the empirical data
results, indicating that the 'Abs' scenario (0% negative connections) yields a lower MFPT
compared to cases considering negative connections. Generally, the relationship between MFPT
and the percentage of negative connections was non-linear. For relatively low percentages (up to
approximately 15%), MFPT increases in line with the percentage. Then, in the range of 15% to
80%, MFPT experiences a slight decrease as the percentage of negative connections increases,
which corroborates our findings with real data depicted in Figure 4B. For exceedingly high
percentages of negative connections (80%-100%), the MFPT augments along with the
percentage increase. Notably, beyond $K = 5 * 10^4$, subsequent increases in K had a minimal
impact on the results.
In a subsequent analysis (Figure 5B), we changed the connection probability, considering four
different values: $p = [0.2, 0.4, 0.6, 0.8]$, while keeping the number of walkers fixed at $K = $
$5 * 10^4$. Higher 'p' values correspond to denser matrices. Similar to the procedure in Figure 5A,
we varied the fraction 'q' of negative connections from 0 to 100%, with 5% increments. Each
combination of 'p' and 'q' values (i.e., each simulation) was replicated 200 times, with the
outcomes being averaged. Our findings suggest that as 'p' increases (hence, increasing the density
of connections within the random signed matrix), the MFPT decreases.
270

271   Insert Figure 1 around here
272
273   Insert Figure 2 around here
274
275   Insert Figure 3 around here
276
277   Insert Figure 4 around here
278
279   Insert Figure 5 around here
280
281

Discussion

In this study, we introduced an ASRW approach for analyzing correlation-based brain
networks, taking into account both positive and negative connections. The proposed method
captures a broader range of network interactions and dynamics, revealing patterns that might be
missed when employing traditional methods. Our results indicate that the classical random walk
approach, which relies on the absolute value of connections, underestimates the MFPT compared
to the proposed adaptive random walk model. This has important implications for understanding
the interregional coordination underlying various cognitive processes and behaviors (Bassett and
Sporns 2017).
Despite the advantages of the ASRW model, there are some limitations that should be
addressed in future research. One limitation is the reliance on static functional connectivity
matrices, which may not fully capture the dynamic nature of brain activity. Future studies could
extend the model to account for dynamic functional connectivity, allowing for the investigation
of time-varying network organization (Preti, Bolton, and Van De Ville 2017).
An additional aspect to consider in our study is the use of GSR in preprocessing the
neuroimaging data. GSR is a common preprocessing step that aims to remove global confounds,
such as physiological noise, from the data (Murphy and Fox 2017). However, it has been shown
that GSR can introduce more negative correlations into the functional connectivity matrices
(Murphy et al. 2009). This has led to some debate regarding the validity of negative correlations
as they may, at least partially, be an artifact of the preprocessing technique (Saad et al. 2012).
The potential impact of GSR on our adaptive random walk model is an important consideration,
as it could affect the observed transition probabilities and the subsequent network measures. In
our analysis, we treated both positive and negative correlations as meaningful connections,
reflecting the underlying physiological mechanisms. However, if GSR artificially inflates the
number of negative correlations, it could bias our results, potentially leading to an overestimation
of the impact of negative connections on the network organization. To address this issue, future
research could explore alternative preprocessing techniques that do not introduce additional
negative correlations or investigate the sensitivity of the adaptive random walk model to the
presence of artificially induced negative correlations. Comparing the results obtained using

different preprocessing methods or incorporating additional steps to correct for the possible effects of GSR could help to disentangle the true physiological significance of the negative correlations from the potential artifacts introduced by GSR. This would contribute to a more robust understanding of the brain network organization and its underlying functional interactions.

Finally, future research could also further refine the adaptive random walk model by incorporating additional factors that may influence the transition probabilities, such as the spatial distance between brain regions or the directionality of connections.

Conclusions

The adaptive signed random walk model presented in this study offers a promising approach for the analysis of correlation-based brain networks, accounting for both positive and negative connections. While there are limitations to the current model, addressing these in future research will help to further enhance its applicability and utility. This method provides a more comprehensive understanding of brain network organization and has the potential to advance our knowledge of the complex interplay between brain regions in various cognitive processes and behaviors.

References

Avants, Brian B., Nicholas J. Tustison, Gang Song, Philip A. Cook, Arno Klein, and James C. Gee. 2011. "A Reproducible Evaluation of ANTs Similarity Metric Performance in Brain Image Registration." *NeuroImage* 54 (3): 2033–44. https://doi.org/10.1016/j.neuroimage.2010.09.025.

Bassett, Danielle S., and Olaf Sporns. 2017. "Network Neuroscience." *Nature Neuroscience* 20 (3): 353–64. https://doi.org/10.1038/nn.4502.

Behzadi, Yashar, Khaled Restom, Joy Liau, and Thomas T. Liu. 2007. "A Component Based Noise Correction Method (CompCor) for BOLD and Perfusion Based FMRI." *NeuroImage* 37 (1): 90–101. https://doi.org/10.1016/j.neuroimage.2007.04.042.

Bressler, Steven L., and Vinod Menon. 2010. "Large-Scale Brain Networks in Cognition: Emerging Methods and Principles." *Trends in Cognitive Sciences* 14 (6): 277–90. https://doi.org/10.1016/j.tics.2010.04.004.

Bullmore, Ed, and Olaf Sporns. 2009. "Complex Brain Networks: Graph Theoretical Analysis of Structural and Functional Systems." *Nature Reviews Neuroscience* 10 (3): 186–98. https://doi.org/10.1038/nrn2575.

Cameron, Craddock, Sikka Sharad, Cheung Brian, Khanuja Ranjeet, Ghosh Satrajit, Yan Chaogan, Li Qingyang, et al. 2013. "Towards Automated Analysis of Connectomes: The Configurable Pipeline for the Analysis of Connectomes (C-PAC)." *Frontiers in Neuroinformatics* 7. https://doi.org/10.3389/conf.fninf.2013.09.00042.

Cameron, Craddock, Benhajali Yassine, Chu Carlton, Chouinard Francois, Evans Alan, Jakab András, Khundrakpam Budhachandra, et al. 2013. "The Neuro Bureau Preprocessing Initiative: Open Sharing of Preprocessed Neuroimaging Data and Derivatives." *Frontiers in Neuroinformatics* 7. https://doi.org/10.3389/conf.fninf.2013.09.00041.

Cox, Robert W. 1996. "AFNI: Software for Analysis and Visualization of Functional Magnetic Resonance Neuroimages." *Computers and Biomedical Research* 29 (3): 162–73. https://doi.org/10.1006/cbmr.1996.0014.

Friston, Karl J. 1994. "Functional and Effective Connectivity in Neuroimaging: A Synthesis." *Human Brain Mapping* 2 (1–2): 56–78. https://doi.org/10.1002/hbm.460020107.

Grabner, Günther, Andrew L. Janke, Marc M. Budge, David Smith, Jens Pruessner, and D. Louis Collins. 2006. "Symmetric Atlasing and Model Based Segmentation: An Application to the Hippocampus in Older Adults." *Medical Image Computing and Computer-Assisted Intervention: MICCAI ... International Conference on Medical Image Computing and Computer-Assisted Intervention* 9 (Pt 2): 58–66. https://doi.org/10.1007/11866763_8.

Heuvel, Martijn P. van den, and Hilleke E. Hulshoff Pol. 2010. "Exploring the Brain Network: A Review on Resting-State FMRI Functional Connectivity." *European Neuropsychopharmacology* 20 (8): 519–34. https://doi.org/10.1016/j.euroneuro.2010.03.008.

Hughes, Barry D. 1995. *Random Walks and Random Environments*. Oxford, New York: Oxford University Press.

Kazeminejad, Amirali, and Roberto C. Sotero. 2019. "Topological Properties of Resting-State FMRI Functional Networks Improve Machine Learning-Based Autism Classification." *Frontiers in Neuroscience* 12. https://www.frontiersin.org/articles/10.3389/fnins.2018.01018.

Mahadevan, Arun S., Ursula A. Tooley, Maxwell A. Bertolero, Allyson P. Mackey, and Danielle S. Bassett. 2021. "Evaluating the Sensitivity of Functional Connectivity Measures to Motion Artifact in Resting-State FMRI Data." *NeuroImage* 241 (November): 118408. https://doi.org/10.1016/j.neuroimage.2021.118408.

Mazziotta, John, Arthur Toga, Alan Evans, Peter Fox, Jack Lancaster, Karl Zilles, Roger Woods, et al. 2001. "A Four-Dimensional Probabilistic Atlas of the Human Brain." *Journal of the American Medical Informatics Association* 8 (5): 401–30. https://doi.org/10.1136/jamia.2001.0080401.

Meszlényi, Regina J., Petra Hermann, Krisztian Buza, Viktor Gál, and Zoltán Vidnyánszky. 2017. "Resting State FMRI Functional Connectivity Analysis Using Dynamic Time Warping." *Frontiers in Neuroscience* 11. https://www.frontiersin.org/articles/10.3389/fnins.2017.00075.

Murphy, Kevin, Rasmus M. Birn, Daniel A. Handwerker, Tyler B. Jones, and Peter A. Bandettini. 2009. "The Impact of Global Signal Regression on Resting State Correlations: Are Anti-Correlated Networks Introduced?" *NeuroImage* 44 (3): 893–905. https://doi.org/10.1016/j.neuroimage.2008.09.036.

Murphy, Kevin, and Michael D. Fox. 2017. "Towards a Consensus Regarding Global Signal Regression for Resting State Functional Connectivity MRI." *NeuroImage* 154 (July): 169–73. https://doi.org/10.1016/j.neuroimage.2016.11.052.

Noh, Jae Dong, and Heiko Rieger. 2004. "Random Walks on Complex Networks." *Physical Review Letters* 92 (11): 118701. https://doi.org/10.1103/PhysRevLett.92.118701.

Pearson, Karl. 1905. "The Problem of the Random Walk." *Nature* 72 (1867): 342–342. https://doi.org/10.1038/072342a0.

Preti, Maria Giulia, Thomas AW Bolton, and Dimitri Van De Ville. 2017. "The Dynamic Functional Connectome: State-of-the-Art and Perspectives." *NeuroImage*, Functional

Architecture of the Brain, 160 (October): 41–54.
https://doi.org/10.1016/j.neuroimage.2016.12.061.

Riascos, A P, and José L Mateos. 2021. "Random Walks on Weighted Networks: A Survey of Local and Non-Local Dynamics." *Journal of Complex Networks* 9 (5): cnab032. https://doi.org/10.1093/comnet/cnab032.

Rubinov, Mikail, and Olaf Sporns. 2011. "Weight-Conserving Characterization of Complex Functional Brain Networks." *NeuroImage* 56 (4): 2068–79. https://doi.org/10.1016/j.neuroimage.2011.03.069.

Saad, Ziad S., Stephen J. Gotts, Kevin Murphy, Gang Chen, Hang Joon Jo, Alex Martin, and Robert W. Cox. 2012. "Trouble at Rest: How Correlation Patterns and Group Differences Become Distorted After Global Signal Regression." *Brain Connectivity* 2 (1): 25–32. https://doi.org/10.1089/brain.2012.0080.

Smith, Stephen M., Mark Jenkinson, Mark W. Woolrich, Christian F. Beckmann, Timothy E. J. Behrens, Heidi Johansen-Berg, Peter R. Bannister, et al. 2004. "Advances in Functional and Structural MR Image Analysis and Implementation as FSL." *NeuroImage* 23 Suppl 1: S208-219. https://doi.org/10.1016/j.neuroimage.2004.07.051.

Sotero, Roberto C., Lazaro M. Sanchez-Rodriguez, Narges Moradi, and Mehdy Dousty. 2020. "Estimation of Global and Local Complexities of Brain Networks: A Random Walks Approach." *Network Neuroscience* 4 (3): 575–94. https://doi.org/10.1162/netn_a_00138.

Tzourio-Mazoyer, N., B. Landeau, D. Papathanassiou, F. Crivello, O. Etard, N. Delcroix, B. Mazoyer, and M. Joliot. 2002. "Automated Anatomical Labeling of Activations in SPM Using a Macroscopic Anatomical Parcellation of the MNI MRI Single-Subject Brain." *NeuroImage* 15 (1): 273–89. https://doi.org/10.1006/nimg.2001.0978.

Wan, Cong, Yanhui Fang, Cong Wang, Yanxia Lv, Zejie Tian, and Yun Wang. 2019. "SignRank: A Novel Random Walking Based Ranking Algorithm in Signed Networks." *Wireless Communications and Mobile Computing* 2019 (April): e4813717. https://doi.org/10.1155/2019/4813717.

Yang, Bo, William Cheung, and Jiming Liu. 2007. "Community Mining from Signed Social Networks." *IEEE Transactions on Knowledge and Data Engineering* 19 (10): 1333–48. https://doi.org/10.1109/TKDE.2007.1061.

Zhou, Jianlin, Lingbo Li, An Zeng, Ying Fan, and Zengru Di. 2018. "Random Walk on Signed Networks." *Physica A: Statistical Mechanics and Its Applications* 508 (October): 558–66. https://doi.org/10.1016/j.physa.2018.05.139.

465
466
Figure 1. Correlation-based functional connectivity matrix and walkers' activity on each node in the
network for one subject. (A). rs-fMRI signals from the 116 areas in the AAL atlas. (B) Functional
connectivity matrix illustrating the strength of correlations between different brain regions for a single
subject. (C) Walker activity (A(i,t)) on each node in the network when using the absolute value of the
connections, demonstrating relatively uniform activity across nodes. (D) Walker activity (A(i,t)) on each
node in the network for the signed case, displaying increased variability in node activity compared to the
'Abs' case.

482
Figure 2: Comparison of walkers' connectivity matrices and connection histograms for the 'Abs' and
signed cases. (A) Walkers' connectivity matrix W, averaged across subjects for the 'Abs' case, illustrating
the number of walkers transiting between different brain regions using the absolute value of the
connections. (B) Walkers' connectivity matrix W, averaged across subjects for the signed case. (C)
Histogram of connections in W for the 'Abs' case, showing the distribution of connections with different
numbers of walkers. (D) Histogram of connections in W for the signed case, with a greater number of
highly transited connections than the 'Abs' case.

497
498 Figure 3: Total number of walkers transiting each brain area, averaged across all subjects for the 'Abs' and
499 signed cases. (A) Bar plot showing the mean and standard deviation of walkers transiting each brain area
500 in the 'Abs' case. (B) Bar plot illustrating the mean and standard deviation of walkers transiting each brain
501 area in the signed case.
502

503
504
505 Figure 4: Comparison of MFPT and influence of negative connections. (A) MFPT for both absolute
506 ('Abs') and signed connection cases, averaged across subjects. (B) MFPT as a function of the percentage
507 of negative connections in the FC matrix across all subjects.

526
527
528   Figure 5: Simulated influence of negative connections, number of walkers, and connection density on
529   MFPT. (A) Influence of negative connections on MFPT for different values of the number of walkers K.
530   (B) Influence of negative connections on MFPT for different values of the connection probability p.
531