Analyzing bivariate cross-trait genetic architecture in GWAS summary statistics with

the BIGA cloud computing platform

Running title: BIGA GWAS cloud platform

Yujue Li[1], Fei Xue[1], Bingxuan Li[2], Yilin Yang[3], Zirui Fan[4], Juan Shu[1], Xiaochen Yang[1], Xiyao

Wang[2], Jinjie Lin[5], Carlos Copana[1], and Bingxin Zhao[4,6-10]*

[1]Department of Statistics, Purdue University, West Lafayette, IN 47907, USA.

[2]Department of Computer Science, Purdue University, West Lafayette, IN 47907, USA.

[3]Department of Computer and Information Science and Electrical and Systems Engineering,

School of Engineering & Applied Science, University of Pennsylvania, Philadelphia, PA 19104, USA.

[4]Department of Statistics and Data Science, University of Pennsylvania, Philadelphia, PA 19104,

USA.

[5]Yale School of Management, Yale University, New Haven, CT 06511, USA.

[6]Applied Mathematics and Computational Science Graduate Group, University of Pennsylvania,

Philadelphia, PA 19104, USA.

[7]Center for AI and Data Science for Integrated Diagnostics, Perelman School of Medicine,

University of Pennsylvania, Philadelphia, PA 19104, USA.

[8]Penn Institute for Biomedical Informatics, Perelman School of Medicine, University of

Pennsylvania, Philadelphia, PA 19104, USA.

[9]Population Aging Research Center, University of Pennsylvania, Philadelphia, PA 19104, USA.

[10]Institute for Translational Medicine and Therapeutics, University of Pennsylvania, Philadelphia,

PA 19104, USA.

Corresponding to:

Bingxin Zhao

413 Academic Research Building

265 South 37th Street, Philadelphia, PA 19104.

E-mail: bxzhao@upenn.edu Phone: (215) 898-8222

Abstract

As large-scale biobanks provide increasing access to deep phenotyping and genomic data,

genome-wide association studies (GWAS) are rapidly uncovering the genetic architecture

behind various complex traits and diseases. GWAS publications typically make their

summary-level data (GWAS summary statistics) publicly available, enabling further

exploration of genetic overlaps between phenotypes gathered from different studies and

cohorts. However, systematically analyzing high-dimensional GWAS summary statistics

for thousands of phenotypes can be both logistically challenging and computationally

demanding. In this paper, we introduce BIGA (https://bigagwas.org/), a website that aims

to offer unified data analysis pipelines and processed data resources for cross-trait

genetic architecture analyses using GWAS summary statistics. We have developed a

framework to implement statistical genetics tools on a cloud computing platform,

combined with extensive curated GWAS data resources. Through BIGA, users can upload

data, submit jobs, and share results, providing the research community with a convenient

tool for consolidating GWAS data and generating new insights.

Keywords: GWAS; Cross-trait analysis; Cloud computing; Online platform.

The rapid development of biobank-scale biomedical databases, encompassing phenotyping and genomic data, has occurred globally[1]. Numerous genome-wide association studies (GWAS) have been conducted to determine the genetic architecture underlying a wide range of complex traits and clinical outcomes, with the aim of improving disease prevention and treatment[2]. Publicly available GWAS summary-level data (or GWAS summary statistics) encompass thousands of phenotypes[3-8]. These summary statistics, derived from large-scale studies, provide valuable opportunities for in-depth investigations into genetic overlaps and shared architectures between phenotypes across studies and cohorts. Various statistical genetic tools have been developed to analyze GWAS summary statistics and examine the shared genetic components between pairs of phenotypes, such as LDSC[9], LAVA[10], SumHer[11], and Popcorn[12]. These methods offer insights into genetic links from various perspectives and have been widely applied to clinical biomarkers and outcomes[13,14].

However, implementing and batch-running these tools often requires robust computing and data infrastructure, which may not always be available to all researchers. Consequently, systematic bivariate cross-trait analyses using massive GWAS summary statistics for thousands of phenotypes can be logistically and computationally challenging. As more complex and deep phenotyping data are obtained from biobanks[15], addressing these limitations becomes increasingly urgent. For example, the UK Biobank (UKB) imaging study[16] collected multimodal brain imaging data, generating over 5,000 imaging-derived phenotypes using different imaging modalities and processing pipelines[17-21]. Researchers interested in a specific disease and its genetic connections with imaging biomarkers have traditionally downloaded all the GWAS summary statistics for over 5,000 imaging biomarkers from the Oxford BIG40 Project (http://big.stats.ox.ac.uk) and the BIG-KP project (https://bigkp.org/), and run their statistical tools in local clusters, which can be inefficient. Such challenges are also present in centralized GWAS databases, such as GWAS Catalog[3] and IEU OpenGWAS[7], where users are expected to download and manage large datasets locally to conduct most analyses. Several online research platforms based on cloud computing have been developed, most of which focus on one database (such as the UKB study, https://ukbiobank.dnanexus.com/), univariate trait GWAS analysis (such as FUMA[22]), or single data analysis method/function (such as LD Hub[23] and Locus

Compare[24]). Developing an integrated platform for cross-trait analyses of GWAS summary

data resources will make existing large-scale GWAS summary data more accessible to

researchers.

To address these limitations, we developed BIGA (https://bigagwas.org/), an online cloud-

based platform that offers unified data harmonization and analysis pipelines and

processed data resources for cross-trait analyses using GWAS summary statistics. BIGA

aims to provide various tools for quantifying cross-trait genetic architectures, such as

genome-wide genetic correlation methods (e.g., LDSC[9], Popcorn[12], and SumHer[11]) and

local genetic correlation analysis (e.g., LAVA[10]). We have also aggregated and harmonized

GWAS summary statistics from various resources, including the GWAS Catalog[3], UKB

study[15], Psychiatric Genomics Consortium[25], FinnGen[6], Biobank Japan[8], CHIMGEN[26], UKB-

PPP[27], BIG-KP[18,19,21], and Oxford BIG40[17,20]. These curated datasets, currently including

over 15,000 traits, have been integrated with multiple methods, facilitating easy online

analysis for users. With our established infrastructure in place, we are committed to the

continuous development and growth of BIGA, aiming to broaden its capabilities by

consistently including new tools and data resources.

Figure 1 provides an overview of the BIGA architecture. We offer users several options

for inputting GWAS summary statistics data with user-friendly features, including

uploading their own data, querying data from public databases (such as the IEU

OpenGWAS[7], GWAS Catalog[3], and Neale Lab (http://www.nealelab.is/uk-biobank), and

reusing data from recent previous jobs (Supplementary Text). Users can specify the tools

and job types they are interested in and submit their requests. After submission, the job

request will be passed to the back-end and executed on our cloud computing platform

using the specified tools and datasets. Briefly, we have developed a thorough pipeline for

harmonizing user-input data, similar to procedures used in the GWAS Catalog

(https://github.com/EBISPOT/gwas-sumstats-harmoniser). After harmonization, datasets

will have a standard format with column names outlined in **Table S1**. Considering the

specific data format needed by the user-requested analysis, we will accordingly adapt the

data to fulfill these requirements and execute the analysis (**Fig. S1**) Once completed, users

will receive email notification and the results will be presented to the users through the

front-end interface. A quick-start tutorial and comprehensive documentation are available on our website for users.

BIGA uses a powerful and efficient computational framework for automated analysis. Every step, from the initial data input to the final results output, is organized by a standardized pipeline, offering the flexibility to incorporate new methods. For example, BIGA operates on the Django 3.2 web framework (https://www.djangoproject.com/) to accommodate various tasks and tools, and we use Redis (https://redis.io/) and Celery (https://docs.celeryq.dev) for task management and queuing system. BIGA's computational infrastructure is efficient, currently supporting 20 concurrent user jobs running with just 128GB of RAM and 16 Intel vCPUs. Notably, cloud computing services provide a flexible management system for CPU and RAM, enabling us to easily modify our resource allocation for scaling up or down as needed. Even with only 16GB of RAM, BIGA can execute 3 jobs concurrently using our efficient configuration. We have conducted large-scale tests to validate the stability and computational efficiency of BIGA (**Figs. S2-3** and Supplementary Text).

To showcase the extensive genetic analyses that BIGA can conduct, we present a blood pressure data analysis example, aiming to explore its genetic correlation with over 15,000 complex traits and diseases curated on BIGA. We initiated the analysis by searching for blood pressure data on the IEU OpenGWAS database and used the BIGA query function to directly query systolic blood pressure[28] summary statistics. BIGA performed harmonization and then used the harmonized data to run LDSC massive analysis, spanning over all groups of traits from European population on BIGA. As expected, at a false discovery rate 5% level, systolic blood pressure was widely associated with complex traits and diseases, such as hypertension, atrial fibrillation, stroke, brain and body imaging traits, as well as plasma proteomics (P range = ($5.44×10^{-244}$, $4.00×10^{-2}$), **Fig. S4**). We further examined the diastolic blood pressure[28] and found similar association patterns to systolic blood pressure (**Fig. S5**). We applied SumHer to repeat the analysis (**Fig. S6**) and observed that the results from LDSC and SumHer were generally consistent (**Fig. S7**, Pearson's correlation = 0.9273). In addition, we performed local genetic correlation analysis using LAVA and cross-population genetic correlation using Popcorn. More details can be found

in the Supplementary Text (**Tables S2-S8**). This data analysis example demonstrates that BIGA facilitates efficient analysis of extensive GWAS summary statistics with different methods.

In summary, our platform enables researchers to easily perform multiple cross-trait analyses without needing access to a local research computing cluster, implementing methods locally, or downloading large datasets. BIGA will help reduce the imbalance in the research community caused by unequal computing resources and attract a wider user base to these developed methods. The source code to build the BIGA platform will be made publicly available on GitHub. The BIGA website welcomes user feedback and requests, which aids in improving the project and implementing new tools and functions to better meet the needs of the research community.

ADDITIONAL INFORMATION

One supplementary pdf file and one supplementary table zip file are available.

ACKNOWLEDGEMENTS

We thank for the helpful conversions with Doug Speed regarding SumHer. Research reported in this publication was supported by the National Institute On Aging of the National Institutes of Health under Award Number RF1AG082938. The content is solely the responsibility of the authors and does not necessarily represent the official views of the National Institutes of Health. The study has also been partially supported by funding from the Wharton Dean's Research Fund, Analytics at Wharton, NSF Grant DMS 2210860, and Purdue Statistics Department. We would like to thank the research computing groups at Purdue University, the Wharton School of the University of Pennsylvania, and the University of North Carolina at Chapel Hill for providing computational resources and support that have contributed to these research results. We would like to thank all the developers of the tools and methods implemented in our project. We gratefully acknowledge all the studies and databases that made GWAS summary data available and thank the individuals who represented these studies for their participation and the research teams for their work in collecting, processing, and disseminating these datasets for analysis.

AUTHOR CONTRIBUTIONS

Y.L. and B.Z. designed the study, developed the BIGA website, and wrote the manuscript with feedback from all authors. B.L. helped with the implementation of statistical genetic methods and website functions. Y.Y., Z.F., J.S., X.Y., X.W., B.L., and C.C. processed the GWAS summary statistics, developed the curated datasets, and contributed to the development of the website. F.X. and J.L. provided feedback on the study design and website.

CORRESPONDENCE AND REQUESTS FOR MATERIALS should be addressed to B.Z.

COMPETING FINANCIAL INTERESTS

The authors declare no competing financial interests.

REFERENCES

1. Zhou, W. *et al.* Global Biobank Meta-analysis Initiative: Powering genetic discovery across human disease. *Cell Genomics* **2**, 100192 (2022).
2. Uffelmann, E. *et al.* Genome-wide association studies. *Nature Reviews Methods Primers* **1**, 1-21 (2021).
3. Sollis, E. *et al.* The NHGRI-EBI GWAS Catalog: knowledgebase and deposition resource. *Nucleic Acids Research* (2022).
4. Watanabe, K. *et al.* A global overview of pleiotropy and genetic architecture in complex traits. *Nature genetics* **51**, 1339-1348 (2019).
5. Canela-Xandri, O., Rawlik, K. & Tenesa, A. An atlas of genetic associations in UK Biobank. *Nature genetics* **50**, 1593-1599 (2018).
6. Kurki, M.I. *et al.* FinnGen provides genetic insights from a well-phenotyped isolated population. *Nature* **613**, 508-518 (2023).
7. Elsworth, B. *et al.* The MRC IEU OpenGWAS data infrastructure. *BioRxiv* (2020).
8. Sakaue, S. *et al.* A cross-population atlas of genetic associations for 220 human phenotypes. *Nature genetics* **53**, 1415-1424 (2021).
9. Bulik-Sullivan, B. *et al.* An atlas of genetic correlations across human diseases and traits. *Nature Genetics* **47**, 1236-1241 (2015).

10. Werme, J., van der Sluis, S., Posthuma, D. & de Leeuw, C.A. An integrated framework for local genetic correlation analysis. *Nature genetics* **54**, 274-282 (2022).

11. Speed, D. & Balding, D.J. SumHer better estimates the SNP heritability of complex traits from summary statistics. *Nature Genetics* **51**, 277-284 (2019).

12. Brown, B.C., Ye, C.J., Price, A.L., Zaitlen, N. & Consortium, A.G.E.N.T.D. Transethnic genetic-correlation estimates from summary statistics. *The American Journal of Human Genetics* **99**, 76-88 (2016).

13. Romero, C. *et al.* Exploring the genetic overlap between twelve psychiatric disorders. *Nature Genetics*, 1-8 (2022).

14. Lee, P.H. *et al.* Genomic relationships, novel loci, and pleiotropic mechanisms across eight psychiatric disorders. *Cell* **179**, 1469-1482. e11 (2019).

15. Bycroft, C. *et al.* The UK Biobank resource with deep phenotyping and genomic data. *Nature* **562**, 203-209 (2018).

16. Littlejohns, T.J. *et al.* The UK Biobank imaging enhancement of 100,000 participants: rationale, data collection, management and future directions. *Nature communications* **11**, 1-12 (2020).

17. Elliott, L.T. *et al.* Genome-wide association studies of brain imaging phenotypes in UK Biobank. *Nature* **562**, 210-216 (2018).

18. Zhao, B. *et al.* Common genetic variation influencing human white matter microstructure. *Science* **372**, eabf3736 (2021).

19. Zhao, B. *et al.* Genome-wide association analysis of 19,629 individuals identifies variants influencing regional brain volumes and refines their genetic co-architecture with cognitive and mental health traits. *Nature genetics* **51**, 1637-1644 (2019).

20. Smith, S.M. *et al.* An expanded set of genome-wide association studies of brain imaging phenotypes in UK Biobank. *Nature neuroscience* **24**, 737-745 (2021).

21. Zhao, B. *et al.* Common variants contribute to intrinsic human brain functional networks. *Nature Genetics* **54**, 508-517 (2022).

22. Watanabe, K., Taskesen, E., Bochoven, A. & Posthuma, D. Functional mapping and annotation of genetic associations with FUMA. *Nature Communications* **8**, 1826 (2017).

23. Zheng, J. *et al.* LD Hub: a centralized database and web interface to perform LD score regression that maximizes the potential of summary level GWAS data for SNP heritability and genetic correlation analysis. *Bioinformatics* **33**, 272-279 (2017).

24. Liu, B., Gloudemans, M.J., Rao, A.S., Ingelsson, E. & Montgomery, S.B. Abundant associations with gene expression complicate GWAS follow-up. *Nature genetics* **51**, 768-769 (2019).

25. Sullivan, P. A framework for interpreting genome-wide association studies of psychiatric disorders. *Molecular psychiatry* (2009).

26. Xu, Q. *et al.* CHIMGEN: a Chinese imaging genetics cohort to enhance cross-ethnic and cross-geographic brain research. *Molecular Psychiatry* **25**, 517-529 (2020).

27. Sun, B.B. *et al.* Plasma proteomic associations with genetics and health in the UK Biobank. *Nature* **622**, 329-338 (2023).

28. Evangelou, E. *et al.* Genetic analysis of over 1 million people identifies 535 new loci associated with blood pressure traits. *Nature Genetics* **50**, 1412-1425 (2018).

Code availability

All source code to develop the BIGA platform will be made publicly available on the BIGA GitHub repository. The statistical tools and methods implemented in the BIGA platform are also open source, and their source code has already been made available to the public by their authors. A summary of our implemented tools and data resources can be found at https://bigagwas.org/documentation.

Data availability

GWAS summary statistics used in the BIGA platform are publicly available and can be found in several public databases, such as the

Neale Lab UK Biobank Results (http://www.nealelab.is/uk-biobank),

Psychiatric Genomics Consortium (https://pgc.unc.edu/),

IEU OpenGWAS (https://gwas.mrcieu.ac.uk/),

FinnGen (https://www.finngen.fi/en/access_results),

Biobank Japan (https://pheweb.jp/),

BIG-KP (https://bigkp.org/),

Oxford BIG40 (https://open.win.ox.ac.uk/ukbiobank/big40/),

UKB-PPP (https://metabolomips.org/ukbbpgwas/),

GWAS Catalog (https://www.ebi.ac.uk/gwas/downloads/summary-statistics), and

CHIMGEN (http://chimgen.tmu.edu.cn/en/index.php?c=article&id=2036).

Figure Legend

Fig. 1 Overview of BIGA GWAS cloud computing platform.

(A) The motivation of this project is to address the substantial logistical and
computational challenges associated with implementing and batch-running the
constantly evolving tools for cross-trait genetic architecture analysis. Our aim is to offer a
cloud computing-based solution that can effectively overcome these challenges. **(B)**
Overview of the BIGA GWAS platform. Users can easily upload or query GWAS summary
statistics and submit data analysis jobs through the front-end interface. These jobs are
then processed on the back-end, and the results are subsequently returned to the users.
(C) The front-end interface of the BIGA GWAS platform offers users a comprehensive set
of options to manage their data resources, choose the appropriate tools, and select the
desired mode of data analysis. **(D)** Details of the back-end of the BIGA GWAS platform. **(E)**
Overview of the analysis workflow.

A

Genetics

G

Phenotype **A**
(e.g., depression)

Phenotype **B**
(e.g., brain imaging)

*Bivariate cross-trait genetic architecture
between phenotypes **A** and **B**

- Using summary-level data from different cohorts
- Numerous tools have been developed:
- Genome-wide genetic correlation
- Local genetic correlation
- ......

**Substantial logistical and computational
challenges of implementing and batch-
running these rapidly evolving tools with
thousands of publicly available phenotypes
(such as imaging biomarkers)**

B

BIGA GWAS

**BIGA GWAS
cloud computing
platform**

**Upload/query data &
submit the data analysis job**

Return analysis results

Front-end

Back-end

Share data and results

- Data options
- Tool options
- Analysis options

- Curated datasets
- Implemented tools
- Easy to scale up

Publicly available GWAS
summary statistics

C

Front-end

Data options
- Upload local data by user
- Query data from public database (e.g., GWAS Catalog and IEU OpenGWAS)

Tool options
- Genome-wise analysis (e.g., LDSC, Popcorn, and SumHer)
- Local analysis (e.g., LAVA)
- Flexible to add more tools

Analysis options
- Pairwise analysis for specific phenotypes of interest
- Massive analysis to screen numerical phenotypes

D

Back-end

Web layer
- Accept job and user data from the front-end

Logic layer
- Data processing and analysis, including control of job status, communications with databases, running algorithms, etc.

Curated
database

E

Workflow

Front-end

Task creation by user
(data, tool, and
analysis options)

Analysis job
submission

Data upload

Request data query

Back-end

Web layer
(accept job and user data
from the front-end)

Data query

Back-end

Logic layer
(data processing
and analysis)

Returning
results

Front-end

Results of job
(display and download)

Sharing (optional)

Public
GWAS data

Regular
update

Curated
database

Queue
system

Public result
browser