Uncovering Co-regulatory Modules and Gene Regulatory Networks in the Heart through Machine Learning-based Analysis of Large-scale Epigenomic Data

Naima Vahab[1,2], Tarun Bonu[3], Levin Kuhlmann[3], Mirana Ramialison[4], and Sonika Tyagi[1,2*]

[1]School of Computational Technologies, RMIT University Melbourne VIC 3000 Australia
[2]Department of Infectious Diseases, Alfred Hospital, Prahran VIC 3008 Australia
[3]Faculty of Information Technology, Monash University, Clayton VIC 3800 Australia
[4]Murdoch Children Research Institute, Melbourne VIC 3000 Australia
[*]Corresponding author: Sonika Tyagi, sonika.tyagi@rmit.edu.au

April 2023

Abstract

The availability of large scale epigenomic data from different cell types and conditions has provided valuable information to evaluate and learn features that predict co-binding of transcription factors (TF). However, previous attempts to develop models for predicting motif co-occurrence were not scalable for global analysis of any combination of motifs or cross-species predictions. Further, mapping co-regulatory modules (CRM) to their gene regulatory networks (GRN) is crucial in understanding the underlying function. Currently, there is no comprehensive pipeline to locate CRM and GRN on a large scale with speed and accuracy. In this study, we analyzed and evaluated different TF binding characteristics that would facilitate co-binding with biological significance to identify all possible clusters of co-binding TFs. We curated the UniBind database, which contains ChIP-Seq data from over 1983 samples and 232 TFs, and implemented two machine learning models to predict CRMs and potential regulatory networks they operate on. We narrowed our focus to study heart related regulatory motifs. Our findings highlight the importance of the NKX family of transcription factors in cardiac development and provide potential targets for further investigation in cardiac disease.

Key Words— CRM, Random Forest, Machine Learning, Transcription factor, Gene regulation, Epigenomics, Gene regulatory networks, Cardiac diseases, CNN

1 Introduction

Epigenomics provides insight into gene expression regulation. Among the many assays used in epigenomic studies, DNase-seq [1], ATAC-seq [2], and chromatin immunoprecipitation (ChIP) assays [3] are the most commonly used techniques. Of these listed methods, ChIP technology provides higher resolution and less noisy data which capture DNA fragments containing the position of transcription factors (TFs) binding or histone marks. Publicly accessible databases of ChIP-seq data include ENCODE [4], Unibind [5], and ChIP-Atlas [6].

Computational tools are used to identify TF binding sites (TFBSs) from ChIP-seq data, which are important for understanding gene regulation. Aligned profiles of TFBSs are called *cis*-regulatory motifs. Popular motif finding tools include ChIP-exo [7], MEME [8], and HOMER [9]. These methods focus on searching for an individual binding site at a time and do not account for cooperation between the binding sites. Additionally, Deepbind [10], FactorNet [11], and BPNet [12] are machine learning approaches based on Deep Neural Network (DNN) to discover patterns of individual motif occurrences even without any labeled sequences. Although such neural network approaches require a considerable amount of processed data and enormous training, once the model is trained, it performs motif finding tasks with high specificity [13]. Deepbind models were trained on 12 terabases of sequence data while BPNet was trained on 147,974 genomic regions. FactorNet trains a DNN on data from one or more reference cell types for which TFs of interest have been profiled, and this model can then predict motifs in other cell types. Another approach, TF-MoDISco [14] uses partially redundant information in DNN to predict a non-redundant set of motifs learned by the convolutional filters.

Since multiple TFs are involved in regulating expression of a gene, identifying clusters of TFBS are critical in elucidating gene regulation. These clusters are referred to as *cis*-regulatory modules (CRMs). CRMs usually correspond to enhancers, although there exist *cis*-regulatory DNA modules for silencers and insulators. Each module is typically 300 bp or more in length and contains on the order of ten or more binding sites for at least four unique TFs [15][16]. This is the definition of CRM we will use in the rest of the article.

A few algorithms to identify CRMs from ChIP-seq data have been published, such as MCOT [17], GEM [18][19], TACO [20], and TF-Cluster [21]. The Motifs Co-Occurrence Tool (MCOT) uses a permutation approach to find one or more suitable partner motifs for the first motif occurrence. MCOT approach relies on over-representation from a single ChIP-seq experiment and does not consider cooperative binding of multiple proteins. Furthermore, MCOT is a species-specific method and works only for three species: *Homo sapiens*, *Mus musculus*, and *Arabidopsis thaliana*. Next, TF-Cluster generates a cluster of TF motifs based on shared co-expressed genes between

multiple TFs. However, its dependency on available gene expression data limits is application in a genome-wide search. The GEM and TACO approaches were trained on known ChIP-seq data from 63 TFs and 29 TFs, respectively, to predict new motif co-occurrences. Hence, they are limited in their prediction accuracy and predict clusters of only two motifs. More recent and relevant algorithms to identify CRMs are BICORN [22], regCNN [23], dePCRM2 [24], and BPNet. BICORN uses a Bayesian-based approach along with TF-gene binding events and gene expression data as input to find a list of candidate CRMs. The regCNN algorithm extracts data from 5 different resources related to TF binding motifs, nucleosome free and variant sites, chromatin binding protein targets, histone modification information, and conservation score data, and feeds it into a CNN to predict whether a given chromosomal location contains CRM or not. Another tool, dePCRM2, extracts binding peaks from different datasets and constructs a graph with TFs as nodes. It adds an edge between two nodes if the corresponding TFs interact with each other based on the interaction information from known pathways. This algorithm uses the node perception program in *Cdlib* to cut the graph into smaller communities with 3 TFs in a CRM. In addition to these methodologies, the ChIP-Atlas database is comprised of peak calls from known ChIP-seq data and links up two ChIP-seq datasets for probable co-localized motifs. The platform provides the facility to visualize peak intensities of these co-occurring motifs. However, the data needs to be further analyzed to convert peaks into motif sequences along with their specific genomic coordinates.

All of the discussed methods either rely on known biological features to predict CRMs, and cannot provide predictions for TFs where corresponding feature datasets are ambiguous or unavailable. Further, these methods are designed to predict CRMs of short fixed lengths (up to 7). Importantly, none of the existing approaches connect the predicting of regulatory motifs to gene regulatory networks (GRN) they operate on.

GRNs describe interactions between genes and gene products, representing a collection of regulators that communicate with each other to govern gene expression levels that determine cell function [15][16]. GRNs can be used to derive novel biological hypotheses about molecular interactions and can be represented as graphs, with genes acting as nodes and inputs being proteins, such as transcription factors. Pathway models are important tools in systems biology to help understand complex biological systems made of GRNs [25] [26] [27].

In this study we have extended ChIP-seq data analysis for the prediction of CRMs. By studying TF co-binding and we developed a flexible, generic, species-agnostic method that can be used with or without prior feature generation to predict any combination of motifs. Our method allows mapping of the clusters back to GRNs in order to discover the TFs associativity and also report new TFs and genes nodes. We demonstrate application of our pipeline in cardiac case studies.

2   Methodology

2.1   Data Resources and Preprocessing

2.1.1   Human genome annotations

We used human gene annotation in gene transfer format (GTF, version GRCh.38.p7) from the ENSEMBL database [28]. Chromosome names were renamed for consistency and random and unlocalized chromosome fragments were ignored. The dataset was then filtered to prepare a dataset containing 57955 genes, which is referred to as "gene data" in the article.

2.1.2   TFBS recovered from ChIP-seq data

We chose to use the Unibind database [5], which contains data from 1983 human ChIP-seq samples generated by over 11,000 ChIP-seq experiments from 9 different species. Although we only used human data for this study, the same workflow can be applied to data from other species. We processed the data to identify binding sites for a total of 321 motifs across "gene data". For each motif, we combined multiple files of experimentally known binding sequences, removing duplicates and calling the resulting data "motif data".

To study co-occurring motifs with biological significance, we focused on the promoter region, which is about 1500 base pairs (bp) upstream of the gene start position. Based on the literature [29], we relaxed the average distance between known pairs of motifs from 21 bp to 30 bp to account for any unknown variation (Figure S1). Pairwise combinations of the binding sites for the 321 motifs in the promoter region generated a total of 4.2 million motif pairs. We further binned pairwise combinations for less than 1k bp, 1k bp to 5k bp and 5k to 10k bp to study the pattern of distance between motif pairs. We visualized the pairwise distances for less than 1500 bp and found that they had a skewed distribution with a mode of 9 bp (Figure S2), while distances greater than 1500 bp showed a uniform distribution.

We used ChIP-seq experiments to obtain positive data for motif pairs that met our constraints, while negative data was generated by considering motif pairs more than 1500 bp apart and not occurring in the promoter region of any gene. Both sub-datasets were combined and shuffled to ensure balanced data for co-occurring and non-co-occurring motif pairs

2.2 ML Model Building for TF Co-occuring Prediction

The dataset containing shuffled combinations of co-occurring and non-co-occurring pairs was used to train two models: a CNN-based deep learning model and a Random Forest Classifier (RFC) model. Motif pairs without a known protein interaction score were kept separately as the "discovery set" to test for new co-occurring pairs. The CNN model requires only TFBS sequences for prediction while the RFC model requires comprehensive data features for pairwise prediction. The CNN model simplifies initial input data, while the RFC model aids in feature selection and understanding of the most effective features for co-occurrence.

2.2.1 Using Convolutional Neural Network (CNN)

CNNs are a powerful choice for processing datasets with spatial or temporal relationships. In CNNs, input data is represented as matrices, and convolution is used to extract features. Pooling layers are used to reduce feature dimensionality and prevent overfitting. Flatten layers bridge the gap between convolution and dense layers by converting extracted features into a vector format. Other layers such as Dense and Dropout are also used. In bioinformatics, CNNs have proven useful for analyzing DNA sequences, particularly in TFBS discovery. CNNs can search for short motifs on long DNA sequences represented as matrices, allowing for efficient analysis without the need for explicit feature extraction.

To provide the biological model with additional context, 30 base pairs (bp) of flanking sequences were extracted for each binding motif sequence. Due to a limited supply of labeled examples of longer clusters, a minimum cluster size of two was enforced. The binding sequences and their corresponding flanking sequences were aligned side-by-side with padding to accommodate different motif sequence lengths, creating a matrix format. Each pair of binding sequences was converted into an image format, and labeled examples were used for training. Hyperparameters were optimized on a representative 30% subset of the entire dataset. The final model was trained on the full dataset, which was split into 60:20:20 train:validation:test sets with 600K data points in the initial training set and 150K data points in the test set (Figure 1). Validation set was used to optimize the model hyperparameters.

The final model consists of convolution layers with a number of filters ranging from 32 to 260, each with a kernel size of 4 * 4. These filters slide over the input vector to generate feature maps by applying convolution operations. The sub-sampling of the feature maps is performed using pooling layers. Here, we use a pooling layer that aggregates features by finding the maximum values in the filters. As the network progresses, the area of focus gradually reduces. Ultimately, the network can return the locations of the filtered sequences. The final model structure for the

Figure 1: CNN Architecture and pipeline diagram for TF co-binding prediction

Hyper parameter	Value Range	Final value
Number of convolution layers	3, 5, step=1	5
Number of filters in convolution layers	32, 260, step=32	filters: 32, 256, 160, 192, 32
Kernel size in convolution layers	(3, 5)	4, 4, 4, 3, 4
Activation function	['relu', 'tanh']	relu
The number of Dense layers	1 to 5	2
Number of Dense neurons	[32, 64, 128, 256, 512]	512, 128
Batch size	[64,200,600,1024,2000,3000]	3000
Drop out	[0.0,0.1,0.2,0.3,0.4,0.5]	0.5
Optimizer	['adam', 'SGD', 'rmsprop']	adam
Learning rate	[0.1, 0.01, 0.001,0.0001]	0.0001

Table 1: Hyper parameters, range, and final Value used for the CNN model

data is presented in Table 1, with a best validation accuracy of 0.92.

2.2.2   Using Random Forest Classifier (RFC)

RFC is a machine learning algorithm that creates multiple decision trees and combines their predictions to make a final classification decision. This ensemble strategy helps RFC achieve accurate predictions and better generalization. RFC also calculates the importance of each feature, and the Gini feature importance method was used to study various features of DNA sequences that drive cooperative binding of TFs.

DNA sequences contain short nucleotide patterns called "hotspots" that have biological significance. Some of these hotspots have transcription factor (TF) binding sites and exhibit a nucleotide skew with polarity at the center of the consensus motif [30]. Nucleotide skew values can be calculated to quantify these hotspots, with the AT and GC skews being common ways to indicate over- or under-abundance of nucleotides in a sequence. Additionally, DNA shape features are the other set of features that can help predict the binding of certain TF families. Researchers have identified certain sequence and structural features that create a favorable micro-environment for binding [31] [32] [33]. As a result, these features can be studied in isolation or in combination with others to predict single TF binding motifs. Pre-computed protein-protein interaction (PPI) values are available for many TFs that can also be used as predicting features. Further, binding sites interact specifically with the DNA-binding domains of a TF, and hence, can be investigated for their role in motif identification.

In total we computed 43 features available for TF co-occuring prediction and by performing a recursive feature elimination with cross-validation, we found that 10 of these features are enough for optimal model training (Figure S3). Below we provide a detailed description of the features used in our model.

Nucleotide skews

The transcription factor binding site sequences were extracted for every pairwise combination to generate AT and GC skews [Equation 1] for *binding_site1* and *binding_site2* sequences. We also concatenated the sequences of both motifs to generate a combined skew.

$$at\_skew = \frac{(a\_count - t\_count)}{(a\_count + t\_count + 1)}$$

$$gc\_skew = \frac{(g\_count - c\_count)}{(g\_count + t\_count + 1)}$$

Equation 1: AT, GC Skew calculation

DNA shape scores

A shape score is assigned to each nucleotide in a DNA sequence, and these scores can provide insights into the readout modes of DNA sequences. The DNA shape features include 13 parameters, and the sum of the respective scores for a 30 bp window centered at the motif sequence were calculated as the structural profile of the binding sites. The extraction of DNA shape scores was performed on the Monash eResearch High-Performance Computing (HPC) system using index-based Unix commands to retrieve precise scores at the motif's location.

Protein-protein interaction score (ppi_score)

The protein-protein interactions among TFs were obtained from the STRING database [26]. These interaction scores were combined and added to the dataset as a new feature called *ppi_score*.

DNA binding domain (dbd)

The DNA binding domains (DBDs) of the TF binding motifs were categorized based on pre-determined domains obtained from the Protein Data Bank [34]. These domains were identified for every motif that was under consideration.

Frequency ratio (fr)

The frequency ratio measures the importance of motif pairs out of all possible combinatorial pairs. The score is calculated using the formula shown below [Equation 2].

$$fr = \frac{count\ of\ pairs <= 30bp}{(count\ of\ all\ motif1\ sequences + count\ of\ all\ motif2\ sequences)}$$

Equation2: FR calculation

General motif features: motif1, motif2, chromosome, ng and dng

In addition to the biophysical features, we also recorded general representative features for the motifs. Since proteins select binding sites in a site-specific manner, a favorable microenvironment is required for TF binding to regulate their target genes [35]. Therefore, we extracted the nearest gene (ng) name and its chromosome name for each motif pair (*motif1* and *motif2*, *chromosome*, and *ng*). Others were distance-specific features. One was the distance between the binding sites (*dbbs*) and the distance to the nearest gene from the anchor motif (*dng*).

Target Variable: binding

The target variable is binary and is either 'co-occurring' or 'non-co-occurring'. The positive dataset is labeled as co-occurring while the negative dataset is labeled as non-co-occurring. The features extracted from the dataset will be used to train the classification model.

2.3 Clustering and generation of GRNs

As the next step, a clustering algorithm was implemented to build biologically significant CRMs from predicted co-occurring motif pairs. The algorithm employed a 'seed and extend' approach where each motif pair with *motif1* or *motif2* is recursively extended by considering either motif1 or motif2 as seed motifs. The extended motifs were selected based on predicted co-occurrence and formed a cluster. This process generated a set of CRMs located in the promoter region of a gene. Sub-clusters were removed to extract a final CRM set.

2.4 Finding gene regulatory networks (GRN)

After clustering, each gene will have multiple clusters corresponding to each TF binding. We only report clusters that have at least four different TFs and provide information such as the number of

Algorithm 1 Clustering algorithm
___
 1: **for** gene in all genes **do**
 2:      Get all predicted co-occurring pairs
 3:      Sort the combinatorial pairs by their motif1 start positions
 4:      **for** motif-pair in in all motif-pairs **do**
 5:          Add motif1 and motif2 into CRM
 6:          Extend recursively with co-occurring motifs to the left of motif1
 7:          Add found motifs to CRM
 8:          Extend recursively with co-occurring motifs to the right of motif2
 9:          Add found motifs to CRM
10:          Calculate CRM_score
11:      **end for**
12:      Add CRM and CRM_score to the list
13: **end for**
14: Remove any sub-clusters from the cluster set
___

binding sites (some TFs can have multiple binding sites), binding site span, unique motifs, and their CRM score. We assume that genes sharing common motifs within their clusters form a regulatory network, which we visualize using a graph representation. By generating multiple graphs for the same genes, we can identify new motif nodes. We extract the list of genes from these graphs and use a pathway enrichment tool to map them to known biological pathways.

3   Results

3.1   TF Feature Importance

We used all 43 sequence-based, structure-based, and interaction-based features (Figure 2) that were scaled with a MinMax scaler[36], and RFC was trained on these features with 100 decision trees, determined through hyperparameter tuning. To understand the rules of cooperative binding, we also looked at individual features and their contribution to classify a motif cluster.

The features were ranked based on their ability to distinguish between co-occurring and non-co-occurring pairs, with the most important features arranged in decreasing order of their f-scores. Highly ranked features included overrepresentation, PPI score, motif representation features, and DNA shape scores. Among the DNA shape scores, the OC2, EP, and Opening scores were found to be particularly significant based on their high f-score values. (Figure 2).

Figure 2: Feature Extraction Pipeline (a) The chromosomal dataset is preprocessed and different categories of features such as sequence-based, structural-based, protein-based and general features are extracted to input into a RF Classifier. (b) Features under each category is listed in this table (c) Once RF model is ready the features are ranked based on their importance score in order to model the predictions (see supplementary section *8.2* for more details)

3.2 Both CNN and RFC models perform well and provide their own advantages

The CNN model achieved an accuracy of 94%, while the RFC model achieved an accuracy of 88% in classification. When the *dng* and *dbbs* features were included in the training, the model achieved a very high accuracy of 99% in determining whether binding pairs were co-occurring or not. However, since these features were used to generate the training dataset, they were removed from the final model to avoid overfitting. Instead, other features were used to train the RFC model. A balanced dataset was used to ensure there was no bias in the predictions.

Both the models were evaluated using a precision-recall ROC curve, with the CNN model performing slightly better than the RFC model with an AUC value of 0.94 and 0.88, respectively. The F1 scores were also calculated, with the CNN model achieving 0.938 and the RFC model achieving 0.872. Both models were deemed to have good performance and were used for further predictions on the *discovery_set*, with the results available on the webserver.

Figure 3: A Precision-Recall Receiver Operating Curve (PR-ROC) to demonstrate difference in the area under the curve (AUC) for the models, RFC and CNN

To predict CRMs, we used the pairs predicted by the neural network as input to a clustering algorithm. The clusters with higher scores are considered to have a higher likelihood of co-occurring and expressing biological significance. Overall, a total of 200k CRMs were generated for 50762 genes, with an average of 10 clusters per gene. Each CRM is typically 300 bp in length and contains atleast 4 unique TFs which can contribute up to 10 or more binding sites. The combined cluster score (CRM score) was calculated by averaging the co-occurring scores in a cluster. We

output these potential CRMs in BED format for easy visualisation with tools such as IGV browser (Figure S4:d). We provide genome-scale annotation of human CRMs via a web-based database that can be queried with gene or motif names. An automated pipeline for predicting CRMs is available both via a web -interface and as a standalone command-line based version (Figure S5).

4 Benchmarking and cardiac CRM identification

4.1 We recovered known CRMs identified by previous tools and predicted novel instances

To compare our model with MCOT and ChIP-Atlas, we selected motif pairs detected by MCOT and scanned them in our CRMs. We found that the motifs (JUN. USF1), (RXRA, USF1), (AR, FOXA1), and (STAT6, CEBPA) were part of co-localised motif pairs, as reported by [17]. However, Unibind data did not include motif data for IKZF1, and we found a smaller number of binding sites for STAT6. As a result, we were unable to find CRMs that contained these motif pairs. For the remaining three pairs, we found them in our annotated CRMs and obtained additional motifs along with the matched motif pairs (Figure S4: a). In most cases, these pairs co-occurred with other motifs, and we calculated the average CRM size. The counts and CRM sizes are reported in the (Figure S4:a). Similar to our report, ChIP-Atlas also identified the first three pairs, but did not include the interaction between the pairs STAT6-CEBPA and RELA-IKZF1. This similarity in the reports may be due to the use of data from the same experimental ChIP-seq data.

4.2 We predict CRMs associated with heart development and diseases

To demonstrate an application of our algorithm we used a dataset of known cardiac TFs [37] to predict CRMs. Prediction and analysis of CRMs is of significance in the study of heart diseases because even minor changes in the complex network of motifs can contribute to the development of these conditions. Therefore, the CRMs can provide valuable insights into the regulatory mechanisms underlying heart diseases and assist in the development of effective diagnostic and therapeutic strategies.

Our pipeline predicts CRMs that can be filtered based on type of motifs, genes or different statistics related to them (Figure S4). Following our definition for CRM we flitered this data to report 1784 Cardiac CRMs with a cut-off score of 0.9 and containing at least four cardiac TFs. A full list of genes and their annotation is provided in the Supplementary Table S1. The TF clusters with critical role in heart function were observed in the data (Figure S4b-d). We narrowed down

Ref	Condition	Genes associated	Matched Cardiac TFs	New TFs reported by CRM Finder	Number of unique motifs	Cluster size	Span length
[38]	HTAD	ACTA2	YY1, JUN	RXRA, HNF4A, MYC	5	6	135
			JUN, TP53	RXRA, HNF4A, MYC, RXRB	6	6	135
			JUN, SMAD3	RXRA, HNF4A, MAX	5	6	135
		TGFBR1	GATA3, JUN	TEAD1, AR,ESR1	5	4	101
		TGFBR2	PPARG, REST	BCL6, MYC, NR3C1, GMEB2, STAT3, AR	8	10	263
[39]	SCAD	F11R	PPARG	ARID3A, RXRB	3	3	69
		MYO18B	REST	NR2F6, MYC, MYB, GATA1	5	5	146
		MAP2K3	GATA4, JUN	ELK3, CTCF, RELA, IRF1, FOS, USF2, TFAP2C, E2F1, RUNX1, MYC,NEURODI	13	15	361
		PCSK5	YY1,REST,RBPJ	ESR1,NEURODI, MAX, STAT3,RXRA,TRUE	9	10	244
			YY1,REST,RBPJ, CREB1	ESR1,NEURODI, RUNX1, STAT3,RXRA, TRUE	10	11	244
			YY1,REST, EOMES,RBPJ	NEURODI,RUNX1, STAT3,RXRA,TRUE	9	10	244
		CACNA1G	REST,TWIST1, SMAD4	MYC,FOS,KLF5, EGR2,TFAP2C, POU5F1, AR,NFE2L2, TCF3,RUNX1	13	16	427
			YY1,REST,RBPJ, CREB1	ESR1,NEURODI, RUNX1, STAT3,RXRA, TRUE	10	11	427
			SOX4,WT1	RXRA,KLF4, MYC,ESR1,EBF1	7	7	196
			RARA,REST, SMAD4 13	MYC,KLF5, EGR2,TFAP2C, POU5F1,AR, NFE2L2,TCF3, RUNX1,PBX3	13	15	427

Ref	Condition	Genes associated	Matched Cardiac Tfs	New Tfs reported by CRM Finder	Number of unique motifs	Cluster size	Span length
[40]	AVB/BB	ID2	HIF1A,TP53	TFAP2C, MYC	4	4	89
	AVN	TBX2	JUN, REST	ESR1,NRF1,TP63,CTCF	6	9	247
[41]	CYTO SKELE-TAL DYS-FUNCTION	TLN1	EOMES, GATA4,SRF	STAT1, MYC, RXRA,ZNF143	7	7	170
			EOMES,GATA4, SRF	STAT1, MYC, RXRA,ZNF143	7	7	170
	EXTRA CEL-LU-LAR MA-TRIX DYS-FUNCTION	FMR1	SMAD3, SMAD4	NFE2, RXRA, EGR3, ESR1, CTCF, SP1, TFAP2C, ETV1, MYC, STAT3	12	14	472
		ECM1	GATA4,JUN	RXRA, ETS1, RELA, TFAP2C, E2F6	7	7	132
[42]	hcCHD	NF1	JUN, REST, PPARG, GATA3	ESR1, E2F1,STAT1, CTCF, MYCN,NFIC, TFAP2C	11	12	330
		EHD1	GRHL2, YY1	ZNF263,SP1,SPI1, AR,ESR1,SP2, TFAP2A,MYC, RUNX1,TFAP4, CTCF, RELB,TCF3	15	15	483

Table 2: The outputs generated by CRM Finder are matched against existing relevant published work to discover new TFs associated with cardiac conditions

our results to focus on cardiac TFs associated with genes implicated in a cardiac conditions such as HTAD, SCAD, AVB, AVN, hcCHD, and cardiac dysfunctions (Table 2). Our analysis identified both known and novel TFs. For instance, F11R, a high-priority genetic candidate for SCAD reported in our previous work [39], has a known cardiac TF called PPARG. Our approach enabled us to predict new TFs such as ARID3A and RXRB as potential regulators of SCAD (Table 2). However, the cluster size for this gene falls below our minimum cluster cut-off of four, and prediction of complete clusters may require further analysis of heart specific datasets. Additional exploration revealed that the average cluster size of cardiac CRMs is between 10 and 11 genes. The genes with large cluster size include ZCWPW2, ADAL, CDK13, APAF1, and RP11. Moreover, we observed that the REST:JUN, JUN:TP53, and RARA:JUN TF pairs were dominant pairs of cardiac CRMs (Figure 4). Mutations in the JUN and TP53 cardiac motifs have been linked to cardiac failure [43] [44].

Figure 4: The Cardiac CRMs generated were analysed to get a comprehensive view on the result. As the first step, a filter is applied to select CRMs of length ¡=4 (a) This shows how many clusters are reported under each cluster size and we find most of the clusters have size 10 or 11.(b) The most frequent cluster size after considering only unique motifs was found to be between 11 and 15 (c) The genes which have most number of TFs are depicted here (d) Frequent co-occurring cardiac TFs are plotted here

4.3   Cardiac gene regulatory networks

The role of the NKX family of TFs in cardiac development [37] was investigated by examining a subset of cardiac CRMs that contained at least one NKX TF binding site. Network analysis (Figure 5a) and K-mean clustering of genes containing these TFs revealed three interaction clusters (reported as red, blue, and green in the Table S2), and the top cluster (red) from here displayed significant enrichment for genes associated with expression, diseases, and biological pathways that are specific to cardiac tissues (Figure 5b). These findings suggest that the NKX TF family may play an important role in regulating the cardiac gene regulatory network, and highlight potential targets for further investigation in cardiac development and disease.

Furthermore, to determine the efficacy of our pipeline, we investigated whether it contained the genes networks as reported by Kiran Musunuru et al [38][45]. Our analysis revealed that we were able to identify a subset of genes with strong evidence for HTAD (heritable thoracic aortic aneurysm or dissection) in our pipeline results. We then extracted network of various TFs that were identified for all of these genes, as shown in the Figure 6.

5   Data and Software Availability

The novel CRMs that our pipeline generates can be accessed through our web-hosted database `https://bioinformaticslab.erc.monash.edu/CRMdatabase`; see Figure S5). Our pipeline implements the latest software and distributed environment strategies, allowing for the efficient processing of large genomic datasets. The source code for our pipeline is readily available for public use (`https://gitlab.com/tyagilab/crc_finder`).

6   Conclusion

Our study offers a comprehensive survey of current CRM-finding approaches and addresses significant gaps in the field. We introduce a novel pipeline for predicting putative CRMs from identified DNA motifs, which can facilitate the study of gene regulation and motif interactions. Our pipeline incorporates both RFC and CNN machine learning models for predicting TF co-occurrence and clustering to identify new CRMs. We also provide a complete annotation of 223 human motifs (excluding the sites used in model training) from the UniBind database, which is accessible through our user-friendly web interface. Our pipeline is highly versatile and can be run via our web server or a command-line interface.

(a)

(b)

Figure 5: Cardiac CRM analysis using the STRING app [26]: (a) Interaction network of CRMs containing one of NKX family TFs. (b) The enrichment analysis of the NKX-TF red cluster shows strong association with heart disorders.

Figure 6: GRNs reported by our pipeline: (a) Depicts a regulatory network where green nodes represent TFs and other colored nodes represent genes. Here, genes MYO18B, MAP2K3, ECM1,TBX2 presented CRMs with common TFs. MYO18B, MAP2K3 are associated with SCAD whereas, genes ECM1, TBX2 are responsible for arterial matrix dysfunction and cardiac networks development. [40] [41] (b) Here, genes TGFBR2, TGFBR1, LOX, MYLK have common TFs and were previously reported to be associated with HTAD condition [38]

This work identified several important factors in predicting TFBS cooperativity, including TFBS overrepresentation, PPI score, motif representation features, and DNA shape scores. In particular, the OC2, EP, and Opening scores (shape features) were found to be highly significant. Using this pipeline, we were able to discover novel cardiac CRMs and GRNs that are associated with cardiac development and disease pathways. The versatility of this pipeline allows it to be applied to a wide range of biological systems and datasets beyond the cardiac development and disease pathways studied in this work. By leveraging the factors identified for predicting TFBS cooperativity, this approach has the potential to uncover novel regulatory pathways involved in various disease and developmental processes. Our approach is species-agnostic and highly flexible meaning it could be extended to other large-scale datasets from similar assays, such as ATAC-seq, ChIP-HiC, or DNAse-seq.

7 Acknowledgements

ST acknowledges support from Australian Academy of Science, Australian Women Research Success Grant at Monash University. We acknowledge the helpful discussions and compute resources from the Monash eResearch Platform and the MASSIVE HPC facility (`www.massive.org.au`). We thank Yashpal Ramakrishanaiah and Tyrone Chen for their feedback and help in packagaing the software and setting up the webserver.

References

[1] Crawford GE. Song L. "DNase-seq: a high-resolution technique for mapping active gene regulatory elements across the genome from mammalian cells". In: *pdb.prot5384* (2010).

[2] Chang HY et. al. Buenrostro JD Wu B. "ATAC-seq: A Method for Assaying Chromatin Accessibility Genome-Wide". In: *PMC4374986* (2015).

[3] Endre Barta. "Command line analysis of ChIP-seq results". In: *EMBnet. journal* 17.1 (2011), pp. 13–17.

[4] The ENCODE Project Consortium. "An integrated encyclopedia of DNA elements in the human genome". In: *Nature* 489 (2012), pp. 57–74.

[5] Rafael Riudavets Puig et al. "UniBind: maps of high-confidence direct TF-DNA interactions across nine species". In: *bioRxiv* (2020).

[6] Shinya Oki et al. "Ch IP-Atlas: a data-mining suite powered by full integration of public Ch IP-seq data". In: *EMBO reports* 19.12 (2018), e46255.

[7] Lai et. al. Rossi M.J. "Simplified ChIP-exo assays". In: *Nat Commun* 9 (2018).

[8] Timothy L Bailey et al. "The MEME suite". In: *Nucleic acids research* 43.W1 (2015), W39–W49.

[9] Chen et. al. Zhang F. "HOMER: a human organ-specific molecular electronic repository". In: *BMC Bioinformatics* 12 (2011).

[10] May D. Wang Hamid Reza Hassanzadeh. "DeeperBind: Enhancing Prediction of Sequence Specificities of DNA Binding Proteins". In: *arxiv* 12 (2016).

[11] Xie X Quang D. "FactorNet: A deep learning framework for predicting cell type specific transcription factor binding from nucleotide-resolution sequential data." In: *PMC* (2019).

[12] Avsec et al. "Base-resolution models of transcription-factor binding reveal soft motif syntax". In: *Nat Genet* 53 (2021), pp. 354–366.

[13] Gökcen Eraslan et al. "Deep learning: new computational modelling techniques for genomics". In: *Nature Reviews Genetics* 20.7 (2019), pp. 389–403.

[14] Avanti Shrikumar et al. "TF-MoDISco v0.4.4.2-alpha: Technical Note". In: *CoRR* abs/1811.00416 (2018). arXiv: 1811.00416. URL: http://arxiv.org/abs/1811.00416.

[15] Levine M. Small S Blair A. "Regulation of even-skipped stripe 2 in the Drosophila embryo". In: *PMC* 11 (1992), pp. 4047–57.

[16] Michael Levine and Eric H. Davidson. "Gene regulatory networks for development". In: *PubMed Central, Gene Regulatory Networks Special FeatureFrom the Cover* 102 (2005), pp. 4936–4942.

[17] Victor Levitsky et al. "A single ChIP-seq dataset is sufficient for comprehensive analysis of motifs co-occurrence with MCOT package". In: *Nucleic acids research* 47.21 (2019), e139–e139.

[18] Yuchun Guo, Shaun Mahony, and David K Gifford. "High resolution genome wide binding event finding and motif discovery reveals transcription factor spatial binding constraints". In: *PLoS Comput Biol* 8.8 (2012), e1002638.

[19] Kenneth E Westerman and Duy T et. al Pham. "GEM: scalable and flexible gene–environment interaction analysis in millions of samples". In: *Bioinformatics* 37.20 (May 2021), pp. 3514–3520. ISSN: 1367-4803. DOI: 10.1093/bioinformatics/btab223. eprint: https://academic.oup.com/bioinformatics/article-pdf/37/20/3514/40854026/btab223.pdf. URL: https://doi.org/10.1093/bioinformatics/btab223.

[20] Aleksander Jankowski, Shyam Prabhakar, and Jerzy Tiuryn. "TACO: a general-purpose tool for predicting cell-type–specific transcription factor dimers". In: *BMC genomics* 15.1 (2014), pp. 1–12.

[21] Jeff Nie et al. "TF-Cluster: a pipeline for identifying functionally coordinated transcription factors via network decomposition of the shared coexpression connectivity matrix (SCCM)". In: *BMC systems biology* 5.1 (2011), pp. 1–19.

[22] Chen et al. "BICORN: An R package for integrative inference of de novo cis-regulatory modules". In: *Sci Rep* (2020).

[23] Tzu-Hsien Yang, Ya-Chiao Yang, and Kai-Chi Tu. "regCNN: identifying Drosophila genome-wide cis-regulatory modules via integrating the local patterns in epigenetic marks and transcription factor binding motifs". In: *Computational and Structural Biotechnology Journal* 20 (2022), pp. 296–308. ISSN: 2001-0370. DOI: `https://doi.org/10.1016/j.csbj.2021.12.015`. URL: `https://www.sciencedirect.com/science/article/pii/S2001037021005249`.

[24] Pengyu Ni and Zhengchang Su. "Accurate prediction of cis-regulatory modules reveals a prevalent regulatory genome of humans". In: *NAR Genomics and Bioinformatics* 3.2 (June 2021). lqab052. ISSN: 2631-9268. DOI: `10.1093/nargab/lqab052`. eprint: `https://academic.oup.com/nargab/article-pdf/3/2/lqab052/38681095/lqab052.pdf`. URL: `https://doi.org/10.1093/nargab/lqab052`.

[25] et al. Fabregat A. "The Reactome Pathway Knowledgebase". In: *Nucleic Acids Res.* 46 (2018), pp. D649–D655. DOI: `10.1093/nar/gkx1132`.

[26] Andrea Franceschini et al. "STRING v9. 1: protein-protein interaction networks, with increased coverage and integration". In: *Nucleic acids research* 41.D1 (2012), pp. D808–D815.

[27] Thomas P. Mi H. "PANTHER pathway: an ontology-based pathway database coupled with data analysis tools." In: *Methods Mol Biol.* 563 (2009), pp. 123–40. DOI: `10.1007/978-1-60761-175-2_7`.

[28] Tim Hubbard and Barker et. al. "The Ensembl genome database project". In: *Nucleic acids research* 30.1 (2002), pp. 38–41.

[29] Jeff Vierstra et al. "Global reference mapping of human transcription factor footprints". In: *Nature* 583 (2020), pp. 729–736.

[30] Fatima Smagulova et al. "Genome-wide analysis reveals novel molecular features of mouse recombination hotspots". In: *In: Nature* 472 (2011), pp. 375–378.

[31] Sachi Inukai et al. "Transcription factor–DNA binding: be- yond binding site motifs". In: *Current opinion in genetics development* 43 (2017), pp. 110–119.

[32] Lin Yang et al. "TFBSshape: a motif database for DNA shape features of transcription factor binding sites". In: *Nucleic acids research* 42 (2014), pp. D148–D155.

[33] Tsu-Pei Chiu et al. "TFBSshape: an expanded motif database for DNA shape features of transcription factor binding sites". In: *Nucleic acids research* 48 (2020), pp. D246–D255.

[34] Peter W Rose et al. "The RCSB protein data bank: integrative view of protein, gene and 3D structural information". In: *Nucleic acids research* (2016), gkw1000.

[35] Allan Haldane, Michael Manhart, and Alexandre V Morozov. "Biophysical fitness landscapes for transcription factor binding sites". In: *PLoS Comput Biol* 10.7 (2014), e1003683.

[36] MultiMedia LLC. *How to Use StandardScaler and MinMaxScaler Transforms in Python.* 2020. URL: https://machinelearningmastery.com/standardscaler-and-minmaxscaler-transforms-in-python/ (visited on 09/30/2020).

[37] Akriti Varshney et al. "Human Cardiac Transcription Factor Networks". In: (2021).

[38] Kiran Musunuru et al. "Genetic Testing for Inherited Cardiovascular Diseases: A Scientific Statement From the American Heart Association". In: *AHA Journals, Genomic and Precision Medicine* (2020).

[39] James K et al. "The Intercellular Tight Junction and Spontaneous Coronary Artery Dissection". In: *Journal of the American College of Cardiology* 72.14 (2018), pp. 1752–1753. DOI: 10.1016/j.jacc.2018.07.040. eprint: https://www.jacc.org/doi/pdf/10.1016/j.jacc.2018.07.040. URL: https://www.jacc.org/doi/abs/10.1016/j.jacc.2018.07.040.

[40] Nikhil V Munsh. "Gene Regulatory Networks in Cardiac Conduction System Development". In: *Circulation Research* 110 (2012), pp. 1525–1537.

[41] Bax et al. "Arterial dissections: Common features and new perspectives". In: *Frontiers in Cardiovascular Medicine* 9 (2022). ISSN: 2297-055X. DOI: 10.3389/fcvm.2022.1055862. URL: https://www.frontiersin.org/articles/10.3389/fcvm.2022.1055862.

[42] Alankarage D et al. "Identification of clinically actionable variants from genome sequencing of families with congenital heart disease". In: *Genet Med* 21.5 (2019), pp. 1111–1120. DOI: 10.1038/s41436-018-0296-x.

[43] Robin Canac et al. "Deciphering transcriptional networks during human cardiac development". In: *https://doi.org/10.1101/2022.08.11.503560* 102 (2022).

[44] Akriti Varshney et al. "Human Cardiac Transcription Factor Networks". In: *sciencedirect, Systems Medicine Integrative, Qualitative and Computational Approaches* 2 (2021), pp. 429–453.

[45] Spielmann et al. "Extensive identification of genes involved in congenital and structural heart disorders and cardiomyopathy". In: *Nat Cardiovasc Res* 1 (2022), pp. 157–173.

[46] Sachi Inukai, Kian Hong Kock, and Martha L Bulyk. "Transcription factor–DNA binding: beyond binding site motifs". In: *Current opinion in genetics & development* 43 (2017), pp. 110–119.

[47] Marius Gheorghe and Geir Kjetil et. al Sandve. "A map of direct TF–DNA interactions in the human genome". In: *Nucleic acids research* 47.4 (2019), e21–e21.

[48] Shaun Mahony and B Franklin Pugh. "Protein–DNA binding in high-resolution". In: *Critical reviews in biochemistry and molecular biology* 50.4 (2015), pp. 269–283.

[49] Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. "Learning Important Features Through Propagating Activation Differences". In: *CoRR* abs/1704.02685 (2017). arXiv: 1704.02685. URL: http://arxiv.org/abs/1704.02685.

[50] Laura O'Hara et al. "Modelling the Structure and Dynamics of Biological Pathways". In: *PubMed Central, PLOS Biology* 14 (2016).

[51] Benjamin Haibe-Kains Frank Emmert-Streib Matthias Dehmer2. "Gene regulatory networks and their applications: understanding biological and medical problems in terms of networks". In: *Frontiers in Cell and Developmental Biology* (2014).

[52] Yumin Nie and Shu et. al. "Cooperative binding of transcription factors in the human genome". In: *Genomics* 112.5 (2020), pp. 3427–3434.

[53] Vierstra et. al. "Global reference mapping of human transcription factor footprints". In: *Nature* 583.7818 (2020), pp. 729–736.

[54] Mahesh Pal. "Random forest classifier for remote sensing classification". In: *International journal of remote sensing* 26.1 (2005), pp. 217–222.

[55] Chiu et. al. "TFBSshape: an expanded motif database for DNA shape features of transcription factor binding sites". In: *Nucleic acids research* 48.D1 (2020), pp. D246–D255.

[56] Tianyin Zhou et al. "DNAshape: a method for the high-throughput prediction of DNA structural features on a genomic scale". In: *Nucleic acids research* 41.W1 (2013), W56–W62.

[57] Lin Yang et al. "TFBSshape: a motif database for DNA shape features of transcription factor binding sites". In: *Nucleic acids research* 42.D1 (2014), pp. D148–D155.

[58] Sukhdeep Kaur Gitanjali Tandon Sunita Yadav. "Pathway modeling and simulation analysis Author links open overlay panel". In: *sciencedirect, Bioinformatics - Methods and Applications* (2022), pp. 409–423.

[59] Babak Alipanahi et al. "Predicting the sequence specificities of DNA-and RNA-binding proteins by deep learning". In: *Nature biotechnology* 33.8 (2015), pp. 831–838.

[60] Žiga Avsec et al. "Deep learning at base-resolution reveals motif syntax of the cis-regulatory code". In: *BioRxiv* (2019), p. 737981.

[61] Jan Zrimec et al. "Deep learning suggests that gene expression is encoded in all parts of a co-evolving interacting gene regulatory structure". In: *Nature communications* 11.1 (2020), pp. 1–16.

[62] Zinzen et al. "Combinatorial binding predicts spatio-temporal cis-regulatory activity". In: *Nature* 462 (2009), pp. 65–70.

[63] Sumantra et. al. Chatterjee. "Gene regulatory elements, major drivers of human disease". In: *Annual review of genomics and human genetics* 18 ().

8 Supplementary Data

8.1 Co-binding distance

Figure S1: Generally millions of binding sites for a TF are found but only a few thousands are bound. GATA1 and TAL1 are a known genome-wide co-occurring motif pair. This pair is known to cooperate to regulate erythroid development across thousands of genomic locations on the DNA

.

Figure S2: Distance between binding sites ($dbbs$) in the promoter region shows a mode at 9 bp. Previously, an average of 21 bp distance was observed [29]. We relaxed this distance to be 30 bp in our methods to allow for any unknown variations.

8.2 Feature Ranking

To calculate and quantify the feature importance, we performed univariate feature importance tests. These tests involved the Chi-square test and one-way ANOVA test (f-score). These univariate methods do not consider any classification algorithm for feature importance. Chi- square is a goodness of fit test which is performed to check if the sample belongs to a population which returns a chi-square score. The f-score indicates the difference between the distributions of values between the classes. The chi-square (χ^2) and the f-scores (F) were calculated for each of the features against the target variable with the following formulae.

$$\chi_c{}^2 = \Sigma \frac{O_i - E_i{}^2}{E_i}$$

$$F = \frac{MeanSquare_{class}}{MeanSquare_{error}}$$

Recursive Feature Elimination with Cross-Validation was performed to select the most important features for data classification. This technique involves the iterative elimination of the least important feature and the importance scores are recalculated. As observed in the (Figure S3), 9 features were sufficient for optimal model training.

8.3 Predictions of Cardiac CRMs and benchmarking

We filtered cardiac CRMs of atleast 1 unique cardiac TFs with clustering score greater than 0.9 which resulted in approximately 150K CRMs (Figure [**fig:validation1**]). The gene list generated from the predicted cardiac CRMs was analysed. Their gene type, GO term name and annotation can be found in the Table S1.

[Table S1: filename=Cardiac_CRM_genes_and_types.txt]

Table S2: filename=NKX-cluster-analysis.xlsx

8.4 CRM Website

Using the web application, users can extract CRMs for specific genes. We also provide options to set criteria like extract using specific motifs or known PPI score of TFs and cluster score cut off. The results can be downloaded as CSV

Figure S3: Recursive Feature Elimination with Cross-Validation (RFECV)

Figure S4: (a) We evaluated the accuracy of our predictions by comparing them to data from MCOT and ChIP Atlas. The validation results are presented. (b) We examined the co-occurrence of TP53, a TF with important role in the functioning of heart. The results are depicted in a Venn diagram, where CREB1 and JUN were the most common TFs forming clusters with TP53. (c) A sample output shows the genes with at least one cardiac TFs listed in their clusters. (d) IGV window showing cardiac TFs TP53, JUN, HIFA1, SMAD4, SPI1, E2F1 with a CRM score of 0.92.

Figure S5: CRM finder and an annotated database of human motifs is accessible via a Webserver