Bayesian updating for self-assessment explains social dominance and winner-loser effects

Abstract

In animal contests, winners of previous contests often keep winning and losers keep losing.

These so-called 'winner-loser effects', can have dramatic impacts on future contests and seem

to play a key role in stabilizing the resulting dominance hierarchies. However, the cognitive

mechanisms through which these effects occur are unknown. Winner-loser effects are often

accompanied by a change in the aggressiveness of experienced individuals, which suggests

individuals may be adjusting their self-assessment of their abilities based on this newly gained

information. This updating of a prior estimate is ideally described by Bayesian updating. Here

we show that Bayesian updating provides a mechanism to explain why winner-loser effects

occur and makes clear predictions for the behavior of individuals and social groups. We

implement an agent-based model to compare Bayesian updating to other possible strategies.

We first show that Bayesian updating reproduces empirical results of the behavior of

individuals and groups in dominance interactions. We then provide a series of testable

predictions that can be used in future empirical work to distinguish Bayesian updating from

other potential mechanisms. Our work demonstrates the utility of Bayesian updating as a

mechanism to explain and ultimately, predict changes in behavior after salient social

experiences.

Introduction

Nearly all social groups have measurable dominance hierarchies (Ellis 1995; Shizuka and

McDonald 2015; Strauss et al. 2022). These hierarchies can be defined by consistent imbalances

in pair-wise aggression and subordination (Rowell 1974; Drews 1993). In the simplest cases,

dominance relationships are a measure of contest ability, with the stronger or otherwise more

competitive individuals consistently winning over weaker ones. If all outcomes were

determined entirely by the intrinsic ability to win a fight (Parker 1974) then dominance

hierarchies would be perfectly linear and predictable. And while dominance hierarchies are

typically very stable and more linear than would be predicted by chance (Jackson and

Winnegrad 1988; Tibbetts et al. 2022), dominance outcomes, both in terms of individual

contests and the overall positioning of particular individuals within the hierarchy, are often

unpredictable (Landau 1951; Chase et al. 2002, 2022). This is because contest outcomes can be

stochastic (reviewed in Strauss et al. 2022), and are influenced by a combination of factors,

including motivation (Arnott and Elwood 2008; O'Connor et al. 2015), strategy (Parker 1974),

individual state (Goetz et al. 2014; Li et al. 2014; Holekamp and Strauss 2016), and perhaps

most importantly, social feedback and previous experiences (Chase et al. 2002).). This

dichotomy—often unpredictable but unusually stable outcomes—highlights the gap between

our current understanding of the mechanisms of dominance and the reality of natural systems.

Despite the importance of social dominance for individual and group outcomes (Dewsbury

1988; Snyder-Mackler et al. 2020; Simons et al. 2022), we still lack models that can predict the

formation of dominance hierarchies over time by incorporating the additional social

mechanisms that reinforce or even supersede differences in intrinsic contest ability (Chase et al.

2002; Tibbetts et al. 2022).

Winner and loser effects may be one of these social mechanisms governing the formation of

dominance hierarchies (Dugatkin 1997; Bonabeau et al. 1999; Hemelrijk 2002). The winner

effect is a widely observed phenomenon where success in one contest leads to increased

probability of success in subsequent contests, while the loser effect describes how defeats

often lead to more defeats (reviewed in Hsu et al. 2006). Although these two phenomena are

tightly related, prior work shows that there is variation in the relative strength of winner and

loser effects, and winner effects can even occur without loser effects (Goubault and

Decuignière 2012), or vice versa (McDonald et al. 1968). Overall, the most typical phenomenon

is for individuals to display both winner and loser effects, with the loser effect being relatively

stronger (reviewed in Hsu et al. 2006; Rutte et al. 2006).

While in some contexts, winner and loser effects could be explained by changes in intrinsic,

individual ability or opponent behavior, experiments tend to control for these effects such that

changes in contest outcomes appear to be largely driven by a change in the focal individual's

aggressive behavior (reviewed in Hsu, 2006). This change in aggression suggests that individuals

may be modifying their self-assessment of their chances of winning in future contests based on

the outcome of their current contest (Rutte et al. 2006). Understanding what motivates this

change in behavior and how changes in self-assessment may occur is central to our

understanding of winner-loser effects and dominance formation.

Most of our biological understanding of winner-loser effects relates to short-term endocrine-mediated shifts in behavior and the accompanying neurophysiology (reviewed in Zhou et al, 2018). For example, several studies in rodents showed that a boost in testosterone following a contest is sufficient to induce winner effects (Fuxjager et al. 2011*a*), however blocking testosterone merely attenuated the winner effect (Fuxjager et al. 2011*b*). Furthermore, winner effects are mediated by social and environmental context (Fuxjager and Marler 2010; Fuxjager et al. 2011*b*), independent of the effects of testosterone, while other studies have pointed to additional contributions from dopamine (Becker and Marler 2015; Ibuchi and Nagayama 2021) and serotonin (Winberg and Thörnqvist 2016; Hu et al. 2020).

Despite these putative mechanisms, our general understanding of the drivers of post-contest behavior remains limited, and even these mechanisms primarily explain short term winner-loser effects (but see Cordero and Sandi 2007; Winberg and Thörnqvist 2016). While winner-loser effects are often short-lived in experimental tests—generally lasting from mere minutes to days (Chase et al. 1994; Johnsson 1997) or until some external disruption occurs (Stevenson et al. 2000)—some studies have found persistent winner/loser effects influencing behavior up to months after the initial conflict (Lan and Hsu 2011; Laskowski et al. 2016; Momohara et al. 2016). A clear mechanistic model of the cognitive changes that occur following contests could help reconcile these seemingly disparate results and allow us to better predict how winner-loser effects determine later contest outcomes.

Early theoretical work regarding winner-loser effects primarily focused on mechanistic

investigations of whether feedback from winner-loser effects explained the observed linearity

of dominance hierarchies (reviewed in Lindquist and Chase 2009; Mesterton-Gibbons et al.

2016)). These models (termed Type I by Masterton-Gibbons et al, 2016) generally used a linear

shift in contest ability, in which after a contest, an individual's intrinsic win potential was

modified, whether by some fixed amount (Bonabeau et al. 1996), as a proportion of prior ability

(Dugatkin 1997), or as a function of the difference between individual and opponent ability

(Hemelrijk 2000; Hock and Huber 2006). This "ability-feedback" approach continues to be used

in more recent models (e.g. Kura et al. 2016; Hickey and Davidsen 2019). All of these models

treat winner-loser effects as a change in intrinsic contest ability, and cannot account for winner-

loser effects where intrinsic ability is unchanged. While these models are useful in exploring the

impacts of (intrinsic) winner-loser effects on the linearity of networks and provide an important

foundation on which subsequent work expanded, we need a model which could isolate the

effect of self-assessment per se.

Another class of models (termed Type-II by Masterton-Gibbons et al, 2016), focuses on how the

strategic rules used in social contests could give rise to winner-loser effects. These models tend

to be more evolutionarily minded and rooted in game theory, in terms of finding the optimal

and/or stable strategies for social contests. There are a range of decision rules used, for

example matching behavior to past probability of winning (Van Doorn et al. 2003; Fawcett and

Johnstone 2010), or by using an actor critic model match expected reward with contest

outcome (Leimar 2021). These models provide clear and even plausible mechanisms to explain

winner-loser effects and other features of dominance hierarchies, however these models either

do not explicitly model self-assessment, or if they do, they leave it unchanged. As with the

"ability-shift" models already mentioned, updating a decision rule is a different model than

modifying an estimated self-assessment, even if the behavioral output may be similar. These

decision rules essentially act as heuristics to capture an implied shift in self-assessed probability

of winning. To our knowledge, only one model (Mesterton-Gibbons 1999), explicitly treats

winner-loser effects as a change in self-assessment, but this is limited to three possible

estimates: [Naïve, post-win, post-loss], and intrinsic ability only factors into contest cost, not

contest outcome. Although these "strategy-based" models are very powerful, none of them are

designed to explore whether winner-loser effects and dominance formation can be explained

solely by agents refining their self-assessment of their intrinsic ability.

Given our goal to explore winner-loser effects as a process of modifying individual's estimates,

Bayesian updating is the most natural framework to use. In brief, Bayesian updating provides a

precise mathematical formula to modify an existing estimate of the state of the world based on

new information (McNamara et al. 2006). It thus operates entirely on changes in individual

assessment. Existing empirical research suggests that many animals use Bayesian processes to

make decisions in other contexts (Luttbeg 1996; McNamara et al. 2006; Olsson 2006; Okasha

2013). Despite being ideally suited to calculate self-assessment of individual ability following a

contest (as noted by Whitehouse 1997), to our knowledge, there is no model that treats

winner-loser effects as a process of Bayesian learning. Admittedly, Bayesian modeling can be

challenging to implement (as noted by McNamara and Leimar 2020), particularly as the

complexity of the information space increases, however understanding the specific predictions

of changing self-assessments using Bayesian updating could provide important insight into the

actual strategies used by different animal groups. Given the potential power of this hypothesis,

it is important to identify the predictions of a Bayesian model and understand how we might

distinguish Bayesian updating from alternative mechanisms.

Here, we present an agent-based model of winner-loser effects—and dominance formation

generally—as a process of Bayesian updating. In brief, individual agents with self-assessed

contest ability compete to win social contests, after which each agent uses Bayesian updating

to modify their estimate of their own contest ability, which they then use to determine how

much to invest in future contests. The purposes of this model were 1) to explore the features

and limitations of Bayesian updating as it relates to winner-loser effects, thereby showing

whether such a framework is plausible; and 2) to identify testable predictions that could

empirically distinguish Bayesian updating from alternative mechanisms of modifying self-

assessments. To first show whether Bayesian updating recreates known empirical features of

dominance behavior, we identified specific features of winner-effects, i.e., the observed

recency biases of winner/loser effects and the higher relative strength of loser effects as shown

in the empirical literature (Bakker et al. 1989; Chase et al. 1994), as well the tendency of

dominance hierarchies to be linear and stable. To achieve our second goal of identifying

testable predictions, we focus on measurable attributes of fights—such as fight intensity or

duration—and compare these measures across staged contests where the agents use either

Bayesian updating or other updating mechanisms. For this comparison, we model linear shifts

in (self-assessed) contest ability, similar to (Dugatkin 1997; Bonabeau et al. 1999), and a fixed

estimate, in which no change in self-assessment occurs. We show that Bayesian updating can

reconcile disparate empirical observations of the attributes of winner/loser effects, while laying

out clear, testable predictions that can be used in future experiments to identify the

mechanisms by which dominance is established.

Figure 1: **A**, Individuals with fixed size (unknown to self) and an estimated self-assessment are paired. **B**,

each individual estimates their own and opponent's size to determine their effort, based on their

estimated probability of winning. **C (bottom right)**, the size and effort of each agent determines their

relative wagers. The relative wager of the smaller individual determines the probability of winning

(calculated as the probability of an upset by the underdog in a given contest). **D (bottom left)**, Based on

this probabilistic outcome, agents update their self-assessment, multiplying their prior assessment by

the calculated likelihood of the observed outcome.

<u>General approach</u>

We envision a scenario where a group of animals compete for dominance in war of attrition

contests (Maynard Smith 1974). As depicted in figure 1, we imagine these agents as fish of

varying sizes, but individual agents could represent any species (mice, humans, etc.) competing

in a social group. Our model consists of four steps, described graphically in figure 1. First, we

generate a group of agents with random (normally distributed) intrinsic ability and imperfect

self-assessments of that ability (figure 1A). For simplicity, we will refer to the intrinsic ability as

"*size*", although in most natural systems other factors also contribute. Second, these agents are

randomly paired and allowed to interact. In each contest, they select their effort, based on their

estimated probability of winning, which is based on their existing self-assessment of their size

and their assessment of opponent size (figure 1B). Third, contest outcomes are determined

probabilistically based the relative size and effort of each participant (figure 1C, bottom-right).

Finally, following the contest, each agent updates their estimate (i.e. their self-assessment)

based on their prior estimate of size and their estimated likelihood of the observed outcome

(figure 1D, bottom-left). This process is then repeated. Each step of the model is described in

detail below.

Table 1 – Overview of parameters and their default values

Symbol	Default	Range	Explanation
$x :$ $(x, x_i, x_o, \bar{x}_i)$	Random	$1 \leq x \leq 100$	Size of an individual. x_i represents actual size for individual i, while x_o is the actual size of opponent. $\bar{x}$ denotes an estimated size
μ_x	50	$1 \leq x \leq 100$	The mean of the population from which individuals are drawn
σ_x	10	$0 \leq \sigma_x < \infty$	Standard deviation of population from which individuals are drawn. At $\sigma = \infty$, uniform distribution is used.
$v :$ (v, v_i, v_o)	None	$0 \leq v \leq 1$	Effort, i.e., the amount of time/energy invested in a contest. As with size, subscripts distinguish effort by the focal individual v_i from their opponent's, v_o
$w :$ (w, w, w)	None	$0 \leq w \leq 1$	Wager, or contest performance, a combination of the agent's size and selected effort. This could also be thought of as work, i.e., the amount of energy imposed on opponent.
s	0.7	$0 \leq s < 1$	Relative importance of size vs. effort, acts as a simple multiplier when summing size and effort.
l	6.3*	$0 \leq l < \infty$	Relative wager dampener, essentially the importance of luck, acting as an exponent on relative wager, such that as l increases, the probability of an upsets decreases
σ_a	20	$0 \leq \sigma_a < \infty$	*self-assessment error*, the accuracy of individuals' starting guesses for their self-assessment.
σ_c	3.1*	$0 \leq \sigma_c < \infty$	*opponent-assessment error*, the accuracy of individuals when guessing the size of opponents prior to contests
$P(\theta)$	-	-	Used to denote the prior, an estimated, discrete distribution of the probability of being some size.

* For all unbounded parameters, we use a tangent scaling function for ease of use (see Supplemental), which is why these

default parameters are arbitrarily specific.

Generation of agents

In order to model the development of self-assessment, we generate agents with some intrinsic

win potential, called *size*, usually drawn from a truncated normal distribution between 1 and

100 (arbitrary units), such that

$$x_i \sim N(\mu_x, \sigma_x), \ \ where \ x_i \in [1,100] \tag{1}$$

195   Each agent has an estimate of their own size, $\bar{x}$, itself drawn from a truncated normal

196   distribution centered around their actual size:

$$\bar{x}_i \sim N(x_i, \sigma_a), \ \ where \ x_i \in [1,100] \tag{2a}$$

199   where σ_a reflects individual *self-assessment error*, i.e., the initial precision with which they can

200   estimate their own size. For all main results, $\sigma_a = 20$. Individuals then calculate a starting prior

201   as a truncated normal distribution centered on their estimate, with standard deviation,

202    $\sigma_\theta = \sigma_a$,

$$P_r(\theta) = N(\bar{x}_i, \sigma_\theta), for \ 1 \le x \le 100 \tag{2b}$$

Effort strategy

Although the purpose of our model is to explore updating strategies, in order to do so, we must

first establish how agents determine their *effort* in a contest, v_i, representing any degree of

variable investment in a contest (e.g., the amount of time/energy an animal will expend before

yielding.) Empirical observations (Hsu et al. 2008) and theory (Smith and Parker 1976; Enquist

and Leimar 1983) suggest that an individual's effort should be proportional to their potential to

win, so we designed the effort strategy to match this. To determine their effort, each agent first

assesses the size of their opponent, by drawing their estimate of opponent size, $\bar{x}_o$, from a

truncated normal distribution centered on their opponent's true size,

$$\bar{x}_o \sim N(x_o, \sigma_c), \; where \; x_o \in [1,100] \tag{3a}$$

216 Here the standard deviation, σ_c, represents opponent assessment error, i.e., the precision of

217 that assessment. For all main results, $\sigma_c = 3.1$ (see Appendix A for notes on parameter

218 selection). Agents then set their effort, v_i, based on their estimated probability of winning, such

219 that

$$v_i = P(win \, | \bar{x}_i, \bar{x}_o) \tag{3b}$$

where effort, v_i, is equal to the conditional probability of winning—given an agent's estimates

about their own and their opponent's sizes and assuming both agents will equally invest 0.5

effort. This probability is calculated using the same function which determines contest outcome

(see equation (4a), below.)

Determining contest outcome

For a given contest, the winner is decided probabilistically, based on the relative size and effort

of each agent, combined to define each agent's *wager*, w_i:

$$w_i = s * x_i + (1 - s) * v_i \tag{4a}$$

Wager, w_i, and *effort, v_i* as terms are somewhat similar. It may be useful to think of wager in

physical terms as *work*, i.e., the amount of energy imposed on the opponent, and effort as

vigor, or the amount of energy expended by the individual. In other words, the wager scales the

individual effort according to their size, where s allow us to control the relative importance of

size and *effort*.

Because in our model (as in natural observations) contests are determined by when the

subordinate individual yields, and contest success if a function of relative, not absolute, ability,

it is convenient to calculate the outcome probability from the perspective of the lower-

wagering individual, termed the underdog. We thus calculated the probability of an upset (a

win by the underdog) with

$$P(upset) = \frac{1}{2} * \left(\frac{w_{min}}{w_{max}}\right)^l \qquad (4b)$$

where l is the bias parameter, *luck*, controlling how close the two wagers need to be for there

to be a meaningful probability of upset, such that as l increases to infinity, the probability of an

upset goes to 0 unless the two wagers are equal. Once $P(upset)$ is established, we use a

random number generator to simulate whether an upset occurs.

This approach for settling contests allows us to vary the relative contributions of size, effort,

and stochasticity while observing the (simulated) behavior of individual agents and groups (e.g.,

how much individuals invests in contests, whether dominance relationships were stable, etc.).

For all main results, we set the values of these bias parameters at s = 0.7, $l = 6.1$.

Updating self-assessment post contest

Here, we compare three possible strategies for updating self-assessment: Bayesian updating,

linear updating, and static estimates (no updating), each described in detail below, in order of

increasing complexity.

Static Estimate (No updating)

The simplest possible update strategy is to not alter your initial estimate. We model this

scenario, where we keep each agent's initial estimate of size fixed throughout the simulation,

regardless of contest outcomes. In the fixed case, an agent's estimate is their initial guess, x_i,

with awareness, σ_a.

Linear Updating

A simple way to implement self-assessment updating, (modeled after Dugatkin 1997), is to

either increase or decrease each agent's self-estimate of their size, using some proportion, p, of

its prior estimate and/or adding or subtracting some constant, k.

$$\bar{x}_{i_{t+1}} = p\bar{x}_{i_t} + k \tag{5a}$$

271   To make this more comparable to our Bayesian updating approach, we set $k = 0$, and set limits

272   on the maximum and minimum possible size ($X_{min} = 1, X_{max} = 100$), such that an agent's

273   new estimate, $\bar{x}_{i_{t+1}}$, is a function of their previous estimate, shifted by some factor, where

$$X_{min} \leq \bar{x}_{i_{t+1}} \leq X_{max} \tag{5b}$$

We then allowed p to vary dynamically as a function of distance from the max/min size, in

order to more closely replicate the variable shifts of Bayesian updating, where

$$p = \quad 0.1 * (X_{max} - \bar{x}_{i_t}), if \ win \quad\quad (5c)$$

$$p = -0.1 * (\bar{x}_{i_t} - X_{min}), if \ loss$$

Since this function only acts on the point-estimate (defined by the maximum likelihood

estimation of the prior distribution), after updating this max likelihood estimate, we generate a

new, truncated normal distribution, centered around that estimate, based on their *self-*

assessment error, σ_a, as in equation (2b). This approach provides a simple heuristic that, like

Bayesian updating, allows for weighted updating, but updates self-assessment without

calculating a likelihood function.

Bayesian updating

In contrast with simpler heuristics, Bayesian updating attempts to calculate the true probability

of being a given size, based on known/estimated parameters about the state of the world and

the probability of outcomes. In general, Bayesian updating modifies some *prior* estimate using a

likelihood function. In our case, the prior is the agent's current estimate of its own size,

modeled as a discrete probability distribution. The likelihood function is the probability of the

observed outcome (i.e. winning a given contest), conditioned on being some assumed size,

calculated across all possible sizes. Then the posterior distribution, i.e., the new probability

distribution of an agent's size estimate, θ, is calculated by

$$P_{post}(\theta|outcome) = \frac{P(outcome \mid \theta)*P_{prior}(\theta)}{P(outcome)} \quad\quad (6a)$$

We discuss the case of a winning outcome, but the formulation is similar following a loss. For

each possible size in our discrete size range, the posterior probability of being a given size is

$$P(x_i = x | win) = \frac{P(win | x_i = x) * P(x_i = x)}{P(win)} \tag{6b}$$

303   where, $P(x_i = x)$ is the prior estimate of being a given size, while the likelihood $P(win | x_i =$

304     $x)$ is the probability of an individual of size x winning the previous contest, which is calculated

305   according to the probability of upset from equation (4b). $P(win)$ is calculated as the sum of

306     $P(win | x_i = x) * P(x_i = x)$ across all sizes, x,

$$P(win) = \sum_{x=0}^{x_{max}} P(win | x_i = x) * P(x_i = x) \tag{6c}$$

309   After calculating the posterior estimate, agents update their point estimate of size, $\bar{x}_i$

$$\bar{x}_i = E(\theta) = \sum_{x=1}^{x_{max}} x * P(x_i = x) \tag{6d}$$

Where E is the maximum likelihood estimate of the size distribution. This value is then used to

compute agent effort in the next contest.

Parameter space

Taken together, our possible parameter space comprises the contest outcome parameters

(s, l), reflecting the influence of *size vs effort*, and *luck,* respectively; as well as the assessment

parameters (σ_a, σ_c), representing *self-assessment error* and *opponent-assessment error*. For all

main figures, we use the default values stated in Table 1, ($s = 0.7; l = 6.3; \sigma_a = 20; \sigma_c =$

3.1), which were chosen to approximate empirical observations (Beacham 1988; Bierbach et al.

2012), namely that upsets were rare, and contests were usually predictable based on size

(figure A1). We explore the full parameter space is in Appendix B.

<u>Model Analysis</u>

The goal of our model is to answer two questions. 1. Does Bayesian updating for self-

assessment produce dominance hierarchies that match the behavior of empirical systems? 2.

How can we distinguish, empirically, Bayesian updating from alternative models of dominance

establishment and winner/loser effects? To answer these questions, werun simulations of

model behavioral experiments while extracting behavioral metrics that would be tractable in

and relevant to an empirical context, such as contest intensity. These experiments, and the

behavioral metrics we measure, are discussed in their relevant results sections.

Implementation

All code was written in python. The random number generator for contest outcome was from

the *numpy* library. All code and results are available on github

(github.com/aperkes/BayesBattleBots).

Results

Part 1: Matching Empirical Observations

<u>1.1 Bayesian updating predicts the existence of winner and loser effects.</u>

We first test whether agents using Bayesian updating show winner-loser effects. To do so, we

model a simulated experiment (based on standard empirical approaches) by forcing either a

win or loss in a contest between a focal agent and a "treatment" opponent of known size (in

this case, the same size as the focal individual). We then measure winner/loser effects by

pairing these focal winners (or losers) against "assay" opponents (a second size-matched

agent). We repeat this process for 1000 focal winners and losers. We can then quantify the

winner/loser effect as the proportion of focal agents which win against their assay opponent

(where no winner-loser effect would yield 50% wins). As shown in figure 2a, we find obvious

winner-loser effects, in that prior winners were more likely to win subsequent contests, while

prior losers were more likely to lose. These winner effects are broadly observed across the

range of parameter values (see figure B1).

<u>1.2 Bayesian updating does not drive dramatic differences between winner and loser effects</u>

Under these conditions, winner and loser effects are roughly equal in strength, with the loser

effect being slightly stronger. Exploring the parameter space, although this loser-effect bias is

broadly observed, these differences are very small (see figure B2). Although empirical results

are mixed, this seems to conflict with known observations, in which loser effects tend to be

dramatically more impactful. This discrepancy does not rule out Bayesian updating as a

mechanism, since the strength of winner-loser effects depend strongly on the specific strategy

used by an organism, which is in turn based on the costs and benefits of winning or losing.

Given that we do not observe a strong loser-effect bias, it seems likely that the differences in

the strength of winner and loser effects observed in natural systems come not from some

inherent bias in Bayesian updating per se, but from the strategies used by organisms to

determine effort in response to changes in self-assessment.

Figure 2: **A.** The proportion of focal agents (out of n=1000) winning against a naïve size-matched assay

fish, after a treatment win/loss. **B.** Agent estimates are plotted over the course of repeated contests

against naive, size-matched opponents, with the branching paths showing the estimates following a win

or loss. The boxes note specific experiences highlighting the recency effect, which diminishes with

increased experience. **C.** Focal agents' estimates change following a staged win against agents of varying

size. The shift in the focal agent's estimate following a win is greater when their opponent is larger.

<u>1.3 Bayesian updating produces a recency bias in winner-loser effects</u>

Although winner-loser effects vary across species, there is strong empirical evidence that many

species show a recency bias, in which the outcomes of more recent contests have a stronger

effect on behavior than do the results earlier contests. We find that our model recreates these

empirical observations. Once again emulating empirical tests of the winner-loser effect, we

simulate contests between naive, size-matched agents and then pair these focal winners and

losers against new, naïve, size-matched individuals, repeating this process over 6 rounds of

contests. We control the outcome of each contest to generate new branching paths with both

winners and losers. To limit noise, all individual priors were centered on their true size, and

agents' opponent-assessment was set to match opponent size exactly. Here, we measure

winner-loser effects directly as the agents' own size estimates. In figure 2b, we see that winner-

loser effects have an experience-dependent recency bias, such that "recent losers", (WL), who

first won a contest and then lost, update their size estimate to be lower than "recent winners",

(LW), who had lost and then won. This recency effect is based on the fact that the recent

winners (LW) win while investing less in their second contest than the recent losers (i.e., initial

winners, WL); the strength of this effect depends on the specific parameters used (see figure

B3), but under all parameters, recent winners have posterior estimates that are greater than or

equal to those of recent losers.

<u>1.4 Bayesian updating explains the observed variation in the persistence of winner/loser effects</u>

In empirical observations of dominance contests, winner-loser effects are persistent in some

cases while in others they are short-lived or even non-existent. Here, we find that our model

can reconcile these apparent discrepancies, based on the size of the initial opponent and the

nature of agent experience between this "treatment" contest and the "assay" contest.

We again simulate a forced-win experimental approach, this time allowing a simulated focal

agent of size $x_o = 50$ to win a staged contest against a treatment opponent of variable size

($x_o = [40, 50, or\ 60]$). As in figure 2b, we measure the winner-effect directly, as the agent's

own self-assessment. Following this initial treatment contest, focal agents are allowed to

interact with additional naïve individuals so that we could observe how their estimate changed

over time. As we see in figure 2c, the scale of the initial shift depends on the size of the

opponent, with larger opponents stimulating larger shifts in estimates. This initial winner effect

attenuates rapidly with additional experience, although it does not fully return to baseline. How

long winner-loser effects persist above a given threshold depends somewhat on the nature of

these post-fight experiences (Supplemental figure B5), but even after 100 contests, the mean

self-assessments of these initial winners are higher than their actual size, and those who won

against bigger opponents have significantly higher self-assessments than those who won over

smaller ones. Whether these changes could be detected is obviously a function of the power of

the experiment used to assay winner-loser effects, however under Bayesian updating, the shift

itself persists indefinitely.

Taken together, our model predicts that under Bayesian updating, the observed variation in

winner effect duration (and whether it is detected generally) can be ascribed to differences in

how the winner effect is generated, the experience of individuals in the interim, and how it is

assayed in the subsequent test matches. All of this is consistent with empirical observations

that the experimental methods used influence whether winner-loser effects are observed

(Huang et al. 2011).

1.5 Bayesian updating produces efficient dominance hierarchies

Winner-loser effects are important not just for individual behavior but also the formation of

dominance hierarchies. In natural systems, low intensity contests are a hallmark of natural

systems, as individuals seek to avoid serious injury in social contest. We find that our simulated

agents using Bayesian updating recreates well documented features of natural dominance

hierarchies (Jackson and Winnegrad 1988), by rapidly reducing the intensity of contests (figure

3A). This occurs in our model as the smaller agents begin to recognize when they are unlikely to

win and yield more easily, resulting in lower mean effort across contests. This shift largely

attributable to the rapid increase in accuracy shown in figure 3A, and is widely observed

regardless of the specific parameters used (see supplemental figures B6 and B7).

Figure 3: Emergence of stable dominance hierarchy through Bayesian updating. **A. Contest intensity**

decreases over time. Here the mean intensity of fights, measured as the effort of the losing individual,

decreases with repeated contests as individuals become more confident in their assessments. **B.**

Estimate error decreases over time. Each line represents the mean stability across 1000 simulations for

different updating strategies. Stability is measured by binning the simulation into 3-round windows, and

comparing the consistency of dominance rank across bins. In both plots, blue dashed line shows

Bayesian updating, while gray shaded solid line shows no-updating.

This improved accuracy also increases the stability and linearity of networks (see supplemental

figures B8 and B9). Although network stability and linearity depend on the relative importance

of size and other parameters, under most conditions, Bayesian updating produce networks that

are more stable and more linear than those in which individual estimates are fixed, although it

did not produce the hyper-stratification observed in models that directly modify intrinsic

contest ability (e.g., Bonabeau et al. 1996; Dugatkin 1997).

Part 2. Distinguishing Bayesian updating from other models

We have shown that our Bayesian model is successful at recreating many empirical

observations of animal contests, consistent with the hypothesis that Bayesian updating may be

the mechanism behind winner-loser effects and hierarchy formation. To provide an approach

that can empirically test whether animals are using Bayesian updating, as compared to other

potential updating mechanisms, we explore two testable predictions of Bayesian updating,

based on the two defining features of Bayesian learning—the likelihood-based updating and

the informed prior. We investigate each of these two aspects separately, with simulated

experiments to model future approaches in animal systems, focusing on measurable contest

outcomes within empirically tractable scenarios.

2.1 The effect of opponent size, but not focal agent experience, distinguishes Bayesian updating

First, we focus on three potential updating mechanisms: Bayesian, linear updating, or static

estimates (no updating). To test how these different updating mechanisms might be

experimentally distinguished, we simulate contests of focal individuals against different sizes

and then measured the strength of winner-effects using a size-matched assay opponent match.

As was shown in figure 2c, agents using Bayesian updating show stronger winner effects when

their initial opponent is larger, while this "discrepancy effect" is not seen if the agents use a

linear shift (figure 6a). This was also true for the loser effect (supplemental figure B10) and is

observed wherever size and effort affect contest outcome (supplemental figure B11).

Figure 4: Simulated experiments show that updating strategy can be distinguished by the effect

of opponent size and focal agent experience. **A.** Under Bayesian updating, the strength of the

winner effect (the proportion of agents winning a size-matched contest after a staged win), is a

function of opponent size. **B.** The strength of the winner effect is also a function of the number

of contests prior to the forced win, however this does not distinguish Bayesian updating from

linear updating.

It seems natural that variable winner-loser effects, based on the amount of prior experience,

would also be a distinguishing feature of Bayesian updating, since Bayesian priors encode past

experiences and can reflect the confidence of an estimate, while linear updating has no such

mechanism. To explore this relationship, we prime simulated focal agents with between 0 and

50 contests against naïve opponents (without fixing the outcome), thereby creating variation in

the extent of each focal agent's experience. We then assess the strength of the winner-loser

effect as before, first pairing the naïve or experienced focal individual with a size-matched

'treatment' opponent in which we force a win/loss, and then recording whether they win

against a naïve size-matched assay opponent. As expected, in agents using Bayesian updating,

winner effects are weaker for experienced agents than for naïve agents (figure 6b, dot-dashed

line). Surprisingly, the same is also true for experienced agents using linear updating schemes

(figure 6b, dashed line). This appears to be driven by the fact that under linear updating,

estimates tend to diverge over time, becoming either extremely large or small, and are thus

resilient to a single outcome. Thus, while this "experience effect" is a core prediction of

Bayesian updating (across a range of parameter values, as shown in supplemental figure B13),

and failing to find one would exclude Bayesian updating as a mechanism, finding an experience-

attenuated winner effect does not rule out other possibilities. The effect of opponent size is the

most straightforward single test for Bayesian updating.

2.2 Informed prior estimates drive consistent individual and context dependent differences

Often when behaviorists test for whether animals are using Bayesian strategies, they are asking

specifically whether animals have "prior opinions" of the general state of the world which are

then applied to each new context, for example the quality of a novel potential mate or some

new foraging patch (reviewed in McNamara et al. 2006). In this sense, the question is not so

much about how individuals update their prior estimate during the task, but whether animals

come into the task having informed prior estimates which reflect their expected state of the

world, either based on their own past experiences or evolved over generations. With this in

mind, we simulate experiments that would allow us to empirically distinguish whether

individuals have informed priors, and how these priors form.

To explore this question, we simulate agents that begin with either informative or

uninformative priors. As a reminder, priors are modeled as a probability distribution of size. For

uninformative priors, we use either 1) a uniform distribution ("uninformed") or 2) a normal

distribution centered on a uniformly random variable ("misinformed"); the informative priors

are similarly divided into 3) a normal distribution centered on the agent's approximate size

("self-informed") or 4) a distribution that reflects the distribution of nearby agents ("peer-

informed", for which we set peers to be either all large or all small)

We conduct simulated experiments in which we measure contest intensity—which in an

empirical context could be quantified as the time spent in aggressive behaviors (Schlinger et al.

1987; Francis 1990)—among individuals using these different prior estimation methods. Each

simulated agent is assayed 3 times, each time against a different, naïve size-matched opponent

(drawn from the same prior method group). Because we simulate 3 trials for each agent, we

can measure both persistent individual differences and context-dependent variation in the

amount of time agents spent before yielding (i.e., *effort*). Here we prevent agents from

updating their estimates after each contest. While allowing them to update estimates did not

change the qualitative results for the self-informed group, allowing other groups to improve

their self-assessment during the contest resulted in the tendency to also correlate their effort

with their size over time, although this correlation was quite weak (see supplemental figure

B14).

In these simulated experiments, we find key differences in aggressive behavior which

successfully characterizes groups based on the source of their prior (figure 7). Specifically, in

groups of individuals using either self-informed or mis-informed priors, there are consistent

individual differences in contest effort (i.e., significant variation within the group based on

individual). Peer-informed agents may show individual differences if these agents were drawn

from different peer groups (small peers vs large peers), but do not show differences when

drawn from the same peer group (small peers vs small peers). Peer-informed agents (drawn

from different groups) show within-group variation in effort correlated with peer size, but only

self-informed agents displayed a correlation between individual variation in effort and size. This

effect was observable across all parameters in which size was a factor in contest outcome

(supplemental figure B15). Thus, by controlling for peer group and characterizing consistent

individual variation in effort (and size), it is possible to identify whether individuals form prior

estimates and, if so, what information they use to inform these estimates.

Figure 5: The y-axis shows contest intensity (effort) for 5 different simulated groups, each using a

different starting prior. For each boxplot, boxes are arranged from left to right according to size. The

left-most two groups (light and dark gray) have "uninformed" priors, either with all individuals having a

uniform prior, or each individual having their own randomly selected prior. In the three groups on the

right (light or dark blue), individuals have "informed" priors, using either internal information (Self-

informed) or external information (small-informed/big-informed, the rightmost two clusters). Only self-

informed priors lead to a correlation between size and effort (red dotted line).

Discussion

Here, we show that Bayesian updating can explain the existence of winner and loser effects

resulting in contest behavior and dominance hierarchies that are consistent with those

observed within social systems in nature. Notably, winner-loser effects occur without any

explicit change in strategy (e.g., "invest more after a win"), simply as a side effect of agents

making their self-assessments as accurate as possible after each contest. More importantly,

our model provides testable predictions to evaluate whether species' behavior is consistent

with Bayesian updating for self-assessment. Our main findings here lay the groundwork for

future work, both empirical and theoretical, in understanding the biological drivers of social

dominance and the winner and loser effects.

Our Bayesian self-assessment model matches some, but not all, features of dominance

interactions and winner-loser effects. Bayesian updating of self-assessment alone is sufficient to

drive winner and loser effects, and because winner and loser effects are affected by the

experience of the focal individual and the size and effort of the opponent, Bayesian updating

can also explain variation in the relative strength and persistence of winner and loser effects,

but it does not explain all aspects of network formation, which are likely mediated through

mechanisms like contest strategy and feedback on intrinsic ability, which we do not model

here. For example, agents using Bayesian updating increase the stability, linearity, and

efficiency of dominance hierarchies, but in our model, Bayesian-based hierarchies do not

stratify into hyper-linearity unless there are large differences in agent size from the start. This

contrasts the work of intrinsic feedback models (e.g., Dugatkin 1997), in which linearity could

emerge in the absence of initial differences. For both our model and prior intrinsic-feedback

models, linearity and stability are a function of the intrinsic ability to win fights ('*size*'). Because

in our model intrinsic ability does not change, agents only form more accurate assessments of

intrinsic ability.

Similarly, Bayesian updating does not appear to generate strong biases towards loser (or

winner) effects against size-matched opponents. The empirically documented loser-effect bias

would thus need to originate from the contest strategy (i.e. how *effort* is calculated), or the

contest function (i.e., how fights are settled), which we also do not explore here, however prior

models based in game theory, most recently Leimar, 2021, show that stronger loser effects can

be selected for when evolving contest strategies, suggesting that Bayesian updating, paired

with evolved effort strategies, would replicate this behavior.

Given the success of strategic models (e.g., Leimar, 2021 and Leimar & Bshary, 2022) in

replicating many of the empirical features of dominance hierarchies and incorporating a greater

range of behavioral information (social eavesdropping, individual recognition, etc.), it is

important to address whether the added complexity of Bayesian modeling provides any

benefit. First, shifting an estimated self-assessment is a fundamentally different mechanism

than updating contest strategy. It may be that given sufficient complexity, either could be

replicate any given behavior, but we still expect the correlates of these approaches to differ.

For example, a shift in self-assessment would likely be generalized across contexts (e.g., with

novel predators or environmental challenges) whereas updating a strategy might be more

limited in scope. More specifically, Bayesian updating is the most accurate possible approach

for modifying an estimate, and thus provides a theoretical best case for any assessment-based

approach, while also providing specific predictions which are different from existing strategy

models. For example, while most strategy-based models encode some discrepancy effect (i.e.,

adapt more strongly to unexpected outcomes), they do not display any notion of estimate

"confidence", whereas under Bayesian updating, experienced animals become more confident

in their self-assessment and thus more resilient to winner-loser effects (as shown in figure 2c).

Whether this matches the behavior of any given species is an empirical question, but doing the

work to generate such predictions will motivate the experiments necessary to identify

mechanisms.

In short, our model uses Bayesian modeling to explore the effects of self-assessment updating

in isolation, which produces specific, testable predictions, and provides insight into the possible

drivers of social behavior. Obviously this Bayesian self-assessment updating would need to be

integrated with additional mechanisms (i.e., more complex effort strategies, direct feedback on

intrinsic ability, social eavesdropping, etc.) in order to fully explain and predict social behavior.

Future work could synthesize these models to observe how different mechanisms interact, and

how the added complexity changes the predictions of our model.

It is important to note that while researchers often discuss "the" winner effect, there are of

course multiple winner-loser effects that occur via different mechanisms and operate across

different timescales. We have discussed winner-loser effects here from the standpoint of self-

assessment, contest strategy, and intrinsic ability, but even within any one of these effects, e.g.,

intrinsic ability, we can imagine varying, overlapping mechanisms, such as resource use and

acquisition, rapid changes in metabolism, and increased skill. Given that winner-loser effects

are both a natural consequence of, and solution to, the common problem of optimizing contest

effort, it should be no surprise that the specific behaviors and mechanisms used for a given

implementation vary based on the features and evolutionary history of the given species.

Bayesian updating may be a fundamental aspect of at least one mechanism of winner-loser

effects, and by developing and testing Bayesian models for social behavior, we can identify the

mechanisms behind not just winner-loser effects specifically, but social interactions generally,

in order to better understand and predict the formation and maintenance of social networks.

Supklemental PDF

This supplement is organized to match the structure of the main paper, and is divided into
three appendices:

Appendix A, which provides greater detail and rational regarding the methods;

Appendix B, which has sub sections matching each results section, generally exploring the
parameter space and, where relevant, the sensitivity of the results, while providing greater
insight into the results; and

Appendix C, which compiles all equations and parameters used for easy reference.

Appendix A: Extended Methods

The effort strategy was chosen for simplicity and to be proportional to odds of winning

Theory and observations suggest that animals should, and do, invest in contests as a function of
their probability of winning. Even within this limitation, there are unlimited possible updating
strategies at various levels of complexity, and empirical work suggests that contest strategies
vary both across (Arnott and Elwood 2008, 2009) and within species (Briffa et al. 2015). We
assumed a very simple strategy—investing proportional to a rough estimate of the probability
of winning. This approach does not fully take into account the certainty of self- or opponent-
assessments, nor does it seek to guess how much an opponent will invest, and there is no
optimization for costs and benefits or bet hedging. Furthermore, there is no variation in
available energy, motivation, boldness, etc. All of these are likely important factors in real effort
strategies, however exploring effort functions is beyond the scope of our primary goal:
exploring the how changes in self-assessment would impact behavior. Future modeling should

explore how different effort functions impact winner/loser effects and social contests within

the context of Bayesian updating.

Additionally, because the probability of winning is a function of the relative size of the smaller

individual, in equation 3b, the probability of winning $P(win\,|\bar{x}_i, \bar{x}_o)$ varies depending on

whether an agent estimates itself to be bigger or smaller than its opponent.

$$v_i = \left(\frac{s\bar{x}_i + (1-s)*0.5}{s\bar{x}_o + (1-s)*0.5}\right)^l \qquad if\ \bar{x}_i \leq \bar{x}_o \qquad\qquad (A1)$$

$$v_i = \left[1 - \left(\frac{s\bar{x}_o + (1-s)*0.5}{s\bar{x}_i + (1-s)*0.5}\right)^l\right] \qquad if\ \bar{x}_i > \bar{x}_o$$

where, s and l are the simulation parameters used to account for the influence of *size* and *luck*

respectively. Although the actual probability of winning depends on both relative size and

individual effort, with this effort strategy, agents must approximate the probability of winning

by assuming that both they and their opponent will invest the same amount in the contest.

Contests were determined in a way that allows us to explore the impact of size and effort

As with agents' effort strategy, there are unlimited possible ways that size and effort could

combine to determine contest outcome. Here we aimed to find an approach that was backed in

empirical observations and theory, while also being tractable and efficient in the context of our

simulation.

First, we had to decide how size and effort combine to determine contest performance, what

we call a wager. We wanted to be able to parameterize the relative impacts of size and effort,

so the simplest way to do that was a weighted sum of these two inputs, as stated in the

Equation 4a from the main text:

$$w_i = s * x_i + (1 - s) * v_i \tag{4a}$$

676   It seems likely that in natural systems there is also some interaction effect, as well some non-

677   linearity in the output, so a more realistic function might be a something like

$$w_i = \beta_o x_i^a + \beta_1 v_i^b + \beta_2 (x_i * v_i)^c \tag{A2}$$

however, since the contest function is not the focus of our model, the increase in complexity

did not seem warranted. That said, in applying this model to any given empirical system,

researchers should take care to ensure whatever function used is relevant to their system.

Next, we had to decide how agents' wagers should determine outcome. Empirical observations

suggest an S-shaped curve for contest outcome as a function of relative size, that is, contests

are highly predictable when individual size is dramatically different, and unpredictable when

agent size is very similar, as shown in figure A1 below, reprinted from Graham & Angiletta,

2020.

Figure A1: Empirical measure of the role of intrinsic attributes (claw size) in determining contest

outcome, (from Graham and Angilletta 2020). In this case, overall body size was matched between

participants, in order to observe the effect of claw size specifically. Note that while the sigmoid function

used above is fit to the absolute difference in claw size, our model is based on relative size of the smaller

individual.

As a theoretical explanation of this behavior, we hypothesize that there is some noise around

an individual's expected performance—based on their size and effort—and the actual output.

This noise would come from both intrinsic and extrinsic factors, such that each individual's

actual wager, w_i, is drawn from a normal distribution centered on the ideal wager, $\overline{w}_i$, (based

on their intrinsic potential, *size*, and their behavior, *effort*) (figure A2a). A contest represents

drawing a single random value from each performance distribution, where the higher observed

performance wins. If we implement this model to generate performance distributions for each

individual from which we could draw their "output" wagers, we can then calculate the

likelihood of the lower performing underdog being the larger draw. Since these are two normal

distributions, $P(w_i > w_j) = P(w_i - w_j > 0)$.

Figure A2: Contests are determined as a function of the relative performance of competing

agents. A. Given some theoretical "output" performance by two different performing

individuals (dotted lines), we assume there is a distribution of "observed" outputs. B. Given two

probability distributions, each line shows the probability of upset as a function of the relative

wager (of lower individual), which is the probability of drawing a larger value from that lower

distribution. The shape of this function is determined by the standard deviation of the observed

performance distribution. C. We approximate this process by raising the relative wager to some

exponent, l.

This model has the parameter σ_w, the amount of variation in performance output. For different

values of σ_w, we get likelihood functions that are more or less convex (figure A2b), representing

contests that are more or less biased towards the higher-performing individual. Note that in

contrast with the empirical figure A1, here we are quantifying the actual contest performance,

the combination of size and effort (which are abstractions of body size, weapon size, contest

skill, energy investment, time investment, etc.), rather than just size.

While this approach is justifiable both theoretically and empirically, it is computationally very

expensive to calculate the cumulative distribution multiple times for each contest, especially

when running millions of iterations of simulations. For this reason, we chose to implement the

simpler exponential described in equation (4a). This produces the win probability function and

parameterization shown in figure A2c, both of which are similar to the CDF-function, while

being both simpler and roughly 100x faster to run. In the main results, we set $l = 6.3$ (see note

on parameter values below) but explore the range of l values shown in figure A2c.

As a note, under this relative wager calculation the agent with greater relative size and effort

(i.e., the '*favorite*') usually won, but the agent with the smaller wager (the '*underdog*') could

win, particularly if the two wagers were close. It is important to highlight that the smaller wager

was not necessarily the smaller sized individual; if a relatively smaller agent contributed far

higher effort, they could have the larger wager, w_{max} , and thus be the '*favorite*' for the

purposes of our calculations.

Like our chosen effort strategy, potential contest functions are not the focus of the model, but

these model decisions have an influence on self-assessment updating and the winner effect,

since the likelihood function used when updating the prior estimate is calculated based on our

chosen contest function. Future work could explore how different contest functions impact the

behavior and predictions of Bayesian updating, and compare these to observed examples of

social dominance.

Further details of Bayesian updating

During Bayesian updating, focal agents multiply their prior self-assessment (a probability

distribution of their size) by the likelihood function of the observed output (winning or losing

against the specific opponent). Finding this likelihood function requires calculating the

probability of winning (or losing), conditioned on the focal agent being each possible size, x ,

across the range of possible sizes. Because probability of winning is calculated as function of the

smaller relative wager, $\frac{w_{min}}{w_{max}}$, the probability of winning is equal to the probability of upset

when the focal agents hypothetical wager is less than the opponent's wager ($w_i| x \leq w_o$), but is

its inverse (i.e. probability of no upset) once the focal agent's hypothetical wager is greater than

the opponent's:

$$P(win|x_i = x) = P(upset), if\ w_i|\ x \leq w_o \qquad\qquad (A3)$$

$$P(win|x_i = x) = 1 - P(upset), if\ w_i|\ x > w_o$$

Note that this inflection point is based not on relative size but on relative wager, such that

agents must take into account both their own and their opponent's effort into their calculations

of relative wager, and thus the probability of winning, $P(win)$. For simplicity, we assume that

after the contest, agents have perfect knowledge of the size and effort of the opponent,

however this calculation could be extended to allow for estimated distributions of opponent

size and opponent effort, assuming we have probability distributions for opponent size and

effort.

Overview of parameter space

There are 4 core parameters $(s, l, \sigma_a, \sigma_c)$ which define the main parameter space. For any given

simulation, there are additional parameters, such as the population makeup or the

experimental design (e.g., the size and effort of a staged opponent), which are discussed in

their relevant sections. For parameters within a fixed range (e.g., s has the range [0,1]) we

sample evenly across this range.

For unbounded parameters (e.g., $\sigma_a \in [0, \infty)$), we use scaling functions for ease of use in

implementation. For l, we use the scaling function

$$l = \text{cotangent}\left(\pi * \frac{(1-L)}{2}\right), \ \ 0 \leq L \leq 1 \qquad \text{(A4a)}$$

Our default $L = 0.8$, corresponds to $l = 6.3138$. For simplicity, we show the scaled, l values in

our plots, rounded to the first decimal place, which represent sampling evenly across the range

of L values. This function can also be used to map L to values of l between [0,1], however in

our parameter exploration, these results all behaved very similarly to $l = 0$, so we focused on

values between [0,1], which are also far more relevant to our behavioral model.

Similar to l, for both σ_a and σ_c, we use the scaling function

$$\sigma_a = 20 \tan\left(\pi * \frac{A}{2}\right), 0 \le A \le 1 \qquad \text{(A4b)}$$

For implementation purposes, evaluating at the limits sometimes requires some conditional

statement to avoid errors, for example where $\sigma_a = \infty$, we use a conditional statement to set

the assessment distribution to be uniform across the range of sizes.

Our default assessment parameters assume a situation where opponent assessment is always

fairly accurate ($\sigma_c = 3.1$), while naïve self-assessment is very noisy ($\sigma_a = 20$). This is based on

the idea that observing opponent size is actually easier than observing your own size, but this is

not necessarily the case. We explore the full range of this space in the figures below, including

where $\sigma = \infty$, in which opponent assessment is a random uniform variable, and $\sigma = 0$, where

assessment is perfect. The case where $\sigma_c = \infty$ also functions as a version of pure self-

assessment, albeit with a strong random component.

Appendix B: Exploration of Results

1.1 Bayesian updating drives winner and loser effects

First, it is useful to highlight the components which drive winner-loser effects in this model.

Winner-loser effects can be broken down into 3 factors: the change in estimate, the extent to

which that estimate leads to a change in effort, and the extent to which the change in effort

leads to a change in outcome. Parameters can act on one or more of these mechanisms, but

even changing only one mechanism can impact winner/loser effects (so, for example, changing

how effort impacts outcome could strengthen winner effects, even if the change in effort and

estimate remained the same.

Figure B1 repeats the simulation show in figure 2a across the range of possible parameters. In

short, focal agents are selected to either win or lose against a size matched 'treatment' agent,

and then tested against a second, size-matched 'assay' agent in order to measure the strength

of the winner effect. For simplicity, starting priors always begin centered on the true agent size,

$x = 50$. We then compare the change in effort estimate (pre-treatment vs post-treatment), the

change in effort (treatment vs assay), and the assay contest win rate. We show that across all

parameters where size contributes to contest outcome, winning increases estimated size, while

losing decreases it. The only exception is where $s = 0$, in which wagers are entirely determined

by effort, $l = 0$, where contests are entirely determined by luck, and $\sigma_a = 0$, in which agent's

being with 100% confidence of their correct size.

Figure B1: The strength of winner-loser effects across a range of parameters. How do estimates, efforts, and

probability of winning change for different parameters. Sensitivity analysis across the whole parameter space

for size matched contests. Lines represent the mean outcome from 1000 iterations, with shading shows the

mean +/- 1 SEM. Gold lines show post-win, blue lines show post-loss. The variation comes from error in initial

self-assessed estimates, and the error in opponent-assessment leading to variation in effort during both the

treatment and assay contests.

There were additional parameter ranges where, despite a difference in agent estimate, there

was no observable difference in win rate, notably wherever l was close to 0, since this flattens

the probability of winning, resulting in similar outcomes. This also, naturally, occurred where

$s = 1$, since a change in effort cannot impact the outcome where wagers are entirely

determined by size.

The shift in estimate is also a function of the opponent used, as shown in figure 2a. In the above

figures, we used an opponent of equal size and effort to the focal fish, however winning against

a large fish with high effort, will of course have a more dramatic impact on estimates than

winning against a small or low-effort fish. Similarly, losing to a small or low-effort fish is very

impactful, while losing to a large fish has little change on estimate.

1.2 Relative strength of winner and loser effects

As with the *presence* of winner/loser effects, their relative strength, compared to one another,

is mediated by changes in estimate as well as how that impacts effort and, in turn, contest

outcomes.

Figure B2: There is little or no bias towards winner or loser effects under Bayesian updating. This simulation

for this plot is identical to figure B1, however here we plot the difference in the strength of the winner and

loser effects (i.e., the absolute difference from the null value, either 50 or 0.5). The color here simply shows

whether the outcome is biased towards winner effects (gold) or loser effects (blue).

Over most parameters there is a slight bias towards increasing estimates (i.e., a stronger winner

effect). This appears to be due to how the likelihood function is based on relative size, and thus

flattens out with increasingly large estimates. In comparison, the effort function amplifies loser

effects somewhat, particularly where size is important and initial self-assessment error is high.

This also seems to be based on the importance of relative size, since increasing an estimate by

some fixed amount (e.g., 25 units) results in a smaller perceived relative change (50 : 75, where

$\frac{w_{min}}{w_{max}} = 0.66$) than decreasing your estimate by the same amount (25 : 50, $\frac{w_{min}}{w_{max}} = 0.5$). Taken

together, in most cases, winner and loser effects have a similar impact on win rate, with slight

bias towards the loser effects over most parameters.

It is also important to note, even in the cases where there is a significant difference in winner vs

loser effects, this bias is very small (the maximum difference observed is only around 5%). In

empirical examples, winner and loser effects can be dramatically different, and in some

examples only winner (or loser) effects are observed. Within our model assumptions, these

outcomes are unlikely to occur, without altering the size or effort of the agents (for example,

having the 'treatment' opponent be very small would cause a strong loser effect but no winner

effect'), however empirical tests generally use size-matched contests, so this is unlikely to

explain the observed strength of the loser effect. It seems likely then that the majority of

differences in winner and loser effects are driven either by the specific effort strategy used, or

else in how contests are determined. As an illustrative example, the effort strategy "invest

100% whenever there's >40% chance of victory, otherwise invest nothing" would create a

strong loser effect and no winner effect. These strategies are likely driven by the specific costs

and benefits of competition, which are different for each taxa, and those seeking to make

predictions for specific systems should seek to identify the relevant underlying functions for

that specific context.

1.3 The recency effect

Initially, the recency effect shown in figure 2b may seem to conflict with Bayesian updating,

which is known to be order invariant, however this occurs because earlier fights determine self-

assessment, and thus effort invested during later fights. Winning first means that an agent

invests more in the second fight. Because prior-winners invest more, the likelihood of losing is

lower except where size is very small. This results in prior winners being more susceptible to

loser effects, while prior losers are more sensitive to winner effects.

To assess the sensitivity of the recency effect, we use a simplified version of the simulation in

figure 2b. Again using size-matched agents, we compare two conflicting cases, recent winners

(LW) and recent losers (WL), and compare the final estimate, effort, and outcome in an assay

contest.

Figure B3: Here agents experienced two contests with conflicting information, i.e. a win then loss (WL) or a

loss then win (LW). Heatmaps show the difference between these outcomes. The top row, A-B shows the

difference in final estimate, showing recent winners were generally higher (red). The second row (C-D) shows

that the same is true for invested effort. The bottom row, E-F, shows the results of a size-matched assay

contest. Under all parameters, the recent winners are (statistically) more successful than or equal to recent

losers.

There is a consistent bias towards more recent outcomes, in this paradigm where the recent

event conflicts with the prior event. This is particularly true where both size and effort play a

role, and where contests are strongly biased towards the higher-wagering 'favorite'. Where s is

small, or large, the difference between recent winners (LW) and recent losers (WL) disappears.

Similarly, where self-assessment error is very low, or opponent-assessment error is very high,

this effect disappears. There are no scenarios where we observe a significant primacy effect, i.e.

the first event overrules later conflicting information.

That said, this recency effect is not necessarily strong enough to overcome any history: with

each additional experience, the difference decreases until eventually the one e.g., win is not

enough to supersede the sum of losses. Across all parameters tested, it never took more than 4

prior events (e.g., 4 wins) to overcome the recency effect, such that WWWWL always results in

higher win-rate than LLLLW.

1.4 The strength and persistence of winner/loser effects

This work was motivated in part by seeking to reconcile conflicting empirical results as to the

strength and persistence of winner-loser effects. For empirical work, the persistence of the

winner effect is really a question of whether experimenters are able to *observe* a winner effect

using some empirical test. There are many potential ways to test for winner effects, but for

simplify, we will only explore this question in the standard experimental assay ('treatment'

win/loss followed by an 'assay' contest).

As we show in Figure 2c, this strength and persistence of winner effects is a function of the

initial event, the intervening experience Figure S8 expands this result for both winner and loser

effects.

Figure B4: The persistence of winner and loser effects are a opponent size and intervening experience. Here

focal agents were subject to a single treatment contest (either win or loss) followed by repeated, unbiased

contests against other agents. The long-term behavior of focal agents following a forced win/loss is

characterized by an initially large shift, followed by rapid correction (which can sometimes overshoot the

correct value, as in the blue-winner line), and then a long slow process that asymptotically approaches the

true value.

The initial change in estimate is simply a question of winner/loser effect strength (figure B1).

The greater this initial change, the longer it will last. This is a natural prediction of Bayesian

updating, and contrasts with 'one-shot' models. In addition to this initial shift, the experiences

agents have between the 'treatment' contest and the 'assay' are also critical in determining

how long winner-loser effects persist (figure B5).

Figure B5: The top row (**A-B**) shows the time to recover from a win. Recovery is the number of rounds

needed to return to within 10 units of actual size (see figure B4). Here each round represents a new

individual with randomly selected size and effort. **A.** shows the number of rounds to recover with

respect to the standard deviation of opponent sizes, plotted for three different mean sizes, while **B**

shows this as a function of the standard deviation of opponent effort, again plotted over 3 different

mean efforts. **C** and **D** show the same metrics after a staged loss.

We show in figure 2c that winner effects attenuate over time, but the speed of this attenuation

(i.e., the number of rounds required to recover) depends on the diversity of info, or more

precisely, the frequency with which an agent receives information which conflicts with its

current self-assessment, as shown in figure B5. Thus with a greater variety of opponent sizes

and efforts, agents can more quickly return to near-accurate self-assessments. Similarly, with

larger mean-sized opponents will quickly erase a winner effect, but prolong a loser-effect (see

green dash-dotted line in figure B5a)

1.5 Accuracy, Efficiency, Linearity, Stability

As shown in figure B4, under Bayesian updating winner/loser effects are essentially temporary

misinformation, in that either estimates were wrong and are now better, or that they were

better and are now worse. Once agent estimates are perfectly accurate, agents will perform as

expected by their size. Thus, in our model, as agents approach accurate assessments, network

metrics like linearity and stability become a function of intrinsic differences and contest

parameters. Given this, it is perhaps not surprising that under most conformations, we do not

observe hyper-stratification. In other words, under Bayesian updating, perfectly stable, linear

hierarchies do not usually emerge from groups of similar or identical individuals.

We do however observe that Bayesian updating generally has a stabilizing influence on

networks, compared to fixed, naive estimates. As in figure 3, we simulate groups of agents

(n=5) and allow them to interact over 10 rounds (40 contests per individual), simulated over

100 iterations, from which we calculate group statistics (discussed below).

Figure B6: Estimate error plotted over a range of parameters. Groups of 5 agents were allowed to interact for

10 rounds, and lines represent the mean error (+/- SEM) over 100 iterations. The blue line represents the

final estimate error for Bayesian updating agents, while the gray line shows the final error for groups with no

updating. The dashed line shows the first round estimate error for Bayesian updaters. Estimate error is

calculated based on squared difference between actual size and estimated size +/- prior standard deviation,

as shown in equation (B1).

To calculate accuracy, we measure the distance from the true agent size, x_i and the $\bar{x}_i \pm \sigma$

confidence interval,

980                            $$\varepsilon = \sqrt{(\bar{x}_i + \sigma_\theta)^2 + (\bar{x}_i - \sigma_\theta)^2}$$ (B1)

Under almost all parameters estimate error decreases compared to initial estimates (the

exception being the edge cases where size has no impact on contest outcome, i.e., $s = 0$ or $l = $

∞). This does not occur in agents that do not perform updating (figure B7, gray shaded line)

Figure B7: Contest cost plotted over a range of parameters. As in figure B6, groups of 5 agents competed

over 10 rounds. Lines represent the mean cost (+/- SEM) over 100 iterations. The blue line represents the

final-round mean cost for Bayesian updating agents, while the gray line shows the cost for groups with no

updating. The dashed line shows the mean first round cost for Bayesian updaters. Contest cost is equal to the

effort of the lower-investing individual.

Similarly, contest cost, measured as the effort of the lower-investing agent, decreases over the

course of the simulation, however the effect of the Bayesian updating is much smaller than the

effect of the simulation parameters themselves, i.e., contest cost is low when l is high, such

that contests are highly biased against the 'underdogs', since an individual will invest

proportional to their probability of winning. Where size is unimportant, or where initial

assessment is high, we do not observe the emergence of low cost behavior that is typical of

many empirical dominance hierarchies, suggesting that Bayesian updating provides the greatest

benefits where naive self assessment in poor and where size and effort both contribute to

contest outcomes.

1001

1002   Like reduced cost contests, linearity (figure B8) and stability (figure B9) are hallmarks of social

1003   dominance hierarchies, and we find that under most conditions where contests are biased

1004   against the underdog (i.e., $l > 6$), Bayesian updating leads to a slight increase in both linearity

1005   and stability.

1006

1007

1008   Figure B8: Network linearity plotted over a range of parameters. As in Figure B6, groups of 5 agents

1009   competed over 10 rounds. Lines represent the mean, final-round linearity (+/- SEM) over 100 iterations. The

1010   blue line represents the final-round linearity for Bayesian updating agents, while the gray line shows the

1011   linearity for groups with no updating. The dashed line shows the mean first round cost for Bayesian updaters.

1012   Linearity is measured as the proportion of triads which are transitive, following Appleby's approach.

1013

To measure the effect of Bayesian updating on the linearity of dominance hierarchies, we

calculate linearity for the first and last rounds using Appleby's approach (Appleby 1983),

measuring the proportion of triads which are transitive. (if A dominates B, and B dominates C, A

dominates C). Stability is calculated by composing per-round dominance hierarchies (a round

represents a series of contests in which every agent faces every other individual). We then bin

the first 3 rounds, and the last 3 rounds, in which we measure the proportion of pairwise

dominance relationships which are consistent for all rounds within a given bin (for two agents,

if A dominates B in round 1, round2, and round 3, that is consistent, otherwise, it is

inconsistent).

1023

Figure B9: Network stability plotted over a range of parameters. As in Figure B6, groups of 5 agents competed

over 10 rounds. Lines represent the mean stability (+/- SEM), calculated over the final three rounds of the

contest, averaged over 100 iterations. The blue line represents the end-state stability for Bayesian updating

agents, while the gray line shows the end-state stability for groups with no updating. The dashed line shows

the mean first-3-round stability for Bayesian updaters. Stability is measured as the proportion of pairwise

dominance relationships which are consistent across all three rounds.

1030

1031   As seen in figures B8 and B9, while Bayesian updating produces some improvement in linearity

1032   and stability (compared to no updating, solid gray, or the first round, dotted red), particularly

1033   where initial self-assessment error is high, the effect is not nearly as dramatic as prior models,

1034   which tend to show strong linearity even in groups with identically sized individuals.

1035

In our case, groups of identically sized individuals almost never form linear dominance

hierarchies. We were able to generate this form of artificial linearity by setting opponent

assessment error to be zero, self-assessment error to be very high, and wager bias, l, to be very

high, such that after the initial, essentially random outcomes, agents arrived at high different

estimates, but because l was so high, smaller-estimating individuals never invested enough to

have a chance at winning and were thus trapped in their incorrect estimates. This is a very

unstable condition, however, for example if some naïve, smaller agent were to stumble into

this group, it would provide an opportunity for the original agents to improve their estimates

and eventually all realize that they the same size as their group mates. This does highlight that

under Bayesian updating, if agents' environment or contest strategy does not provide any

opportunity to gain new, informative experiences, they can become trapped in estimates that

might have been formed based on stochastic outcomes and very little information. This is an

important feature of Bayesian updating, but the general point is that without the any feedback

on intrinsic ability, our assessment-only, Bayesian updating model has limited potential for

hyper-stratification. It seems likely that most natural systems have some feedback mechanisms

that allow winners to gain greater resources or social capital, which increases their true contest

potential, in addition to increasing their estimates. Future models could incorporate estimate

update and feedback on intrinsic ability to observe how these processes complement and

interact.

1055

Summary of Part 1

So far, we have explored the observations in Part 1 of the main-body—namely that 1) Bayesian

updating produces winner-loser effects, 2) that Bayesian updating does not have a strong bias

towards the loser-effect, that under Bayesian-updating, winner-loser effects 3) show a recency

bias and 4) attenuate quickly in the face of new information, and that 5) Bayesian updating

produces networks that are moderately stable, accurate, efficient, and linear. In all of these

cases, these qualitative phenomenon were broadly observed in the parameter space, although

it is important to note the edge-cases mentioned, and that winner effects generally disappear

where effort is not a factor, or where contests are strongly dependent on chance. We now

explore the sensitivity of the empirical predictions.

1066

1067   **Part 2: Empirical Predictions**

1068

1069   **2.1 Size and Experience**

1070   As shown in figure 4a, we observe a discrepancy effect for winners in Bayesian updating, but

1071   not other updating paradigms. We repeated this experiment, this time including losers, but

1072   limiting 'treatment' opponents to either small and large agents (figure B10), iterating across the

1073   full range of parameters to observe whether this discrepancy effect always occurs (figure B11).

1074

1075

Figure B10: The discrepancy effect is measured as the difference between the winner/loser effect for a

smaller 'treatment' opponent vs a larger 'treatment' opponent. These lines show the probability of winning

against a second, size-matched 'assay' opponent, for three different updating strategies. This phenomenon

requires that opponent size is factored into the strength of the winner-loser effect, as in the Bayesian

updating approach in blue. Note that for both winners and losers, competing against a larger 'treatment'

opponent results in a higher probability of winning the 'assay' contest.

1082

1083

Figure B11: The discrepancy effect is broadly observed, but drops off quickly as l increases. Similar to the winner-loser effect in general (see Figure S5), the discrepancy effect is largely dependent on contests being strongly biased against the underdog ($l > 4$). Where the relationship between relative wager and winning is closer to linear, this effect is no longer observed.

Note that the discrepancy effect is only observed if both size and effort are factors, where self-assessment error is greater than 0, and opponent assessment error is lower than self-assessment error. This assessment limitation is because where opponent assessment is high, the opponent size-estimate in the size-matched 'assay' contest was largely random, meaning

1093   the focal agent effort was also very noise. This behavioral noise masks weak winner-loser

1094   effects.

1095

1096   We also show in figure 5b that winner effects are subject to prior experience, and the same is

1097   true for loser effects (figure B12). We can measure this "experience effect" by comparing naïve

1098   and experienced (in this case 10 previous contest) agents.

1099

1100

1101   Figure B12: The experience effect is measured as the difference between the probability of winning a size-

1102   matched 'assay' contest after a 'treatment' contest for a naïve individual vs an experienced individual. In this

1103   case, the only difference is the number of contests agents have experienced prior to their 'treatment'

1104   contest. For both focal winners and focal losers, Bayesian updating results in a decreased winner/loser effect

1105   as experience (and thus prior confidence) increases.

1106

1107   As before, we repeated this simulation, averaging across 1000 iterations, comparing the naïve

1108   or experienced agents, across all contest parameters, to observe where this experience effect

1109   occurred. This phenomenon is observable under roughly the same parameters as the

1110   discrepancy effect is observed, but with added noise introduced by the 10 pre-treatment

1111   opponents for the experienced individuals.

1112

1113   Figure B13: The experience effect is broadly observed wherever the winner-loser effect exists. The top row

1114   shows the strength of the experience effect (measured as the difference between naïve and experienced

1115   individuals) for winners over contest parameters s and l (left column) and assessment parameters σ_a and σ_c

1116   (right column), while the bottom row shows the same for focal losers.

1117

1118   Taken together, the discrepancy and experience effects are hallmarks of Bayesian updating, and

1119   indeed we would define any model which featured these two effects as "Bayesian-like", even if

1120   the actual mechanism is not strictly Bayesian. We would expect these phenomena to occur in

1121   systems size and effort both contribute to contest outcome, and where naïve self-assessment

1122   error is roughly equal to or greater than error in opponent assessment.

1123

2.2 Informed and uninformed priors

Finally, we explore under what conditions we should expect to see an effect between size and

effort. We show in figure 5 that for agents using self-informed Bayesian priors, there is a strong

correlation between size and effort. In the main body, we did not allow agents to update their

self-assessment between contests, The results are qualitatively similar for the self-informed

prior groups if updating occurs, although allowing Bayesian updating for all groups obviously

introduces weak to moderate correlations between size and effort (figure S18).

1131

1132   Figure B14: This modifies of the results figure 5 by allowing agents perform Bayesian updating after each

1133   repeated contest. Under these conditions, there are strong correlations for both uniform and self-informed

1134   priors, while random and externally-informed priors showed only weak correlations.

1135

1136   Focusing on the effect between effort and size observed in self-informed agents (and once

1137   again restricting updating), we repeat the simulation shown in figure 5 for every point in the

1138   parameter space, averaging the effect size across 1000 iterations (figure B15). We observe a

1139   positive effect in all conditions, except in unlikely edge cases (e.g., where the large animal wins

1140   without exception).

1141

1142

1143   Figure B15: Size and effort correlates for self-informed agents across a range of parameter values. Here, the

1144   heatmap shows the strength of the effect (i.e., the slope of normalized size, $\frac{x}{100}$, and effort, simulated as in

1145   Figure 5, averaged across 1000 iterations. For utility, the heatmap is clipped at 1.1, such that any slope higher

1146   than that is normalized. Over all values where size contributes, there is a significant effect between size and

1147   effort.

1148

It is also important to note that while this effect a consistent prediction of self-informed

assessment, to measure this effect, it is necessary to isolate "effort" from possible confounds

like energy budget or motivation. In our model, we typically think of *effort* as the amount of

time an individual animal stays in the contest, however this will often be linked to their

available energy, which is frequently a function of individual size. This experiment would be

most useful where *size* referred to something more specific, such as weapon size (as in figure

A1), so that experimenters could control for intrinsic differences in the ability to persist in a

fight. Alternatively, *effort* could measure the latency to engage in a contest, or some other non-

energy-based metric. Obviously, applying theoretical predictions to empirical systems requires

care and system-specific understanding to design experiments appropriately.

1159

Summary

Bayesian updating predicts the existence of winner-loser effects, and several associated

phenomena, however these predictions are most useful where individuals combine intrinsic

ability and effort to determine the outcome, and where there is some (but not too much)

uncertainty in own and opponent ability. These conditions likely apply to many social animals,

and future empirical work should test these predictions in appropriate systems to observe

whether natural behavior matches the predictions of Bayesian updating.

Appendix C – Parameters and Equations

Table 1: model parameters and abbreviations, reprinted here for reference

Symbol	Default	Range	Explanation
$x :$ $(x, x_i, x_o, \bar{x}_i)$	Random	$1 \leq x \leq 100$	Size of an individual. x_i represents actual size for individual i, while x_o is the actual size of opponent. $\bar{x}$ denotes an estimated size
μ_x	50	$1 \leq x \leq 100$	The mean of the population from which individuals are drawn
σ_x	10	$0 \leq \sigma_x < \infty$	Standard deviation of population from which individuals are drawn. At $\sigma = \infty$, uniform distribution is used.
$v :$ (v, v_i, v_o)	None	$0 \leq v \leq 1$	Effort, i.e., the amount of time/energy invested in a contest. As with size, subscripts distinguish effort by the focal individual v_i from their opponent's, v_o
$w :$ (w, w, w)	None	$0 \leq w \leq 1$	Wager, or contest performance, a combination of the agent's size and selected effort. This could also be thought of as work, i.e., the amount of energy imposed on opponent.
s	0.7	$0 \leq s < 1$	Relative importance of size vs. effort, acts as a simple multiplier when summing size and effort.
l	6.3*	$0 \leq l < \infty$	Relative wager dampener, essentially the importance of luck, acting as an exponent on relative wager, such that as l increases, the probability of an upsets decreases
σ_a	20	$0 \leq \sigma_a < \infty$	*self-assessment error*, the accuracy of individuals' starting guesses for their self-assessment.
σ_c	3.1*	$0 \leq \sigma_c < \infty$	*opponent-assessment error*, the accuracy of individuals when guessing the size of opponents prior to contests
$P(\theta)$	-	-	Used to denote the prior, an estimated, discrete distribution of the probability of being some size.

1170   Equations Sheet

1171   Agent generation

1172
$$x_i \sim N(\mu_x, \sigma_x)$$
(1)

1173   Agent estimate generation

1174
$$\bar{x}_i \sim N(x_i, \sigma_a)$$
(2a)

1175
$$P_r(\theta) = N(\bar{x}_i, \sigma_\theta)$$
(2b)

1176   Effort strategy via opponent assessment

1177
$$\bar{x}_o \sim N(x_o, \sigma_c)$$
(3a)

1178
$$v_i = P(win \,|\bar{x}_i, \bar{x}_o)$$
(3b)

1179   Calculating contest outcome as a function of relative wagers

1180
$$w_i = s * x_i + (1 - s) * v_i$$
(4a)

1181
$$P(upset) = \frac{1}{2} * \left(\frac{w_{min}}{w_{max}}\right)^l$$
(4b)

1182   Linear updating strategy

1183
$$\bar{x}_{i_{t+1}} = p\bar{x}_{i_t} + k$$
(5a)

1184
$$X_{min} \leq \bar{x}_{i_{t+1}} \leq X_{max}$$
(5b)

1185
$$p = \quad 0.1 * (X_{max} - \bar{x}_{i_t}), if \; win$$
(5c)

1186
$$p = -0.1 * (\bar{x}_{i_t} - X_{min}), if \; loss$$

1187   Bayesian updating of self-assessment

1188
$$P_{post}(\theta|outcome) = \frac{P(outcome \,|\, \theta) * P_{prior}(\theta)}{P(outcome)}$$
(6a)

1189
$$P(x_i = x|win) = \frac{P(win|x_i = x) * P(x_i = x)}{P(win)}$$
(6b)

1190
$$P(win) = \sum_{x=0}^{x_{max}} P(win|x_i = x) * P(x_i = x)$$
(6c)

1191

$$\bar{x}_i = E(\theta) = \sum_{x=1}^{x_{max}} x * P(x_i = x) \tag{6d}$$

1193   Full effort strategy

$$v_i = \left(\frac{s\bar{x}_i + (1-s)*0.5}{s\bar{x}_o + (1-s)*0.5}\right)^l \qquad if\ \bar{x}_i \leq \bar{x}_o \tag{A1}$$

$$v_i = \left[1 - \left(\frac{s\bar{x}_o + (1-s)*0.5}{s\bar{x}_i + (1-s)*0.5}\right)^l\right] \qquad if\ \bar{x}_i > \bar{x}_o \tag{}$$

1196   Possible expansion of wager calculation

$$w_i = \beta_o x_i^a + \beta_1 v_i^b + \beta_2 (x_i * v_i)^c \tag{A2}$$

1198   Full likelihood calculation

$$P(win|x_i = x) = P(upset), if\ w_i|\ x \leq w_o \tag{A3}$$

$$P(win|x_i = x) = 1 - P(upset), if\ w_i|\ x > w_o \tag{}$$

1201   Scaling functions

$$l = \text{cotangent}\left(\pi * \frac{(1-L)}{2}\right),\ \ 0 \leq L \leq 1 \tag{A4a}$$

$$\sigma_a = 20 \tan\left(\pi * \frac{A}{2}\right), 0 \leq A \leq 1 \tag{A4b}$$

1204   Accuracy Calculation

$$\varepsilon = \sqrt{(\bar{x}_i + \sigma_\theta)^2 + (\bar{x}_i - \sigma_\theta)^2} \tag{B1}$$

1206

References

Appleby, M. C. 1983. The probability of linearity in hierarchies. Animal Behaviour 31.
Arnott, G., and R. W. Elwood. 2008. Information gathering and decision making about resource
value in animal contests. Animal Behaviour.
———. 2009. Assessment of fighting ability in animal contests. Animal Behaviour.
Bakker, T. C. M., E. F. Bruijn, and P. Sevenster. 1989. Asymmetrical Effects of Prior Winning and
Losing on Dominance in Sticklebacks (Gasterosteus aculeatus). Ethology 82.
Beacham, J. L. 1988. The relative importance of body size and aggressive experience as
determinants of dominance in pumpkinseed sunfish, Lepomis gibbosus. Animal Behaviour 36.
Becker, E. A., and C. A. Marler. 2015. Postcontest blockade of dopamine receptors inhibits
development of the winner effect in the California Mouse (Peromyscus californicus). Behavioral
Neuroscience 129.
Bierbach, D., M. Klein, V. Sassmannshausen, I. Schlupp, R. Riesch, J. Parzefall, and M. Plath.
2012. Divergent Evolution of Male Aggressive Behaviour: Another Reproductive Isolation
Barrier in Extremophile Poeciliid Fishes? International Journal of Evolutionary Biology 2012.
Bonabeau, E., G. Theraulaz, and J. L. Deneubourg. 1996. Mathematical model of self-organizing
hierarchies in animal societies. Bulletin of Mathematical Biology 58.
———. 1999. Dominance orders in animal societies: The self-organization hypothesis revisited.
Bulletin of Mathematical Biology 61.
Briffa, M., L. U. Sneddon, and A. J. Wilson. 2015. Animal personality as a cause and
consequence of contest behaviour. Biology Letters 11.
Chase, I. D., C. Bartolomeo, and L. A. Dugatkin. 1994. Aggressive interactions and inter-contest
interval: How long do winners keep winning? Animal Behaviour 48.
Chase, I. D., D. Coelho, W. Lee, K. Mueller, and J. P. Curley. 2022. Networks never rest: An
investigation of network evolution in three species of animals. Social Networks 68.
Chase, I. D., C. Tovey, D. Spangler-Martin, and M. Manfredonia. 2002. Individual differences
versus social dynamics in the formation of animal dominance hierarchies. Proceedings of the
National Academy of Sciences of the United States of America 99.
Cordero, M. I., and C. Sandi. 2007. Stress Amplifies Memory for Social Hierarchy. Frontiers in
Neuroscience 1.
Dewsbury, D. A. 1988. Copulatory Behavior as Courtship Communication. Ethology.
Drews, C. 1993. The concept and definition of dominance in animal behaviour. Behaviour 125.
Dugatkin, L. A. 1997. Winner and loser effects and the structure of dominance hierarchies.
Behavioral Ecology 8.
Ellis, L. 1995. Dominance and reproductive success among nonhuman animals: A cross-species
comparison. Ethology and Sociobiology 16.
Enquist, M., and O. Leimar. 1983. Evolution of fighting behaviour: Decision rules and
assessment of relative strength. Journal of Theoretical Biology 102.
Fawcett, T. W., and R. A. Johnstone. 2010. Learning your own strength: Winner and loser effects
should change with age and experience. Proceedings of the Royal Society B: Biological Sciences
277.
Francis, R. C. 1990. Temperament in a Fish: A Longitudinal Study of the Development of
Individual Differences in Aggression and Social Rank in the Midas Cichlid. Ethology 86.

Fuxjager, M. J., and C. A. Marler. 2010. How and why the winner effect forms: Influences of
contest environment and species differences. Behavioral Ecology 21.
Fuxjager, M. J., J. L. Montgomery, and C. A. Marler. 2011*a*. Species differences in the winner
effect disappear in response to post-victory testosterone manipulations. Proceedings of the
Royal Society B: Biological Sciences 278.
Fuxjager, M. J., T. O. Oyegbile, and C. A. Marler. 2011*b*. Independent and additive contributions
of postvictory testosterone and social experience to the development of the winner effect.
Endocrinology 152.
Goetz, S. M. M., L. Tang, M. E. Thomason, M. P. Diamond, A. R. Hariri, and J. M. Carré. 2014.
Testosterone rapidly increases neural reactivity to threat in healthy men: A novel two-step
pharmacological challenge paradigm. Biological Psychiatry 76.
Goubault, M., and M. Decuignière. 2012. Previous experience and contest outcome: Winner
effects persist in absence of evident loser effects in a parasitoid wasp. American Naturalist 180.
Graham, Z. A., and M. J. Angilletta. 2020. Claw size predicts dominance within and between
invasive species of crayfish. Animal Behaviour 166.
Hemelrijk, C. K. 2000. Towards the integration of social dominance and spatial structure. Animal
Behaviour 59.
———. 2002. Despotic societies, sexual attraction and the emergence of male "tolerance": An
agent-based model. Behaviour 139.
Hickey, J., and J. Davidsen. 2019. Self-organization and time-stability of social hierarchies. PLoS
ONE 14.
Hock, K., and R. Huber. 2006. Modeling the acquisition of social rank in crayfish: Winner and
loser effects and self-structuring properties. Behaviour 143.
Holekamp, K. E., and E. D. Strauss. 2016. Aggression and dominance: an interdisciplinary
overview. Current Opinion in Behavioral Sciences.
Hsu, Y., R. L. Earley, and L. L. Wolf. 2006. Modulation of aggressive behaviour by fighting
experience: Mechanisms and contest outcomes. Biological Reviews of the Cambridge
Philosophical Society.
Hsu, Y., S. P. Lee, M. H. Chen, S. Y. Yang, and K. C. Cheng. 2008. Switching assessment strategy
during a contest: fighting in killifish Kryptolebias marmoratus. Animal Behaviour 75.
Hu, S. W., Y. T. Yang, Y. Sun, Y. P. Zhan, and Y. Zhu. 2020. Serotonin Signals Overcome Loser
Mentality in Drosophila. iScience 23.
Huang, S. P., S. Y. Yang, and Y. Hsu. 2011. Persistence of Winner and Loser Effects Depends on
the Behaviour Measured. Ethology 117.
Ibuchi, K., and T. Nagayama. 2021. Opposing effects of dopamine on agonistic behaviour in
crayfish. Journal of Experimental Biology 224.
Jackson, W. M., and R. L. Winnegrad. 1988. Linearity in dominance hierarchies: a second look at
the individual attributes model. Animal Behaviour 36.
Johnsson, J. I. 1997. Individual recognition affects aggression and dominance relations in
rainbow trout, Oncorhynchus mykiss. Ethology 103.
Kura, K., M. Broom, and A. Kandler. 2016. A Game-Theoretical Winner and Loser Model of
Dominance Hierarchy Formation. Bulletin of Mathematical Biology 78.
Lan, Y. T., and Y. Hsu. 2011. Prior contest experience exerts a long-term influence on
subsequent winner and loser effects. Frontiers in Zoology 8.

Landau, H. G. 1951. On dominance relations and the structure of animal societies: I. Effect of
inherent characteristics. The Bulletin of Mathematical Biophysics 13.
Laskowski, K. L., M. Wolf, and D. Bierbach. 2016. The making of winners (And losers): How early
dominance interactions determine adult social structure in a clonal fish. Proceedings of the
Royal Society B: Biological Sciences 283.
Leimar, O. 2021. The evolution of social dominance through reinforcement learning. American
Naturalist 197.
Li, C. Y., R. L. Earley, S. P. Huang, and Y. Hsu. 2014. Fighting experience alters brain androgen
receptor expression dependent on testosterone status. Proceedings of the Royal Society B:
Biological Sciences 281.
Lindquist, W. B., and I. D. Chase. 2009. Data-based analysis of winner-loser models of hierarchy
formation in animals. Bulletin of Mathematical Biology.
Luttbeg, B. 1996. A comparative Bayes tactic for mate assessment and choice. Behavioral
Ecology 7.
Maynard Smith, J. 1974. The theory of games and the evolution of animal conflicts. Journal of
Theoretical Biology 47.
McDonald, A. L., N. W. Heimstra, and D. K. Damkot. 1968. Social modification of agonistic
behaviour in fish. Animal Behaviour 16.
McNamara, J. M., R. F. Green, and O. Olsson. 2006. Bayes' theorem and its applications in
animal behaviour. Oikos (Vol. 112).
McNamara, J. M., and O. Leimar. 2020. Game theory in biology: concepts and frontiers. Oxford
University Press, Oxford, UK.
Mesterton-Gibbons, M. 1999. On the evolution of pure winner and loser effects: A game-
theoretic model. Bulletin of Mathematical Biology 61.
Mesterton-Gibbons, M., Y. Dai, and M. Goubault. 2016. Modeling the evolution of winner and
loser effects: A survey and prospectus. Mathematical Biosciences.
Momohara, Y., H. Minami, A. Kanai, and T. Nagayama. 2016. Role of cAMP signalling in winner
and loser effects in crayfish agonistic encounters. European Journal of Neuroscience 44.
O'Connor, C. M., A. R. Reddon, I. Y. Ligocki, J. K. Hellmann, K. A. Garvy, S. E. Marsh-Rollo, I. M.
Hamilton, et al. 2015. Motivation but not body size influences territorial contest dynamics in a
wild cichlid fish. Animal Behaviour 107.
Okasha, S. 2013. The evolution of Bayesian updating. Philosophy of Science 80.
Olsson, O. 2006. Decisions under uncertainty: Bayesian foraging - A meeting held at Lund
University in August 2003. Oikos (Vol. 112).
Parker, G. A. 1974. Assessment strategy and the evolution of animal conflicts. Journal of
theoretical Biology 47:223–243.
Rowell, T. E. 1974. The concept of social dominance. Behavioral Biology 11.
Rutte, C., M. Taborsky, and M. W. G. Brinkhof. 2006. What sets the odds of winning and losing?
Trends in Ecology and Evolution 21.
Schlinger, B. A., B. Palter, and G. V. Callard. 1987. A method to quantify aggressiveness in
Japanese quail (Coturnix c. japonica). Physiology and Behavior 40.
Shizuka, D., and D. B. McDonald. 2015. The network motif architecture of dominance
hierarchies. Journal of the Royal Society Interface 12.

Simons, N. D., V. Michopoulos, M. Wilson, L. B. Barreiro, and J. Tung. 2022. Agonism and
grooming behaviour explain social status effects on physiology and gene regulation in rhesus
macaques. Philosophical Transactions of the Royal Society B: Biological Sciences 377.
Smith, J. M., and G. A. Parker. 1976. The logic of asymmetric contests. Animal Behaviour 24.
Snyder-Mackler, N., J. R. Burger, L. Gaydosh, D. W. Belsky, G. A. Noppert, F. A. Campos, A.
Bartolomucci, et al. 2020. Social determinants of health and survival in humans and other
animals. Science.
Stevenson, P. A., H. A. Hofmann, K. Schoch, and K. Schildberger. 2000. The fight and flight
responses of crickets depleted of biogenic amines. Journal of Neurobiology 43.
Strauss, E. D., A. R. Decasien, G. Galindo, E. A. Hobson, D. Shizuka, and J. P. Curley. 2022.
DomArchive: a century of published dominance data. Philosophical Transactions of the Royal
Society B: Biological Sciences 377.
Tibbetts, E. A., J. Pardo-Sanchez, and C. Weise. 2022. The establishment and maintenance of
dominance hierarchies. Philosophical Transactions of the Royal Society B: Biological Sciences
377.
Van Doorn, G. S., G. M. Hengeveld, and F. J. Weissing. 2003. The evolution of social dominance
I: Two-player models. Behaviour 140.
Whitehouse, M. E. A. 1997. Experience influences male-male contests in the spider Argyrodes
antipodiana (Theridiidae: Araneae). Animal Behaviour 53.
Winberg, S., and P. O. Thörnqvist. 2016. Role of brain serotonin in modulating fish behavior.
Current Zoology 62.
1358