1   **Bayesian updating for self-assessment explains social dominance and winner-loser effects**
2
Abstract

In animal contests, winners of previous contests often keep winning and losers keep losing.
These so-called 'winner-loser effects', can have dramatic impacts on future contests and seem
to play a key role in stabilizing the resulting dominance hierarchies. However, the cognitive
mechanisms through which these effects occur are unknown. Winner-loser effects are often
accompanied by a change in the aggressiveness of experienced individuals, which suggests
individuals may be adjusting their self-assessment of their abilities based on this newly gained
information. This updating of a prior estimate is ideally described by Bayesian updating. Here
we show that Bayesian updating provides a mechanism to explain why winner-loser effects
occur and makes clear predictions for the behavior of individuals and social groups. We
implement an agent-based model to compare Bayesian updating to other possible strategies.
We first show that Bayesian updating reproduces empirical results of the behavior of
individuals and groups in dominance interactions. We then provide a series of testable
predictions that can be used in future empirical work to distinguish Bayesian updating from
other potential mechanisms. Our work demonstrates the utility of Bayesian updating as a
mechanism to explain and ultimately predict changes in behavior after salient social
experiences.

20
21

Introduction

Nearly all social groups have measurable dominance hierarchies (Ellis 1995; Shizuka and McDonald 2015; Strauss et al. 2022). These hierarchies can be defined by consistent imbalances in pair-wise aggression and subordination (Rowell 1974; Drews 1993). In the simplest cases, dominance relationships are a measure of contest ability, with the stronger or otherwise more competitive individuals consistently winning over weaker ones. If all outcomes were determined by the intrinsic ability to win a fight (Parker 1974) then dominance hierarchies would be perfectly linear and predictable. And while dominance hierarchies are typically very stable and more linear than would be predicted by chance, dominance outcomes, both in terms of individual contests and the overall positioning of particular individuals within the hierarchy, are often unpredictable (Landau 1951; Chase et al. 2002, 2022). This is because contest outcomes can be stochastic [reviewed in (Strauss et al. 2022)], and are influenced by a combination of factors, including motivation (Arnott and Elwood 2008; O'Connor et al. 2015), strategy (Parker 1974), individual state (Goetz et al. 2014; Li et al. 2014; Holekamp and Strauss 2016), and most importantly, social feedback and previous experiences (Chase et al. 2002).). This dichotomy—often unpredictable but unusually stable outcomes—highlights the gap between our current understanding of the mechanisms of dominance and the reality of natural systems. Despite the importance of social dominance for individual and group outcomes (Dewsbury 1988; Snyder-Mackler et al. 2020; Simons et al. 2022), we still lack models that can predict the formation of dominance hierarchies over time by incorporating the additional social mechanisms that reinforce or even supersede differences in intrinsic resource holding potential (Chase et al. 2002; Tibbetts et al. 2022).

Winner and loser effects may be one of these social mechanisms determining the linearity and stability of dominance hierarchies (Dugatkin 1997; Bonabeau et al. 1999; Hemelrijk 2002). The winner effect is a widely observed phenomenon where success in one contest leads to increased probability of success in subsequent contests, while the loser effect describes how defeats often lead to more defeats (reviewed in (Hsu et al. 2006)). Although these two phenomena are similar, prior work has shown the loser effect tends to be stronger than the winner effect [reviewed in (Rutte et al. 2006)], and in some systems the winner effect has been shown to occur without an accompanying loser effect (and vice versa) [(McDonald et al. 1968; Goubault and Decuignière 2012) reviewed in (Hsu et al. 2006)]. In general, unless otherwise specified, we will discuss winner-loser effects together.

While winner and loser effects can be impacted by changes in individual contest potential or opponent behavior, experiments tend to control for these effects such that changes in contest outcomes appear to be largely driven by a change in an individual's aggressive behavior [reviewed in Hsu, 2006]. This change in aggression suggests that individuals are modifying their self-assessment of their chances of winning in future contests based on the outcome of their current contest (Rutte et al. 2006). While some studies have linked changes in androgens and serotonin to winner-loser effects, the mechanisms behind post-fight shifts in behavior, as well as the broader evolutionary explanation of why changing behavior might be selected for, remain largely unknown. This fundamental gap in knowledge is further illustrated by the

conflicting empirical evidence on the duration of winner/loser effects. Winner-loser effects are
typically observed as relatively short-term phenomena, lasting a limited time (i.e., minutes to
days) (Chase et al. 1994; Johnsson 1997) or until some external disruption occurs (Stevenson et
al. 2000). However, some studies have found persistent winner/loser effects influencing
behavior up to months after the initial conflict (Lan and Hsu 2011; Laskowski et al. 2016;
Momohara et al. 2016). A clear understanding of the mechanisms explaining the cognitive
changes that occur following contests could help reconcile these seemingly disparate results
and allow us to better predict how winner-loser effects determine later contest outcomes.
74
Early theoretical work regarding winner-loser effects focused on whether their existence was
sufficient to explain the observed linearity of dominance hierarchies [reviewed in (Lindquist and
Chase 2009)]. These models generally use a linear shift in estimate (and/or ability), in which
after a contest, individuals' estimated (or actual) fight potentials increase by some fixed
amount, (e.g., (Dugatkin 1997; Bonabeau et al. 1999)). This approach continues to be used in
more recent models (e.g., (Hickey and Davidsen 2019)), though other models have developed
more complex methods of contest assessment ((Hemelrijk 2002; Van Doorn et al. 2003; Hock
and Huber 2006)). While these models are useful in exploring the impacts of winner-loser
effects generally, they were not designed to identify the mechanisms of these effects, nor make
specific predictions on animal behavior. Critically for mathematical ease, these models have
typically conflated self-assessment and contest ability. However, empirical data show that
winners and losers typically change their aggressiveness in subsequent fights suggesting that
self-assessment alone may be sufficient to describe winner-loser effects, and we wanted a
model which could isolate the effect of self-assessment. Second, some models have relied on
complex learning algorithms for the agents, requiring perfect knowledge of opponent history.
We sought to find a simpler and perhaps more biologically plausible mechanism to explain the
persistence of winner-loser effects.
92
Bayesian updating provides the optimal modeling framework to explain winner/loser effects: it
depends solely on changes in individual assessment and existing empirical research suggests
that many animals use Bayesian processes to make decisions in other contexts [[McNamara et
al, 2006, Okasha 2013, Olsson 2006, Luttbeg 1996). In brief, Bayesian updating provides a
precise mathematical framework to modify an existing estimate of the state of the world based
on new information (McNamara, 2006). Despite being ideally suited to calculate self-
assessment of individual ability following a contest (as noted by (Whitehouse 1997)), to our
knowledge, there is no model that treats winner-loser effects as a process of Bayesian learning.
This is surprising, because Bayesian updating can account for both the *how* and the *why* of
winner-loser effects: Under Bayesian updating, winner-loser effects are an expected side-effect
of the central process of animals assessing and establishing their social status. Given the
potential power of this hypothesis, it is important to identify the predictions of a Bayesian
model and understand how we might distinguish Bayesian updating from alternative
mechanisms.
107
Here, we present an agent-based model of winner-loser effects—and dominance formation
generally—as a process of Bayesian updating. In brief, individual agents with self-assessed

contest ability compete to win social contests, after which each agent uses Bayesian updating
to modify their estimate of their own contest ability, to better determine how much to invest in
future contests. The purposes of this model were to first, explore the features and limitations of
Bayesian updating as it relates to winner-loser effects, to show whether such a framework is
plausible. To do so, we test whether it recreates known empirical features of dominance
hierarchies, which tend to be linear and stable, as well as the recency biases of winner/loser
effects and the higher relative strength of loser effects as shown in the empirical literature. Our
second goal was to identify testable predictions that could empirically distinguish Bayesian
updating from alternative mechanisms of dominance establishment and winner-loser effects.
Here, we focus on measurable attributes of fights, such as fight intensity and duration and
compare these measures across staged contests where the agents use either Bayesian updating
or other updating mechanisms like linear shifts in self-assessment [as in (Dugatkin 1997)
(Bonabeau et al. 1999), or a fixed estimate, in which no change in self-assessment occurs. We
show that Bayesian updating can reconcile disparate empirical observations of the attributes of
winner/loser effects, while laying out clear, testable predictions that can be used in future
experiments to identify the mechanisms by which dominance is established.
126

129   *Figure 1: Graphical overview of conceptual framework. **Top left**, Individuals with fixed size*
130   *(unknown to self) and an estimated self-assessment are paired randomly. **Top right**, each*
131   *individual estimates their own and opponent's size to determine their effort, based on their*
132   *estimated probability of winning. **Bottom right**, the size and effort of each agent determines*

their relative wagers, based on the relative size and effort of the smaller individual. The relative
wager of the smaller individual determines the probability of winning (calculated as the
probability of an upset by the underdog in a given contest). The outcome is determined by
*whether a randomly generated value is below this probability. **Bottom left**, based on this*
probabilistic outcome, agents update their self-assessment, multiplying their prior assessment
by the calculated likelihood of the observed outcome, summed across all possible sizes. This
process is repeated many times for all possible pairings to allow dominance hierarchies to
emerge.

General approach

We envision a scenario where a group of animals compete for dominance in war of attrition contests. In our case, we imagine a group of fish of varying size, but individual agents could represent any species (mice, humans, etc.) competing in a fixed social group where there is uncertainty around one's own and their competitor's contest abilities. Our model consists of four steps, described graphically in Figure 1. First, we generate a group of Agents with random (normally distributed) intrinsic ability and imperfect self-assessments of that ability, which we call their 'estimates' (Fig 1, top-left). For simplicity, we will refer to the intrinsic ability as "*size*", although in most natural systems other factors also contribute. Second, these agents are randomly paired and allowed to interact. In each contest, they select their effort, based on their estimated probability of winning which is based on their existing self-assessment of their size (Fig 1, top-right). Third, contest outcomes are determined probabilistically based the relative size and effort of each participant (Fig 1, bottom-right). Finally, following the contest, each agent updates their estimate (i.e., their self-assessment) based on their prior estimate of size and their estimated likelihood of the observed outcome (Fig 1, bottom-left). This process is then repeated. Each step of the model is described in detail below.

Table of Abbreviations:

Symbol	Default	Range	Explanation
$x : (x, x_i, x_o, \bar{x}_i)$	Random	$1 \leq x \leq 100$	Size of an individual. x_i represents actual size for individual i, while x_o is the actual size of opponent. $\bar{x}$ denotes an estimated size
μ_x	50	$1 \leq x \leq 100$	The mean of the population from which individuals are drawn
σ_x	10	$0 \leq \sigma_x < \infty$	Standard deviation of population from which individuals are drawn. At $\sigma = \infty$, uniform distribution is used.
$v : (v, v_i, v_o)$	None	$0 \leq v \leq 1$	Effort, i.e., the amount of time/energy invested in a contest. As with size, subscripts distinguish effort by the focal individual v_i from their opponent's, v_o
$w : (w, w, w)$	None	$0 \leq w \leq 1$	Wager, or the time/energy invested in a contest, scaled by the size of the agent. This could also be thought of as work, i.e., the amount of energy imposed on opponent.
s	1	$0 \leq s < \infty$	Relative size dampener, acts as an exponent such that as s increases, so does the importance of relative size

f	1	$0 \leq f < \infty$	Effort dampener. Acts as an exponent, such that as f increases, so does marginal benefit of increased effort relative to the opponent
l	13	$0 \leq l < \infty$	Relative wager dampener, essentially the importance of luck, acting as an exponent on relative wager, such that as l increases, the probability of upsets decreases
σ_a	10	$0 \leq \sigma_a < \infty$	*awareness*, the accuracy of individuals' starting guesses for their self-assessment.
σ_c	10	$0 \leq \sigma_c < \infty$	*acuity*, the accuracy of individuals when guessing the size of opponents prior to contests
$P(\theta)$	-	-	Used to denote the prior, an estimated, discrete distribution of the probability of being some size.
Φ	-	-	Standard notation to denote the cumulative distribution function used to calculate confidence
p	1.1	$0 \leq x \leq 100$	Proportional shift after a contest, used in linear updating
k	0	$0 \leq x \leq 100$	Constant shift after a contest, used in linear updating
r	10	$1 \leq x < \infty$	Proportional shift after a contest, used in linear updating

163 Generation of agents

164 In order to model the development of self-assessment for each iteration, we first randomly
165 generated agents with some intrinsic win potential, called *size*, drawn from a normal
166 distribution, such that

168
$$x_i \sim N(\mu_x, \sigma_x) \tag{1}$$

170 Each agent had an estimate of their own size, $\bar{x}$, formed by drawing from a normal distribution
171 centered around their actual size:

173
$$\bar{x}_i \sim N(x_i, \sigma_a) \tag{2a}$$

175   where σ_a reflects individual *awareness*, i.e., the precision with which they can estimate their
176 own size. Individuals then calculated a starting prior as a normal distribution centered on their
177 estimate, with standard deviation, $\sigma_\theta = \sigma_a$,

179
$$P_r(\theta) = N(\bar{x}_i, \sigma_\theta) \tag{2b}$$

181 In addition to their estimate of size, all agents had an effort strategy and an estimate updating
182 strategy, which we explain below. Groups of *n* simulated agents were paired across *r* rounds of

183 (*n-1*) contests, such that in every round, every agent faced every other agent, for a total of (*n-1*
184 ** r*) contests, with the order of contests being shuffled for each round.
185
Effort strategy
The purpose of our model was to explore updating strategies, but in order to do this, we
needed to establish how agents would determine their *effort* in a contest, v_i, representing the
amount of time/energy an animal spends on a contest before yielding. Empirical observations
[Hsu et al, 2008] and theory [Maynard Smith & Parker, 1976; Enquist & Leimar, 1983] suggest
that individual effort should be proportional to their potential to win, so we designed the effort
strategy to match this. To determine their effort, each agent first estimated the size of their
opponent, by drawing their estimate of opponent size, $\bar{x}_o$, from a normal distribution centered
on their opponent's true size, and standard deviation reflecting their *acuity, σ_c, i.e., the*
precision of that assessment,
196
197 $$\bar{x}_o \sim N(x_o, \sigma_c) \tag{3a}$$
198
199 Agents then set their effort, v_i, based on their estimated probability of winning, such that
200
201 $$v_i = P(win\,|\bar{x}_i, \bar{x}_o) * P(x_i \geq 0.9x_o) \tag{3b}$$
202
203 Here effort, v_i, is equal to the conditional probability of winning—given an agent's estimates
204 about their own and their opponent's sizes—multiplied by their estimated probability that their
205 size is within 10% of their opponent's size (calculated using the confidence of these respective
206 distributions, see Eq. 3d)
207
208 Because the probability of winning is a function of the relative size of the smaller individual, in
209 equation 3b, the probability of winning $P(win\,|\bar{x}_i, \bar{x}_o)$ varies depending on whether an agent
210 estimates itself to be bigger or smaller than its opponent,
211
212 $$\tag{3c}$$

213 $$v_i = \left(\frac{\bar{x}_i}{\bar{x}_o}\right)^{sl} * P(\bar{x}_i \geq 0.9\bar{x}_o), \qquad if\ \bar{x}_i \leq \bar{x}_o$$
214 $$v_i = \left[1 - \left(\frac{\bar{x}_o}{\bar{x}_i}\right)^{sl}\right] * P(\bar{x}_i \geq 0.9\bar{x}_o), \qquad if\ \bar{x}_i > \bar{x}_o$$

215
where, s and l are simulation parameters used in several equations to account for the influence
of *relative size* and *luck* respectively, on contest outcomes. Here, *luck* means how close the two
agents' respective sizes and efforts need to be for there to be a reasonable probability of upset.
Although the actual probability of winning depends on both relative size and individual effort
(see contest calculation below), with this effort strategy, agents approximate the probability of
winning by assuming that both they and their opponent will invest the same amount in the
contest.
223

The second term in Eq. 3b and 3c, $P(\bar{x}_i \geq 0.9\bar{x}_o)$, accounts for the confidence of an individual's estimates, calculated as the probability that the individual is within at least 10% of the opponent size using a cumulative distribution function of the combined normal distributions:

$$P(x_i \geq 0.9x_o) = \Phi_{\mu_\delta, \sigma_\delta}(-0.1 * x_o) \tag{3d}$$

Because an agent's estimates of both their own size and opponent size are represented by normal distributions, these two distributions can be combined to calculate a new normal distribution representing the probability density of the difference in their sizes, where the new mean, μ_δ, represents the estimated difference in size $(\bar{x}_i - \bar{x}_o)$, and σ_δ is the sum of the standard deviations of the component distributions, i.e., *acuity* and *awareness*, $(\sigma_c + \sigma_a)$. In Equation 3d above, to calculate the probability that x_i is at least 0.9 times the size of x_o, agents use the cumulative distribution function, i.e., the sum of the probability over a set range of their size estimate distribution.

Determining contest outcome

For a given contest, the winner was decided probabilistically (Figure 1, bottom right), based on the relative size and effort of each agent, combined to define each agent's *wager*, w_i:

$$w_i = \left(\frac{x_i}{x_{max}}\right)^s * v_i^f \tag{4a}$$

Wager, w_i, and *effort*, v_i as terms are quite similar. It may be useful to think of wager in physical terms as *work*, i.e., the amount of energy imposed on the opponent, and effort as *vigor*, or the amount of energy expended by the individual. In other words, the wager scales the individual effort according to their relative size, and the parameters s and f allow us to control the relative importance of *size* and *effort*, respectively. Because these exponents always operate on fractions between 0 and 1, we can conceptualize them as "bias" parameters, where, as they increase, larger inputs (of size or effort) are exponentially more successful than smaller inputs (Supplemental Figure S1a provides further intuition on the behavior of these parameters).

Because in both our model and natural observations, contests are determined by when the subordinate individual yields, and contest success if a function of relative, not absolute, ability, it was convenient to calculate the outcome probability from the perspective of the lower-wagering individual, termed the underdog. We thus calculated the probability of an upset (a win by the underdog) with

$$P(upset) = \frac{1}{2} * \left(\frac{w_{min}}{w_{max}}\right)^l \tag{4b}$$

where l is a third bias parameter, *luck*, controlling how close the two wagers need to be for there to be a meaningful probability of upset, such that as l increases to infinity, the probability of an upset goes to 0 unless the two wagers are equal.

266
Once $P(upset)$ is established, we use a random number generator to simulate whether an
upset occurs. In this way the agent with greater relative size and effort (termed the *favorite)*
usually won, but the agent with the smaller wager (the underdog) could win, particularly if the
two wagers were close. It is also important to note that the smaller wager was not necessarily
the smaller sized individual; if a relatively smaller agent contributed far higher effort, they could
have the larger wager, w_{max} , and thus be the *favorite* for the purposes of our calculations.
273
This approach to settling contests allowed us to vary the relative contributions of size, effort,
and stochasticity in order to observe how this changed the behavior of the group (i.e., how
much individuals invested in contests, whether dominance relationships were stable, etc.). For
most purposes, we set the values of these bias parameters at s = 5, $e = 1, l = 13$ in order to
match empirical observations (Beacham 1988; Bierbach et al. 2012), that upsets were rare, and
contests were usually predictable based on size (Supplemental Figure S1a).
280
281 Updating self-assessment post contest
282 Here, we compare three possible strategies for updating self-assessment: Bayesian updating,
283 linear updating, and fixed (no updating), each described in detail, by increasing complexity,
284 below.
285
286 Fixed Estimate (No updating)
287 The simplest possible update strategy is to not alter your initial estimate. We modeled this
288 scenario, where we kept each agent's initial estimate of size fixed throughout the simulation,
289 regardless of contest outcomes. In the fixed case, an agent's estimate is their initial guess, x_i,
290 with awareness, σ_a.
291
Linear Updating
A simple way to model estimate updating, (see, e.g., (Dugatkin 1997)), is to either increase or
decrease each agent's self-estimate of their size, using some proportion, p of its prior estimate
and/or adding or subtracting some constant, k. To make this more comparable to our Bayesian
updating approach, we modified this approach to set limits on the maximum and minimum
possible size (X_{min}, X_{max}), such that their new estimate, $\bar{x}_{i_{t+1}}$, was a function of their previous
estimate, shifted by some factor,
299
300 $$\bar{x}_{i_{t+1}} = p\bar{x}_{i_t} + k \tag{5a}$$
301 where
302 $$X_{min} \leq \bar{x}_{i_{t+1}} \leq X_{max} \tag{5b}$$
303
304 The scaling parameters are theoretically unbounded, but to more closely compare to the
305 dynamic shifts of Bayesian updating, in practice we set $k = 0$, and
306 $$p = 0.1 * (X_{max} - \bar{x}_{i_t}), if\ win \tag{5c}$$
307 $$p = -0.1 * (\bar{x}_{i_t} - X_{min}), if\ loss$$
308

309 such that individuals shifted their estimates of their own size as a function of their distance
310 from the maximum or minimum possible size. After updating the mean estimate, we generated
311 a new normal distribution, centered around that estimate, based on their *awareness*, σ_a, as in
312 Eq. 2b.
313
Bayesian updating
In contrast with simple heuristics like linear updating, Bayesian updating attempts to calculate
the true probability of being a given size, based on known/estimated parameters about the
state of the world and the probability of outcomes. In general, Bayesian updating modifies
some *prior* estimate using a *likelihood function*. In our case, the prior is the agent's current
estimate of its own size, modeled as described above as a discrete probability distribution
across all possible sizes. The likelihood function is the probability of the observed outcome (i.e.,
winning a given contest), conditioned on being some assumed size, calculated across all
possible sizes. Thus, for our purposes, the posterior distribution, i.e., the new probability
distribution of an agent's size estimate, θ, is calculated by
324

$$P_{post}(\theta|outcome) = \frac{P(outcome \mid \theta) * P_{prior}(\theta)}{P(outcome)} \qquad (6a)$$

326
We discuss the case of a winning outcome, but the formulation is similar following a loss.
Equation 6a means that to update the probability distribution of size, at each size x, we multiply
the previously estimated probability of being size x by the likelihood of winning the previous
contest at that size. The probabilities of winning, for every possible size, are then divided by the
sum of the probabilities of winning for all size values (i.e., the total probability of winning).
Thus, for each possible size in our discrete size range, the posterior probability of being a given
size is
334

$$P(x_i = x|win) = \frac{P(win|x_i = x) * P(x_i = x)}{P(win)} \qquad (6b)$$

336
337 where, $P(x_i = x)$ is the prior estimate of being a given size, while the likelihood $P(win|x_i =$
338 $x)$ is the probability of an individual of size x winning the previous contest, which is calculated
339 according to the probability of upset from Eq. 4b. Because probability of winning is a function of
340 the relative of the smaller wager, the probability of winning goes from being equal to the
341 probability of upset, to its inverse, once winning is conditioned on having the bigger wager.
342
343
344 $$P(win|x_i = x) = P(upset), if \ w_i| \ x \le w_o \qquad (6c)$$
345 $$P(win|x_i = x) = 1 - P(upset), if \ w_i| \ x > w_o$$
346
Note that there is an inflection point based not on relative size but on relative wager, such that
agents must take into account both their own and their opponent's effort into their calculations
of relative wager, and thus the probability of winning, $P(win)$. For simplicity, we assume that
after the contest, agents have perfect knowledge of the size and effort of the opponent,

however this calculation could be extended to allow for estimated distributions of opponent
size and opponent effort (see Equation S2).
353
354 The prior and likelihood are then divided by the total $P(win)$, which in our case is the sum of
355 prior ∗ likelihood for all possible sizes,
356
$$P(win) = \sum_{x=0}^{x_{max}} P(win|x_i = x) * P(x_i = x) \qquad (6d)$$
358
359 After calculating the posterior estimate, agents update their size estimate, $\bar{x}_i$
360
$$\bar{x}_i = E(\theta) = \sum_{x=1}^{x_{max}} x * P(x_i = x) \qquad (6e)$$
362
363 Where E is the maximum likelihood estimate of the size distribution. Agents then calculate an
364 estimated confidence, σ_θ,
365
$$\sigma_\theta = \sum_{x=1}^{x_{max}} P(x_i = x) * (x - \bar{x}_i)^2 \qquad (6f)$$
367
368 These values are then used to compute their effort in the next contest (using Equation 3c, with
369 the updated σ_θ taking the place of initial awareness, σ_a).
370
Total parameter space
Taken together, our possible parameter space comprises the contest outcome parameters
(s, f, l), reflecting the influence of *size*, *effort*, *luck*; the assessment parameters (σ_a, σ_c),
representing *acuity* and *awareness*; and, for linear updating, the value of the *scalar* and
proportional parameters (k, p). Even with our simplifying assumptions, this represents a
somewhat daunting parameter space, especially since these parameters are theoretically
unbounded. To aid in exploring the parameter space, for the contest and assessment
parameters, which all varied between [0, ∞), we used a scaling function (Supplemental
Equation S1) so that we could input parameters as values between either [1,-1] for (s, f, l)—
such that the inflection point at e.g., $s = 1$ was maintained at the scaled value of 0—and [0,1]
for (σ_a, σ_c). By doing this, it was more straightforward to explore the full range of possible
parameter values.
383
384 Model Analysis
385 The goal of our model was to answer two questions. 1. Does Bayesian updating for self-
386 assessment produce dominance hierarchies that match the behavior of empirical systems? 2.
387 How can we distinguish, empirically, Bayesian updating from alternative models of dominance
388 establishment and winner/loser effects?
389
Our core approach to answering these questions was to run many (e.g., 1000, but see results)
iterations of social simulations while extracting behavioral metrics that would be tractable in
and relevant to an empirical context, such as contest intensity. Because these are simulations,
we were also able to directly inspect the hidden variables (e.g., an agent's actual estimate of

own size) that were driving the behavior. We organize the metrics according to the level of
complexity at which they are observed.
396
397 Agent metrics
398 For each agent, we recorded true intrinsic ability (referred to simply as *size*), as well as their
399 self-assessment—the estimated probability distribution of their size—at every timepoint t, with
400 the calculated mean and variance of the distribution.
401
402 Contest metrics
403 For every contest, we record the outcome, as well as the intensity of the contest, determined
404 by the lower effort, $min(v_i, v_o)$, of the two competitors. We also recorded the effort, v, and
405 wager, w of each agent for each contest.
406
Hierarchy metrics
For the full history of social interactions, we track the linearity, stability, accuracy, and
efficiency of dominance contest interactions. In order to provide network metrics throughout
the simulation, we binned the history of interactions into 3-round sub-histories, using a sliding
window, and calculated metrics both within bins, and (where applicable) across the full history.
Linearity is calculated using Appleby's formula (Appleby 1983), which calculates the proportion
of triads that are transitive. For *stability*, we first calculate binary dominance-subordinance
status for each pairwise relationship, then calculate the proportion of time bins for which the
binary dominance network, calculated within that time bin, matches the binary dominance
network calculated for the entire simulation. For *accuracy*, we calculate ordered dominance,
using an ELO ranking (Albers and De Vries 2001; Neumann et al. 2011), then calculate the
spearman correlation between actual size and dominance rank. For our metric of *efficiency*, we
simply measure the mean intensity of contests within each time bin, where here a time bin was
one round of all pairwise contests.
421
422 Implementation
423 All code was written in python. The random number generator for contest outcome was from
424 the *numpy* library. For ELO ranking we used an *elosports* module (pypi.org/project/elosports).
425 All code and results are available on github (github.com/aperkes/BayesBattleBots).
426
427 <u>Results</u>
428
429 **Part 1: Matching Empirical Observations**
430
<u>1.1 Bayesian updating predicts that the loser effect is stronger than the winner effect.</u>
We first tested whether agents using Bayesian updating experienced winner-loser effects at all.
To do so, we modeled our simulation on empirical approaches by staging a win or loss between
a focal agent and a "treatment" opponent of known size (in this case, the same size as the focal
individual). We then measured whether there was a winner/loser effect by pairing these focal
winners and losers against new "assay" opponents (again size-matched to the focal individual).
We could then quantify the strength of the winner/loser effect as the proportion of focal agents

which won against their second size-matched assay opponent (where no winner-loser effect
would yield 50% wins). Here we found obvious winner-loser effects, in that prior winners were
more likely to win subsequent contests, while prior losers were more likely to lose (Fig 2).
Additionally, consistent with the strong empirical support documenting that the effects of
losing a contest tend to be stronger than the effects of winning a contest, in our model, the
loser effect is significantly stronger (Fig 2). In our model, this phenomenon is driven by two
mechanisms, stemming from the empirically based assumption that contests are determined by
the relative size of the smaller competitor, such that differences in the perceived *relative* sizes
of winners or losers vs their opponents (e.g., 70% vs 50% of the larger agent) will result in
disproportionate outcomes, even if the *absolute* perceived size differences (50:75 vs 25:50) are
the same (see Supplemental Figure S2).
449
450

451
452
453 Figure 2. *A. Loser effects are stronger than winner effects. This plot shows the proportion of*
454 *focal agents (averaged from groups of n=1000) winning against a naïve size-matched fish, after*
455 *experienced either a loss (blue) or a win (gold). The dotted line shows the expected proportion of*
456 *wins (0.5) if this second contest were unbiased. In this context, loser effects are stronger than*
457 *winner effects, measured as the distance from 0.5.*
458
1.2 Bayesian updating produces a recency bias in winner-loser effects
Although winner-loser effects vary across species, there is strong empirical evidence that many
species show a recency bias with the outcomes of more recent contests having a stronger effect
than earlier contests on current behavior. We found that our model recreated these empirical
observations. Again, emulating empirical tests of the winner-loser effect, we simulated contests
between naive, size-matched agents and then paired the subsequent winners and losers
against new, naïve, size-matched individuals. To simplify this simulation, all individual priors
were centered on their true size, and agents correctly assessed opponent size, regardless of
their acuity, σ_c. Focal agent then faced new, size-matched, naive individuals, where each
contest generated a new branch in the focal agent's path. This process was repeated 6 times,

for 1000 individuals to explore all possible outcomes of the sequence of 6 contests. This time,
we measured winner-loser effects directly as the agents' own size estimates. We observed that
winner-loser effects have an experience-dependent recency bias (Figure 3), such that after first
winning a contest and then losing a contest (WL), agents updated their size estimate to be
lower than if they had lost and then won (LW). This recency effect was based on the fact that
the initial losers (LW) won while investing less in their second contest than the initial winners
(WL); the strength of this effect depends on the specific parameters (see Supplemental S.3),
but under all parameters, losing then winning resulted in estimates that are greater than or
equal to winning than losing.
478
479
480

481
482
Figure 3: Divergent experience leads to stochastic formation of self-assessment. Agent self-
assessments are plotted as they compete in repeated contests against naive, size-matched
opponents. Each vertical dotted line represents a contest, with the branching paths showing the
estimates following a win or loss. The boxes note specific experiences (e.g., LW: a loss followed
by a win), highlighting the recency effect, and how the recency effect diminishes with increased
experience. The box outlines are colored to represent the agent's experience, prior to the
penultimate contest. Here, fight parameters are [S,E,L] = [0,0.7,-0.8]
490
<u>1.3 Bayesian updating explains the observed variation in the persistence of winner/loser effects</u>
In empirical observations of dominance contests, winner-loser effects are persistent in some
cases while in others they are short-lived or even non-existent. Here, we find that our model
provides a mechanism through which to reconcile these apparent discrepancies based on the
size of the initial opponent, the number of new events agents experience following this
"treatment" contest, and the method used to assay the strength of the winner effect.
497
We again simulated a forced-win experimental approach, this time allowing a simulated focal
agent of size $x_o = 50$ to win a staged contest against an opponent of variable size ($x_o =$
$(40,50, or\ 60)$. As before, we measured the winner-effect directly, as the agent's own self-
assessment. Following this initial "treatment" contest, focal agents were allowed to interact

with additional naïve individuals to observe how their estimate changed over time. In this
context, it is apparent that the size of the opponent has a strong effect both on both the degree
of the initial shift in self-assessment and how long this boosted estimate persists (Figure 4A),
with additional experiences causing agents' estimates to tend towards their actual size. Exactly
how long the winner effect lasts above some given value is influenced by the nature of these
post-fight experiences (Supplemental Figure S3), but even after 100 contests, our "distant past"
winners' self-assessment was higher than their actual size, and those who won against bigger
opponents had significantly higher self-assessments than those who won over smaller ones.
510
To test whether these differences in self-assessment would be detectable in experimental
contexts, we simulated experiments of varying sample sizes, in which we measured the
performance of these focal winners and losers (i.e., the proportion of fights won) against either
size-matched or smaller opponents. In this context, the size of the assay opponent was critical
(Figure 4B). The "distant-past" winners and losers could be reliably distinguished by comparing
the proportion who won in contests against size-matched individuals. This was true even for
small sample sizes (e.g., 5 winners vs 5 losers). In comparison, if focal agents were tested
against smaller opponents, it was extremely rare to capture any significant difference for
groups smaller than 100.
520
521 Taken together, our model predicts that under Bayesian updating, the observed variation in
522 winner effect duration (and whether it is detected generally) can be ascribed to differences in
523 how the winner effect was generated, the experience of individuals in the interim, and how it is
524 assayed in the subsequent test matches. All of this is consistent with empirical observations
525 that the specific methods used influence whether winner-loser effects are observed.
526

527
528
Figure 4: Strength and persistence of the winner effect is a function of social information and
experimental power. A. This plot shows focal agents' estimates following a staged win against
agents of varying size. The shift in the focal agent's estimate following a win is greater when
their opponent was larger. B. This plot shows the mean estimated winner effect in 1000
simulated experiments, calculated by measuring the difference in win rate for focal winners and
losers against a size-matched agent (black) or a smaller agent (blue), with the dotted lines
showing the standard deviation of estimates.
536

<u>1.4 Bayesian updating produces linear, stable, and efficient dominance networks</u>
Winner-loser effects are important not just for individual behavior but also the formation of
dominance hierarchies. We found that our simulated agents using Bayesian updating recreated
well-known empirical observations patterns of dominance networks. Matching observations of
typical natural dominance hierarchies, we found that our simulated agents recreated stable
linear hierarchies across a range of parameters tested (Supplemental Fig S4). This tendency
toward stabilization was sufficiently strong that groups of agents formed linear dominance
hierarchies even in the absence of size differences (Figure 5b, yellow line). There were certain
edge cases where other outcomes occurred (see Supplemental S4) but linearity was a general
phenomenon across the parameter space. We additionally found that the linearity of
hierarchies of our simulated agents rapidly increased (Fig 5b) while the intensity of contests
decreased (measured as the lower of the two efforts, v_{min}) (Fig 5c). Low intensity contests are
a hallmark of many empirical observations as individuals often seek to avoid serious injury, and
in our simulation, these occurred as the smaller agent in each contest began to recognize that
they were unlikely to win and thus yielded quickly.
552

553
554
*Fig 5: Emergence of stable dominance hierarchy through Bayesian updating. **A. Network***
***stability increases over time.** Each line represents the mean stability across 1000 simulations*
for a given amount of variation in population size (with yellow, $\sigma_x = 0$, where all individuals are
equally sized). Stability is measured by binning the simulation into 3-round windows and
comparing the consistency of dominance rank across bins (calculated using an ELO score).
*Stability tended to increase, particularly where real size differences were low. **B. Linearity of***
***dominance networks increase over time.** As with stability, the linearity, measured as the*
proportion of triads in the dominance network that are transitive, following Appleby's approach.
***C. Contest intensity decreases over time**. Here the mean intensity of fights, measured as the*
effort of the losing individual, decreases with repeated contests as individuals become more
confident in their assessments. Although there was relatively little difference in contest
intensity, based on size variance, more variable populations did have lower intensity contests,
which is to be expected, since assessment is easier when the absolute difference is greater.
568
569
570
571

Part 2. Distinguishing Bayesian updating from other models

We have shown that our Bayesian model is successful at recreating many empirical
observations of animal contests, consistent with the hypothesis that Bayesian updating may be
the mechanism behind winner-loser effects and hierarchy formation. To provide an approach
that can empirically test whether animals are using Bayesian updating, as compared to other
potential mechanisms, we explore two testable predictions of Bayesian updating, based on the
two defining features of Bayesian learning—the likelihood-based updating and the informed
prior. We investigated each of these two aspects separately, with simulated experiments to
model future approaches in animal systems, focusing on measurable contest outcomes within
empirically tractable scenarios.

2.1 The effect of opponent size, but not focal agent experience, distinguishes Bayesian updating
First, we focus on potential updating mechanisms: Bayesian, linear updating, or fixed shifts (no
updating). To test how these different updating mechanisms might be experimentally
distinguished, we simulated contests of focal individuals against treatment opponents of the
full range of possible sizes and then measured the strength of winner-effects using a size-
matched assay opponent match. In this context, we found that the effect of opponent-size on
the strength of the winner effect provides a method to distinguish the different potential
updating mechanisms: agents using Bayesian updating show increases in winner effects when
their initial opponent is larger, whereas these effects are not seen if the agents use linear
updating or fixed shift (Figure 6a). This is in line with the discrepancy effect, which is a well-
known characteristic of Bayesian updating processes whereby more surprising (and therefore
informative) outcomes lead to a more dramatic shift when updating the estimate, whereas
linear updating has no mechanism to incorporate opponent size.

598
599
600 *Figure 6: Simulated experiments show that updating strategy can be distinguished by the effect*
601 *of opponent size and focal agent experience. A. Under Bayesian updating, the strength of the*

winner effect (the proportion of agents winning a size-matched contest after a staged win), is a
function of opponent. B. The strength of the winner effect is also a function of the number of
contests prior to the forced win, however this does not distinguish Bayesian updating from
linear updating. C. The inset table shows the predictions for each updating. approach, with
green checks denoting a predicted significant effect of treatment on the strength of the winner
effect.

We next explored how the updating mechanism used by agents alters the influence of past
experience (i.e., the number of prior contests) on winner-loser effects. To do so, we allowed
simulated focal agents to experience between 0 and 50 fair contests against naïve opponents,
in which the probability of upset determined by size and effort (as described in Equation 4b),
thus creating variation in the extent of each focal agent's experience. We then assessed the
strength of the winner-loser effect by allowing this focal individual to fight against a size-
matched individual in a final test match. In this context, agents using Bayesian updating show
weaker winner effects with greater experience (i.e., more contests, Figure 6b, dotted line). This
is consistent with the 'confidence' effect of Bayesian updating: more experienced individuals
are expected to have more confident priors and thus be less influenced by new information. To
our surprise, this same experience effect was also evident in individuals that were using linear
updating schemes (Figure 6b, dashed line), which appears to be driven by the fact that under
linear updating, estimates tend to diverge over time, being either extremely large or small (see
Supplemental Figure S9). Thus, while an experience effect is a core prediction of Bayesian
updating, and failing to find one would exclude Bayesian updating as a mechanism, finding an
experience-attenuated winner effect does not rule out other possibilities. The discrepancy
effect (i.e., opponent-size) is the most straightforward single test for Bayesian updating.

2.2 Informed prior estimates drive consistent individual and context dependent differences
Often when behaviorists test for whether animals are using Bayesian strategies, they are asking
specifically whether (and how) animals form prior estimates of the general state of the world
and then apply that to a new context, for example the quality of a novel potential mate or some
new foraging patch. In this sense, the question is not about how individuals update their prior
estimate in the moment, but whether animals form prior estimates from past experience and
use them in new contexts. With this in mind, we simulated experiments that would allow us to
distinguish whether individuals had informed priors, independent of their updating strategy
after a contest, and what information these priors were based on.

To do this, we first simulated agents that used one of four sources to form their prior own-size
estimate: 1. An uninformed prior, the uniform distribution; 2. a mis-informed prior, a normal
distribution centered on a uniformly random variable; 3. A self-informed prior, a normal
distribution where mu approximated the agents size (See Equation 2a & 2b), or a peer-
informed prior, a distribution that reflected the distribution of nearby agents (which we set to
be either all large or all small). Of these, (3) and (4) both represent "informed" priors.

We then conducted simulated experiments in which we measured contest intensity—which in
an empirical context could be quantified as the time spent in aggressive behaviors (Schlinger et

al. 1987; Francis 1990)—among individuals using these different prior estimation methods.
Each simulated agent was assayed 3 times, each time against a different, naïve size-matched
opponent (drawn from the same prior method group). Because we had 3 trials for each agent,
we could measure both persistent individual differences and context-dependent variation in
the amount of time agents spent before yielding (i.e., *effort*). We allowed agents to update
their estimates after each contest, but results were not dependent on the updating strategy.
652
In these simulated experiments, we found key differences in aggressive behavior which
successfully characterized groups based on the source of their prior (Figure 7). Specifically, in
groups of individuals using either self-informed or mis-informed priors, there were consistent
individual differences in contest effort (i.e., significant variation within the group based on
individual). Peer-informed agents could show individual differences if these agents were drawn
from different peer groups (small peers vs large peers) but did not show differences when
drawn from the same peer group (small peers vs small peers). In self-informed agents only, the
individual variation in effort correlated with own-size, while in peer-informed agents (drawn
from different groups) variation in effort correlated with peer size. Thus, by controlling for peer
group and characterizing individual size and effort, it is possible to identify whether individuals
form prior estimates and, if so, what information they use to inform these estimates.
664

665
666
Figure 7: Agent behavior reveals the information agents used to form prior Top: Contest
intensity measured for 5 different simulated groups, each using a different starting prior. The
two left-most populations have "uninformed" prior, either with all individuals having a uniform
prior, or each individual having their own randomly selected prior. In the right three groups,
individuals have "informed" prior, using either internal information (central cluster, blue) or
external information (two rightmost clusters). Black lines show the best fit line between effort
and size for each population. The inset table shows, for each group, which effects are predicted
to be significant for contest effort (green check).
675

Discussion
Here, we show that Bayesian updating can explain the existence of winner and loser effects
resulting in contest behavior and dominance hierarchies that are consistent with those
observed in natural social systems. More importantly, our model provides testable predictions
to evaluate whether species' behavior is consistent with Bayesian updating for self-assessment.
Our main findings here lay the groundwork for future work, both empirical and theoretical, in
understanding the biological drivers of social dominance and the winner and loser effects.
683
Our model broadly matches the known features of dominance interactions and winner-loser
effects. Empirical observations vary with regard to the existence of winner-loser effects, how
long those effects last when they are found, as well as the relative strength of winning or losing
on future contest outcomes, but our model shows that the properties of Bayesian updating
provide a mechanism that can reconcile the disparate results seen in the empirical literature.
We show that the strength and duration of winner/loser effects follow directly from the
information given to the individual before, during, and after the contest. This provides an
important framework for interpreting existing winner-loser effect results, as well as planning
future experiments.
693
In our model, varying the amount of information given to the individual is enough to match the
strength and persistence of winner/loser effects to any given values, but it is likely there are
additional mechanisms that could be added to our model to better match empirical
observations of social dynamics. One obvious expansion would be to allow individual ability
(*size*) to vary over short and long timescales. In our model, we deliberately kept agent size fixed
in order to focus on the importance of their self-assessment, but in nature, contests use energy
and often yield new resources and/or territory, all of which alter an individual's short- and long-
term contest potential. Physiologically, there are also multiple cascades of "fight or flight"
neuro-endocrine responses that are activated during a contest and in response to wins and
losses, and the metabolic state of the individual likely changes independent of any permanent
change in self-assessment. These processes add short- and long-term uncertainty as to the
state of an individual and thus the probability of winning a contest. All of this could be
incorporated into our Bayesian framework, by allowing *size* to vary over short and long
timescales in response to contests and allowing agents to maintain both "current" and
"average" estimates of their self-assessed contest ability which are updated according to new
information. This would allow us to explore how this added uncertainty changes the value of
Bayesian updating.
711
A second important addition would be to allow individuals to gather more information from
contests between peers. While our model generated social networks that function similar to
those observed in nature, our agents were only maintaining estimates about their own size and
did not attempt to "remember" any information about opponents. Empirical work has shown
that in most animal societies, individuals are keenly aware of the social interactions happening
around them, and that allowing individuals to observe contests reinforces linearity and
produces dynamics that cannot be experimentally replicated with the "round robin"
tournaments on which our model is based (Lindquist and Chase 2009). While social

eavesdropping and individual recognition increase the complexity of the model, these could
easily be incorporated as additional Bayesian priors which agents update and incorporate into
their decisions, and doing so would make it possible to make predictions for how access to both
intrinsic and social information, as well as individual recognition, changes the behavior of social
networks.
725
An implicit assumption in most discussions of "the" winner-loser effect is that there is a single
"effect" of winning or losing; however, it is far more likely there are multiple effects that occur
across different timescales. The existence of Bayesian updating for self-assessment does not
rule out other concurrent mechanisms, like rapid changes in metabolism due to fight-flight
responses, however Bayesian updating does provide an intuitive and powerful explanation for a
wide range of variation observed in animal behavior, which can be scaled to include multiple
processes that occur over both short and long timespans. Given that Bayesian updating is the
most accurate possible approach to improve an estimate in the face of uncertainty, Bayesian
updating can serve as useful null hypothesis for any repeated behavior, allowing us to make
both general and specific predictions for how individuals and groups behave over time, as we
have shown here with our predictions that past experience or contest information (i.e.,
intensity) should impact the strength and persistence of winner-loser effects. To our
knowledge, there is no existing empirical work testing how these factors impact behavior in
social contests, providing several possible directions for future experiments. By developing and
testing Bayesian models for social behavior, we can better identify the mechanisms behind not
just winner-loser effects specifically, but social interactions generally, in order to better
understand and predict the formation and maintenance of social networks.
743

744 **Supplemental PDF**
745
746 S.1 Contest parameter intuition
747
748 As described in the methods are settled by based on relative wager (Eq) where wager is a
749 function of relative size and effort, each raised to an exponent between 0 and infinity. In order
750 to explore the parameter space more evenly, we use a scaling function
751

$$l = \cot\left(\frac{(L+1)}{2} * \frac{\pi}{2}\right), -1 \leq L \leq 1 \tag{S1}$$

753
This effectively maps $L = 1$ to $l = 0$, L = 0 to $l = 1$, and $L = -1$ to $l = \infty$, as shown in Figure
S1a. We can think of these parameters as magnifying or flattening differences in the different
aspects of wager, which varies the importance of these aspects. To help illustrate this, we
simulated a contest between two fish, one larger ($x_i = 60$) but low effort ($v_i = 0.3$), another
smaller ($x_j = 50$) but high effort ($v_j = 0.6$). When s is large, the larger agent tends to win, when
f is large, the higher investing agent tends to win, and as l increases, the bias against the
"underdog" increases.
761
762

763
764
Supplemental Figure S1: Contest parameters. Panel A shows how relative size, effort, and
relative wagers are scaled based on the value of s,f or l, respectively. Here again we use
Equation S1 to scale parameters, such that 1 represents s^0 while -1 represents s^∞. Panel B
shows the probability of a larger fish (size=60, effort=0.3) winning against a smaller, smaller
competitor investing greater effort (size=50,effort = 0.6). Axes move evenly from -1 to 1 in the
scaled parameter space (Supplemental Equation S1).
771
772
773

774
775
<u>S.2 Understanding why the loser effect is stronger</u>
To illustrate why the loser effect is stronger, we will first examine this simplified scenario
where, following a size-matched contest, 50cm individuals either increase or decrease their
estimate of their own size by 25cm, based on winning or losing, respectively. For simplicity in
exploring the effect of effort, we assume here that the probability of winning, $P(win)$ is strictly
equal to relative effort, $\frac{v_{min}}{v_{max}}$. As Figure 4b illustrates, after the staged contest, the perceived
probability of winning a new contest against a naïve, size-matched individual is 25% for the
loser and 67% for the winner (The probability for a naïve agent would be 50%). Here, assuming
their effort is simply equal to their perceived relative size, we see that the loser decreases their
effort by 0.25, while the winner only increases their effort by 0.17, thus the loser will have a
relatively lower wager ($w_{rel} = 0.5$) against a naïve opponent, than that same opponent would
have against a winner ($w_{rel} = 0.\bar{6}$). In other words, equal (but opposite) shifts in absolute size
estimates lead to unequal shifts in perceived relative size, leading to different relative effort,
and thus different relative outcomes, for winners versus losers.
790
This relative effort effect is sufficient to drive differences in the winner and loser effect, but
Bayesian updating further increases the relative strength of the loser effect due to asymmetry
in likelihood functions across the range of relative sizes. As a reminder, when calculating
likelihood functions, agents calculate their probability of winning against an opponent of fixed
size, x_o, for all possible values of their own size, x_i. Here, to highlight size effects, we assume
likelihood of winning is strictly equal to relative size. First, as Figure 4c shows, likelihood
functions are asymmetrical with respect to the size of the opponent for winning and losing. This
asymmetry occurs because, once an agent is larger than the size opponent, as the agent's
assumed size increases, the relative size of the smaller opponent, and thus the likelihood of
winning, decreases hyperbolically. Simplifying equation 6c, we have
801
802 $$P(win\,|x_i = x) = 1 - \frac{x_o}{x_i},\ for\ x \geq x_o \qquad (S2)$$
803
In the extreme cases of the smallest or biggest possible individual (in the range $[1,100]$)
competing against a mean individual, the size of the minimum individual is 2% of the mean
($\mu_x = 50$), whereas a mean individual is 50% of the maximum sized agent. This flattens the
right side of the likelihood function (Figure 4c). Since the new, posterior size estimate is found
by multiplying the likelihood by the prior, this asymmetry in the likelihood function means, all
else equal, posterior estimates decrease following a loss by more than they increase following a
comparable win. Taken together, the two effects of relative size and relative effort combine to
make the loser effect stronger than the winner effect, consistent with empirical observations.
812

Supplemental Figure S2 A. The effects of relative scaling are such that an equal decrease in estimate leads to a disproportionate decrease in effort. B. The flattening of the likelihood function at larger sizes means losses are more impactful.

S.3 Understanding the Recency Effect

While it is consistent with empirical findings, it may seem counterintuitive mathematically that our Bayesian updating model shows a recency effect, since Bayesian updating is typically order invariant. This recency effect results from the fact that effort, v_i, is determined by an agent's estimate of their own size, such that the agents that won their first contest, but lost their second (WL) invested more heavily in their second contest (after having won their first) and thus the upset was even more surprising. In Bayesian terms, prior winners (WL) experienced a steeper likelihood function in their second-contest loss than the LW agents did in their first contest, and thus WL agents decreased their prior more dramatically. In other words, in a Bayesian updating paradigm, the recency bias comes not from any particular temporal bias, but from a difference in the experience itself, vis-à-vis the perceived likelihood of winning given the relative effort given by the focal agent.

It is important to note that our model lacks any explicit measure of time, only the number of contests experienced. Thus, with no time-bias, winner and loser effects remain fixed in our model until some new experience alters them. In this context, the strength of the recency bias decreases with each additional contest agents had experienced previously, making winner-loser effects weaker as experience increases (see Figure 6b below). Indeed, there are some conditions (e.g., WWWL vs LLLW, highlighted in Figure 3) where the observed recency bias is not sufficient to overcome the dramatically different prior experiences and so no winner or loser effect is observed, in the sense that LLLW agents are still less likely to win a size-matched contest (as compared to a naïve individual).

 S.4 Understanding persistence of winner effect
In the main results we discuss the impact of opponent size, but Bayesian updating also allows
us to model individual estimate confidence (i.e., the narrowness of the distribution of possible
size estimates). We tested the impact of estimate confidence by repeating the above
experiment, but instead of varying the size of the focal opponent, we varied the precision of
individuals initial estimates, σ_θ, while keeping the accuracy (i.e., *awareness*, σ_a) the same (See
Equation 2a,2b). Here, not surprisingly, the confidence of the prior at the time of the treatment
contest attenuated the winner effect but had relatively little impact on the final state.
852
We also explored the how changing the post-contest environment changes the persistence of
the winner effect. In any empirical observation of the winner-loser effect, individuals are
typically placed in an initial contest (in which they win or lose) and then assayed again in a
subsequent winner-loser test match. However, in between these two contests, individuals are
still experiencing their environment and any additional information or experiences in this
environment may influence the individual in their subsequent contest. In the empirical world,
relevant information come from any number of sources; in our model, we explored how access
to other interactions prior to the subsequent winner-loser test match alters the strength and
persistence of the measured effects. We created focal winners of size $x_i = 50$, and allowed
these focal individuals to win against treatment opponents (this time of size $x_o = 60$), but this
time, we placed our focal agents with groups of varying numbers of naïve opponent agents (i.e.,
n = 3,5,10,20, or 40). Here, the sizes of naïve agents were sampled randomly from a normal
distribution, $N(\mu_x = 50, \sigma_x = 10)$. This allowed all focal agents to compete against several
other naïve agents, thus gaining new information and updating their estimates with each
contest. [DID NAÏVE INDIVIDUALS UPDATE THEIR ESTIMATES?] In this simulated experiment,
the number, and body size of naive individuals our focal agents faced over the course of 100
contests had a strong effect on how much and how quickly the winner-effect from the initial
focal contest was attenuated. Briefly, focal agents that interacted with naïve agents with
greater variation in their body sizes more rapidly improved their estimates of their own sizes
thus attenuating winner effects more quickly than focal individuals who only interacted with
similarly sized opponents (supplemental). (Figure 5b).
874

B.

875
876
Supplemental Figure S3. Here, the focal winner is placed in groups of varying size. The x axis
shows the number of total contests, during which focal agents face all other opponents in their
group to form their round, and then face all opponents again and again (each round in a
different, randomized order) until they reach 100 contests. The circles along the lines mark the

start of each round of opponents. The persistence of this shift depends on the variation in the
actual sizes of the other agents in the group.
883
S.5 Linearity persists or increases across parameters
In general, we found that our simulated agents recreated stable linear hierarchies across the
range of parameters tested (Supplemental Figure S2). However, there were certain edge cases
where other outcomes occurred: for example, if the error of agents' starting estimates, σ_a, was
high and/or the size differences between individuals were small (Figure 2a), there were more
frequent upsets (both based on size and based on relative wager) resulting in less-stable
hierarchies, especially in early rounds. Where size differences were large (Figure 2a,2b), or if
the size-bias parameter, s, in Eq. 4a was high, such that any size difference could entirely
determine outcome (i.e., s approaches infinity and l is set sufficiently low that outputs are not
extremely stochastic), then hierarchies were entirely deterministic based on size and thus
generally stable from the start. This initial stability is inconsistent with most empirical
dominance hierarchies, which tend to feature an initial period of high intensity, lower-
consistency contests, during which dominance relationships are established (Tibbetts et al.
2022), followed by stabilization. In our simulation, under most parameter configurations, the
tendency toward stabilization was sufficiently strong that groups of agents formed linear
dominance hierarchies even in the absence of size differences (Figure 2b, yellow line). This was
especially true where small differences in effort could strongly determine outcomes (i.e., a high
effort-bias parameter, f, in Eq. 4a), and in these contexts we observed the strongest contrast
between the initially chaotic network (with less linearity, higher mean contest intensity and less
consistent winners/losers) and the eventual stable state, (Supplemental Figure S3c)
904
To test whether the stabilization effect that we observed based on Bayesian updating was
consistent across parameters, we simulated 100 dominance hierarchies across the range of
possible parameters. Using the scaling function above, we tested every combination from -1 to
1 in intervals of 0.1. For any dominance hierarchy, the random expectation of linearity is 0.75
(i.e., 3 of 4 triads should be linear just by chance). Dominance hierarchies tended to begin more
linear when size was a larger component (Figure S2a). We allowed these groups to interact
across 20 rounds, and again measured linearity (Figure S2b). By taking the difference between
this initial linearity, and the end-state linearity, we observed that in general, linearity either
increased or stayed the same (Figure S2c) This increase was most dramatic where size had little
to no effect on contest outcome, and where effort was a strong factor. Dominance networks
that started out strictly linear obviously did not increase.
916
917

918
919
920 Supplemental Figure S4: Linearity. These plots show the results of simulating dominance
921 hierarchies across various parameters. For each parameter set, we repeated the simulation 100
922 times. Panel A shows the linearity in the first three rounds of contests. Panel B shows the
923 linearity after 20 rounds. Panel C shows the difference.
924
925 S.6 How is effort determined?
926
Agents invested in a contest based on their perceived probability of winning, which was
calculated according to (Equation 3c), as their probability of winning given their estimate,
multiplied by the (rough) probability of their estimate being correct. To demonstrate this, we
simulated a contest between a smaller agent and a bigger agent, with various awareness and
acuity parameters (Figure S3). As an agent's awareness decreased (i.e., the confidence of its
self-assessment) so did effort. As acuity increased, effort decreased, since the smaller agents
correctly identified that their probability of winning was low.
934

935
936
937 Supplemental Figure S5: The effects of acuity and awareness on effort. This plot shows the
938 mean effort (from 1000 simulated contests) of a smaller agent ($x_i = 40$) against a bigger agent
939 ($x_j = 60$) as a function of acuity. The different lines represent agent of different awareness.
940
941

Because they change both the magnitude and variance of effort, acuity and awareness also had
an impact on the linearity, and the stabilization of dominance networks. As before, we
simulated many groups across the range of acuity and awareness parameters (Figure S4),
measuring linearity before (S4a) and after (S4b) repeated interactions. Here the most dramatic
stabilization was observed when acuity was low and there was moderate awareness (S4c).
Where agents had strong self-assessment, dominance networks were linear from the start, high
acuity tended to increase stabilization, since it allows accurate self-assessments to be used
effectively.
950
951

952
953
954 Supplemental Figure S6: Linearity across possible parameters acuity and awareness. As in
955 Figure S2, these panels show the measured linearity before (A) and after (B) 20 rounds of
956 contests. Here, the axes move exponentially from 0 to infinity, and represent the standard
957 deviation around the mean when assessing opponents. Acuity 10 (i.e., $c = \infty$) is the same as
958 pure self-assessment, since agents simply assume the opponent is average size.
959
960 To confirm that our stabilization effect was not an artifact of mutual assessment, we repeated
961 our linearity measures with moderate awareness but minimal acuity. Under these conditions,
962 agents still increased their linearity over time (Figure S5).
963

964
965
966 Supplemental Figure S7: This plot shows the difference in initial and end-state linearity with
967 agents with no opponent assessment (acuity variance = ∞). Except in certain edge cases,
968 linearity always increased.

969
970 <u>S.7 The number of agents impacts the persistence and extent of linearity</u>

971
The number of agents also impacts linearity. We explored this in a context where all agents
were equal size, thus the "correct" dominance hierarchy would be flat and/or random. We
simulated many rounds of contests with few (n=5) and many (n=50) individuals (Figure S6). In
both cases, linearity started above random chance and initially increased, however with many
individuals, linearity eventually fell back to baseline. This is likely due to the large amount of
information individuals received causing them to all (correctly) conclude that they were the
same size, where in the low number, low information environment, it was easy to establish
relative assessments to enforce linearity.

981
982

983 Supplemental Figure S8: Artificial linearity among equally sized individuals is stronger and more
984 persistent in small social groups. This plot shows mean linearity for two simulated dominance
985 networks, one with 5 agents, a second with 50 agents. In both cases, all individuals were the
986 same size ($x_i = 50$). Error bars show SEM over 1000 iterations.
987
988 S.8 What drives the experience effect under linear updating
989
This similarity between Bayesian and linear updating is due to the divergent effects of linear
updating on size updating. With linear updating, any individual that is larger—or smaller—than
the median size is winning—or losing—the majority of their contests, respectively. This means
agent estimates will diverge over time, with all individuals bigger than the median eventually
assuming they are extremely large and all below-average individuals concluding they are
extremely small. [Make a figure for this]
996
997

998
999
Supplemental Figure S9: Winner-loser affects attenuate with experiences. A. Compared to not
updating estimates (black), Bayesian updating shows both a winner (gold) and a loser (blue)
effect which attenuates over time. B. Linear updating (green) also shows attenuation over time,
even though the actual shift is fixed. This is because individuals' estimates (black lines, plotted
as a ratio of maximum possible size) diverge to either the maximum or minimum sizes, since
any individual that is not precisely the median size will necessarily either win or lose the
majority of contests. C. This same pattern holds even if the shift is a function of the size from
min/max size. Unless the shift is extremely large (i.e., 50% of maximum size), a single
experience isn't enough to compensate for past experience, and so winner-loser effects are
weaker for experienced individuals.
1010

References
Albers, P. C. H., and H. De Vries. 2001. Elo-rating as a tool in the sequential estimation of
dominance strengths. Animal Behaviour.
Appleby, M. C. 1983. The probability of linearity in hierarchies. Animal Behaviour 31.
Arnott, G., and R. W. Elwood. 2008. Information gathering and decision making about resource
value in animal contests. Animal Behaviour.
Beacham, J. L. 1988. The relative importance of body size and aggressive experience as
determinants of dominance in pumpkinseed sunfish, Lepomis gibbosus. Animal Behaviour 36.
Bierbach, D., M. Klein, V. Sassmannshausen, I. Schlupp, R. Riesch, J. Parzefall, and M. Plath.
2012. Divergent Evolution of Male Aggressive Behaviour: Another Reproductive Isolation
Barrier in Extremophile Poeciliid Fishes? International Journal of Evolutionary Biology 2012.
Bonabeau, E., G. Theraulaz, and J. L. Deneubourg. 1999. Dominance orders in animal societies:
The self-organization hypothesis revisited. Bulletin of Mathematical Biology 61.
Chase, I. D., C. Bartolomeo, and L. A. Dugatkin. 1994. Aggressive interactions and inter-contest
interval: How long do winners keep winning? Animal Behaviour 48.
Chase, I. D., D. Coelho, W. Lee, K. Mueller, and J. P. Curley. 2022. Networks never rest: An
investigation of network evolution in three species of animals. Social Networks 68.
Chase, I. D., C. Tovey, D. Spangler-Martin, and M. Manfredonia. 2002. Individual differences
versus social dynamics in the formation of animal dominance hierarchies. Proceedings of the
National Academy of Sciences of the United States of America 99.
Dewsbury, D. A. 1988. Copulatory Behavior as Courtship Communication. Ethology.
Drews, C. 1993. The concept and definition of dominance in animal behaviour. Behaviour 125.
Dugatkin, L. A. 1997. Winner and loser effects and the structure of dominance hierarchies.
Behavioral Ecology 8.
Ellis, L. 1995. Dominance and reproductive success among nonhuman animals: A cross-species
comparison. Ethology and Sociobiology 16.
Francis, R. C. 1990. Temperament in a Fish: A Longitudinal Study of the Development of
Individual Differences in Aggression and Social Rank in the Midas Cichlid. Ethology 86.
Goetz, S. M. M., L. Tang, M. E. Thomason, M. P. Diamond, A. R. Hariri, and J. M. Carré. 2014.
Testosterone rapidly increases neural reactivity to threat in healthy men: A novel two-step
pharmacological challenge paradigm. Biological Psychiatry 76.
Goubault, M., and M. Decuignière. 2012. Previous experience and contest outcome: Winner
effects persist in absence of evident loser effects in a parasitoid wasp. American Naturalist 180.
Hemelrijk, C. K. 2002. Despotic societies, sexual attraction and the emergence of male
"tolerance": An agent-based model. Behaviour 139.
Hickey, J., and J. Davidsen. 2019. Self-organization and time-stability of social hierarchies. PLoS
ONE 14.
Hock, K., and R. Huber. 2006. Modeling the acquisition of social rank in crayfish: Winner and
loser effects and self-structuring properties. Behaviour 143.
Holekamp, K. E., and E. D. Strauss. 2016. Aggression and dominance: an interdisciplinary
overview. Current Opinion in Behavioral Sciences.
Hsu, Y., R. L. Earley, and L. L. Wolf. 2006. Modulation of aggressive behaviour by fighting
experience: Mechanisms and contest outcomes. Biological Reviews of the Cambridge
Philosophical Society.

Johnsson, J. I. 1997. Individual recognition affects aggression and dominance relations in rainbow trout, Oncorhynchus mykiss. Ethology 103.

Lan, Y. T., and Y. Hsu. 2011. Prior contest experience exerts a long-term influence on subsequent winner and loser effects. Frontiers in Zoology 8.

Landau, H. G. 1951. On dominance relations and the structure of animal societies: I. Effect of inherent characteristics. The Bulletin of Mathematical Biophysics 13.

Laskowski, K. L., M. Wolf, and D. Bierbach. 2016. The making of winners (And losers): How early dominance interactions determine adult social structure in a clonal fish. Proceedings of the Royal Society B: Biological Sciences 283.

Li, C. Y., R. L. Earley, S. P. Huang, and Y. Hsu. 2014. Fighting experience alters brain androgen receptor expression dependent on testosterone status. Proceedings of the Royal Society B: Biological Sciences 281.

Lindquist, W. B., and I. D. Chase. 2009. Data-based analysis of winner-loser models of hierarchy formation in animals. Bulletin of Mathematical Biology.

McDonald, A. L., N. W. Heimstra, and D. K. Damkot. 1968. Social modification of agonistic behaviour in fish. Animal Behaviour 16.

Momohara, Y., H. Minami, A. Kanai, and T. Nagayama. 2016. Role of cAMP signalling in winner and loser effects in crayfish agonistic encounters. European Journal of Neuroscience 44.

Neumann, C., J. Duboscq, C. Dubuc, A. Ginting, A. M. Irwan, M. Agil, A. Widdig, et al. 2011. Assessing dominance hierarchies: Validation and advantages of progressive evaluation with Elo-rating. Animal Behaviour.

O'Connor, C. M., A. R. Reddon, I. Y. Ligocki, J. K. Hellmann, K. A. Garvy, S. E. Marsh-Rollo, I. M. Hamilton, et al. 2015. Motivation but not body size influences territorial contest dynamics in a wild cichlid fish. Animal Behaviour 107.

Parker, G. A. 1974. Assessment strategy and the evolution of animal conflicts. Journal of theoretical Biology 47:223–243.

Rowell, T. E. 1974. The concept of social dominance. Behavioral Biology 11.

Rutte, C., M. Taborsky, and M. W. G. Brinkhof. 2006. What sets the odds of winning and losing? Trends in Ecology and Evolution 21.

Schlinger, B. A., B. Palter, and G. V. Callard. 1987. A method to quantify aggressiveness in Japanese quail (Coturnix c. japonica). Physiology and Behavior 40.

Shizuka, D., and D. B. McDonald. 2015. The network motif architecture of dominance hierarchies. Journal of the Royal Society Interface 12.

Simons, N. D., V. Michopoulos, M. Wilson, L. B. Barreiro, and J. Tung. 2022. Agonism and grooming behaviour explain social status effects on physiology and gene regulation in rhesus macaques. Philosophical Transactions of the Royal Society B: Biological Sciences 377.

Snyder-Mackler, N., J. R. Burger, L. Gaydosh, D. W. Belsky, G. A. Noppert, F. A. Campos, A. Bartolomucci, et al. 2020. Social determinants of health and survival in humans and other animals. Science.

Stevenson, P. A., H. A. Hofmann, K. Schoch, and K. Schildberger. 2000. The fight and flight responses of crickets depleted of biogenic amines. Journal of Neurobiology 43.

Strauss, E. D., A. R. Decasien, G. Galindo, E. A. Hobson, D. Shizuka, and J. P. Curley. 2022. DomArchive: a century of published dominance data. Philosophical Transactions of the Royal Society B: Biological Sciences 377.

Tibbetts, E. A., J. Pardo-Sanchez, and C. Weise. 2022. The establishment and maintenance of
dominance hierarchies. Philosophical Transactions of the Royal Society B: Biological Sciences
377.
Van Doorn, G. S., G. M. Hengeveld, and F. J. Weissing. 2003. The evolution of social dominance
I: Two-player models. Behaviour 140.
Whitehouse, M. E. A. 1997. Experience influences male-male contests in the spider Argyrodes
antipodiana (Theridiidae: Araneae). Animal Behaviour 53.
1106