Unified neural representation model for physical space and linguistic concepts

Tatsuya Haga[1,2,*], Yohei Oseki[3], and Tomoki Fukai[1]

[1]Neural Computation and Brain Coding Unit, Okinawa Institute of Science and Technology, Okinawa, Japan
[2]Center for Information and Neural Networks (CiNet), National Institute of Information and Communications Technology, Osaka, Japan
[3]Graduate School of Arts and Sciences, University of Tokyo, Tokyo, Japan
[*]Corresponding author E-mail: tatsuyahaga@nict.go.jp

Abstract

The entorhinal cortex uses grid-like neural representations (grid cells) for spatial processing. Neural representations for concepts (concept cells), which presumably support high-level conceptual processing, have been also found in the same brain region. However, the relationship behind those neural representations is still unclear. We propose a unified model called "disentangled successor information (DSI)" that produces neural representations for physical space and linguistic concepts. DSI generates grid-like representations in a 2-dimensional space that highly resemble those observed in the brain. Moreover, the same model creates concept-specific representations from linguistic inputs, corresponding to concept cells. Mathematically, DSI approximate value functions for navigation and word vectors obtained by word embedding methods, thus those representations support both spatial navigation and analogical inference based on a simple arithmetic computation. Our results suggest that representations and computation for physical space and linguistic concepts in the brain can emerge from a shared mechanism.

1   Introduction

In the brain, grid cells in the entorhinal cortex (EC) represent the space by hexagonal grid-like representations (Hafting et al., 2005; Doeller et al., 2010; Jacobs et al., 2013). This neural representation is often related to vector-based spatial navigation and path integration. Theoretically, an animal can estimate the direction to a goal when representations of a current position and a goal position are given (vector-based navigation) (Bush et al., 2015). Furthermore, self-position can be estimated by integrating self-motions when sensory information is not available (path integration) (McNaughton et al., 2006; Burak & Fiete, 2009). These functions are bases of robust spatial navigation by animals.

There are not only spatial but also conceptual representations in EC. Neurons called as "concept cells" have been found in human medial temporal lobe including EC (Quiroga, 2012; Reber et al., 2019; Bausch et al., 2021). Concept cells respond to specific concepts, namely, stimuli related to a specific person, a famous place, or a specific category like "foods" and "clothes". Furthermore, recent experiments also suggest that grid-like representations appear not only for physical space but also for conceptual space if there is a 2-dimensional structure (e.g. lengths of a neck and legs, intensity of two odors), and those representations are the basis of vector-based conceptual inference (Bao et al., 2019; Constantinescu et al., 2016; Park et al., 2021). Thus, it is expected that there is a shared processing mechanism

for physical and conceptual spaces in EC. However, a mathematical principle behind such universal computation in the brain is still unclear.

In this paper, we propose a representation model which we call disentangled successor information (DSI) model. DSI is an extension of successor representation (SR), which stems from a theory of reinforcement learning and became one of plausible computational models of the hippocampus and EC (Dayan, 1993; Stachenfeld et al., 2017; Momennejad et al., 2017; Momennejad, 2020). Like eigenvectors of SR, DSI forms grid-like codes in a 2-D space, which support path integration and goal-directed spatial navigation. On the other hand, when we apply DSI to text data by regarding a sequence of words as a sequence of states, DSI forms concept-specific representations like concept cells. Furthermore, we show two mathematical interpretation of DSI. First, DSI approximates value functions in the framework of linear reinforcement learning (Todorov, 2006, 2009; Piray & Daw, 2021). Therefore, spatial navigation using DSI vectors can be regarded as near-optimal decision making. Second, DSI is related to word embedding models in natural language processing (NLP) (Mikolov et al., 2013a,b; Pennington et al., 2014; Levy & Goldberg, 2014). As in those models, DSI vectors capture the semantic structure of words, and we can perform inference of novel spatial contexts and linguistic concepts through a simple arithmetic composition of DSI vectors. Our model reveals a new theoretical relationship between spatial and linguistic representation learning, and suggests a hypothesis that there is a shared computational principle behind grid-like and concept-specific representations in EC.

2 Contributions and related works

We summarize contributions of this work as follows. (1) We extended SR to successor information (SI), by which we theoretically connected reinforcement learning and word embedding, thus spatial navigation and conceptual inference. (2) We argue that constraints for the emergence of grid-like representations is sufficient for generation of disentangled word vectors with concept-specific units. (3) Combining these results, we demonstrated that a computational model for grid cells can be extended to represent and compute linguistic concepts in an intuitive and biologically plausible manner.

Our model is an extension of successor representation (SR), which is recently viewed as a plausible model of hippocampus and EC (Dayan, 1993; Stachenfeld et al., 2017; Momennejad et al., 2017; Momennejad, 2020). Furthermore, default representation (DR), which is based on linear reinforcement learning theory, has been also proposed as a model of EC (Piray & Daw, 2021). Our model is closely related to those previous works, however, we show that our model can extract and compute linguistic concepts, which has not been shown for SR and DR. Furthermore, we demonstrate compositionality of words in our model, which expands the range of compositionality of EC representations (Piray & Daw, 2021) to semantic processing.

Our model produces biologically plausible grid-like representations in 2-D space, which supports path integration and spatial navigation. Previous studies have revealed that non-negative and orthogonal constraints are important to obtain realistic grid-like representations (Dordek et al., 2016; Sorscher et al., 2019, 2023). Furthermore, recurrent neural networks form grid-like representations through learning path integration, and those representations support efficient spatial navigation (Banino et al., 2018; Cueva & Wei, 2018; Gao et al., 2019; Sorscher et al., 2023). Some of those models have reproduced experimentally observed scaling ratios between grid cell modules (Banino et al., 2018; Sorscher et al., 2019). However, previous models have not been applied to learning of linguistic concepts, or other complex conceptual spaces in real-world data. Whittington et al. (2020) proposed a unified model for spatial and non-spatial cognition. However, their model was applied only to simple graph structures and conceptual specificity like our model was not observed.

Analogical inference by our model is a same function as word embedding methods in NLP (Mikolov et al., 2013a,b; Pennington et al., 2014; Levy & Goldberg, 2014). However,

a unique feature of DSI representations is that each dimension of vectors corresponds to a specific concept like concept cells in the human brain (Quiroga, 2012; Reber et al., 2019). Such concept-specific representations have been reported in Murphy et al. (2012) previously, however, we additionally found that such disentangled conceptual representations emerge in the model of representations for spatial navigation (grid cells), thus they can be regarded as a natural model of concept cells in EC. Furthermore, we found that analogical inference in our model can be interpreted as a simple recombination of concept-specific units, which has not been discussed in the previous study. Our model provides biologically plausible interpretation of word embedding: each word is represented by combination of disentangled conceptual units, inference is recombination of those concepts, and such representations emerge through the same constraints with grid cells. It was recently shown that transformer-based models (Vaswani et al., 2017; Brown et al., 2020), which are currently state-of-the-art models in NLP, generate grid-like representations when applied to spatial learning (Whittington et al., 2022). Similarly to our model, this finding implies the relationship between spatial and linguistic processing in the brain. However, concept-specific representations has not been found in such model. Furthermore, clear theoretical interpretation like this study is currently difficult for transformer-based models because of their complex structures.

3 Model

3.1 Disentangled successor information

Let us assume N_s discrete states exist in the environment. Successor representation (SR) between two states s and s' is defined as

$$SR(s, s') = E\left[\sum_{t=0}^{\infty} \gamma^t \delta(s_t, s')|s_0 = s\right] = \sum_{t=0}^{\infty} \gamma^t P(s_t = s'|s_0 = s), \qquad (1)$$

where $\delta(i, j)$ is Kronecker's delta and γ is a discount factor. SR and its dimension-reduced representations can be viewed as models of hippocampus and EC, respectively (Stachenfeld et al., 2017). We describe how we calculate SR from data in this study in Appendix A.1.

Based on SR, we define successor information (SI) and positive successor information (PSI) as

$$SI(s, s') = \log(SR(s, s')) - \log(P(s')), \qquad (2)$$
$$PSI(s, s') = \max\{SI(s, s'), 0\}. \qquad (3)$$

Furthermore, we introduce a dimension reduction method which we call decorrelative non-negative matrix factorization (decorrelative NMF). Decorrelative NMF can be regarded as a variant of NMF (Lee & Seung, 1999) with additional constraints of decorrelation. By applying decorrelatve NMF to PSI, we obtain representation vectors called as disentangled successor information (DSI), which we regard as a model of EC. In decorrelative NMF, we obtain D-dimensional vectors $\boldsymbol{x}(s)$ and $\boldsymbol{w}(s)$ ($D < N_s$) by minimization of the following objective function

$$J = \frac{1}{2}\sum_{s,s'} \rho(s, s')(PSI(s, s') - \boldsymbol{x}(s) \cdot \boldsymbol{w}(s'))^2$$
$$+ \frac{1}{2}\beta_{cor}\sum_{i \neq j}(Corr(i, j))^2 + \frac{1}{2}\beta_{reg}\sum_s(||\boldsymbol{x}(s)||^2 + ||\boldsymbol{w}(s)||^2), \qquad (4)$$

subject to non-negative constraints $\forall i, x_i(s) \geq 0, w_i(s) \geq 0$. $\rho(s, s')$ is a weight for the square error

$$\rho(s, s') = \frac{1}{N_s V}\left(\frac{1}{M}PSI(s, s') + \rho_{min}\right), \qquad (5)$$

where M and V are mean and variance of PSI, respectively, and ρ_{min} is a small value to avoid zero-weight. $Corr(i,j)$ is a correlation between two dimensions in $\boldsymbol{x}(s)$

$$Corr(i,j) = \frac{\sum_s \tilde{x}_i(s)\tilde{x}_j(s)}{\sqrt{\sum_s(\tilde{x}_i(s))^2 \sum_s(\tilde{x}_j(s))^2}}, \tag{6}$$

where $\tilde{x}_i(s) = x_i(s) - \frac{1}{N_s}\sum_s x_i(s)$. The first term of the objective function is weighted approximation error minimization, the second term works for decorrelation between dimensions, and the third term regularizes representation vectors. Optimization was performed by Nesterov's accelerated gradient descent method (Nesterov, 1983) with rectification of $x_i(s), w_i(s)$ every iteration. We describe additional details in Appendix A.2.

3.2 Relationships with reinforcement learning and word embedding

We show dual interpretation of our model. On the one hand, DSI approximates value estimation of linear reinforcement learning, thus supports goal-directed spatial navigation. On the other hand, the same representation approximates word embedding in NLP, thus supports semantic computation.

First, our model approximates value functions of linear reinforcement learning (Todorov, 2006, 2009; Piray & Daw, 2021) in the setting of spatial navigation. Linear reinforcement learning assumes default policy and imposes additional penalty on deviation from default policy, then we can obtain value functions explicitly by solving linear equations. Let us consider a specific condition in which the environment consists of non-terminal states, and a virtual terminal state is attached to a goal state s_G arbitrarily chosen from non-terminal states. When the agent gets to the goal, it transits to the terminal state and obtain positive reward. Furthermore, we assume that reward at non-terminal states are uniformly negative so that the agent has to take a short path to goal to maximize reward. In this setting, we can obtain value functions $v^*(s)$ in linear reinforcement learning as

$$\lambda^{-1}v^*(s) = \log(SR^d(s, s_G)) - \log P^d(s_G) = SI^d(s, s_G) \approx \boldsymbol{x}(s) \cdot \boldsymbol{w}(s_G), \tag{7}$$

where $SR^d(s, s_G)$ and $SI^d(s, s_G)$ are SR and SI under the default policy, respectively, and λ is a parameter representing the relative weight of penalty on deviation from default policy. We describe details of derivation in Appendix A.3. Therefore, SI is proportional to value functions for spatial navigation and inner products of DSI vectors approximates value functions. Based on this interpretation, we basically regard $\boldsymbol{x}(s)$ as a representation of each state, and $\boldsymbol{w}(s)$ represents a temporary goal.

Second, DSI is related to word embedding methods in NLP (Mikolov et al., 2013a,b; Pennington et al., 2014; Levy & Goldberg, 2014). In linguistics, pointwise mutual information (PMI) and positive pointwise mutual information (PPMI) are used to measure the degree of coincidence between two words (Levy & Goldberg, 2014). They are defined as

$$PMI = \log\left(\frac{P(word_i, word_j)}{P(word_i)P(word_j)}\right), \tag{8}$$

$$PPMI = \max\{PMI, 0\}, \tag{9}$$

where $P(word_i, word_j)$ is a coincidence probability of two words (in a certain temporal window). It has been proven that dimension reduction of PMI approximates a word embedding method skip-gram (Mikolov et al., 2013a,b), and similar performance is obtained using PPMI (Levy & Goldberg, 2014). GloVe (Pennington et al., 2014) is also based on this perspective. SI can be written as

$$SI(s, s') = \log(SR(s, s')) - \log(P(s')) = \log\left(\frac{\sum_{t=0}^{\infty}\gamma^t P(s_t = s', s_0 = s)}{P(s)P(s')}\right). \tag{10}$$

In this formulation, we can see mathematical similarity between PMI and SI by regarding words as states ($s = word_i, s' = word_j$), thus the correspondence between PPMI and PSI. Because of this relationship, we can expect that DSI, which is obtained through dimension reduction of PSI, has similar properties to word embedding methods. The difference is how to count coincidence: the coincidence in SI is evaluated with an asymmetric exponential kernel as in SR, in contrast that a symmetric rectangular temporal window is often used in typical word embedding.

3.3 The role of decorrelative NMF in learning spatial and linguistic representations

Constraints in decorrelative NMF (non-negativity, decorrelation (or orthogonality), and regularization) are important for generation of grid cells, as shown in previous theoretical studies on grid cells. (Dordek et al., 2016; Cueva & Wei, 2018; Banino et al., 2018; Gao et al., 2019; Sorscher et al., 2019, 2023). A previous study also suggests that non-negativity (with sparsity) enables generation of disentangled word representation vectors (Murphy et al., 2012). Therefore, we hypothesized that decorrelative NMF generates both grid-like spatial representations and disentangled (concept-specific) linguistic representations, which correspond to grid cells and concept cells, respectively. Later, we show that constraints in decorrelative NMF were actually crucial for results obtained in this study (Section 6). Furthermore, these constraints are biologically plausible because neural activity is basically non-negative and decorrelation is possible through lateral inhibition.

4 Learning representations of physical spaces

In this section, we empirically show that DSI model forms biologically plausible grid-like representations in a 2-D physical space, and they support spatial navigation. These results also apply to conceptual spaces with the 2-D structure, depending on the definition of states.

4.1 Learning procedure

As an environment, we assumed a square room tiled with 30×30 discrete states (Figure 1A). In each simulation trial, an agent starts at one of those 900 states and transits to one of eight surrounding states each time except that transitions are limited at states along the boundary (the structure was not a torus). Transitions to all directions occur with an equal probability. We performed 500 simulation trials and obtained a sequence of 100,000 time steps in each trial. We calculated occurrence probabilities ($P(s)$) and a successor representation matrix ($SR(s, s')$) of 900 states from those sequences, and calculated PSI and DSI (100-dimensional) as described in the Model section. The discount factor γ was set to 0.99. We additionally tested spatial navigation in a structure with separated and interconnected rooms (see Figure 3C). In that case, we used the discount factor $\gamma = 0.999$.

4.2 Emergence of grid-like representations

Here we call each dimension of DSI representation vectors $\boldsymbol{x}(s)$ as a neural "unit", and we regard a value in each dimension at each state as a neural activity (or a neural representation). As shown in Figure 1B, many units exhibited grid-like activity patterns in the space. We performed a gridness analysis that has been used in animal experiments (Sargolini et al., 2006) and found that 51% of units were classified as grid cells. Similarly, 53% of units in $\boldsymbol{w}(s)$ were classified as grid cells.

Furthermore, we checked whether DSI representations in the physical space reproduce a property of biological grid cells. Actual grid cells in the rat brain exhibit multiple discrete spatial scales and the ratio between grid scales of adjacent modules is $\sqrt{2}$ (Stensola et al.,

Figure 1: DSI representations for the physical space. (A) The square room tiled with 30x30 discrete states. (B) Grid-like DSI representations in the space (upper) and their spatial autocorrelation (lower). (C) The distribution of grid scales of DSI representations. Red and blue broken lines indicate positions of peaks and $\frac{30}{(\sqrt{2})^n}$, respectively.

2012). We constructed a distribution of grid scales of DSI units by kernel density estimation, which revealed that multiple peaks of grid scales existed and the ratio between grid scales of adjacent peaks was $\sqrt{2}$ (Figure 1C). These results show that DSI model constructs biologically plausible grid-like representations in the 2-D physical space. We describe details of analysis methods in Appendix A.4.

4.3 Path integration by DSI vectors

We checked whether we can use DSI representations for path integration which is one of important functions of grid cells. We used movement-conditional recurrent weights to perform path integration (McNaughton et al., 2006; Burak & Fiete, 2009; Oh et al., 2015; Gao et al., 2019). This strategy has been used in previous studies such as grid cell modeling (Gao et al., 2019) and action-conditional video prediction (Oh et al., 2015). This mechanism is also consistent with a conventional biological model for path integration in which head direction signals activate one of attractor networks specialized for different directional shifts of grid patterns (McNaughton et al., 2006; Burak & Fiete, 2009; Sorscher et al., 2023).

We made an estimate of the next representation vector $\hat{\boldsymbol{x}}_{t+1}$ by linear transformation of the current representation vector $\boldsymbol{x}(s_t)$ as

$$\hat{\boldsymbol{x}}_{t+1} = \boldsymbol{M}(a_t)\boldsymbol{x}(s_t) \tag{11}$$

where a_t represents a movement (one of eight directional movements in this study) and $\boldsymbol{M}(a_t)$ is movement-conditional recurrent weight matrix. Here, $\boldsymbol{x}(s_t)$ was a DSI representation vector, and we optimized the matrix $\boldsymbol{M}(a_t)$ by minimizing prediction error $||\boldsymbol{x}(s_{t+1}) - \boldsymbol{M}(a_t)\boldsymbol{x}(s_t)||_2^2$ by stochastic gradient descent during random walk on the state transition graph (20 simulation trials of 100,000 time steps). After optimization, we set an initial state s_0 and a sequence of movements $\{a_0, a_1, \ldots, a_{T-1}\}$, and performed path integration by recursive estimation $\hat{\boldsymbol{x}}_{t+1} = \boldsymbol{M}(a_t)\hat{\boldsymbol{x}}_t$. We determined a position at each time step by searching a state representation vector that has minimum Euclidian distance with the estimated vector ($s_t = \arg\min_s ||\boldsymbol{x}(s) - \hat{\boldsymbol{x}}_t||_2$). As shown in Figure 2, this strategy gave accurate estimation of the spatial path from movement signals.

| Correct path | Estimation by path integration |

Figure 2: Path integration using DSI model. (Left) Actual path. (Right) Path estimated from DSI vectors updated by movement information.

Figure 3: Spatial navigation using DSI representation vectors. (A) Geometric interpretation of the state transition rule in the DSI representation space. (B) An example spatial path obtained by DSI-based navigation. (C) Example spatial paths by DSI-based navigation in the four-room environment.

4.4 Near-optimal spatial navigation by DSI vectors

As discussed in Section 3.2, the inner product of DSI representations approximate value functions for spatial navigation. Therefore, we tested whether DSI representations actually enable near-optimal navigation in the space.

We assume that a start location (state s_{init}) and a goal location (state s_G) are randomly given in each trial such that the shortest path length is minimally 10, and an agent has to navigate between them. To solve the task, we define a vector-based state transition rule. Suppose that the agent exists at a state s, and a set of neighboring states of s is $\mathbb{A}(s)$. Given the goal representation vector $\boldsymbol{w}(s_G)$, a value function of a neighboring state $s_{next} \in \mathbb{A}(s)$ is estimated by $\boldsymbol{x}(s_{next}) \cdot \boldsymbol{w}(s_G)$, and the agents transits to the state that has a maximum value. This state transition rule can be geometrically interpreted as the choice of movements that has the closest angle with the goal vector in the representation space (Figure 3A). Otherwise, we can interpret that the agent estimates value functions by linear readout from grid-like DSI representations. Because of the approximation error, this rule did not always give optimal navigation (the shortest path from the start to the goal). However, the agent could take the shortest path to the goal in 93.9% of 1,000 trials we tested (an example is shown in Figure 3B). Furthermore, 97.2% were near-optimal navigation in which the actual path length was shorter than 1.1 times the shortest path length. The same framework also worked in a relatively complex environment with separated rooms (Figure 3C). In this environment,

Figure 4: Vector-based inference of a novel spatial context. (A) We constructed representation vectors for a novel context A+B (a square room with two barriers) by the sum of DSI representation vectors for two familiar contexts A and B (with either of two barriers). (B) Rates of near-optimal navigation in various settings of representation vectors and contexts.

the ratio of optimal and near-optimal navigation was 68% and 82.6%, respectively. These results show that DSI representations can support spatial navigation, which corresponds to the contribution of biological grid cells for spatial navigation.

4.5 Arithmetic compositionality of spatial representations

We found that we can perform compositional inference of spatial representations for a novel context. First, we constructed DSI representation vectors in spatial contexts A and B, each of which has a barrier (Figure 4A). Then, we created representation vectors for a novel context A+B with two barriers by simply adding representation vectors for familiar contexts A and B (Figure 4A). We tested vector-based navigation (described in the section 4.4) in three spatial contexts A, B, and A+B, using one of three representations for A, B, and A+B. Naturally, representation vectors for A and B gave the best performance in contexts A and B, respectively (Figure 4B). Notably, composite representation vectors for A+B achieved the best performance in the context A+B (Figure 4B).

Additional analysis by multidimensional scaling (MDS) suggest that summing DSI vectors leads to composition of an appropriate metric space for the novel context. In Figure 5, we visualized metric spaces defined by representation vectors for contexts A and B, and composite vectors for the context A+B, by using multidimensional scaling (MDS). This visualization clearly shows that DSI vectors for A and B capture structures of spatial contexts A and B, and adding those vectors yields appropriate metric space for novel context A+B. These results suggest that we can utilize vector-based composition of representations for a novel spatial context. We describe details of the simulation in Appendix A.5.

5 Learning representations of conceptual spaces

In this section, we show that the same DSI model can learn representations for a complex conceptual space from linguistic inputs, and those representations support vector-based conceptual inference.

5.1 Learning procedure

We used text data taken from English Wikipedia, which contains 124M tokens and 9376 words (see Appendix A.6 for the detail of preprocessing). To construct DSI representations, we regarded each word as a "state", and considered the text data as a sequence of 9376 states ($N_s = 9376$). Then, we applied the exactly same learning procedure as in the experiment of physical spaces. We obtained 300-dimensional DSI representation vectors for each word. The discount factor γ was set to 0.9. The setting of other parameters was the same as the experiment of physical spaces.

Figure 5: Visualization of metric spaces defined by representation vectors for contexts A and B, and composite vectors for the context A+B using MDS. Red, blue, and green dots correspond to states (positions) in the left, center, and right parts of the original 2-D space (Figure 10), respectively.

Table 1: Evaluation of conceptual specificity. Numbers of evaluated and significantly concept-specific units, the ratio of concept-specific units, and average conceptual specificity are summarized.

Method	Evaluated	Significant	Ratio	Specificity
DSI	285	100	35%	0.32
Skip-gram	297	14	5%	-0.11
CBOW	298	83	28%	0.26
GloVe	297	6	2%	-0.07
PPMI-SVD	297	36	12%	0.06
BERT	755	51	7%	0.03

5.2 Emergence of concept-specific representations

As in the previous section, we regard each dimension of representation vectors as a neural unit, and checked how various words activate those units. Specifically, we listed ten words that elicited the highest activities in each unit (TOP-10 words). Then, we found that many units are activated by words related to specific concepts (Figure 6; other examples in Appendix A.9), which could be named as "game cell" or "president cell", for example. We quantified this conceptual specificity through WordNet-based semantic similarity between words (Princeton University, 2010). We compared mean similarity among TOP-10 words and a null distribution of similarity between random word pairs, by which we determined statistically significant concept-specific units and quantified the degree of conceptual specificity of each unit (see Appendix A.7 for details). DSI exhibited the larger number of significantly concept-specific units and higher average conceptual specificity than other well-established word embedding methods such as skip-gram and GloVe (Table 1) (Mikolov et al., 2013a,b; Pennington et al., 2014; Levy & Goldberg, 2014). We also analyzed conceptual specificity of representations in the embedding layer of pretrained BERT model (bert-base-uncased in Hugging Face transformers) (Devlin et al., 2018; Wolf et al., 2020), which was lower than DSI (Table 1). This result shows that our DSI model forms more concept-specific representations than typical models in NLP.

TOP 10 words for each unit

Unit 9	Unit 31	Unit 113	Unit 244	Unit 269
eleventh 2.13	orbit 2.16	playstation 2.38	covid-19 1.84	reagan 1.84
tenth 2.09	spacecraft 2.12	nintendo 2.25	virus 1.76	obama 1.81
ninth 2.00	saturn 1.95	xbox 2.13	infected 1.71	barack 1.78
seventh 1.96	apollo 1.84	console 1.93	pandemic 1.65	bush 1.61
eighth 1.95	lunar 1.80	arcade 1.78	viral 1.64	trump 1.55
twelfth 1.95	planets 1.78	360 1.62	epidemic 1.62	clinton 1.53
7th 1.93	nasa 1.73	gameplay 1.56	hiv 1.50	presidents 1.35
8th 1.86	mars 1.73	pc 1.46	plague 1.42	roosevelt 1.31
10th 1.84	moon 1.69	mario 1.40	infections 1.39	nixon 1.30
11th 1.84	orbital 1.66	metacritic 1.33	outbreak 1.37	presidential 1.29
Order cell	*Space cell*	*Game cell*	*Virus cell*	*President cell*

Figure 6: Concept-specific representations formed by DSI. Ten words that gave the highest activation (TOP-10 words) are shown. We also marked each unit with a descriptive label.

Table 2: Performances of vector-based computations in the conceptual space. The correlation of word similarity evaluated by vectors and humans, and the rate of correct analogical inference.

Method	Similarity	Analogy
DSI	0.70	0.63
Skip-gram	0.69	0.71
CBOW	0.69	0.74
GloVe	0.69	0.71
PPMI-SVD	0.52	0.58

5.3 Representational structure and compositionality of word representations

Given that DSI and word embedding methods are mathematically similar (Section 3.2), we expect that DSI vectors have similar properties to representation vectors learned by those word embedding methods. We evaluated the performance of DSI vectors in two tasks that have been used to evaluate word embedding methods: word similarity and analogical inference (Mikolov et al., 2013a,b; Pennington et al., 2014; Levy & Goldberg, 2014). In the word similarity task, we calculated cosine similarity between representation vectors of word pairs, and evaluated the rank correlation between those cosine similarities and human word similarities (WS353 dataset (Agirre et al., 2009); 248/345 word pairs were used). In the analogical inference task, we performed calculation of vectors such as $\boldsymbol{x}(king) - \boldsymbol{x}(man) + \boldsymbol{x}(woman)$ and checked whether the resultant vector has the maximum cosine similarity with $\boldsymbol{x}(queen)$ (Mikolov's dataset (Mikolov et al., 2013a,b); 3157/19544 questions were used; examples in Appendix A.8). The result shows that DSI vectors show comparable performance with word embedding methods (Table 2). This indicates that DSI vectors represent the semantic structure of words, and it is possible to perform conceptual inference through arithmetic composition of representations in a similar manner to the case of physical spaces.

This property suggests that the representational structure of DSI vectors is consistent with the experimental observation that population-level pattern similarity of concept cell activities represents semantic categories (Reber et al., 2019). Figure 7 shows the structure of DSI word representations visualized by MDS. We arbitrarily chose words based on 10

Figure 7: Visualization of the representational structure of DSI using MDS. Words are plotted in coordinates embedded in 2-D DSI space. Each color corresponds to a semantic category used in Reber et al. (2019).

semantic categories used in Reber et al. (2019), and used same dissimilarity metric with Reber et al. (2019) (1 - Pearson's correlation coefficient). In this visualization, we can see clustering of words corresponding to 10 semantic categories used in Reber et al. (2019).

5.4 Intuitive mechanism of word representations by DSI

In this section, we discuss intuitive interpretation of how DSI vectors represent and compute words as neural activity patterns. At least in a simple case, each word is represented by a combination (assembly) of concept-specific units, and analogical inference is recombination of those units.

First, we analyzed the ratio of each element to the sum of all elements in DSI vectors. We found that even the largest element accounted for 5% of the sum of all elements on average. (Figure 8). This shows that DSI vectors for words are non-sparse and distributed, thus each word is represented by the combination of multiple conceptual units.

Next, we inspected representations of an example set of words: France, Paris, Germany and Berlin. In those words, we can see two analogical relationships (country-capital and French-German relationships). We identified the most active units (TOP-2) in DSI vectors for those words, and listed TOP-10 words for identified units. As a result, we could see that "France" is represented by the combination of units that we could name as French cell and country cell, whereas "Berlin" is represented by the combination of German cell and capital cell, and so on (Figure 9). This example gives a simple interpretation of word similarity in DSI vector space. If words are similar, they share the large number of active conceptual units, like the country cell shared by representations of France and Germany. Thus, semantic similarity between words increases cosine similarity between word vectors.

Furthermore, we also identified the largest elements (the largest absolute values) in the difference vectors between words, and found that they correspond to semantic difference between words (Figure 9). Thus, we can regard analogical inference by DSI vectors as recombination of conceptual units. Transformation from "Paris" to "France" corresponds

Figure 8: Non-sparsity of word representations. Gray lines show ratio of each element to sum of all elements in each word representation vector, and the black line is the average of them. Elements were sorted in descending order.

to activation of country cell and deactivation of capital cell, which is possible by summing the difference of Germany and Berlin vectors.

Such property of the vector space is same as conventional word embedding methods, but unique feature of our disentangled representations is that those analogical relationships are factorized into separated units. We speculate that constraints of decorrelative NMF are sufficient conditions to align each semantic factors to each axis of the word vector space.

6 Relationship between model components and representations

To clarify the contribution of each model component to the results in this study, we performed a "lesion study" in which we removed some components in DSI and repeated the same evaluation procedure as above. We summarize results in Table 3. First, we tested representations obtained by singular value decomposition of successor representation (SR-SVD), which was regarded as a model of grid cells in a previous study (Stachenfeld et al., 2017). DSI model exceeded SR-SVD in all aspects shown in this study. Next, we tested DSI model without decorrelation ($\beta_{cor} = 0$) and DSI model without non-negativity (no rectification of representation vectors). Neither modification impaired the performance of navigation and inference, showing the importance of using SI for vector-based computations as theoretically expected. In contrast, removing decorrelation and non-negativity significantly impaired the emergence of grid-like units and concept-specific units, respectively. Thus, constraints in decorrelative NMF is crucial to obtain biologically plausible representations.

7 Discussion

In this paper, we proposed a theoretically interpretable and biologically plausible neural representation model for physical and conceptual spaces. We demonstrated that our DSI model forms grid-like representations in the physical space and concept-specific representations in the linguistic space, which are assumed to correspond to neural representations in EC. Furthermore, we showed that SI is mathematically related to reinforcement learning and word embedding, thus DSI representations support spatial navigation and conceptual inference. These results suggest that we can extend the spatial representation model of EC

The most active units in each vector (the largest absolute values)

France	Germany	Paris	Berlin
1. Unit 285	1. Unit 285	1. Unit 142	1. Unit 134
2. Unit 142	2. Unit 134	2. Unit 281	2. Unit 281

France-Paris	Germany-Berlin	France-Germany	Paris-Berlin
1. Unit 281	1. Unit 285	1. Unit 142	1. Unit 142
2. Unit 285	2. Unit 281	2. Unit 134	2. Unit 134

TOP 10 words for each unit

Unit 134	Unit 142	Unit 281	Unit 285
friedrich	et	stockholm	belgium
heinrich	des	budapest	finland
ludwig	le	oslo	bulgaria
karl	du	frankfurt	denmark
johann	les	são	countries
von	françois	copenhagen	greece
und	jacques	istanbul	colombia
ernst	michel	paulo	switzerland
wilhelm	pays	amsterdam	austria
der	jean	seoul	croatia
German cell	*French cell*	*Capital cell*	*Country cell*

Figure 9: Words as combination of concepts and inference as recombination. (Upper) The most active units (the largest absolute values) in representation vectors for France, Germany, Paris, Berlin, and difference vectors between them. (Lower) TOP-10 words of active units and their interpretation.

Table 3: Contribution of each model component (SI, decorrelation, non-negativity) to the performance. Rates of grid-like units, near-optimal navigation, significantly concept-specific units, correct analogical inference are shown.

Method	Grid cell	Navigation	Concept cell	Analogy
Full DSI	51%	97.2%	35%	63%
Decorr. OFF	5%	99.9%	38%	64%
Non-neg. OFF	29%	99.8%	2%	63%
SR-SVD	21%	57.2%	13%	28%

to learn and compute linguistic concepts, which apparently seems a different computational domain from physical space.

In decorrelative NMF, we introduced non-negativity and decorrelation as constraints. Those constraints are also important for extraction of independent components (Oja & Plumbley, 2004; Hyvärinen & Oja, 2000), and it is known that imposing independence in latent spaces of deep generative models results in the emergence of disentangled representations for visual features (Higgins et al., 2017). As those disentangled visual representations explain single-cell activities in higher-order visual cortex (Higgins et al., 2021), we may similarly interpret conceptual representations in our model as concept cells in the human medial temporal lobe (Quiroga, 2012). Previous studies suggest that each concept cell respond to a specific concept, whereas population-level activity patterns represent abstract semantic structures (Reber et al., 2019). Such property is consistent with the factorized and distributed nature of disentangled representation vectors.

Although DSI has clear mathematical interpretation, how biological neural networks can learn DSI is still unclear. A possible solution is an extension of skip-gram neural network

with SR, non-negativity, and decorrelation. Because SI corresponds to PMI which is the optimum of skip-gram neural network, we can expect that extended skip-gram network learns DSI. Building such model and relating it to the circuit mechanism in hippocampus and EC are left for future research.

Our model relates word embedding to conceptual representations in the brain. Previously study showed that skip-gram representations support high-performance decoding of semantic information from fMRI data (Nishida & Nishimoto, 2018). Another study revealed that hippocampal theta oscillation codes semantic distances between words measured in word2vec subspace (Solomon et al., 2019). These experimental results support our hypothesis. However, recent studies have shown that representations in transformer-based models (Vaswani et al., 2017) such as GPT (Brown et al., 2020) achieve remarkable performance in linear fitting to neural recording during linguistic processing (Goldstein et al., 2022; Schrimpf et al., 2021). A major difference between our DSI model and transformer-based models is that DSI representations are basically fixed (static embedding) whereas transformer-based models flexibly create context-dependent representations (dynamic embedding). Computation of concepts obviously depends on the context, thus activities of concept cells are dependent on contexts such as memory contents and task demands (Bausch et al., 2021). Therefore, our DSI model should be extended to process context-dependence, hopefully by combination with other models for learning context-dependent latent cognitive states (Uria et al., 2020; George et al., 2021; Whittington et al., 2020).

Another direction of future research is application to general conceptual spaces by learning DSI representations from low-level sensory inputs, like spatial learning from visual and auditory inputs in previous models (Banino et al., 2018; Taniguchi et al., 2018; Uria et al., 2020). It may be possible by learning discrete states by unsupervised clustering for deep networks (Caron et al., 2018). As for the human brain, infants probably form primitive spatial and conceptual representations from sensory signals, and later linguistic inputs enrich those representations. We speculate that real-world sensory data also contain the information of the conceptual space, which extended DSI can learn. Such model would clarify the role of the hippocampal system and EC in computation of general conceptual spaces.

Acknowledgments

We thank Ryo Yoshida for supporting the analysis of representations in BERT model. This research was partially supported by JSPS KAKENHI Grant Numbers 21K15611, 19H04994, 18H05213, and JST PRESTO Grant Number JPMJPR21C2.

References

Eneko Agirre, Enrique Alfonseca, Keith Hall, Jana Kravalova, Marius Pas¸capas¸ca, and Aitor Soroa. A study on similarity and relatedness using distributional and wordnet-based approaches. pp. 19–27, 2009. URL https://aclanthology.org/N09-1003/.

Andrea Banino, Caswell Barry, Benigno Uria, Charles Blundell, Timothy Lillicrap, Piotr Mirowski, Alexander Pritzel, Martin J. Chadwick, Thomas Degris, Joseph Modayil, Greg Wayne, Hubert Soyer, Fabio Viola, Brian Zhang, Ross Goroshin, Neil Rabinowitz, Razvan Pascanu, Charlie Beattie, Stig Petersen, Amir Sadik, Stephen Gaffney, Helen King, Koray Kavukcuoglu, Demis Hassabis, Raia Hadsell, and Dharshan Kumaran. Vector-based navigation using grid-like representations in artificial agents. *Nature*, 557:429–433, 5 2018. ISSN 14764687. doi: 10.1038/s41586-018-0102-6.

Xiaojun Bao, Eva Gjorgieva, Laura K. Shanahan, James D. Howard, Thorsten Kahnt, and Jay A. Gottfried. Grid-like neural representations support olfactory navigation of a two-dimensional odor space. *Neuron*, 102:1066–1075.e5, 6 2019. ISSN 10974199. doi: 10.1016/j.neuron.2019.03.034.

Marcel Bausch, Johannes Niediek, Thomas P. Reber, Sina Mackay, Jan Boström, Christian E. Elger, and Florian Mormann. Concept neurons in the human medial temporal lobe flexibly represent abstract relations between concepts. *Nature Communications*, 12, 12 2021. ISSN 20411723. doi: 10.1038/s41467-021-26327-3.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. *arXiv*, 5 2020. URL http://arxiv.org/abs/2005.14165.

Yoram Burak and Ila R. Fiete. Accurate path integration in continuous attractor network models of grid cells. *PLoS Computational Biology*, 5, 2009. ISSN 15537358. doi: 10.1371/journal.pcbi.1000291.

Daniel Bush, Caswell Barry, Daniel Manson, and Neil Burgess. Using grid cells for navigation. *Neuron*, 87:507–520, 8 2015. ISSN 10974199. doi: 10.1016/j.neuron.2015.07.006.

Mathilde Caron, Piotr Bojanowski, Armand Joulin, and Matthijs Douze. Deep clustering for unsupervised learning of visual features. pp. 132–149, 7 2018. URL https://openaccess.thecvf.com/content_ECCV_2018/html/Mathilde_Caron_Deep_Clustering_for_ECCV_2018_paper.html.

Alexandra O Constantinescu, Jill X O'reilly, and Timothy E J Behrens. Organizing conceptual knowledge in humans with a gridlike code. *Science*, 352:1464–1468, 2016. doi: 10.1126/science.aaf0941. URL http://science.sciencemag.org/.

Christopher J Cueva and Xue-Xin Wei. Emergence of grid-like representations by training recurrent neural networks to perform spatial localization. 2018. URL https://openreview.net/forum?id=B17JTOe0-.

Peter Dayan. Improving generalization for temporal difference learning: The successor representation. *Neural Computation*, 5:613–624, 1993. ISSN 0899-7667. doi: 10.1162/neco.1993.5.4.613.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arxiv*, 10 2018. URL http://arxiv.org/abs/1810.04805.

Christian F. Doeller, Caswell Barry, and Neil Burgess. Evidence for grid cells in a human memory network. *Nature*, 463:657–661, 2 2010. ISSN 00280836. doi: 10.1038/nature08704.

Yedidyah Dordek, Daniel Soudry, Ron Meir, and Dori Derdikman. Extracting grid cell characteristics from place cell inputs using non-negative principal component analysis. 2016. doi: 10.7554/eLife.10094.001.

Ruiqi Gao, Jianwen Xie, Song-Chun Zhu, and Ying Nian Wu. Learning grid cells as vector representation of self-position coupled with matrix representation of self-motion. 2019. URL https://openreview.net/forum?id=Syx0Mh05YQ.

Dileep George, Rajeev V. Rikhye, Nishad Gothoskar, J. Swaroop Guntupalli, Antoine Dedieu, and Miguel Lázaro-Gredilla. Clone-structured graph representations enable flexible learning and vicarious evaluation of cognitive maps. *Nature Communications*, 12, 12 2021. ISSN 20411723. doi: 10.1038/s41467-021-22559-5.

Ariel Goldstein, Zaid Zada, Eliav Buchnik, Mariano Schain, Amy Price, Bobbi Aubrey, Samuel A. Nastase, Amir Feder, Dotan Emanuel, Alon Cohen, Aren Jansen, Harshvardhan Gazula, Gina Choe, Aditi Rao, Catherine Kim, Colton Casto, Lora Fanda, Werner Doyle, Daniel Friedman, Patricia Dugan, Lucia Melloni, Roi Reichart, Sasha Devore, Adeen Flinker, Liat Hasenfratz, Omer Levy, Avinatan Hassidim, Michael Brenner, Yossi Matias, Kenneth A. Norman, Orrin Devinsky, and Uri Hasson. Shared computational principles for language processing in humans and deep language models. *Nature Neuroscience*, 25: 369–380, 3 2022. ISSN 15461726. doi: 10.1038/s41593-022-01026-4.

Torkel Hafting, Marianne Fyhn, Sturla Molden, May Britt Moser, and Edvard I. Moser. Microstructure of a spatial map in the entorhinal cortex. *Nature*, 436:801–806, 8 2005. ISSN 00280836. doi: 10.1038/nature03721.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. 2017. URL `https://openreview.net/forum?id=Sy2fzU9gl`.

Irina Higgins, Le Chang, Victoria Langston, Demis Hassabis, Christopher Summerfield, Doris Tsao, and Matthew Botvinick. Unsupervised deep learning identifies semantic disentanglement in single inferotemporal face patch neurons. *Nature Communications*, 12, 12 2021. ISSN 20411723. doi: 10.1038/s41467-021-26751-5.

A. Hyvärinen and E. Oja. Independent component analysis: algorithms and applications. *Neural Networks*, 13:411–430, 6 2000. ISSN 08936080. doi: 10.1016/S0893-6080(00)00026-5. URL `https://linkinghub.elsevier.com/retrieve/pii/S0893608000000265`.

Joshua Jacobs, Christoph T. Weidemann, Jonathan F. Miller, Alec Solway, John F. Burke, Xue Xin Wei, Nanthia Suthana, Michael R. Sperling, Ashwini D. Sharan, Itzhak Fried, and Michael J. Kahana. Direct recordings of grid-like neuronal activity in human spatial navigation. *Nature Neuroscience*, 16:1188–1190, 9 2013. ISSN 10976256. doi: 10.1038/nn.3466.

Daniel D. Lee and H. Sebastian Seung. Learning the parts of objects by non-negative matrix factorization. *Nature*, 401:788–791, 10 1999. ISSN 0028-0836. doi: 10.1038/44565. URL `http://www.nature.com/articles/44565`.

Omer Levy and Yoav Goldberg. Neural word embedding as implicit matrix factorization. pp. 2177–2185, 2014.

Bruce L. McNaughton, Francesco P. Battaglia, Ole Jensen, Edvard I. Moser, and May Britt Moser. Path integration and the neural basis of the 'cognitive map'. *Nature Reviews Neuroscience*, 7:663–678, 8 2006. ISSN 1471003X. doi: 10.1038/nrn1932.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv*, 1 2013a. URL `http://arxiv.org/abs/1301.3781`.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Distributed representations of words and phrases and their compositionality. *arXiv*, 2013b. URL `https://arxiv.org/abs/1310.4546`.

I. Momennejad, E. M. Russek, J. H. Cheong, M. M. Botvinick, N. D. Daw, and S. J. Gershman. The successor representation in human reinforcement learning. *Nature Human Behaviour*, 1:680–692, 9 2017. ISSN 2397-3374. doi: 10.1038/s41562-017-0180-8. URL `http://www.nature.com/articles/s41562-017-0180-8`.

Ida Momennejad. Learning structures: Predictive representations, replay, and generalization. *Current Opinion in Behavioral Sciences*, 32:155–166, 4 2020. ISSN 23521546. doi: 10.1016/j.cobeha.2020.02.017.

Brian Murphy, Partha Pratim Talukdar, and Tom Mitchell. Learning effective and interpretable semantic models using non-negative sparse embedding. pp. 1933–1950, 2012.

Yurii Evgen'evich Nesterov. A method of solving a convex programming problem with convergence rate o(k^2). In *Doklady Akademii Nauk*, volume 269, pp. 543–547. Russian Academy of Sciences, 1983.

Satoshi Nishida and Shinji Nishimoto. Decoding naturalistic experiences from human brain activity via distributed representations of words. *NeuroImage*, 180:232–242, 10 2018. ISSN 10959572. doi: 10.1016/j.neuroimage.2017.08.017.

Junhyuk Oh, Xiaoxiao Guo, Honglak Lee, Richard Lewis, and Satinder Singh. Action-conditional video prediction using deep networks in atari games. pp. 2863–2871, 2015. URL `https://proceedings.neurips.cc/paper/2015/file/6ba3af5d7b2790e73f0de32e5c8c1798-Paper.pdf`.

Erkki Oja and Mark Plumbley. Blind separation of positive sources by globally convergent gradient search. *Neural Computation*, 16:1811–1825, 9 2004. ISSN 0899-7667. doi: 10.1162/0899766041336413. URL `https://direct.mit.edu/neco/article/16/9/1811-1825/6847`.

Seongmin A. Park, Douglas S. Miller, and Erie D. Boorman. Inferences on a multidimensional social hierarchy use a grid-like code. *Nature Neuroscience*, 24:1292–1301, 9 2021. ISSN 15461726. doi: 10.1038/s41593-021-00916-3.

Jeffrey Pennington, Richard Socher, and Christopher Manning. Glove: Global vectors for word representation. pp. 1532–1543. Association for Computational Linguistics, 2014. doi: 10.3115/v1/D14-1162. URL `http://aclweb.org/anthology/D14-1162`.

Payam Piray and Nathaniel D. Daw. Linear reinforcement learning in planning, grid fields, and cognitive control. *Nature Communications*, 12, 12 2021. ISSN 20411723. doi: 10.1038/s41467-021-25123-3.

Princeton University. About wordnet. `https://wordnet.princeton.edu/`, 2010.

Rodrigo Quian Quiroga. Concept cells: the building blocks of declarative memory functions. *Nature Reviews Neuroscience*, 13:587–597, 8 2012. ISSN 1471003X. doi: 10.1038/nrn3251.

Thomas P. Reber, Marcel Bausch, Sina Mackay, Jan Boström, Christian E. Elger, and Florian Mormann. Representation of abstract semantic knowledge in populations of human single neurons in the medial temporal lobe. *PLoS Biology*, 17, 6 2019. ISSN 15457885. doi: 10.1371/journal.pbio.3000290.

Francesca Sargolini, Marianne Fyhn, Torkel Hafting, Bruce L. McNaughton, Menno P. Witter, May-Britt Moser, and Edvard I. Moser. Conjunctive representation of position, direction, and velocity in entorhinal cortex. *Science*, 312:758–762, 5 2006. ISSN 0036-8075. doi: 10.1126/science.1125572. URL `https://www.science.org/doi/10.1126/science.1125572`.

Martin Schrimpf, Idan Asher Blank, Greta Tuckute, Carina Kauf, Eghbal A. Hosseini, Nancy Kanwisher, Joshua B. Tenenbaum, and Evelina Fedorenko. The neural architecture of language: Integrative modeling converges on predictive processing. *Proceedings of the National Academy of Sciences*, 118, 11 2021. ISSN 0027-8424. doi: 10.1073/pnas.2105646118. URL `https://pnas.org/doi/full/10.1073/pnas.2105646118`.

Ethan A. Solomon, Bradley C. Lega, Michael R. Sperling, and Michael J. Kahana. Hippocampal theta codes for distances in semantic and temporal spaces. *Proceedings of the National Academy of Sciences of the United States of America*, 116:24343–24352, 11 2019. ISSN 10916490. doi: 10.1073/pnas.1906729116.

Ben Sorscher, Gabriel C Mel, Surya Ganguli, and Samuel A Ocko. A unified theory for the origin of grid cells through the lens of pattern formation. pp. 10003–10013, 2019. URL https://proceedings.neurips.cc/paper/2019/file/6e7d5d259be7bf56ed79029c4e621f44-Paper.pdf.

Ben Sorscher, Gabriel C. Mel, Samuel A. Ocko, Lisa M. Giocomo, and Surya Ganguli. A unified theory for the computational and mechanistic origins of grid cells. *Neuron*, 111: 121–137.e13, 1 2023. ISSN 10974199. doi: 10.1016/j.neuron.2022.10.003.

Kimberly L. Stachenfeld, Matthew M. Botvinick, and Samuel J. Gershman. The hippocampus as a predictive map. *Nature Neuroscience*, 20:1643–1653, 2017. ISSN 15461726. doi: 10.1038/nn.4650.

Hanne Stensola, Tor Stensola, Trygve Solstad, Kristian FrØland, May Britt Moser, and Edvard I. Moser. The entorhinal grid map is discretized. *Nature*, 492:72–78, 12 2012. ISSN 00280836. doi: 10.1038/nature11649.

Akira Taniguchi, Tadahiro Taniguchi, and Tetsunari Inamura. Unsupervised spatial lexical acquisition by updating a language model with place clues. *Robotics and Autonomous Systems*, 99:166–180, 1 2018. ISSN 09218890. doi: 10.1016/j.robot.2017.10.013.

Emanuel Todorov. Linearly-solvable markov decision problems. pp. 1369–1376, 2006. URL https://papers.nips.cc/paper/2006/hash/d806ca13ca3449af72a1ea5aedbed26a-Abstract.html.

Emanuel Todorov. Efficient computation of optimal actions. *Proceedings of the National Academy of Sciences of the United States of America*, 106:11478–11483, 7 2009. ISSN 00278424. doi: 10.1073/pnas.0710743106.

Benigno Uria, Borja Ibarz, Andrea Banino, Vinicius Zambaldi, Dharshan Kumaran, Demis Hassabis, Caswell Barry, and Charles Blundell. A model of egocentric to allocentric understanding in mammalian brains. *biorxiv*, 2020. doi: 10.1101/2020.11.11.378141. URL https://doi.org/10.1101/2020.11.11.378141.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. pp. 5998–6008, 6 2017. URL https://papers.nips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html.

James C. R. Whittington, Joseph Warren, and Timothy E. J. Behrens. Relating transformers to models and neural representations of the hippocampal formation. 12 2022. URL http://arxiv.org/abs/2112.04035.

James C.R. Whittington, Timothy H. Muller, Shirley Mark, Guifen Chen, Caswell Barry, Neil Burgess, and Timothy E.J. Behrens. The tolman-eichenbaum machine: Unifying space and relational memory through generalization in the hippocampal formation. *Cell*, 183:1249–1263.e23, 11 2020. ISSN 10974172. doi: 10.1016/j.cell.2020.10.024.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick Von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M Rush. Transformers: State-of-the-art natural language processing. pp. 38–45, 2020. doi: 10.18653/v1/2020. emnlp-demos.6. URL https://aclanthology.org/2020.emnlp-demos.6.

A Appendix

A.1 Calculation of SR

Throughout this study, we used a direct count method because we performed only offline processing of finite data. In a sequence of states $\{s_1, \ldots, s_t, \ldots, s_T\}$, we recursively calculated exponential traces of past states $z(s, t) = \sum_{\tau=0}^{t-1} \gamma^\tau \delta(s_{t-\tau}, s)$ as

$$z(s, t) = \gamma z(s, t-1) + \delta(s_t, s), \tag{12}$$

and calculated SR from state counts and coincidence counts as

$$SR(s, s') = \frac{\sum_{t=1}^{T} z(s, t)\delta(s_t, s')}{\sum_{t=1}^{T} \delta(s_t, s)}. \tag{13}$$

A.2 Details of decorrelative NMF

In decorrelative NMF, we iteratively updated vectors $\boldsymbol{x}(s)$ and $\boldsymbol{w}(s)$ by Nesterov's accelerated gradient descent method to minimize the objective function (Eq. 4), rectifying all elements every iteration. Gradients are

$$\frac{\partial J}{\partial x_k(s)} = -\sum_{s'} \rho(s, s')(PSI(s, s') - \boldsymbol{x}(s) \cdot \boldsymbol{w}(s'))w_k(s')$$

$$+ \beta_{cor} \sum_{j \neq k} \frac{Corr(k, j)\tilde{x}_j(s)}{\sqrt{\sum_s (\tilde{x}_k(s))^2 \sum_s (\tilde{x}_j(s))^2}} + \beta_{reg} x_k(s), \tag{14}$$

$$\frac{\partial J}{\partial w_k(s')} = -\sum_{s} PSI(s, s')(PSI(s, s') - \boldsymbol{x}(s) \cdot \boldsymbol{w}(s'))x_k(s) + \beta_{reg} w_k(s'). \tag{15}$$

We note that we regarded mean and variance of $x_i(s)$ in the correlation ($\frac{1}{N_s} \sum_s x_i(s), \sum_s (\tilde{x}_i(s))^2$ in Eq. 6) as constants in the calculation of these gradients. Practically, this heuristic did not affect the performance of decorrelation.

Throughout this paper, the learning rate was 0.05 and the number of iteration was 10000. Parameters were $\beta_{cor} = 1, \beta_{reg} = 0.001$, and $\rho_{min} = 0.001$.

A.3 Mathematical relationship of DSI and reinforcement learning

In this section, we show that our model approximates value functions of linear reinforcement learning (Todorov, 2006, 2009; Piray & Daw, 2021) in the setting of spatial navigation.

In linear reinforcement learning, an agent aims to maximize "gain" instead of reward. Assuming a default policy $\pi^d(s)$ (any policy is available; typically random walk in the case of exploration task), gain function is defined as

$$g(s) = r(s) - \lambda KL(\pi(s)|\pi^d(s)), \tag{16}$$

where $r(s)$ is expected reward at the state s and $\lambda KL(\pi(s)|\pi^d(s))$ is the cost imposed on the difference between the current policy $\pi(s)$ and the default policy $\pi^d(s)$ (λ is a relative weight of the cost). Then, previous works have shown that the optimal policy and corresponding value functions can be determined explicitly by solving linear equations (Todorov, 2006, 2009; Piray & Daw, 2021). Here we consider an environment that consists of N_N non-terminal states and N_T terminal states. We define two transition probability matrices under the default policy: $\boldsymbol{P}_{NT}$ is a $N_N \times N_T$ matrix for transitions from non-terminal states to terminal states, and $\boldsymbol{P}_{NN}$ is a $N_N \times N_N$ matrix for transitions across non-terminal states. Furthermore, $\boldsymbol{r}_N$ and $\boldsymbol{r}_T$ are vectors of rewards at non-terminal states and terminal

states, respectively. In this condition, a vector of value functions under optimal policy $\boldsymbol{v}^* = (v^*(s_1), \ldots, v^*(s_{N_N}))$ is obtained as

$$\exp(\lambda^{-1}\boldsymbol{v}^*) = \boldsymbol{M}\boldsymbol{P}_{NT}\exp(\lambda^{-1}\boldsymbol{r}_T), \qquad (17)$$

where $\boldsymbol{M} = (\text{diag}(\exp(-\lambda^{-1}\boldsymbol{r}_N)) - \boldsymbol{P}_{NN})^{-1}$ is DR (Piray & Daw, 2021).

To relate $\boldsymbol{v}^*$ to SI, we consider a specific condition in which the environment consists of non-terminal states, and a virtual terminal state is attached to a goal state s_G arbitrarily chosen from non-terminal states. When the agent gets to the goal, it transits to the terminal state with a probability p_{NT}. Furthermore, we assume that reward at non-terminal states are uniformly negative and reward at the terminal state is positive so that the agent has to take a short path to goal to maximize reward. Specifically, we assume all elements of $\boldsymbol{r}_N$ are $\lambda \log \gamma$, and $r_T = -\lambda(\log \gamma + \log p_{NT} + \log P^d(s_G))$ where γ is an arbitrary value in the range $(0, 1)$, and $P^d(s_G)$ is a probability of visiting the state s_G under the default policy. Then, we obtain

$$\exp(\lambda^{-1}\boldsymbol{v}^*) = \frac{1}{P^d(s_G)}(\boldsymbol{I} - \gamma P_{NN})^{-1}\boldsymbol{e}^{(i_G)}, \qquad (18)$$

where $\boldsymbol{e}^{(i_G)} = (0, \ldots, 0, 1, 0, \ldots, 0)^T$ (i_G is the index of the goal state). Because $(\boldsymbol{I} - \gamma P_{NN})^{-1}$ is equivalent to a successor representation matrix with a discount factor γ (Dayan, 1993; Stachenfeld et al., 2017), we finally obtain

$$\lambda^{-1}v^*(s) = \log(SR^d(s, s_G)) - \log P^d(s_G) = SI^d(s, s_G) \approx \boldsymbol{x}(s) \cdot \boldsymbol{w}(s_G), \qquad (19)$$

where $SR^d(s, s_G)$ and $SI^d(s, s_G)$ are SR and SI under the default policy, respectively. Thus, SI is proportional to value functions for spatial navigation and inner products of DSI vectors approximates value functions. Based on this interpretation, we basically regard $\boldsymbol{x}(s)$ as a representation of each state, and $\boldsymbol{w}(s)$ represents a temporary goal.

A.4 Details of evaluation of grid representations

In the section 4.2, we performed the gridness analysis following a previous experimental study (Sargolini et al., 2006). For each unit, we rotated the spatial autocorrelation map (Figure 1B, lower) and calculated correlations between the original and rotated maps. Gridness was defined as the difference between the lowest correlation at $60°$ and $120°$ and the highest correlation at $30°$, $90°$ and $150°$. A unit was classified as a grid cell when gridness exceeds zero.

In Figure 1C, we constructed a distribution of grid scales. Grid scales were determined as the median of distances between the central peak and the six closest peaks (vertices of inner hexagon) in the spatial autocorrelation map. The kernel function for kernel density estimation was Gaussian with a standard deviation 1.

A.5 Details of vector-based inference of the spatial context

In the section 4.5, we performed vector-based inference for spatial navigation in a novel context. Specifically, we define separated states in contexts A, B, A+B as s_i^A, s_i^B and s_i^{A+B}, where i is a positional index which indicates a same position in all contexts ($i = 1, 2, \cdots, 900$). We constructed representation vectors $\boldsymbol{x}(s_i^A)$, $\boldsymbol{w}(s_i^A)$, $\boldsymbol{x}(s_i^B)$, and $\boldsymbol{w}(s_i^B)$ through direct experiences, then we created $\boldsymbol{x}(s_i^{A+B})$ and $\boldsymbol{w}(s_i^{A+B})$ as

$$\boldsymbol{x}(s_i^{A+B}) = \boldsymbol{x}(s_i^A) + \boldsymbol{x}(s_i^B), \qquad (20)$$

$$\boldsymbol{w}(s_i^{A+B}) = \boldsymbol{w}(s_i^A) + \boldsymbol{w}(s_i^B). \qquad (21)$$

We performed spatial navigation in a given context using one of three representations $\{\boldsymbol{x}(s_i^A), \boldsymbol{w}(s_i^A)\}$, $\{\boldsymbol{x}(s_i^B), \boldsymbol{w}(s_i^B)\}$, and $\{\boldsymbol{x}(s_i^{A+B}), \boldsymbol{w}(s_i^{A+B})\}$ for corresponding positions, following the rule described in the section 4.4. In figure 10, we show structures of state transition graphs for three contexts A, B, and A+B.

Figure 10: Structures of state transition graphs used in the section 4.5.

To learn representations in contexts A and B, we sampled sequences of $\{s_i^A\}_{i=1,\cdots,900}$ and $\{s_i^B\}_{i=1,\cdots,900}$ by random walk in context A and B. The procedure was basically same with the section 4 except that we increased the number of simulation trials from 500 to 1,000, and state transition to the same position in the other context occurred every 5,000 time steps (transition between s_i^A and s_i^B). We added this transition to associate the same position in different contexts. It means that we assumed that the setting of barriers can change during the experience but this temporal association may be substituted by similarity of sensory inputs across contexts. From sampled sequences, we calculated PSI for all combinations of $\{s_i^A\}_{i=1,\cdots,900}$ and $\{s_i^B\}_{i=1,\cdots,900}$, and calculated 100-dimensional DSI vectors for 1,800 states by simultaneous compression of all states. The discount factor γ was set to 0.999.

A.6 Details of preprocessing of text data

In the section 5, we used text data taken from English Wikipedia dump (enwiki-latest-pages-articles, 22-May-2020). We first generated text files from raw data using wikiextrator (`https://github.com/attardi/wikiextractor`). We tokenized texts by nltk Punkt sentense tokenizer, and randomly sampled 100,000 articles containing 1,000 tokens at minimum. We lowercased all characters and removed punctuation characters in the data. After that, we selected words that appeared more than 1,000 times in the data, and substituted all other rare words by <unk> symbol. Finally, we obtained data that contains 124M tokens and 9376 words.

A.7 Details of evaluation of conceptual specificity

In the section 5.2, conceptual specificity of each unit was evaluated using WordNet database (Princeton University, 2010). In WordNet, a word belongs to several synsets (sets of cognitive synonyms), and semantic similarity of two synsets can be evaluated from the shortest path length between them in the WordNet structure (we used path_similarity function in nltk library). We defined similarity of two words as the highest similarity among all combinations of synsets of those words. We calculated mean similarity of all combinations of TOP-10 words (ten words that highly activated the unit; Figure 6A) that are available in WordNet. We evaluated only units which had at least five TOP-10 words available in WordNet. Furthermore, we randomly generated 1,000 pairs of words available in WordNet, and generated a null distribution of similarity between words. We defined a significance threshold of similarity as a 95 percentile of the null distribution, and a unit was classified as a significantly concept-specific unit if mean similarity of TOP-10 words exceeded the threshold. Furthermore, we quantitatively defined a conceptual specificity of each unit as

$$\frac{s_{unit}}{s_{null}} - 1, \tag{22}$$

where s_{unit} is mean similarity of TOP-10 words and s_{null} is the mean of the null distribution. This quantity becomes zero if similarity between TOP-10 words is not different from random

pairs, and becomes positive if TOP-10 words are semantically similar. This conceptual specificity was averaged over all evaluated units.

A.8 Details of the analogical inference task

In table 4, we show some examples of the analogical inference in Mikolov's dataset. There is a relationship "WORD1 is to WORD2 as WORD3 is to WORD4". Then, an expected relationship in the vector space is WORD2-WORD1=WORD4-WORD3. In this study, we performed inference of WORD4 by WORD3+WORD2-WORD1. We regarded an inference was correct if the actual vector of WORD4 had the largest cosine similarity to the inferred vector among all word representation vectors (except those for WORD1, WORD2, and WORD3). If the number of words is 10,000, a chance level of the correct answer rate is 0.01%. Therefore, the performance shown in this study (more than 50%) is far above the chance level.

Table 4: Examples of analogical relationships in Mikolov's dataset.

WORD1	WORD2	WORD3	WORD4
boy	girl	king	queen
husband	wife	he	she
Paris	France	Tokyo	Japan
China	Chinese	Italy	Italian
big	bigger	small	smaller
free	freely	quick	quickly
convenient	inconvenient	possible	impossible

A.9 Example DSI representations for words

In the figure 11, we show TOP-10 words of DSI units without manual selection. We found several non-significant units exhibit conceptual specificity according to manual inspection (for example, unit4 may be named as university cell). This is probably because of the limitation of knowledge covered by WordNet. Therefore, we suppose that the current evaluation method tends to underestimate the number of concept-specific units. However, the comparison across models was fair because we used the same procedure and criteria for all models.

Unit 1	Unit 2	Unit 3	Unit 4	Unit 5
faced	transit	humid	universities	sheets
overcome	commuter	winters	colleges	olivia
facing	trains	summers	uc	compact
due	bus	climate	usc	senators
owing	buses	mild	consortium	antony
citing	subway	precipitation	institutes	proposes
experiencing	rail	warm	carnegie	atlas
cope	passenger	temperatures	affiliated	spaces
amid	metro	cool	alumni	geometry
suffered	passengers	cold	selective	rough

Unit 6	Unit 7	Unit 8	Unit 9	Unit 10
designers	rebounds	nbc	eleventh	nhl
scientists	assists	aired	tenth	confirmation
experts	averaged	abc	ninth	hockey
professionals	steals	airing	seventh	maple
consumers	nba	cbs	eighth	roller
researchers	averaging	syndicated	twelfth	judiciary
filmmakers	partition	programming	7th	flames
lawyers	points	broadcast	8th	devils
composers	prussia	channel	10th	batch
scholars	mvp	espn	11th	senators

Unit 11	Unit 12	Unit 13	Unit 14	Unit 15
lowest	valve	archive	hatch	rotten
ranked	wheel	archives	deaf	tomatoes
highest	steering	manuscripts	robot	metacritic
ranks	rotating	collections	suffrage	aggregate
literacy	wheels	collection	egg	approval
demographic	cylinder	manuscript	seymour	reviews
rising	trigger	library	salem	grossed
prevalence	shaft	catalogue	wwe	rating
ratings	pump	valuable	monte	byron
rank	gear	documents	resist	apparatus

Figure 11: A part of word representations formed by DSI. Ten words that gave the highest activation (TOP-10 words) are shown for units 1 - 15. Those classified as concept-specific units in our analysis are boxed with bold lines.