Social navigation: distance and grid-like codes support navigation of abstract social space in human brain

Zilu Liang[1], Simeng Wu[1], Jie Wu[1], Wenxu Wang[2], Shaozheng Qin[1] [*], Chao Liu[1] [*]

[1]State Key Laboratory of Cognitive Neuroscience and Learning & IDG/McGovern Institute for Brain Research, Beijing Normal University

[2]School of Systems Science, Beijing Normal University, Beijing, 100875, China

*Correspondence authors:
Shaozheng Qin: szqin@bnu.edu.cn
Chao Liu: liuchao@bnu.edu.cn

Abstract

People form impressions about others during daily social encounters and infer personality traits from others' behaviors. Such trait inference is thought to rely on two universal dimensions, i.e., competence and warmth. These two dimensions can be used to construct a 'social cognitive map' organizing massive information obtained from social encounters efficiently. Originated from spatial cognition, the neural codes supporting representation and navigation of spatial cognitive map has been widely studied. Recent studies suggest similar neural mechanism subserves the map-like architecture in social cognition as well. Here we investigated how spatial codes operate beyond physical environment and support the representation and navigation of social cognitive map. We designed a social value space defined by two dimensions of competence and warmth. Behaviorally, participants were able to navigate to a learned location from random starting locations in this abstract social space. At neural level, we identified representation of distance in precuneus, fusiform gyrus and middle occipital gyrus. We also found partial evidence of grid-like representation patterns in medial prefrontal cortex and entorhinal cortex. Moreover, the intensity of grid-like response scaled with performance of navigating in social space and social avoidance trait scores. Our findings suggest a neurocognitive mechanism by which social information can be organized into a structured representation namely cognitive map and its relevance to social well-being.

Introduction

Countless daily social encounters pose people with the need to organize information about social encounters efficiently. Though people may ascribe a variety of traits to others, these inferences has been identified to rely on a few universal dimensions (Fiske et al., 2007; Stolier et al., 2020). The most widely recognized dimensions are warmth, which concerns others intentions, and competence, which concerns others capability and possession of resources (Cuddy et al., 2008). These universal dimensions can be

used to construct a structured representation organizing impressions of other people or other social information alike, just like how one would specify a location in a plane using orthogonal dimensions for spatial navigation. Analogous to Tolman's original concept (Tolman, 1948), here we termed this structured representation of social information about other people as 'social cognitive map', which may form the basis for social cognition. Having such a cognitive map for social perception is crucial. It helps us organize various experiences, track updates and guide novel inferences efficiently (Son et al., 2021). Despite its importance in navigating social world, its neural underpinning remains under-investigated.

The resemblance between social and spatial cognitive map has led to the proposition that social cognitive map is also supported by similar mechanisms that map physical space (Schafer & Schiller, 2018). In the domain of spatial navigation, it has been demonstrated that entorhinal grid cell activity supports representational coding of cognitive map. Direct recordings in rodents (Hafting et al., 2005) and humans (Jacobs et al., 2013) have found that the firing locations of grid cells form periodic triangular that covers the entire available arena during spatial navigation task. In this sense, grid cells form the basic units of a neural map of the spatial environment. One of the prominent properties of grid cells is their consistent grid orientation (i.e., the orientation of the grid relative to the environment) shared by neighboring grid cells (Hafting et al., 2005; Sargolini et al., 2006). Moreover, the overlapping population formed by grid cells and head direction cells as well as conjunctive grid × head-direction cells in deeper layers of entorhinal cortex enables directional as well as positional tuning of the firing rate (Sargolini et al., 2006). It has been proposed that this conjunctive representation at a population level can yield a directionally modulated firing pattern with hexagonal periodicity in which population activity is enhanced when agent's moving direction is aligned to the grid axes (Kriegeskorte & Storrs, 2016; Kunz et al., 2019). Human studies using non-invasive neuroimaging techniques rely on this directional preference of populational conjunctive grid by head direction cell activity to detect evidence of grid-like code in fMRI BOLD signals during spatial navigation (Doeller et al., 2010). Follow-up studies have reported entorhinal grid code during virtual as well as imagined navigation (Horner et al., 2016), and even mental simulation (Bellmund et al., 2016). More importantly, pioneering studies showed that the function of grid-like code goes beyond the scope of spatial navigation. Grid-like codes in entorhinal cortex and prefrontal cortex have been observed during nonspatial navigation such as perceptual (Aronov et al., 2017; Bao et al., 2019; Killian et al., 2012; Nau et al., 2018), conceptual (Constantinescu et al., 2016), semantic space (Vigano & Piazza, 2020; Vigano et al., 2021) and more recently, discrete social hierarchy (Park et al., 2021). Evidence from above studies converges into a domain-general role of grid-like codes that may play in organizing cognitive maps of various types including spatial and nonspatial domains (Bellmund et al., 2018).

In this study, we tested the above hypothesis that social cognitive map is supported by a grid cell-like coding mechanism observed in spatial navigation. First, leveraging the theoretical framework of the stereotype content model, we set up an abstract two-dimensional social value map which are composed of competence and trustworthiness dimensions of social perception. Next, we adapted paradigms used in human fMRI grid-code study to test the hypothesis that grid-like codes and distance codes resembling those underpinning spatial navigation are involved in navigation in this abstract social space. Finally, to complete our argument that neural codes for social navigation subserve social cognition, we explored the link between neural codes during social navigation and social skills measured by navigational performance and social trait scores.

Results

To look for neural underpinnings of navigation in an abstract social space, we adapted a set of tasks from previous studies illustrating the relevance of grid-like code in navigating abstract concept space (Constantinescu et al., 2016). Participants received intensive training on navigating in this abstract social space with precision. They completed a learning session, a review session during behavioral training on the first day, and a scanning session on the second day.

We designed the social value map, an abstract social space structuring one's social perception of other people's social value. It was defined by two ecologically important dimensions: competence and trustworthiness. A visualization with two adjacent bars enclosed by a square box was designed to represent the location on this social value map, with the height of each bar representing value of each dimension. We operationally defined these two dimensions under the framework of an investment game, in which trustee's social value is determined by the ability to earn profit (i.e., profit rate as competence) and the proportion of earnings returned to the investor (i.e., return rate as trustworthiness). We limited the range of competence and trustworthiness between 0 and 1. This made sure that the two dimensions are realistic (i.e., it is unlikely that a trustee will return you more than he/she has gained), and more importantly, orthogonal and share same metric system (cite paper on distorted grid field). Participants played the role of an investor in this investment task (**Figure S1A**) at the very beginning of the experiment to develop a concrete understanding of the visual analogue and the quantitative meaning of these two dimensions.

Six avatars with different levels of competence and trustworthiness (**Figure 1A**), in analogy to landmarks in the physical environment, were placed on the social value map of size 1 unit × 1unit which was in accordance with the range of competence and trustworthiness. The current spatial arrangement aimed to make avatars distinguishable on both dimensions while spreading widely across the whole space. Specifically, each participant's set of avatars' coordinates was sampled within circles of 1/30-unit radius around center coordinates (**Figure 1B**). Avatars were represented by standard photographs of real human faces. Photographs were matched on competence and trustworthiness ratings based on rating data collected online via Qualtrics in an independent sample of participants (**Supplementary Methods**). Additionally, participants in the current sample also completed rating on the selected faces before the experiment and after the fMRI scan to reassure that the used face stimuli did not elicit biased social perception and to test whether participants learned each avatar's characteristics and updated their social perception accordingly.

In the training, participants explored the vast social space by morphing the bars with different competence: trustworthiness ratio using the non-spatial controller to look for the six avatars (**Figure S1C**). Morphing the bars resembles making a transition in the social space in that it was done by two steps: 1) deciding a trajectory to follow by changing the competence: trustworthiness ratio using the non-spatial controller, 2) how further along to follow that trajectory. No prior information about the characteristics of the avatars was provided to the participants. Thus, participants could only explore social space as if they were looking for landmarks in a newly introduced physical environment. An avatar would pop out when the visualization matched his/her characteristics. Specifically, the avatar would pop out when participants' current location fell within a 0.01-unit radius of the correct location on the social value map. In this way, participants not only learned the characteristics of each avatar but

also became familiar with the whole space even though this map-like structure was never revealed to

them.

Figure 1. Experimental Design and Behavioral Performance. (A) Visual analogues illustrating each

avatar's social values. Height of the left bars signals values on competence dimension, while height of

the right bars signals trustworthiness. Labels for each of the two bars are omitted for illustration purpose.

(B) Corresponding layout of the social value map and example trajectory in recall task. Scattered dots

indicate the actual sets of positions generated for participants. (C) Positions of the avatars indicated by

participants at the end of the whole experiment. (D) Trial timeline of the recall task. Participants first

watched the bars morphing for one second according to a predefined competence-trustworthiness ratio

(i.e., the first half of a trajectory in Figure 1B). After the bars stopped morphing, they were instructed to

imagine the bars continue to morph according to the same ratio, at the same speed and for the same

amount of time. (i.e., the second half of a trajectory in Figure 1B) (E) Color-coded trajectory map of the

explore task during learning and review session. Color indicated the percentage of time spent in each

pixel of the social value map during the explore task in the learning (left panel) and review (right panel)

session. A pattern emerged that participants spent more time at avatars and less time at edge during

review. (F) Memory test performance of the collect and recall task in learning, review and scan-day

session. (G) The distance effect in comparison task across the review and scan-day session. Colored dots

indicated the estimates of distance effect regressor while error bars indicated standard error of the

estimates. (H) Ratings became predictable from the avatars' social value after experiment. Icons of

avatars are for illustration and retrieved from https://pixabay.com/vectors/avatar-flat-modern-minimal-

5261900/, https://pixabay.com/vectors/avatar-flat-modern-minimal-5261896/.

After participants were fully acquainted with the avatars and the social space, a set of tasks were used to

test if participants learned the avatars, and more importantly, if they formed an internal representation of

the social value map, even though the map-like structure was never directly revealed to them. The first
one was the collect task (**Figure S1D**) which required participant to navigate to the location of the avatars
from random starting locations in the abstract space. In each trial, they were instructed to morph the box
on the left to match the characteristic of the avatar shown on the right. Specifically, we asked participants
to make as few transitions as possible. Two performance indices were calculated: 1) the deviation of
participant's first transition from the ideal trajectory; and 2) the Euclidean distance between the location
corresponding to participants' morphed bars and the avatar's actual location in the abstract space. The
second one was the recall task, which required participant to mentally traverse the abstract social space
according to a half-seen trajectory and identify the destination that follows (**Figure 1D**). In each trial,
participants were first shown the two bars morphing according to a predefined competence:
trustworthiness ratio for 1 second. The bars then stopped morphing, and participants were instructed to
imagine the bars keep morphing according to the same ratio, at the same speed, and for the same amount
of time. After this, participants had to choose which of the three given options matched the bars after
imagination. Essentially, each trial is a trajectory vector defined by moving direction (i.e., morphing ratio)
and travelled distance on the social value map. Participants' recall accuracies were taken as performance
index. We investigated the neural representation of the trajectory in each trial while participant perform
this task. The third one was the compare task which required participants to compare different pairs of
avatars on one given dimension (competence and trustworthiness) or by a fair combination of both
dimensions (willingness to cooperate). Under the assumption that participant's accuracy and response
time would be moderated by the similarity between the avatars, we predicted that participants would be
less accurate and take longer time when comparing avatars with closer distance on the given dimension
than when comparing avatars far apart if they represent the six avatars in the 2D space (similar to the
inferential distance effect in ordered relationships (Potts, 1974)). The final one was the map task at the
end of the experiment in which participants were informed about the map-like structure and were asked
to indicate the location of each avatar on an empty social value map using mouse click.

Participants construct social value map after associative learning of avatars and corresponding characteristics

Participants were successful in reconstructing such a layout in a map task at the end of experiment
(**Figure 1C**). Linear mixed effect models revealed that participants' performance in tasks significantly
improved over sessions. In the explore task, it took them significantly less time to find all avatars in the
review session ($\beta_{session}$ = -67.589, t = -37.604, p < 0.001). They also spent much less time at edge (β = -
0.104, t = -9.070, p < 0.001) and more time at avatars ($\beta_{session}$ = 0.023, t = 7.367, p < 0.001) during
exploration in the review session (**Figure 1E**). Likewise, performance indices suggest evident
improvement in collect and recall task as training progressed (**Figure 1F**, Percentage of first transition
deviation < 15° in recall task: $\beta_{session}$ = 0.050411, t = 3.2187, p = 0.002; Percentage of distance within
0.01 in recall task: $\beta_{session}$ = 0.047, t = 3.002, p = 0.003; Accuracy in recall task: $\beta_{session}$ = 0.020, t =
4.213, p < 0.001). Furthermore, participants were able to form an implicit map-like structure and
integrate both dimensions when making decisions between avatars. In the compare task, linear mixed
effect models revealed significant effect of distance between avatars in the compared dimension on
response time and accuracy as predicted (**Figure 2G**, all p<0.001). Lastly, learning induced changes in
participants' ratings on avatars on all rating items (competence, trustworthiness, and attractiveness)
(**Figure 2H, Table S1A**). There was no preference over the six presented faces when participants were

naïve to the social value of different avatars (**Table S1B**, all p>0.890), but their ratings became
significantly dissociable according to the learned social value at the end of the experiment (**Table S1B**,
all p<0.001). These results indicated successful formation of a 2D social map by associating each
avatar with respective social value.

Precuneus and fusiform jointly encode Euclidian distance during social navigation

Next, we investigated the neural representations supporting the social cognitive map. To examine the
neural code for distance information, we conducted whole-brain analysis with a GLM in which travelled
Euclidian distance (i.e., the length of each trial's trajectory vector) was entered as parametric modulator
of the morph stage regressor.

This analysis revealed two marginally significant clusters in the precuneus whose activity positively
correlated with travelled distance on the social value map (**Figure 2A**, **Table S2A**, right precuneus: peak
coordinate [x, y, z] = [12, -56, 26], t(37) = 4.952, p = 0.056 FWE-corrected; left precuneus: peak
coordinate [x, y, z] = [-12, -54, 18], t(37) = 4.530, p = 0.058 FWE-corrected; cluster-defining threshold
p < 0.001 FWE-corrected). Interestingly, we also observed negative correlation between travelled
distance and activity of clusters in several regions, including bilateral fusiform gyrus (**Figure 2B**, **Table
S2B**, right fusiform: peak coordinate [x, y, z] = [36, -48, -20], t(37) = 5.912, p < 0.001 FWE-corrected;
left fusiform: peak coordinate [x, y, z] = [-38, -56, -10], t(37) = 4.724, p = 0.008 FWE-corrected) and the
right middle occipital gyrus (**Figure 2B**, **Table S2B**, peak coordinate [x, y, z] = [34, -68, 20], t(37) =
4.649, p = 0.018 FWE-corrected; cluster-defining threshold p < 0.001).

202
203 *Figure 2. Neural representation of Euclidian distance on the social value map. (A) Activity in the*
204 *bilateral Precuneus positively correlated with travelled Euclidian distance. (B) Activity in bilateral*
205 *Fusiform and the right middle occipital gyrus negatively correlated with travelled Euclidian distance.*
206 *Display threshold: cluster-defining threshold p < 0.001.*

Grid-like activity aligned to prefrontal and entorhinal grid orientation

The whole-brain quadrature filter analysis served as a functional localizer and identified several regions
sensitive to hexagonal modulation, independent of grid orientation (**Table S3**). Thus, we defined
spherical ROIs with a 5-mm radius centered at each of the peak coordinate to estimate the grid orientation
of each ROI. As no region in the entorhinal cortex survived this analysis, we defined four entorhinal ROI
based on subdivisions from anatomical mask (Maass et al., 2015). We then conducted the leave-one-out

cross-validation analysis to test for the grid orientation consistency effect.

Of all the grid orientations derived from the above ROIs, we only found a hexagonally modulated effect
aligned to the grid orientation of the ROI in the right frontal pole (right FP) cluster (**Figure 3B**, peak
coordinate [x, y, z] = [26, 52, -2], t(37) = 4.494, cluster-level p = 0.017 FWE-corrected, cluster-defining
threshold p < 0.001) and the grid orientation of the anatomically defined right posterior-medial entorhinal
cortex (right pmEC**, Figure 3C**). For the right FP grid orientation, whole-brain analysis revealed this
alignment effect in bilateral ventral medial prefrontal cortex (vmPFC, **Figure 3D** left and middle panel,
peak coordinate [x, y, z] = [-14, 56, -12], t(37) = 4.245, cluster-level p = 0.033 FWE-corrected, cluster-
defining threshold p < 0.005) and the left entorhinal cortex (left EC) extending to the parahippocampus
region (**Figure 3E** left and middle panel, peak coordinate [x, y, z] = [-16, -22, -26], t(37) = 4.563, cluster-
level p = 0.024 FWE-corrected, cluster-defining threshold p < 0.005). For the right pmEC grid orientation,
significant alignment effect was found in two clusters in bilateral vmPFC (**Figure 3F** left and middle
panel, right rectus: peak coordinate [x, y, z] = [10, 34, -18], t(37) = 4.908, cluster-level p = 0.033 FWE-
corrected; left ACC: peak coordinate [x, y, z] = [-8, 32, 6], t(37) = 4.810, cluster-level p = 0.009 FWE-
corrected; cluster-defining threshold p < 0.005) and one cluster in right superior temporal pole (right STP,
Figure 3G left and middle panel, peak coordinate [x, y, z] = [36, 20, -30], t(37) = 4.962, cluster-level p
= 0.018 FWE-corrected, cluster-defining threshold p < 0.005). However, we did not find evidence of
grid-like code in the entorhinal cortex aligned to its own putative grid orientation either with this
orientation estimation approach (**Figure S5A-B**) or with the representation similarity analysis approach
(**Figure S5C-D**).

One important assumption underlying the univariate analysis for grid-like code in human fMRI data is
neighboring grid cells share similar grid orientation. Consistent with previous studies, we examined this
assumption in our dataset by testing the distribution of putative voxel-wise grid orientations in the right
FP ROI and in the right pmEC ROI for each participant. This revealed a clustered distribution of voxel-
wise grid orientations in FP ROI (V-test, all p < 0.011, except in one participant's one estimating set p =
0.176; see **Figure S2A** for representative participants). Previous studies have also shown that grid
orientations across participants tend to distribute uniformly. This has been replicated in the right FP ROI
in our dataset (**Figure S3** left panel, Rayleigh's tests for nonuniformity, all p > 0.782). However, in the
pmEC ROI, these results are less consistent. With regards to voxel-wise orientations, 31 participants
show the above clustered distribution (V-test, all p < 0.040; see **Figure S2B** for representative
participants), but there are 7 participants each of whom has at least one estimating set that didn't pass the
statistical test (V-test, all p > 0.068). Across participants, only grid orientations from two estimating sets
conformed to the uniform distribution (**Figure S3** right panel, Rayleigh's tests for nonuniformity, run
1,2,3: p = 0.010, run 1,2,4: p =0.019).

For completeness, we tested the specificity of hexagonal modulation. That is, the identified alignment
effect only exists with six-fold periodicity. The above orientation estimation and cross-validation
procedure was repeated for each of the four controlled periodicity (i.e., 4-fold, 5-fold, 7-fold, and 8-fold).
Signals were extracted from the clusters that showed significant hexagonal consistency. One-sample t-
tests showed that signals within these clusters were not modulated by any of the controlled periodicities
and paired t-test showed that six-fold periodicity in general showed greater alignment effect (**Figure 3D-**
G, right panels). In sum, our univariate analysis revealed that the vmPFC and left EC showed six-fold

specific grid-like code aligned to right FP's grid orientation and that the vmPFC and right STP showed

six-fold specific grid-like code aligned to right pmEC's grid orientation.

Figure 3. Evidence of grid-like activity aligned to putative grid orientation in the right frontal pole

and the right posterior-medial entorhinal cortex (A) Theoretical prediction of grid-like activity (B-C)

*ROIs for deriving putative grid orientations: (**B**) right FP ROI from quadrature filter analysis showing*

sensitivity to hexagonal modulation. A 5-mm sphere was defined around the peak coordinate to compute

*grid angle. Display threshold: voxel-level p < 0.001, cluster-level p < 0.05 FWE-corrected. (**C**)*

*Anatomically defined right pmEC ROI used to compute grid angle. (**D-G**) Grid like activity aligned to*

*putative grid orientations in the right FP ROI (**D-E**) and right pmEC (**F-G**) ROI respectively. Left panels:*

clusters from whole-brain hexagonal consistency analysis. Color indicates T statistics as shown in the

*colorbar in **B**. Display threshold: voxel-level p < 0.005, cluster-level p < 0.05 FWE-corrected. Middle*

panels: hexagonal consistency effects plotted as contrast estimates of the 12 trial-bin regressors

extracted from corresponding cluster in the left panel; To illustrate effect in EC in E, estimates were

extracted from the intersection of the suprathreshold cluster and anatomical mask of EC. Right panels:

such effects were specific to six-fold. Notes: n.s., p>0.05, *p<0.05, **p<0.01, ***p<0.001.

Abbreviations: FP, frontal pole; pmEC, posterior-medial entorhinal cortex; vmPFC, ventral medial

prefrontal cortex; STP, superior temporal pole.

Figure 4. Behavioral relevance of hexagonal consistency effect. (A-B) Higher hexagonal consistency
in temporal lobe aligned to grid orientation of (A) right FP ROI and (B) right pmEC significantly
correlated with stronger distance effect in compare task when choosing preferred partners for
cooperation. Display threshold: voxel-level p < 0.005, cluster-level p < 0.05 FWE-corrected. (C)
Hexagonal consistency effect in left Precuneus aligned to grid orientation of right FP ROI significantly
correlated with social avoidance score. Display threshold: voxel-level p < 0.001, cluster-level p < 0.05
FWE-corrected. Notes: n.s., p>0.05, *p<0.05, **p<0.01, ***p<0.001. Abbreviations: FP, frontal pole;
pmEC, posterior-medial entorhinal cortex; MTG, middle temporal gyrus; LING, lingual gyrus.

<u>Behavioral relevance of spatial codes for the social value map</u>

Additionally, we explored whether these identified grid-like code could have any behavioral relevance
beyond the scanned task. We quantify this using several indices that can be classified into two categories.
The first category of indices reflects participants ability to make decision based on the social value map,
i.e., the distance effect in the compare task. Specifically, we focused on the distance effect during the
cooperation block when participants decide the avatar they are more willing to cooperate with by taking
into account both dimensions. This is essentially the beta weight of the distance regressor in predicting
participant's accuracy and log-transformed response time. The second category of indices reflects
participants' social trait, including social anxiety and social avoidance scores. We tested the behavioral
relevance of grid-like code by entering the above indices as covariates into the second-level analysis
when testing grid orientation consistency effect, and all covariates were tested in separate regression
models.

Whole-brain analysis revealed significant clusters in the temporal lobe whose consistency effect scaled
with distance effect in response time. For grid orientation of right FP ROI (**Figure 4A**), hexagonal

consistency effect in the left middle temporal gyrus and right Lingual gyrus correlated with the distance
effect (left middle temporal gyrus: peak coordinate [x, y, z] = [-36, -70, 8], t(37) = 4.528, cluster-level p
< 0.001 FWE-corrected; right Lingual gyrus: peak coordinate [x, y, z] = [-38,-66, 4], t(37) = 4.369,
cluster-level p < 0.001 FWE-corrected; cluster-defining threshold p < 0.005). For grid orientation of right
pmEC ROI (**Figure 4B**), hexagonal consistency effect in bilateral Lingual correlated with the distance
effect (left Lingual gyrus: peak coordinate [x, y, z] = [-12,-68, -2], t(37) = 4.355, cluster-level p = 0.077
FWE-corrected; right Lingual gyrus: peak coordinate [x, y, z] = [16,-62, -2], t(37) = 3.934, cluster-level
p = 0.032 FWE-corrected; cluster-defining threshold p < 0.005). In general, greater distance effect in the
comparison task was correlated with greater hexagonal consistency in temporal lobe aligned to both
prefrontal and entorhinal grid orientations. In addition, this analysis also revealed a significant cluster in
the left precuneus/posterior cingulate cortex (PCC), and its consistency effect aligned to the right FP grid
orientation (**Figure 4C**, peak coordinate [x, y, z] = [0, -64, 28], t(37) = 4.965, cluster-level p < 0.001
FWE-corrected, cluster-defining threshold p < 0.001) was negatively correlated with social avoidance
score.

Discussion

In this study, we investigated whether cognitive map in social cognition domain recruit the neural
processing mechanism similar to its spatial counterpart. We identified distance representation in
precuneus, fusiform gyrus and middle occipital gyrus. In addition, we demonstrated some evidence of
grid-like activity in prefrontal cortex and entorhinal cortex. Furthermore, we explored the behavioral
relevance of grid-like activity in temporal pole and precuneus.

When participants were mentally traversing a predefined social value map, we found that activities in the
bilateral precuneus were positively correlated with travelled distance, while activities in bilateral FFG
and right MOG were negatively correlated with travelled distance. In spatial navigation literature, though
intracranial electroencephalography studies have shown the relevance of hippocampal theta oscillation
in encoding travelled distance, neural correlates of travelled distance at macroscopic level using fMRI
are relatively sparsely investigated (Kunz et al., 2019). Patai et al. (2019) showed that retrosplenial cortex
positively correlated with path distance in that greater distance is associated with increased precuneus
activity and that this effect remained robust after controlling for Euclidean distance. Likewise, we
showed that precuneus activity was positively correlated with travelled Euclidian distance during implicit
navigation in the abstract social space. Moreover, the present peak coordinates coincide with those
reported in a previous study by Park et al. (2020). In their study, participants learned 2D social hierarchy
(competence and popularity) of two groups of agents and were asked to perform a transitive inference
task in which compare a pair of agents on their competence or popularity. The authors found that bilateral
precuneus represented pairwise difference in the task-relevant dimension instead of pairwise Euclidian
distance in the two-dimension space. Another study reported that posterior cingulate cortex/precuneus
tracks the length of the vector of social relationship change, i.e., an egocentric distance (Tavares et al.,
2015). Taken together, we speculate that precuneus may encode the distance of the route, either on a
concrete or an abstract map, that participants trespass under task demand. Less clear is the negative
correlation we observed between travelled distance and activity in fusiform as well as middle occipital
gyrus. Both FFG and MOG are involved during human spatial navigation (Boccia et al., 2014). In
particular, fusiform gyrus extending into the parahippocampal place area has been showed to involve in

processing spatial information such as landmark and orientation cues (Qiu et al., 2019). However, to our
knowledge, there is no study that reports such negative distance coding in these occipitotemporal regions
during navigation.

Apart from the distance code, another focus of the current study was to test whether grid-like codes
support the organization of social knowledge. Previous studies on reporting grid-like codes mostly report
hexagonal modulated pattern in the entorhinal cortex and medial prefrontal regions aligned to putative
grid orientation from both regions (Constantinescu et al., 2016). Our current study partly replicated these
findings, most of which are in the prefrontal region. In terms of prefrontal orientation, whole-brain
analysis revealed alignment effects in the bilateral vmPFC and left EC. In terms of entorhinal orientation,
however, alignment effect was found in the bilateral vmPFC and right superior temporal pole, but not in
entorhinal cortex. Though we found evidence of prefrontal grid-like codes subserving social navigation,
its origin remains elusive. Up to date, there has been no significant evidence of grid-like neuronal tuning
in this area (Wikenheiser et al., 2021). Jacobs et al. (2013) examined grid-like cells in a variety of brain
regions including the frontal cortex in neurosurgical patients during a virtual navigation task, but the
proportion of significant grid-like cells in the frontal cortex did not exceed type I error rate (they did
identify grid-like cells in cingulate cortex which is posterior to the prefrontal regions). Therefore, it is
less likely that prefrontal grid-like codes reported in our study and previous literature come from grid
cells in the prefrontal cortex. A more plausible explanation is that the anatomically and functionally
connected medial- and orbitofrontal cortex and entorhinal cortex (Navarro Schroder et al., 2015; Peng et
al., 2018; Squire & Zola, 1996) coordinated together to support flexible decision making. However,
adopting both univariate and multivariate approaches, our current study did not find reliable effect of
hexagonal grid-like code in the entorhinal region aligned to its own grid orientation, which should be
evident if such hypothesis stands. Previous studies postulated that lack of univariate evidence of grid-
like code may have to do with low signal-to-noise ratio (tSNR) in data from the entorhinal cortex (Bao
et al., 2019). Indeed, we found lower mean tSNR in all four entorhinal sub regions compared to the
frontal pole cluster from the quadrature filter analysis (**Supplementary Methods, Figure S6A**). But we
did not identify a significant relationship between tSNR and the z-transformed F statistics of hexagonal
modulation either across participants or within participants (**Supplementary Methods, Figure S6B-C,
Table S4**). Thus, we cannot conclude that low signal-to-noise ratio in entorhinal cortex led to this null
finding in our study.

Nonetheless, our study did provide some incomplete evidence of grid-like activity in the entorhinal cortex
and prefrontal region while participants were mentally trespassing an abstract social space. Grid codes
are proposed to provide a metric of space (Moser & Moser, 2008) and underly the process of path
integration (McNaughton et al., 2006). Previous studies have suggested that entorhinal grid codes are
capable of representing space even at a higher level of abstraction that goes beyond spatial navigation to
support cognitive flexibility in general (Bellmund et al., 2018). Existing literature revealed correlation
between entorhinal and prefrontal grid-like code and performance in spatial, perceptual and conceptual
space. Indeed, our exploratory analysis showed that the univariate hexagonal consistency effect in
temporal lobe scaled with the distance effect in a comparison task block when participants chose their
preferred partner for future cooperation. The distance effect reflected the extent to which participants
relied their preference judgment on the pairwise distance between given pair of avatars. As we explicitly
required participants to take both dimension into consideration, it reflected participant's ability to plan a

route between landmarks (which represents retained impression of social encounters) in the abstract
social space. This is very similar to what Park et al. (2021) reported in their recent study. In this study,
participants were trained on the rankings of 16 individuals on two dimensions (competence and
popularity) separately, then they were asked to make comparisons between novel pairings unseen during
training. Replicating their previous findings (Park et al., 2020), the authors found that the entorhinal and
hippocampus system successfully reconstruct the unseen whole spectrum of social hierarchies as a 2D
cognitive map. Moreover, they found that grid-like representations support trajectories of novel
inferences on this 2D cognitive map that underpins decision making. Park's study and ours differed in
that they focused on discrete relational structures whilst we constructed a continuous social space.
Collectively, these evidence support the notion that grid-like codes underpin navigation in an abstract
social cognitive map, be it discrete or continuous.

Intriguingly, our study found that the intensity of hexagonal modulation in precuneus aligned to estimated
grid orientation of prefrontal region is negatively correlated with participants' social avoidance tendency.
While previous studies mainly reported grid-like codes in the entorhinal cortex and prefrontal cortex and
its relevance to spatial navigation deficit in clinically risky population (Kunz et al., 2015), to the best of
our knowledge, no report has shown the psychological relevance of grid-like code outside these classical
regions to potential social deficit. One study of direct neuronal recording revealed grid-like neuronal
activity in patients' cingulate cortex during virtual spatial navigation task (Jacobs et al., 2013), implying
that the human grid-cell network previously focused around entorhinal and prefrontal region also extends
to the cingulate cortex. However, our study did not find evidence of grid-like pattern in precuneus. Thus,
we cannot conclude that our result points to a direct relationship between precuneus grid-like code and
social functionality. Meanwhile, precuneus, as a core node of the DMN, has abundant neuroanatomical
connections with prefrontal regions (Greicius et al., 2009; Khalsa et al., 2014; Oane et al., 2020).
Precuneus has also been reported to show a decrease in resting-state connectivity to parahippocampal
gyrus and medial prefrontal cortex in patients with SAD (Yuan et al., 2018). Therefore, it is likely that
downstream projections from the OFC/vmPFC motivated the observed correlation pattern in our study.

In conclusion, our present study demonstrates that navigating in a continuous social space recruited
distance codes and grid-like codes in brain regions reported by spatial navigation studies and their
behavioral and psychological relevance. Our findings further strengthen the notion that neural
mechanisms involved in spatial cognitive map may play a domain-general role in maintaining abstract,
structured representation of knowledge that support flexible cognitive behavior.

Our study has a few limitations. First, to make our study comparable to those investigating representation
of abstract nonsocial knowledge, our scanner task investigate social navigation in a static environment
and no social interaction or social decision is involved. Further studies should be conducted to investigate
how such structured representation of social knowledge is reused and updated during social decisions
and social interactions. Second, we specifically designed the abstract social value map to be formed by
two orthogonal dimensions that have the same scale. This allows us to examine grid-like activity pattern
with six-fold periodicity unambiguously. But this set-up may lack generality. For one thing, it is unlikely
that all parts of the whole social value space span by the warmth and competence dimension are equally
important. Social ties are more likely to be formed among human alike (McPherson et al., 2001) and
human show the tendency to represent ingroup members more differentially than outgroup members

(Hugenberg et al., 2010; Ostrom et al., 1993), so it is likely that some area of the social value space is
represented in finer granularity than other. In spatial navigation, entorhinal grid cells showed sensitivity
to geometric and environmental features, and the resulting distorted grid fields no longer form a regular
hexagonal lattice and fail to show six-fold periodicity (Derdikman et al., 2009; He & Brown, 2019;
Krupic et al., 2015). For instance, grid fields has been found to sometimes warp towards reward (Boccara
et al., 2019). In this sense, spontaneous social value space may bear more resemblance to such kind of
reward map covered by distorted grid fields rather than a regular, uniform square/circular open arena
where six-fold symmetric grid-like coding was originally identified. For another, the geometric
properties of social and non-social cognitive space in real life can be very different from that of the
physical space in navigation. Our knowledge of other people in real life is often high-dimensional
integrating multi-modal information from sensory features (face, voice etc.) to social cognitive
information (hobbies, social status, etc.). Moreover, while dimensions of physical space (the cartesian
axes) are orthogonal and their metrics are on the same scale, the dimensions of social perception in real
life may not be orthogonal and may be incomparable. The stereotype content model predicted that there
is a weak but low correlation between warmth and competence (Cuddy et al., 2009) and other studies
have found there exists compensation between these dimensions (Kervyn et al., 2010). To the best of our
knowledge, it remains elusive whether and how grid cells can represent such high-dimensional space
with non-orthonormal basis and how the univariate and multivariate analysis pipeline used to identify
grid-like coding in fMRI signal could be revised to address these concerns. Taken together, the intrinsic
social cognitive map in which human structure their knowledge of others may be non-uniform, high-
dimensional and have non-orthonormal dimensions. Future studies would need to take this into account
and explore beyond the six-fold grid-like activity pattern in regular 2D space.

Materials and Methods

Participants

No power analysis was done to pre-determine the sample size. Instead, we tried to achieve a sample size
comparable to previous studies investigating grid-like representations using fMRI (Doeller et al., 2010).
44 participants (18 males, mean age ± standard deviation: 21.59±2.56) recruited from surrounding
universities finished all behavioral training and fMRI scanning in the current study at the Beijing Normal
University Imaging Center for Brain Research (BICBR). Each participant underwent intensive
behavioral training (including one learning session and one review session) and one fMRI scanning
session **(Figure S1F)**. Three participants were excluded from all further analyses due to excessive head
motion in the scanner (framewise displacement greater than 3mm). Another three participants failing to
achieve satisfactory behavioral accuracies (lower than 60%) in the scanning session were excluded from
all further analyses. The remaining 38 participants' data were included in the behavioral and fMRI
analysis reported in the main text (15 males, mean age ± standard deviation: 21.47±2.64).

The study was approved by the ethics committee of National Key Laboratory of Cognitive Neuroscience
and Learning at Beijing Normal University (ICBIR_A_0071_011). All regulations were followed, and
participants signed paper-form informed consent before the experiment. Participants received monetary
compensation for their participation in the current study.

Data acquisition

Behavioral data acquisition

Behavioral tasks were programmed using Psychophysics Toolbox-3 in MATLAB or E-prime 2.0. Online pilot rating study, pre- and post-experiment questionnaires were collected via Qualtrics.

MRI data acquisition

We acquired T2-weighted functional images on a 3T SIEMENS MAGNETOM Prisma scanner with a 64-channel head coil. We acquired 33 slices, 3mm thick with: repetition time (TR) = 2000ms, echo time (TE) = 30ms, flip angle = 90°, field of view (FoV) = 224 mm, voxel size = 3.5×3.5×3.5 mm^3. To correct for spatial distortion, a field map was acquired with dual echo-time images covering the whole brain with the following parameters: TR = 400ms, TE1= 4.92ms, TE2 = 7.38ms, flip angle = 60°, FoV = 224mm, voxel size = 3.5×3.5×3.5 mm^3. A T1-weigted structural image was acquired with the following parameters: TR = 2530ms, TE= 2.98ms, flip angle = 7°, FoV = 256mm, voxel size = 0.5×0.5×1 mm^3.

Data analysis

All analyses were performed with customed code in MATLAB and R.

Pre-processing of functional MRI data

Pre-processing of functional MRI data was done with SPM12. Functional images were spatially realigned to the first image in the time series and corrected for slice-timing. Spatial distortion based on field map. The T1-weighted structure image was co-registered to the mean aligned functional image, segmented and normalized to MNI space. The derived transformation parameters from structural image normalization were applied to normalize realigned functional images. Finally, smoothing was done with a 6mm full-width half-maximum Gaussian kernel.

Searching for representation of distance on 2D social value map in human fMRI signal

To look for neural representation of the travelled distance on the social value map, we conducted a whole-brain univariate analysis. Two regressors were included in this GLM, one modeling the morph stage and one modeling the choice stage. The travelled Euclidian distance during morph stage was entered as a parametric modulator for the morph-stage regressor.

Searching for grid-like representations of 2D social value map in human fMRI signal

To search for evidence of entorhinal and prefrontal grid-like activity supporting representation of social space, we further implemented two popular approaches to examine hexa-directional coding with fMRI data at the morphing stage in each trial. The first one is the orientation-estimation approach (Bellmund et al., 2018; Doeller et al., 2010) based on univariate analysis. In this approach, we first defined Regions of Interest (ROIs) that were sensitive to hexagonal modulation using univariate analysis (see **Supplementary Methods** for details). Thereafter, with a leave-one-out cross-validation procedure, we tested for hexagonal modulation aligned to grid orientation of the ROIs for each participant. In this procedure, we split the four acquired functional scanning runs into an 'estimating set' and a 'testing set'.

The estimating set consisted of three runs and was used to calculate the grid orientation of the ROIs (see **Supplementary Methods** for details). The remaining one run then served as the testing set where the alignment effect was tested with the inferred grid orientation. This procedure was repeated four times to independently yield the inferred orientations for each run. Specifically, we divided trials into 12 bins of 30° according to the offset of trial trajectory from the putative grid orientation (**Figure 3A** left panel). The theoretical prediction for grid-like code is that neural signal should be stronger in trials aligned than misaligned to the grid orientation (0° modulo 60° vs 30° modulo 60°). In other words, activation should be higher in the aligned (odd-numbered) bins than the misaligned (even-numbered) bins (**Figure 3B** right panel). In addition to the above region-wise orientations, we also derived voxel-wise putative grid orientations in each ROI and used the circulate statistics to test whether there were clustered distributions of grid orientations as observed by the direct neuron recordings. As we failed to find evidence of grid-like activity in EC aligned to its own putative grid orientation using the first approach, we took the anatomical mask of EC (Maass et al., 2015) and explored grid-like activity using a multivariate approach. This approach leverages representational similarity analysis (RSA) and is widely adopted based on the assumption that a distributed coding scheme is employed by the entorhinal cortex. To start with, we estimated trial-specific activation for each trial in each run using the 'Least Squares Separate' (LSS) approach (Abdulrahman & Henson, 2016; Mumford et al., 2012). This approach built separate GLMs for each trial with one target regressor modeling the current trial of interest and a second nuisance regressor modeling the rest. Beta estimates of the target regressors were extracted from the entorhinal ROI as trial-specific activity pattern for each of the 320 trials (**Figure S4A**). We then tested whether this multivariate pattern is hexagonally modulated. Though the exact implementations varied slightly across studies, they fell into the following two categories according to their dependence on the estimated putative grid orientation. The 'orientation-independent' approach (**Figure S4B**) tested the hypotheses that multivariate pattern similarity between trajectory pairs is proportional to the angular difference between their moving direction modulated by 60° (Bellmund et al., 2016; Vigano & Piazza, 2020; Vigano et al., 2021), which is done by calculation the correlation between the derived neural dissimilarity matrix and the model matrix. The 'orientation-dependent' approach **(Figure S4C)** leveraged the assumption that if activity in a given ROI is aligned to a preferred orientation, the similarity of multivoxel patterns in this region should be higher for aligned trial-pairs than that between aligned and misaligned trial-pairs (Bao et al., 2019). Grid-orientations were calculated as described in the previous section using the leave-one-out cross-validation procedure. Trials were then classified into aligned and misaligned trials according to the angular difference between trajectories and the estimated entorhinal grid orientation. We then computed the similarities between aligned-aligned trial pairs (AA pairs) and aligned-misaligned trial pairs (AM pairs). By subtracting similarity between AM pairs from AA pairs, we yielded an index for difference between pattern similarity of the two trial-pair types for each participant. One-sample t-test was used to test whether similarity between AM pairs was significantly lower than that of AA pairs. All representational similarity analyses were based on non-smoothed fMRI data.

Data Availability

We have published preprocessed smoothed and unsmoothed functional MRI data, the code to run the experiment and the code to run the univariate analysis reported in the main text. Dataset and code are publicly available at https://doi.org/10.57760/sciencedb.08637.

Acknowledgements

We are grateful for the volunteers who participated in this study. We thank Alexandra Constantinescu for providing helpful information regarding the experiment design in their previous study. We thank Kelou Jin for his hard work and help when conducting pilot experiments. We thank Shen Zhang and Huagen Wang for their help in data analysis. This work was supported by the National Natural Science Foundation of China (32271092 and 32130045), the Major Project of National Social Science Foundation (19ZDA363), the Beijing Municipal Science and Technology Commission (Z151100003915122), the National Program for Support of Top-notch Young Professionals.

Author contributions

Zilu Liang, Conceptualization, Investigation, Formal analysis, Visualization, Writing – original draft, Writing – review and editing; Simeng Wu, Investigation; Jie Wu, Investigation; Wenxu Wang, Conceptualization; Shaozheng Qin, Conceptualization, Supervision, Writing – review and editing; Chao Liu, Conceptualization, Supervision, Writing – review and editing, Funding acquisition.

References

Abdulrahman, H., & Henson, R. N. (2016). Effect of trial-to-trial variability on optimal event-related fMRI design: Implications for Beta-series correlation and multi-voxel pattern analysis. *Neuroimage*, *125*, 756-766. https://doi.org/10.1016/j.neuroimage.2015.11.009

Aronov, D., Nevers, R., & Tank, D. W. (2017). Mapping of a non-spatial dimension by the hippocampal-entorhinal circuit. *Nature*, *543*(7647), 719-722. https://doi.org/10.1038/nature21692

Bao, X., Gjorgieva, E., Shanahan, L. K., Howard, J. D., Kahnt, T., & Gottfried, J. A. (2019). Grid-like Neural Representations Support Olfactory Navigation of a Two-Dimensional Odor Space. *Neuron*, *102*(5), 1066-1075 e1065. https://doi.org/10.1016/j.neuron.2019.03.034

Bellmund, J. L., Deuker, L., Navarro Schroder, T., & Doeller, C. F. (2016). Grid-cell representations in mental simulation. *Elife*, *5*. https://doi.org/10.7554/eLife.17089

Bellmund, J. L. S., Gardenfors, P., Moser, E. I., & Doeller, C. F. (2018). Navigating cognition: Spatial codes for human thinking. *Science*, *362*(6415). https://doi.org/10.1126/science.aat6766

Boccara, C. N., Nardin, M., Stella, F., O'Neill, J., & Csicsvari, J. (2019). The entorhinal cognitive map is attracted to goals. *Science*, *363*(6434), 1443-1447. https://doi.org/10.1126/science.aav4837

Boccia, M., Nemmi, F., & Guariglia, C. (2014). Neuropsychology of environmental navigation in humans: review and meta-analysis of FMRI studies in healthy participants. *Neuropsychol Rev*, *24*(2), 236-251. https://doi.org/10.1007/s11065-014-9247-8

Constantinescu, A. O., O'Reilly, J. X., & Behrens, T. E. J. (2016). Organizing conceptual knowledge in humans with a gridlike code. *Science*, *352*(6292), 1464-1468. https://doi.org/10.1126/science.aaf0941

Cuddy, A. J., Fiske, S. T., Kwan, V. S., Glick, P., Demoulin, S., Leyens, J. P., Bond, M. H., Croizet, J. C., Ellemers, N., Sleebos, E., Htun, T. T., Kim, H. J., Maio, G., Perry, J., Petkova, K., Todorov, V., Rodriguez-Bailon, R., Morales, E., Moya, M., . . . Ziegler, R. (2009). Stereotype content model across cultures: towards universal similarities and some differences. *Br J Soc Psychol*, *48*(Pt 1), 1-33. https://doi.org/10.1348/014466608X314935

Cuddy, A. J. C., Fiske, S. T., & Glick, P. (2008). Warmth and Competence as Universal Dimensions of Social Perception: The Stereotype Content Model and the BIAS Map. In (pp. 61-149). https://doi.org/10.1016/s0065-2601(07)00002-0

Derdikman, D., Whitlock, J. R., Tsao, A., Fyhn, M., Hafting, T., Moser, M. B., & Moser, E. I. (2009). Fragmentation of grid cell maps in a multicompartment environment. *Nat Neurosci*, *12*(10), 1325-1332. https://doi.org/10.1038/nn.2396

Doeller, C. F., Barry, C., & Burgess, N. (2010). Evidence for grid cells in a human memory network. *Nature*, *463*(7281), 657-661. https://doi.org/10.1038/nature08704

Fiske, S. T., Cuddy, A. J., & Glick, P. (2007). Universal dimensions of social cognition: warmth and competence. *Trends Cogn Sci*, *11*(2), 77-83. https://doi.org/10.1016/j.tics.2006.11.005

Greicius, M. D., Supekar, K., Menon, V., & Dougherty, R. F. (2009). Resting-state functional connectivity reflects structural connectivity in the default mode network. *Cereb Cortex*, *19*(1), 72-78. https://doi.org/10.1093/cercor/bhn059

Hafting, T., Fyhn, M., Molden, S., Moser, M. B., & Moser, E. I. (2005). Microstructure of a spatial map in the entorhinal cortex. *Nature*, *436*(7052), 801-806. https://doi.org/10.1038/nature03721

He, Q., & Brown, T. I. (2019). Environmental Barriers Disrupt Grid-like Representations in Humans during Navigation. *Curr Biol*, *29*(16), 2718-2722 e2713.

https://doi.org/10.1016/j.cub.2019.06.072

Horner, A. J., Bisby, J. A., Zotow, E., Bush, D., & Burgess, N. (2016). Grid-like Processing of Imagined
Navigation. *Curr Biol*, *26*(6), 842-847. https://doi.org/10.1016/j.cub.2016.01.042

Hugenberg, K., Young, S. G., Bernstein, M. J., & Sacco, D. F. (2010). The categorization-individuation
model: an integrative account of the other-race recognition deficit. *Psychol Rev*, *117*(4), 1168-
1187. https://doi.org/10.1037/a0020463

Jacobs, J., Weidemann, C. T., Miller, J. F., Solway, A., Burke, J. F., Wei, X. X., Suthana, N., Sperling, M.
R., Sharan, A. D., Fried, I., & Kahana, M. J. (2013). Direct recordings of grid-like neuronal
activity in human spatial navigation. *Nat Neurosci*, *16*(9), 1188-1190.
https://doi.org/10.1038/nn.3466

Kervyn, N., Yzerbyt, V., & Judd, C. M. (2010). Compensation between warmth and competence:
Antecedents and consequences of a negative relation between the two fundamental dimensions
of social perception. *European Review of Social Psychology*, *21*(1), 155-187.
https://doi.org/10.1080/13546805.2010.517997

Khalsa, S., Mayhew, S. D., Chechlacz, M., Bagary, M., & Bagshaw, A. P. (2014). The structural and
functional connectivity of the posterior cingulate cortex: comparison between deterministic and
probabilistic tractography for the investigation of structure-function relationships. *Neuroimage*,
102 Pt 1, 118-127. https://doi.org/10.1016/j.neuroimage.2013.12.022

Killian, N. J., Jutras, M. J., & Buffalo, E. A. (2012). A map of visual space in the primate entorhinal
cortex. *Nature*, *491*(7426), 761-764. https://doi.org/10.1038/nature11587

Kriegeskorte, N., & Storrs, K. R. (2016). Grid Cells for Conceptual Spaces? *Neuron*, *92*(2), 280-284.
https://doi.org/10.1016/j.neuron.2016.10.006

Krupic, J., Bauza, M., Burton, S., Barry, C., & O'Keefe, J. (2015). Grid cell symmetry is shaped by
environmental geometry. *Nature*, *518*(7538), 232-235. https://doi.org/10.1038/nature14153

Kunz, L., Maidenbaum, S., Chen, D., Wang, L., Jacobs, J., & Axmacher, N. (2019). Mesoscopic Neural
Representations in Spatial Navigation. *Trends Cogn Sci*, *23*(7), 615-630.
https://doi.org/10.1016/j.tics.2019.04.011

Kunz, L., Schroder, T. N., Lee, H., Montag, C., Lachmann, B., Sariyska, R., Reuter, M., Stirnberg, R.,
Stocker, T., Messing-Floeter, P. C., Fell, J., Doeller, C. F., & Axmacher, N. (2015). Reduced
grid-cell-like representations in adults at genetic risk for Alzheimer's disease. *Science*,
350(6259), 430-433. https://doi.org/10.1126/science.aac8128

Maass, A., Berron, D., Libby, L. A., Ranganath, C., & Duzel, E. (2015). Functional subregions of the
human entorhinal cortex. *Elife*, *4*. https://doi.org/10.7554/eLife.06426

McNaughton, B. L., Battaglia, F. P., Jensen, O., Moser, E. I., & Moser, M. B. (2006). Path integration
and the neural basis of the 'cognitive map'. *Nat Rev Neurosci*, *7*(8), 663-678.
https://doi.org/10.1038/nrn1932

McPherson, M., Smith-Lovin, L., & Cook, J. M. (2001). Birds of a Feather: Homophily in Social
Networks. *Annual Review of Sociology*, *27*(1), 415-444.
https://doi.org/10.1146/annurev.soc.27.1.415

Moser, E. I., & Moser, M. B. (2008). A metric for space. *Hippocampus*, *18*(12), 1142-1156.
https://doi.org/10.1002/hipo.20483

Mumford, J. A., Turner, B. O., Ashby, F. G., & Poldrack, R. A. (2012). Deconvolving BOLD activation
in event-related designs for multivoxel pattern classification analyses. *Neuroimage*, *59*(3),
2636-2643. https://doi.org/10.1016/j.neuroimage.2011.08.076

Nau, M., Navarro Schroder, T., Bellmund, J. L. S., & Doeller, C. F. (2018). Hexadirectional coding of
visual space in human entorhinal cortex. *Nat Neurosci*, *21*(2), 188-190.
https://doi.org/10.1038/s41593-017-0050-8

Navarro Schroder, T., Haak, K. V., Zaragoza Jimenez, N. I., Beckmann, C. F., & Doeller, C. F. (2015).
Functional topography of the human entorhinal cortex. *Elife*, *4*.
https://doi.org/10.7554/eLife.06738

Oane, I., Barborica, A., Chetan, F., Donos, C., Maliia, M. D., Arbune, A. A., Daneasa, A., Pistol, C., Nica,
A. E., Bajenaru, O. A., & Mindruta, I. (2020). Cingulate cortex function and multi-modal
connectivity mapped using intracranial stimulation. *Neuroimage*, *220*, 117059.
https://doi.org/10.1016/j.neuroimage.2020.117059

Ostrom, T. M., Carpenter, S. L., Sedikides, C., & Li, F. (1993). Differential processing of in-group and
out-group information. *Journal of Personality and Social Psychology*, *64*(1), 21-34.
https://doi.org/10.1037/0022-3514.64.1.21

Park, S. A., Miller, D. S., & Boorman, E. D. (2021). Inferences on a multidimensional social hierarchy
use a grid-like code. *Nat Neurosci*, *24*(9), 1292-1301. https://doi.org/10.1038/s41593-021-
00916-3

Park, S. A., Miller, D. S., Nili, H., Ranganath, C., & Boorman, E. D. (2020). Map Making: Constructing,
Combining, and Inferring on Abstract Cognitive Maps. *Neuron*, *107*(6), 1226-1238 e1228.
https://doi.org/10.1016/j.neuron.2020.06.030

Patai, E. Z., Javadi, A. H., Ozubko, J. D., O'Callaghan, A., Ji, S., Robin, J., Grady, C., Winocur, G.,
Rosenbaum, R. S., Moscovitch, M., & Spiers, H. J. (2019). Hippocampal and Retrosplenial
Goal Distance Coding After Long-term Consolidation of a Real-World Environment. *Cereb*
Cortex, *29*(6), 2748-2758. https://doi.org/10.1093/cercor/bhz044

Peng, L., Zeng, L. L., Liu, Q., Wang, L., Qin, J., Xu, H., Shen, H., Li, H., & Hu, D. (2018). Functional
connectivity changes in the entorhinal cortex of taxi drivers. *Brain Behav*, *8*(9), e01022.
https://doi.org/10.1002/brb3.1022

Potts, G. R. (1974). Storing and retrieving information about ordered relationships. *Journal of*
Experimental Psychology, *103*(3), 431-439. https://doi.org/10.1037/h0037408

Qiu, Y., Wu, Y., Liu, R., Wang, J., Huang, H., & Huang, R. (2019). Representation of human spatial
navigation responding to input spatial information and output navigational strategies: An ALE
meta-analysis. *Neurosci Biobehav Rev*, *103*, 60-72.
https://doi.org/10.1016/j.neubiorev.2019.06.012

Sargolini, F., Fyhn, M., Hafting, T., McNaughton, B. L., Witter, M. P., Moser, M. B., & Moser, E. I.
(2006). Conjunctive representation of position, direction, and velocity in entorhinal cortex.
Science, *312*(5774), 758-762. https://doi.org/10.1126/science.1125572

Schafer, M., & Schiller, D. (2018). Navigating Social Space. *Neuron*, *100*(2), 476-489.
https://doi.org/10.1016/j.neuron.2018.10.006

Son, J. Y., Bhandari, A., & FeldmanHall, O. (2021). Cognitive maps of social features enable flexible
inference in social networks. *Proc Natl Acad Sci U S A*, *118*(39).
https://doi.org/10.1073/pnas.2021699118

Squire, L. R., & Zola, S. M. (1996). Structure and function of declarative and nondeclarative memory
systems. *Proc Natl Acad Sci U S A*, *93*(24), 13515-13522.
https://doi.org/10.1073/pnas.93.24.13515

Stolier, R. M., Hehman, E., & Freeman, J. B. (2020). Trait knowledge forms a common structure across

680   social cognition. *Nat Hum Behav*, *4*(4), 361-371. https://doi.org/10.1038/s41562-019-0800-6

681   Tavares, R. M., Mendelsohn, A., Grossman, Y., Williams, C. H., Shapiro, M., Trope, Y., & Schiller, D.

682   (2015). A Map for Social Navigation in the Human Brain. *Neuron*, *87*(1), 231-243.

683   https://doi.org/10.1016/j.neuron.2015.06.011

684   Tolman, E. C. (1948). Cognitive maps in rats and men. *Psychol Rev*, *55*(4), 189-208.

685   https://doi.org/10.1037/h0061626

686   Vigano, S., & Piazza, M. (2020). Distance and Direction Codes Underlie Navigation of a Novel Semantic

687   Space in the Human Brain. *J Neurosci*, *40*(13), 2727-2736.

688   https://doi.org/10.1523/JNEUROSCI.1849-19.2020

689   Vigano, S., Rubino, V., Soccio, A. D., Buiatti, M., & Piazza, M. (2021). Grid-like and distance codes for

690   representing word meaning in the human brain. *Neuroimage*, *232*, 117876.

691   https://doi.org/10.1016/j.neuroimage.2021.117876

692   Wikenheiser, A. M., Gardner, M. P. H., Mueller, L. E., & Schoenbaum, G. (2021). Spatial Representations

693   in Rat Orbitofrontal Cortex. *J Neurosci*, *41*(32), 6933-6945.

694   https://doi.org/10.1523/JNEUROSCI.0830-21.2021

695   Yuan, C., Zhu, H., Ren, Z., Yuan, M., Gao, M., Zhang, Y., Li, Y., Meng, Y., Gong, Q., Lui, S., Qiu, C., &

696   Zhang, W. (2018). Precuneus-related regional and network functional deficits in social anxiety

697   disorder: A resting-state functional MRI study. *Compr Psychiatry*, *82*, 22-29.

698   https://doi.org/10.1016/j.comppsych.2017.12.002

699