Predictable Modality Transitions and Amodal Representations Enable Crossmodal Statistical Learning

Alexis Pérez-Bellido [1,2,3,4], Daniel Duato [2]; Francesco Giannelli [2,3,4]; Ruth de Diego-Balaguer [2,3,5,6]

* Correspondence concerning this article should be addressed to Dr. Alexis Pérez-Bellido, [1] Department of Cognition, Development and Educational Psychology, Universitat Autònoma de Barcelona, Spain. [2] Department of Cognition, Development and Educational Psychology, University of Barcelona, Spain. [3] Cognition and Brain Plasticity Unit [Bellvitge Biomedical Research Institute – IDIBELL], L'Hospitalet de Llobregat, Barcelona, Spain. [4] Università Bocconi, Milano, Italy. [5] Institute of Neurosciences, University of Barcelona, Barcelona, Spain. [6] ICREA, Barcelona, Spain. Email: alexisperezbellido@gmail.com

Public significance statement:

Previous research has established that low-level statistical learning occurs within individual sensory modalities. However, evidence for statistical learning across modalities remains limited. This has led to the hypothesis that statistical learning operates as a modality-specific system, constrained by the perceptual properties and content of each sensory system. In this study, we demonstrate that modality transitions' predictability enables crossmodal statistical learning, even in the absence of semantic information. Notably, this constraint does not apply to meaningful stimuli, which can be processed at an amodal level. Our findings broaden the classical neurobiological model of statistical learning by highlighting the roles of attentional mechanisms and representational levels in supporting crossmodal statistical learning.

Abstract

Statistical learning involves extracting statistical regularities from the environment. Despite the ubiquitous crossmodal relations in our environment, previous research has failed in showing crossmodal learning suggesting that statistical learning is modality-specific, occurring within but not between sensory modalities. The present study investigates under which circumstances statistical learning can occur between modalities. In the first experiment, participants viewed a stream of meaningless visual fractals and synthetic auditory stimuli. Importantly, the sequence of stimuli could be grouped into unimodal or crossmodal pairs based on their internal transitional probabilities. Using implicit and explicit measures of learning, we found that participants only learned the unimodal pairs. In the second experiment, pairs were presented in separate unimodal and crossmodal blocks. The crossmodal blocks alternated visual and auditory modalities allowing

participants to anticipate the upcoming modality. This manipulation allowed significant statistical

learning for the crossmodal pairs, reflected only by implicit measures. This suggests that modality

transitions predictability aids correct attention deployment across sensory modalities, crucial for

learning crossmodal statistical contingencies. In the third experiment, where audiovisual stimuli with

semantic content were used leaving access to an amodal shared representation, participants could

explicitly recognize statistical regularities between crossmodal pairs even when the upcoming

modality was unpredictable. This finding suggests statistical learning between crossmodal pairs can

occur when sensory-level limitations are bypassed, and when learning unfolds at an amodal level of

representation. These findings challenge the view that statistical learning is strictly modality-specific,

instead indicating that crossmodal statistical learning depends on attentional mechanisms and

representational level.

Keywords: statistical learning, multisensory, crossmodal, prediction, attention

Introduction

Environmental information is highly structured conforming temporal and spatial patterns. The

human brain has developed an exquisite sensitivity to implicitly detect these statistical regularities

and exploit them to efficiently anticipate upcoming environmental changes. This ability, termed

statistical learning, has been thoroughly investigated in the last decades showing that the human

brain is ready to pick-up on statistical regularities at very early ages of development (Saffran et al.,

1996). Statistical learning is evolutionarily rooted, as it has been observed in other animals, and it

operates across sensory modalities, including auditory, visual, and tactile systems (Conway &

Christiansen, 2005; Fiser & Aslin, 2001; Saffran et al., 1999). Concerning the relation between

modalities, there is empirical evidence demonstrating that statistical learning in one sensory

modality is not impervious to stimulation in other sensory modalities (Cunillera, Càmara, et al., 2010;

Cunillera, Laine, et al., 2010; Glicksohn & Cohen, 2013; Mitchel & Weiss, 2011; Thiessen, 2010; Toro

et al., 2005). However, the evidence showing that statistical learning takes place between sensory

modalities is limited and inconsistent (Frost et al., 2015; Walk & Conway, 2016).

For instance, prior research has demonstrated that humans can concurrently learn statistical

regularities independently in two sensory modalities without interference, pointing to parallel

statistical learning mechanisms across perceptual systems (Conway & Christiansen, 2006; Li et al.,

2018; Mitchel & Weiss, 2011; Seitz et al., 2007). Additionally, statistical learning of an artificial

grammar does not transfer across modalities (Redington & Chater, 1996; Siegelman & Frost, 2015)

and there is no empirical evidence showing that humans can detect statistical regularities between

inputs presented in different sensory modalities (Walk & Conway, 2016).

As a result, the most accepted framework in the literature postulates that while statistical learning

relies on a domain-general set of computations, learning of the statistical associations between low-

level sensory features is modular and constrained by the specific characteristics of each sensory

modality (Frost et al., 2015). From this perspective, statistical learning of low-level sensory

regularities would be modality-specific, taking place in their corresponding sensory areas through

neural plasticity changes (Reber, 2013). Crossmodal statistical learning would be exclusively limited

to those sensory inputs that encode high-level representations of meaningful stimuli, and in theory

could occur through amodal representations shared between modalities.

In this non-preregistered study, we aim to scrutinize this framework in three experiments while

testing three complementary hypotheses that might explain why finding statistical learning between

low-level sensory inputs is so elusive. Firstly, studies on crossmodal statistical learning typically

involve a phase in which participants are passively exposed to statistical regularities, followed by a

phase in which participants must explicitly recognize the crossmodally associated items (Conway &

Christiansen, 2005; Seitz et al., 2007; Walk & Conway, 2016). This approach has obvious limitations,

as relying solely on explicit tests may provide an incomplete depiction of whether participants have

learned or not. Statistical learning typically unfolds in parallel in both implicit and explicit fashions

(Batterink et al., 2015; Conway, 2020), with the implicit system always "on" but the explicit system

optional. Therefore, for completeness, implicit statistical learning must be quantified using an online

measure of performance during the exposure phase (Siegelman et al., 2017). Indeed, previous

studies utilizing implicit measures have contributed to uncovering statistical learning, as

demonstrated by the facilitation in detecting expected targets or discriminating unexpected noisy

stimuli during the learning phase (Barakat et al., 2013; López-Barroso et al., 2016; Orpella et al.,

2021; Richter et al., 2018; Richter & de Lange, 2019). Thus, it is possible that previous studies that

only assessed learning based on explicit statistical learning measures might have overlooked

significant but implicit crossmodal statistical learning effects.

Second, crossmodal statistical learning might be impeded compared to unimodal statistical learning

due to a modality switching cost. Specifically, in randomly intermixed sequences of multimodal trials,

reaction times are slower when the target stimulus is preceded by a stimulus delivered in a different

sensory modality (Gondan et al., 2004; Otto & Mamassian, 2012; Shaw et al., 2020). This phenomenon, defined as modality switching cost, is associated with an attentional bias where we tend to expect information in the last processed sensory modality (Spence et al., 2001). In previous studies investigating crossmodal statistical learning (Walk & Conway, 2016), multimodal stimuli were randomly intermixed during the learning phase. Therefore, the presence of modality switching costs could potentially introduce biases favoring the perceptual grouping of inputs delivered within the same sensory modality. As suggested in Conway (2020), while learning unimodal regularities may be relatively independent of attention, the acquisition of statistical regularities across different sensory modalities may rely more heavily on precise selective attentional mechanisms. Consequently, if such a bias in perceptual grouping exists, it could affect the ability to bind together crossmodal items and learn crossmodal transitions effectively.

Third, previous studies assessing crossmodal statistical learning (Seitz et al., 2007; Walk & Conway, 2016) used meaningless audiovisual stimuli. According to the framework proposed by Frost and colleagues (Frost et al., 2015), crossmodal statistical learning can only occur between amodal representations. Therefore, the hypothesis that the level of representation of unisensory inputs determines the formation of crossmodal associations remains to be tested.

To test these hypotheses, we designed three statistical learning experiments where participants were exposed to a continuous stream of auditory and visual stimuli. The stream contained adjacent dependencies between stimulus pairs, with each stimulus in the pair being deterministically associated with another at 100% probability. Our design incorporated both within-modality (unimodal) and across-modality (crossmodal) pairs to compare how effectively people learn these different types of patterns.

For the first two experiments, we deliberately chose synthetic stimuli without semantic meaning: computer-generated fractal images and artificial sounds (see Fig. 1A). This design allowed us to determine whether crossmodal statistical learning could occur at a sensory level rather than through semantic associations. Across all experiments, we assessed statistical learning through two measures: an implicit measure during exposure (online) and an explicit measure after exposure (offline). Experiment 1 sought to validate previous findings by (Walk & Conway, 2016), unimodal and crossmodal pairs were presented in random order during training. In our study we introduced an implicit learning measure, in addition to the explicit judgement used in their original study. Building on this, Experiment 2 investigated whether people's natural tendency to attentionally group same-modality stimuli together might interfere with learning crossmodal patterns. To test our second hypothesis, we organized the stimuli into distinct blocks by modality combination, allowing participants to anticipate switches between visual and auditory input. This modification was

designed to counteract any perceptual bias towards grouping together stimuli of the same modality.

For Experiment 3, and to test the third hypothesis, we shifted to using meaningful auditory and

visual stimuli to test whether crossmodal statistical learning becomes possible when inputs from

different senses can be represented at higher-level, through modality-independent (amodal)

representations.

Foreshadowing our results, we found that when unimodal and crossmodal stimuli transitions are

randomly intermixed in during the exposure phase, participants only reliably learned the

associations between the unimodal pairs (Seitz et al., 2007; Walk & Conway, 2016). However, when

crossmodal transitions were predictable, participants could implicitly learn the association between

crossmodal pairs. Finally, we demonstrated that participants learned crossmodal transitional

probabilities (even when the upcoming modality was unpredictable) if the sensory inputs in the

different modalities are meaningful, validating the hypothesis that statistical learning also occurs

between higher amodal stimuli representations, regardless of their input modality.

Experiment 1

In the first experiment, we investigated whether participants could implicitly learn unimodal and

crossmodal statistical regularities between meaningless auditory and visual stimuli. To assess this,

we measured implicit statistical learning by recording participants' reaction times in detecting

predictable and unpredictable noisy stimuli during the exposure phase. We then used linear

regression models to examine whether detection of predictable noisy stimuli, compared to

unpredictable ones, improved with increasing exposure during this phase. After the exposure phase,

we assessed whether participants could explicitly recognize the pairs with a two-interval forced

choice task.

Methods

Figure 1.**A** Example of a standard visual stimulus and its noisy version in the Experiments 1 and 2 **B** 12 visual and 12 auditory meaningless
synthetic (Experiment 1 and 2) or meaningful natural (Experiment 3; not displayed here) stimuli were combined conforming 12 standard
pairs (3 x each modality combination). **C** Each experiment consisted in three parts: First, a training phase in which the participants were
familiarized with the task and the different stimuli. Second, an exposure phase with the same number of blocks in all experiments. In
Experiment 1 and 3, during the exposure phase, all the modality combinations were randomly intermixed in each block ("ALL" grey square
in the top row of the Exposure phase in panel C). In Experiment 2 only one modality combination was presented in each block (depicted
with different colors in the bottom row of the Exposure phase in panel C). Third, after the exposure phase, participants performed an
explicit recognition test. **D** Example of a stimuli sequence during the exposure phase in the first experiment (for illustrative purposes, color
frames denote standard pairs as represented in B and C). **E** An example trial of the explicit 2AFC test. The "Old" pair is one of the
previously presented pairs and a "New foil" pair is a new stimuli combination that was never presented during the exposure phase. The
color frame is added here for illustrative purposes: red for VV, yellow for AA pairs, green for AV and blue for VA pairs.

Participants

Forty-five university students participated in Experiment 1 (40 females, mean age 20.36, range 18-
28). None of the participants reported history of auditory problems, and all had normal or corrected-
to-normal vision. All participants signed informed consent before the experiment following the
guidelines of the Ethics committee of the University of Barcelona. Participants were paid with course
credit for their participation. The sample size for this and subsequent experiments was set to a
minimum of forty-five participants in consistence with similar studies and considering a medium
effect size (Cohen's d > 0.5) with a power of 95% in the explicit test.

Stimuli

Visual stimuli consisted of twelve artificially generated images of symmetric round fractals. Images

were created in Apophysis 7x, a fractal flame renderization software that uses iterated function

systems (Spotworks & Berthoud, 2008). The luminance saliency of the selected stimuli was

normalized using histogram equalization applied to the value channel of their HSV (hue, saturation,

value) representation. Every image had a diameter of 800 px. And was presented in the middle of a

CRT monitor, on a black background.

Auditory stimuli were created using random parametrization of multiple synthesizers from the

digital audio workstation FL Studio. Twelve different, unequivocally distinguishable abstract sounds

were generated. Stimuli were then edited using the software Audacity: their amplitude was

normalized, and their length reduced to 500 ms by cutting and time-stretching. To remove any

clicking in the sounds an envelope of 100 ms of attack and 100 ms of release was applied. Auditory

stimuli were presented through headphones to reduce interference with any possible environmental

noise.

Noisy versions of all stimuli were created to have a measure of implicit learning during the exposure

phase. In the visual modality, a layer of upscaled RGB white Gaussian noise with the same shape as

the stimuli was added to each stimulus. The noise was upscaled to get an additional pixelated effect

(Fig. 1A). In the auditory modality, white Gaussian noise with the same amplitude as the stimuli was

added to the sounds. Visual and auditory noisy stimuli were designed so that they could be easily

discriminated from the standard stimuli while still sharing enough characteristics with their

corresponding standard stimulus.

Procedure

The participants seated in a dimly light, sound attenuated room, facing a computer screen. The

viewing distance from the participants to the monitor was approximately 50 cm. Before the

experiment, participants were informed they would watch and listen to a series of images and

sounds that could either be standard or noisy. To ensure that the participants understood the

difference between standard stimuli and noisy stimuli, they were presented with an example of a

stimulus per modality and their corresponding noisy version before starting. Instructions were given

to the participants both orally by the experimenter and in written form printed on the screen.

The experiment consisted of three phases (Fig. 1C): a *training phase*, in which participants got

familiar with the stimuli and the task; an *exposure phase*, in which they were exposed to the stimuli

paired following the statistical regularities; and an explicit *test phase*, in which participants were

tested regarding their knowledge acquired from such regularities. Each phase was separated by a

short break of 1 minute.

During the training and exposure phases, the participants' task consisted of detecting noisy stimuli

by pressing the spacebar key whenever they saw or hear one. The task was orthogonal to the hidden

structure of pairs that randomly appeared during the stream. Participants were instructed to direct

their gaze at a white fixation cross at the center of the monitor. Each visual or auditory stimulus was

presented for a duration of 500 ms and they were separated by a 250 ms interval.

In the *training phase*, all the stimuli were presented to the participant in random order, without any

paired structure. Noisy stimuli appeared at a higher rate than during the exposure phase (35% of the

stimuli), because the objective of this phase was to teach participants to discriminate between

standard and noisy stimuli. The training phase lasted for one minute, but it was repeated until the

participant was able to detect at least the 80% of the noisy stimuli correctly. This way we ensured

that the participant would perform the noisy stimuli detection task correctly.

The *exposure phase* had the objective to expose the participants to learn the transitional

probabilities and measure their implicit learning of the pairs. In this phase, visual and auditory

stimuli (twenty-four in total) were pseudo-randomly grouped into twelve pairs conforming four

different modality combinations (Fig. 1B): auditory to auditory (AA), visual to visual (VV), auditory to

visual (AV) and visual to auditory (VA), with three pairs for each modality combination. All four

conditions were randomly sorted conforming one single stream (Fig. 1D). Transitional probabilities

between the stimuli within a pair was set at 100%, while the transitional probabilities between

stimuli of different pairs was set at 10%. Each pair was presented 110 times during exposure leading

to a total of 1320 pair presentations at the end of the exposure phase. Pairs were therefore

presented in random order with the only restriction that the same pair could not repeat after itself.

Each stimulus appeared in its noisy version 10 times, out of a total of 110. Noisy appearances were

randomly scattered across the exposure phase and they appeared half of the times on the first item

of the pair (leading stimulus) or on the second item of the pair (trailing stimulus).

This part of the experiment was divided into eight blocks, each of them lasting for approximately six

and a half minutes. Between blocks, participants had the opportunity to rest and then resume the

experiment by pressing a key whenever they wanted. In order to maintain the participants engaged

with the task, after each block, participants received feedback about the percentage of noisy stimuli

detected. To constrain the temporal window between noisy stimuli and keypresses and calculate the

proportion of correct noisy stimuli detection, we considered a correct detection whenever a

keypress occurred no later than 2 seconds after the noisy stimulus' onset.

Following the exposure phase, we informed the participants for the first time that they would need

to complete an additional task. In this *explicit test phase*, we explained that the visual and auditory

stimuli they encountered during the exposure phase were presented conforming pairs. To evaluate

whether the participants had explicit knowledge of these pairs, we administered a two-alternative

forced choice (2AFC) task. In each trial, participants were sequentially shown an old pair and a new

foil pair, with the deviant item equally often inserted in either leading or trailing positions. The old

pair had been presented during the exposure phase, while the foil pair violated the statistical

regularities of the exposure phase.

For each condition, the stimuli included three old pairs from the learning phase (e.g., for visual pairs:

V1-V4, V2-V5, V3-V6), and three new foil pairs of the same modality. These foils were created by

randomly pairing the leading stimuli of each standard pair with a trailing stimulus from another pair

(e.g., V1-V5, V2-V6, V3-V4). Importantly, these foils were new to the participants and were matched

in frequency of occurrence for each stimulus, ensuring that participants could not rely on differences

in stimulus frequency to solve the task. This procedure was repeated for each modality, resulting in a

total of 24 pairs (12 old and 12 foil). Each old pair was presented against three foil pairs of the same

modality (e.g., V1-V4 vs. V1-V5, V1-V4 vs. V2-V6, V1-V4 vs. V3-V4), yielding a total of 36 test trials.

After viewing both old and new foil pairs in sequence, participants selected, using the left and right

arrow keys, which pair felt more familiar to them (left for the first pair, right for the second). They

were also asked to report the confidence of their decision by pressing 'Z' if they "remembered the

sequence," 'X' if "the sequence was more familiar," or 'C' if they were "guessing." These responses

correspond to three confidence levels: Remember, Know, and Guess, respectively. We treated the

Remember and Know responses as indicators of explicit knowledge, accessed through either recall

or familiarity. The test was self-paced: participants pressed a key to initiate each pair and had no

time limit for responding.

Analyses

To evaluate whether participants could implicitly learn the statistical regularities, we focused our

analysis on reaction times (RTs). We included only RTs longer than 200 ms and shorter than 2

seconds relative to the noisy stimulus onset. To reduce the positive skewness typical of RT

distributions, we normalized them by calculating the reciprocal of the latencies (Whelan, 2008),

where higher 1/RT values indicate faster responses.

To assess learning, we examined the impact of noisy stimulus position (leading vs. trailing within

each pair) on detection speed using a linear mixed-effects model (LMM). LMMs offer greater

statistical power than classical ANOVA analyses because they can account for variability in RTs

between participants or stimuli as random effects. Specifically, we quantified implicit statistical

learning by modelling RTs as a function of the noisy stimulus position within the pair (i.e., the

"learning" regressor).

Based on prior research (Barakat et al., 2013; Richter & de Lange, 2019; Yan et al., 2021; Zhou et al.,

2019), we predicted that participants would demonstrate implicit learning by using the leading

stimulus to anticipate the trailing stimulus in each pair. This anticipation must lead to faster RTs for

detecting trailing compared to leading noisy stimulus, reflecting implicit learning throughout the

exposure phase (Fig. 2, middle panel).

To assess continuous and sustained implicit learning of transition probabilities throughout the

experiment, we used the "trial" number of each stimulus presentation as a continuous regressor in

relation to the learning regressor. The trial number reflects the number of times a specific modality

combination was presented during the implicit phase. For instance, a trial number of 600 for the

crossmodal conditions indicates that participants had encountered 600 crossmodal pairs in the

exposure phase. Importantly, the interaction between the "learning" and "trial" regressors (Fig. 2C)

represents the learning rate, which captures sustained variations in learning across multiple trials. To

improve the mixed model's convergence, we rescaled trial number regressor to z-scores.

To test for potential differences in implicit learning between unimodal and crossmodal transitions, in

our main analyses we grouped auditory and visual conditions together (unimodal transitions) and

audiovisual and visuo-auditory conditions together (crossmodal transitions) (see Table 1; Eq. 1). To

account for variability due to the modality of the noisy stimulus, we included "modality"

(visual/auditory) as a regressor of no interest and as an additional random-effect term, addressing

modality-specific differences it might cause on RT. We also included random error effects, allowing

the intercept to vary independently for each participant and stimulus identity. In addition, we

performed exploratory analyses to test whether statistical learning within the unimodal and

crossmodal conditions was driven by the auditory, the visual noisy stimulus or both.

The models were optimized using the bobyca algorithm from the lme4 package (Baayen et al., 2008;

Bates et al., 2014) in R (version 3.6.2, R Foundation for Statistical Computing). We used post-hoc

likelihood-ratio (χ^2) model comparisons to assess the predictive power and significance of all main

effects and interactions. A reduced model, containing only trial number and modality transition as

fixed effects, was compared to increasingly complex models, including the learning regressor. After

multiple comparisons, we identified a model that best explained the data, reporting the obtained χ^2

against the immediately less complex model. We then assessed the significance of each fixed effect

estimate by calculating the Wald (z) statistic in the full model. For additional support of a null

hypothesis, Bayes-factor (BF) estimates from model comparisons showing null effects are reported.

Figures in this manuscript display regressor coefficients and confidence intervals from the most

complex model, which includes all main effects and interactions, allowing for direct comparison

across experimental conditions.

Figure 2. Implicit Statistical Learning Model Regressors Predictions. The upper rows represent artificially generated linear regression
model predictions for different possible experimental outcomes, while the bottom rows depict the corresponding parameter estimates of
the models described above. Interpretation of parameter estimates: The 'intercept' of the model represents the estimate of 1/RT at the
beginning of the experiment (baseline 1/RT prior to any learning). The 'trial' regressor estimate indicates the modulation of 1/RT as a
function of the number of trials. The 'learning' regressor represents the average difference in 1/RT between trailing and leading noisy
stimuli. Finally, the learning rate is computed as the linear interaction between the number of trials and the learning regressor. A. Shows
the parameter combination for an outcome where there is no statistical learning, with performance improving as the experiment
progresses. B. Shows the parameter combination for an outcome where participants successfully learned the statistical regularities. A
significantly positive value for the learning regressor indicates that participants promptly learned the statistical associations, as
performance differences appear from the beginning of the experiment. C. Shows a positive learning rate, indicating that participants
increasingly utilized the predictive association between leading and trailing items, with the learning gradually unfolding over time. The
grey and black points in the upper row represent the artificially generated underlying 1/RT averages of trailing and leading stimuli,
respectively, across trials.

To test whether participants could explicitly recognize the associations between the leading and

trailing stimuli, we modelled the responses of the 2AFC explicit learning test using GLMM (family

binomial logit) implemented in lme4. As this task consisted of a 2AFC, chance level is equal to a 50%

of correct responses (logistic regression intercept = 0). Similarly to the implicit learning analyses, we

modelled unimodal and crossmodal modality transitions conditions separately. This approach was
primarily motivated by the low number of trial repetitions for each modality combination. If the
intercept of the model is significantly larger than 0, it means that participants can discriminate the
old pairs from the foils above chance level (>50%). Moreover, to determine whether the participants
guessed or explicitly recognized the old pairs, we also modelled the level of confidence reported in
the decision (Table 1; Eq.2). We only report the results and statistics of the post hoc model
comparisons in the main results section. Again, the reported χ2 values reflect the contrast of the
best model against the immediately simpler contrasted model. The stimuli and code used to run the
experiments, and reproduce the analyses and figures is available at https://osf.io/tcxe9/ (Pérez-
Bellido, 2023).

Table 1: Linear Mixed Models for Quantifying Implicit and Explicit Statistical Learning Effects. Eq.1 depicts the full Linear Mixed Model
(LMM) model used to quantify implicit learning from speediness measurements (1/RT). We compared our base model, which includes a
trial regressor and its interaction with the modality transition regressor, against other extended versions of the model including a main
effect [+] or an interaction [*] with the learning regressor. Eq.2 represents the Generalized Linear Mixed Model (GLMM) utilized to predict
the probability of correct responses based on the confidence level. Random effects of the mixed models include (modality|participant)
and (1|stimulus).

	Dependent variable	Regressors	Equation ID
Implicit statistical learning effects	1/RT	~ modality + trial * modality transition [+ or *] learning (noisy stimulus position) + Random effects	Eq. 1
Explicit statistical learning effects	P(Correct)	~ confidence level + Random effects	Eq. 2

Results

Exposure phase: implicit learning for unimodal pairs only

The high accuracy of the participants in noise detection (Fig. 3A) indicated thar participants were
paying attention to both modalities (group average: $P(Hits)_v = 0.99$ and $P(Hits)_A = 0.85$). A repeated
measures ANOVA showed that participants detected more noisy stimuli in the visual compared to
the auditory conditions ($F(1, 63) = 52.2$, $P < 0.01$), but their detection performance did not change as
a function of modality transition ($F(1, 63) = 0.063$, $P = 0.8$).

Figure 3. Performance during the exposure and explicit learning phases in Experiment 1: A. Group-average speediness (1/RT) for the unimodal and crossmodal pairs, separated by stimulus modality (V, A) and modality transition (unimodal, crossmodal). B. Full model predictions for the unimodal and crossmodal pairs. Thin lines represent the confident intervals of the model. Filled points with error-bars represented group-level average values at different trials bins and their corresponding standard error. C. Parameter estimates of the full model depicted in B. D. Explicit test accuracy in discriminating old from new foils in the unimodal and crossmodal conditions. E. Analysis of participants accuracy as a function of the confidence. Confidence intervals (error bars) are calculated as the parameter estimate standard error multiplied by 1.96. Based on model parameter contrasts, black asterisks indicate significant differences between conditions estimates, while colored asterisks indicate significant modulations of a given parameter with respect to 0.

We used linear mixed-effects models (LMMs) and conducted post hoc likelihood-ratio (χ^2) model comparisons to investigate the impact of trial number and learning regressors on participants' response times for detecting noisy stimuli (as illustrated in Fig. 3B and C). Our analysis showed that the full model, which included a triple interaction between trial number, modality transition, and learning, provided the best explanation for the data (χ^2 = 14, df = 3, P < 0.01). A closer look at the regressors fitted to the unimodal trials showed that participants' noise detection speed did not differ between leading and trailing noisy stimuli at the beginning of the experiment (χ^2 = 1.2, df = 1, P = 0.2; BF = 0.02), as indicated by the non-significant difference between the leading and trailing intercepts (learning: z = -1.7, P = 0.07). However, as the experiment progressed and the number of trials increased, participants became faster in detecting trailing noisy stimuli compared to leading ones (learning rate: z = 3.46, P < 0.01), consistent with an implicit learning effect (Fig. 2C). We

replicated similar effects for the unimodal auditory (learning rate: z = 2.3, P < 0.05) and visual

(learning rate: z = 3.2, P < 0.005) noise, demonstrating that unimodal statistical learning was not

primarily driven by either modality. In contrast, we did not observe a similar learning effect in the

crossmodal pairs (learning rate: z = 0.3, P = 0.78; Model comparison χ^2 = 0.01, df = 2, P = 0.95, BF <

0.01). Overall, these findings suggest that participants gradually acquired and utilized the stimulus

associations to improve noise discrimination only for the unimodal pairs.

Additional analyses revealed that participants' RTs on average were faster for visual noise compared

to auditory noise (modality: z = -4.1, P < 0.001), suggesting that detecting auditory noise is more

effortful than detecting visual noise, and improved with the number of trials in the crossmodal pairs

(trial: z = 7.4, P < 0.001). Moreover, differences between unimodal and crossmodal intercepts

indicated that participants, on average, were slower in detecting noise during crossmodal modality

transitions (modality transition: z = -5.6, P < 0.001), consistent with the modality switching cost

observed in the proportion of hits for noisy stimuli detection.

Explicit test phase: explicit learning of unimodal transitional probabilities

The GLMM analyses of correct response proportions in the explicit learning test phase revealed that

participants could recognize unimodal old pairs above chance level (intercept: z = 3.61, P < 0.001; χ2

= 10.02, df = 1, P < 0.005). However, we found no evidence of old pair recognition for crossmodal

conditions (χ2 = 2.93, df = 1, P = 0.23; BF = 0.3; Fig. 3D). Additionally, the confidence level regressor

only improved the model's fit in the unimodal conditions (χ2 = 6.1, df = 2, P < 0.05). Specifically,

participants showed a higher proportion of correct responses in both the "know" (z = 2.65, P <

0.005) and "remember" (z = 2.18, P < 0.05) conditions compared to the "guess" condition (Fig. 3E).

These results suggest that participants could only explicitly recognize the unimodal pairs.

In summary, this experiment shows evidence of unimodal implicit and explicit statistical learning.

However, the results regarding crossmodal statistical learning align with previous studies showing a

modality-specific limitation that prevents the extraction of regularities between modalities at the

sensory level.

Experiment 2

In our first experiment, we observed that participants were able to learn and use unimodal

transitional probabilities effectively to discriminate the noisy stimuli, while crossmodal transitional

probabilities were not learned. These findings support the notion that statistical learning is a
modality-specific process that operates within each sensory modality (Frost et al., 2015). However, it
is important to note that in Experiment 1, stimuli were presented in a continuous stream, where
unimodal and crossmodal transitions were randomly intermixed. This random presentation may
have hindered the learning of crossmodal pairs due to the perceptual costs associated with
switching between modalities, as previously demonstrated in multisensory research (Gondan et al.,
2004; Otto & Mamassian, 2010; Spence et al., 2001). To reduce the potential impact of this
attentional cost on statistical learning, we designed our second experiment to include eight different
experimental blocks, each containing a specific combination of visual-visual (VV), auditory-auditory
(AA), audio-visual (AV), and visual-audio (VA) stimuli (Fig. 1C). By doing so, participants could
anticipate the modality of the incoming stimuli in the crossmodal blocks (e.g., AVAVA or VAVAV),
thus eliminating the possibility of a bias to perceptually group consecutive visual or auditory stimuli
together.

Methods

Participants

Sixty-three university students participated in Experiment 2 (59 females, 4 males, mean age 20.36,
range 18-28). Participant recruitment criteria and stimuli were identical to those in the previous
experiment. Due to an error in participant recruitment, we collected 13 more participants than our
target (45 + 5 possible dropouts). Since eliminating the last 13 participants from the final sample did
not change the results, we decided to maintain them in the analyses.

Procedure

The experimental procedure was almost identical to Experiment 1. However, here there was only
one modality combination in each experimental block, being either VV, AV, AA, or VA (Fig. 1C). The
order of each modality block was randomized for each participant, and two blocks of the same
modality combination could not come one after the other. We kept the transitional probabilities
between the stimuli within a pair at 100%. Importantly, because we kept the stimuli identical to
Experiment 1 varying only the stimuli presentation, this implied a smaller number of possible pairs
within each block (only 3 pairs, 6 stimuli). Therefore, the transitional probabilities between pairs was
0.5 (more than ×4 higher than in Experiment 1), potentially rendering the statistical learning of the
associated pairs more challenging compared to the previous experiment.

Results

Implicit learning of crossmodal transitional probabilities only

During the exposure phase (Fig. 4A), participants successfully detected most of the visual and auditory noisy stimuli ($P(Hits)_V$ = 0.99 and $P(Hits)_A$= 0.88). A repeated measures ANOVA showed that participants detected more noisy stimuli in the visual compared to the auditory conditions ($F(1, 63)$ = 52.2, P < 0.01), but their detection performance did not change as a function of modality transition ($F(1, 63)$ = 0.063, P = 0.8).

To investigate whether participants learned the item associations, we used a linear mixed model (LMM) to analyze 1/RTs as a function of trial number (full model in Fig. 4B and C). The best-fitting model included trial number, type of modality transition, and learning as fixed effects (χ^2 = 10.13, df = 3, P < 0.02). A closer look at the parameter's estimates showed that the learning effect was driven by the crossmodal conditions, as on average, participants were faster in detecting crossmodal trailing than leading noise (learning: z = 4.6, P < 0.001). This difference did not continue increasing throughout the number of trials (χ^2 = 0.16, df = 2, P = 0.9, BF < 0.01), as the learning rate parameter was not significantly different from 0 (learning rate: z = -0.4, P = 0.68). That is, the learning of crossmodal statistical regularities reaches its maximum in a relatively small number of trials and does not continue evolving with additional exposure. We replicated significant positive differences in the learning parameter when analysing the auditory (learning$_A$: z = 3.7, P < 0.001) and visual (learning$_V$: z = 3.2, P < 0.005) crossmodal conditions separately, demonstrating that crossmodal statistical learning was not driven by either of the two possible crossmodal modality combinations.

Our complementary analyses on the unimodal trials did not provide evidence that participants learned the unimodal transitional probabilities, as the RTs in detecting leading and trailing noisy stimuli were not significantly different (χ^2 = 1.4, df = 1, P = 0.23, BF = 0.05).

This rapid statistical learning (Fig. 2B), which contrasts with Experiment 1 where implicit learning developed gradually, may be attributed to differences in the experimental design. In this new experiment, each modality combination pair was repeatedly presented within its experimental block (e.g. AV block), whereas in Experiment 1, modality combinations appeared throughout the entire experiment. Frequent exposure to the same pairs over a few trials may enhance the learning of statistical dependencies.

Additionally, the analyses revealed that on average, participants' reaction times improved with the

number of trials for both the noisy stimuli in unimodal and crossmodal pairs (trial: z = 6, P < 0.001).

This sustained and general RTs improvement can be attributed to a practice effect. Participants also

showed faster responses to visual compared to auditory noise (modality: z = -2.14, P = 0.04)

suggesting that it was easier to detect visual noise. Finally, based on the significant differences

between the unimodal and crossmodal model intercepts, we replicated that, on average,

participants were slower in detecting a noisy stimulus preceded by a stimulus in a different modality

(modality transition: z = -10.1, P < 0.001). These results indicate that in Experiment 2, despite

participants were able to anticipate modality alternations due to the task structure, they still

incurred in a cost associated with modality switches.

Figure 4. Performance during the exposure and explicit test phases in Experiment 2: A. Group-average speediness (1/RT) for the unimodal
and crossmodal pairs, separated by stimulus modality (V, A) and modality transition. B. Full model predictions for the unimodal and
crossmodal pairs. Thin lines represent the confident intervals of the model. Filled points with error-bars represented group-level average
values at different trials bins and their corresponding standard error. C. Parameter estimates of the full model depicted in B. D. Explicit
test accuracy in discriminating old from new foil pairs in the unimodal and crossmodal conditions. E. Analysis of participants accuracy as a
function of the confidence. Confidence intervals (error bars) are calculated as the parameter estimate standard error multiplied by 1.96.
Based on model parameter contrasts, black asterisks indicate significant differences between conditions estimates, while colored asterisks
indicate significant modulations of a given parameter with respect to 0.

No evidence of explicit statistical learning

GLMM analyses on the proportion of correct responses showed that participants could not explicitly

recognize the unimodal ($\chi2$ = 0.93, df = 1, P = 0.3, BF = 0.04) nor the crossmodal pairs ($\chi2$ = 0.1, df =

1, P = 0.7, BF = 0.03). Overall, the results of this second experiment show that participants were able

to benefit for the predictable alternation between modalities to learn crossmodal transitional

probabilities and use them to improve their detection of trailing noisy stimuli but this was not

reflected in the explicit measures of learning. The unimodal conditions were more penalized by the

higher transitional probabilities at boundaries between pairs in comparison to the first experiment

than the crossmodal pairs. These findings suggest that crossmodal statistical learning occurs when

modality transitions are predictable. Additionally, our results indicate that crossmodal statistical

learning is primarily evident when assessed through implicit measures. In contrast, we also

demonstrate that unimodal statistical learning can be observed through both implicit and explicit

indices, provided there is a sufficient difference in the transitional probabilities between paired and

non-paired items.

Experiment 3

In Experiment 3, we tested the prediction that both unimodal and crossmodal regularities can be

learned if the stimuli contain semantic information and are therefore not tight to the sensory level

characteristics. Consistent with the hypothesis proposed by Frost et al., (2015), we predicted that if

statistical learning can occur between high-level stimuli representations (Brady & Oliva, 2008),

participants should be able to learn crossmodal contingencies between meaningful crossmodal pairs.

To test this prediction, we used visual and auditory stimuli with meaningful content to facilitate the

formation of sensory-independent stimulus relations.

Methods

Participants

Fifty university students participated in Experiment 3 (7 males, mean age 21.9, range 18-45).

Participant's recruitment criteria and the stimuli were identical to the previous experiments.

Procedure

Similar to the first experiment, we randomly intermixed visual, auditory, audiovisual, and visuo-
auditory pairs in each experimental block while maintaining the transitional probabilities between
stimuli within a pair at 100% and the transitional probabilities between pairs at 10%. However,
unlike the previous experiments, we used meaningful stimuli to represent visual and auditory
objects. The visual images were composed of the same number of visual and auditory items than
Experiments 1 and 2. Six animate objects (e.g., crocodile) and 6 inanimate objects (e.g., piano) were
overlaid on a black background. Similarly, auditory stimuli consisted of 500 ms clips corresponding to
6 animate (e.g., dog barking) and 6 inanimate objects (e.g., phone ringing). All stimuli were freely
downloaded from the internet and pre-processed in the same manner as the fractals and synthetic
stimuli used in the previous experiments to generate the noisy version of the stimuli. Prior to the
beginning of the experiment, the experimenter presented all the stimuli to the participants one by
one to ensure that they understood the semantic referent of each image and sound. We found that
all the stimuli referents could be correctly identified by all the participants.

Results

No evidence of implicit statistical learning

During the exposure phase, participants accurately detected both the visual and auditory noisy
stimuli, with group averages of $P(Hits)_V = 0.97$ and $P(Hits)_A = 0.84$ (Fig. 5A). To explore how
participants' noise detection changed as a function of modality and modality transition, we
conducted a repeated measures ANOVA. This analysis revealed that participants detected more
noisy stimuli in the visual than auditory modalities ($F(1,48) = 75.6$, $P < 0.01$) and more noisy stimuli in
the crossmodal than unimodal pairs ($F(1,48) = 75.6$, $P < 0.01$). We also observed a significant
interaction between modality and modality transition ($F(1,48) = 15.5$, $P < 0.01$), indicating that
auditory noise was better detected in the crossmodal than unimodal pairs

We fitted a LMM on reaction times to determine whether participants learned pair associations
implicitly (Fig. 5B and C). Our analysis revealed that the best model for explaining participants'
responses only included trial and modality transition as fixed-effect regressors ($\chi2 = 22.8$, df = 1, $P <$
0.01). We did not find evidence of implicit statistical learning, as including the learning regressor did
not improve the model fit ($\chi2 = 0.58$, df = 1, $P = 0.44$, BF < 0.01). Further investigation of the
regression estimates showed that participants' performance improved with increased practice in the
unimodal and crossmodal conditions (trial: $z = 1.91$, $P = 0.04$), indicating a practice effect.
Participants also showed faster responses to visual compared to auditory noisy stimuli (modality: $z =$
-5.3, $P < 0.001$). Furthermore, in line with previous analyses, the differences between unimodal and
crossmodal intercepts indicated that participants were generally slower at detecting noise in stimuli

when these were in crossmodal than unimodal pairs(modality transition: z = -3.4, P < 0.001),

reflecting a modality switching cost. Overall, these findings did not provide empirical evidence of

statistical learning through the implicit measure of noise detection in either modality or during

modality transitions.

Figure 5. Performance during the exposure and explicit learning phases in Experiment 3: A. Group-average speed (1/RT) for the unimodal

and crossmodal pairs, separated by stimulus modality (V, A) and modality transition. B. Full model predictions for the unimodal and

crossmodal pairs with confident intervals. Thin lines represent the confidence intervals of the model. Filled points with error-bars

represented group-level average values at different trials bins and their corresponding standard error. C. Parameter estimates of the full

model depicted in B. D. Explicit test accuracy in discriminating old from new foil pairs in the unimodal and crossmodal conditions. E.

Analysis of participants accuracy as a function of the confidence. Confidence intervals (error bars) are calculated as the parameter

estimate standard error multiplied by 1.96. Based on model parameter contrasts, black asterisks indicate significant differences between

conditions estimates, while colored asterisks indicate significant modulations of a given parameter with respect to 0.

Explicit learning of unimodal and crossmodal pairs

GLMM analyses on the proportion of correct responses in the explicit learning test phase reveal that

participants did recognize the unimodal old pairs above chance level ($\chi 2$ = 20.9, df = 1, P < 0.001; Fig.

5D). Interestingly, we also found that participants explicitly recognized the crossmodal old pairs ($\chi 2$ =

6.3, df = 1, P < 0.02). The confidence level regressor significantly improved the model's fit in both the

unimodal ($\chi2$ = 15.8, df = 2, P < 0.01) and the crossmodal conditions ($\chi2$ = 7.8, df = 2, P < 0.03).

Participants reported a larger proportion of correct responses in the "know" confidence level

compared to the "remember" (know vs remember; unimodal: z = 3.4, P < 0.005; crossmodal: z = 2.7,

P < 0.01) and "guess" (know vs guess; unimodal: z = 3.2, P < 0.005; crossmodal: z = 2.2, P < 0.03)

levels highlighting the explicit nature of the observed learning (Fig. 5D).

These results indicate that participants can recognize both unimodal and crossmodal old pairs when

they contain meaningful information. Moreover, participants showed a degree of awareness in their

learning, as evidenced by greater accuracy in decisions rated with a confidence level of know.

Discussion

Previous studies have failed in showing crossmodal interactions in statistical learning (Conway &

Christiansen, 2006; Seitz et al., 2007; Walk & Conway, 2016). This has led to propose that, although

statistical learning relies on domain-general computational principles, the learning of statistical

dependencies between multimodal low-level stimulus features (e.g. tones, shapes, vibrations) is

constrained by the representational characteristics of its correspondent sensory modality (Frost et

al., 2015). Here, in three separate experiments we investigated different explanations that could

have impeded previous studies to detect crossmodal statistical learning.

In our first experiment, we replicated previous studies that demonstrated significant statistical

learning between unimodal stimuli, but null statistical learning between crossmodal stimuli (Walk &

Conway, 2016). Our results provided evidence of statistical learning through both explicit task

responses and the use of an implicit measure. Specifically, we found that while reaction times

towards leading and trailing noise detection were not significantly different at the beginning of the

implicit training phase, as the experiment progressed, participants became faster in detecting the

noisy stimuli in trailing compared to the leading positions in unimodal pairs, indicating implicit

learning and exploitation of the unimodal associations. Crossmodal learning was not observed even

when learning was measured with implicit measures during the learning phase.

One possible explanation for the null crossmodal statistical learning in Experiment 1 is that unimodal

and crossmodal stimuli pairs were randomly intermixed during the exposure phase. This mixing may

have introduced modality switching costs, potentially biasing participants' attention toward grouping

inputs from the same sensory modality together. This attentional bias might facilitate the learning of

unimodal associations but impair the learning of crossmodal contingencies, as previous research has

highlighted the crucial role of attention in both unimodal (Treisman & Gelade, 1980) and crossmodal

(Talsma et al., 2010) information binding, as well as in statistical learning processes (López-Barroso

et al., 2016; Richter & de Lange, 2019; Toro et al., 2005). To address this potential confound, in

Experiment 2 we tested whether participants could learn crossmodal associations more effectively

when stimuli were paired in modality-predictable transitions, thereby eliminating the attentional

bias toward grouping stimuli from the same modality. Notably, the reaction time analysis in

Experiment 2 revealed that participants were able to implicitly learn and exploit the crossmodal

associations, contrasting with their inability to learn the unimodal associations. While the latter were

hindered by the increased transitional probabilities at the boundaries between pairs in Experiment

2, rising from 10% to 50% with respect to Experiment 1, the alternation between modalities might

have helped to mitigate this limitation in crossmodal pairs. In this condition, participants could use

the modalities alternation as a cue to know which modality was the leading item once one pair was

accurately segmented. This could have facilitated the learning process even in the face of increased

transitional probabilities between items. Alternatively, it is possible that different cognitive

mechanisms are involved in learning unimodal versus crossmodal associations, leading to differential

effects of transitional probabilities on learning. However, further research is needed to fully

understand the underlying mechanisms behind these findings. In any event, the results of

Experiment 2 are consistent with our a priori hypothesis, which posited an attentional bias to group

stimuli from the same modality together. Such a bias might hinder the capacity to learn the

associations between inputs delivered through different sensory modalities when these are not

temporally segmented as pairs. In line with this idea, previous research (Kok et al., 2012) using

audiovisual associations between low-level stimuli (i.e., frequency tones and grating orientations),

but presented in temporally discernible pairs and always and with modality associations occuring

always in the same order, has already shown learning of the crossmodal correspondences at both

the behavioral and neural levels. In summary, the results of this second experiment highlight the

importance of attention as a modulatory factor of statistical learning (Orpella et al., 2021; Perruchet

& Pacton, 2006), here guided by the predictability of modality alternations, facilitating crossmodal

learning when stimuli are processed only at the sensory level.

Finally, in a third experiment, we tested whether participants could learn crossmodal associations

using meaningful visual and auditory stimuli. Drawing from findings demonstrating that humans can

learn category-level statistical regularities (Brady & Oliva, 2008; Yan et al., 2023), we aimed to show

that humans can also learn transitional probabilities between multisensory inputs that can be

encoded in an amodal format, detached from their sensory referents. In line with this hypothesis, in

Experiment 3, using an implicit learning task, similar to the one used in Experiment 1, participants

were able to learn both the unimodal and the crossmodal associations explicitly. Our results are

consistent with previous studies (Cunillera, Laine, et al., 2010) that demonstrate that the semantic
processing of the stimuli may facilitate the explicit recognition of the associated pairs in both
unimodal and crossmodal conditions.

The inclusion of implicit and explicit measures of statistical learning was essential in this study to be
able to observe whether crossmodal SL took place. This was particularly important, in Experiments 2
and 3 where dissociations between those measures were observed. Previous studies have
documented the absence of a correlation between those measures (Forscher et al., 2019). For this
reason, the inclusion of both is critical in all SL studies since different mechanisms may underlie the
two types of learning and/or these measures have different sensitivity to learning. Nevertheless,
whereas implicit learning can occur without explicit learning, as we observed in Experiment 2, the
opposite is unlikely (Batterink et al., 2015; Conway, 2020). Therefore, we believe that a null effect in
implicit learning in Experiment 3 does not necessary mean that there was not implicit learning.
Although we do not have a priori explanation for this null result, we speculate that it is possible that
the online measure that we used to index implicit learning was not optimal in capturing the learning
when using semantic stimuli. Whereas the processing of meaningless stimuli in Experiments 1 and 2
may favor the encoding of sensory differences (i.e., sensory noise), the processing of meaningful
stimuli may prioritize the neural encoding of high-level referents of the presented inputs, reducing
the impact of statistical learning on the processing of the low-level sensory characteristics of the
inputs (Hochstein & Ahissar, 2002). Perhaps using a task in which participants must perform a
semantic task would help reveal implicit statistical learning. Indeed, the fact that the stimuli had a
semantic content but the task that used to measure implicit learning required focusing at the
perceptual level made the detection task more difficult, as reflected by the increased reaction time
in Experiment 3 compared to Experiments 1 and 2. This may have impeded to observe learning in
the implicit measure due to a reduced sensitivity at such high reaction times.

Our behavioral results do not allow us to draw definitive conclusions about the neural mechanisms
involved in crossmodal statistical learning. However, they do support the idea that statistical
learning can occur at multiple levels of representation, encompassing both sensory and amodal
information. The key difference lies in the fact that while the learning of low-level associations is
constrained by perceptual phenomena (i.e., grouping biases), learning of semantic associations
bypasses these limitations. This aligns with neural evidence from intracranial recordings (Henin et
al., 2021), which shows that both supramodal and modality-specific brain structures are involved in
statistical learning across sensory modalities. While sensory areas encode transitional probabilities
specific to either auditory or visual statistical learning, the hippocampus and higher-order brain
regions—which process the internal structure related to the order and identity of elements—are

shared across modalities. The existence of shared statistical learning mechanisms across sensory
modalities has also been characterized behaviorally. Sabio-Albert et al. (2025) demonstrated that
accuracy in one modality was influenced not only by the predictability of this modality but also by
the predictability of an ignored modality. These interactive effects reveal an interdependence
between the visual and the auditory statistical learning mechanisms.

In summary, this study demonstrates that humans can indeed learn crossmodal statistical
regularities. It identifies several factors that may be determinant for this learning, including the
presence of within-modality attentional biases and the level of representation of sensory inputs. Our
results contribute to expand the view of statistical learning suggesting that learning of statistical
regularities between low-level stimuli features relies on hard-wired learning computations occurring
in their respective sensory cortex. Specifically, we show that visual and auditory synthetic stimuli,
which are challenging to represent in an amodal format (e.g., semantic representations), can still be
bound together, albeit with perceptual limitations that can be overcome through attention
mechanisms (Conway, 2020).

On the other hand, this work raises new questions for future research. For instance, are the
mechanisms underlying crossmodal statistical learning functionally and neurophysiologically
comparable to those of unimodal statistical learning? Additionally, is crossmodal statistical learning
more effective than unimodal learning when attentional biases are controlled?

Author contributions: D.D., R.D.B., and A.P.B. designed the experiments. D.D. and F.G. conducted
the experiment. A.P.B. analyzed the data. F.G. and A.P.B. wrote the original draft. R.D.B. and A.P.B.
edited the manuscript. D.D. and F.G have contributed equally to the development of this project.

Acknowledgments: We thank Alicia Macià-Mendoza for help in data collection for Experiment 3.
This work was supported by the AGAUR (BP 00213), and the Spanish Ministerio de Ciencia,
Innovación y Universidades, which is part of Agencia Estatal de Investigación (AEI), and the European
Regional Development Fund awarded to the projects RTI2018-100977-J-I00 and RYC2022-037652-
I to A.P.B. and PID2021-127146NB-I00 project to R.D.B) and the Maria de Maeztu to the Institute of
Neuroscience. The work was also supported by the SGR (2021 SGR 00352) from AGAUR, Generalitat
de Catalunya to R.D.B. We also thank the CERCA Programme / Generalitat de Catalunya for
institutional support.

Conflict of interest statement: The authors declare no competing financial interests.

References

Baayen, R. H., Davidson, D. J., & Bates, D. M. (2008). Mixed-effects modeling with crossed random
effects for subjects and items. *Journal of Memory and Language*, *59*(4), 390–412.
https://doi.org/10.1016/j.jml.2007.12.005

Barakat, B. K., Seitz, A. R., & Shams, L. (2013). The effect of statistical learning on internal stimulus
representations: Predictable items are enhanced even when not predicted. *Cognition*, *129*(2),
205–211. https://doi.org/10.1016/j.cognition.2013.07.003

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2014). *Fitting Linear Mixed-Effects Models using*
lme4. *1*. https://doi.org/10.18637/jss.v067.i01

Batterink, L. J., Reber, P. J., Neville, H. J., & Paller, K. A. (2015). Implicit and explicit contributions to
statistical learning. *Journal of Memory and Language*, *83*, 62–78.
https://doi.org/10.1016/j.jml.2015.04.004

Brady, T. F., & Oliva, A. (2008). Statistical Learning Using Real-World Scenes. *Psychological Science*,
19(7), 678–685. https://doi.org/10.1111/j.1467-9280.2008.02142.x

Conway, C. M. (2020). How does the brain learn environmental structure? Ten core principles for
understanding the neurocognitive mechanisms of statistical learning. *Neuroscience and*
Biobehavioral Reviews, *112*(January), 279–299.
https://doi.org/10.1016/j.neubiorev.2020.01.032

Conway, C. M., & Christiansen, M. H. (2005). Modality-constrained statistical learning of tactile,
visual, and auditory sequences. *Journal of Experimental Psychology. Learning, Memory, and*
Cognition, *31*(1), 24–39. https://doi.org/10.1037/0278-7393.31.1.24

Conway, C. M., & Christiansen, M. H. (2006). Statistical Learning Within and Across Modalities：
Abstract versus Stimulus-Specific Representations. *Psychological Science*, *17*(10), 905–912.

Cunillera, T., Càmara, E., Laine, M., & Rodríguez-Fornells, A. (2010). Speech segmentation is
facilitated by visual cues. *Quarterly Journal of Experimental Psychology*, *63*(2), 260–274.
https://doi.org/10.1080/17470210902888809

Cunillera, T., Laine, M., Càmara, E., & Rodríguez-Fornells, A. (2010). Bridging the gap between speech
segmentation and word-to-world mappings: Evidence from an audiovisual statistical learning
task. *Journal of Memory and Language*, *63*(3), 295–305.
https://doi.org/10.1016/j.jml.2010.05.003

Fiser, J., & Aslin, R. N. (2001). Unsupervised statistical learning of higher-order spatial structures
from visual scenes. *Psychological Science*, *12*(6), 499–504. https://doi.org/10.1111/1467-
9280.00392

Forscher, P. S., Lai, C. K., Axt, J. R., Ebersole, C. R., Herman, M., Devine, P. G., & Nosek, B. A. (2019). A
meta-analysis of procedures to change implicit measures. *Journal of Personality and Social*
Psychology, *117*(3), 522–559. https://doi.org/10.1037/pspa0000160

Frost, R., Armstrong, B. C., Siegelman, N., & Christiansen, M. H. (2015). Domain generality versus
modality specificity: The paradox of statistical learning. *Trends in Cognitive Sciences*, *19*(3),
117–125. https://doi.org/10.1016/j.tics.2014.12.010

Glicksohn, A., & Cohen, A. (2013). The role of cross-modal associations in statistical learning.
Psychonomic Bulletin & Review, *20*(6), 1161–1169. https://doi.org/10.3758/s13423-013-0458-4

Gondan, M., Lange, K., Rösler, F., & Röder, B. (2004). The redundant target effect is affected by
modality switch costs. *Psychonomic Bulletin and Review*, *11*(2), 307–313.
https://doi.org/10.3758/BF03196575

Henin, S., Turk-Browne, N. B., Friedman, D., Liu, A., Dugan, P., Flinker, A., Doyle, W., Devinsky, O., &
Melloni, L. (2021). Learning hierarchical sequence representations across human cortex and
hippocampus. *Science Advances*, *7*(8). https://doi.org/10.1126/sciadv.abc4530

Hochstein, S., & Ahissar, M. (2002). View from the Top: Review Hierarchies and Reverse
Hierarchiesin the Visual System. *Neuron*, *36*(5), 791–804. https://doi.org/10.1016/S0896-
6273(02)01091-7

Kok, P., Jehee, J. F. M., Lange, F. P. De, & de Lange, F. P. (2012). Less is more: expectation sharpens
representations in the primary visual cortex. *Neuron*, *75*(2), 265–270.
https://doi.org/10.1016/j.neuron.2012.04.034

Li, X., Zhao, X., Shi, W., Lu, Y., & Conway, C. M. (2018). Lack of cross-modal effects in dual-modality
implicit statistical learning. *Frontiers in Psychology*, *9*(FEB), 1–10.
https://doi.org/10.3389/fpsyg.2018.00146

López-Barroso, D., Cucurell, D., Rodríguez-Fornells, A., & de Diego-Balaguer, R. (2016). Attentional
effects on rule extraction and consolidation from speech. *Cognition*, *152*, 61–69.
https://doi.org/10.1016/j.cognition.2016.03.016

Mitchel, A. D., & Weiss, D. J. (2011). Learning across senses: Cross-modal effects in multisensory
statistical learning. *Journal of Experimental Psychology. Learning, Memory, and Cognition*,
37(5), 1081–1091. https://doi.org/10.1037/a0023700

Orpella, J., Mas-Herrero, E., Ripollés, P., Marco-Pallarés, J., & de Diego-Balaguer, R. (2021). Language
statistical learning responds to reinforcement learning principles rooted in the striatum. *PLOS*
Biology, *19*(9), e3001119. https://doi.org/10.1371/journal.pbio.3001119

Otto, T. U., & Mamassian, P. (2010). Divided Attention and Sensory Integration: The Return of the
Race Model . *Journal of Vision* , *10*(7), 863.
http://www.journalofvision.org/content/10/7/863.abstract

Otto, T. U., & Mamassian, P. (2012). Noise and Correlations in Parallel Perceptual Decision Making.
Current Biology : CB, 1–6. https://doi.org/10.1016/j.cub.2012.05.031

Pérez-Bellido, A. (2024). Predictable Modality Transitions and Amodal Representations Enable
Crossmodal Statistical Learning. https://doi.org/10.17605/OSF.IO/TCXE9

Perruchet, P., & Pacton, S. (2006). Implicit learning and statistical learning: one phenomenon, two
approaches. *Trends in Cognitive Sciences*, *10*(5), 233–238.
https://doi.org/10.1016/j.tics.2006.03.006

Reber, P. J. (2013). The neural basis of implicit learning and memory: A review of neuropsychological
and neuroimaging research. *Neuropsychologia*, *51*(10), 2026–2042.
https://doi.org/10.1016/j.neuropsychologia.2013.06.019

Redington, M., & Chater, N. (1996). Transfer in Artificial Grammar Learning: A Reevaluation. *Journal
of Experimental Psychology: General*, *125*(2), 123–138. https://doi.org/10.1037/0096-
3445.125.2.123

Richter, D., & de Lange, F. P. (2019). Statistical learning attenuates visual activity only for attended
stimuli. *ELife*, *8*, 1–27. https://doi.org/10.7554/eLife.47869

Richter, D., Ekman, M., & de Lange, F. P. (2018). Suppressed sensory response to predictable object
stimuli throughout the ventral visual stream. *Journal of Neuroscience*, *38*(34), 7452–7461.
https://doi.org/10.1523/JNEUROSCI.3421-17.2018

Sabio-Albert, M., Fuentemilla, L., & Pérez-Bellido, A. (2025). Anticipating multisensory environments:
Evidence for a supra-modal predictive system. *Cognition*, *254*, 105970.
https://doi.org/10.1016/j.cognition.2024.105970

Saffran, J. R., Aslin, R. N., & Newport, E. L. (1996). Statistical learning by 8-month-old infants. In
Science (New York, N.Y.) (Vol. 274, Issue 5294, pp. 1926–1928).
https://doi.org/10.1126/science.274.5294.1926

Saffran, J. R., Johnson, E. K., Aslin, R. N., & Newport, E. L. (1999). Statistical learning of tone
sequences by human infants and adults. *Cognition*, *70*(1), 27–52.
https://doi.org/10.1016/S0010-0277(98)00075-4

Seitz, A. R., Kim, R., Van Wassenhove, V., & Shams, L. (2007). Simultaneous and independent
acquisition of multisensory and unisensory associations. *Perception*, *36*(10), 1445–1453.
https://doi.org/10.1068/p5843

Shaw, L. H., Freedman, E. G., Crosse, M. J., Nicholas, E., Chen, A. M., Braiman, M. S., Molholm, S., &
Foxe, J. J. (2020). Operating in a Multisensory Context: Assessing the Interplay Between
Multisensory Reaction Time Facilitation and Inter-sensory Task-switching Effects. *Neuroscience*,
436, 122–135. https://doi.org/10.1016/j.neuroscience.2020.04.013

Siegelman, N., Bogaerts, L., Kronenfeld, O., & Frost, R. (2017). Redefining "Learning" in Statistical
Learning: What Does an Online Measure Reveal About the Assimilation of Visual Regularities?
Cognitive Science, 1–36. https://doi.org/10.1111/cogs.12556

Siegelman, N., & Frost, R. (2015). Statistical learning as an individual ability: Theoretical perspectives
and empirical evidence. *Journal of Memory and Language*, *81*, 105–120.
https://doi.org/10.1016/j.jml.2015.02.001

Spence, C., Nicholls, M. E. R., & Driver, J. (2001). The cost of expecting events in the wrong sensory
modality. *Perception and Psychophysics*, *63*(2), 330–336. https://doi.org/10.3758/BF03194473

Spotworks, S., & Berthoud, E. (2008). The Fractal Flame Algorithm. *Http://Citeseerx. Ist. Psu.
Edu/Viewdoc/Summary.*

Talsma, D., Senkowski, D., Soto-Faraco, S., & Woldorff, M. G. (2010). The multifaceted interplay
between attention and multisensory integration. *Trends in Cognitive Sciences, 14*(9), 400–410.
https://doi.org/10.1016/j.tics.2010.06.008

Thiessen, E. D. (2010). Effects of Visual Information on Adults' and Infants' Auditory Statistical
Learning. *Cognitive Science, 34*(6), 1093–1106. https://doi.org/10.1111/j.1551-
6709.2010.01118.x

Toro, J. M., Sinnett, S., & Soto-faraco, S. (2005). *Speech segmentation by statistical learning depends*
on attention. 97, 25–34. https://doi.org/10.1016/j.cognition.2005.01.006

Treisman, a M., & Gelade, G. (1980). A feature-integration theory of attention. *Cognitive Psychology,*
12(1), 97–136. http://www.ncbi.nlm.nih.gov/pubmed/7351125

Walk, A. M., & Conway, C. M. (2016). Cross-Domain Statistical–Sequential Dependencies Are Difficult
to Learn. *Frontiers in Psychology, 7*(February), 1–9. https://doi.org/10.3389/fpsyg.2016.00250

Whelan, R. (2008). Effective analysis of reaction time data. *The Psychological Record, 58*, 475–482.

Yan, C., de Lange, F. P., & Richter, D. (2023). Conceptual Associations Generate Sensory Predictions.
Journal of Neuroscience, 43(20), 3733–3742. https://doi.org/10.1523/JNEUROSCI.1874-22.2023

Yan, C., Pérez-Bellido, A., & de Lange, F. P. (2021). Amodal completion instead of predictive coding
can explain activity suppression of early visual cortex during illusory shape perception. *Journal*
of Vision, 21(5), 13. https://doi.org/10.1167/jov.21.5.13

Zhou, Y. J., Pérez-Bellido, A., Haegens, S., & de Lange, F. P. (2019). Perceptual expectations modulate
low-frequency activity: A statistical learning magnetoencephalography study. *Journal of*
Cognitive Neuroscience, 32(4), 691–702. https://doi.org/10.1162/jocn_a_01511

858