Title

SonicParanoid2: fast, accurate, and comprehensive orthology inference with machine learning

and language models

Authors: Salvatore Cosentino[1] and Wataru Iwasaki[1-6]

Affiliations:

1. Department of Integrated Biosciences, Graduate School of Frontier Sciences, the University

of Tokyo, Kashiwa, Japan

2. Department of Biological Sciences, Graduate School of Science, the University of Tokyo,

Bunkyo-ku, Japan

3. Department of Computational Biology and Medical Sciences, Graduate School of Frontier

Sciences, the University of Tokyo, Kashiwa, Japan

4. Atmosphere and Ocean Research Institute, the University of Tokyo, Kashiwa, Japan

5. Institute for Quantitative Biosciences, the University of Tokyo, Bunkyo-ku, Japan

6. Collaborative Research Institute for Innovative Microbiology, the University of Tokyo, Bunkyo-

ku, Japan

Contact

Salvatore Cosentino (salvocos@k.u-tokyo.ac.jp)

Wataru Iwasaki (iwasaki@k.u-tokyo.ac.jp)

Abstract

The accurate inference of orthologous genes is a prerequisite for various genomic and

evolutionary studies. SonicParanoid is one of the fastest tools for orthology inference. However,

its scalability and sensitivity are hampered by time-consuming all-versus-all alignments and

proteins with complex domain architectures, respectively. Herein, we report an update to

SonicParanoid, which involves the use of machine learning to overcome the abovementioned

two limitations. An AdaBoost classifier is used, which reduced the execution time of the all-

versus-all alignment by up to 42% without degrading the accuracy. The Doc2Vec neural

network model enables orthology inference at the domain level and increases the number of

predicted orthologs by one-third, compared to graph-based orthology alone. Evaluation on

standardized benchmark datasets and a 2,000 MAG dataset indicate that SonicParanoid2 is up

to 18 times faster and more scalable than other orthology inference tools, and is as accurate as

well-established methods.

Introduction

The accurate inference of orthologous genes originating from speciation events is crucial in various areas of genomics and evolutionary biology[1]. Many tools and resources have been developed to identify orthologous relationships among multiple proteomes. They are classified into graph[2–6] and tree based[7–9], which do not include tools that integrate both approaches[10] (hybrid) or integrate publicly available resources to perform their predictions[11]. Graph-based tools infer orthologs by calculating all-versus-all pairwise similarity scores and using the bidirectional-best-hit (BBH) method or its derivatives[12,13]. In tree-based methods, orthologs are identified by analyzing phylogenetic trees, which allows the identification of speciation and duplication events. Tree-based tools are more computationally demanding and are typically available to users only via databases or web services. A comparative study showed no significant differences in the ability of the two approaches in inferring orthologs[13].

The steep decrease in sequencing costs and the associated increase in genomic and metagenomic data[14] challenge the scalability of orthology inference tools. Inferring orthologs *de novo* for a few hundred proteomes using graph-based methods on high-performance computing servers may require days to weeks, even when local alignment tools, such as MMseqs2[15] and Diamond[16], are used as faster alternatives to BLAST[17].

In addition to the scalability problem, graph-based methods tend to miss orthologs in duplication-rich proteomes[18] (e.g., plant proteomes) and in proteins with complex domain arrangements (architectures) originating from fusion and fission events[19,20]. For example, BBH-based methods fail to identify human kinase orthologs detected using a domain-based orthology inference method[21].

Machine learning (ML), particularly methods borrowed from natural language processing (NLP), has been extensively used in genomics[22]. Currently, deep learning and language models are used in multiple areas of genomics[23], including sequence assembly and binning[24,25] as well as protein folding[26,27]. ML is gradually being adopted for orthology inference[28,29]; however, the sensitivity, scalability, and usability of ML-based methods can be further improved.

Herein, we report a major update to SonicParanoid[30], which is one of the fastest *de novo* orthology inference tools[29,31]. The update uses two ML methods, AdaBoost[32] and Doc2Vec[33], to deliver a substantially faster and more comprehensive orthology inference.

Results and Discussion

Overview of SonicParanoid2 and comparison to other methods

For a set of *N* proteomes, SonicParanoid2 performs *de novo* orthology inference using a novel graph-based algorithm that halves the execution time with an AdaBoost classifier and avoiding

unnecessary alignments (Figure 1a). Furthermore, for a more comprehensive identification of

orthologs, SonicParanoid2 conducts domain-based orthology inference using Doc2Vec neural

network models (Figure 1b). The orthologs predicted by these two algorithms are merged

(Figure 1c) and input into the Markov cluster algorithm[34] (MCL) to infer the ortholog groups[2]

(OGs) for the N input proteomes. SonicParanoid2 can be executed using three predefined

modes (fast, default, and sensitive), in which different local alignment tools and settings are

used (Supplementary Table S1).

The effect of domain-based orthology on the number of predicted orthologs and the total

execution time differs depending on the input dataset and settings for SonicParanoid2. For

example, on a dataset provided by the Quest for Orthologs[35,36] (QfO)(Supplementary Figure

S1a), the number of predicted orthologs increased by one-third at the default settings, and the

total execution time showed a similar increase (29.17% (10.70')) (Table 1). The increase in the

total execution time becomes relatively negligible for larger datasets and at higher sensitivity

settings because of the high scalability of the domain-based pipeline (Supplementary Figure

S2). For example, on a dataset with 2,000 metagenome-assembled genomes (MAGs)

(Supplementary Figure S1b), the increase in execution time was 10% and 24% for the default

and fast modes, respectively, whereas one-third more orthologs were predicted regardless of

the settings (Table 2).

We compared the execution time of SonicParanoid2 with that of OrthoFinder[10] and Broccoli[29],

which are among the fastest tools available for *de novo* orthology inference[31]. Broccoli reduces

the burden of all-versus-all alignments through *k*-mer clustering and uses label propagation

instead of the typically used MCL to infer OGs. Multiple studies demonstrated that these three

tools are equally accurate for inferring OGs[31,37,38].

On the QfO dataset, SonicParanoid2 was 18X and 5X faster than OrthoFinder and Broccoli,

respectively, in the fast mode (Table 1). At the default settings, SonicParanoid2 was 12X and

3X faster, respectively. In the sensitive mode, SonicParanoid2 was approximately 1.5X slower

than Broccoli. At these settings, MMseqs2 at the highest sensitivity was used (Supplementary

Table S1), whereas Broccoli and OrthoFinder used Diamond which is faster. Orthologous

relationships for the MAG dataset were inferred by SonicParanoid2 in 1.6 and 1 day in the

default and fast modes, respectively (Table 2). Conversely, OrthoFinder and Broccoli failed to

complete the orthology inference on the MAG dataset within eight days (i.e., more than 8X

longer than SonicParanoid2).

The accuracy of SonicParanoid2 was evaluated using the QfO benchmark[36] and compared with

14 well-established methods, including a legacy version of SonicParanoid[30]. In 12 tests

performed, methods close to or constituting the Pareto frontier were regarded as those that

provided the best tradeoff between precision and recall. SonicParanoid2 was Pareto optimal in

multiple tests, including the LUCA and bacterial species tree discordance tests (Figure 2 and

Supplementary Figures S3 and S4).

Substantially faster and scalable graph-based orthology inference using ML

Graph-based *de novo* orthology inference for *N* proteomes generally requires *N* intra-proteome

and *N(N-1)* bidirectional inter-proteome all-versus-all alignments. For the bidirectional inter-

proteome alignment of proteomes A and B, all proteins in A are queried against proteome B

(denoted as alignment A-B), and all proteins in B are queried against proteome A (B-A). The key

rationale behind the way in which SonicParanoid2 reduces the computational cost are: (1) The

execution times of alignments A-B and B-A can substantially differ depending on the proteome

size and evolutionary distance between A and B (Supplementary Figs. S5 and S6), and (2)

query and target proteins that have no hits with bitscores above a predefined threshold in one of

the two inter-proteome alignments cannot be predicted as orthologs, based on the definition of

BBH (Equation 1). Accordingly, for a pair of proteomes A and B, SonicParanoid2 first predicts

the faster alignment between A-B and B-A using an adaptive gradient boosting[32] (AdaBoost)

binary classifier (Supplementary Table S2). If A-B is predicted to be faster, then SonicParanoid2

first conducts the alignment A-B and creates two subsets, ess(A) and ess(B), which include only

proteins with alignment scores above the threshold (Equation 2). Subsequently, the alignment

between ess(B) and ess(A) is performed instead of the expectedly slower alignment of B-A

(Supplementary Fig. S7). Finally, the algorithm identifies the orthologs as shown in Equation 3.

Henceforth, we will refer to the subsets of proteins generated by this graph-based algorithm as

"essential subsets" and to the all-versus-all among these subsets as "essential alignments".

We evaluated the execution time of the novel graph-based algorithm in SonicParanoid2 (Figure

1a) on the two proteome sets shown in Supplementary Figure S1 using different alignment tools

and sensitivity settings (Supplementary Table S3). For the QfO dataset, the execution time for

the all-versus-all alignments was reduced by 42% (Supplementary Table S4). Moreover, when

only inter-proteome alignments were considered, the reduction in execution time was as high as

95% (Figure 3). A speedup was observed regardless of the alignment tool used (MMseqs2,

Diamond, or BLAST). Nevertheless, the extent depended on both the alignment tool used and

its sensitivity settings (Supplementary Table S4). Specifically, the proportions of sequences

used in the second alignment were smaller for the proteome pairs of phylogenetically distant

species (Supplementary Figure S8), thus resulting in higher speedups. For example, 97% of the

input proteins was not used in the second alignment between *Leptospira interrogans* (bacteria)

and *Giardia intestinalis* (protist), which consequently reduced the execution time substantially.

Conversely, less than 2% of the original input was removed for the second alignment between

closely related chimpanzee and gorilla proteomes.

144 The accuracy of the AdaBoost classifier differed depending on the alignment tool for which it
145 inferred faster alignments, partly because it was trained for MMseqs2 (Supplementary Table
146 S4). The necessity of the AdaBoost model was assessed by measuring the reduction in
147 execution time when the slowest alignments were conducted first. This task was performed by
148 inverting the predictions of the AdaBoost classifier. For example, when the classifier predicted
149 A-B as the fastest alignment, we first aligned B-A. We observed that the amount of saved time
150 was up to 70% less, which proved the importance of predicting the fastest inter-proteome
151 alignments (Supplementary Table S5).
152 To evaluate the scalability of the graph-based algorithm of SonicParanoid2, we performed
153 orthology inference on a large dataset comprising 2,000 MAGs from aquatic and terrestrial
154 environments (Supplementary Figure S1b). The required four million all-versus-all alignments
155 were performed in 56.48 and 23.74 hours using MMseqs2 and Diamond, respectively, which
156 corresponded to execution times reduced by 16.18% and 24.99%, respectively (Supplementary
157 Table S6). The MAG dataset contained many closely related microbial genomes, and the
158 closely related proteomes therein limited the reduction in execution time (Supplementary
159 Figures S9 and S8).
160

161 **Speed and accuracy of AdaBoost-enhanced graph-based method**
162 We compared the execution times of the AdaBoost-enhanced graph-based algorithm (Figure
163 1a) with those of Broccoli and OrthoFinder. In particular, we compared the execution times for
164 the alignment-based orthology inference alone; hence, SonicParanoid2 was set to omit the
165 domain-based orthology. SonicParanoid2 executed in the fast mode using Diamond
166 (Supplementary Table S3) completed the execution in 0.38 hours for the 78-proteome QfO
167 dataset, whereas OrthoFinder and Broccoli required 10.19 and 2.77 hours (7.3 and 26.9-folds
168 slower), respectively (Supplementary Table S7). Subsequently, we tested OrthoFinder and
169 Broccoli on the 2,000-proteome MAG dataset; however, both tools failed to complete the
170 orthology inference within eight days, whereas SonicParanoid2 required one day
171 (Supplementary Table S6).
172 To compare the AdaBoost-enhanced method with the conventional graph-based approach,
173 which uses all the input sequences, we evaluated the prediction sets of 18 trials (Supplementary
174 Table S4) using the QfO benchmark. The accuracies of the two graph-based approaches were
175 highly similar, with no apparent adverse effect on the accuracy despite the substantial reduction
176 in computational time (Supplementary Figures S10 and S11).
177

178 **Fast and scalable domain-based orthology inference using Doc2Vec**
179 The graph-based approach based on BBH can miss orthologs of proteins with many

duplications or those that have undergone domain fusion or fission[18,20,21] (Figure 4a and

Supplementary Figure S12). Thus, in addition to the orthologs predicted using the graph-based

approach, SonicParanoid2 infers orthologs at the domain level by comparing functional domain

architectures using techniques typically used in natural language processing (Figures 1b and

4b).

SonicParanoid2 uses fast profile searches on Pfam[39] to infer the domain architectures of the

input proteins and converts them into "phrases", where "words" are the annotated functional

domains and the amino-acid lengths of the inter-domain regions (Figure 1b). The phrases are

used as the training corpus for a Doc2Vec[33] neural network model, that associates a numerical

vector with each domain architecture. For each inter-proteome pair, after a filtering step, the

cosine similarities of the inter-proteome domain architecture pairs are computed. Pairs of

architectures with cosine similarities above a predefined threshold are considered candidate

orthologs.

The increase in total execution time due to the inclusion of the domain-based pipeline was

negligible, considering the increase in the number of predicted orthologs (Table 1). Due to the

high scalability of the domain-based pipeline (Supplementary Figure S2), the aforementioned

smallness of the increase in execution time was more apparent when processing larger

datasets. For example, for the MAG dataset, the increase in execution time was 10% and 24%

for the default and fast modes, respectively, whereas the increase in the number of predicted

orthologs was higher than one-third, regardless of the settings (Table 2).

The inclusion of the domain-based pipeline substantially increased the recall. For example, in

the bacterial species tree discordance test, it doubled in some settings (Supplementary Figures

S13 and S14).

The recovery of eukaryotic uridine–cytidine kinases are examples of orthologous relationships

recovered using domain-based orthology inference. Previous studies showed that the fusion of

prokaryotic phosphoribulokinase/uridine kinase and uracil phosphoribosyltransferase domains

(P0A8F4 and P0A8F0) resulted in the emergence of this enzyme in human[20] (UniProt ID

Q9NWZ5). Whereas the graph-based method of SonicParanoid2 identified P0A8F4 only as an

ortholog of Q9NWZ5, the domain-based method identified P0A8F0 as well. Additionally, the

domain-based method predicted P0A8F0 to be an ortholog of other 17 eukaryotic uridine–

cytidine kinases in 12 eukaryotic species in the QfO dataset (Supplementary Table S8).

Conclusion

Fast, accurate, and comprehensive identification of orthologous genes is becoming increasingly

important in genomic and evolutionary studies owing to the steady growth of publicly available

genomic data[14]. Nevertheless, existing *de novo* orthology inference tools require long execution

times because of the necessary all-versus-all alignments and cannot effectively detect orthologs
of proteins with complex domain architectures or those that have undergone gene fusion or
fission events[20,21].
SonicParanoid2 solves the two abovementioned problems using ML and is faster and more
accurate than existing tools. The novel graph-based algorithm almost halves the execution time
by avoiding unnecessary homology searches and does not degrade the accuracy. The domain-
aware algorithm increased the number of predicted orthologs by one-third with minimal costs for
the total execution time. Evaluation based on standardized benchmarks showed that the
accuracy of SonicParanoid2 is comparable to those of well-established orthology-inference
methods.
Considering the way SonicParanoid2 uses language models to infer orthologs, and their recent
applications in bioinformatics (e.g., ProtVec[40], SeqVec[41] and ESMFold[27]), we expect accurate
alignment-free orthology inference tools to be realized in the near future, which will result in
significant advancements in comparative and evolutionary biology.
230
231 **Material and Methods**
232
Test datasets and accuracy benchmark
The execution times of SonicParanoid2, Broccoli, and OrthoFinder were evaluated using the
2020 version of a benchmark dataset provided by the QfO consortium[36]. This dataset contains
78 proteomes (Supplementary Figure S1a). Because it includes both closely and distantly
related species, it provides a good example on the manner by which evolutionary relatedness
affects the AdaBoost-enhanced graph-based algorithm in SonicParanoid2 (Supplementary
Figure S8).
The scalability of SonicParanoid2 was evaluated on a dataset comprising 2,000 microbial MAGs
from terrestrial and aquatic environments (Supplementary Figure S1b), which were randomly
selected from a public catalogue of 52,515 MAGs[42]. The MAGs in the dataset satisfied or
exceeded the medium quality level of the minimum information about metagenome-assembled
genome (MIMAG) standard[43] and contained 5.1 million proteins. The final dataset contained
1,786 pairs of MAGs (involving 931 MAGs) with an average amino acid similarity (AAI)
exceeding 99%, suggesting that for approximately a quarter of the MAGs there is another MAG
which is almost identical. Although we processed these MAGs, we recommend removing highly
similar proteomes from the input dataset to avoid bias in the orthology inference.
To evaluate the accuracy of SonicParanoid2, the orthologs predicted for the QfO dataset were
uploaded to a benchmark service provided by the QfO. The benchmark provides 12 tests[36]: two
are based on reference gene trees, two use functional information, one is based on manually

curated sets of orthologous relationships among mammals, and seven assess the validity of

predictions in terms of the accuracy of the species trees that can be reconstructed from them. In

most of the tests, small subsets of the uploaded predictions were used, except for the LUCA

generalized species tree discordance test, which evaluated all predictions.

The accuracy of SonicParanoid2 was compared with those of other 14 methods, the results of

which are publicly available on the benchmark web page (as of February 2023). Benchmark

results for Broccoli are not available; furthermore, because only the developers of each tool can

render the benchmark results publicly available on OpenEbench[44], the accuracy of Broccoli is

not discussed herein.

Software, databases, and settings

To perform a comparison of the execution times on the QfO 2020 and the MAG datasets, we

used SonicParanoid 2.0.0 (commit 6698944d), Broccoli 1.2 (commit 032064c), and OrthoFinder

2.5.4 (commit 93e0e20). For the results regarding only graph-based orthology inference,

SonicParanoid2 was executed with the option "skip-arch-orthologs" to omit domain-based

predictions and sensitivity settings, as shown in Supplementary Table S1. OrthoFinder was

executed with additional parameters, i.e., "msa" and "ot". The former instructs OrthoFinder to

use MAFFT[45] (v7.490) to compute multiple sequence alignments, whereas the latter terminates

execution after the creation of HOGs[46], thus avoiding the computation of the final species tree.

Broccoli was executed at the default settings.

To evaluate the AdaBoost-enhanced graph-based method, SonciParanoid2 was executed using

the settings described in Supplementary Table S3, which were used in older versions of

SonicParanoid (up to v1.3.8).

OrthoFinder and Broccoli were implemented in the Python3 programming language, whereas

SonicParanoid2 was implemented in Python3 and Cython[47] (v3.0.0a10). All tests were

performed using Python 3.8.10. The execution times of SonicParanoid2, Broccoli, and

OrthoFinder were computed using the *Perf_counter* function in Python.

The alignment tools used in this study were MMseqs2[15] (13-45111), Diamond[16] 2.0.12, and

BLAST[17] 2.12.0. Supplementary Table S3 shows the mapping of the sensitivity of the alignment

tools to the sensitivity settings of the tested orthology inference tools.

The average AAIs of proteome pairs in the QfO and MAGs datasets were computed using

CompareM 0.1.2 (https://github.com/dparks1134/CompareM).

The profile database for Pfam[39] (version 35) was retrieved using the command *databases* in

MMseqs2 with "Pfam-A.seed" as a parameter and indexed using the *createindex* command with

parameters "-k = 5" and "-s = 7".

The Doc2Vec model was trained using the Gensim[48] (ver. 4.2) library for Python3.

Graph-based orthology inference

The workflow of graph-based orthology inference (Figure 1a) for N input proteomes is shown in
Supplementary Figure S7. The first step involves predicting the $N(N-1)/2$ fastest inter-proteome
alignments using the AdaBoost binary classifier. Next, local alignments of the proteome pairs
predicted to have the shortest execution time are performed using all input proteomes. For each
of these alignments, let us assume A-B, the hits are processed to create two essential subsets
(*ess(A)* and *ess(B)*) of the original proteomes using the conditions shown in Equation 2. These
subsets are used for the remaining $N(N-1)/2$ inter-proteome alignments. N intra-proteome
alignments are performed in parallel using complete proteome sets.
Once all local alignments are completed, their outputs are processed, and the graph-based
ortholog relations are inferred using Equation 3 and clustered as in the original SonicParanoid[30].
300

AdaBoost training and optimization

The AdaBoost[32] binary classifier was built using 62,250 training samples containing properties
extracted from 250 reference proteomes (Supplementary Figure S15) and labeled using the
execution times of inter-proteome alignments performed using MMseqs2 at the highest
sensitivity. Given N input proteomes, for each of the $N(N-1)$ inter-proteome alignments, we
created a training sample with properties such as protein count, proteome size, and average
protein length. Additionally, we included the differences in proteome size and protein count,
expressed in folds, by assuming that the query proteome (leftmost in the pair) was smaller and
had fewer proteins than the target proteome. Each sample was labeled based on the execution
times of the two inter-proteome alignments of the proteome pair (Supplementary Table S2). As
an example, for a sample representing A-B, if the execution time for its alignment is shorter than
that of the other alignment (B-A), then its label is set to 1 (faster); otherwise, it is set to 0
(slower).
We selected the features in Supplementary Table S2 because, for two proteomes (A and B)
with substantially different compositions, the execution times for the inter-proteome alignments
can differ significantly. More specifically, if proteome A contains much fewer sequences (or
amino acid bases) than proteome B, then the time required to align A-B may be much shorter
than that to align B-A. Furthermore, because the difference in execution time was directly
proportional to the difference in the composition of the proteomes, regardless of the alignment
tool used (Supplementary Figures S5 and S6); this information was used as the training feature
of the AdaBoost classifier. Finally, because this information is computed and used at each
execution by SonicParanoid2, regardless of the binary classifier, the creation of samples to
predict the fastest alignments has virtually no overhead.

Based on the accuracies of the model on Diamond and MMseqs2 (Supplementary Table S4) as
well as considering the estimated execution time for labeling the training samples using BLAST
(which is likely more than two months), we decided to use only the model trained on samples
labeled using MMseqs2.
The training, validation, and optimization of the model were conducted using AdaBoost libraries
in Scikit-learn[49]. Hyperparameter optimization was performed using a grid search, where the
best performing model achieved a mean test accuracy of 97.90 in a 10-fold cross validation. For
the independent QfO test dataset, the maximum accuracy achieved by the model was 96.70%
(Supplementary Table S4).
333
Construction of domain architectures and training corpus for Doc2Vec
Examples of architecture estimation and document creation for a single protein are depicted in
Supplementary Figure S16. Hereinafter, we will use the terms "document" and "architecture"
interchangeably, and similarly for "word" and "annotated/unannotated domains". The first step in
estimating the architectures involves searching for input proteins in a Pfam profile database
using MMseqs2. The hits are filtered to obtain a bit score and target coverage of at least 30 and
75%, respectively. For queries with multiple domains, the architectures are composed of non-
overlapping domains and inter-regions for which no annotation was identified (uncovered
regions). The elements of the architectures are converted into words, and the architectures into
phrases (documents). In the documents, annotated domains are represented by their Pfam
annotations, and uncovered regions (longer than four amino acid) by their lengths
(Supplementary Figure S16). A document constitutes the training corpus if it has a protein
coverage (the proportion of the protein sequence annotated with domains) of at least 70% and
is not repeated in the corpus.
348
Doc2Vec model training
Doc2Vec (also known as Paragraph2Vec) is an extension of Word2Vec[50] that represents a
document as a numerical vector[33]. It uses Word2Vec to generate embeddings of single words;
therefore, the embeddings can be learned through a continuous bag-of-words or skip-gram
algorithm. In Doc2Vec, an algorithm that is similar to skip-gram is known as the "distributed bag-
of-words of the paragraph vector", and is used to train the Doc2Vec models in SonicParanoid2.
The context window value for the skip-gram was set to two, the number of dimensions (vector
size) was set to 100, and training was performed for 200 epochs. Although these parameter
settings are typically used in studies pertaining to NLP[51], we set the minimum word frequency to
one. This parameter controls the minimum number of times a certain word must appear in the
corpus in order to be used for training. Because NLP models are typically trained on billions of

documents[22], this parameter is often set to values equal to or higher than five to reduce the

training time and memory usage. Nevertheless, in our case, the training sets were relatively

small, where 134,520 and 567,119 documents were obtained for the QfO and MAG datasets,

respectively. Hence, we set the minimum word frequency to one, allowing the neural networks

of the Doc2Vec model to be trained using all documents in the corpus.

Architecture prefiltering and creation of domain-based ortholog clusters

Given proteomes A and B with l and m architectures, respectively, l x m pairs of architectures

exist. Accordingly, computing the cosine similarities for all the possible pairs of architectures for

the $N(N-1)/2$ combinations of input proteomes will be extremely computationally demanding. To

reduce the execution time, SonicParanoid2 performs prefiltering, in which pairs of architectures

that are unlikely to be orthologous are rejected before their cosine similarities are computed.

Filtering is performed by comparing features of the architectures, including the protein length,

protein coverage, and number of annotated domains (Supplementary Figure S16c).

A pair of architectures is rejected if one of the following conditions applies:

1) The protein length of one architecture exceed 3X the length of the other.

2) Their protein coverages differ by more than 25%.

3) One of the two architectures has more than double the domains of the other.

4) The two architectures have no mutual domains.

After prefiltering, the cosine similarities between the remaining pairs of architectures are

computed, and cosine similarity values of at least 0.5 populate a matrix M of dimension l x m.

The domain-based algorithm generates clusters of orthologs by selecting the maximum cosine

similarities in M for proteins from A (row-wise) and B (column-wise) proteomes (Supplementary

Figure S17).

Merging of pairwise orthologs and inference of OGs

The pipelines depicted in Figures 1a and 1b infer pairwise orthologous relationships using the

graph- and domain-based algorithms, respectively. SonicParanoid2 combines these orthologs

to generate ortholog graphs, which are subsequently used to infer OGs (Figure 1c). Because we

regarded graph-based predictions as more accurate, we integrated domain-based predictions

into them.

Let G and D be sets of ortholog clusters for proteomes A and B generated by the graph- and

domain-based algorithms, respectively. Let g ∈ G and d ∈ D be clusters of pairwise ortholog

relationships. When merging the two sets of predicted orthologs, we considered the following

three cases:

1) d is a completely new cluster with no proteins contained in any cluster in G.

2) All proteins in d are already predicted as orthologs in other clusters in G.

3) Some proteins in d are not in any cluster in G, and some proteins in g are not in any d ∈

D.

In Case 1, the architecture of each ortholog in d must have a protein coverage of at least 75%;

otherwise, it is rejected. Additionally, if even a single pair of architectures has a different number

of annotated domains, cluster d is rejected completely; cluster d is added as a new cluster in G

if none of the aforementioned applies.

In case 2, we prioritized graph-based predictions and use the clusters in G, which already

contain the orthologs in d, without any modifications.

Case 3 is the most complicated and involves scenarios in which some proteins in d are

contained in one or more clusters in G, whereas others are not. In this case, the orthologous

proteins from d with coverages higher than or equal to 75% are integrated into the existing G

clusters. One such example is the protein P0A8F4 (Figure 4b). For proteins A0A3B3HHD8,

P0A8F4, and P0A8F0, the graph-based cluster g ∈ G contains all proteins except P0A8F0.

Cluster d contains all three proteins; therefore, P0A8F0 (with 96.2% coverage) is inserted as a

new ortholog into the corresponding cluster in G.

Combined sets of pairwise orthologs are used to construct ortholog graphs, which are the input

to the MCL[34]. The output from the MCL is analyzed to extract the OGs, which is the final output

of the SonicParanoid2.

Hardware used

The results described herein were obtained using an Ubuntu 20.04.3 (Linux 5.11.0) HPC server,

which was equipped with a 128 cores AMD EPYC 7742 CPU, 2 terabytes of memory, and a 3.5

terabytes solid state disk.

Code availability and installation instructions

SonicParanoid2 is freely available with a GNU GPLv3 license in the Python Package Index and

GitLab. Its documentation is available at http://iwasakilab.k.u-tokyo.ac.jp/sonicparanoid.

Data availability

The benchmark results for SonicParanoid2 are publicly available at

https://orthology.benchmarkservice.org/proxy/results/2020. Data and programs used to train and

evaluate AdaBoost and Doc2Vec models are available at

https://gitlab.com/salvo981/sonic-manuscript.

Acknowledgements

We are grateful to the members of the QfO consortium and all the members of the Iwasaki

Laboratory for their helpful comments pertaining to this study.

Author contributions

S.C. designed the program and conducted the experiments. S.C. and W.I. designed the study

and wrote the manuscript.

Funding

This study was supported by JSPS KAKENHI (16H06279, 19H05688, and 22H04925), JST

CREST (JPMJCR19S2), and MEXT (JPMXD1521474594).

Competing interests: The authors declare no competing interests.

467 **Figures**

485 **Figure 1: Overview of SonicParanoid2. a**, Graph-based orthology inference pipeline using a
486 novel ML-based approach to substantially reduce execution time of homology searches; **b**,
487 Domain-based orthology inference pipeline that compares domain architectures using methods
488 from NLP; **c**, Pairwise orthologous tables predicted using the two pipelines combined to
489 generate ortholog graphs from which the output ortholog groups are inferred.

Figure 2: Accuracy of SonicParanoid2 compared with other 14 methods. Accuracies of SonicParanoid2 (SP2) using different settings on four among 12 QfO 2020 benchmark tests. Methods lying on Pareto frontier indicate the best balance between precision and recall. Results obtained using only the novel graph-based approach are shown (squares) for comparison with older versions of SonicParanoid (crosses). **a**, Species tree discordance tests on LUCA and bacteria datasets. **b**, Reference gene tree test based on TreeFam-A. **c**, Functional benchmark test based on Enzyme Commission (EC) numbers.

Figure 3: Speedup from essential alignments and evolutionary relatedness. For two proteomes A and B, the total execution time is computed as the sum of the execution times for the inter-proteome alignments A-B and B-A. The speedup (on the Y-axis) obtained for each bidirectional alignment was computed as the difference in total execution time required with and without using the essential alignments. The speedups obtained using the novel approach in SonicParanoid2 are inversely proportional to the evolutionary relatedness (expressed in terms of AAI) of the proteome pairs. The results above were obtained using the QfO dataset as input and MMseqs2 at the most sensitive settings.

Figure 4: Recovery of orthologs missed by BBH via domain-based orthology inference. a, Protein A0A3B3HHD8 from *O. latipes* is a representative example of domain fusion resulting from two single-domain *E. coli* proteins. Pink and green boxes in **a** are functional domains (annotated with their Pfam ID and gene name), whereas black boxes represent inter-regions with no Pfam annotation in InterPro (as of January 2023). P0A8F4 and P0A8F0 are orthologous to A0A3B3HHD8 (black arrows), but the graph-based pipeline identifies only P0A8F4 as an ortholog. **b**, Using domain-aware orthology, SonicParanoid2 predicts P0A8F0 as an ortholog of A0A3B3HHD8. Text inside the white boxes represent the architectures for the proteins above as they appear in the training corpus for the Doc2Vec model. The rounded rectangles in orange show the cosine similarities assigned to the two pairs of domain architectures.

639 **Figure S1:** Test datasets. **a**, Version 2020 of the benchmark dataset from the QfO consortium.
640 The dataset comprises 78 proteomes with an average size of 5.63 million AA. **b**, A set of 2,000
641 bacterial MAGs from terrestrial and aquatic environments randomly selected from a catalogue of
642 52,515 MAGs described by Nayfach *et al.* 2021.
643
644
645
646

Figure S2: Scalability of domain-based pipeline. Plots on the right and left refer to trials with QfO and MAG datasets as input, respectively. Multiple trials were performed using the domain-based pipeline with increasing numbers of input proteomes from both datasets (x-axis). Domain-based pipeline shows high scalability with a quasi-linear execution time growth as the number of input proteomes increases. **a**, Increase in execution time for profile searches and Doc2Vec model training. Total execution time for both steps was approximately 6 min for the complete QfO dataset and approximately 18 min (only 3X longer) for the 2,000 MAGs. **b**, Time required to train the Doc2Vec models increases linearly with the corpus size. **c**, Size of vocabulary (single words in the corpus) reaches a plateau when the input proteomes have similar contents (e.g. for the MAG dataset).

Figure S3: Accuracy of SonicParanoid2 with and without domain-based orthology. Methods shown by markers on the Pareto frontier demonstrate the best balance between precision and recall. Square markers represent accuracies obtained when using only the graph-based pipeline. Results of **a**, generalized species tree discordance tests and **b**, functional benchmark tests.

Figure S4: Accuracy of SonicParanoid2 with and without domain-based orthology. Methods shown by markers on Pareto frontier demonstrate the best balance between precision and recall. Square markers represent accuracies obtained when using only the graph-based pipeline. Results of **a**, reference-tree based tests, **b**, species tree discordance tests (eukaryota, fungi, bacteria), and **c**, Vertebrate Gene Nomenclature Committee (VGNC) test.

791　**Figure S5:** Execution time differences between complete inter-proteome alignments using
792　MMseqs2 at multiple settings. The execution time difference for a specified pair (e.g., A-B) is
793　computed as the absolute value of the execution times of the two inter-proteome alignments.
794　Each dot represents one of the 3,003 possible combinations for the QfO dataset.

Figure S6: Execution time differences between complete inter-proteome alignments using multiple local alignment tools. Y-axis shows execution time difference between inter-proteome alignments for each of the 3,003 possible combinations in the QfO proteome set, using (left to right) MMseqs2, Diamond, and BLAST at the default mode (as in Supplementary Table S3). As in Figure S5, the execution time difference is proportional to the difference in proteome size (top row) and inversely proportional to AAI (bottom row).

Figure S7: Flowchart of AdaBoost-enhanced graph-based method in SonicParanoid2. For each possible combination of *N* input proteomes, the fastest inter-proteome alignments are predicted using an AdaBoost binary classifier (left branch). After the fastest alignments are performed, they are processed and the essential protein sets are generated, as in Equation 2. The remaining inter-proteome alignments are performed on the reduced protein sets. The intra-proteome (right branch) and the predicted fastest inter-proteome alignments are performed using the complete input proteomes.

Figure S8: Percentage of input sequences used and evolutionary relatedness in graph-based

orthology inference (QfO 2020). Y-axis shows the average percentage of original input

constituting the essential subsets of each pair of proteomes. For example, if the essential sets

for A and B contain 15% and 25% of the original input proteins, respectively, then 20 will be on

the y-axis. The percentage of the original input proteins used is directly proportional to the

evolutionary relatedness (expressed in terms of the AAI on the x-axis) and agnostic on the

alignment tool used.

Figure S9: Percentage of input sequences used and evolutionary relatedness in graph-based orthology inference (2,000 bacterial MAGs). Y-axis shows average percentage of input proteins constituting the essential subsets of each inter-proteome alignment. Similarly to the observations for the QfO dataset (Supplementary Figure S8), the average percentage of input proteins used in the essential subsets is directly proportional to the evolutionary relatedness (expressed as AAI). The leftmost plots refer to pairs of MAGs, in which one MAG was obtained from aquatic samples and the other from terrestrial samples.

Figure S10: Benchmark results for predictions obtained with and without essential alignments. **a**, Accuracies of SonicParanoid2 obtained using essential alignments (empty markers) on the generalized species tree discordance tests are highly similar to those obtained using the complete alignments, regardless of the alignment tool and sensitivity settings used. **b**, The prediction accuracies on functional benchmark tests conducted using the essential and complete alignments are extremely similar and do overlap in many cases.

Figure S11: Benchmark results for predictions obtained with and without essential alignments. Empty markers represent predictions obtained using essential alignments. **a**, Prediction accuracies on gene-tree-based benchmark tests tend to overlap, which is likely due to the small sizes of the benchmark sets. Accuracies overlap on species tree discordance tests in **b** for fungi and bacteria, which use relatively small test sets. Accuracies based on eukaryote dataset appear more similar at higher sensitivity settings.

Figure S12: Orthologous domains typically missed by BBH. Proteins involved in fission or fusion events during evolution may contain orthologous relationships at the domain level (black arrows) that may be missed by BBH. **a**, Gene fission event in which a multi-domain protein from species X has its orthologous domains separated into two single-domain proteins in species Y. **b**, Gene-fusion event in which two domains in two different proteins in species X have their orthologs arranged into a single protein in species Y.

Figure S13: QfO benchmark results for SonicParanoid2 with and without domain-based orthology inference. Results shown by empty markers were obtained using the graph-based pipeline only (Figure 1a), whereas those shown by filled markers include orthologs predicted from the domain-based algorithm (Figure 1b). Settings described in Supplementary Table S3 were used. **a**, Accuracy results obtained from generalized species tree discordance tests. **b**, Prediction accuracies obtained from functional benchmark tests.

Figure S14: QfO benchmark results for SonicParanoid2 with and without domain-based orthology inference. Results shown by empty markers were obtained using the graph-based pipeline only (Figure 1a), whereas those shown by filled markers include orthologs predicted from the domain-based algorithm (Figure 1b). Settings described in Supplementary Table S3 were used. Results obtained from **a**, gene tree-based tests and **b**, species tree discordance tests.

Figure S15: Dataset used to generate training samples and labels for binary AdaBoost classifier. Average size of the proteomes is 5.50 million AA, with *Glicine max* (21.73 million AA) and *Nanoarchaeum equitans* (0.15 million AA) being the largest and smallest, respectively.

Figure S16: Example of architecture estimation and document creation for a single input protein. **a**, Search the protein in the Pfam profile database using MMseqs2. **b**, Only hits with a bitscore exceeding 30 and domain coverage (t-coverage) exceeding 75% are used to build the architectures. **c**, Representation of the architecture as a sequence of domains, document, and architecture features. Black blocks in the architecture represent unannotated regions.

Figure S17: Selection of candidate orthologs in the domain-based pipeline. Maximum cosine similarities for each protein from proteomes A (top-left) and B (top-right) are selected. Proteins corresponding to entries in the final matrix (bottom) will populate the ortholog clusters generated by the domain-based pipeline.

1295 **Tables**

1296

1297

	Execution time		Predicted ortholog pairs		Speed-up on other methods	
Mode	Total (hours)	Increase (%)	Count (million)	Increase (%)	Broccoli (folds)	OrthoFinder (folds)
Default	0.86	29.17	15.28	27.39	3.23	11.89
Fast	0.56	49.16	14.64	29.79	4.92	18.10
Sensitive	4.36	4.45	19.27	23.14	-1.57	2.34

Table 1: Execution times of SonicParanoid2 and effects of including domain-based orthology.
Results were obtained using the QfO dataset as input. Execution time columns show the total
execution time and its increase due to the execution of the domain-based pipeline. Increase in
predicted orthologs provided by the domain-aware pipeline is up to one-third (columns of
predicted ortholog pairs). Last two columns show speedup folds relative to the execution times
of Broccoli and OrthoFinder (both at default settings).

1309

1310

	Execution time		Predicted ortholog pairs	
Mode	Total (hours)	Increase (%)	Count (million)	Increase (%)
Default	37.99	10.40	1817.40	30.66
Fast	24.33	23.51	1694.88	37.39

1315 **Table 2:** Effects of including domain-oriented orthology when processing a set of 2,000 MAGs.
1316 Execution time columns show the total execution time and its increase due to the inclusion of
1317 the domain-based pipeline. The increase in execution time is low if we consider the magnitude
1318 of the input dataset, whereas the number of predicted orthologs increased by more than one-
1319 third.

1320

1321

Mode	Alignment tool	Settings
Default	Diamond	very-sensitive
Fast	Diamond	mid-sensitive
Sensitive	MMseqs	-s 7.5

1325 **Table S1:** SonicParanoid2 presets. Alignment tools and settings used for the three
1326 SonicParanoid2 presets. In addition to the presets in the table, users can execute
1327 SonicParanoid2 using custom settings for the alignment tool (Diamond, MMseqs2 or BLAST)
1328 and its sensitivity.

1329

1330

Pair	Sequence count sp1	Sequence count sp2	Sequence count difference folds (assuming sp1<sp2)	Proteome size sp1	Proteome size sp2	Proteome size difference folds (assuming sp1<sp2)	Mean protein length A	Mean protein length B	Fastest
A-B	3,422	2,236	-1.53	769,203	739,153	-1.04	224.78	330.57	0
B-A	2,236	3,422	1.53	739,153	769,203	1.04	330.57	224.78	1
A-C	3,422	2,353	-1.45	769,203	637,663	-1.21	224.78	271.00	0
C-A	2,353	3,422	1.45	637,663	769,203	1.21	271.00	224.78	1
A-D	3,422	1,889	-1.81	769,203	537,042	-1.43	224.78	284.30	0
D-A	1,889	3,422	1.81	537,042	769,203	1.43	284.30	224.78	1

Table S2: AdaBoost training samples. The first column shows the pairs of proteomes each sample represents (not used in the training). Columns 2–9 show training features for AdaBoost, which include information extracted from the input proteomes, such as protein count, proteome size, and average protein length. Last column shows the training labels.

Tool	Version	Mode	MMseqs	Diamond	BLAST
SonicParanoid	2.0.0	Fast	-s 2.5	mid-sensitive	X
SonicParanoid	2.0.0	Default	-s 4.0	sensitive	default
SonicParanoid	2.0.0	Sensitive	-s 6.0	very-sensitive	X
SonicParanoid	2.0.0	Most-sensitive	-s 7.5	ultra-sensitive	X
Broccoli	1.2.1	Default	X	more-sensitive	X
OrthoFinder	2.5.4	Default	X	more-sensitive	X

Table S3: Mapping of sensitivities of alignment tools to sensitivity settings of the tested orthology inference tools. Cells filled with "X" represent unavailable or untested settings.

MMseqs2						
Mode	**Complete alignments**	**Essential alignments**	**AdaBoost accuracy (%)**	**Avg. (%) used in essential sets**	**Saved hours**	**Saved time (%)**
most-sensitive	6.76	3.91	95.94	33.45	2.85	42.18
sensitive	2.57	1.65	94.91	31.22	0.91	35.60
default	0.64	0.47	94.61	25.50	0.17	25.84
fast	0.33	0.26	92.77	20.22	0.07	20.87
Diamond						
Mode	**Complete alignments**	**Essential alignments**	**AdaBoost accuracy (%)**	**Avg. (%) used in essential sets**	**Saved hours**	**Saved time (%)**
most-sensitive	2.35	1.71	95.37	31.94	0.63	27.01
sensitive	0.62	0.45	95.20	31.42	0.17	27.69
default	0.46	0.30	96.10	29.71	0.16	34.29
fast	0.23	0.16	96.70	26.78	0.07	31.05
BLAST						
Mode	**Complete alignments**	**Essential alignments**	**AdaBoost accuracy (%)**	**Avg. (%) used in essential sets**	**Saved hours**	**Saved time (%)**
default	18.41	13.32	83.38	33.83	5.09	27.65

Table S4: Saved execution time using AdaBoost-enhanced graph-based algorithm when processing QfO 2020 dataset. Results for 18 trials of SonicParanoid2 using the graph-based pipeline are shown. Sub-tables show the results obtained using (from top to bottom) MMseqs2, Diamond, and BLAST at different sensitivities. Columns two and three show the time required to perform homology searches (in hours) using the conventional all-versus-all (complete alignments) and the novel approach (essential alignments), respectively. Accuracies for the AdaBoost classifier and the average sizes of the original input proteins used in the essential subsets are shown in columns four and five, respectively. The last two columns on the right show the amount of time saved using the novel graph-based approach (in hours and percentage, separately).

Alignment tool	SonicParanoid mode	AdaBoost model	Ex. time (hours)	Saved hours	Saved time (%)	Saved time decrease (%)
MMseqs2	most-sensitive	Correct	3.91	2.85	42.18	-70.34
		Wrong	5.91	0.85	12.51	
	sensitive	Correct	1.65	0.91	35.60	-58.68
		Wrong	2.19	0.38	14.71	
	default	Correct	0.47	0.17	25.84	-53.30
		Wrong	0.56	0.08	12.07	
	fast	Correct	0.26	0.07	20.87	-38.81
		Wrong	0.29	0.04	12.77	
Diamond	most-sensitive	Correct	1.71	0.63	27.01	-23.11
		Wrong	1.86	0.49	20.77	
	sensitive	Correct	0.45	0.17	27.69	-37.29
		Wrong	0.51	0.11	17.36	
	default	Correct	0.30	0.16	34.29	-47.37
		Wrong	0.38	0.08	18.05	
	fast	Correct	0.16	0.07	31.05	-52.65
		Wrong	0.19	0.03	14.70	
BLAST	default	Correct	13.32	5.09	27.65	-12.17
		Wrong	13.94	4.47	24.29	

Table S5: Importance of correctly predicting the fastest inter-proteome alignments. To evaluate the importance of AdaBoost, we performed trials using a "wrong" model, which outputs the opposite prediction of the "correct" one. For example, if the model has an accuracy of 95.94% using MMseqs in the most-sensitive mode, then the "wrong" model will have an accuracy of 4.06%. Column four shows the total execution times for the homology searches using the "correct" or "wrong" AdaBoost classifier. The rightmost column shows the decrease in percentage of saved time when using the wrong model.

Alignment tool	Complete alignments	Essential alignments	AdaBoost accuracy (%)	Avg. (%) used in essential sets	Saved hours	Saved time (%)
MMseqs2	67.38	56.48	83.89	28.09	10.90	16.18
Diamond	31.65	23.74	91.37	42.96	7.91	24.99

Table S6: Saved execution time on 2,000-MAG dataset using the novel graph-based approach at default sensitivity settings. Columns two and three show the time required to perform the homology searches (in hours) using the conventional all-versus-all (complete alignments) approach and the novel approach (essential alignments), respectively. The AdaBoost accuracies and the average sizes of the original input proteins used in the essential subsets are listed in columns four and five, respectively. The last two columns on the right show the amount of time saved (in hours and percentage) when compared with the complete alignments.

Alignment tool	SonicParanoid mode	Ex. time (hours)	Speed-up folds on Broccoli	Speed-up folds on OrthoFinder
MMseqs	most-sensitive	4.17	-1.51	2.44
	sensitive	1.91	1.45	5.33
	default	0.75	3.69	13.57
	fast	0.55	5.01	18.44
Diamond	most-sensitive	1.93	1.43	5.27
	sensitive	0.66	4.17	15.33
	default	0.52	5.32	19.57
	fast	0.38	7.31	26.90
BLAST	default	13.67	-4.94	-1.34

Table S7: Speedup folds on Broccoli and OrthoFinder when processing QfO dataset. Speedups refer to trials performed on SonicParanoid2 using only the graph-based algorithm and include the creation of ortholog groups. OrthoFinder and Broccoli used Diamond to perform the alignments, whereas SonicParanoid was executed using different alignment tools (Supplementary Table S3). Negative values represent settings for which SonicParanoid was slower.

Species	Common name	Ortholog (UniProt ID)	Architecture in SonicParanoid2	Cosine sim. with PF0A8F4	Cosine sim. with PF0A8F0
Branchiostoma floridae	Florida lancelet	C3ZI77	52 PF00485 32 PF14681	0.563	0.666
Ciona intestinalis	Sea squirt	F6U8B5	70 PF00485 44 PF14681	0.619	0.702
Danio rerio	Zebrafish	A0A2R8Q5J9	91 PF00485 40 PF14681 16	0.633	0.72
Danio rerio	Zebrafish	E9QGS0	93 PF00485 40 PF14681 15	0.664	0.694
Danio rerio	Zebrafish	B0S7A4	79 PF00485 40 PF14681 21	0.623	0.646
Dictyostelium discoideum	Slime mold	Q55EL3	72 PF00485 40 PF14681	0.637	0.722
Gallus gallus	Chicken	A0A1D5PCN9	90 PF00485 35 PF14681 14	0.668	0.686
Gallus gallus	Chicken	A0A1L1RJC9	99 PF00485 40 PF14681 15	0.657	0.686
Gorilla gorilla	Gorilla	G3QI51	100 PF00485 39 PF14681 16	0.689	0.701
Homo sapiens	Human	Q9NWZ5	100 PF00485 40 PF14681 16	0.655	0.713
Lepisosteus oculatus	Spotted gar	W5MBZ5	87 PF00485 40 PF14681 16	0.595	0.706
Monodelphis domestica	Gray opossum	A0A5F8GEJ6	103 PF00485 41 PF14681 15	0.629	0.641
Mus musculus	Mouse	Q91YL3	100 PF00485 40 PF14681 16	0.655	0.713
Oryzias latipes	Medaka	A0A3B3HHD8	78 PF00485 40 PF14681	0.662	0.679
Oryzias latipes	Medaka	A0A3B3HWV8	85 PF00485 41 PF14681 16	0.599	0.699
Oryzias latipes	Medaka	H2LXZ5	100 PF00485 43 PF14681 15	0.656	0.685
Pan troglodytes	Chimpanzee	K7CT77	100 PF00485 40 PF14681 16	0.655	0.713
Rattus norvegicus	Rat	D3ZYQ8	100 PF00485 40 PF14681 16	0.655	0.713

Table S8: Domain-orthologs of eukaryote uridin–ecytidine kinase proteins recovered using SonicParanoid2. Third column shows a list of proteins predicted as orthologous to the human uridine–cytidine kinase proteins (Q9NWZ5), which was shown as an example of domain-fusion event by Persson *et al.* 2020. Column four shows the architectures of each protein as they appear in the training corpus for the Doc2Vec model. The last two columns show the cosine similarities assigned by Doc2Vec to each eukaryote uridine–cytidine kinase ortholog for *E. coli* PF0A8F4 and PF0A8F0 proteins, respectively.

$I)$ b is best hit for query a in the alignment A-B

$II)a$ is best hit for query b in the alignment B-A

Equation 1: Bidirectional best hit (BBH).

$I')$ $\forall a \in A \,\exists$ at least one target $b \in B : score(a,b) \geq t$

$II')\forall b \in B \,\exists$ at least one target $a \in A : score(b,a) \geq t$

Equation 2: Necessary conditions for the inclusion of query and target proteins in protein subsets (*ess(A)* and *ess(B)*) used in the second inter-proteome alignment.

$I)$ b is best hit for query a in the alignment A-B

$II)a$ is best hit for query b in the alignment $ess(A)$-$ess(B)$

Equation 3: Bidirectional best hits applied to alignments conducted on essential protein subsets.

1547 **References**

1. Koonin, E. V. Orthologs, Paralogs, and Evolutionary Genomics. *Annu. Rev. Genet.* **39**, 309–338 (2005).

2. Li, L., Stoeckert, C. J. & Roos, D. S. OrthoMCL: Identification of Ortholog Groups for Eukaryotic Genomes. *Genome Res.* **13**, 2178–2189 (2003).

3. Lechner, M. *et al.* Proteinortho: Detection of (Co-)orthologs in large-scale analysis. *BMC Bioinformatics* **12**, 1–9 (2011).

4. Sonnhammer, E. L. L. & Östlund, G. InParanoid 8: orthology analysis between 273 proteomes, mostly eukaryotic. *Nucleic Acids Res.* **43**, D234–D239 (2015).

5. Nevers, Y. *et al.* OrthoInspector 3.0: open portal for comparative genomics. *Nucleic Acids Res.* **47**, D411–D418 (2019).

6. Altenhoff, A. M. *et al.* OMA orthology in 2021: website overhaul, conserved isoforms, ancestral gene order and more. *Nucleic Acids Res.* **49**, D373–D379 (2021).

7. Vilella, A. J. *et al.* EnsemblCompara GeneTrees: Complete, duplication-aware phylogenetic trees in vertebrates. *Genome Res.* **19**, 327–335 (2009).

8. Mi, H. *et al.* PANTHER version 16: a revised family classification, tree-based classification tool, enhancer regions and extensive API. *Nucleic Acids Res.* **49**, D394–D403 (2021).

9. Fuentes, D. *et al.* PhylomeDB V5: an expanding repository for genome-wide catalogues of annotated gene phylogenies. *Nucleic Acids Res.* **50**, D1062–D1068 (2022).

10. Emms, D. M. & Kelly, S. OrthoFinder: phylogenetic orthology inference for comparative genomics. *Genome Biol.* **20**, 238 (2019).

11. Chorostecki, U., Molina, M., Pryszcz, L. P. & Gabaldón, T. MetaPhOrs 2.0: integrative, phylogeny-based inference of orthology and paralogy across the tree of life. *Nucleic Acids Res.* **48**, W553–W557 (2020).

12. Kristensen, D. M., Wolf, Y. I., Mushegian, A. R. & Koonin, E. V. Computational methods for Gene Orthology inference. *Brief. Bioinform.* **12**, 379–391 (2011).

13. Altenhoff, A. M. *et al.* Standardized benchmarking in the quest for orthologs. *Nat. Methods* **13**, 425–430 (2016).

14. Sayers, E. W. *et al.* GenBank 2023 update. *Nucleic Acids Res.* **51**, D141–D144 (2023).

15. Steinegger, M. & Söding, J. MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. *Nat. Biotechnol.* **35**, 1026–1028 (2017).

16. Buchfink, B., Reuter, K. & Drost, H.-G. Sensitive protein alignments at tree-of-life scale using DIAMOND. *Nat. Methods* **18**, 366–368 (2021).

17. Camacho, C. *et al.* BLAST+: architecture and applications. *BMC Bioinformatics* **10**, 421 (2009).

18. Dalquen, D. A. & Dessimoz, C. Bidirectional Best Hits Miss Many Orthologs in Duplication-Rich Clades such as Plants and Animals. *Genome Biol. Evol.* **5**, 1800–1806 (2013).

19. Wang, M. & Caetano-Anollés, G. The Evolutionary Mechanics of Domain Organization in Proteomes and the Rise of Modularity in the Protein World. *Structure* **17**, 66–78 (2009).

20. Persson, E., Kaduk, M., Forslund, S. K. & Sonnhammer, E. L. L. Domainoid: domain-oriented orthology inference. *BMC Bioinformatics* **20**, 523 (2019).

21. Huang, L.-C. *et al.* KinOrtho: a method for mapping human kinase orthologs across the tree of life and illuminating understudied kinases. *BMC Bioinformatics* **22**, 446 (2021).

22. Unsal, S. *et al.* Learning functional properties of proteins with language models. *Nat. Mach. Intell.* **4**, 227–245 (2022).

23. Liu, J., Li, J., Wang, H. & Yan, J. Application of deep learning in genomics. *Sci. China Life Sci.* **63**, 1860–1878 (2020).

24. Nissen, J. N. *et al.* Improved metagenome binning and assembly using deep variational autoencoders. *Nat. Biotechnol.* **39**, 555–560 (2021).

25. Pan, S., Zhu, C., Zhao, X.-M. & Coelho, L. P. A deep siamese neural network improves metagenome-assembled genomes in microbiome datasets across different environments. *Nat. Commun.* **13**, 2326 (2022).

26. Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**, 583–589 (2021).

27. Lin, Z. *et al.* Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science* **379**, 1123–1130 (2023).

28.   Sutphin, G. L., Mahoney, J. M., Sheppard, K., Walton, D. O. & Korstanje, R. WORMHOLE: Novel Least Diverged Ortholog Prediction through Machine Learning. *PLOS Comput. Biol.* **12**, e1005182 (2016).

29.   Derelle, R., Philippe, H. & Colbourne, J. K. Broccoli: Combining Phylogenetic and Network Analyses for Orthology Assignment. *Mol. Biol. Evol.* **37**, 3389–3396 (2020).

30.   Cosentino, S. & Iwasaki, W. SonicParanoid: fast, accurate and easy orthology inference. *Bioinformatics* **35**, 149–151 (2019).

31.   Kuznetsov, D. *et al.* OrthoDB v11: annotation of orthologs in the widest sampling of organismal diversity. *Nucleic Acids Res.* **51**, D445–D451 (2023).

32.   Freund, Y. & Schapire, R. E. A Decision-Theoretic Generalization of On-Line Learning and an Application to Boosting. *J. Comput. Syst. Sci.* **55**, 119–139 (1997).

33.   Le, Q. & Mikolov, T. Distributed Representations of Sentences and Documents. in *Proceedings of the 31st International Conference on Machine Learning* 1188–1196 (PMLR, 2014).

34.   Enright, A. J., Van Dongen, S. & Ouzounis, C. A. An efficient algorithm for large-scale detection of protein families. *Nucleic Acids Res.* **30**, 1575–1584 (2002).

35.   Linard, B. *et al.* Ten Years of Collaborative Progress in the Quest for Orthologs. *Mol. Biol. Evol.* **38**, 3033–3045 (2021).

36.   Nevers, Y. *et al.* The Quest for Orthologs orthology benchmark service in 2022. *Nucleic Acids Res.* **50**, W623–W632 (2022).

37.   Deutekom, E. S., Snel, B. & van Dam, T. J. P. Benchmarking orthology methods using phylogenetic patterns defined at the base of Eukaryotes. *Brief. Bioinform.* **22**, bbaa206 (2021).

38.   Emms, D. M. & Kelly, S. Benchmarking Orthogroup Inference Accuracy: Revisiting Orthobench. *Genome Biol. Evol.* **12**, 2258–2266 (2020).

39.   Mistry, J. *et al.* Pfam: The protein families database in 2021. *Nucleic Acids Res.* **49**, D412–D419 (2021).

40.   Asgari, E. & Mofrad, M. R. K. Continuous Distributed Representation of Biological

Sequences for Deep Proteomics and Genomics. *PLOS ONE* **10**, e0141287 (2015).

41.   Heinzinger, M. *et al.* Modeling aspects of the language of life through transfer-learning protein sequences. *BMC Bioinformatics* **20**, 723 (2019).

42.   Nayfach, S. *et al.* A genomic catalog of Earth's microbiomes. *Nat. Biotechnol.* **39**, 499–509 (2021).

43.   Bowers, R. M. *et al.* Minimum information about a single amplified genome (MISAG) and a metagenome-assembled genome (MIMAG) of bacteria and archaea. *Nat. Biotechnol.* **35**, 725–731 (2017).

44.   Altenhoff, A. M. *et al.* The Quest for Orthologs benchmark service and consensus calls in 2020. *Nucleic Acids Res.* **48**, W538–W545 (2020).

45.   Katoh, K., Rozewicki, J. & Yamada, K. D. MAFFT online service: multiple sequence alignment, interactive sequence choice and visualization. *Brief. Bioinform.* **20**, 1160–1166 (2019).

46.   Altenhoff, A. M., Gil, M., Gonnet, G. H. & Dessimoz, C. Inferring Hierarchical Orthologous Groups from Orthologous Gene Pairs. *PLOS ONE* **8**, e53786 (2013).

47.   Behnel, S. *et al.* Cython: The Best of Both Worlds. *Comput. Sci. Eng.* **13**, 31–39 (2011).

48.   Radim Rehurek, P. S. Software Framework for Topic Modelling with Large Corpora. in *Proceedings of the LREC 2010 workshop on new challenges for NLP frameworks* 46–50 (2010).

49.   Pedregosa, F. *et al.* Scikit-learn: Machine Learning in Python. *Mach. Learn. PYTHON* 6.

50.   Mikolov, T., Chen, K., Corrado, G. & Dean, J. Efficient Estimation of Word Representations in Vector Space. Preprint at http://arxiv.org/abs/1301.3781 (2013).

51.   Melidis, D. P. & Nejdl, W. Capturing Protein Domain Structure and Function Using Self-Supervision on Domain Architectures. *Algorithms* **14**, 28 (2021).