ExMove: An open-source toolkit for processing and exploring

animal tracking data in R

Liam Patrick Langley[1], Stephen Lang[1], Luke Ozsanlav-Harris[1,2], Alice Trevail[1]

[1]Centre for Ecology and Conservation, University of Exeter, Penryn, Cornwall

[2]Wildfowl and Wetlands Trust, Slimbridge, Gloucester

Keywords: Animal movement, Tracking data, Reproducibility, Code sharing, User guide, GPS,

geolocator, ARGOS

Abstract

1. Ongoing technological advances have led to a rapid increase in the number, type, and scope of animal tracking studies. In response, many software tools have been developed to analyze animal movement data. These tools generally focus on movement modelling, but the steps required to clean raw data files from different tracking devices have been largely ignored. Such pre-processing steps are often time-consuming and involve a steep learning curve. Moreover, decisions made at this early stage can substantially influence subsequent analyses.

2. Here we present an open-access, reproducible toolkit written in the programming language R for processing raw data files into a single cleaned data set for analyses and upload to online tracking databases (found here: https://github.com/ExMove/ExMove). The toolkit is a codebase that users interact with directly to allow flexibility and understanding of code functionality. Additionally, we provide a Shiny app to help users explore tracking data and provide convenient visualizations to assist with appropriate parameter determination during data cleaning.

3. The toolkit is generalizable to different data formats and device types, uses modern 'tidy coding' practices, and relies on few well-maintained packages. We provide transparent, flexible code to flatten the learning curve associated with animal movement data processing, and produce robust, reproducible datasets.

4. Overall, we envision our resource as a time-saving approach that provides a single reproducible pipeline from data collection to archiving on open access databases, useful for anyone conducting animal movement analyses.

1 Introduction

We live in a golden age of animal-tracking data. Recent technological advancements have

reduced the size and cost of telemetry devices and improved their capacities, with more species

and individuals tracked over longer periods, allowing researchers to expand the frontiers of

ecological research (Bodey et al., 2018; Kays et al., 2015; Wilmers et al., 2015). These studies

have generated a rapidly expanding volume of data (Gupte et al., 2022; Kays et al., 2022), from

an increasing range of device types, with associated formats and errors. This proliferation has

complicated the workflow from raw files to a cleaned data set suitable for analysis and sharing,

with knock-on impacts for reproducibility. Such pre-analysis steps are universal when working

with animal movement data and involve the determination of key filtering parameters to

remove data that can strongly influence the conclusions drawn from subsequent analysis.

Moreover, these steps are time consuming, often involving a steep learning curve, and large

amounts of time and associated grant funding are lost as unacquainted researchers re-run

these steps and, in many cases, attempt to re-invent what should be a standardized and

reproducible process. Numerous software tools have been developed to facilitate animal

movement research (Beal et al., 2021; Joo et al., 2020). However, these tools largely focus on

evaluating dataset suitability (Bjørneraas et al., 2010; Morera-Pujol et al., 2023) and conducting

movement analyses of cleaned and/or collated data (e.g., Jonsen et al., 2023; Kölzsch et al.,

2022), and the upstream filtering and processing steps required to generate an appropriate

data set have been given scant attention (however see Gupte et al., 2022). The value of

transparent data pre-processing and the accessibility of authentic data sets is being realised

amid the push towards open and reproducible science. Software tools to facilitate this move

are urgently required.

There has been progress in developing tools for pre-processing. Gupte *et al.* (2022) provides an

informative framework outlining the key pre-processing steps involved in processing high-

throughput animal tracking data, alongside a pipeline to implement these steps. However, the

associated atlastools R package wraps these steps up into opaque functions, which may be

challenging for less-experienced analysts to de-bug. Additionally, bespoke functions, whilst

convenient in many instances, essentially constitute a black box and may provide an

impediment to learning. Over-reliance on existing functions may hinder researchers in their

effort to develop a foundational understanding of their animal tracking data and the steps

required to process it. MoveApps (Kölzsch et al., 2022) takes an alternative approach to the

problem, providing an online user interface where researchers can upload and explore their

own tracking data. This provides a tool to rapidly visualize animal tracking data, especially for

researchers who lack programming experience, however the background code is not

immediately apparent to users, which again limits the scope for learning. Moreover, MoveApps

does not allow upload of raw data from tags, requiring pre-processing into specific formats.

Existing approaches demonstrate the need for resources that integrate data processing goals

with user learning and development, alongside trends towards open and reproducible science

(Brunsdon & Comber, 2021).

Here, we fill this gap by providing a toolkit of foundational code to process raw tracking files

into clean data sets, thereby establishing a reproducible starting point for animal movement

analysis (found here: https://github.com/ExMove/ExMove). Moreover, we format these data

sets for upload to two widely used online tracking databases; Movebank (Kays et al., 2022) and

the Seabird Tracking Database (www.seabirdtracking.org). In doing so we provide a single

pathway for creating a standardised dataset for analyses and archiving. Our methods focus on

accessible and robust data processing and thorough interrogation of user-defined parameters,

which have important downstream consequences for biological inference. By sharing

transparent code, we equip users with tools to learn from and adapt for their own analyses.

This will make processing tracking data accessible to a wider audience, breaking down financial

barriers associated with expensive training courses, while simultaneously flattening the learning

curve for ecologists everywhere. Limited learning opportunities and confidence in code quality

have contributed to historically low uptake of journal-mandated code archiving (Baker, 2016),

and this will further contribute towards more open-access attitudes in science (Barnes, 2010;

Potts & Börger, 2023).

2 Objectives

Given the increase in animal movement research, and current gaps in availability and

accessibility of data processing tools, we have developed a toolkit in the programming language

R. This manuscript and the code provided have the following overall objectives:

1. Provide a flexible pipeline to process data from tracking devices, such as GPS, GLS and

Argos, into a foundational clean data set upon which researchers can build their own

bespoke animal movement analyses.

2. Streamline the path from data collection to sharing of cleaned datasets in online

repositories to facilitate open-access and reproducibility requirements of funders,

journals, and institutions.

3. Increase accessibility to new R users by providing an interactive shiny app that is still

useful for more advanced R users by assisting with appropriate parameter

determination and visualizations for data cleaning.

4. Generate a learning tool for users to develop skills in animal movement analysis. We

provide code organized into annotated code chunks which prioritize user understanding

rather than wrapping code up in opaque functions.

5. Maximize stability by using a few well-maintained core R packages, including *here*,

tidyverse and *sf*. This is timely given the widespread adoption of tidy-style coding and

deprecation of *sp* (Müller & Bryan, 2020; Pebesma, 2018; Wickham et al., 2019).

6. Provide open source code, the initial steps of which can be adapted for biologging

studies, such as merging and standardizing additional sensor data (e.g., immersion/TDR)

from multiple individuals.

By following this workflow, the user will achieve the following minimum requirements for clean

data which we define as:

• Date and time formats standardised across time zones

• Rows with corrupted timestamps removed

• Relevant metadata included

• No-data values removed (e.g., "NA", "0,0" in lat/longs or other erroneous sensor values)

• Duplicates removed

• Undeployed locations removed (e.g., before tag attachment)

• Spatial projections standardised

• Erroneous speeds and locations removed

• Locations at start of tracking period when behaviour is likely to be influenced by capture

removed

123   3 Preliminary Setup

124   Producing open-access and reproducible analyses is now a common goal for scientific research

125   (Culina et al., 2020; McKiernan et al., 2016), and there are various ways to version and publicly

126   share code (such as git & GitHub). Here, we outline the core best practices that we have

127   followed to help to ensure that the code itself is reliable and can be reproduced by others.

129   3.1 Preparing your machine and R libraries

In order to make use of the included materials, users must have downloaded R and the RStudio

IDE (Ihaka & Gentleman, 1996). Our code is compatible with R versions 4.0.3 - 4.2.1. In general,

it is recommended that users are not more than two sub-versions behind the most recent

release of R. We make use of the most recent releases of core packages in the *tidyverse*

(Wickham et al., 2019), which is composed of *ggplot2* (v3.4.0), *dplyr* (v1.0.10), *tidyr* (v1.2.1), *readr*

(v2.1.2), *purrr* (v1.0.1), *tibble* (v3.1.8), *stringr* (v1.5.0) and *forcats* (v0.5.1), as well as *lubridate*

(v1.8.0). We also use *sf* (v1.0-9) for spatial analyses, and the *here* package (v1.0.1) for making

reproducible file paths (Müller & Bryan, 2020; Pebesma, 2018).

3.2 Accessing the GitHub resources

The ExMove toolkit can be found in the following GitHub repository:

https://github.com/ExMove/ExMove. It can be utilised in a variety of ways, accessible to all

levels of experience and desired user outcomes. Users can either: i) 'clone' an updatable

version of the ExMove repository via git, ii) download a static copy of the entire repository by

navigating to <> Code > Download ZIP, or iii) view and download individual scripts as required. To

maximise reproducibility and future functionality, our recommended approach would be to set

up R/RStudio with git version control, set up and connect a personal GitHub account, then clone

the ExMove repository. Additional information and links for on getting set up with GitHub and

RStudio can be found in the ExMove repository readme.

3.3 Directory structure

Directory structure relates to how folders and sub-folders are arranged. We recommend

following the directory structure outlined by Figueiredo *et al.* (2022), which suggests that all

data required for a project should be inside a single directory, with separate sub-folders for raw

data, processed data, and outputs (such as tables and figures). Folders are best named in

snakecase format (e.g., "raw_data") to avoid issues with encoding spaces in filepaths (Trisovic

et al., 2022). For R Studio users, this folder structure is enhanced with the use of R Studio

projects, whose location denotes the 'top' of the directory allowing for shorter, reproducible

filepaths. We also use the here package to maximise reproducibility between operating systems

that use different file path delimiters (Müller & Bryan, 2020). When used in combination, these

best practices ensure that when sharing or archiving a single project folder, other users have all

the data required to recreate your analyses, and results will be reproducible regardless of their

machine.

3.4 Data structure

Raw animal tracking data should be saved into a "raw_data" folder in the exact format they are

downloaded or decompressed from devices (i.e., completely unaltered). These files should be

considered read-only and must not be opened with other software (such as Excel) which can

cause problems in changing data formats. Data from different devices will usually arrive in

separate files and as such there should be one file per individual (though some cases and data

sources may mean that data are combined in some way). We recommend that each individual

file should include a unique identifier in the filename. Note that raw data from some GLS

devices is provided as light levels and pre-processing may be required to obtain spatial co-

ordinates before the data is processed using this workflow (Lisovski & Hahn, 2012; Sumner et

al., 2009, p. 2; Thiebot & Pinaud, 2010). Metadata files should also be saved in raw_data as a

single file per dataset containing all additional data for each tag deployment, for example

individual ID, tag ID, tagging location/time or location of central place if applicable.

The tidyverse is an increasingly used approach for coding in R, with a collection of core

packages that use consistent grammar and data structures that allows user to quickly create

analyses that can be easily understood by others (Wickham et al., 2019). To follow tidyverse

coding practices, data should adhere to three core rules: i) every variable must have its own

column, ii) every observation must have its own row, and iii) every value must have its own cell

(Wickham, 2014). Tracking data inherently follow this tidy structure, with rows as observations,

with at minimum require a column for time, plus additional columns for variables associated

with each time point (e.g., latitude and longitude, depth, temp etc.). Finally, focusing on using

core, well-maintained packages (specifically *here*, *tidyverse* and *sf*), helps to maximise code

longevity.

4 Workflow

Here, we provide an outline of the data workflow structure and methods (Figure 1) that enable

a user to import raw tracking data and metadata, perform basic to advanced cleaning, filtering

and processing steps, ready for further scientific analysis. We will introduce the required data

structure and outline the flexibility and utility of the workflow for anyone undertaking analysis

of animal movement data. For a full example of how to use all code within the workflow, please

see the user guide (Supplementary Material User guide & https://exmove.github.io).

Figure 1: Diagram of workflow used for processing movement data from raw data to archiving

(thick line denotes core path of workflow)

4.1 Read in data, Read in metadata, and Merge

The workflow starts with reading in raw tracking data and metadata files. Raw tracking data

refers to data downloaded directly from telemetry devices, which fundamentally must contain

a time stamp and location data. We also provide alternative code for data that have already

been partially processed, for example data downloaded from an existing repository that

contains multiple tags and/or individuals. Metadata provide essential technical, biological and

ecological context for the raw data, such as the tag deployment period, sex, age and

population. Metadata should contain one row for each tag deployment per individual, with ID

numbers corresponding to those in the raw data. The ID numbers are used to match each row

of the raw data to the corresponding metadata. Additional code is provided to handle scenarios

where a single individual has carried multiple tags in its lifetime, or a single tag has been

deployed on multiple individuals. Example data are saved as .csv files (see supplementary files),

and guidance is provided for importing data in other text-based formats (e.g., such as .txt or

.tsv).

Figure 2. Example mutating join of raw GPS tracking data file (orange) and metadata file (lilac)

using left_join, with "animal_id" as the index column. Note that accuracy of latitude and

longitude data has been reduced for clarity.

4.2 Cleaning

The cleaning step removes data that are incorrect based on deployment periods and technical

tag information. This includes limiting data to the deployment period (i.e., for loggers

programmed to start ahead of deployment or not turned off immediately following retrieval),

removing duplicate rows, and removing NA's or known values that correspond to missing data

based on tag manufacturer guidance. Some tags record a specific 'no data' value when sensor

information cannot be derived (e.g., "0,0" for latitude and longitude).

4.3 Processing

During the processing step we calculate spatial and temporal metrics to allow downstream

analyses and filtering of data based on ecological knowledge. These include metrics pertaining

to ecological processes, such as distance traveled (Euclidian distance between successive

locations), net displacement (Euclidian distance from first location for each unique ID, e.g., used

to quantify migration phenology; Soriano-Redondo et al., 2020), time step duration (duration

between successive locations), travel speed (distance travelled dived by time step duration) and

turning angle (trajectory of movement at current time step relative to previous trajectory) and

travel bearing (trajectory of movement relative to true north) (See Fig. 3 for graphical

visualization of these metrics, the code for which is presented in the workflow and incorporated

into the shiny app).

Location information from biologging devices is recorded in a particular coordinate reference

system (CRS) that the user should know. Often locations are recorded as latitudes and

longitudes (WGS84 coordinate system) which are un-projected and represent locations on a

sphere and are generally not recommend for calculating distances. Projected spatial data (like

the format we convert data to in the workflow) possess a coordinate reference system (CRS)

that refers to the 2D projection of the earth's surface used to represent locations. This type of

CRS is recommended for calculating distances and angles. During the processing step the user

must define the CRS that they wish to use for calculating distances and angles. We transform

data in the workflow to a global 'equal area projection' for spatial calculation, which can be

useful for tracking data spans a large geographic range. However there is no "correct" CRS and

the specific choice may depend on whether users want to preserve differences or angles and

the spatial extent of the data. We provide further guidance and links in section 4 of our FAQs

(https://exmove.github.io/FAQs.html).

Figure 3. Processed metrics derived from animal tracking data. Plot A depicts a movement track

of a Greenland White-fronted Goose with three different metrics labelled: i) step length, ii)

turning angle and iii) travel bearing. The net displacement (plot B) and speed (plot C) over time

is shown for the movement track plot A. Plot D depicts a single foraging trip of a Red-footed

Booby from a central place (grey filled diamond). Two metrics are labelled here: iv) distance to

central place and v) bearing to central place. The distance to colony (plot E) and cumulative

distance traveled (plot F) are shown for the track in Plot D.

4.4 Filter

The filter step allows users to remove erroneous locations based on three derived variables: 1)

speed, 2) net displacement and 3) time since tag deployment. Each of these variables are

described and calculated during the 4.3 processing step (Fig 3). Threshold values are selected by

the user to filter the data, if these values are exceeded then the particular rows are removed.

The downstream consequences of these decision can be explored with the visualizations we

provide and within the shiny app. Ecological knowledge from the user is required to help inform

the thresholds selected, for instance a species' maximum travel speed or the time after tag

deployment that behavior returns to normal. We encourage users to explore a range of values

and visualize the consequences using maps of movement tracks and histograms of speed and

net squared displacement.

4.5 Summarise

This step provides a full summary of the data that the user has retained after the filtering step.

This is an important opportunity to scrutinize the integrity of the data and determine if further

filtering is required. The user selects grouping variables for the data — we suggest initially

grouping by individual but broader (e.g., year and population) or narrower (e.g. date) groupings

may be required depending on the type of analysis to be undertaken. For each level of the

grouping variable the following summary statistics are provided: number of locations, number

of unique tracking days, start and end dates of tracking period, and the sampling frequency

locations.

4.6 Post-processing: re-sampling, segmenting, & central place foragers (optional)

Some types of animal movement analyses require additional processing to prepare data (e.g.

hidden Markov models and step selection functions). The toolkit includes code to conduct

three-post processing steps; segmenting, sub-sampling and classifying foraging trips.

Segmenting separates tracks into bursts of continuous data with consistent sampling intervals

to avoid over-interpolation across large gaps. Tracks are segmented into separate bursts if the

time between two locations exceeds a user defined threshold. Then only burst that contain a

minimum number of locations are kept for further analysis and this threshold is also defined by

the user. Sub-sampling down samples tracking data to facilitate comparisons among datasets

with different sampling regimes (Fig 4). The user defines a new sampling frequency which

should be greater than the average sampling frequency determined at earlier steps.

For central place foragers, we include an optional script to calculate distance and bearing to a

central place (typically a breeding colony) and classify distinct foraging trips (e.g., Trevail et al.,

2019). The central place is user defined and may refer to a known nest site, a central colony

location for the population, or a shape file delineating the spatial boundary of the central place.

We provide code to classify and number trips away from the central place by using distance or a

shape file, and then to classify trips as 'foraging' trips using a time threshold, facilitating the

removal of very short trips e.g. in response to disturbance events. We then calculate standard

metrics of foraging trips: total distance travelled, maximum distance from the central place, trip

duration, and distal location, to facilitate standardized reporting of central place forager's

behavioral ecology.

All post-processing steps are provided as additional scripts and are designed to follow on from

the main code workflow. Scripts can be run iteratively if multiple additional post-processing

steps are required. Each script contains tools to summarise, visualise, and save the post-

processed data. The shiny app can also be used here to aid parameter determination.

Figure 4. Example of sub-sampling GPS tracking data using an optional post-processing step.

The data used are from two Greenland White-fronted Geese migrating from the United

Kingdom to Iceland. Panel a depicts a histogram of sampling intervals present in the data,

clearly there is a mixture of data collected at one- and two-hour resolution. Therefore, to make

sampling intervals consistent the data were sub-sampled to 2 hours (dashed vertical line). In

panel b the output of this sub-sampling is visualized and retained (red) and removed (grey) GPS

fixes are shown. The individual starting from a more southerly location was originally collected

at a 1-hour resolution hence roughly every other fix is removed.

4.7 Standardising output for tracking databases

Many users may need to archive their data on an online database, which often require data to

be in a specific format before files can be uploaded (Kays et al., 2022). As such, we provide code

for users to format and save their data, processed within the workflow, in the required format

of two common tracking databases: (1) MoveBank, and (2) the Seabird Tracking Database.

5 Tools and additional practical resources

5.1 User guide

We provide a fully-coded user guide that follows each step of the workflow, with worked

examples in baseR and tidy code. This guide contains example outputs of data frames and plots

produced for each step. The user guide is available as a supplementary material, within the

GitHub repository (https://github.com/ExMove/ExMove/tree/main/Documentation), and via

the ExMove website (https://exmove.github.io/userguide).

5.2 FAQ's

Some important principles of movement and spatial analyses can be a common source of

confusion (for example: understanding data projections). Given ExMove's goal as a learning

tool, we provide information to help facilitate better understanding of these core concepts, and

links to useful materials made available by others (FAQ page can be found here:

https://github.com/ExMove/ExMove/tree/main/Documentation &

https://exmove.github.io/FAQs.html).

5.3 Shiny app

The shiny app is available online at the following link:

https://lukeozsanlav.shinyapps.io/exmove_explorer/. The shiny app uses the same code as the

main workflow from section 6 onwards (including optional processing scripts), incorporated

into a user friendly UI. The code for the shiny app is also available in the GitHub repository,

alongside the workflow. There is an upload limit so users can either explore the app with

examples data sets we provide or a subset of their own data. If the user wants to run the app

on their full data set, then we recommend that they clone the repository and then run the app

locally on their own machine. The code for doing this is explained in section 6 of the user guide.

The app is designed to be accessible for new R users to visualize data and data filtering but also

provides a convenient interactive platform for more experienced users to determine the

downstream effects of user-input parameters on the resulting cleaned data frames. When

processing animal tracking data, prior to analysis, users often select rather arbitrary values by

which to filter data, i.e., to eliminate erroneous speeds users often remove points creating

speeds above a selected threshold. The app allows users to explore the implications of these

arbitrary decisions via interactive manipulation of threshold values and subsequent

visualizations that include, data summary tables, histograms of the variable of interest and

maps. There are multiple tabs to navigate within the app once users have uploaded their own

data, in each there are a series of interactive user input threshold values and a number of plots

and tables detailing the consequences of the user selected values (Fig 5). There are tabs for

basic data filters (e.g., speed, post-deployment period and date), calculating foraging trips for

central placed foragers, sub-sampling location frequency, segmenting movement tracks and

finally visualizing the locations in an interactive leaflet map. To facilitate integration with the

main workflow there are code chunks output at the bottom of each shiny tab that contain the

selected parameter values, which can be copied into the workflow.

Figure 5. Shiny app to explore and visualise tracking data and test the influence of parameter

selection on filtering and post-processing. The data filters tab is depicted here, and each

labelled element is described in more detail here. Data upload: search the users system for a

file to upload to the app, this should be the equivalent of df_diagnostic. Toggle tab: toggle

between different tabs in the app, for each tab the user input box and outputs will change. Info

Boxes: summary information of the tracking data that is calculated automatically for the

tracking uploaded by the user. User Values: Values that the user can alter that specify the

parameters in filtering or post-processing steps. These maybe be sliders, buttons, dropdown

menus or calendar date selectors Help; Click to access a pop-up help page that guides users

through each tab. Action; press this button to apply the current user value selection to the

data. Plot Controls: change whether all or a single individuals is depicted in a map. The specific

individual visualised can be chosen using a dropdown menu

5.5 Example datasets

Within the GitHub repo we provide four road-tested example datasets for users to familiarise themselves with running the pipeline. These datasets are from Trindade Petrels (*Pterodroma arminjoniana*; Figure 6A) breeding on Round Island (Nicoll et al., 2017), immature and adult red-footed boobies (*Sula leucogaster,* Figure 6B & D) breeding in the Chagos Archipelago (Carr et al., 2022) and Greenland white-fronted goose (*Anser albifrons flavirostris*, Figure 6C) migrating from Ireland and Scotland to Greenland (Ozsanlav-Harris et al., 2022).

Figure 6. Visualisation of the four example datasets provided as part of the toolkit. Individual

locations are shown in red and colony locations shown in orange diamonds for seabirds. A: GLS

data from a Trindade petrel tracked during its non-breeding migration in 2011. The device was

deployed and retrieved when the individual was resting on Round Island Nature Reserve

(19.85° south; 57.78° east), situated 23 km off the North coast of Mauritius, Indian Ocean. Full

methods and ethics are detailed in Nicoll *et al.* (2017). B: Argos data from two immature red-

footed boobies tracked during 2022 using Microwave Telemetry Solar Argos/GPS PTT loggers

(Figure 6B). Data represent movements of individuals that have not yet recruited into a

breeding population, tagged whilst roosting on East Island in the Chagos Archipelago, central

Indian Ocean. C: GPS data from four Greenland White-fronted Geese tracked during spring

2018 and 2019. These data cover the spring migration from Ireland and Scotland to Greenland

with a stopover in Iceland. Full methods and ethics are detailed in Ozsanlav-Harris *et al.* (2022).

D: GPS data from three adult red-footed boobies tracked during 2016 and 2018 using igotU

loggers (Figure 6D). Data represent central-place foraging trips of breeding adults from two

colonies, Diego Garcia and Nelsons Island in the Chagos Archipelago, central Indian Ocean. Full

methods and ethics are detailed in Carr *et al.* (2022).

Acknowledgments

Alice Trevail was funded by the Bertarelli Programme in Marine Science, who also funded

collection of adult and immature red-footed booby data. We thank the Wildfowl and Wetlands

Trust for providing tracking data from Greenland White-fronted Geese and Larry Griffin for

deploying tags. We thank Malcolm Nicoll for valuable comments on an earlier version of the

manuscript, and for providing tracking data from a Trindade petrel. The Trindade petrel tracking

programme (Round Island, Mauritius) was supported by NERC (Grant NE/H5081500) and

Research England, with thanks to Mauritian Wildlife Foundation (MWF) and the National Parks

and Conservation Service (NPCS). We also thank Evelyn Alexander, Jacqueline Glencross and

Tess Handby for providing valuable feedback on the code, workflow and Shiny app.

Author contributions

All authors contributed equally to the manuscript.

Data availability statement

All data and code presented in this manuscript can be found in the following public GitHub

repository: https://github.com/ExMove/ExMove. All tracking data sets used are cited

appropriately in section 5.5.

References

Baker, M. (2016). 1,500 scientists lift the lid on reproducibility. *Nature*, *533*(7604), 452–454.

https://doi.org/10.1038/533452a

Barnes, N. (2010). Publish your computer code: It is good enough. *Nature*, *467*(7317), 753–753.

https://doi.org/10.1038/467753a

Beal, M., Oppel, S., Handley, J., Pearmain, E. J., Morera-Pujol, V., Carneiro, A. P. B., Davies, T. E.,

Phillips, R. A., Taylor, P. R., Miller, M. G. R., Franco, A. M. A., Catry, I., Patrício, A. R.,

Regalla, A., Staniland, I., Boyd, C., Catry, P., & Dias, M. P. (2021). track2KBA: An R

package for identifying important sites for biodiversity from tracking data. *Methods in*

Ecology and Evolution, *12*(12), 2372–2378. https://doi.org/10.1111/2041-210X.13713

Bjørneraas, K., Moorter, B., Rolandsen, C. M., & Herfindal, I. (2010). Screening Global

Positioning System Location Data for Errors Using Animal Movement Characteristics. *The*

Journal of Wildlife Management, *74*(6), 1361–1366. https://doi.org/10.1111/j.1937-

2817.2010.tb01258.x

Bodey, T. W., Cleasby, I. R., Bell, F., Parr, N., Schultz, A., Votier, S. C., & Bearhop, S. (2018). A

phylogenetically controlled meta-analysis of biologging device effects on birds:

Deleterious effects and a call for more standardized reporting of study data. *Methods in*

Ecology and Evolution, *9*(4), 946–955.

Brunsdon, C., & Comber, A. (2021). Opening practice: Supporting reproducibility and critical

spatial data science. *Journal of Geographical Systems*, *23*(4), 477–496.

https://doi.org/10.1007/s10109-020-00334-2

Carr, P., Trevail, A. M., Koldewey, H. J., Sherley, R. B., Wilkinson, T., Wood, H., & Votier, S. C.

(2022). Marine Important Bird and Biodiversity Areas in the Chagos Archipelago. *Bird*

Conservation International, 1–8. https://doi.org/10.1017/S0959270922000247

Culina, A., Van Den Berg, I., Evans, S., & Sánchez-Tójar, A. (2020). Low availability of code in

ecology: A call for urgent action. *PLOS Biology*, *18*(7), e3000763.

https://doi.org/10.1371/journal.pbio.3000763

Figueiredo, L., Scherer, C., & Cabral, J. S. (2022). A simple kit to use computational notebooks

for more openness, reproducibility, and productivity in research. *PLOS Computational*

Biology, *18*(9), e1010356. https://doi.org/10.1371/journal.pcbi.1010356

Gupte, P. R., Beardsworth, C. E., Spiegel, O., Lourie, E., Toledo, S., Nathan, R., & Bijleveld, A. I.

(2022). A guide to pre-processing high-throughput animal tracking data. *Journal of*

Animal Ecology, *91*(2), 287–307. https://doi.org/10.1111/1365-2656.13610

Ihaka, R., & Gentleman, R. (1996). R: A Language for Data Analysis and Graphics. *Journal of*

Computational and Graphical Statistics, *5*(3), 299–314.

https://doi.org/10.1080/10618600.1996.10474713

Jonsen, I. D., Grecian, W. J., Phillips, L., Carroll, G., McMahon, C., Harcourt, R. G., Hindell, M. A.,

& Patterson, T. A. (2023). aniMotum, an R package for animal movement data: Rapid

quality control, behavioural estimation and simulation. *Methods in Ecology and*

Evolution, *14*(3), 806–816. https://doi.org/10.1111/2041-210X.14060

Joo, R., Boone, M. E., Clay, T. A., Patrick, S. C., Clusella-Trullas, S., & Basille, M. (2020).

Navigating through the R packages for movement. *Journal of Animal Ecology*, *89*(1),

248–267. https://doi.org/10.1111/1365-2656.13116

Kays, R., Crofoot, M. C., Jetz, W., & Wikelski, M. (2015). Terrestrial animal tracking as an eye on

life and planet. *Science*, *348*(6240), aaa2478–aaa2478.

https://doi.org/10.1126/science.aaa2478

Kays, R., Davidson, S. C., Berger, M., Bohrer, G., Fiedler, W., Flack, A., Hirt, J., Hahn, C., Gauggel,

D., Russell, B., Kölzsch, A., Lohr, A., Partecke, J., Quetting, M., Safi, K., Scharf, A.,

Schneider, G., Lang, I., Schaeuffelhut, F., … Wikelski, M. (2022). The Movebank system

for studying global animal movement and demography. *Methods in Ecology and*

Evolution, *13*(2), 419–431. https://doi.org/10.1111/2041-210X.13767

Kölzsch, A., Davidson, S. C., Gauggel, D., Hahn, C., Hirt, J., Kays, R., Lang, I., Lohr, A., Russell, B.,

Scharf, A. K., Schneider, G., Vinciguerra, C. M., Wikelski, M., & Safi, K. (2022). MoveApps:

A serverless no-code analysis platform for animal tracking data. *Movement Ecology*,

10(1), 30. https://doi.org/10.1186/s40462-022-00327-4

Lisovski, S., & Hahn, S. (2012). GeoLight—Processing and analysing light-based geolocator data

in R. *Methods in Ecology and Evolution*, *3*(6), 1055–1059.

https://doi.org/10.1111/j.2041-210X.2012.00248.x

McKiernan, E. C., Bourne, P. E., Brown, C. T., Buck, S., Kenall, A., Lin, J., McDougall, D., Nosek, B.

A., Ram, K., Soderberg, C. K., Spies, J. R., Thaney, K., Updegrove, A., Woo, K. H., &

Yarkoni, T. (2016). How open science helps researchers succeed. *ELife*, *5*, e16800.

https://doi.org/10.7554/eLife.16800

Morera-Pujol, V., Catry, P., Magalhães, M., Péron, C., Reyes-González, J. M., Granadeiro, J. P.,

Militão, T., Dias, M. P., Oro, D., Dell'Omo, G., Müller, M., Paiva, V. H., Metzger, B., Neves,

V., Navarro, J., Karris, G., Xirouchakis, S., Cecere, J. G., Zamora-López, A., … Ramos, R.

(2023). Methods to detect spatial biases in tracking studies caused by differential

representativeness of individuals, populations and time. *Diversity and Distributions*,

29(1), 19–38.

Müller, K., & Bryan, J. (2020). *here: A Simpler Way to Find Your Files* (1.0.1) [Computer

software]. https://cran.r-project.org/web/packages/here/index.html

Nicoll, M. A. C., Nevoux, M., Jones, C. G., Ratcliffe, N., Ruhomaun, K., Tatayah, V., & Norris, K.

(2017). Contrasting effects of tropical cyclones on the annual survival of a pelagic

494  seabird in the Indian Ocean. *Global Change Biology*, *23*(2), 550–565.

495  https://doi.org/10.1111/gcb.13324

496 Ozsanlav-Harris, L., Griffin, L. R., Weegman, M. D., Cao, L., Hilton, G. M., & Bearhop, S. (2022).

497  Wearable reproductive trackers: Quantifying a key life history event remotely. *Animal*

498  *Biotelemetry*, *10*(1), 24. https://doi.org/10.1186/s40317-022-00298-8

499 Pebesma, E. (2018). Simple Features for R: Standardized Support for Spatial Vector Data. *The R*

500  *Journal*, *10*(1), 439. https://doi.org/10.32614/RJ-2018-009

501 Potts, J. R., & Börger, L. (2023). How to scale up from animal movement decisions to

502  spatiotemporal patterns: An approach via step selection. *Journal of Animal Ecology*,

503  *92*(1), 16–29. https://doi.org/10.1111/1365-2656.13832

504 Soriano-Redondo, A., Acácio, M., Franco, A. M. A., Herlander Martins, B., Moreira, F., Rogerson,

505  K., & Catry, I. (2020). Testing alternative methods for estimation of bird migration

506  phenology from GPS tracking data. *Ibis*, *162*(2), 581–588.

507  https://doi.org/10.1111/ibi.12809

508 Sumner, M. D., Wotherspoon, S. J., & Hindell, M. A. (2009). Bayesian Estimation of Animal

509  Movement from Archival and Satellite Tags. *PLoS ONE*, *4*(10).

510  https://doi.org/10.1371/journal.pone.0007324

511 Thiebot, J., & Pinaud, D. (2010). Quantitative method to estimate species habitat use from light-

512  based geolocation data. *Endangered Species Research*, *10*(1), 341–353.

513  https://doi.org/10.3354/esr00261

514 Trevail, A. M., Green, J. A., Sharples, J., Polton, J. A., Miller, P. I., Daunt, F., Owen, E., Bolton, M.,

515  Colhoun, K., Newton, S., Robertson, G., & Patrick, S. C. (2019). Environmental

heterogeneity decreases reproductive success via effects on foraging behaviour.

Proceedings of the Royal Society B: Biological Sciences, 286(1904), 20190795.

https://doi.org/10.1098/rspb.2019.0795

Trisovic, A., Lau, M. K., Pasquier, T., & Crosas, M. (2022). A large-scale study on research code

quality and execution. *Scientific Data, 9*(1), 60. https://doi.org/10.1038/s41597-022-

01143-6

Wickham, H. (2014). Tidy Data. *Journal of Statistical Software, 59*(10).

https://doi.org/10.18637/jss.v059.i10

Wickham, H., Averick, M., Bryan, J., Chang, W., McGowan, L., François, R., Grolemund, G.,

Hayes, A., Henry, L., Hester, J., Kuhn, M., Pedersen, T., Miller, E., Bache, S., Müller, K.,

Ooms, J., Robinson, D., Seidel, D., Spinu, V., … Yutani, H. (2019). Welcome to the

Tidyverse. *Journal of Open Source Software, 4*(43), 1686.

https://doi.org/10.21105/joss.01686

Wilmers, C. C., Nickel, B., Bryce, C. M., Smith, J. A., Wheat, R. E., & Yovovich, V. (2015). The

golden age of bio-logging: How animal- borne sensors are advancing the frontiers of

ecology. *Ecology, 96*(7), 1741–1753. https://doi.org/10.1890/14-1401.1

532