Aging modulates the effects of scene complexity on visual search and target selection in virtual environments

Isaiah J. Lachica[1], Aniruddha Kalkar[2], and James M. Finley[1,3,4]*

[1]Division of Biokinesiology and Physical Therapy, University of Southern California, Los Angeles, 90033, USA

[2]Department of Computer Science, University of Southern California, Los Angeles, 90089, USA

[3]Neuroscience Graduate Program, University of Southern California, Los Angeles, 90089, USA

[4]Department of Biomedical Engineering, University of Southern California, Los Angeles, 90089, USA

*Corresponding Author

Contact information of the corresponding author:

Email Address: jmfinley@usc.edu

Mailing Address: USC BKN/PT, 1540 Alcazar St, CHP 155, Los Angeles, CA, 90033

Phone Number: 323-442-4837

Fax Number: 323-442-1515

Keywords: virtual reality, visual complexity, aging, visual search, target selection, cognition

Number of figures: 5

Number of tables: 3

Abstract

Processing task-relevant visual information is important for many everyday tasks. Prior work demonstrated that older adults are more susceptible to distraction by salient task-irrelevant stimuli, leading to less efficient visual search. However, these studies often used simple stimuli, and less is known about how aging influences visual attention in environments more representative of real-world complexity. Here, we test the hypothesis that aging impacts how the visual complexity of the environment influences visual search. Young and older adults completed a virtual reality-based visual search task in environments with increasing visual complexity. As visual complexity increased, all participants exhibited longer times to complete the task which resulted from increased time transferring gaze from one correct target to the next and increased delay between when correct targets were fixated and selected. The increase in time to completion can also be attributed to longer times spent re-fixating task-relevant objects and fixating task-irrelevant objects. These changes in visual search and target selection with increasing visual complexity were greater in older adults and working memory capacity was associated with multiple performance measures in the visual search task. These findings suggest that visual search performance could be integrated into assessments of working memory in dynamic environments.

Introduction

Selecting and processing relevant visual information from the environment is vital for planning and executing everyday tasks (1–4). For example, when walking in environments where precision stepping is required, we use vision to plan routes, step over obstacles, or step onto safe footholds (5–7). However, the ability to properly direct vision to relevant visual stimuli appears to be impaired in older adults. While walking, older adults appear to be more easily distracted by future threats on their path than young adults as they shift their gaze away from the current stepping target to the next before completing the step (8,9). This gaze behavior can be problematic as it can result in greater stepping errors (10). Understanding how we select and process visual information in the environment and how these processes change with aging is crucial for preventing potentially injurious behaviors.

Natural and human-made environments are filled with visual stimuli that may be relevant or irrelevant for guiding future actions. Which visual stimuli are selected and processed may depend on how overt visual attention is directed. The control of visual attention has been prominently described as a balance between bottom-up and top-down processes. Bottom-up processes emphasize saliency, a characteristic of visual stimuli based on low-level visual features such as contrast and luminance (11), which makes highly salient stimuli "pop out" of a scene and capture attention automatically. In contrast, top-down processes control visual attention based on cognitive processes that prioritize factors such as task demands, prior knowledge, or gist of realistic scenes (12–15). Task-dependent trade-offs between these processes enable attention to be directed based on top-down factors when performing a task or by highly salient stimuli when necessary. However, the balance between bottom-up and top-down control appears to rely on an individual's cognitive capacity, which is affected by normal aging (16,17).

Older adults appear more susceptible to distraction by irrelevant visual stimuli than young adults due to age-related changes in their cognition, particularly in their ability to exert top-down inhibition (18–20). These effects prevent older adults from suppressing the automatic capture of

attention by salient task-irrelevant stimuli, negatively affecting their performance in visually

demanding tasks (21–24). Impaired capacity for inhibition can also lead to task-irrelevant

information being encoded into working memory at the cost of task-relevant information (22,25).

However, prior studies on age-related changes in visual search used simple visual scenes

composed of arbitrarily selected shapes and letters. It is unclear whether these age-related effects

on visual attention extend to performing tasks in scenes more closely reflecting the visual

complexity in everyday visual search.

The Trail Making Test (26) is a visual search task commonly used to assess cognitive

domains such as visual attention, working memory, and inhibition (27–29). It is typically

implemented in a pen-and-paper format with numbers and letters as search targets and

completion time as the primary outcome measure. Performance in the test appearing to decline

with age as older adults tend to take more time to complete the task (30–34). Recent attempts

have been made to improve the generalizability of the test by transforming it into a three-

dimensional pointing task in virtual reality (VR) (35). Studies have also supplemented completion

time with eye-tracking measures, such as average fixation time and number of fixations, to

improve the interpretability of test results and identify differences in experimental (36) and

neurological (37,38) conditions. However, the context in which people search for targets in both

test versions does not reflect the visual complexity of search targets or the level of distraction

present in everyday visual search. Questions remain on how increasing visual complexity

influences visual search in young and older adults.

We aimed to determine how aging-related differences in cognition influence visual search

and target selection in increasingly complex virtual environments. Participants completed a

custom-designed VR-based visual search task based on the Trail Making Test-B in three levels

of increasing visual complexity (39). To determine the influence of visual attention on task

performance, we recorded eye movements from which we calculated the time between fixations

on correct targets, average and total fixation times, number of fixations, and the saliency of fixated

regions. We also determined how the actions involved in target selection using a laser pointer

influenced task completion time by measuring the number of selection errors and the delay

between fixating and selecting a correct target. Additionally, all participants completed

assessments of global cognition, short-term memory, working memory, and inhibitory capacity.

We hypothesized that as the complexity of the visual scene increased, participants would take

longer to complete the task because attention would be attracted by task-irrelevant stimuli, leading

to a reduced capacity to encode correct targets in working memory. Specifically, all participants

would be more prone to re-fixating search targets and fixating on salient, task-irrelevant

distractors, leading to longer times between fixations on correct targets. In addition, we

hypothesized that this performance decline would be greater in older adults due to aging-related

impairments in their cognition.

Methods

Participants. 15 young (9 female, age: 27.7 ± 3.33 years) and 15 older adults (9 female,

age: 71.8 ± 4.46 years) with normal or corrected-to-normal vision participated in the study. Data

from two older adults were excluded due to hardware/software issues. We conducted a sample

size calculation for mixed-effects regression models using GLIMMPSE (40) and used pilot data to

estimate the variance in our dependent variables (task completion time, total task-relevant fixation

time, and saliency of fixated regions). We found the largest sample size estimate across our three

dependent variables and determined that a sample size of 26 (13 for each age group) was needed

for a target power of 0.80, assuming a medium effect size of 0.45. All study procedures were

reviewed and approved by the University of Southern California's Institutional Review Board. All

participants provided written informed consent before participating and were provided monetary

compensation for their time. All aspects of the study conformed to the principles described in the

Declaration of Helsinki.

Experimental protocol. All participants completed the paper-based Trail Making Test-B

(26) to allow for comparison with their performance in the VR-based visual search task.

Additionally, the participants completed a battery of tests selected to assess different domains of

cognition including the Montreal Cognitive Assessment (41) for global cognition, the Corsi task

(42) for short-term memory, the Backwards Corsi task (43) for working memory, and the Flanker

(44) task for the ability to inhibit the direction of attention to task-irrelevant stimuli. The Montreal

Cognitive Assessment was administered on paper while the rest of the cognitive assessments

were completed on a computer using Psytoolkit (45,46).

After completing the cognitive assessments, the participants completed three

familiarization trials of the visual search task. These trials were completed in virtual environments

with only the search targets present in front of a blank background to emphasize the identity of

the search targets. In the first familiarization trial, the experimenter guided the participant through

a single repetition of the task to provide a clear description of the task goal, the visual and auditory

feedback that they will encounter, and the search target sequence. The guided familiarization trial

was followed by two trials where participants completed the task independently and were only

provided feedback by the experimenter at the end. After the familiarization trials, the participants

completed 30 trials of the visual search task presented in three sets of 10 trials, each

corresponding to one of three visual complexity levels. Only the data from the last five trials at

each visual complexity level were processed and analyzed to account for potential learning

effects.

VR task. All participants completed a VR visual search task (Fig. 1a) which we based on

the principles of the Trail Making Test-B. We particularly incorporated the visual attention, working

memory, and inhibition (27–29) components of the Trail Making Test-B into our VR task.

Participants were instructed to search for and select targets alternating between letters of the

alphabet and animals whose names start with those letters in ascending order (A, Ant, B, Butterfly,

C, Chickens, D, Dog, E, Eagle, F, and Frogs). The search targets were positioned randomly for

each trial in regions of the virtual environments where they would not be overly distinct from the

background, such as across the sky for the letters and at ground level for the objects. The

participants viewed the virtual environments using the HTC Vive Pro Eye (HTC, New Taipei,

Taiwan) head-mounted display and selected targets using an HTC Vive Controller. The head-

mounted display had a 110-degree field of view with a resolution of 1440x1600 pixels per eye

(2880x1600 pixels combined). A laser pointer extended from the top of the controller in the virtual

environment, and participants selected targets by aiming the laser at the center of the target and

pulling the trigger on the controller. All participants were informed that they could freely move their

heads in all directions. Visual and auditory feedback were provided to indicate whether the

selected target was correct. Specifically, the participants heard a bell sound and saw a "Correct!"

text appear in the environment when the correct target was selected. In contrast, the participants

heard a buzzer sound and saw a "Try Again!" text appear when they selected an incorrect target

or when they did not select the correct target properly (laser not aimed at the center of the target).

Figure 1. VR visual search task. (*a*) Single frames from representative gameplay recordings of each visual complexity level. Visual complexity was increased by adding visual distractors in the foreground and background in the form of vehicles, structures, plants, and agriculture-related inanimate objects to dissociate them from the search targets, which were the only letters and animals in the environment. (*b*) Swarm plot comparing feature congestion of each visual complexity level with each data point representing a frame from representative gameplay recordings. *Indicates significant difference between High and Low visual complexity levels and High and Medium visual complexity levels. +Indicates significant difference between Medium and Low visual complexity levels.

The participants completed the visual search task in virtual environments with three levels of increasing visual complexity (Fig. 1a). The sequence of complexity levels was pseudo-randomized such that five participants in both young and older adult groups started with the low visual complexity level, another five with the medium visual complexity level, and the remaining five with the high visual complexity level. The visual complexity of the environment was manipulated by adding visual distractors in the foreground and background. These visual distractors came strictly in the form of vehicles, structures, plants, and agriculture-related inanimate objects to dissociate them from the search targets, which were the only letters and animals in the environment. Visual complexity was measured using feature congestion (47), which

quantifies the distribution of low-level visual features of an image, including color, edge

orientation, and luminance, as a single scalar measure with higher values indicating a more

complex image. To determine if the modifications to the virtual environments produced increasing

levels of visual complexity, we applied the feature congestion method to every frame of a

representative gameplay recording from each visual complexity level (using Rosenholtz et al.'s

Matlab implementation: https://dspace.mit.edu/handle/1721.1/37593). Feature congestion

increased monotonically across visual complexity levels (Fig. 1b; $F(2,2349) = 22550$, $p < 0.001$).

Post-hoc tests indicate that the high visual complexity level had greater feature congestion than

the medium (Bonferroni-corrected $p < 0.001$) and low (Bonferroni-corrected $p < 0.001$) visual

complexity levels. In addition, feature congestion was higher in the medium visual complexity level

than in the low (Bonferroni-corrected $p < 0.001$).

Data collection and processing. We collected the timing of each trigger press as

participants selected objects. To quantify each participant's overall performance, we calculated

task completion time, which is defined as the difference between the time when the trial started

and when the last correct target was selected. This measure of overall task performance is

equivalent to the primary outcome measure of the paper-based versions of the Trail Making Test.

Task completion time was calculated for every trial and reported as an average of the last five

trials at each visual complexity level for each participant.

We collected eye and head movement data at 90 Hz using eye trackers and an inertial

measurement unit built into the HTC Vive Pro Eye. The eye trackers were calibrated following a

5-point calibration process provided by HTC. Additionally, video recordings of the participants'

first-person point of view were recorded at 60 Hz for each trial using NVIDIA Shadowplay (NVIDIA,

Santa Clara, CA, USA). All data processing was performed using a custom script in MATLAB

R2022a (Mathworks, Natick, MA, USA). Horizontal and vertical eye-in-head angles were

calculated from the unfiltered raw eye movement data and were combined with the horizontal and

vertical rotations of the head to compute gaze angles. The gaze angles were then time-

synchronized with the video recordings. Since the video recordings and the gaze angles did not

have the same sampling rate, the gaze angles were then interpolated at each video recording

frame.

As visual processing primarily occurs during periods of fixation(48,49), it was important to

identify which samples qualified as such to determine how visual attention was deployed. To do

so, we first computed horizontal and vertical gaze angular velocities by differentiating the

interpolated gaze angles with respect to the time between video frames. We then identified

fixations using a combination of a simple velocity threshold and a minimum fixation duration

threshold. First, we categorized samples as fixations if their horizontal or vertical gaze angular

velocity was less than 100 degrees per second(50). We computed gaze vectors for these fixations

in the virtual environment with their origins set as the head position in the virtual environment and

their direction determined by the gaze angles. We then recorded the names and locations of the

objects or regions that the gaze vectors intersected in the virtual environment. We collapsed

consecutive fixations to the same object or region together, calculated their durations, and

removed fixations that were less than 60 milliseconds(51). We then classified a fixation as task-

relevant if they were directed toward one of the search targets and task-irrelevant if they were

directed toward the visual distractors or any other region in the environment. We further classified

task-relevant fixations as either the first fixation on a search target in a trial or a re-fixation, which

we define as fixations on search targets that were previously fixated.

We computed several measures of gaze-related task performance to capture how overt

visual attention varied across conditions and between groups. We calculated the average time

between fixations on correct targets by recording the time intervals from the end of a fixation on

one correct target to the beginning of a fixation on the next correct target and then averaging

these times within a trial. The average time between fixations on correct targets includes the

saccade times between targets and any fixation time on incorrect targets. We also recorded the

number of fixations on task-irrelevant objects and the number of re-fixations on task-relevant

objects. Additionally, we calculated the average time spent on first fixations on task-relevant

objects, re-fixations on task-relevant objects, and fixations on task-irrelevant objects by recording

the time intervals from the start of a fixation on an object to the end of a fixation on the same

object and averaging these times within a trial by fixation category. We similarly calculated the

total time spent on first fixations on task-relevant objects, re-fixations on task-relevant objects,

and fixations on task-irrelevant objects by recording the time intervals from the start of a fixation

on an object to the end of fixation on the same object and finding the sum of these times within a

trial by fixation category. These gaze-related task performance measures were calculated for

every trial and reported as an average of the last five trials at each visual complexity level for each

participant.

We generated saliency maps from each frame of the video recordings of the participants'

first-person point of view during the task using the original Itti, Koch, and Neibur(52) algorithm as

implemented   by   Harel   (J.   Harel,   A   Saliency   Implementation   in   MATLAB:

http://vision.caltech.edu/~harel/share/gbvs.php). Specifically, each video frame was decomposed

into feature maps of its low-level visual features, which included color, orientation, and intensity.

These feature maps were combined into a saliency map with corresponding scalar values for

each pixel. These scalar saliency values were then converted to percentile ranks(53,54), with

100% indicating the most salient pixel and 0% the least salient pixel in the video frame. We

recorded the percentile rank of each fixated region and then calculated saliency by averaging

these recorded percentile ranks within a trial. We calculated saliency for every trial and reported

it as an average of the last five trials at each visual complexity level for each participant.

We also recorded information on the objects selected at every trigger press, which

included the identity of the selected object, the location where the laser pointer was being aimed

in the virtual environment at the time of the trigger press, and whether the selection was correct.

We then calculated from the number of selection errors, defined as selecting an incorrect target

or misaiming (controller aimed outside the bounds of the correct target) when selecting a correct

target, and selection delay, which is the time interval between fixating a correct target and

successfully selecting it averaged within a trial. The number of selection errors and selection delay

were calculated for every trial and reported as an average of the last five trials at each visual

complexity level for each participant.

Statistical analysis. All statistical analyses were performed in R (R Project for Statistical

Computing) with the alpha value set at $p < 0.05$. Tests for normality and equal variances were

performed using the Shapiro-Wilk test and Levene's test with functions from the *stats* and *car*

packages, respectively. Welch's analysis of variance and pairwise Wilcoxon rank sum tests were

used to compare the feature congestion of each visual complexity level using the *stats* package

when assumptions of equal variance and normality were violated.

We fit linear mixed-effects models using the *lme4* package to test for the effects of age

group, visual complexity, and their interaction on the following dependent variables: task

completion time, average time between fixations on correct targets, average and total first fixation

time on task-relevant objects, number of re-fixations on task-relevant objects, average and total

re-fixation time on task-relevant objects, number of fixations on task-irrelevant objects, average

and total fixation time on task-irrelevant objects, saliency, number of selection errors, and

selection delay. We used the *lmerTest* package, which uses Satterthwaite approximations for the

degrees of freedom, to test the null hypothesis that our model coefficients were zero. All models

included random intercepts for each participant to account for repeated measures. Lastly, we

performed post-hoc Bonferroni-corrected pairwise comparisons using the *emmeans* package

when significant main effects or interactions, particularly differences between age groups within

visual complexity levels, were found.

We compared cognitive assessment scores between age groups to determine the effect

of age on various domains of cognition using functions from the *stats* package. Assumptions of

normality and equal variance were tested using the Shapiro-Wilk and Levene's tests, respectively.

The Wilcoxon rank sum test was used when the normality assumption was violated; otherwise, a

two-sample t-test was used.

To determine if our VR visual search task was able to mimic the paper-based Trail Making

Test-B, we fit a multiple linear regression model using the *stats* package to identify any

relationships between performances in both tasks. Specifically, we used Trail Making Test-B

completion time as the response and VR task completion time and its interaction with visual

complexity level as the predictors.

We fit three multiple linear regression models to test for associations between

performance in the task and various cognitive domains. In our first model, we used VR task

completion time in the high visual complexity level as our response and scores on the Montreal

Cognitive Assessment, Corsi Block task, Backwards Corsi Block task, and the Flanker task as

predictors. In our second model, we used the number of re-fixations on task-relevant objects as

our response and scores on the Corsi Block task and the Backwards Corsi Block task as

predictors. Finally, we used the number of fixations on task-irrelevant objects as our response

and the Flanker task score as the predictor in our third model. We used the performance metrics

recorded from the high visual complexity level as the range of values observed at this level

covered those found at the lower visual complexity levels. We also included age as a predictor in

all three models to control for age-related deficits in performance.

Results

Task completion times. All participants took longer to complete the task as the visual

complexity of the environment increased, and this effect was greatest in older adults (Fig. 2). We

found main effects of age group ($F(1,26) = 49.19$, $p < 0.001$) and visual complexity level ($F(2,52)$

$= 83.36$, $p < 0.001$) on task completion time. We also found an interaction between age group

and visual complexity level ($F(2,52) = 9.50$, $p < 0.001$). Compared to the young adults, the older

adults took 8.9 seconds longer in the low complexity level ($p = 0.002$), 10.7 seconds longer in the

medium complexity level ($p < 0.001$), and 17.7 seconds longer in the high complexity level ($p <$

0.001) to complete the task. In addition, the young adults took 8.2 seconds longer in the high

versus low visual complexity (p < 0.001) and 7.5 seconds longer in the high versus medium visual

complexity (p < 0.001), while the older adults took 17.0 seconds longer in the high versus low

visual complexity (p < 0.001) and 14.4 seconds longer in the medium versus high visual

complexity (p < 0.001) to complete the task.

309
Figure 2. Effect of age group and visual complexity on VR task completion times. *Indicates
significant difference between age groups.

Time between fixations on correct targets. Several performance-related factors could

explain the changes in task completion time with complexity level and differences in completion

time between groups. For example, participants may have taken longer to complete the task in

levels with higher visual complexity because they spent more time searching for correct targets.

We calculated the average time between fixations on correct targets as the time interval from the

end of a fixation on one correct target to the beginning of a fixation on the next correct target and

found main effects of age group (F(1,26) = 42.13, p < 0.001) and visual complexity (F(2,52) =

83.69, p < 0.001; Fig 3a). We also found an interaction between age group and visual complexity

(F(2,52) = 10.03, p < 0.001). Compared to young adults, older adults spent 0.6 seconds longer in

the medium complexity level ($p < 0.001$) and 1.0 seconds longer in the high visual complexity

level ($p < 0.001$) between fixations on correct targets. The effect of visual complexity level was

larger in older adults, with young adults spending 0.5 seconds longer in the high versus low

complexity level ($p < 0.001$) and in the high versus medium complexity level ($p < 0.001$), while the

older adults spent 1.0 seconds longer in the high versus low complexity level ($p < 0.001$) and in

the high versus medium complexity level ($p < 0.001$) on average between fixations on correct

targets.

Figure 2. Effect of age group and visual complexity level on gaze behavior. (*a*) Average time between fixations on correct targets, (*b*) average task-relevant first fixation time, (*c*) total task-relevant first fixation time, (*d*) number of task-relevant re-fixations, (*e*) average task-relevant re-fixation time, (*f*) total task-relevant re-fixation time, (*g*) number of task-irrelevant fixations, (*h*) average task-irrelevant fixation time, and (*i*) total task-irrelevant fixation time. *Indicates significant difference between age groups.

The increase in task completion time in more complex environments may also stem from changes in gaze behavior, such as an increase in fixations on task-relevant versus task-irrelevant objects. We classified fixations into three categories. We considered the first fixation on task-relevant objects as a measure that potentially reflects when participants encoded information about these objects, such as location, in memory. We then identified re-fixations on task-relevant

objects as a potential indicator that participants did not recall the location of a given object. Lastly,

we measured fixations on task-irrelevant objects as a measure of distractibility. We separately

quantified the average duration of each fixation type, total fixation time, and the number of each

type of fixation in a trial.

First fixations on task-relevant objects. We found a main effect of age group on

average task-relevant first fixation time ($F(1,26) = 12.95$, $p = 0.001$, Fig. 3b), but there was no

significant effect of visual complexity level ($F(2,52) = 2.56$, $p = 0.087$) or interaction between age

group and visual complexity level ($F(2,52) = 1.47$, $p = 0.238$). Compared to young adults, older

adults spent 0.1 seconds longer on average on their first fixations on task-relevant objects. We

also found a main effect of age group on total task-relevant first fixation time ($F(1,26) = 13.23$, p

$= 0.001$, Fig. 3c) but not a main effect of visual complexity ($F(2,52) = 2.85$, $p = 0.067$) or an

interaction between age group and visual complexity on total ($F(2,52) = 1.43$, $p = 0.250$) task-

relevant first fixation times. Compared to young adults, older adults spent 1.3 seconds longer in

total on their first fixations on task-relevant objects.

Re-fixations on task-relevant objects. We calculated the number of re-fixations, the

average re-fixation time, and the total re-fixation time on task-relevant objects. We found a main

effect of age group ($F(1,26) = 35.20$, $p < 0.001$) and visual complexity ($F(2,52) = 68.21$, $p < 0.001$)

on the number of task-relevant re-fixations (Fig. 3d). We also found an interaction effect between

age group and visual complexity ($F(2,52) = 3.91$, $p = 0.026$). Compared to young adults, older

adults re-fixated task-relevant objects eight more times in the low complexity level ($p = 0.021$), 10

more times in the medium complexity level ($p = 0.002$), and 16 more times in the high complexity

level ($p < 0.001$). Additionally, the young adults re-fixated task-relevant objects 11 more times in

the high versus low complexity level ($p < 0.001$) and 10 more times in the high versus medium

complexity level ($p < 0.001$), while the older adults re-fixated task-relevant objects 18 more times

in the high versus low complexity level ($p < 0.001$) and 15 more times in the high versus medium

complexity level ($p < 0.001$).

We found a main effect of age group on the average task-relevant re-fixation time ($F(1,26)$

= 13.58, p = 0.001; Fig. 3e) but did not find a main effect of visual complexity ($F(2,52)$ = 1.22, p =

0.304) or an interaction effect between age group and visual complexity ($F(2,52)$ = 0.01, p =

0.994). Compared to the young adults, the older adults spent 0.1 seconds longer on average on

their re-fixations on task-relevant objects.

We found main effects of age group ($F(1,26)$ = 40.20, p < 0.001) and visual complexity

($F(2,52)$ = 47.42, p < 0.001) on the total task-relevant re-fixation time (Fig. 3f). We also found an

interaction effect between age group and visual complexity ($F(2,52)$ = 5.97, p = 0.005). Compared

to the young adults, the older adults spent 6.1 seconds longer in the low complexity level (p =

0.005), 7.8 seconds longer in the medium complexity level (p < 0.001), and 11.2 seconds longer

in the high complexity level (p < 0.001) in total on their task-relevant re-fixations. In addition, young

adults spent 4.5 seconds longer in the high versus low complexity level (p = 0.001) and 3.7

seconds longer in the high versus medium complexity level (p = 0.011), while older adults spent

9.6 seconds longer in the high versus low complexity level (p < 0.001) and 7.1 seconds longer in

the high versus medium complexity level (p < 0.001) on their total task-relevant re-fixation times.

Fixations on task-irrelevant objects. We separately quantified the number of fixations,

average fixation time, and total fixation time on task-irrelevant objects. We found main effects of

age group ($F(1,26)$ = 29.97, p < 0.001) and visual complexity ($F(2,52)$ = 166.40, p < 0.001) on the

number of task-irrelevant fixations (Fig. 3g). We also found an interaction effect between age

group and visual complexity ($F(2,52)$ = 23.16, p < 0.001). Compared to the young adults, the older

adults fixated on task-irrelevant objects 14 more times in the high complexity level (p < 0.001). In

addition, the young adults fixated on task-irrelevant objects nine more times in the high versus

low complexity level (p < 0.001) and eight more times in the high versus medium complexity level

(p < 0.001) while the older adults fixated on task-irrelevant objects 20 more times in the high

versus low complexity level (p < 0.001) and 18 more times in the high versus medium complexity

level (p < 0.001).

We found a main effect of age group ($F(1,26) = 4.42$, $p = 0.045$) on the average task-irrelevant fixation time (Fig. 3h) as the older adults spent 0.01 seconds longer on average on their fixations on task-irrelevant objects. We also found a main effect of visual complexity ($F(2,52) = 14.57$, $p < 0.001$) as all participants spent 0.02 seconds longer in the high versus low complexity ($p < 0.001$) and in the high versus medium complexity ($p < 0.001$) on their average task-irrelevant fixation time. We did not find an interaction effect between age group and visual complexity ($F(2,52) = 2.16$, $p = 0.125$).

We found main effects of age group ($F(1,26) = 26.36$, $p < 0.001$) and visual complexity ($F(2,52) = 119.33$, $p < 0.001$) on the total task-irrelevant fixation time (Fig. 3i). We also found an interaction effect between age group and visual complexity level ($F(2,52) = 24.17$, $p < 0.001$). Compared to the young adults, the older adults spent 3.7 seconds longer on their total task-irrelevant fixation time in the high visual complexity level ($p < 0.001$). In addition, the young adults spent 1.8 seconds longer in the high versus low complexity level ($p < 0.001$) and 1.7 seconds longer in the high versus medium complexity level ($p < 0.001$), while the older adults spent 4.8 seconds longer in the high versus low complexity level ($p < 0.001$) and 4.3 seconds longer in the high versus medium complexity level ($p < 0.001$) in total on their task-irrelevant fixations.

Saliency of fixated regions. Although both young and older adults increased their fixations on task-irrelevant objects as the visual complexity of the environment increased, these fixations were not towards more salient regions or objects (Fig. 4). We quantified the saliency of the fixated regions on the visual scene using the Itti, Koch, and Neibur model of saliency-based visual attention(52) and found main effects of age group ($F(1,26) = 10.82$, $p = 0.003$) and visual complexity ($F(2,52) = 60.37$, $p < 0.001$). We also found an interaction between age group and visual complexity ($F(2,52) = 9.27$, $p < 0.001$). Young adults fixated more salient regions than older adults in the highest visual complexity level ($p < 0.001$). In addition, young adults fixated more salient regions in the low versus the medium ($p < 0.001$) and high ($p < 0.001$) complexity levels, while older adults fixated more salient regions in the low versus the medium ($p < 0.001$) and high

419   (*p* < 0.001) complexity levels as well as in the medium versus the high (*p* = 0.015) complexity

420   level.

421
422   **Figure 3.** Effect of age group and visual complexity on the saliency of fixated regions. *Indicates
423   significant difference between age groups.

424   **Number of selection errors.** Participants may have also taken longer to complete the

task with increasing visual complexity due to changes in their target selection strategy. To this

end, we quantified target selection errors, defined as selecting an incorrect target or misaiming

(laser pointed off-center) when selecting a correct target (Fig. 4a). We found a main effect of age

group on the number of selection errors ($F(1,26) = 6.02$, *p* = 0.021), with older adults committing

more selection errors than younger adults. We also found a main effect of visual complexity

($F(2,52) = 3.25$, *p* = 0.047) on the number of selection errors; however, post-hoc tests found no

differences between visual complexity levels. We did not find an interaction effect between age

group and visual complexity ($F(2,52) = 2.05$, *p* = 0.140) on the number of selection errors.

Figure 4. Effect of age group and visual complexity level on (*a*) the number of selection errors and (*b*) the time between fixating and selecting a correct target. *Indicates significant difference between age groups.

Selection delay. Another way to investigate possible influences of changes in target selection on task completion time is to quantify selection delay, defined as the average time interval between fixating a correct target and successfully selecting it (Fig. 4b). We found main effects of age group ($F(1,26) = 34.08$, $p < 0.001$) and visual complexity ($F(2,52) = 11.47$, $p < 0.001$) on selection delay. We also found an interaction effect between age group and visual complexity ($F(2,52) = 4.39$, $p = 0.017$) on selection delay. Compared to the young adults, the older adults selected the correct target 0.5 seconds slower in the medium complexity level ($p = 0.001$) and 0.6 seconds slower in the high complexity level ($p < 0.001$). In addition, older adults selected the correct target 0.5 seconds slower in the high versus low complexity level ($p < 0.001$) and 0.3 seconds slower in the high versus medium complexity level ($p < 0.001$).

Cognitive assessment scores. Age-related differences were observed in several standard cognitive assessments (Table 1). Compared to young adults, older adults had lower global cognition according to their Montreal Cognitive Assessment(41) scores (Wilcoxon rank sum test $p = 0.044$) and poorer short-term memory according to their Corsi Block task(42) results (Wilcoxon rank sum test $p = 0.001$). However, no differences between age groups were found in

452 working memory (two sample t-test *p* = 0.229) as tested using the Backwards Corsi Block task(43)

453 or inhibition (two sample t-test *p* = 0.620) with the Flanker task(44).

454 **Table 1.** Cognitive assessment scores (Mean ± SD) of young and older adults with the
455 corresponding p-value from their comparisons using two-sample t-tests and Wilcoxon rank sum
456 tests. *Indicates significant differences between age groups.

Cognitive Assessment	Cognitive Domain	Young Adults (Mean ± SD)	Older Adults (Mean ± SD)	P-value
Montreal Cognitive Assessment	Global Cognition	28 ± 2	27 ± 3	0.0440*
Corsi Block Task	Short Term Memory	6 ± 1	5 ± 1	0.0014*
Backwards Corsi Block Task	Working Memory	5 ± 1	5 ± 2	0.229
Flanker Task	Inhibition	5 ± 70.17 ms	-10.77 ± 95.82 ms	0.6203

Trail Making Test-B and VR visual search task. As we designed our VR visual search

task to mimic several aspects of the paper-based Trail Making Test-B, we were also interested in

determining if the outcomes of these assessments were correlated. As such, we fit a multiple

linear regression model to determine if performance in our VR visual search task was related to

performance in the paper-based Trail Making Test-B (Table 2). In our model, we used Trail Making

Test-B completion time as the response and VR task completion time and its interaction with

visual complexity level as predictors (F(3,80) = 5,61, *p* = 0.002, *Adj. R2* = 0.143). Trail Making

Test-B completion time was positively correlated with VR task completion time (β = 1.254, *p* <

0.001), but this correlation decreased in the high visual complexity level (β = -0.400, *p* = 0.029).

Table 2. Results of the multiple linear regression testing for associations between Trail Making
Test-B completion time and VR task completion time. Performance in the low visual complexity
level was used as the reference.

Predictor	β Estimate	Standard Error	P-value
VR Task Completion Time	1.254	0.324	< 0.001
VR Task Completion Time:Medium Visual Complexity Level	-0.080	0.171	0.641
VR Task Completion Time:High Visual Complexity Level	-0.400	0.180	0.029

VR visual search task performance and cognitive assessments. Performance in the

visual search task could have been influenced by various cognitive domains such as short-term

memory, working memory, and inhibitory capacity. As such, we fit a multiple linear regression

model to determine if scores on the Montreal Cognitive Assessment, Corsi Block task, Backwards

Corsi Block task, and the Flanker task are associated with VR task completion time in the high

visual complexity level (Table 3). Additionally, we included age as a predictor to control for

potential age-related performance deficits. We specifically chose the high visual complexity level

since its range of completion times covered those observed in the lower visual complexity levels.

We found significant relationships between VR task performance and cognitive assessment

scores ($F(5,22)$ = 26.14, p < 0.001, $Adj. R2$ = 0.82). Specifically, VR task completion times were

lower in participants with higher scores on the Montreal Cognitive Assessment (β = -1.42, p =

0.005) and Backwards Corsi Block task (β = -2.70, p = 0.002). Additionally, VR task completion

times increased with age (β = 0.296, p < 0.001).

Table 3. Results of multiple linear regressions testing for associations between performance
metrics in the high visual complexity level and cognitive assessment scores. Age was added as
a predictor to control for age-related performance deficits. *Indicates p < 0.05.

Response	Predictor: β Estimate (Standard Error)				
	Montreal Cognitive Assessment	Corsi Block Task	Backwards Corsi Block Task	Flanker Task	Age
VR task completion time	-1.42 (0.45)*	-0.02 (1.21)	-2.70 (0.79)*	-0.02 (0.01)	0.30 (0.05)*
Number of task-relevant re-fixations		-0.44 (1.31)	-3.96 (0.84)*		0.27 (0.06)*
Number of task-irrelevant fixations				-0.02 (0.02)	0.32 (0.06)*

Gaze behavior and cognitive assessments. Gaze behavior in the task could also act as

internal measures of certain cognitive domains. For instance, the number of re-fixations on task-

relevant objects could reflect a participant's short-term and working memory capacity. To test this,

we fit a multiple linear regression model to determine if scores in the Corsi Block and Backwards

Corsi Block tasks are related to the number of re-fixations on task-relevant objects in the high

visual complexity level (Table 3). We included age as a predictor to control for age-related

performance deficits and chose to use gaze behavior measurements from the high visual

complexity level since its range of values covered those observed in the lower visual complexity

levels. Our model explained the data well ($F(3,24) = 28.99$, $p < 0.001$, *Adj. R2* = 0.76) and

indicated that the number of re-fixations on task-relevant objects decreased as Backwards Corsi

Block score increased (β = -3.96, $p < 0.001$) and increased with age (β = 0.268, $p < 0.001$).

Additionally, the number of fixations on task-irrelevant objects could reflect a participant's

inhibitory capacity. To test this, we fit a separate multiple linear regression model to determine if

Flanker task scores are related to the number of fixations on task-irrelevant objects in the high

visual complexity level (Table 3). We included age as a predictor to control for age-related

performance deficits and chose to use gaze behavior measurements from the high visual

complexity level since its range of values covered those observed in the lower visual complexity

levels. From this model ($F(2,25) = 17.58$, $p < 0.001$, *Adj. R2* = 0.55), we found that while the

number of fixations on task-irrelevant objects increased with age (β = 0.323, $p < 0.001$), it was

not associated with scores on the Flanker task (β = -0.019, $p = 0.218$).

Discussion

We used a VR-based visual search task to determine if increasing the visual complexity

of a three-dimensional search environment would lead to changes in performance and if this effect

is modulated by age. Additionally, we sought to understand which cognitive domains were

associated with performance in VR-based visual search task. For both age groups, increasing the

visual complexity of the virtual search environments led to longer task completion times. This

effect was due, in part, to the fact that all participants spent more time between fixations on correct

targets as they increased their re-fixations on task-relevant and fixations on task-irrelevant

objects. We also found that all participants took more time to select a correct target after fixating

them in levels with higher visual complexity, which likely contributed to the longer task completion

times. Each of these effects was greater in older adults. However, increased completion time did

not appear to be influenced by saliency as both groups increasingly fixated on less salient regions

as the visual complexity of the environment increased. Lastly, we found that short-term and working memory capacities explained the variability in performance across participants.

As the complexity of the virtual environments increased, all participants spent more time completing the search task because they spent more time searching for correct targets, as demonstrated by the increase in the time interval between fixations on correct targets. These results are consistent with those classically found in simple conjunction search paradigms with simple stimuli composed of arbitrarily selected shapes and colors. When participants searched for stimuli that shared features with distractors, search times increased as the number of distractors in the visual display increased(55). We also found that the effect of visual complexity on search performance was greater in older adults than in young adults. Similar age-related differences in search performance have been demonstrated using simple conjunction search paradigms(56–58) and paradigms using more complex stimuli. For example, when searching for and responding to a star-shaped stimulus in a vehicle's digital dashboard, older adults demonstrated longer search times as the visual complexity of the display increased than young adults(59). Similar results were observed when comparing search times for specific face configurations(60). It appears then that the influence of visual complexity, age, and their combination on search performance generalizes from two-dimensional displays to more complex, three-dimensional virtual environments.

The increase in suboptimal gaze behavior demonstrated by all participants with increasing visual complexity could have also contributed to the changes in visual search performance. One such suboptimal gaze behavior is the increase in the number of and total time on task-irrelevant fixations with increasing visual complexity, which was found to be greater in older adults. Increased fixations on task-irrelevant objects could be due to a decreased capacity for top-down suppression of irrelevant stimuli with increasing visual complexity of search displays(61). Older adults are also more susceptible to distraction by task-irrelevant information than young adults in various two-dimensional visual-perceptual tasks(21–24,62) and this has been attributed to

cognitive impairments, particularly with deficiencies in inhibitory capacity(18,19). However,

performance in the Flanker task, a common assessment for inhibitory capacity, was not

associated with the number of fixations on task-irrelevant objects and did not differ between age

groups in our study. While all participants, particularly older adults, were more prone to directing

their attention towards task-irrelevant distractors in higher visual complexity levels in our VR visual

search task, it did not seem to be related to their inhibitory capacity.

Another suboptimal gaze behavior observed from all participants at higher visual

complexity levels was an increase in the number of and total time on task-relevant re-fixations,

with this effect being greater in older than young adults. We also found that scores on the

Backwards Corsi Block task, a known test for working memory, were inversely associated with

the number of task-relevant re-fixations but did not differ between age groups. It has been

previously demonstrated that working memory processes and visual attention are tightly linked.

Particularly, increased distraction by task-irrelevant visual stimuli may interfere with encoding

task-relevant visual information, ultimately resulting in poor maintenance and retrieval from

working memory(25,63). As such, the increased distraction by task-irrelevant objects experienced

at higher visual complexity levels may have led to the greater re-fixations observed across all

participants.

While all participants became more prone to distraction by task-irrelevant stimuli as visual

complexity increased, this effect was not driven by the saliency of as the participants increasingly

fixated regions that have lower saliency values as the visual complexity of the virtual environments

increased. While prior studies showed that susceptibility to distraction during visual perception

tasks is greater in the presence of salient visual stimuli, particularly in older adults(21,23,62), this

effect appears to be subdued in more complex scenes as people weigh prior knowledge of or the

gist of the scene more than saliency(13–15). In our task, participants may have formed a gist of

each visual complexity level during practice and the initial five trials in a visual complexity level.

Specifically, they would have learned that the search environments are modeled after farms, the

animals are located naturally at ground level, and the letters are arbitrarily placed in the sky. The

emphasis on prior knowledge and gist instead of bottom-up saliency when directing gaze and

visual attention in realistic images(64–67) appears to generalize to three-dimensional virtual

environments. As such, the ability of visual stimuli to automatically capture visual attention may

not be contingent upon the stimuli being highly salient.

Proper allocation of visual attention is important for completing visual search tasks and

appears to be associated with cognition. Performance in our task was related to global cognition

and working memory capacity, as those who scored higher in the Montreal Cognitive Assessment

and the Backwards Corsi block task demonstrated shorter task completion times. These results

echo the importance of working memory capacity on visual attention(68–70), which has been

demonstrated in simple selective attention(71) and visual search(60) tasks. Beyond memory,

inhibitory capacity is another cognitive domain that influences the allocation of visual attention

and the successful completion of visual search tasks. As previously discussed, inhibitory capacity

allows for the proper allocation of visual attention by selecting for and processing information

relevant to the task while suppressing those that are irrelevant. However, we found no relationship

between inhibitory capacity, which was tested using the Flanker task, and VR task completion

times. Visual search performance and the relevant gaze behavior that may influence it appear to

be influenced by an individual's general cognitive capacity, with working memory playing a more

prominent role, but not inhibition.

The increase in task completion times at higher visual complexity levels can be explained

not only by the time required to search for the correct targets, as exhibited by the calculated

fixation times, but also by changes that influence the speed with which targets are selected, such

as by moving slower. We quantified selection delay as the time between fixating and selecting a

correct target, which is influenced by a combination of the time it takes to move the laser pointer

to the correct target and successfully select it. All participants demonstrated longer selection delay

as the visual complexity of the search environments increased, with this effect being greater in

older adults. These effects on selection delay could have been due to participants spending more

time during information processing to determine whether the target is correct relative to the

sequence. However, we did not find an effect of visual complexity on average fixation times on

task-relevant objects. Longer selection delays at higher visual complexity levels could also have

been caused by a general movement slowing as participants traded off speed for

accuracy(72,73). This effect seems to be supported by the lack of changes in the number of

selection errors with increasing visual complexity for all participants. However, the selection errors

were greater in older adults than young adults, contradicting previously demonstrated parity

between the two groups resulting from older adults using movement slowing as a compensatory

mechanism to maintain accuracy(72,73).

It is important to consider that our study contains limitations that may have influenced our

results and their interpretability. While the task design improves on prior visual search tasks on

static two-dimensional realistic images, using letters in the search sequence may have diminished

the ecological validity of our task. Additionally, the search targets in our tasks were related (letters

of the alphabet and visual representation of animals whose names started with those letters) such

that participants only needed to keep track of a single set in their working memory. In contrast,

the paper-based Trail Making Test-B uses two different, unrelated lists (letters of the alphabet

and numbers), requiring working memory to keep track of two sets. The low adjusted R2 we found

when determining the relationship between performance in our VR task and the paper-based Trail

Making Test-B also supports this limitation. Future work may benefit from creating a VR-based

visual search task that uses only search targets that can be found in the real world and fully

incorporates all aspects of the paper-based Trail Making Test-B. While all of our participants have

normal or corrected-to-normal vision, we were not able to assess the visual acuity and contrast

sensitivity of our participants, which may influence a person's perception of saliency since it is

quantified using the low-level visual features of a scene and ultimately the results in our study.

Future work should include assessments that target various visual domains. Finally, the lack of a

relationship between inhibitory capacity and the various performance metrics used may be due to our sample of older adults being cognitively high functioning and the assessment used not targeting the type of inhibition present during visual search. Future work would benefit from including participants with a broader range of cognitive assessment scores and using a more comprehensive cognitive assessment battery targeting more cognitive domains.

In conclusion, time to complete the VR visual search task increased with the visual complexity of the environment as participants increased time on re-fixating task-relevant objects and fixating task-irrelevant objects. This negative effect was greater in older adults and is associated with differences in cognitive capacity, particularly in working memory. Increased susceptibility to distraction is potentially problematic as suboptimal allocation of visual attention may lead to difficulties completing everyday tasks and can potentially lead to injuries. For instance, young and older adults who show greater anxiety stemming from fear of falling while walking demonstrate greater susceptibility to distraction by threatening stimuli, which may negatively affect their ability to adapt their gait for safe locomotion(74–76). These results highlight the importance of designing cognitive assessments that use tasks that closely simulate the visual complexity and dynamicity in the real world. In addition, our study also emphasizes the need for a more comprehensive analysis of task performance beyond completion time to accurately assess visuomotor behavior, particularly in older adults.

Data Accessibility

The processed data and the code used to generate the figures and statistics are available on the Open Science Framework at https://osf.io/r9q3k/.

Author Contributions

IJL and JMF conceived and designed the experiment. IJL and AK developed the VR-based visual search task. IJL collected the data. IJL and JMF analyzed the data and interpreted the results. IJL and JMF drafted, edited, and revised the manuscript. IJL, AK, and JMF approved the final version of the manuscript.

Conflicts of Interests

The authors declare that they do not have conflicts of interest.

Ethical Statement

All study procedures have been reviewed and approved by University of Southern California's

Institutional Review Board (UP-22-00317). All participants provided their written informed consent

before the start of the experiment and all aspects of study conformed to the principles expressed

in the Declaration of Helsinki of 1975, as revised in 2013.

Funding

This work was supported by NSF Award 2043637.

References

1. Land MF, Hayhoe M. In what ways do eye movements contribute to everyday activities? Vision Res. 2001;41(25–26):3559–65.

2. Land MF. Eye movements and the control of actions in everyday life. Prog Retin Eye Res. 2006;25:296–324.

3. Hayhoe M, Ballard D. Eye movements in natural behavior. Trends Cogn Neurosci. 2005;9(4):188–94.

4. Hayhoe MM, Rothkopf CA. Vision in the natural world. Wiley Interdiscip Rev Cogn Sci. 2011 Mar 1;2(2):158–66.

5. Patla AE. Understanding the roles of vision in the control of human locomotion. Gait Posture [Internet]. 1997;5(1):54–69. Available from: http://www.sciencedirect.com/science/article/pii/S0966636296011095

6. Marigold DS, Patla AE. Gaze fixation patterns for negotiating complex ground terrain. Neuroscience. 2007 Jan 5;144(1):302–13.

7. Matthis JS, Yates JL, Hayhoe MM. Gaze and the Control of Foot Placement When Walking in Natural Terrain. Curr Biol. 2018 Apr 23;28(8):1224-1233.e5.

8. Chapman GJ, Hollands MA. Evidence for a link between changes to gaze behaviour and risk of falling in older adults during adaptive locomotion. Gait Posture. 2006;24(3):288–94.

9. Chapman GJ, Hollands MA. Evidence that older adult fallers prioritise the planning of future stepping actions over the accurate execution of ongoing steps during complex locomotor tasks. Gait Posture. 2007;26(1):59–67.

10. Young WR, Hollands MA. Can telling older adults where to look reduce falls? Evidence for a causal link between inappropriate visual sampling and suboptimal stepping performance. Exp Brain Res. 2010 Jul;204(1):103–13.

11. Itti L, Koch C. Computational modelling of visual attention. Nat Rev Neurosci. 2001;2(3):194–203.

12. Tatler BW, Hayhoe MM, Land MF, Ballard DH. Eye guidance in natural vision: Reinterpreting salience. J Vis. 2011;11(5).

13. Wolfe JM, Võ MLH, Evans KK, Greene MR. Visual search in scenes involves selective and nonselective pathways. Trends Cogn Sci. 2011 Feb 1;15(2):77–84.

14. Wolfe JM. Visual search. Curr Biol. 2010 Apr 27;20(8):R346–9.

15. Henderson JM. Human gaze control during real-world scene perception. Trends Cogn Sci. 2003;7(11):498–504.

16. Mather M. Aging and cognition. WIREs Cogn Sci. 2010;1(3):346–62.

17. Harada CN, Natelson Love MC, Triebel K. Normal Cognitive Aging. Clin Geriatr Med. 2013
Nov;29(4):737–52.

18. Dempster FN. The rise and fall of the inhibitory mechanism: Toward a unified theory of
cognitive development and aging. Dev Rev. 1992 Mar 1;12(1):45–75.

19. Lustig C, Hasher L, Zacks RT. Inhibitory deficit theory: Recent developments in a "new view."
In: Gorfein DS, Macleod CM, editors. Inhibition in cognition. American Psychological
Association; 2007. p. 145–62.

20. Gazzaley A, Mark D'esposito A. Top-Down Modulation and Normal Aging. Ann N Y Acad Sci.
2007;1097:67–83.

21. Kramer AF, Hahn S, Irwin DE, Theeuwes J. Age differences in the control of looking behavior:
Do You Know Where Your Eyes Have Been? Psychol Sci. 2000;11(3):210–7.

22. Schmitz TW, Cheng FHT, De Rosa E. Failing to ignore: paradoxical neural effects of
perceptual load on early attentional selection in normal aging. J Neurosci Off J Soc Neurosci.
2010 Nov 3;30(44):14750–8.

23. Schmitz TW, Dixon ML, Anderson AK, De Rosa E. Distinguishing attentional gain and tuning
in young and older adults. Neurobiol Aging. 2014 Nov 1;35(11):2514–25.

24. Mertes C, Wascher E, Schneider D. Compliance instead of flexibility? On age-related
differences in cognitive control during visual search. Neurobiol Aging. 2017 May 1;53:169–
80.

25. Gazzaley A, Clapp W, Kelley J, McEvoy K, Knight RT, D'Esposito M. Age-related top-down
suppression deficit in the early stages of cortical visual memory processing. Proc Natl Acad
Sci. 2008 Sep 2;105(35):13122–6.

26. Reitan RM. Validity of the Trail Making Test as an indicator of organic brain damage. Percept
Mot Skills. 1958;8(7):271.

27. Sánchez-Cubillo I, Periáñez JA, Adrover-Roig D, Rodríguez-Sánchez JM, Ríos-Lago M,
Tirapu J, et al. Construct validity of the Trail Making Test: Role of task-switching, working
memory, inhibition/interference control, and visuomotor abilities. J Int Neuropsychol Soc.
2009;15(3):438–50.

28. Salthouse TA. What cognitive abilities are involved in trail-making performance? Intelligence.
2011 Jul;39(4):222.

29. Llinàs-Reglà J, Vilalta-Franch J, López-Pousa S, Calvó-Perxas L, Torrents Rodas D, Garre-
Olmo J. The Trail Making Test. Assessment. 2017 Mar 1;24(2):183–96.

30. Cangoz B, Karakoc E, Selekler K. Trail Making Test: Normative data for Turkish elderly
population by age, sex and education. J Neurol Sci. 2009 Aug 15;283(1):73–8.

31. Hashimoto R, Meguro K, Lee E, Kasai M, Ishii H, Yamaguchi S. Effect of age and education
on the Trail Making Test and determination of normative data for Japanese elderly people:
The Tajiri Project. Psychiatry Clin Neurosci. 2006;60(4):422–8.

32. Specka M, Weimar C, Stang A, Jöckel KH, Scherbaum N, Hoffmann SS, et al. Trail Making
Test Normative Data for the German Older Population. Arch Clin Neuropsychol. 2022 Feb
1;37(1):186–98.

33. Suzuki H, Sakuma N, Kobayashi M, Ogawa S, Inagaki H, Edahiro A, et al. Normative Data of
the Trail Making Test Among Urban Community-Dwelling Older Adults in Japan. Front Aging
Neurosci. 2022 May 25;14.

34. Tombaugh TN. Trail Making Test A and B: Normative data stratified by age and education.
Arch Clin Neuropsychol. 2004 Mar 1;19(2):203–14.

35. Plotnik M, Ben-Gal O, Doniger GM, Gottlieb A, Bahat Y, Cohen M, et al. Multimodal immersive
trail making-virtual reality paradigm to study cognitive-motor interactions. J NeuroEngineering
Rehabil. 2021 Dec 1;18(1):1–16.

36. Recker L, Poth CH. Test–retest reliability of eye tracking measures in a computerized Trail
Making Test. J Vis. 2023 Aug 22;23(8):15.

37. Wölwer W, Falkai P, Streit M, Gaebel W. Trait Characteristic of Impaired Visuomotor
Integration during Trail-Making Test B Performance in Schizophrenia. Neuropsychobiology.
2003 Sep 26;48(2):59–67.

38. Singh T, Perry CM, Fritz SL, Fridriksson J, Herter TM. Eye Movements Interfere With Limb
Motor Control in Stroke Survivors. Neurorehabil Neural Repair. 2018 Aug 1;32(8):724–34.

39. Adlakha G, Singh S, Patil A, Nuthalapati K, Khandve P, Bhattacharyya P, et al. Development
of a virtual reality assessment of visuospatial function and oculomotor control. In: 2021 IEEE
Conference on Virtual Reality and 3D User Interfaces Abstracts and Workshops (VRW).
Institute of Electrical and Electronics Engineers Inc.; 2021. p. 753–4.

40. Kreidler SM, Muller KE, Grunwald GK, Ringham BM, Coker-Dukowitz ZT, Sakhadeo UR, et
al. GLIMMPSE: Online Power Computation for Linear Models with and without a Baseline
Covariate. J Stat Softw. 2013 Sep;54(10):i10.

41. Nasreddine ZS, Phillips NA, Bédirian V, Charbonneau S, Whitehead V, Collin I, et al. The
Montreal Cognitive Assessment, MoCA: A Brief Screening Tool For Mild Cognitive
Impairment. J Am Geriatr Soc. 2005 Apr 1;53(4):695–9.

42. Corsi PM. Memory and the medial temporal region of the brain. [Montreal]: McGill University;
1972.

43. Isaacs EB, Vargha-Khadem F. Differential course of development of spatial and verbal
memory span: A normative study. Br J Dev Psychol. 1989 Nov;7(4):377–80.

44. Eriksen BA, Eriksen CW. Effects of noise letters upon the identification of a target letter in a
nonsearch task. Percept Psychophys. 1974 Jan;16(1):143–9.

45. Stoet G. PsyToolkit: A software package for programming psychological experiments using
Linux. Behav Res Methods. 2010 Nov;42(4):1096–104.

46. Stoet G. PsyToolkit: A Novel Web-Based Method for Running Online Questionnaires and
Reaction-Time Experiments. Teach Psychol. 2017 Jan 1;44(1):24–31.

47. Rosenholtz R, Li Y, Nakano L. Measuring visual clutter. J Vis. 2007 Jan 2;7(2):17–17.

48. Matin E. Saccadic suppression: a review and an analysis. Psychol Bull. 1974
Dec;81(12):899–917.

49. Rayner K. Eye movements and attention in reading, scene perception, and visual search. Q
J Exp Psychol 2006. 2009;62(8):1457–506.

50. Salvucci DD, Goldberg JH. Identifying Fixations and Saccades in Eye-Tracking Protocols. In:
Proceedings of the EyeTracking Research and Applications Symposium. New York:
Association for Computing Machinery; 2000. p. 71–8.

51. Tobii Pro Lab Gaze Filter [Internet]. 2023 [cited 2024 Jul 15]. Tobii Pro Lab Gaze Filter.
Available from: https://connect.tobii.com

52. Itti L, Koch C, Niebur E. A model of saliency-based visual attention for rapid scene analysis.
IEEE Trans Pattern Anal Mach Intell. 1998;20(11):1254–9.

53. Le Meur O, Baccino T. Methods for comparing scanpaths and saliency maps: Strengths and
weaknesses. Behav Res Methods. 2013;45(1):251–66.

54. Kretch KS, Adolph KE. Active vision in passive locomotion: Real-world free viewing in infants
and adults. Dev Sci. 2015 Sep 1;18(5):736–50.

55. Treisman AM, Gelade G. A feature-integration theory of attention. Cognit Psychol.
1980;12(1):97–136.

56. Folk CL, Lincourt AE. The effects of age on guided conjunction search. Exp Aging Res. 1996
Jan 1;22(1):99–118.

57. Hommel B, Li KZH, Li SC. Visual search across the life span. Dev Psychol. 2004
Jul;40(4):545–58.

58. Müller-Oehring EM, Schulte T, Rohlfing T, Pfefferbaum A, Sullivan EV. Visual Search and the
Aging Brain: Discerning the Effects of Age-related Brain Volume Shrinkage on Alertness,
Feature Binding, and Attentional Control. Neuropsychology. 2013;27(1):48.

59. Lee SC, Kim YW, Ji YG. Effects of visual complexity of in-vehicle information display: Age-
related differences in visual search task in the driving context. Appl Ergon. 2019 Nov
1;81:102888.

60. Aziz JR, Good SR, Klein RM, Eskes GA. Role of aging and working memory in performance
on a naturalistic visual search task. Cortex. 2021;136:28–40.

61. Bonacci LM, Bressler S, Kwasa JAC, Noyce AL, Shinn-Cunningham BG. Effects of Visual
Scene Complexity on Neural Signatures of Spatial Attention. Front Hum Neurosci. 2020 Mar
24;14:91.

62. Tsvetanov KA, Mevorach C, Allen H, Humphreys GW. Age-related differences in selection by
visual saliency. Atten Percept Psychophys. 2013;75(7):1382–94.

63. Gazzaley A, Nobre AC. Top-down modulation: bridging selective attention and working
memory. Trends Cogn Sci. 2012 Feb 1;16(2):129–35.

64. Henderson JM, Malcolm GL, Schandl C. Searching in the dark: Cognitive relevance drives
attention in real-world scenes. Psychon Bull Rev. 2009 Oct 1;16(5):850–6.

65. Henderson JM, Hayes TR. Meaning guides attention in real-world scene images: Evidence
from eye movements and meaning maps. J Vis. 2018;18(6).

66. Peacock CE, Hayes TR, Henderson JM. Meaning guides attention during scene viewing, even
when it is irrelevant. Atten Percept Psychophys. 2019;81(1):20–34.

67. Peacock CE, Hayes TR, Henderson JM. The role of meaning in attentional guidance during
free viewing of real-world scenes. Acta Psychol (Amst). 2019 Jul 1;198.

68. Hayhoe MM. Vision and Action. Annu Rev Vis Sci. 2017;3:389–413.

69. Madden DJ. Aging and Visual Attention. Curr Dir Psychol Sci. 2007 Apr;16(2):70.

70. Diamond A. Executive Functions. Annu Rev Psychol. 2013 Jan 2;64:135–68.

71. Shipstead Z, Harrison TL, Engle RW. Working memory capacity and visual attention: Top-
down and bottom-up guidance. Q J Exp Psychol. 2012 Mar;65(3):401–7.

72. Zhang L, Yang J, Inai Y, Huang Q, Wu J. Effects of aging on pointing movements under
restricted visual feedback conditions. Hum Mov Sci [Internet]. 2015 Apr 1 [cited 2025 Feb
20];40:1–13.   Available   from:
https://www.sciencedirect.com/science/article/pii/S016794571400205X

73. Lamb DG, Correa LN, Seider TR, Mosquera DM, Rodriguez JA, Salazar L, et al. The aging
brain: Movement speed and spatial control. Brain Cogn [Internet]. 2016 Nov 1 [cited 2023 Oct
27];109:105–11.   Available   from:
https://www.sciencedirect.com/science/article/pii/S0278262616301634

74. Ellmers TJ, Young WR. The influence of anxiety and attentional focus on visual search during
adaptive gait. J Exp Psychol Hum Percept Perform. 2019 Jun 1;45(6):697–714.

75. Ellmers TJ, Cocks AJ, Kal EC, Young WR. Conscious movement processing, fall-related
anxiety, and the visuomotor control of locomotion in Older Adults. J Gerontol - Ser B Psychol
Sci Soc Sci. 2020 Nov 1;75(9):1911–20.

76. Young WR, Wing AM, Hollands MA. Influences of state anxiety on gaze behavior and stepping
accuracy in older adults during adaptive locomotion. J Gerontol - Ser B Psychol Sci Soc Sci.
2012;67 B(1):43–51.

(a) Low — Medium — High

(b) Feature Congestion vs. Visual Complexity Level (Low, Medium, High)

(a) Selection Errors by Age Group (Young, Old)

(b) Selection Delay (s) by Visual Complexity Level (Low, Medium, High)

Young Old Group Means