The timecourse of inter-object contextual facilitation

Genevieve L. Quek[1,2,*], Alexandra Theodorou[2,3], Marius V. Peelen[2]

[1]The MARCS Institute for Brain, Behaviour and Development,

Western Sydney University, Sydney, Australia

[2]Donders Institute for Brain, Cognition and Behaviour,

Radboud University, Nijmegen, The Netherlands

[3]Department of Psychology,

University of California, Davis, CA, USA

*Corresponding author: g.quek@westernsydney.edu.au

Figure count: 6

Word counts: Abstract (238), Introduction (650), Discussion (1494)

Conflict of interest statement:

The authors declare no competing financial interests.

Acknowledgements:

This project has received funding from the European Research Council (ERC) under the European Union's

Horizon 2020 research and innovation programme (grant agreement No. 725970). The authors thank

Angeliki Karaiskou and Manon Maarseveen for their assistance with data collection.

Abstract

High-level vision is frequently studied at the level of either individual objects or whole scenes. An intermediate level of visual organisation that has received less attention is the "object constellation" – a familiar configuration of contextually-associated objects (e.g., plate + spoon). Recent behavioural studies have shown that information from multiple objects can be integrated to support observers' high-level understanding of a "scene" and its constituent objects. Here we used EEG in human participants (both sexes) to test when the visual system integrates information across objects to support recognition. We briefly presented masked object constellations consisting of object silhouettes of either large (e.g., chair + table) or small (e.g., plate + spoon) real-world size, while independently varying retinal size. As a control, observers also viewed each silhouette in isolation. If object context facilitates object recognition, real-world size should be inferred more effectively when the objects appear in their contextually-associated pairs than in isolation, leading to the emergence of real-world size information in multivariate EEG patterns. Representational similarity analysis revealed that neural activity patterns captured information about the real-world size of object constellations from ~200 ms after stimulus onset. This representation was stronger for, and specific to, object pairs as compared to single objects, and remained significant after regressing out visual similarity models derived from computational models. These results provide evidence for inter-object facilitation of visual processing, leading to a qualitatively different high-level representation of object pairs than single objects.

Significance Statement

This study used electroencephalography decoding to reveal the neural timecourse of inter-object facilitation present for contextually-associated groups of objects (e.g., chair + table). Although ubiquitous in daily life, the 'object constellation' level of representation has rarely been examined compared to isolated objects or entire scenes. By shedding new light on facilitatory interactions between objects, arising before 200ms of visual processing, our results provide insight into the continuum along which objects and scenes exist. At the same time, this work advances the current understanding of the neural basis of real-world size, using strict visual controls to show that inferred real-world size representations emerge around 200 ms after stimulus onset.

Introduction

Many scenes in daily life are meaningfully defined by the specific constellations of objects they contain (e.g., a knife and fork either side of a plate, or a sofa facing a television). Our encounters with such multi-object arrangements are so ubiquitous that the visual system is remarkably sensitive to statistical regularities within these groups, with both the likelihood of objects' co-occurrence and their configural arrangement influencing the way we search for, attend to, and remember familiar objects (Biederman, 1972; Biederman et al., 1973; Kaiser et al., 2015; Võ et al., 2019; Nah and Geng, 2022).

Notably, higher-level statistical regularities between objects also appear to influence object processing itself (Kaiser et al., 2019). Behavioural studies have shown that objects are recognized faster and more accurately when viewed together with one or more contextually-associated objects (Auckland et al., 2007; Davenport, 2007). Furthermore, ambiguous objects that appear with an associated object in a familiar configuration (e.g., a keyboard in front of a monitor) are recognized more accurately than the same objects shown in isolation or in an unfamiliar configuration (Bar and Ullman, 1996; Green and Hummel, 2006). In the present study, we use time-sensitive decoding of electroencephalography (EEG) data to examine the timecourse of this inter-object facilitation effect.

Previous EEG studies investigating the timecourse of contextual associations between objects, or between objects and scenes, measured the neural response to semantic violations by contrasting incongruent vs. congruent object associations. This contrast gives rise to reliable event-related potentials (ERPs; Ganis and Kutas, 2003; Mudrik et al., 2010; Võ and Wolfe, 2013; Quek and Peelen, 2020), including the domain-general N400 over centro-parietal electrodes (Kutas and Federmeier, 2011). Notably, these studies used clearly visible objects, as the interest was in measuring when neural signals reflected the violation. In contrast, here we were interested in how the processing of *ambiguous* objects is facilitated by object context.

A similar question has been addressed for objects disambiguated by global scene context (Brandman and Peelen, 2017; Wischnewski and Peelen, 2021). In those studies, an object was degraded such that it was difficult to recognize when viewed in isolation, but readily identifiable in the context of its original scene. Multivariate decoding analysis showed that the visual representation of the object's category (animate or inanimate) was facilitated by scene context from ~300 ms after stimulus onset. Subsequent fMRI and TMS studies revealed that this facilitation resulted from an interaction between processing in scene-selective and object-selective cortex (Brandman and Peelen, 2017; Wischnewski and Peelen, 2021). One possibility is that

inter-object facilitation follows the same timecourse as scene-object facilitation, for example because both

scene-object and object-object facilitation result from the same feedback mechanism based on the activation

of a common conceptual "schema" (Bar, 2004). Alternatively, however, we may expect inter-object facilitation

to be faster than scene-object facilitation, as interactions are between representations within the same object

processing pathway rather than between separate object and scene processing pathways (Peelen et al.,

2023).

To reveal the timecourse of inter-object contextual facilitation, we took advantage of an object property that

is rapidly and automatically retrieved following the recognition of objects – real-world size (Konkle and Oliva,

2012a; Hagen et al., 2023). Since real-world size is a large-scale organising principle in the visual system

(Konkle and Oliva, 2012b; Coutanche and Thompson-Schill, 2019) that is readily decoded using M/EEG

(Cichy et al., 2017; Khaligh-Razavi et al., 2018; Wang et al., 2022), tracking the emergence of real-world size

representations is an ideal proxy for examining how an object's processing is facilitated by its context.

Here, in behavioural and EEG experiments, observers viewed pairs of contextually-associated objects with

small or large canonical real-world size. We obscured object identity by presenting the objects in silhouette

against phase-scrambled noise. If object context facilitates object recognition, real-world size should be

inferred more effectively when the objects appear in their contextually-associated pairs than in isolation,

leading to the emergence of real-world size information in multivariate EEG patterns.

Materials & Methods

105 All experimental procedures were carried out with the approval of the Radboud University Faculty of Social

106 Sciences Ethics Committee (ECSW2017–2306-517).

Participants

For Experiment 1 (behavioural), we recruited 75 online participants (40 female, 33 male, 2 not answered)

aged between 18-35 years (M = 26.31, SD = 4.89) via Prolific (www.prolific.co). All were living in the

Netherlands, had normal or corrected-to-normal vision, and had prior experience in online research

participation (>10 studies). For Experiment 2 (EEG), we aimed for a final sample of N=34, which provides

80% power to detect a medium-sized effect (Cohen's d = 0.5) with α=0.05 (one sample t-test). To achieve

this, we tested 41 English-speaking individuals (11 males) aged between 18 and 35 years (M = 23.46, SD =

3.88) from the local region of Nijmegen, the Netherlands. All had normal or corrected-to-normal vision, with

no history of neurological illness/concussion/brain surgery/migraine. Data from 6 participants were discarded

to reach the eventual N=34 - these included one participant who terminated the experiment early due to

discomfort, and 6 participants with very high noise/muscle artefact in the signal. Individuals in both

experiments were monetarily compensated for their participation.

Stimuli

Stimuli were identical across the two experiments and were based on 20 pairs of contextually-associated

objects, each denoting either a small- or large-scale object constellation (Figure 1A). 'Small' displays

contained pairs of desktop-sized objects that could fit into a shoebox, typically with grasp/reach affordances

(e.g., bottle + glass). 'Large' displays contained pairs of furniture-sized objects, typically with navigational

affordances (e.g., table + chair). All objects appeared in silhouette, embedded in a noise mask, with no other

meaningful visual information (e.g., background). These sparse visual displays served to eliminate many of

the inherent low- and mid-level visual differences between naturalistic scenes of different spatial scales. Note

that such visual controls do not eliminate more conceptual differences between desktop-size and furniture-

size objects – for example, their respective manipulation and navigation affordances. Importantly, where

these and other distinctions between large and small objects could be problematic for isolating neural signals

corresponding to real-world size *per se,* they do not impede our ability to treat real-world size

judgements/representations as a useful index of object processing and recognition.

Inspired by previous work showing that relative spatial positioning modulates the extent to which observers

group/integrate concurrently-presented objects (Bar and Ullman, 1996; Baeck et al., 2013; Kaiser et al.,

2019; Xu et al., 2021), we varied the relative sizing of the objects within each pair as depicted in Figure 1B.

We began with the stimuli shown in Figure 1A, wherein the proportional relative sizing of the object

silhouettes within each pair implied them to be at the same distance or depth. We then created an identical

'depth-match' version of the pair at a decreased retinal size (2:1 size decrease), and recombined the

elements of these two versions to create two different 'depth-mismatch' pairs in which the objects'

disproportionate retinal sizes (e.g., large pillow + small bedframe) implied they were at different distances

from the viewer. To ensure that the pixel distance between the two objects in a depth-mismatch pair was

equivalent to the pixel distance between their depth-match counterparts, we randomly labelled the objects in

each pair as object 1 and object 2. We then utilized the smaller distance whenever object 1 was the small

object in the depth-mismatch pair and the large distance when it was the larger object. We maintained the

surface alignment of the two-object scene as much as possible across versions, e.g., since desk and chair

both rest on the floor, we aligned these items at their bottom edge regardless of whether their depths were

matched or mismatched.

In addition to the four versions of each object pair, observers also saw the small and large retinal size

versions of every silhouetted object in isolation (Figure 1C). The position of each isolated object at a given

retinal size was always halfway between where that object had appeared as part of the depth-match and

depth-mismatch pair. This made for a total of 80 object pairs and 80 single objects (10 exemplars x 4

versions representing each level of real-world size). There were 248 phase scrambled noise images, two of

which were randomly selected to serve as masks on each trial.

Trial structure was near identical across Experiments 1 and 2 (Figure 1D): The trial began with a central

fixation cross (duration of 500 ms in Experiment 1; between 200-500 ms in Experiment 2). Following the

fixation period, a phase-scrambled noise mask appeared for 400 ms, then the silhouette target appeared at

40% contrast embedded within the mask for 100 ms. The trial concluded with a different phase-scrambled

backward mask that lasted 300 ms. In both experiments, the trial sequence appeared against a uniform grey

background.

Figure 1. Stimuli used in Experiments 1 and 2. A) The 20 base object pairs drawn from small (top row) and large (bottom row) real-world contexts. B) Each object pair had four versions: A large and small retinal size in which the objects' relative sizing implied they were at the same depth (Depth-match). Recombining the elements of these versions produced two pairs where the objects were implied to be at different depths (Depth-mismatch). C) Participants also saw each individual object in isolation. D) Basic trial structure for both experiments. Following fixation, the target appeared at 40% contrast embedded in a phase-scrambled noise mask, and was immediately followed by a different phase-scrambled mask. In Experiment 1, the fixation period was fixed at 500 ms.

Procedure

Experiment 1 (behavioural) was programmed in PsychoPy (jsPsych) and hosted online on Pavlovia (Open

Science Tools Limited, 2021). Participants completed the experiment in a browser window on either a

desktop or laptop computer. Before beginning, we instructed them to minimise any distractions in the

environment (e.g., music, TV, other people), and to disconnect any external monitors to ensure the

experiment appeared on their main screen. On each trial (see Figure 1D), participants had 1000 ms from

target onset to categorise the displayed object(s) as either large or small in real life by pressing either the *f*

(small) or *j* (large) key. Our rationale here was that the objects would be more readily recognised when they

appeared in familiar constellations than when they appeared alone – and that this should result in

faster/more accurate categorisation of their real-world size. Response key labels appeared onscreen

throughout the trial. We specifically instructed participants to consider the size of the objects in the real world

(not the size at which they appeared onscreen), and to fixate on the central cross whenever it appeared

between trials. Prior to commencing the experimental trials, observers saw three example object pairs

representing each real-world size category, and completed 16 practice trials in which the target duration was

set at 500 ms to facilitate learning. These training trials used an independent stimulus set to the main

experiment. In the experiment proper, 80 object pairs and 80 single objects appeared in random,

intermingled order for a total of 160 trials. Mask stimuli were sized at 560x560 pixels; we could not fully

control the visual angle subtended by the stimuli owing to conducting the study online. Total testing time for

Experiment 1 was approximately 10 minutes including a self-paced break at the halfway point.

Experiment 2 (EEG) was conducted in the lab. The trial sequence was programmed in Presentation®

(Neurobehavioral Systems, Inc., Berkeley, CA, www.neurobs.com), and displayed on a BenQ XL2420Z

computer monitor (120Hz refresh rate; 1920x1080 resolution). Mask stimuli were sized 14x14cm, with

viewing distance set at 65cm such that each stimulus subtended 12.3 x 12.3 degrees of visual angle.

Experiment 2 saw a 10-fold increase in the number of trials: each of the 160 unique stimuli appeared once

per block, with 10 blocks in the full experiment. In contrast to Experiment 1, here participants were engaged

in a 1-back task, monitoring the target from trial to trial and pressing the spacebar whenever they saw an

exact image repeat (10 instances per block). Prior to the main experiment, observers performed 25 practice

trials with a slightly longer target duration (300 ms); this included 5 repeat instances to enable them to learn

the task. The full experimental session including EEG set up lasted around 2.5 hours.

We recorded scalp EEG in Experiment 2 using a 64-channel BrainProducts actiCAP active electrode system

with a sampling rate of 500Hz (Brain Products GmbH, Gilching, Germany). We used customized electrode

positions adapted from the actiCAP 64Ch Standard-2 system (ground placed at AFz; TP10 placed on right

mastoid). Impedances for individual scalp channels were held <40 kOhm, with data referenced online to the

left mastoid and filtered between 0.016 and 125 Hz using BrainVision Recorder (Brain Products GmbH,

Gilching, Germany). We monitored participants' eye movements via external passive electrodes situated at

the outer canthus of each eye, as well as immediately above and below the right eye. The ground electrode

for passive ocular channels was placed on the tip of the nose. The experimenter visually monitored the EEG

trace throughout the experiment, initiating each experimental block manually after ensuring there were no

high amplitude deflections resulting from ocular/muscular artefacts. Stimulus onsets were marked in the EEG

file using numeric triggers.

Experimental Design & Statistical Analysis

<u>Experiment 1</u>

For the behavioural real-world size categorisation task, we removed participants who failed to provide a

response on more than 30% of trials ($n = 5$), and subsequently any participant whose mean accuracy or

response time (RT) on correct trials fell more than 2 standard deviations below the group mean ($n = 6$). We

further discarded any trials on which the participant responded sooner than 200 ms following target onset

(0.62% of trials), under the rationale that these early responses were unlikely to be informative. We then

inspected *i)* response accuracy (treating trials with no response as incorrect responses) and *ii)* RT on correct

trials. For the latter, we bounded each participant's RT distribution at 2 standard deviations above and below

the mean by replacing values outside this range with the top and bottom RTs respectively (4.6% of trials).

For each metric, we ran a 2 x 2 repeated measures ANOVA with the factors *Stimulus Type* (Pair, Single) and

Retinal Size (Large, Small). Note that for the depth-mismatch pair stimuli, the 'large' and 'small' retinal size

labels were simply arbitrary labels, since each depth-mismatch pair necessarily comprised one large retinal

size object and one small retinal size object (see Figure 1B). A subsequent analysis inspected the effect of

Relative Depth (match, mismatch) for the Object Pairs data alone (since there was no relative depth

manipulation for single objects).

<u>Experiment 2</u>

EEG preprocessing

We preprocessed the EEG data in MATLAB 2016b using FieldTrip functions (Oostenveld, Fries, Maris &

Schoffelen, 2011; http://fieldtriptoolbox.org). This included a bandpass filter between 0.05-100 Hz, a line

noise filter at 50 Hz, 100 Hz, & 150 Hz, and downsampling the data to 250 Hz for easier storage and

handling. A maximum of three artefact ridden channels were identified by eye and interpolated using the

weighted average of neighbouring electrodes. To combat artefacts introduced by eyeblinks, we relied on an

independent components analysis approach (runica decomposition), visually inspecting the components and

associated topographies for each participant to identify and remove the eye blink component. No trial or

epoch rejection was applied. We then re-referenced each participant's cleaned EEG trace to the average of

all channels before segmenting an epoch from -200 ms to 500 ms around the onset of each target stimulus

(excluding 1-back repeat instances). The resulting 800 single object epochs and 800 object pair epochs were

then baseline-corrected using the 200 ms prior to stimulus onset.

Representational Similarity Analysis (RSA)

<u>RSA using individual versions of each object pair</u>

For the object pair neural data, we used RSA (Kriegeskorte et al., 2008; Kriegeskorte and Kievit, 2013) to

build a pairwise representational dissimilarity matrix (RDM) at each 4 ms timepoint, for each participant

separately. This involved pairwise decoding of every version of every object pair exemplar (i.e., 80 items)

using Linear Discriminant Analysis (LDA) with 10 fold cross-validation as implemented in the CoSMoMVPA

toolbox (Oosterhof et al., 2016; https://www.cosmomvpa.org/). We used multiple regression to relate the

resulting time-varying RDM to four categorical predictors corresponding to the binary models given by our

experimental design (see Figure 3B). These were <u>Pair Identity</u> (i.e., the specific real-world context the

objects were drawn from), <u>Retinal Size</u> (i.e., large or small version), <u>Real-World Size</u> (i.e., small- or large-

scale objects), and <u>Relative Depth</u> (i.e., implied depth of the objects either matched or mismatched within the

pair). Here and in all following analyses, we inspected the utility of each model as a predictor of the neural

RDM at each timepoint between 0 and 500 ms via a Bayesian one sample *t*-test that examined whether the

participant mean betas were greater than zero.

<u>RSA using object pairs collapsed across version</u>

Next, we ran a simplified RSA that pooled the neural data for the four versions of each object pair (see

Figure 1B) for pairwise decoding. This effectively collapsed across all design factors other than Real-World

Size, which remained the primary model of interest. Here we aimed to inspect the predictive power of the

real-world size model while controlling for the inherent low-level differences between large and small object

pairs. To this end, we built four low-level visual control RDMs (see details below), each sized 80x80 (i.e.,

every version of every object pair treated individually). We then collapsed these into the reduced 20×20

RDMs by averaging values over the four versions of each object pair, e.g., collapsed dissimilarity value for

Pair 1 vs. Pair 2 was the average of all RDM intersections of [1A, 1B, 1C, 1D] and [2A, 2B, 2C, 2D]. The

visual control models we considered were: *1)* An image similarity model reflecting 1 minus the pixel-wise

correlation between each of the 80 object pair images; *2)* A silhouette overlap model (Jaccard, 1901)

comprising 1 minus the Jaccard similarity (ranges between 0 and 1) for each pairwise combination of the 80

object pair images; 3) A computational model of low-level visual processes, obtained by applying HMAX

(Riesenhuber and Poggio, 1999; Serre et al., 2007; https://maxlab.neuro.georgetown.edu/hmax.html) to

each of the 80 object pair images embedded in an example noise mask (just as they appeared in both

experiments). RDM values were 1 minus the Spearman correlation between the vectorised responses on the

final HMAX C2 layer; and 4) A mid-level feature model comprising the pairwise Euclidean distances between

curvature indices for object pairs obtained using a computational model developed by Li and Bonner (2020;

https://github.com/shipui2005/Curvature-Model). In this and the following multiple regressions, we inspected

the Spearman rank-order correlations between all model RDMs, applying a significance criterion of *p* <.01,

FDR corrected. Since the <u>Pixel Correlation</u> and <u>Jaccard Similarity</u> models were highly correlated (rho =

0.9844, *p* <.0001) and displayed large Variance Inflation Factors (pix = 31.09, jac = 39.91), we elected to

drop the <u>Jaccard</u> model from our multiple regression, leaving 1 categorical predictor (<u>Real-world Size</u>) and 3

continuous control predictors (<u>pixel correlation</u>, <u>HMAX C2</u>, and <u>curvature</u>, see Figure 4). Since the

intercorrelations between these predictors were not especially high (only <u>Pixel Correlation</u> and <u>Curvature</u>

were significantly correlated, rho = 0.2587, *p* = .002), and since VIFs were all close to 1 (RwS = 1.0046, pix =

1.0645, hmx = 1.0262, cur = 1.0884), we felt justified in including these models as independent predictors in

the same multiple regression.

<u>Comparisons with Single Objects</u>

If recognising an object is facilitated by its inclusion in a familiar object constellation, then the representation

of real-world size it evokes will be stronger than that evoked by the same object viewed in isolation. To

enable this comparison, we duplicated the above collapsed RSA pipeline for the Single Object neural data,

producing corresponding real-world size and low-level visual control models for the single object stimuli. For

the singles objects, we found significant correlations between the real-world size and curvature models (rho

= 0.2516, p = .0028) and the curvature and pixel correlation models (rho = 0.2276, p = .0049). Importantly,

variance inflation factors for the predictors were all close to 1 (RwS = 1.0884, pix = 1.0885, hmx = 1.0251,

cur = 1.1608), such that we felt confident interpreting the beta estimates from a multiple regression that

included these models as independent variables.

<u>Comparisons with a Deep Convolutional Neural Network</u>

To further rule out the possibility that real-world size representations evoked by the object pair stimuli arose

in response to low-level featural differences between large and small objects, we examined representations

of these sparse scenes in the layers of a deep convolutional neural network trained to label objects using 1.2

million naturalistic images (AlexNet, Krizhevsky et al., 2012). We obtained output activations corresponding

to the 80 object pair images embedded in an example noise mask (i.e., as they appeared to human

observers in the two experiments) on each of the 8 AlexNet layers (input layer, five convolutional layers, two

fully connected layers), each of which was used to build an RDM. Just as for the low-level visual control

models, we collapsed the resulting 80×80 RDMs down to 20×20 by averaging values over the four versions

of each object pair. Using the same significance criterion as detailed above, we inspected the intercorrelation

matrix for these eight AlexNet RDMs and the model of Real-world Size. If featural differences between our

large/small stimuli account for the predictive power of real-world size, then we would expect strong

correlations between this model and the earlier layers of AlexNet.

Lastly, given that the upper layers of convolutional neural networks capture some important organising

principles of object vision (e.g., animacy, Khaligh-Razavi and Kriegeskorte, 2014), we also asked whether

the information about real-world size in our neural data could be accounted for by the representational

structure evident in these layers of AlexNet (i.e., FC6 & FC7). To this end, we subjected the (reduced) neural

RDM series for object pairs to separate multiple regressions that included <u>Real-world Size</u> as a categorical

predictor alongside i) the FC6 RDM, and 2) the FC7 RDM (treated as continuous predictors). Although the

<u>Real-world Size</u> model was significantly correlated with both AlexNet layer models (FC6: rho = 0.20, *p* =

0.0079; FC7: rho = 0.24, p = 0.0016, FDR-corrected), Variance Inflation Factors (VIF) for these regressors

were close to zero in both cases (RwS & FC6 = 1.0378; RwS & FC7 = 1.0391). As such, we felt justified in

treating them as independent predictors in these multiple regressions.

Results

Experiment 1: Behavioural judgements of real-world size

To verify that the object silhouettes were recognised better when presented in pairs than in isolation (Bar and

Ullman, 1996), we compared participants' ability to determine the real-world size of the silhouettes between

these conditions. A 2x2 repeated measures ANOVA for conditional mean accuracies confirmed that

participants could determine the real-world size of object silhouettes significantly better when the items

appeared in contextually-related pairs that formed sparse scenes (M = 77.3% correct) rather than in isolation

(M = 65.32% correct; main effect of *Stimulus Type*, $F(1,63)$ = 194.72, p <.00001, ges = 0.512, see Figure

2A). This was qualified by a significant interaction with *Retinal Size*, $F(1,63)$ = 17.40, p <.0001, ges = .084,

wherein the magnitude of the Pair > Single difference was larger for the small retinal size versions (M_{diff} =

.155, SD = .096) than the large retinal size versions (M_{diff} = .084, SD = .098). The main effect of *Retinal Size*

was not significant, $F(1,63)$ = 0.25, p = .619, ges = .001. For RT (Figure 2B), we observed a similar main

effect of *Stimulus Type*, $F(1,63)$ = 8.16, p <.01, ges = .041. On average, participants were slower to

categorise the real-world size of single objects (M = 595 ms, SD = 139 ms) compared to object pairs (M =

590 ms, SD = 136 ms). Neither the main effect of *Retinal Size,* $F(1,63)$ = 3.49, p = .467, ges = .003, nor the

two way interaction, $F(1,63)$ = 0.53, p = .066, ges = .016, reached significance in the case of RT. Together,

these results indicate that observers recognised objects (and could therefore access information about their

real-world size) better when the objects appeared as part of a familiar constellation than when they appeared

alone, replicating previous work (Bar and Ullman, 1996).

Contrary to our predictions, there was no evidence in accuracy or RT that participants' real-world size

judgements were affected by the relative size of objects within a pair (Figure 2). Paired *t*-tests of both

accuracy, $t(63)$ = 0.413, p = .681, and RT, $t(63)$ = -0.62, p = .539, revealed no difference between responses

to depth-match and depth-mismatch object pairs. Note that there was no such comparison for single objects,

as relative depth does not apply to isolated objects.

Figure 2. Behavioural judgements of real-world size in Experiment 1. Overlaid violin and box-and-whiskers

plots of A) accuracy and B) RTs. Single Object data (in grey) appear at right, with Object Pair data (in green)

split into depth-match and depth-mismatch versions (there was no significant difference between these

conditions in either metric). Upper and lower box edges correspond to the first and third quartiles (capturing

the interquartile range, IQF); whiskers encompass values less than 1.5*IQF from the box edges. Example

stimuli for each condition appear below the x-axis labels.

Experiment 2: The timecourse of inter-object facilitation

In Experiment 2, we applied RSA to our EEG data to examine the temporal dynamics of real-world size

representations evoked by our silhouetted object pairs. We reasoned that if presenting objects in familiar

constellations facilitates object processing, then the neural response to object pairs should carry information

about their associated real-world size to a greater extent than the response to single objects.

<u>RSA for the individual versions of each object pair</u>

We began by inspecting how well the binary models based on our design factors (Figure 3B) could predict

the neural RDM series for object pairs (Figure 3A). In this analysis, we treated the four versions of each

object pair (e.g., stapler + paper) independently, building an 80×80 RDM for each timepoint (see Methods for

details). Multiple regression beta estimates over time for each of the four predictor models are given in

Figure 3C, together with Bayesian one-sample t-tests evaluating beta > 0.

Two of these models predicted the neural RDM from a relatively early stage of stimulus processing: <u>Retinal</u>

<u>Size</u> (onset = 84 ms, peak = 152 ms) and <u>Pair Identity</u> (onset = 88 ms, peak = 176 ms). This was expected,

since both models capture visual features inherent to the stimuli such as pixel coverage and global shape.

Notably, information about both the object identities and their display size was also present in the neural

response at much later timepoints, suggesting that the visual system maintains representations of both of

these dimensions for some 500 ms after the objects come into view.

Figure 3. RSA for 80 individual object pair stimuli in Experiment 2 (i.e., treating each of the 4 versions for the 20 object pairs separately). **A)** The neural RDM averaged over the epoch between 180-250 ms. **B)** Binary RDMs for the stimulus design factors treated as categorical predictors in a multiple regression of the neural RDM series. **C)** Beta estimates for the four predictors included in the multiple regression, plotted as a function of time from stimulus onset. Shaded regions are within-subjects standard error. Lower panel shows colour coded Bayes Factors for Bayesian one-sample t-tests comparing beta against zero at each timepoint, for each predictor.

In contrast to the Pair Identity and Retinal Size models, the Real-world Size model requires similar neural

responses across stimuli with both distinct object identities and visual features (i.e., the response to

hat+scarf has to resemble that of *stapler+paper*, while also generalising across large and small versions of

those pairs). This real-world size model emerged as a significant predictor of the neural response at a

comparatively later stage of stimulus processing (onset = 184 ms, peak = 224 ms), and remained a relevant

predictor until as late as 400 ms.

The other high-level model yielded by our design was Relative Depth, which captured whether the objects

within a pair were implied to be at the same or different depth from the viewer. As is clear in Figure 3C, this

model was not a significant predictor of the neural data at any timepoint, suggesting that the objects' relative

sizing in each display did not modulate the neural response. Relative Depth was also not a relevant predictor

of the object pair neural data when considered as an isolated categorical predictor in a separate regression

analysis (data not shown). This was consistent with behavioural observations from Experiment 1, where we

found no evidence that the relative depth of objects within a pair influenced participants' real-world size

judgements.

RSA for object pairs collapsed across version

Since the relative depth of objects within a pair modulated neither the neural response to our object stimuli

nor participants' overt categorisations of real-world size (Experiment 1), we next ran a simplified RSA in

which the depth-match and depth-mismatch versions of every object pair were treated as a group.

Collapsing across version in this way had the effect of eliminating the Relative Depth, Retinal Size, and Pair

Identity models (the latter becomes the RDM diagonal), leaving only the Real-world Size model. We

evaluated the utility of this categorical predictor in a multiple regression analysis alongside three low-level

visual control models included as continuous predictors (see Methods). Our rationale here was to isolate

real-world size representations that could not be explained by inherent differences in visual features between

the object constellations representing small and large spatial scales. Since information about objects' real-

world size should become accessible only after the objects are recognised, representations of real-world size

that are controlled for visual feature differences serve as a useful proxy for object processing.

Figure 4 shows the results of this multiple regression analysis collapsing over the four versions of each

object pair. Real-world Size did not correlate with any of the three low-level visual control models (**pix:** rho =

-0.04, *p* = .608; **hmx:** rho = -0.05, p = .608; **cur:** rho = 0.05, p = .608, FDR-corrected). Bayesian one-sample

t-tests indicated that the model which predicted the neural response earliest in time was <u>Pixel Correlation</u>

(onset = 104 ms, peak = 156 ms), followed by the <u>HMAX (C2)</u> (onset = 148 ms, peak = 176 ms). These early

onsets of predictive power were consistent with these models capturing perceptual features of the images,

which should be relevant to the feed-forward sweep of visual processing. We did not find any evidence that

the <u>Curvature</u> model contributed unique predictive power to the neural response, although it was a

meaningful predictor when treated as the sole factor in a regression of the neural RDM series analysis (as

were all the low-level visual control models; data not shown).

Our primary interest in this analysis was to determine whether the <u>Real-world Size</u> model would offer any

unique explanation of the neural response when evaluated in the context of various low-level visual control

models. This was indeed the case, with <u>Real-world Size</u> remaining a significant predictor even when

simultaneously regressing out three visual control models (Figure 4A). The timecourse was similar to that

observed in the previous analysis (onset = 172 ms, peak = 200 ms), and remained intermittently relevant to

the neural response throughout the period examined here (i.e., up to 500 ms).

Figure 4. RSA for the 20 object pairs pooled across the four versions (see Figure 1B). A) Multiple regression betas for Real-world Size (in green) and low-level visual control predictors (in grey) of the neural RDM series. Shaded region for the RWS model is within-subjects standard error. Lower panel shows colour coded Bayes Factors for one-tailed t-tests (mean beta > 0) at each timepoint, for each predictor. Inset: Model intercorrelation matrix; asterisks indicate Spearman correlations significant at p <.01 (FDR corrected). Real-world Size was not significantly correlated with any of the low-level feature models. B) Models RDMs. Note that all models were confirmed as relevant predictors when treated as an isolated predictor of the neural RDM series (not shown here).

Comparison with single objects

In Experiment 1, observers were less able to judge the real-world size of objects when viewed in isolation compared to when they appeared in related pairs. Here we asked whether the neural response to single

objects contained information about their real-world size, once again controlling for visual feature differences

between large and small objects. We ran the same multiple regression analysis as for Object Pairs, in which

Real-world Size was a categorical predictor alongside three low-level visual control predictors derived from

the single object stimuli (i.e., pixel correlation, HMAX (C2), & Curvature). Figure 5 shows the resulting beta-

timecourse for the Real-world Size model of Single Object data, with the corresponding beta-timecourse for

object pair neural data overlaid in green. In summary, there was no evidence that Real-world Size was a

relevant predictor for the single object neural response. Real-world Size was also a significantly better

predictor for object pairs than for single objects around 200 ms after stimulus onset (Figure 5), providing a

possible neural correlate for the behavioural effect observed in Experiment 1.

Figure 5. Beta values for Real-world Size included as a categorical predictor in (separate) multiple regression

analyses for the single object (in grey) and object pair (in green) neural RDM series. Each regression also

included three low-level visual control models as continuous predictors (see Figure 4). Note that the object pair

betas here are identical to those in Figure 4 (green lines); shaded region is within-subjects standard error.

Lower panel shows colour coded Bayes Factors for each timepoint: circles are one-sample Bayesian t-tests

evaluating $\beta > 0$; triangles are paired Bayesian t-tests evaluating $\beta_{pair} > \beta_{single}$.

Comparisons with a Deep Convolutional Neural Network

Finally, we considered how real-world size information about our object pair stimuli emerged in the layers of

a deep convolutional neural network (AlexNet, Krizhevsky et al., 2012). Here we inspected the correlations

between the real-world size model and RDMs corresponding to the 5 convolutional and 2 fully-connected

layers of AlexNet. As can be seen in Figure 6B, real-world size was significantly correlated with the upper,

fully-connected layers (FC6: rho = 0.20, p = 0.0079; FC7: rho = 0.24, p = 0.0016, FDR-corrected), but had

little representational overlap with the early layers of AlexNet. Since low-level features differences between

the large and small stimuli should be well-captured by the lowest DNN layers, the fact that these layers did

not correlate with Real-world Size once again suggests that this model did not simply reflect visual

differences between the large and small stimuli.

To further examine the overlap of the real-world size model with AlexNet, we next ran multiple regressions of

the object pair neural RDM series using Real-world Size as a categorical predictor alongside the later RDMs

for FC6 and FC7 of AlexNet (treated as continuous predictors, see Figure 6A). Figure 6C and 6D show that

in both cases, Real-world Size contributes unique explanatory power for the neural response evoked by

object pairs, indicating that representations of spatial scale evoked by Object Pairs are not accounted for by

the high-level representations that the DNN gleaned from these stimuli.

Figure 6. Predicting the neural response to Object Pairs using Real-world Size and DNN activations. A) Model RDMs based on Real-world Size and activations on the final two fully-connected layers of AlexNet. B) Intercorrelation matrix for Real-world Size and AlexNet RDMs for all layers. Asterisks indicate correlations significant at p <.01, FDR adjusted. Where Real-world Size was significantly correlated with both fully-

467 connected layers, this model bore little resemblance to the lower layers of AlexNet. C&D) Beta estimates from

468 (separate) multiple regressions of the neural RDM series for object pairs that included <u>Real-world Size</u> as a

469 categorical predictor alongside continuous predictors based on AlexNet layers FC6 (C) and FC7 (D). Shaded

470 region is within-subjects standard error.

Discussion

To apprehend a familiar object is to rapidly and automatically appreciate its inherent 'real-world' size (Konkle

and Oliva, 2012a; Hagen et al., 2023). Investigations of both isolated objects and entire scenes have

revealed real-world size to be a key organising principle of the visual system, with the spatial scale of objects

influencing both their neural representation and the way observers recognise and respond to them (Konkle

and Oliva, 2012b). Here we exploited the automatic retrieval of real-world size information following object

recognition to examine how object processing is facilitated when the object forms part of a contextually-

associated pair (i.e., object constellation).

We found that observers judged the real-world size of ambiguous (silhouetted) objects faster and more

accurately when they appeared in contextually-associated pairs than when they appeared in isolation. This

inter-object contextual facilitation replicates the findings of Bar and Ullman (1996), whose participants

recognised ambiguous objects better when they appeared in the context of another related object. Moreover,

neural representations of real-world size evoked by silhouetted object pairs arose from around 170 ms after

stimulus onset and peaked around 200 ms. These representations endured even when controlling for

differences in large and small objects' visual features. Importantly, real-world size representations were only

evident for contextually-associated pairs of objects, and not for the individual object elements presented

alone. Furthermore, real-world size representations around 200 ms after stimulus onset were significantly

stronger for object pairs than for isolated objects.

We interpret these results as reflecting inter-object facilitation of object recognition (Bar and Ullman, 1996).

Here, integrating information across contextually-associated objects in a familiar constellation facilitated their

recognition, making it easier to access information about the objects' real-world size. On this interpretation,

the facilitatory interaction between the processing of individual objects must have occurred shortly before

200 ms (when real-world size was represented). This is substantially earlier than facilitatory interactions

between associated scenes and objects, which arise some 300 ms after stimulus onset (Brandman and

Peelen, 2017, 2023). An explanation for this difference could relate to the finding that scenes and objects are

processed in parallel ventral stream pathways (Levy et al., 2001; Park et al., 2011), such that interactions

between scenes and objects require interactions across pathways. By contrast, interactions between objects

could occur within the object processing pathway itself.

Alternatively, our results could also reflect the accumulation of evidence (about object identity, and thus also

real-world size) for both objects, but without facilitatory inter-object interactions. For example, each object

may provide weak evidence for either large or small real-world size, with this evidence accumulating for

multiple objects presented together. The behavioural and EEG results suggest that such evidence

accumulation is non-linear; for example, evidence may have been more likely to reach a critical real-world

size recognition threshold (and associated neural representation) for two versus one object. Future studies

could distinguish between this account and the inter-object facilitation account by testing a condition in which

objects are recombined (or "shuffled"; Kaiser et al., 2014) across pairs within each size condition. In such a

condition, both objects would still provide individual evidence for large or small real-world size, but would not

be expected to facilitate each other's recognition.

We also manipulated objects' relative depth, with the proportional retinal size of the two objects within the

pair suggesting they were either at the same or different depth. We hypothesized that objects inferred to be

at different depths to the viewer would be harder to integrate, similar to how disrupting objects' relative

spatial position impairs recognition (Bar and Ullman, 1996) and reduces neural measures of integration

(Quek and Peelen, 2020). However, there was no evidence that this manipulation influenced either overt

recognition of real-world size or the neural representations of real-world size evoked by object pairs. This

suggests that the visual system is tolerant to relative size when integrating information across objects. This

may reflect the variability of objects' relative sizes in daily life, where contextually-associated objects are

encountered at different depths (and thus have non-proportional retinal sizes). For example, a stapler can be

observed next to a piece of paper (Figure 1B), but is also frequently observed closer or farther away from

this object. On the other hand, given that texture is a strong cue for distance (Gibson, 1950; Todd and

Akerstrom, 1987), the silhouette stimuli used here may have impaired or reduced the degree to which

observers perceived the depth of the objects. Relative-depth effects for contextually-associated objects could

well be evident when texture and other internal object cues are preserved, as in photographs.

The data here also speak to the literature on the neural representation of real-world size itself. Real-world

size is a dimension that pertains to all stimuli along the object-scene continuum**.** At the level of individual

objects, real-world size is an organising principle within ventral occipitotemporal cortex (Konkle and Oliva,

2012b; He et al., 2013; Konkle and Caramazza, 2013). When retinal size is fixed, lateral ventral temporal

regions respond more strongly to objects of small real-world size (e.g., a tennis ball) compared to large (e.g.,

a desk), while medial temporal regions exhibit the opposite activation pattern (Konkle and Oliva, 2012b).

Such effects appear to reflect regional sensitivity to featural and functional characteristics that vary

systematically between small and large objects (Mullally and Maguire, 2011; Konkle and Oliva, 2012b;

Troiani et al., 2014; Julian et al., 2016; Long et al., 2018; Wang et al., 2022). Studies investigating the

timecourse of real-world size using single objects have shown that real-world size is reflected in the neural

response just 120 ms after stimulus onset (e.g., Khaligh-Razavi et al., 2018; Wang et al., 2022). Such early

real-world size representations likely reflect visual feature differences between large and small objects, such

as degree of rectilinearity (Long et al., 2018; Wang et al., 2022). At the same time, small and large objects

also vary systematically in conceptual and functional characteristics (e.g., potential for manipulation vs.

navigation), which also contribute to the neural dissociation between large and small items. In our case, we

found no evidence that isolated object silhouettes evoked representations of real-world size beyond what

could be accounted for by visual feature differences. This almost certainly relates to the 'degraded' nature of

our stimuli, whose silhouette composition significantly impedes object recognition.

To our knowledge, we are the first to measure the timecourse of real-world size representations for *object*

constellations, showing that real-world size is represented at around 200 ms after stimulus onset. Crucially,

these results are unlikely to reflect low-or mid-level visual feature differences between large and small

constellations, for several reasons. First, we selected our stimuli to avoid obvious differences between large

and small conditions and used silhouettes to remove texture and colour features. Second, we included the

output of multiple computational models in the EEG analyses to show that visual feature differences could

not account for the real-world size representation at 200 ms. Finally, the absence of real-world size

representations for the same objects presented in isolation further argues against a feature driven effect.

If not the representation of size-covarying visual features, what drives the different neural activity patterns for

large and small constellations? One possibility is that recognizing the constellations activated corresponding

scene representations, such that the activity patterns reflect scene size (e.g., desktop *vs.* living room). Neural

responses to scene images capture information about spatial scale as early as 100 ms after stimulus onset

(Cichy et al., 2017), though as for objects, such early representations are likely driven by differences in low-

level features across small and large scenes (Stansbury et al., 2013). More abstract signals of scene size

(i.e., representations that generalise across image-level changes in clutter, luminance, and contrast) appear

to arise later, from around 250 ms (Cichy et al., 2017), and are evident even for auditory stimuli that capture

the spatial extent of real-world spaces (Teng et al., 2017).

More generally, our results raise the question of how object and scene representations are related. By

moving from single objects to object constellations, it becomes clear that the object-scene distinction is not

so clear-cut. Indeed, even the processing of single objects may involve processing their real-world context –

i.e., surrounding scene. Seeing a large object necessarily implies a large space, activating scene-selective

cortex (Mullally and Maguire, 2011). Furthermore, object representations in scene-selective regions reflect

the context within which objects are usually observed, including their co-occurrences with other objects

(Aminoff et al., 2007; Bonner and Epstein, 2021; Fu et al., 2022). Our results align with these findings,

showing that multiple objects viewed together activate the objects' shared context within 200 ms.

To conclude, our results reveal the timecourse of object processing for objects comprising familiar

constellations, showing that neural responses code for the objects' real-world size around 200 ms after

stimulus onset only when the objects appear in pairs, and not when they appear in isolation. We interpret

these findings as reflecting inter-object facilitation between contextually-associated objects. Our study raises

several new questions, including about the relationship between representations along the continuum from

objects to scenes.

References

Aminoff E, Gronau N, Bar M (2007) The Parahippocampal Cortex Mediates Spatial and Nonspatial Associations. Cerebral Cortex 17:1493-1503.

Auckland ME, Cave KR, Donnelly N (2007) Nontarget objects can influence perceptual processes during object recognition. Psychon Bull Rev 14:332-337.

Baeck A, Wagemans J, Op de Beeck HP (2013) The distributed representation of random and meaningful object pairs in human occipitotemporal cortex: The weighted average as a general rule. Neuroimage 70:37-47.

Bar M (2004) Visual objects in context. Nature Reviews Neuroscience 5:617.

Bar M, Ullman S (1996) Spatial Context in Recognition. Perception 25:343-352.

Biederman I (1972) Perceiving real-world scenes. Science 177:77-80.

Biederman I, Glass AL, Stacy EW (1973) Searching for objects in real-world scenes. Journal of Experimental Psychology 97:22-27.

Bonner MF, Epstein RA (2021) Object representations in the human brain reflect the co-occurrence statistics of vision and language. Nature communications 12:4081.

Brandman T, Peelen MV (2017) Interaction between Scene and Object Processing Revealed by Human fMRI and MEG Decoding. J Neurosci 37:7700-7710.

Brandman T, Peelen MV (2023) Objects sharpen visual scene representations: evidence from MEG decoding. bioRxiv:2023.2004.2006.535903.

Cichy RM, Khosla A, Pantazis D, Oliva A (2017) Dynamics of scene representations in the human brain revealed by magnetoencephalography and deep neural networks. Neuroimage 153:346-358.

Coutanche MN, Thompson-Schill SL (2019) Neural activity in human visual cortex is transformed by learning real world size. Neuroimage 186:570-576.

Davenport JL (2007) Consistency effects between objects in scenes. M&C 35:393-401.

Fu Z, Wang X, Wang X, Yang H, Wang J, Wei T, Liao X, Liu Z, Chen H, Bi Y (2022) Different

computational relations in language are captured by distinct brain systems. Cerebral Cortex 33:997-1013.

Ganis G, Kutas M (2003) An electrophysiological study of scene effects on object identification. Brain Res

Cogn Brain Res 16:123-144.

Gibson JJ (1950) The Perception of Visual Surfaces. The American Journal of Psychology 63:367-384.

Green C, Hummel JE (2006) Familiar interacting object pairs are perceptually grouped. Journal of

Experimental Psychology: Human Perception and Performance 32:1107.

Hagen S, Zhao Y, Moonen L, Ulken N, Peelen M (2023) What drives the automatic retrieval of real-world

object size knowledge?

He C, Peelen MV, Han Z, Lin N, Caramazza A, Bi Y (2013) Selectivity for large nonmanipulable objects in

scene-selective visual cortex does not require visual experience. Neuroimage 79:1-9.

Jaccard P (1901) Étude comparative de la distribution florale dans une portion des Alpes et des Jura. Bull

Soc Vaudoise Sci Nat 37:547-579.

Julian JB, Ryan J, Epstein RA (2016) Coding of Object Size and Object Category in Human Visual

Cortex. Cerebral Cortex 27:3095-3109.

Kaiser D, Stein T, Peelen MV (2014) Object grouping based on real-world regularities facilitates

perception by reducing competitive interactions in visual cortex. Proceedings of the National Academy of

Sciences of the United States of America 111:11217-11222.

Kaiser D, Stein T, Peelen MV (2015) Real-world spatial regularities affect visual working memory for

objects. Psychon Bull Rev 22:1784-1790.

Kaiser D, Quek GL, Cichy RM, Peelen MV (2019) Object Vision in a Structured World. Trends Cogn Sci

23:672-685.

Khaligh-Razavi SM, Kriegeskorte N (2014) Deep Supervised, but Not Unsupervised, Models May Explain

IT Cortical Representation. PLOS Computational Biology 10:e1003915.

Khaligh-Razavi SM, Cichy RM, Pantazis D, Oliva A (2018) Tracking the Spatiotemporal Neural Dynamics

of Real-world Object Size and Animacy in the Human Brain. J Cogn Neurosci 30:1559-1576.

Konkle T, Oliva A (2012a) A familiar-size Stroop effect: Real-world size is an automatic property of object

representation. Journal of Experimental Psychology: Human Perception and Performance 38:561-569.

Konkle T, Oliva A (2012b) A real-world size organization of object responses in occipito-temporal cortex.

Neuron 74:1114-1124.

Konkle T, Caramazza A (2013) Tripartite organization of the ventral stream by animacy and object size.

Journal of Neuroscience 33:10235-10242.

Kriegeskorte N, Kievit RA (2013) Representational geometry: integrating cognition, computation, and the

brain. Trends Cogn Sci 17:401-412.

Kriegeskorte N, Mur M, Bandettini P (2008) Representational Similarity Analysis – Connecting the

Branches of Systems Neuroscience. Front Syst Neurosci 2:4.

Krizhevsky A, Sutskever I, Hinton GE (2012) Imagenet classification with deep convolutional neural

networks. In: Advances in neural information processing systems, pp 1097-1105.

Kutas M, Federmeier KD (2011) Thirty years and counting: finding meaning in the N400 component of the

event-related brain potential (ERP). Annual review of psychology 62:621-647.

Levy I, Hasson U, Avidan G, Hendler T, Malach R (2001) Center-periphery organization of human object

areas. Nat Neurosci 4:533-539.

Li SPD, Bonner M (2020) Curvature as an Organizing Principle of Mid-level Visual Representation: A

Semantic-preference Mapping Approach. In: NeurIPS 2020 Workshop SVRHM.

Long B, Yu C-P, Konkle T (2018) Mid-level visual features underlie the high-level categorical organization

of the ventral stream. Proceedings of the National Academy of Sciences 115:E9015-E9024.

Mudrik L, Lamy D, Deouell LY (2010) ERP evidence for context congruity effects during simultaneous

object–scene processing. Neuropsychologia 48:507-517.

Mullally SL, Maguire EA (2011) A new role for the parahippocampal cortex in representing space. Journal

of Neuroscience 31:7441-7449.

Nah JC, Geng JJ (2022) Thematic object pairs produce stronger and faster grouping than taxonomic

pairs. Journal of Experimental Psychology: Human Perception and Performance 48:1325-1335.

Oosterhof NN, Connolly AC, Haxby JV (2016) CoSMoMVPA: Multi-Modal Multivariate Pattern Analysis of

Neuroimaging Data in Matlab/GNU Octave. Front Neuroinform 10.

Park S, Brady TF, Greene MR, Oliva A (2011) Disentangling scene content from spatial boundary:

complementary roles for the parahippocampal place area and lateral occipital complex in representing

real-world scenes. J Neurosci 31:1333-1340.

Peelen M, Berlot E, de Lange F (2023) Predictive processing of scenes and objects.

Quek GL, Peelen MV (2020) Contextual and Spatial Associations Between Objects Interactively Modulate

Visual Processing. Cerebral Cortex 30:6391-6404.

Riesenhuber M, Poggio T (1999) Hierarchical models of object recognition in cortex. Nature neuroscience

2:1019-1025.

Serre T, Kreiman G, Kouh M, Cadieu C, Knoblich U, Poggio T (2007) A quantitative theory of immediate

visual recognition. Progress in brain research 165:33-56.

Stansbury DE, Naselaris T, Gallant JL (2013) Natural scene statistics account for the representation of

scene categories in human visual cortex. Neuron 79:1025-1034.

Teng S, Sommer VR, Pantazis D, Oliva A (2017) Hearing Scenes: A Neuromagnetic Signature of

Auditory Source and Reverberant Space Separation. eNeuro 4.

Todd JT, Akerstrom RA (1987) Perception of three-dimensional form from patterns of optical texture.

Journal of Experimental Psychology: Human Perception and Performance 13:242-255.

Troiani V, Stigliani A, Smith ME, Epstein RA (2014) Multiple object properties drive scene-selective

regions. Cerebral cortex 24:883-897.

Võ MLH, Wolfe JM (2013) Differential Electrophysiological Signatures of Semantic and Syntactic Scene

Processing. Psychol Sci 24:1816-1823.

Võ MLH, Boettcher SEP, Draschkow D (2019) Reading scenes: how scene grammar guides attention and

aids perception in real-world environments. Current Opinion in Psychology 29:205-210.

Wang R, Janini D, Konkle T (2022) Mid-level Feature Differences Support Early Animacy and Object Size

Distinctions: Evidence from EEG Decoding. J Cogn Neurosci:1-11.

Wischnewski M, Peelen MV (2021) Causal neural mechanisms of context-based object recognition. eLife

10:e69736.

Xu S, Liu X, Almeida J, Heinke D (2021) The contributions of the ventral and the dorsal visual streams to

the automatic processing of action relations of familiar and unfamiliar object pairs. Neuroimage

245:118629.