Integrative Multiscale Biochemical Mapping of the Brain via Deep-Learning-Enhanced High-Throughput Mass Spectrometry

Yuxuan Richard Xie[1][2], Daniel C. Castro[2][3], Stanislav S. Rubakhin[2][4],

Jonathan V. Sweedler[1][2][3][4]*, Fan Lam[1][2]*

[1] Department of Bioengineering, [2] Beckman Institute for Advanced Science and Technology,

[3] Department of Molecular and Integrative Physiology, [4] Department of Chemistry

University of Illinois Urbana-Champaign, Urbana, IL 61801, United States.

*Corresponding Authors.
Email: jsweedle@illinois.edu, fanlam1@illinois.edu

Abstract:

Elucidating the spatial-biochemical organization of the brain across different scales produces invaluable insight into the molecular intricacy of the brain. While mass spectrometry imaging (MSI) provides spatial localization of compounds, comprehensive chemical profiling of large brain regions in three dimensions by MSI with single-cell resolution has not been achieved. We demonstrate complementary brain-wide and single-cell biochemical mapping via MEISTER, an integrative experimental and computational mass spectrometry framework. MEISTER integrates a deep-learning-based reconstruction that accelerates high-mass-resolving MS by 15-fold, multimodal registration creating 3D molecular distribution, and a data integration method fitting cell-specific mass spectra to 3D data sets. We imaged detailed lipid profiles in tissues with data sets containing millions of pixels, and in large single-cell populations acquired from the rat brain. We identified region-specific lipid contents, and cell-specific localizations of lipids depending on both cell subpopulations and anatomical origins of the cells. Our workflow establishes a blueprint for future developments of multiscale technologies for biochemical characterization of the brain.

Introduction

1
Genomic and transcriptomic tools have transformed neuroscience by allowing us to visualize,
untangle, and understand the spatiotemporal expression patterns of thousands of genes in the
brain as well as how they are related to various functions and diseases[1–3]. Beyond gene
expression profiles, the biochemical compositions and dynamics of metabolites, lipids, peptides
and proteins play essential roles in many neurobiological processes[4,5], and have been implicated
in neurodevelopment[6], learning, memory[7], aging[8,9], and a myriad of neurological or
neurodegenerative diseases[10]. However, approaches to characterize these molecular
compositions lag behind transcriptomics, especially at the single-cell and whole-brain level.
Recent technical advances in single-cell measurements using isolated populations of individual
cells and mass spectrometry (MS) have great potential to solve these bottlenecks, prompting
single-cell metabolomics to be listed as one of the technologies to watch in 2023[11]. MS is
recognized as a key method of choice for metabolomic and proteomic measurements due to its
unique capability of untargeted, sensitive and specific detection of numerous biomolecules in both
tissues[12,13] and single cells[14–17]. Spatial organizations of biomolecules in the brain have been
mapped at cellular and subcellular resolution using advanced mass spectrometry imaging (MSI)
methods[18–21]. Nevertheless, small metabolites and lipid profiling of large brain regions in three
dimensions at single-cell resolution with simultaneous brain-wide coverage and chemical detail
(important for untargeted and unbiased molecular characterization) has yet been achieved. We
provide several innovations to the existing workflows that enable multiscale biochemical profiling
at a scale never attempted before. First, as existing high-resolution MSI is throughput limited, we
integrate deep learning approaches to enhance the high-mass-resolving Fourier Transform MS
(FTMS) acquisition by 10-fold, enabling imaging of many tissue sections with brain-wide coverage
and reconstruction of three-dimensional (3D) molecular distributions/atlases. Second, high-
throughput single-cell MS (SCMS) allows populations of individual cells to be characterized[22];
however, isolated cells lack spatial context of tissue. We integrate both workflows (high-
throughput tissue MSI and SCMS) to map the chemical profiles of single cells onto the tissue
sections, allowing multiscale characterization of spatial-biochemical organization of the brain.

More specifically, we introduce the MEISTER (**M**ass sp**E**ctrometry for **I**ntegrative **S**ingle-
cell and **T**issu**E** analysis with deep learning-based **R**econstruction) framework that integrates
high-throughput MS platforms with several technical innovations: (1) A deep-learning-based
signal reconstruction approach capable of producing high-resolution mass spectra with
significantly enhanced throughput for both tissue MSI and SCMS, (2) a multimodal image
registration technique that produces coherent 3D reconstruction of MSI data from many tissue

sections and affords quantitative analysis of regional chemical profiles, (3) a computational approach that exploits dictionary learning concepts to create and map cell-specific chemical profiles to tissue imaging data for multiscale integration. We validated MEISTER using computational simulations as well as experimental tissue MSI and SCMS data. With MEISTER, we achieved 3D mapping of the rat brain with an unprecedented combination of large volume coverage, high spatial resolution (50 μm lateral and 16 μm sections) over millions of pixels, and high chemical content (>1,000 lipid features). We also profiled 13,566 single cells that were isolated from five rat brain regions and built cell-type-specific chemical dictionaries, which were then mapped to the tissue images, to obtain spatially-resolved cell-type distributions across the brain. To further demonstrate the capabilities of our framework, we studied how lipids associate with the brain's anatomical structures. We extracted lipid profiles from 11 brain regions by registering serial MSI sections to rat magnetic resonance imaging (MRI) brain atlas via a data-driven nonlinear image registration method that generated volumetric reconstruction of thousands of lipid features over a large brain volume while identifying region-specific lipid contents. With the single cell-to-tissue data integration approach, we identified heterogeneous lipid distributions and differential lipid features at both tissue and single-cell levels, discovering relationships of single-cell biochemical profiles to region-specific spatial distributions of lipids. The MEISTER approach establishes a blueprint for multiscale biochemical characterization of the brain which can be adapted and generalized beyond lipid mapping, e.g., neurotransmitters and peptides.

Results

MEISTER: A deep learning enabled, high-throughput multiscale MSI framework. MEISTER integrates high-throughput MS experiments, a deep-learning-based signal reconstruction method, and data-driven high-dimensional MSI analysis, to enable brain-wide, multiscale profiling of brain biochemistry. To resolve detailed chemical contents, we collected both high-resolution tissue MSI and SCMS data leveraging a high-throughput experimental platform using matrix-assisted laser desorption/ionization (MALDI) Fourier-transform ion cyclotron resonance (FT-ICR) MS. Achieving brain-wide coverage and cell-specific profiling requires probing a large number of tissue sections and cells (Fig. 1a), which is time prohibitive on high-mass-resolution platforms such as FT-ICR (see Methods, signal modeling). To this end, we developed a deep-learning model to reconstruct high-resolution MS data from low-mass resolving measurements (Fig. 1b). In short, we model the underlying high-dimensional transient signals S as points on a low-dimensional nonlinear manifold embedded in the high-dimensional space. These low-dimensional embeddings Z can be effectively learned by training a deep autoencoder (DAE) network, using experimental and/or

Figure 1| The MEISTER framework for multiscale biochemical profiling using high-mass-resolution MS enhanced by computational methods. **a**, Obtained from surgically extracted brain, serial tissue sections are imaged for 3D MSI using a fast acquisition strategy, and single cell populations prepared by tissue dissociation are probed with high-throughput image-guided MS. **b**, A deep learning model reconstructs high-mass resolving and high-SNR MS data from the low-mass resolution measurements acquired with fast acquisitions by exploiting low-dimensional manifold structure for high-dimensional MS data, producing large data sets with millions of pixels, which was previously time prohibitive with the conventional acquisition. **c**, Our multifaceted data analysis pipeline uses various data-driven methods for multimodal image registration to align MSI with 3D anatomical MRI for volumetric reconstruction, identifying differential lipid distributions, tissue typing using MS data, and integrating MSI and single-cell MS data for joint analysis and resolving cell-type-specific contributions at the tissue level across the brain.

simulated full transients with the desired mass resolution. The presence of low-dimensional representations implies that high-mass-resolution spectra can be reconstructed from significantly shorter transients than conventionally acquired. We realized this by training a "regressor" network jointly with the DAE to estimate the low-dimensional embeddings Z from only short transients $\widehat{S}$, which were subsequently decoded (by the same decoder from the DAE) into high-mass-resolution data (More details in Extended Data Fig. 1a, and Methods). For 3D MSI, the networks were trained only on a small number of tissue sections and applied to reconstruct data for the remaining sections consisting of millions of pixels (Extended Data Fig. 1b, Methods). For SCMS, a small

subset of cells were used for training and applied to large cell populations (Extended Data Fig.

1c), allowing a much higher data collection throughput. Particularly, an MSI data set containing

more than 1.5 million pixels only required 20 h of acquisition time, which would have taken about

300 h using the conventional acquisition approach. This allowed us to image 16-µm-thick serial

sections from rat brains that covers ~10 mm range (along z) with a 50 µm raster width used in

MSI. In conjunction with the MSI, 13,566 single cells isolated from five major brain structures (the

cerebral cortex, hippocampus, thalamus, striatum, corpus callosum) were probed by an image-

guided MALDI SCMS[23] approach (Fig. 1a). Detailed experimental parameters for MSI and SCMS

can be found in Methods.

To enable biochemical characterization of the brain and knowledge discovery from such

unprecedented data, we developed and integrated several data-driven methods for analyzing the

high-dimensional, multiscale 3D MSI and SCMS data (Fig. 1c). First, The MSI data were mapped

to MRI and the Waxholm Space atlas through a customized nonlinear image registration

procedure (Fig. 1c, left panel), which enabled a coherent volumetric MSI reconstruction from the

sections imaged. Through registration, we extracted the mass spectra of 11 major brain structures

across the 3D volume and identified spatially differential biochemical profiles. Next, we classified

the brain structures based on their lipids for tissue typing, which identified enriched lipid species

in each region/tissue type. To connect the tissue MSI and SCMS across different scales, we built

cell-type-specific "chemical dictionaries" and introduced a joint union-of-subspaces (UoSS) fitting

technique that resolved cell-specific contributions to the spatio-chemical contents at the brain-

wide tissue level for the first time (Fig. 1c, right panel).

Validation of the deep-learning-based MSI reconstruction. Using a carefully designed,

biochemically-relevant simulated MSI dataset that contained rich chemical details and brain-

mimicking spatial variations, we trained and validated the proposed deep-learning-based method

for reconstructing high-mass-resolution mass spectra and ion images from noisy short transients

(Extended Data Fig. 2a,b and Methods). Our method showed near ground-truth level fidelity with

more than 10 dB gain in signal-to-noise ratios (SNRs) over the noisy reference using only 5%

data. We compared the performance of our model (Extended Data Fig. 2c) for spectral and spatial

feature recovery in the simulated dataset over the standard FT reconstruction and a previously

described linear subspace approach[24,25] (Extended Data Fig. 2d). Compared to the standard FT

reconstruction from full transients, our method also yielded a higher SNR, owing to the denoising

effects of the learned low-dimensional representation.

To evaluate our method on experimental data, we trained the model using high-resolution

MSI data acquired from rat brain tissue sections using an FT-ICR mass spectrometer. We then

validated the model using reference full-transient data acquired at different days from tissue

sections not seen during training. For the noise contaminated reference (0.731s transient duration,

1 million temporal points), images from peaks that were indicated in the single-pixel mass spectra

showed ions with distinct spatial distributions, whereas the signals were unresolved in the reduced

data with short transients (first 64,000 temporal points) due to poor mass resolution

(Supplementary Fig. 1a, b). The deep-learning-based reconstruction from the reduced data

successfully resolved nearby mass features, providing enhanced signal strength over the

subspace-based reconstruction also from the same reduced data (Fig 2a, b, Supplementary Fig.

1b). Our method yielded quantitatively better spectral and spatial fidelity w.r.t. the reference than

reduced data and subspace reconstruction. This was further supported by subsequent principal

component analysis (PCA) and spatial segmentation through k-means clustering on the

reconstructed spectral features (Extended Data Fig. 2e, f, Supplementary Fig. 2), with our method

producing less noisy spatial parcellation. Our evaluation suggests that the model can learn robust

nonlinear low-dimensional features from complex and noisy imaging data, while accurately

predicting those features from short transients even for the highly heterogeneous brain tissue.

Furthermore, we examined the model performance for reconstructing SCMS data.

Specifically, we trained a model using high-resolution SCMS data from approximately 4,000 cells,

and tested on 1,000 independent cells (Methods). We found high correlation scores (Pearson r >

0.95) between full-resolution reference and reconstructed single-cell spectra. Consistent

molecular profiles across individual cells (Extended Data Fig. 3a) resulted in nearly identical

outcomes via uniform manifold approximation and projection (UMAP) and unsupervised

clustering (Extended Data Fig. 3b). Even with larger chemical heterogeneity, our model was able

to effectively recover the variations within and across cell populations (Extended Data Fig. 3c).

High-resolution 3D MSI with large volume coverage. High-mass-resolving MSI with FT-ICR or

Orbitrap mass spectrometers has been limited to 2D imaging or a small number of tissue sections

due to the throughput constraint, especially when high spatial resolution is desired (e.g., <50 μm

pixel grid across a whole rat brain slice). The higher throughput afforded by MEISTER allowed us

to spatially profile metabolites and lipids for many serial tissue sections that cover a large volume

of the brain. To demonstrate this capability, we imaged 37 coronal and 39 sagittal sections of the

rat brains, and used data with the targeted mass resolution from a few tissue sections for training

(Methods). We were able to efficiently reconstruct high-mass resolution, high-SNR spectra from

Figure 2| High-throughput MSI via MEISTER. **a**, Correlation measures of mass spectra produced by different reconstruction methods; the case "reduced" stands for a standard FT reconstruction from the short transients (reduced data); **b**. Comparisons of mass spectra and corresponding ion images to reference (top two columns) show enhanced signal strength by MEISTER. Bottom row depicts line scans for signal intensity distributions in reference, subspace, and MEISTER images. **c**. Averaged mass spectra from three different tissue sections for the reduced data (top) and our deep learning model (bottom). Inlet displays a small *m/z* window of the mass spectra. **d**, Ion images obtained from raw MSI data (left columns) and deep learning reconstructed MSI data (right columns) at *m/z* 813.4838 and m/z 813.6009. **e**, Reconstruction improved SNRs as shown in SNR distributions for signals at *m/z* 813.4838 (top, 100-fold higher) and at *m/z* 813.6009 (bottom, 10-fold higher) than raw data. **f**, The 3D volumetric reconstruction of localization of two representative lipids. **g**, Volcano plots show differential lipid distributions in hippocampus (top) and thalamus (bottom). Red dots indicate significantly different lipid features for the brain region.

raw data acquired with short transient duration (i.e., <10% collection time per transient) for all remaining serial sections for approximately 2 million total pixels in each 3D data set (Extended Data Fig. 4a, Supplementary Fig. 3). Reconstructed data exhibited significantly improved quality

with larger than 10-fold increment in SNRs over the raw data processed by traditional FT analysis

while maintaining sub-ppm mass accuracy for putative lipid assignment (Fig. 2c, d, e, Extended

Data Fig.4b, c).

To enable spatially resolved biochemical profiling across the brain, we designed and

implemented a multimodal registration strategy to align the misaligned reconstructed MSI sections

to a high-resolution rat brain MRI[26] to form a volumetric reconstruction. Inspired by a previously

proposed approach, we applied parametric UMAP[27] to embed the MSI hyperspectral data cube

into "feature" images for co-registration with MRI anatomical images (Extended Data Fig. 5a). By

learning the embedding process, our method can simultaneously obtain low-dimensional

representations of the entire 3D MSI data cube (Extended Data Fig. 4d, Supplementary Fig. 4 a,

b). These low-dimensional features are effective in delineating tissue morphology for cross-

modality image registration (Extended Data Fig. 4d, e, Supplementary Fig. 4c, d). Images of three

selected UMAP dimensions of each 2D tissue section were converted to a single gray-scale

image to yield anatomical contrast and registered to its corresponding MRI slice via affine and B-

spline registration (Extended Data Fig. 5b, Methods). The obtained transformations can then be

applied to all ion images, resulting in the final high-quality volumetric reconstruction of the ion

distributions (Fig. 2f, g, Supplementary Fig. 5). To the best of our knowledge, this is the first time

that 3D reconstruction of the biochemical distribution of the brain with the combination of coverage,

spatial resolution and chemical detail (e.g., >1000 lipid features; see below) has been generated.

3D MSI reconstruction enabled region-specific lipid profiling across the brain. Brain lipids

serve as both inter- and intracellular signaling molecules and play important functional roles in

the formation of morphologically distinct membranes of the diverse neuronal cells[28,29]. Previous

studies on brain lipids showed that lipid enrichments may be distinct across different brain

anatomical structures[8,30,31]. With our data, a total of 1156 lipid features annotated by LIPID

MAPS[32], 728 matched with <3 ppm error were extracted from 3D MSI reconstruction for

downstream analysis (Fig. 3). We performed both single-pixel analysis of individual tissue

sections through UMAP visualization (Fig. 3b, Supplementary Fig. 5) and supervised classification

with gradient-boosted trees. Accurate brain region classification of pixels based on lipid profiles

can be achieved with an average classifier area-under-curve (AUC) 0.96±0.02 (Supplementary

Fig. 6a, Methods). We also investigated the feature attributions to interpret model decisions and

selected the lipids that were contributing most to the anatomical classifications (Methods). Our

analysis uncovered the anatomically differential lipid compositions of the brain, as shown by the

Figure 3| Differential lipid profiles across 11 brain structures revealed by high-resolution 3D MSI. a, Atlas annotations colored for 11 brain regions with abbreviations. **b**, Low-dimensional UMAP embeddings of the pixel-wise lipid profiles across different brain serial sections, revealing region-specific lipid distributions across a tissue volume. **c**, Interpreting the machine learning model trained to classify brain region using lipid profiles reveals attribution of lipids most discriminative for specific brain structures. Examples of top predictive lipid features show distinct spatial distributions and feature attribution maps across the brain (left panel). **d**, UMAP analysis of the average lipid profiles from different regions across the entire 3D volume (each dot representing region per tissue section). **e**, Regional distributions of myelination-related lipids (HexCer, Cer, and LPC) annotated protonated ion and quantified by log2 of fold change, and **f,** representative ion images corresponding to the lipids described in **e**.

ion images and feature attribution maps of the top-scoring features (Fig. 3c, Supplementary Fig. 7). Multivariate analysis of the 3D data was performed on the mass spectra intensity profiles of each brain region (averaged per region, per tissue section). UMAP embeddings showed a preservation of the relative spatial organizations of brain regions, which contain gray matter, white matter, or a mixture of both (Fig. 3d). The near perfect classification accuracy of anatomical structures was achieved (Supplementary Fig. 6e) using averaged region-specific lipids, indicating

that MEISTER robustly uncovered anatomically specific biochemical profiles for the entire tissue
volume. The mean intensities of the most discriminative lipid features from the classification model
were summarized (Supplementary Fig. 6f). Among these features, we identified highly elevated
region-specific lipids by comparing one structure against the rest within the tissue volume; for
instance, PC O-(20:4) and Cer (42:6) were elevated in the hippocampal region and the corpus
callosum respectively. We further examined how sphingolipids, a lipid category critical to brain
development and function, are regionally distributed (Fig. 3e, f). Hexosylceramide (HexCer)
exhibits higher level in thalamus, brainstem, and superior colliculus, which contain large amount
of nerve fiber projections responsible for sensation. Ceramide (Cer), abundant in the myelin
sheath around the nerve fibers, is found elevated in subcortical white matter such as the corpus
callosum and corticofugal pathway, with similar a trend observed for sphingomyelin (SM). In
subcortical areas, a higher level of lysophosphatidylcholine (LPC) is also found, perhaps due to
its emphasized role in myelination and neuronal membrane synthesis[33].

Multiscale data integration via mapping single-cell chemical profiles to tissue imaging data.
Our high-throughput multiscale tissue MSI and SCMS data enabled integrative analysis to
combine their powers for investigating cell-specific biochemical composition in tissues. High-
throughput 3D MSI allows brain-wide biochemical characterization (e.g., lipid mapping
demonstrated above), but the information at each tissue pixel contains convolved biochemical
fingerprints of multiple cell types. MSI with subcellular-level resolution has been demonstrated[18,19]
but with limited tissue coverage. Furthermore, brain cells often are not organized into regular grids
but interwind in complex ways. On the other hand, SCMS data acquired from individual cells
dissociated from brain tissues provide cell-specific mass spectra but with limited spatial
information. To integrate these two types of measurements, we reconstructed SCMS data from
13,566 cells (Methods), and annotated SCMS data using the lipid features from the tissue MSI
data (considering presence of both intracellular and extracellular lipids; Methods, feature cross-
annotation), resulting in 344 cross-annotated lipids in single cells. Using these lipid species, we
obtained 18 single-cell clusters defined by lipid contents, each cluster containing mixed cell
populations from different anatomical regions (Fig. 4a). We characterized the similarity among
cells across different clusters, as well as identified region-specific lipid markers, suggesting both
intra- and inter-regional diversity of cellular lipids (Extended Data Fig. 6a). Single cells within the
corpus callosum contain a higher level of sphingolipids, consistent with observations from the
tissue MSI data (Extended Data Fig. 6b). Differential single-cell lipid marker analysis was carried

out for other brain regions, showing agreement between cellular- and tissue-level lipidomes

(Extended Data Fig. 6c).

Figure 4| Joint visualization and analysis of tissue MSI and SCMS data. **a**, A total of 13,566 cells with
344 cross-annotated lipid features are subjected to UMAP and clustering analysis. 18 cell clusters were
identified (left) and each cluster contains cells from different brain regions (right). **b**, Cell-specific chemical
dictionaries (lipids) extracted, e.g., from cluster 2, 6, and 13 (20 basis items were obtained in each
dictionary). **c-e**, Results of our proposed UoSS fitting for mapping of cell-type-specific dictionaries (obtained
from SCMS data) to the tissue MSI data. **c**, Estimated contributions of cell-specific biochemical signatures
across brain regions (from the UoSS coefficients). Distinct cell compositions can be resolved for different
regions. Images show results of mapping contributions of each cell cluster to individual pixels in different
tissue sections (left three columns), and the percent compositions of regional cell populations (right column)
for each cluster. **d**. Signal intensities from single tissue pixels obtained with MSI are well correlated with the
model fitted values (mean correlation coefficients > 0.6 for all regions, bottom box plot). **e**, Top four images
illustrate spatial consistency between the actual tissue images and the fitted data. The consistency is
evaluated for 344 ion images by spatial correlation across different mean signal intensity ranges. Lipids at
high mean intensity range have slightly better fitting results than ones at lower intensity range (lower box
plots). Brain region abbreviations: cc. corpus callosum, cor. cortex, hip. hippocampus, str. striatum, tha.
thalamus.
20

To integrate tissue and single-cell data and resolve cell-type-specific contributions at each

image pixel, we developed a new UoSS fitting strategy exploiting cell-specific chemical

dictionaries. Specifically, we performed non-negative matrix factorization (NMF) to extract sets of

chemical "basis" that represent chemical variations within each cell cluster (Methods). These

bases are "dictionaries" that promote sparsity and parts-based representations that delineate the

biochemical components in each cell cluster[34,35], ideal for stratifying cellular biochemical

signatures. For each of the 18 clusters, we extracted 20 non-negative single-cell dictionary items

(Fig. 4b, Supplementary Fig. 8b), and used a UoSS linear regression model to fit all

Figure 5| Integrative analysis of hippocampal tissue MSI and single-cell data. a, A total of 2692
hippocampal cells were probed and data were subjected to UMAP and clustering analysis, producing 8
chemically unique single-cell clusters in terms of lipid profiles. **b**, Maps of resolved cell-type contributions
from fitting the cell-specific chemical dictionaries to tissue data. **c**, Correlation matrix for weights obtained
from 8 clusters. **d**, Basis values averaged on 20 dictionary items versus fold change for lipid features in
cluster 0. **e**, Chemical dictionaries extracted for cluster 0 and cluster 1, with arrows indicating dominant
cluster-specific lipid features. **f**, Ion images showing the distributions of lipids that are more cluster specific
within the hippocampal region. ST(22:0) and TG(46:7) were selected based on cluster 0 basis values,
whereas LPE O-(16:0) and PG (48:8) were determined by cluster 1 basis.

components to tissue MSI data while forcing model weights to be non-negative (Methods). The

weights can then be interpreted as the cell-type-specific contributions and yielded deconvolved

cellular features at every tissue pixel (Fig. 4c). By analyzing the weights of individual cell-type

clusters with respect to brain regions, we identified distinct lipid spatial organizations at the single-cell level. For example, two clusters (0 and 2) are more enriched in cortex and hippocampal regions (Fig. 4c), consistent with the observation in Fig. 4a. Although these two clusters have similar cell numbers from each region, one is more localized to the granular layer of the dentate gyrus and pyramidal layer, whereas the other is more general to Cornu Ammonis (CA) areas. Similarly, several clusters show strong spatial contributions toward the thalamus, corpus callosum and striatum (Fig. 4c). From single-cell fitting, we found a moderate to high spectral and spatial correlation of the fitted signal intensity to the original tissue signal intensity, indicating the alignment of SCMS and MSI data (Fig. 4d, e). Note that some lipid features show negative correlation after spatial reconstruction using single-cell data. These might represent extracellular lipid components, false positive annotations, or modeling errors.

To further elucidate the spatial organization of cell subpopulations within a certain anatomical region, we jointly examined hippocampal-only SCMS and tissue MSI data (Fig. 5). A total of 2,692 cells (103 annotated lipid features) were analyzed with MSI data through the joint fitting of 8 identified cell clusters (with dictionaries estimated using NMF). Single-cell lipids display heterogeneous distributions within the hippocampus, with unique lipid markers (Fig. 5a, Supplementary Fig. 9). The fitted contributions of single-cell dictionaries suggest different spatial organizations of hippocampal cell subpopulations (Fig. 5b, c). Large model weights were found in the dentate gyrus and CA3 for cluster 0, the granular layer of CA1 for cluster 1, and the molecular layer for cluster 5, respectively, approximating the morphological structure of the hippocampus (Fig. 5b). We further analyzed the extracted dictionary items, which showed strong correlation with the lipid fold change (Fig. 5d), serving as indicators of the cluster-specific lipid signatures. Features were then selected based on magnitude of the averaged basis values, which are a good proxy to lipid specificity to cell clusters. For example, LPE O-(16:0) and PG(48:8) (indicated in dictionary items for cluster 1, Fig. 5e), the corresponding tissue distributions for these two lipids showed agreement with the fitted model weights from cluster 1 (Fig. 5b, f).

Discussion

We demonstrated integrative 3D tissue and single-cell biochemical mapping of the brain at a large scale using MESTER. This is enabled by a synergy of unique experimental capabilities and innovations in computational aspects including deep-learning-based reconstruction, image registration, and spatially-resolved cell-specific dictionary learning and fitting. While the power of deep learning has been illustrated in various imaging modalities including MSI[36–38], our method exploits unique signal characteristics in FTMS data and a special network design. Instead of

training a deep neural network to generate high-resolution mass spectra from a low-resolution

counterpart, or interpolating missing pixel values directly[39], we jointly learn low-dimensional

embeddings of the high-dimensional data and train a regression network to predict these

embeddings from reduced transients, providing a strong generalization ability for both tissue and

SCMS data. We validated that training can be done using different sections or animals, and works

well for new datasets. Through the unique capability of MEISTER, we resolved thousands of brain

lipid features over millions of pixels across a 3D volume and large cell population, while

significantly reducing the data collection time. Our method should be readily adaptable to different

types of molecules besides lipids (e.g., small metabolites and proteins) and other organ systems.

MEISTER relies on several alignment steps for knowledge extraction from integrating

high-dimensional MSI and SCMS data. First, while alignment between MSI and other imaging

modalities has been performed[40–45], we chose to register MSI data to brain MRI which was

acquired from the intact brain (without deformation) and offered a coherent 3D volumetric "atlas"

for registration. We realize that the majority of prior approaches emphasized on extracting feature

images from individual 2D sections, which can lead to incoherent image registration across

different serial sections in large 3D MSI data sets. Our pixel-wise parametric-UMAP strategy

generated feature images with a similar contrast to MRI images (Extended Data Fig. 4) and

provided structurally informative features across the entire 3D data set for easier registration. The

3D registration capability can also enable richer analysis leveraging both in vivo MRI and ex vivo

MSI. Second, we align SCMS and MSI data through cross-annotation to facilitate integrative

analysis. Recent progress has made FDR-controlled metabolite annotation for MSI possible[46,47].

However, it is difficult to leverage such methods to annotate image-guided SCMS data due to lack

of spatial information, which is a crucial statistical consideration in the annotation algorithm.

Rather, we leverage the biochemical information that mutually exists in tissue and single cells,

which are searched against the "tissue feature database". This approach boosts the confidence

in selecting biologically viable features, as retaining mutual features can minimize the inclusion of

the experiment- or sample-specific artifacts. Another advantage for cross-annotation is to

consider only molecules that are present in the intracellular spaces for more accurate single-cell

to tissue mapping. Meanwhile, we think it is possible to extend our approach to look at changes

in extracellular spaces (e.g., in different diseases) by interrogating the fitting residual as well as

lipid species filtered out via cross-annotation. For the UoSS fitting, modelling errors may occur

due to falsely cross-annotated features from the tissue data caused by mass shifts and an

inappropriate ppm window, or due to nonlinearities between MSI and SCMS data. Nonlinear

models can potentially alleviate such modeling errors by capturing more complex data

representations for improved integration.

Computational methods for integrating single-cell sequencing and spatial transcriptomics

(ST) data have been explored[48], including deconvolution of cell type fractions[49–51], joint clustering

for mapping single-cell transcriptomics to ST data[52], and estimating the number of cells per ST

spot[53]. Our work is the first attempt for similar cross-scale integration for large metabolomics and

lipidomics data. Our UoSS regression model is also distinct in that it does not assume only a

"reference signature" but a more general mathematical representations of the ensemble chemical

profiles for each cell type, capturing the intrinsic variations within each cell cluster. We used all

the cross-annotated lipid species making the approach "unbiased". In addition to identifying brain

region-specific lipid variability, clustering of single cells suggests that a continuity of lipid-defined

cell type diversity exists across brain regions (Fig. 4a). Similar observations have been made by

transcriptomics of single cells from various brain regions, supporting that many cell types are

shared between brain regions[54,55]. We have demonstrated a proof-of-concept on linking single-

cell and spatial organizations of lipids, paving the way to build biochemical cartography of tissue

and primary cells.

Previous studies have used liquid chromatography tandem-MS (LC-MS^2) measurements

to study differential lipid contents within different brain regions and cell types[8,30]. Comparing the

LC-MS^2-based shotgun lipidomics and our MS imaging-based lipid profiling, we have found

agreements in region-specific distributions of major lipid classes, including HexCer, Cer, and SM

that are more enriched in regions such as the corpus callosum with higher myelin content[30] (Fig.

3d, e). Our multiscale imaging-based approach offers not only the capability of resolving hundreds

of lipid molecules, but also a new tool for understanding spatial-biochemical tissue architecture

with cellular specificity, transforming how we study brain chemistry just as how spatial

transcriptomics transforms determination of gene expression. We envision future endeavors on

creating multiscale biochemical atlases, with increasingly powerful profiling technology for

metabolites, lipids, peptides and proteins, as well as integrative analysis with other omics data.

Reference

1. Hawrylycz, M. J. *et al.* An anatomically comprehensive atlas of the adult human brain transcriptome. *Nature* **489**, 391–399 (2012).

2. Darmanis, S. *et al.* A survey of human brain transcriptome diversity at the single cell level. *Proceedings of the National Academy of Sciences* **112**, 7285–7290 (2015).

3. Rao, A., Barkley, D., França, G. S. & Yanai, I. Exploring tissue architecture using spatial transcriptomics. *Nature* **596**, 211–220 (2021).

4. Tsui-Pierchala, B. A., Encinas, M., Milbrandt, J. & Johnson, E. M. Lipid rafts in neuronal signaling and function. *Trends in Neurosciences* **25**, 412–417 (2002).

5. Allaman, I., Bélanger, M. & Magistretti, P. J. Astrocyte–neuron metabolic relationships: for better and for worse. *Trends in Neurosciences* **34**, 76–87 (2011).

6. Iwata, R. *et al.* Mitochondria metabolism sets the species-specific tempo of neuronal development. *Science* **379**, eabn4705 (2023).

7. Lynch, G. & Baudry, M. The Biochemistry of Memory: A New and Specific Hypothesis. *Science* **224**, 1057–1063 (1984).

8. Ding, J. *et al.* A metabolome atlas of the aging mouse brain. *Nat Commun* **12**, 6021 (2021).

9. Mutlu, A. S., Duffy, J. & Wang, M. C. Lipid metabolism and lipid signals in aging and longevity. *Developmental Cell* **56**, 1394–1407 (2021).

10. Hou, Y. *et al.* Ageing as a risk factor for neurodegenerative disease. *Nat Rev Neurol* **15**, 565–581 (2019).

11. Eisenstein, M. Seven technologies to watch in 2023. *Nature* **613**, 794–797 (2023).

12. Piehowski, P. D. *et al.* Automated mass spectrometry imaging of over 2000 proteins from tissue sections at 100-μm spatial resolution. *Nature Communications* **11**, 8 (2020).

13. Guo, G. *et al.* Automated annotation and visualisation of high-resolution spatial proteomic mass spectrometry imaging data using HIT-MAP. *Nature Communications* **12**, 3241 (2021).

14. Mund, A. *et al.* Deep Visual Proteomics defines single-cell identity and heterogeneity. *Nat Biotechnol* **40**, 1231–1240 (2022).

15. Brunner, A.-D. *et al.* Ultra-high sensitivity mass spectrometry quantifies single-cell proteome changes upon perturbation. *Molecular Systems Biology* **18**, e10798 (2022).

16. Budnik, B., Levy, E., Harmange, G. & Slavov, N. SCoPE-MS: mass spectrometry of single mammalian cells quantifies proteome heterogeneity during cell differentiation. *Genome Biology* **19**, 161 (2018).

17. Specht, H. *et al.* Single-cell proteomic and transcriptomic analysis of macrophage heterogeneity using SCoPE2. *Genome Biology* **22**, 50 (2021).

18. Passarelli, M. K. *et al.* The 3D OrbiSIMS—label-free metabolic imaging with subcellular lateral resolution and high mass-resolving power. *Nature Methods* **14**, 1175–1183 (2017).

19. Kompauer, M., Heiles, S. & Spengler, B. Atmospheric pressure MALDI mass spectrometry imaging of tissues and cells at 1.4-μm lateral resolution. *Nature Methods* **14**, 90–96 (2017).

20. Rappez, L. *et al.* SpaceM reveals metabolic states of single cells. *Nat Methods* 1–7 (2021) doi:10.1038/s41592-021-01198-0.

21. Capolupo, L. *et al.* Sphingolipids control dermal fibroblast heterogeneity. *Science* (2022) doi:10.1126/science.abh1623.

22. Rubakhin, S. S., Romanova, E. V., Nemes, P. & Sweedler, J. V. Profiling metabolites and peptides in single cells. *Nat Methods* **8**, S20–S29 (2011).

23. Comi, T. J., Neumann, E. K., Do, T. D. & Sweedler, J. V. microMS: A Python Platform for Image-Guided Mass Spectrometry Profiling. *J. Am. Soc. Mass Spectrom.* **28**, 1919–1928 (2017).

24. Xie, Y. R., Castro, D. C., Lam, F. & Sweedler, J. V. Accelerating Fourier Transform-Ion Cyclotron Resonance Mass Spectrometry Imaging Using a Subspace Approach. *J. Am. Soc. Mass Spectrom.* **31**, 2338–2347 (2020).

25. Xie, Y. R., Castro, D. C., Rubakhin, S. S., Sweedler, J. V. & Lam, F. Enhancing the Throughput of FT Mass Spectrometry Imaging Using Joint Compressed Sensing and Subspace Modeling. *Anal. Chem.* **94**, 5335–5343 (2022).

26. Papp, E. A., Leergaard, T. B., Calabrese, E., Johnson, G. A. & Bjaalie, J. G. Waxholm Space atlas of the Sprague Dawley rat brain. *NeuroImage* **97**, 374–386 (2014).

27. Sainburg, T., McInnes, L. & Gentner, T. Q. Parametric UMAP Embeddings for Representation and Semisupervised Learning. *Neural Computation* **33**, 2881–2907 (2021).

28. Bazinet, R. P. & Layé, S. Polyunsaturated fatty acids and their metabolites in brain function and disease. *Nat Rev Neurosci* **15**, 771–785 (2014).

29. Piomelli, D. & Sasso, O. Peripheral gating of pain signals by endogenous lipid mediators. *Nat Neurosci* **17**, 164–174 (2014).

30. Fitzner, D. *et al.* Cell-Type- and Brain-Region-Resolved Mouse Brain Lipidome. *Cell Reports* **32**, 108132 (2020).

31. Li, T. *et al.* Ion mobility-based sterolomics reveals spatially and temporally distinctive sterol lipids in the mouse brain. *Nat Commun* **12**, 4343 (2021).

32. Fahy, E., Sud, M., Cotter, D. & Subramaniam, S. LIPID MAPS online tools for lipid research. *Nucleic Acids Res* **35**, W606–W612 (2007).

33. Tan, S. T., Ramesh, T., Toh, X. R. & Nguyen, L. N. Emerging roles of lysophospholipids in health and disease. *Progress in Lipid Research* **80**, 101068 (2020).

34. Devarajan, K. Nonnegative Matrix Factorization: An Analytical and Interpretive Tool in Computational Biology. *PLoS Comput Biol* **4**, e1000029 (2008).

35. Townes, F. W. & Engelhardt, B. E. Nonnegative spatial factorization applied to spatial genomics. *Nat Methods* **20**, 229–238 (2023).

36. Li, X. *et al.* Reinforcing neuron extraction and spike inference in calcium imaging using deep self-supervised denoising. *Nat Methods* 1–6 (2021) doi:10.1038/s41592-021-01225-0.

37. Lecoq, J. *et al.* Removing independent noise in systems neuroscience data using DeepInterpolation. *Nat Methods* 1–8 (2021) doi:10.1038/s41592-021-01285-2.

38. Abdelmoula, W. M. *et al.* Peak learning of mass spectrometry imaging data using artificial neural networks. *Nat Commun* **12**, 5544 (2021).

39. Hu, H. *et al.* High-Throughput Mass Spectrometry Imaging with Dynamic Sparse Sampling. *ACS Meas. Sci. Au* **2**, 466–474 (2022).

40. Sinha, T. K. *et al.* Integrating spatially resolved three-dimensional MALDI IMS with in vivo magnetic resonance imaging. *Nature Methods* **5**, 57–59 (2008).

41. Van de Plas, R., Yang, J., Spraggins, J. & Caprioli, R. M. Image fusion of mass spectrometry

and microscopy: a multimodality paradigm for molecular tissue mapping. *Nature Methods*

12, 366–372 (2015).

42. Vollnhals, F. *et al.* Correlative Microscopy Combining Secondary Ion Mass Spectrometry and

Electron Microscopy: Comparison of Intensity–Hue–Saturation and Laplacian Pyramid

Methods for Image Fusion. *Anal. Chem.* **89**, 10702–10710 (2017).

43. Patterson, N. H., Tuck, M., Van de Plas, R. & Caprioli, R. M. Advanced Registration and

Analysis of MALDI Imaging Mass Spectrometry Measurements through Autofluorescence

Microscopy. *Anal. Chem.* **90**, 12395–12403 (2018).

44. Neumann, E. K. *et al.* Multimodal Chemical Analysis of the Brain by High Mass Resolution

Mass Spectrometry and Infrared Spectroscopic Imaging. *Anal. Chem.* **90**, 11572–11580

(2018).

45. Porta Siegel, T. *et al.* Mass Spectrometry Imaging and Integration with Other Imaging

Modalities for Greater Molecular Understanding of Biological Tissues. *Mol Imaging Biol* **20**,

888–901 (2018).

46. Palmer, A. *et al.* FDR-controlled metabolite annotation for high-resolution imaging mass

spectrometry. *Nature Methods* **14**, 57–60 (2017).

47. Alexandrov, T. *et al.* METASPACE: A community-populated knowledge base of spatial

metabolomes in health and disease. *bioRxiv* 539478 (2019) doi:10.1101/539478.

48. Longo, S. K., Guo, M. G., Ji, A. L. & Khavari, P. A. Integrating single-cell and spatial

transcriptomics to elucidate intercellular tissue dynamics. *Nat Rev Genet* **22**, 627–644

(2021).

49. Li, B. *et al.* Benchmarking spatial and single-cell transcriptomics integration methods for transcript distribution prediction and cell type deconvolution. *Nat Methods* **19**, 662–670 (2022).

50. Nitzan, M., Karaiskos, N., Friedman, N. & Rajewsky, N. Gene expression cartography. *Nature* **576**, 132–137 (2019).

51. Biancalani, T. *et al.* Deep learning and alignment of spatially resolved single-cell transcriptomes with Tangram. *Nat Methods* **18**, 1352–1362 (2021).

52. Korsunsky, I. *et al.* Fast, sensitive and accurate integration of single-cell data with Harmony. *Nat Methods* **16**, 1289–1296 (2019).

53. Vahid, M. R. *et al.* High-resolution alignment of single-cell and spatial transcriptomes with CytoSPACE. *Nat Biotechnol* 1–6 (2023) doi:10.1038/s41587-023-01697-9.

54. Yao, Z. *et al.* A taxonomy of transcriptomic cell types across the isocortex and hippocampal formation. *Cell* **184**, 3222-3241.e26 (2021).

55. Yao, Z. *et al.* A high-resolution transcriptomic and spatial atlas of cell types in the whole mouse brain. 2023.03.06.531121 Preprint at https://doi.org/10.1101/2023.03.06.531121 (2023).

56. Marshall, A. G., Comisarow, M. B. & Parisod, G. Relaxation and spectral line shape in Fourier transform ion resonance spectroscopy. *J. Chem. Phys.* **71**, 4434–4444 (1979).

57. Marshall, A. G., Hendrickson, C. L. & Jackson, G. S. Fourier transform ion cyclotron resonance mass spectrometry: A primer. *Mass Spectrometry Reviews* **17**, 1–35 (1998).

1   58. Dittwald, P., Claesen, J., Burzykowski, T., Valkenborg, D. & Gambin, A. BRAIN: A Universal

2   Tool for High-Throughput Calculations of the Isotopic Distribution for Mass Spectrometry.

3   *Anal. Chem.* **85**, 1991–1994 (2013).

4   59. Sunkin, S. M. *et al.* Allen Brain Atlas: an integrated spatio-temporal portal for exploring the

5   central nervous system. *Nucleic Acids Research* **41**, D996–D1008 (2013).

Online Methods

Experimental Details.

Animals. The male Sprague-Dawley® outbred rats (*Rattus norvegicus*) used in this study were sourced from Inotivco (www.inotivco.com). These rats were provided with ad libitum access to food and housed on a 12-h light cycle. All animal euthanasia procedures were carried out in strict accordance with the guidelines set forth by the Illinois Institutional Animal Care and Use Committee as well as the federal and ARRIVE guidelines to ensure the humane care and treatment of animals.

Tissue Dissociation and Preparation of Single Cells. A total of 3, 2.0–2.5-month-old male rats were used for tissue isolation. Each isolated tissue region was individually treated with a papain dissociation system (Worthington Biochemical, Lakewood, NJ) and incubated for 120 min at 34 °C with oxygenation. The treated tissue regions were then mechanically dissociated in ice cold modified Gey's balanced salt solution (mGBSS) containing (in mM): 1.5 $CaCl_2$, 5 KCl, 0.2 KH_2PO_4, 11 $MgCl_2$, 0.3 $MgSO_4$, 138 NaCl, 28 $NaHCO_3$, 0.8 Na_2HPO4, and 25 HEPES, pH 7.2, and supplemented with 0.08% paraformaldehyde to stabilize cells against damage during dissociation and other methodological steps. A solution of 80% glycerol and 20% mGBSS was added to a final glycerol concentration of 40% (v/v). The cells were stained with Hoechst 33342 (0.1 µg/mL in mGBSS) and a 30 µL aliquot of cell suspension was plated onto an indium tin oxide (ITO)-unpolished float glass slide, Rs = 70-100 Ω (Delta Technologies, Loveland, CO). After ~16 h, glycerol was aspirated off the dissociated cells before rinsing with 150 mM ammonium acetate. Each slide held 3 biological replicates of each brain region and were placed in discrete but random locations on the ITO-glass slide to mitigate batch and spatial-dependent artifacts.

Tissue Sectioning. Coronal and sagittal brain slices were obtained from the rats in this study. The entire rat brain was quickly removed and flash-frozen after decapitation, before being sectioned. Sagittal brain slices were prepared at a temperature of –20 °C and sliced into 16-µm-thick tissue sections. The tissue slices were then thaw-mounted onto indium-tin oxide glass slides for MALDI matrix application.

Matrix Application. The MALDI matrix 2,5-dihydroxybenzoic acid (DHB) was prepared to a concentration of 30 mg/mL in 70% methanol. Matrix was applied using an HTX-M5 Sprayer (HTX Technologies, Chapel Hill, NC), with a spray spacing of 2.5 mm at a temperature of 75 °C

using a flow rate of 100 μL/min. The distance of the sprayer nozzle was 50 mm from the sample

and a spray pressure of 10 psi with a spray nozzle motion velocity of 1200 mm/min was used.

Four passes were used to apply MALDI matrix.

Image Guided SCMS Analysis. The Brightfield and fluorescent microscopy images were

obtained using an Axio Imager M2 (Zeiss, Jena, Germany) equipped with an AxioCam ICc 5

camera and a .63× camera adaptor. For transmitted light, a VIS-LED lamp was used, while for

fluorescence, an X-cite Series 120 Q mercury lamp (Lumen Dynamics, Mississauga, Canada)

was employed. The imaging was done using DAPI (ex. 335–383 nm; em. 420–470 nm), GFP

(ex. 450–490 nm; em. 500–550), and HE DsRed (ex. 538–562; em. 570–640) dichroic filter

cubes. The images were acquired in mosaic mode with a 10× objective and 10% tile overlap.

The resulting tiles were stitched together before being exported in TIFF-file format using ZEN

2.0 Pro edition (Zeiss, Jena, Germany) software. The single-cell coordinates, geometry files,

and an Excel file required for the target automation function on ftmsControl (v. 2.1.0, Bruker

Corp., Billerica, MA) were obtained using microMS, as described previously[23]. To ensure data

quality, cells were filtered from lists of analyzed structures based on their distance from each

other, with cells closer than 200 μm being removed, and based on their size, with any free

nuclei resulting from cell lysis being removed. High-throughput single-cell analysis was

performed using a SolariX 7T FT-ICR mass spectrometer (Bruker Corp.), with a mass window of

50–1000 m/z. MALDI mass spectra were acquired in positive mode using a Smartbeam-II UV

laser in "ultra" mode, which produces a 100 μm diameter laser-spot size. Each MALDI

acquisition was comprised of one ICR accumulation, consisting of 150 laser shots at a

frequency of 1000 Hz.

Signal modeling. A transient can be modeled as a temporal signal that contains many

frequencies corresponding to different ions, following the generic signal model proposed by

Marshall[56,57]:

28
$$s(t) = \sum_i A_i \cdot exp\left(-\frac{t}{\tau_i}\right) cos(\omega_i t) + \varepsilon(t).$$

29   For ion i, constant A_i represents the initial signal amplitude, τ_i is the decay rate of the excited

30   ICR signal due to ion collisions, ω_i is the ion cyclotron frequency, and ε is the independent

31   noise. The theoretical mass resolution is calculated as**:**

32
$$\frac{m}{\Delta m} = \frac{1.274 \times 10^7 z B_0 T_{aqn}}{m}$$

where B_0 is the magnetic field strength, and T_{aqn} is the transient acquisition time. Given a fixed

B_0, the theoretical mass resolution is thus proportional to T_{aqn}: a certain T_{aqn} is required for a

target high mass resolution. We used the described signal model for the MSI data simulation.

Simulation of MSI data. We followed a previously described procedure to simulate the MSI

data[25]. Briefly, transients were generated through the generic signal model discussed above

with a list of 30 chemical formulas. Frequencies were reverse calculated for all possible ions

including H+, Na+, and K+ adducts were assigned to each formula, and theoretical isotopic

distributions were calculated using the Python version of the BRAIN algorithm[58]. Allen Brain

Atlas (ABA) mouse brain annotation was used as the spatial reference[59] to generate 8 pseudo-

tissue regions with different combinations of chemical formulas. All transients were simulated for

262,144 temporal data points in total of 26,497 pixels. Independent Gaussian noise was added

to each simulated transient.

Model design for MEISTER.

Reconstruction model. The signal reconstruction model consists of three parts: 1) an encoder

network encoding input high-resolution transient signals into lower-dimensional latent features,

2) a regression network transforming corresponding low-resolution signals to their latent

features, and 3) a decoder network decoding the estimated low-dimensional latents back to

high-resolution signals. We use a deep autoencoder architecture to learn low-dimensional

features directly from raw high-resolution transient signals for both tissue and single-cell

measurements. Each transient signal $s(r_n, t)$ is sampled with a specific temporal sampling rate,

with $t = \{t_1, t_2, \dots t_{N_T}\}$ where N_T is the number of discrete time points and the duration T for a

defined mass resolution, and $n = 1, 2, \cdots, N_r$, where N_r corresponds to number of pixels in MSI

or number of cells in SCMS data. Denoting $\boldsymbol{S} = \{s(r_n, t_i)\}_{n,i=1}^{N,N_T}$ as the ensemble of training data,

our objective is to train the network to encode $\boldsymbol{S}$ into a set of low-dimensional features and

produce reconstruction $\widehat{\boldsymbol{S}} = \{\hat{s}(r_n, t_i)\}_{n,i=1}^{N,N_T}$ that are as close to $\boldsymbol{S}$ as possible. Specifically, our

network can be described mathematically as:

$$\boldsymbol{Z} = \boldsymbol{E}(\boldsymbol{S}; \boldsymbol{W}_E, \boldsymbol{B}_E)$$

$$\widehat{\boldsymbol{S}} = \boldsymbol{D}(\boldsymbol{Z}; \boldsymbol{W}_D, \boldsymbol{B}_D)$$

where $\boldsymbol{Z}$ represents a 32-dimensional latent vector encoding $\boldsymbol{S}$, $\boldsymbol{E}(\cdot)$ **and** $\boldsymbol{D}(\cdot)$ denote the

encoder and decoder functions, respectively, each containing three fully-connected layers with

512, 256, and 64 neurons respectively (symmetric design). Denoting the whole network as $\phi(\cdot$

; Θ) (combining encoder and decoder) with $\Theta = [\boldsymbol{W_E}, \boldsymbol{B_E}, \boldsymbol{W_D}, \boldsymbol{B_D}]$ containing all the network

parameters, the MSE loss was minimized during training:

3
$$\Theta = arg\min_{\Theta} ||\boldsymbol{S} - \phi(\boldsymbol{S}; \Theta)||^2_2 + \lambda ||\Theta||_2^{\;2}$$

4 We then trained a regressor network $\boldsymbol{R}(\cdot)$ to map the low-resolution measurements

5 $\boldsymbol{S'} = \{s'(r_n, t_j)\}_{n,j=1}^{N_r, N_{T'}}$, with N_r transients ($N_r \gg N$) and first $N_{T'}$ temporal points corresponding to

6 a shorter acquisition duration T' ($T' \ll T$), to the latent features $\boldsymbol{Z'}$:

7
$$\boldsymbol{Z'} = \boldsymbol{R}(\boldsymbol{S'}; \boldsymbol{W_R}, \boldsymbol{B_R})$$

8 which can be decoded into full-resolution transients. Denoting all the regressor network

9 parameters as $\Theta_{\mathbf{R}} = [\boldsymbol{W_R}, \boldsymbol{B_R}]$, the model was trained by minimizing the mean-squared-error

10 between $\boldsymbol{Z}$ (encoded from $\boldsymbol{S}$) and the regressor output $\boldsymbol{Z'}$:

11
$$\Theta_{\mathbf{R}} = arg\min_{\Theta_{\mathbf{R}}} ||\boldsymbol{Z} - \boldsymbol{R}(\boldsymbol{S'}; \Theta_{\mathbf{R}})||^2_2 + ||\Theta_{\mathbf{R}}||_2^{\;2}$$

12 Low-resolution measurements $\boldsymbol{S'}$ can then be transformed into high-resolution data by:

13
$$\widehat{\boldsymbol{S}} = \boldsymbol{D}(\boldsymbol{R}(\boldsymbol{S'}; \Theta_{\mathbf{R}}); \boldsymbol{W_D}, \boldsymbol{B_D})$$

Evaluation on simulated and experimental MSI data. First, we validated MEISTER's signal

reconstruction performance on simulated MSI data. We trained MEISTER on 2,000 randomly

sampled pixels containing noisy transients (simulation data described above), and performed

reconstruction on all pixels containing reduced noisy transients (taking the first 10,000 temporal

points). We compared the reconstructed data against the ground truth high-resolution data

without Gaussian noise. All sets of transients (clean, noisy, noisy reduced, and reconstructed)

were transformed into mass spectra and converted to peak intensity lists, which consist of peak

centroids identified from the ground truth spectra. Peak and spatial correlation scores against

the ground truth were computed as the Pearson correlation coefficients between each peak list

and ion image pairs. Encoded features of the latent space were extracted from the bottleneck

layer and subjected to UMAP for visualization.

For the experimental data, we trained the networks using a set of high-resolution data

(1M temporal points) acquired on rat sagittal and coronal brain sections and the corresponding

low-resolution data (64K temporal points). Reconstruction was performed on the 160 µm, 1 mm

and 2 mm sections away from the training sections to validate the model's generalizability

across tissue volume. High-resolution data were acquired from these tissue sections (serving as

the reference) and reduced to 64K temporal points as the input to MEISTER reconstruction

model. Reduced (zero-padded), reconstructed and reference transients were then transformed

into mass spectra and converted to peak intensity lists. For each tissue section, the peak

centroids were determined on the average mass spectra obtained from the high-resolution

reference data. Peak and spatial correlation scores were calculated the same way as for the

simulation, but against the high-resolution reference. SNRs were defined as the ratios between

the signal intensity and the standard deviation of the noise, which was obtained over a spectral

region without apparent signals. K-means clustering was performed for different reconstructions

with k=6. The components and scores for first 5 PCs were compared between reconstructed

and reference data.

MEISTER for 3D MSI. For 3D MSI of rat coronal sections, training data (transients collected for

1M temporal points) were collected on 3 tissue sections with a total number of 124,370 pixels.

For rat sagittal sections, data from 2 tissue sections in total of 105,954 pixels were used for the

model training. Training sections were roughly 2 mm apart to ensure the coverage of all

possible brain regions. The autoencoders were trained for 20 epochs and the regressors were

trained for 50 epochs. A batch size of 128 and Adam optimizer were applied to train both

networks. We then acquired low-resolution data with 64K temporal points for all remaining

tissue sections (37 coronal and 39 sagittal). During reconstruction, these low-resolution signals

were served as input for the regressor network, which predicted 32-dimensional latent vectors

for each signal. The predicted latent vectors were decoded to transient signals with 1M temporal

points by the previously trained decoder. Finally, high-resolution mass spectra were generated

from the decoded transients.

MEISTER for image-guided SCMS. We trained MEISTER using 3,840 random cells (data with

1M temporal points) from five brain regions using microMS. The autoencoder and regressor

were trained for 20 and 50 epochs respectively, with a 64 batch size. Model was validated on a

validation set containing 1,000 cells. The spectral correlation scores were calculated between

the reference peak intensity and the reconstructed peak intensity. To show MEISTER

reconstruction provides consistent downstream analysis, we compared UMAP and Leiden

clustering results between the reference (validation set) and reconstructed single-cell data, and

visualized the single-cell distributions of *m/z* features over UMAP (Extended Data Fig. 3). A total

number of 13,566 cells (64K temporal points) was reconstructed (1M temporal points) to obtain

high-resolution single-cell mass spectra.

Analysis of 3D MSI data.

Data preparation. To prepare for data analysis, we first determined the peak centroids on the

average mass spectra for each tissue section, and extracted the intensities of the peak

centroids for all pixels. The peak lists were then processed by *m/z* binning in 3 ppm increments

to align peaks affected by potential mass shift. After extracting peak lists from a 3D data set, we

retained *m/z* bins common across all tissue sections for further analysis. Each pixel was

normalized by total ion count (TIC). The processed data were finally converted into imzML file

format.

Data-driven image registration. To enable 3D reconstruction and analysis of MSI data with

respect to brain anatomy, we registered MSI serial sections to T_2*-weighted anatomical MRI

from Waxholm Space atlas of the Sprague Dawley rat brain. To ensure precise and accurate

registration across serial sections, we adapted parametric-UMAP to extract both structurally

informative and consistent feature images from high-dimensional MSI data. Previous work has

demonstrated using low-dimensional feature images (embeddings) obtained via nonparametric

dimensionality reduction methods (both t-SNE and UMAP) for image registration tasks.

However, feature images from different tissue sections can provide disparate morphological

contrasts, since data are essentially embedded into different embedding space per tissue

section. Embedding the entire 3D MSI data set can overcome such issue, but it is

computationally intractable for t-SNE and UMAP optimization over millions of input pixels with

thousands of dimensions. The major advantage of parametric version of UMAP is to use a

neural network to learn a relationship between data and embedding. Thus, a small subset of

pixels can be sampled from 3D MSI data for training the network, which can rapidly embed a

large number of pixels into a single embedding space. We used an autoencoder in conjunction

with UMAP, of which the encoder is trained to minimize UMAP loss and the decoder is trained

to minimize reconstruction loss. The autoencoder input and output size is set to be the number

of *m/z* features, followed by 256, 128, 64 size of fully connected layers. The UMAP loss function

between two data points i and j is the cross-entropy defined as:

29
$$C_{UMAP} = \sum_{i \neq j} v_{ij} \log\left(\frac{v_{ij}}{w_{ij}}\right) + (1 - v_{ij})\log\left(\frac{1 - v_{ij}}{1 - w_{ij}}\right)$$

Ten percent of total pixels were randomly sampled as training data, and the network was trained

for 20 epochs. For each tissue section, embedding vectors from three UMAP dimensions were

encoded into RGB channels to form feature images, which were then converted to gray-scale

ready for registration.

The anatomical images from MRI atlas were selected based on the tissue sectioning

distance with manual inspection. We applied a two-step multimodal image registration to align

gray-scale MSI feature images as the moving images with the reference anatomical images.

First, rigid affine registration was performed to roughly align the two with 9 hand-selected initial

transformation points. After rough alignment, a nonrigid cubic B-spline registration was

performed with Mutual Information as the similarity measure with 200 maximum optimization

steps. The registration quality was evaluated via Dice Index (DI), which assesses the image

mask overlap between the i-th brain region labels from the atlas and the human-annotated

masks from the j-th registered tissue section:

$$DI_{ij} = \frac{2|Label_{ij} \cap Annotation_{ij}|}{|Label_{ij}| + |Annotation_{ij}|}$$

The transformation matrices were applied to each MSI section to visualize registered ion

images. The regional-specific mass spectral profiles were extracted from pixels based on the

atlas brain region labels.

Brain regional-specific analysis. To analyze regional lipid distributions at the single-pixel

level, we extracted all MSI pixels belonging to 11 brain regions based on the atlas labels. For

individual tissue section, the extracted pixels were first subjected to UMAP for visualization, and

used to train Gradient boosting tree (GBT) models to predict the brain regions, a multiclass

classification task. Training and testing set sizes were set to 0.8 and 0.2. GBT modesl were

further interpreted through SHAP (SHapley Additive exPlanations) values. In SHAP, each pixel

provides the lipid feature attributions toward predicting certain brain regions, which can be used

to generate feature attribution maps for ion images. The most contributing lipid features were

selected by ranking mean absolute SHAP values. Regional average lipid profiles were obtained

from every tissue sections, which were repeated for the aforementioned analysis. Differential

analysis of lipid features was performed for each brain region to obtain the log2 fold-change and

p-values tested by Wilcoxon rank-sum and adjusted by Benjamini-Hochberg. For putative lipid

annotation, we searched the *m/z* values against LIPID MAPS[32] with a 3ppm threshold for

chemical formula and lipid species assignments.

Joint analysis of MSI and SCMS data.

Cross annotation strategy. We applied a straightforward strategy to annotate lipids in SCMS

data using features observed in MSI data. Similar to putative annotation, features in MSI were

served as a database to search the SCMS peak lists for matching lipids within a 3ppm *m/z*

window. Features present in less than 5% of cells were discarded, and cells with less than 5%

total number of features were filtered out. Using an alternative method, we first annotated the

tissue MSI data using METASPACE with CoreMetabolome database and obtained the

monoisotopic *m/z* features from the annotation results with a 50% FDR. These monoisotopic

ions were then used to search the SCMS data.

Integrative analysis using union-of-subspace fitting. The mxn single-cell lipid feature matrix

X were first processed by TIC normalization, with m being the number of cells in each identified

cluster and n being the number lipid features. Leiden clustering was performed with on the first

40 PCs with the parameters n_neighbors=30, min_dist=0.5, and resolution=0.25, and cosine as

the distance metric. The single-cell matrix $X^{(l)}$ of cell cluster l can be decomposed into :

$$X^{(l)} = W^{(l)}D^{(l)}$$

where $W^{(l)}$ represents the mxk weight matrix (k being the number of dictionary item capturing

the chemical variations within each cluster), and $D^{(l)}$ is the kxn nonnegative dictionary matrix

that contains sparse representations of lipid signatures in l-th single-cell cluster. We choose

k=20 for the NMF algorithm. The union of dictionary items concatenated across L number of

clusters $U = \left[D^{(0)}; D^{(1)}; \dots D^{(L)}\right]$ is fitted to the pxn tissue imaging data matrix Y, where p being

the number of tissue pixels, by a constrained linear least-squares fitting, with model weights

constrained to be nonnegative:

$$Y = CU$$

$$C = arg \min_{C}\|Y - CU\|_2{}^2 \; , C \geq 0$$

The pxk*L tissue weight matrix C has the row vectors $C_{p_i,} = [c_{p_i,0}, c_{p_i,1} \dots c_{p_i,L}]$ and $c_{p_i,l}$ contains

the weights for pixel p_i and k dictionary items from the l-th single-cell cluster. The vector norm

$\left|c_{p_i l}\right|_2$ was taken corresponding to the summarized contributions from all dictionary items of the

l-th cluster. The vector norms were mapped back to original pixel locations to visualize the

spatial contributions of single-cell lipid signatures at the tissue level.

Data availability

The processed 3D MSI, single-cell MS and other relevant imaging data that support the findings of this study are publicly available and free to download from Figshare upon publication of the work. Due to large file sizes, raw data including simulated and experimental transients can be available upon reasonable request to the corresponding authors to arrange data sharing.

Code availability

The code used in this study are free for noncommercial use and available on GitHub (https://github.com/richardxie1119/MEISTER).

Acknowledgments

This project was supported by the National Institute on Drug Abuse under Award No. P30 DA018310, the National Institute on Aging under Award No. 1R01AG078797 and the National Human Genome Research Institute under award No. RM1HG010023. The content is solely the responsibility of the authors and does not necessarily represent the official views of the awarding agencies.

Author contributions

Y.R.X, F.L. and J.V.S. conceived the project idea. Y.R.X. and F.L. developed the deep learning and computational methods. S.S.R. and D.C.C. designed and performed the sample preparation for tissues and single cells. Y.R.X. and D.C.C. acquired mass spectrometry data. Y.R.X. implemented and evaluated the computational algorithms. Y.R.X, F.L. and J.V.S performed data analysis. Y.R.X. created the figures and all authors wrote the manuscript. F.L. and J.V.S. acquired funding and provided direction throughout the project.

Competing interests

The authors declare no competing interests.

Additional information

Supplementary information is available online.

1 Extended Data Figures

2
3 **Extended Data Fig. 1| a,** MEISTER reconstruction model that contains an autoencoder to learn latent
4 features from high-resolution signals, and a regressor network that maps low-resolution signals to encoded
5 latent features. MEISTER training workflow for **b,** 3D MSI using high-mass resolution data acquired on a
6 small number of tissue sections, and **c,** SCMS using high-mass resolution data acquired on a subset of
7 individual cells.
8

Extended Data Fig. 2| Comparisons of **a,** mass spectra from the simulated MSI data. **b,** ion images
extracted from several *m/z* features, showing enhanced spectral and image quality enabled by MEISTER
reconstruction. **c,** Correlation coefficient and error distributions by evaluating mass spectra and ion images
against the ground truth. **d,** UMAP embeddings of encoded features of the simulated HR data and the
features of reconstruction from LR data. Colors indicate different pseudo-tissue regions. **e,** K-means
clustering for the experimental reference, subspace reconstruction, and MEISTER reconstruction. **f,**
Pearson correlation coefficients between top-5 PCs extracted from the experimental reference versus from
the data reconstructed by subspace (top) and MEISTER (bottom).

2
3 **Extended Data Fig. 3| a,** Experimental high-resolution single-cell mass spectra versus MEISTER
4 reconstructed mass spectra. High peak correlation scores were obtained on 1000 validation cells (bottom
5 box plot). b, Downstream analysis of the reference and reconstructed data shows nearly identical clustering
6 patterns and ion distributions at the single-cell level. **c,** Peak correlation scores for cells sampled from five
7 different brain regions.

Extended Data Fig. 4| **a,** Number of pixels versus the slice order for the 3D rat coronal data set. **b**, Average mass spectra for 37 coronal sections obtained from MEISTER reconstruction. **c,** Comparison of the raw (reduced) and reconstructed mass spectra (left) in a small *m/z* window, and representative ion images (right). **d,** Across serial sections in z-axis, parametric UMAP embeddings (top, colored by point density) formed consistent and structurally informative feature images (middle) and k-means clusters (bottom), with **e** showing the cluster proportions for 7 clusters varying with the slice order.

2
Extended Data Fig. 5| High-resolution 3D MSI of the brain with volumetric reconstruction. a, The
proposed workflow leveraging pixel-wise parametric UMAP to efficiently align MSI data from serial tissue
sections to an inherent 3D MRI volume. **b,** Nonlinear image registration aligning the hyperspectral UMAP
image to the target MR image via sequential affine registration and B-spline registration. The combination
apparently improved the alignment and enabled coherent volumetric reconstruction of MSI sections. **c**,
Differential signal intensity distributions for 2 lipids detected in 11 unique brain anatomical regions identified
by ROI labels from a rat MRI atlas.

Extended Data Fig. 6| a, Top five single-cell lipid features identified to be brain-region specific
(left), and top two lipid features identified to be cluster-specific (right). Lipid features were selected
based on p-values and log2 of fold change obtained by differential analysis. Rows and columns
correspond to cells organized by the clusters and lipid features organized by regions or clusters
respectively. **b**, Tissue and single-cell distributions of lipid markers identified by region-specific
lipid analysis, demonstrated by data of two representative lipids, SM (31:2) and PG O-(44:7).
Bottom: regional distributions of SM and PG signal intensities quantified by log2 of fold change at
the single-cell level. **c, d,** Highly specific lipid markers (significance indicated by p-values) were
identified for different brain regions, showing agreement between single-cell and tissue imaging
data for **c,** corpus callosum and **d,** cortex regions. For **c, d,** top left: single-cell UMAP, top right:
corresponding ion images, bottom left: relations between clusters, mean signal intensity for single
cells in cluster, and size of cell fraction per cluster, bottom right: relation between mean of signal
intensities, brain locations of collected signals.

SUPPLEMENTARY INFORMATION

Integrative Multiscale Biochemical Mapping of the Brain via Deep-Learning Enhanced High-Throughput Mass Spectrometry

Yuxuan Richard Xie[1][2], Daniel C. Castro[2][3], Stanislav S. Rubakhin[2][4], Jonathan V. Sweedler[1][2][3][4]*, Fan Lam[1][2]*

[1] Department of Bioengineering
[2] Beckman Institute for Advanced Science and Technology
[3] Department of Molecular and Integrative Physiology
[4] Department of Chemistry University of Illinois at Urbana-Champaign, Urbana, IL 61801, United States.

*Corresponding Authors.

Table of Contents

Supporting Figures

Supplementary Figure 1| a, Experimental and reconstructed transients (1M temporal points for 0.73 s duration) and the transformed mass spectra. b, From top to bottom rows: reference, reduced, subspace and MEISTER reconstructed mass spectra (left column), and ion images formed from signals indicated by the colored arrows (right column). The data were from a validation data set of a sagittal section adjacent to the training section.

Supplementary Figure 2| a, From top to bottom rows: reference, reduced, subspace, and MEISTER reconstructed ion images from a validation data set acquired on a sagittal section 2mm away from the training section. **b,** Peak and spatial correlation scores compared to the reference. **c,** K-means clustering assignments for the reduced and reconstructed data by the subspace approach and MEISTER. **d,** Pearson correlation coefficients between top-5 PCs extracted from the experimental reference versus from the data reconstructed by subspace (top) and MEISTER (bottom).

Supplementary Figure 3| Reconstruction of the 3D sagittal data set showing a, Average mass spectral from 3 sagittal sections obtained from MEISTER reconstruction. **b,** Number of pixels versus the slice order for the 3D rat sagittal data set. **c,** Ion images reconstructed by MEISTER (left) and the optical images from the same tissue sections.

Supplementary Figure 4| a, Parametric UMAP embeddings of the 3D sagittal data set, data shown on 3 representative sections. **b,** Feature images formed by individual UMAP dimensions. **c,** Zoom-in views of the feature images and the k-means clustering assignments, with **d** showing the cluster proportions for 5 clusters varying with the slice order.

Supplementary Figure 5| UMAP embeddings of representative 2D tissue sections covering all 11 brain regions (colors indicated at the bottom).

Supplementary Figure 6| Machine learning models trained on 3D MSI pixels to predict brain regions. **a,** The AUC curves of a model trained on a tissue section containing 8 brain regions. **b-d,** Confusion matrices (validated on 20% pixels) of the models for three tissue sections demonstrated in Figure 4 (top left, top right, and bottom left), and **e,** the confusion matrix of the model trained on the average mass spectra (bottom right). **f,** Mean intensity profiles of the top selected lipid features for different brain structures.

Supplementary Figure 7| Machine learning models trained on individual MSI pixels to predict brain regions and using interpretable machine learning based on SHAP values for top contributing lipid features toward model predictions. For each tissue section, image representations of the UMAP on SHAP values (left) and average SHAP values of top-20 lipid features (right) are shown.

Supplementary Figure 8| a, Volcano plots obtained from differential analysis of regional-specific lipids for 13,566 single cells. **b**, Additional representative cell-specific chemical dictionaries extracted from clusters. **c**, basis values averaged on 20 dictionary items versus fold change for lipid features in cluster 4 and 8. **d**, Analysis of contributions of cell-specific biochemical signatures to brain regions, by summarizing the estimated pixel-wise model weights for each single-cell clusters. Distinct cell compositions can be observed for different regions.

Supplementary Figure 9| a, UMAP of 2,692 hippocampal cells overlaid with number of lipids per cell (left) and total intensity per cell (right). **b**, Heatmap showing the normalized scores (z scores) for the top-5 differential *m/z* features of 8 hippocampal cell clusters.